


No. 860,481.

PATENTED JULY 16, 1907.

E. O. JACKSON.
ELECTRIC CUT-OUT.
APPLICATION FILED FEB. 6, 1907.



Inventor

Everett O. Jackson,

Witnesses

Witnesses
 Geo. Schmanp.
 T. O. Allen.

 \mathfrak{A}_y

Victor J. Evans

Attorney

UNITED STATES PATENT OFFICE.

EVERETT O. JACKSON, OF STILLWELL, ILLINOIS.

ELECTRIC CUT-OUT.

No. 860,481.

Specification of Letters Patent.

Patented July 16, 1907.

Application filed February 6, 1907. Serial No. 356,092.

To all whom it may concern:

Be it known that I, EVERETT O. JACKSON, a citizen of the United States, residing at Stillwell, in the county of Hancock and State of Illinois, have invented new and useful Improvements in Electric Cut-Outs, of which the following is a specification.

The invention relates to an improvement in switches or cut-outs for telephones, telegraphs and similar circuits, whereby to provide a simple means for disconnecting the instrument from the main line in the event of an electrical storm and thereby prevent damage to the instrument.

The main object of the present invention is the provision of a simple form of switch carrying a fixed ground connection and having the service terminal arranged for manual disconnection when desired, said service terminal being normally under tension to automatically engage the ground in the event of such disconnection.

The invention will be described in the following specification, reference being had particularly to the accompanying drawing, in which:—The drawing represents a perspective view of a cut-out constructed in accordance with my invention.

In the drawings, wherein is shown the preferred embodiment of the details of structure, 1 represents an insulated base designed to be secured to a suitable fixture in any desired manner. On this base, near the upper end, is arranged a metallic loop 2, preferably of inverted U-shape with the terminals inserted in series in the base. The loop 2, which is preferably of substantial wire forms the grounding loop of the cut-out, the grounding conductor 3 of the instrument being connected to one arm of the loop, preferably by winding the terminal of said conductor about the arm, as at 4. A grounding conductor 5 is similarly connected at 6 to the opposite arm of the loop, thereby effectively grounding the instrument as is necessary for instruments arranged in grounded circuits. The service conductor 7 leading to the instrument is also connected to the base, and is terminally wound at 8 about the relatively lower end of a hook 9. The hook is arranged within the plane of the loop 2, with its hook portion 10 disposed some distance below the cross bar 11 of the loop. The service conductor from the source of current supply, as 12, is also secured to the base, and terminally coiled at 13 about a contact member 15. The contact member comprises a single length of wire mounted in a socket in the base 1 adjacent the lower end of said base, said member being, immediately adjacent its connection with the base, formed to provide

spring coils 16. From the coils the contact member projects in the form of an arm 17, with its upper terminal so arranged as to permit its engagement with the hook 10. The respective wires or conductors are preferably secured to the base through the medium of staples 18, the conductor being provided with insulating sleeves 19 to be engaged by the staples, thereby providing additional insulation at this point.

In use the cut-out is arranged as illustrated in the drawing, with the terminal of the arm 17 engaged beneath the hook 10. The service current then enters the instrument through the conductor 7, hook 9, arm 17, and conductor 12, the grounding from the instrument being through conductor 3, loop 2, and conductor 5. In the event of an electrical storm or other disturbance, the arm 17 is manually disengaged from the hook 10 and released, whereupon the spring coils 16 operate to automatically force said arm into engagement with the cross bar 11 of the loop 2. The service current is thus effectively grounded and the instrument disconnected, thereby preventing its damage by electrical energy generated by a storm, or other means.

The invention provides a simple form of cut-out designed to be quickly and conveniently operated to disrupt the service conductor and automatically ground the live portion thereof.

Having thus described the invention what is claimed as new is:—

1. A cut-out comprising a loop arranged in the grounded conductor, a spring member forming a part of the service conductor, and means for normally maintaining said spring member to form a continuation of the service conductor.

2. A cut-out comprising a loop arranged in the grounded conductor, a spring member forming a part of the service conductor, and means for normally maintaining said spring member to form a continuation of the service conductor, said member being arranged to automatically engage the grounding loop when disconnected from the service conductor.

3. A cut-out comprising an insulated base, a loop member secured thereon, grounding conductors electrically engaging the loop member, a hook secured on the base and forming one terminal of a service conductor, and a spring arm secured on the base and forming an additional terminal of the service conductor.

4. A cut-out comprising an insulated base, a loop member secured thereon, grounding conductors electrically engaging the loop member, a hook secured on the base and forming one terminal of a service conductor, and a spring arm secured on the base and forming an additional terminal of the service conductor, said spring member being designed to engage the hook to complete the service conductor or to engage the loop to ground the service conductor.

5. A cut-out comprising an insulated base, a loop se-

cured thereon, grounding conductors connected to the loop, a hook secured to the base in the plane of the loop, a service conductor connected to the hook, an arm mounted in the base and formed with a spring coil, a service conductor connected to the arm, the free terminal of the arm being arranged to engage the hook beneath the cross bar of the loop, whereby upon disconnection of the arm from the hook electrical engagement of the arm and loop will be automatically effected.

In testimony whereof, I affix my signature in presence 10
of two witnesses.

his
EVERETT O. X JACKSON.
mark

Witnesses:

THOMAS JACKSON,
TILFORD HOWARD.