
S. R. WELLS.

EAR MUFF.

APPLICATION FILED OCT. 22, 1908.



## UNITED STATES PATENT OFFICE.

SAMUEL R. WELLS, OF GREENFIELD, INDIANA.

## EAR-MUFF.

No. 869,401.

Specification of Letters Patent.

Patented Oct. 29, 1907.

Application filed October 22, 1906. Serial No. 340,014.

To all whom it may concern:

Be it known that I, Samuel R. Wells, a citizen of the United States, residing at Greenfield, in the county of Hancock and State of Indiana, have invented certain new and useful Improvements in Ear-Muffs, of which the following is a specification.

The principal object of my present invention is to provide in connection with a head covering, such as a hat or cap, a convenient ear muff which may be folded up into the crown of the hat or cap when not in use, and which can be readily unfolded and brought into use when desired. A further object is to provide a frame for such a muff which will also serve as a holder to secure the hat in place on the head.

Referring to the accompanying drawings, which are made a part hereof, and on which similar reference characters indicate similar parts, Figure 1 is a perspective view illustrating the appearance of my invention in use; Fig. 2, a central sectional view through a hat equipped with said invention, certain portions being also broken away to show construction which would otherwise be hidden; Fig. 3, a horizontal sectional view as seen when looking downwardly from the dotted lines 3 3 in Fig. 2; Fig. 4, a detail sectional view upon an enlarged scale similar to a portion of Fig. 2, and Fig. 5 an elevation of the parts shown in Fig. 4.

I have shown this invention as it appears when applied to an ordinary "Derby" hat; but, of course, it may be applied to any other form of head covering.

The device includes a band 21, preferably of thin metal, which extends entirely around the head of the wearer, the ends a and b thereof being united by a slip joint and thus rendered adjustable, as shown where the sweat band of the hat is broken away in Fig. 2. Upon 35 this metal band is mounted the frame of the ear muff which is composed of wire. The ends 22 of the wire hook around the band 21 on one side, and said wire extends up and hooks over the band at the other side at 23. The wire is spring wire and is coiled into small springs 40 at the points 23, in order to cause the device to hug closely upon the parts to which it is attached. The wire is again coiled at 25 around a pin 26, and from thence extends out and forms a loop-like frame 27 upon which the fabric 28 forming the body of the ear muff is 45 secured. The springs are so arranged that normally. the ear muffs are held into the crown of the hat, as shown by dotted lines in Fig. 2, but when they are desired for use they are brought down over the ears as shown in Fig. 1—the position also being shown in Fig. 50 2. The loop-like frames 27 are of a size and shape to

surround the ears of the wearer, while the soft, warm fabric of which the bodies of the muffs is composed covers the ears and protects them. The frames also engage with the ears and serve as an efficient means for holding the hat on the head. These frames may also be used for this purpose in warm weather, in which case the fabric 28 would be removed.

In applying this invention to a hat, the band 21 is placed between the sweat band 31 and the body 32 of the hat. The portions of the wires which extend down and terminate in the coiled springs 25 are brought down over the sweat band as shown. The device is thus securely held in place within the hat. The band 21 is slipped to fit tightly within the interior wall of the hat by means of the slip joint at its ends a and b shown in 65 Fig. 2.

Having thus fully described my said invention, what I claim as new and desire to secure by Letters Patent, is.—

1. An ear muff comprising a band other than a band on 70 the head-covering adapted to entirely surround the head of the wearer, separately-constructed wire muff frames mounted on said band, and a suitable covering fabric mounted on the frames

2. An ear must comprising a band adapted to surround the head of the wearer, wire must frame mounted on said band, and a suitable covering fabric mounted on the frame, the wire being formed into coiled springs at the point where the must frame leaves the band on which it is mounted.

mounted.

3. The combination, with a head-covering, of an earmust structure comprising a band adapted to be inserted between the sweat band and the wall of the head-covering and united by a slip joint at the ends whereby it may be adjusted to the size of said head-covering, spring wire must frames mounted on said band and having loops adapted to surround the ears of the wearer, and suitable fabric segment of said loops.

4. The combination, with a head-covering, of a band adapted to be inserted between the sweat band and the 90 wall of the head covering, wire muff-frames mounted on said band and having springs formed therein and adapted to be arranged to clasp the sweat-band of the head-covering to the metal band, and suitable ear covering fabric secured to the metal band, and suitable ear covering fabric secured to the muff frames.

5. The combination, with a head-covering, of a frame secured within said head-covering composed of a continuous flat band and separately-constructed spring wire frames mounted on said band and adapted to be held either within the head covering or to come down and engage with the ears of the wearer.

6. The combination, with a head covering embodying the usual sweat band, of suitable supports constructed independently of said head covering and its sweat band and adapted to be removably inserted between said sweat band and the wall of said head covering, wire must frames mounted on said supports and having coiled springs em-

bodied therein at points on the opposite side of the sweat band from the supports when the latter are placed in position behind the sweat band, and a suitable covering fabric secured to the muff frames.

7. The combination, with a head-covering, of suitable supports secured between the sweat band and the wall of the head-covering, wire muff frames mounted on said supports, said wire frames embodying coiled springs forming part of the support clasps, and other coiled springs at a little dis-

tance therefrom which operate to hold the muff frames 10 into the head-covering when not in use.

In witness whereof, I, have hereunto set my hand and seal at Indianapolis, Indiana, this 20th day of October, A. I). one thousand nine hundred and six.

SAMUEL R. WELLS. [L. S.]

Witnesses:

CHESTER BRADFORD, THOMAS W. MCMEANS.