

No. 889,283.

PATENTED JUNE 2, 1908.

A. WEISZ.
CIGARETTE PIPE.
APPLICATION FILED JULY 16, 1907.

FIG. 1.




FIG. 2.





FIG. 3.



Inventor

Andrew Weisz

Witnesses

[Handwritten signature]
W. P. Woodson

By

[Handwritten signature] Attorneys

UNITED STATES PATENT OFFICE.

ANDREW WEISZ, OF COLORADO SPRINGS, COLORADO.

CIGARETTE-PIPE.

No. 889,283.

Specification of Letters Patent.

Patented June 2, 1908.

Application filed July 16, 1907. Serial No. 383,981.

To all whom it may concern:

Be it known that I, ANDREW WEISZ, a citizen of the United States, residing at Colorado Springs, in the county of El Paso and State of Colorado, have invented certain new and useful Improvements in Cigarette-Pipes, of which the following is a specification.

The present invention relates to certain new and useful improvements in smoking appliances and more particularly to a novel form of pipe which may be termed a cigarette pipe since the tobacco being smoked is held in a long roll.

The object of the invention is to provide a simple and inexpensive pipe of this character which is so constructed as to enable the various parts to be readily taken apart and cleaned and thereby prevented from becoming saturated with nicotine.

For a full description of the invention and the merits thereof and also to acquire a knowledge of the details of construction and the means for effecting the result, reference is to be had to the following description and accompanying drawings, in which:

Figure 1 is a side elevation of a pipe embodying the invention. Fig. 2 is a longitudinal sectional view through the same. Fig. 3 is a detail view of the tubular casing.

Corresponding and like parts are referred to in the following description and indicated in all the views of the drawings by the same reference characters.

Specifically describing the invention the numeral 1 designates the stem which is provided with the usual longitudinally extending opening 2 and has the mouth-piece 3 at one of its extremities. The opposite end of the stem is enlarged as indicated at 4 and is designed to engage an end of the tubular casing 5 which is arranged in alinement with the stem 1 and is designed to receive the tobacco or other material being smoked within the pipe. It will also be observed that the inner end of the tubular casing 5 carries an annular rib 6 which is designed to be engaged by a pair of spring catches 7 upon the stem 1, the tubular casing being thereby securely locked against accidental displacement. This tubular casing 5 is also preferably formed in longitudinal sections which are loosely connected

along one pair of adjacent edges by any suitable means such as the hinge joint 8 while the opposite edges are designed to be locked together by a spring catch such as that indicated at 9. It will thus be apparent that the tubular casing can be readily detached from the stem and the two sections thereof opened so as to expose the interior of the casing for any desired purpose.

The outer end of the casing 5 is shown as closed by a perforated disk 10 which has one edge thereof hinged to the casing at 11 while the opposite edge carries a finger-piece 12 for manipulating the perforated disk. In the operation of the pipe the tobacco is placed within the casing 5 and lighted in the usual manner, the smoke being drawn through the passage 2 in the stem and the air entering the pipe through the perforated disk 10.

Having thus described the invention, what is claimed as new is:

1. In a pipe of the character described, the combination of a tubular casing formed in hinged longitudinal sections, a stem applied to one end of the tubular casing and disposed in alinement therewith, and a perforated disk hinged to the opposite end of the tubular casing and adapted to be swung over the same.

2. In a pipe, the combination of a stem, a tubular casing detachably connected to the stem and formed in two hinged longitudinal sections, and a closure for the end of the tubular casing, the said closure being pivoted upon the pintle of the said hinged longitudinal sections of the casing.

3. In a pipe, the combination of a stem, a tubular casing detachably connected to the stem and provided with a rib, and catches upon the stem designed to engage the rib.

4. In a pipe, the combination of a stem, a tubular casing formed in hinged longitudinal sections and detachably applied to the stem, catches carried by the stem for engaging the casing, and a perforated disk closing the said casing.

In testimony whereof I affix my signature in presence of two witnesses.

ANDREW WEISZ. [L. s.]

Witnesses:

M. W. PURCELL,
M. T. MURTAUGH.