

R. R. ELLIS.
PINCUSHION.
APPLICATION FILED MAY 18, 1907.



Witnesses Phil E. Baruses. Read Oright.



Robert R. Ellis.

Meana Brock

ditorneys

## UNITED STATES PATENT OFFICE.

ROBERT R. ELLIS, OF MEMPHIS, TENNESSEE.

## PINCUSHION.

No. 890,628.

Specification of Letters Patent.

Patented June 16, 1908.

Application filed May 18, 1907. Serial No. 374,336.

To all whom it may concern:

Be it known that I, ROBERT R. ELLIS, a citizen of the United States, residing at Memphis, in the county of Shelby and State of Tennessee, have invented a new and useful Improvement in a Pincushion, of which the following is a specification.

This invention relates to pin holders, and more particularly to pin holders to be arranged on the arm of a sewing machine, the object being to provide a pin holder which is so constructed, that it can be readily secured on the arm of a sewing machine or person so that it will always be at hand.

Another object of my invention is to provide a pin cushion which is very simple and cheap in construction, and one which is provided with means for securing it in place.

With these and other objects in view, the invention consists in the novel features of construction, combination and arrangement of parts, hereinafter fully described and pointed out in the claims.

In the drawing forming a part of this specification:—Figure 1 is a perspective view of my improved pin cushion showing it arranged on the arm of a sewing machine. Fig. 2 is a sectional view of the same, and Fig. 3 is a section taken on the line 3—3 of Fig. 2.

In the drawing A indicates a horse-shoe shaped pin cushion which may be formed of any suitable material, and is provided with the ordinary stuffing used in articles of this kind.

Arranged in the stuffing of the pin cushion

is a horse-shoe shaped spring B which is spaced a short distance away from the inner wall of the cushion, adapted to hold the cushion in shape, and to clamp the same securely on any object it is desired to use the cushion on. It will readily be seen that the ends of the cushion can be readily forced apart so that it can be slipped over an arm and that the spring being embedded in the 45 stuffing of the cushion will be surrounded by a padding which will prevent the cushion from scarring the object it is placed on.

In constructing this cushion I preferably employ a flat steel spring as shown in the 50 drawing, but it is of course understood that a wire spring can be embedded in the stuffing and will answer the same purpose as a flat spring.

From the foregoing description it will be readily seen that I have provided a novel pin cushion which can be easily and quickly attached to or removed from the arm of a sewing machine, and one which is so constructed that it will receive pins on all sides without any danger of the pins coming into contact with the spring.

Having thus fully described my invention, what I claim as new and desire to secure by Letters Patent is:—

A horse-shoe-shaped pin cushion having a bowed clamping spring arranged therein.

ROBT. R. ELLIS.

Witnesses:

J. W. Wynne, Jr., Katherine D. Ellis.