
E. G. FREY. TRUNDLING TOY. APPLICATION FILED MAY 13, 1908.



Inventor L.G. FAEY,

Mitnesses A.H. IZAB5UG,

MA Dutler

34 H

attorneys

UNITED STATES PATENT OFFICE.

EDWARD G. FREY, OF PITTSBURG, PENNSYLVANIA.

TRUNDLING TOY.

No. 898,351.

Specification of Letters Patent.

Patented Sept. 8, 1908.

Application filed May 13, 1908. Serial No. 432,716.

To all whom it may concern:

Be it known that I, Edward G. Frey, a citizen of the United States of America, residing at Pittsburg, in the county of Allebeny and State of Pennsylvania, have invented certain new and useful Improvements in Trundling Toys, of which the following is a specification, reference being had therein to the accompanying drawing.

This invention relates to trundling toys, and the primary object of my invention is to provide a novel toy the design and operation of which is adapted to afford consid-

erable amusement to juveniles.

A further object of this invention is to provide a toy that can be easily propelled to actuate a figure mounted upon the toy and cause the same to perform certain movements. To this end, I have devised a toy 20 that is used similar to the sport of "rolling hoop", a wheel similar to a hoop being used. The wheel is propelled by a suitable handle rod or stick and upon this handle rod or stick are located one or more figures adapt-25 ed to be actuated by a pitman connection with the wheel. The figures can be of a grotesque design and so connected to the handle rod or stick that the movement imparted | to said figures by the wheel will cause said 30 figures to perform certain gymnastics that will be pleasing to the eye and attractive to juveniles.

My invention will be further considered in detail and reference will now be had to the drawing forming a part of this specification,

wherein,

Figure 1 is a perspective view of a toy constructed with one figure, and Fig. 2 is a simi-

lar view illustrating two figures.

In the accompanying drawings 1 designates a handle rod or stick. Journaled upon the end of said rod or stick by a pin 2 is a wheel 3 having spokes 4. The handle rod or stick 1 adjacent to the wheel 3 is provided with 45 a vertical slot 5 in which is guided an upright 6. The lower end of the upright 6 is pivotally connected by a pin 7 to a pitman 8 and to a link 9, the former being pivotally connected to one of the spokes 4 by a pin 10 and the latter to the handle rod or stick 1 by a pin 11.

Suitably secured to the upper end of the

upright 6 is a body 12 having jointed arms 13 and legs 14, said legs being pivotally connected to the handle rod or stick 1, as at 15, 55 while the arms 13 are pivotally connected to the upper sections of the legs 14, as at 16. As shown in the drawings, the body 12, arms 13, and legs 14 represent a grotesque figure, and in this connection I reserve the 60 right to use any design of figure with my toy.

In operation, the link 9 is adapted to maintain the upright 6 in approximately a vertical position, while said upright is vertically reciprocated and oscillated by the rotary 65 movement of a wheel 3, through the medium

of a pitman 8.

In Fig. 2 of the drawings, I have illustrated a toy as provided with two figures and these two figures are actuated in unison by virtue 70 of a connecting bar 17, the remainder of the construction being similar to the toy illustrated in Fig. 1 of the drawings.

It is thought that the manner of operating my toy will be fully understood and that 75 wood or metal can be used in the construction of the same, although wood is preferably used to reduce the expense of manufacture to a minimum.

While in the accompanying drawings I 80 have illustrated a preferable form of construction embodying my invention, it is to be understood that the elements therein may be varied or changed without departing from

the spirit of the invention.

Having now described my invention what

I claim as new, is:—

1. A trundling toy comprising a handle rod, a wheel journaled at one end of said rod, uprights slidably mounted in said rod, links 90 pivotally connected to the lower ends of said uprights and to said handle rod, a connecting bar pivotally connected to the lower end of said uprights, a pitman pivotally connected to one of said uprights and eccentrically connected to said wheel, bodies carried by the upper ends of said uprights, jointed legs pivotally connected to said bodies and to said handle rod, and jointed arms pivotally connected to said bodies and to said handle rod, and jointed arms pivotally connected to said bodies and to the upper sections of said legs.

2. A trundling toy comprising a handle rod, a wheel journaled at one end thereof, an upright slidably mounted in said handle rod, a

link pivotally connected to the lower end of said upright and to said handle rod, a pitman pivotally connected to the lower end of said upright and eccentrically connected to said wheel, a figure carried by the upper end of said upright and connected with said handle rod.

In testimony whereof I affix my signature in the presence of two witnesses.

EDWARD G. FREY.

Witnesses:

K. H. Butler, Max H. Srolovitz.