
## L. FADUM. CLOTHES HANGER. APPLICATION FILED MAY 2, 1908.

898,455.

Patented Sept. 15, 1908.



Witnesses: 6. Huymann. 6. Schallinger

Inventor Ludwig Fadum by B. Singer' Attorney.

## UNITED STATES PATENT OFFICE.

LUDWIG FADUM, OF HAMBURG, GERMANY.

## CLOTHES-HANGER.

No. 898,455.

Specification of Letters Patent.

Patented Sept. 15, 1908.

Application filed May 2, 1908. Serial No. 430,548.

To all whom it may concern:

Be it known that I, Ludwig Fadum, a subject of the German Emperor, and resident of Hamburg, Germany, have invented certain 5 new and useful Improvements in Clothes-Hangers, of which the following is a specification.

This invention relates to improvements in clothes hangers and has to do more particu-10 larly with that class of hangers adapted for coats and the invention relates to improved means for supporting the collar portion of the coat so as to maintain the shape thereof when suspended on the hanger and to pre-15 vent the formation of wrinkles and creases resulting from sagging of the collar portion.

The invention however is designed to afford means for suspending a number of gar-

ments if desired.

The invention will be more fully described in connection with the accompanying drawing and will be more particularly pointed out and ascertained in and by the appended claims.

In drawing:—Figure 1, is a side elevation illustrating one embodiment of my invention. Fig. 2, is a similar view illustrating a slightly modified form of the embodiment

shown in Fig. 1.

As shown the invention includes a hanger 1 adapted to extend beneath the shoulder portion of the garment in the usual manner and a supporting hook 6 by means of which the hanger may be suspended. Said hanger 35 1 is provided with a collar supporting device which as shown consists of a supporting wire and a plurality of members loosely mounted thereon. As shown this supporting wire is formed similar to an inverted U the lower 40 end thereof passing through the hanger 1 and being secured therein in any desired manner. A convenient method of securing the ends of the wire 2 may consist in hammering the projections downwardly into said 45 hanger as indicated in Fig. 1. The horizontal portion of the wire 2 is provided with loosely mounted members 4 and the downwardly. inclined portion of the wire 2 is provided with loosely mounted members 3 as clearly shown 50 in Fig. 1. As shown the shank of the supporting hook 6 is wound about the horizontal portion of the wire 2 and serves not only to space the members 4 apart from each other but also to support the hanger 1 by means of 55 its connection with the wire 2. The lower end of the shank of the hook 6 extends down-

wardly through the hanger 1 and may terminate in an eye 8 adapted to be utilized for supporting any article of apparel. In order to maintain the members 4 on the horizontal 60 portion of the wire 2 and to space said members 4 and 3 apart from each other the wire 2 is looped as indicated at 5 and the loop 5 and loop 7 are so disposed with respect to the length of the members 4 as to allow the same a 65 slight longitudinal play. The members 3 are disposed between the loop 5 and the hanger 1 and are loosely mounted so as to rotate about the wire and also slide longitudinally thereof to a limited extent. It will be seen 70 the symmetrically arranged members 3 and 4 would effectively support the collar portions of the garment and that by reason of the loose mounting of said members the material of the garment will become worn when 75 put on and taken off from the hanger.

In the form shown in Fig. 2, the members 3 are supported by additional members 12 which latter are obliquely cut at their lower ends to fit the upper curved portions of 80 hanger 1. The upper curved portions of the members 12 gradually merge into the curve of the hanger 1 in a manner to fit that portion of the garment where the collar portion joins the shoulder portion and it will thus be 85 seen from the foregoing construction that it will be impossible for the collar portion to

form creases and wrinkles.

A plurality of double hooks 10 may be mounted on the lower portion of the hanger 90 1 to permit the user to suspend therefrom a plurality of pieces of wearing apparel. Conveniently the hooks 10 are secured to the hanger 1 by screws 11 so that said hooks 10 may be adjusted if desired.

I claim:—

1. In a clothes hanger the combination with the hanger proper of a collar supporting member made of wire bent into the shape of an inverted U, means for securing this collar 100 supporting member to the said hanger proper and a plurality of rollers loosely mounted on said wire supporting member, substantially as and for the purpose set forth.

2. In a clothes hanger the combination 105 with the hanger of a collar supporting member made of wire bent into the shape of an inverted U, means for securing the said member to the hanger, a plurality of horizontal rollers symmetrically and loosely mounted 110 on the horizontal part of said member, a plurality of rollers symmetrically and freely

 $\epsilon$ 

mounted on the descending parts of said member and a spring loop bent into the said member and adapted to separate the said horizontal rollers from the other ones, substantially as and for the purpose set forth.

3. In a clothes hanger the combination with the hanger of a collar supporting member made of wire bent into the shape of an inverted U, means for securing this collar supporting member to the hanger, a plurality of loosely mounted horizontal rollers symmetrically arranged on the horizontal part of said supporting member, a plurality of rollers symmetrically arranged and loosely mounted on the inclined parts of members, the lower ones of said rollers being cut away obliquely

at their lower part and spring loops bent in the said wire supporting member and separating the said horizontal rollers from the other ones, substantially as and for the pur- 20 pose set forth.

4. In a clothes hanger the combination with a hanger, of a collar supporting member secured to said hanger and provided with a plurality of members loosely mounted 25 thereon.

In testimony whereof I have hereunto set my hand in presence of two witnesses.

Witnesses:

WILHELM SCHULTEN, ERNEST H. L. MUMMENHOFF.