





F. WESTERBECK.
 IMPLEMENT FOR APPLYING AND REMOVING CAN STOPPERS.
 APPLICATION FILED JULY 10, 1908.

913,336.

Patented Feb. 23, 1909.



Attest:
Wm. H. Corbin
 W. H. Corbin

Inventor:
 F. Westerbeck,
 by *J. H. Wright* atty.

UNITED STATES PATENT OFFICE.

FREDERICK WESTERBECK, OF ST. LOUIS, MISSOURI.

IMPLEMENT FOR APPLYING AND REMOVING CAN-STOPPERS.

No. 913,336.

Specification of Letters Patent.

Patented Feb. 23, 1909.

Application filed July 10, 1908. Serial No. 442,896.

To all whom it may concern:

Be it known that I, FREDERICK WESTERBECK, a citizen of the United States of America, residing at the city of St. Louis, in the State of Missouri, have invented certain new and useful Improvements in Implements for Applying and Removing Can-Stoppers, of which the following is a full, clear, and exact description, reference being had to the accompanying drawings, forming part of this specification.

My invention relates to an implement for use in applying and removing stoppers of sheet metal cans and it has for its object the production of a device of this description by which the stoppers may be efficiently gripped in tightening them upon the threaded necks of the cans or in removing them from such necks without injury to the stoppers.

Figure I is a top or plan view of my implement shown in position for service upon a can stopper. Fig II is a longitudinal section taken on line II—II, Fig. I. Fig. III is an enlarged inverted view of the implement. Fig. IV is a cross section taken on line IV—IV, Fig. III in the position shown in Figs. I and II.

In the accompanying drawings: 1 designates one of the jaws of my implement which is provided with a handle 2 and 3 is the other jaw provided with a handle 4 and hinged to the jaw 1 at 5. The jaw 3 is movable relative to the jaw 1 and is normally held separated therefrom by an expansion spring 6.

1^a and 3^a are gripping members of segmental shape which are mounted respectively in the jaws 1 and 3 so that they oppose each other. These gripping members are serrated at their inner faces and they are adapted to be introduced into the jaws from the upper or back sides of the jaws and are rabbeted at their inner edges so as to rest upon ledges 1^b and 3^b respectively extending inwardly from the jaws, as seen in full lines Fig. IV and in dotted lines Fig. III. To prevent lateral movement of the gripping members in the jaws, I provide at the inner and outer ends of the jaws, lugs 1^c and 3^c, see Fig. III.

7 designates a cap plate that is secured removably, independent of the pivot 5, to the jaw 1 by suitable means, such as screws 8, see Fig. I, and which serves to close the space between the jaws at the top of the implement. This cap plate is provided with a slot 9 that receives a pin 10 carried by the

movable jaw 3 and which, by operating in the plate, serves to restrict the degree of outward movement of the jaw 3 relative to the jaw 1, in order that the spring 6 between the jaws may be retained in its proper position. The cap plate in addition to the service mentioned also serves as a means for confining the gripping members 1^a and 3^a in the jaws of the implement after they have been introduced thereinto and further as a means for limiting the degree of downward movement of the implement when it is applied to the stopper of a can for the purpose of applying the stopper to or removing it from the can.

The gripping members 1^a and 3^a of my implement are loosely seated in their respective jaws in order that they may be removed from the implement and other gripping members either larger or smaller in size substituted for those previously used, whereby the implement may be made serviceable in connection with can stoppers of various sizes. The changing of the gripping members is readily accomplished upon the removal of the cap plate 7.

In the practical use of my implement, the implement is fitted to the stopper of a can as illustrated in Figs. I and II, so that the cap plate 7 will rest upon the stopper and the jaws of the implement are moved toward each other in order that the gripping members therein will tightly grip the stopper after which either the implement or the can is turned with the result of causing the stopper to be tightly secured onto the neck of the can or removed therefrom, according to the service desired.

I claim:—

1. In an implement of the character described, the combination with a pair of jaws having handles and hinged to each other, removable gripping members in said jaws, and a cap plate for confining said gripping members; said cap plate being secured to one of said jaws and having slot and pin connection with the other jaw, substantially as set forth.

2. In an implement of the character described, the combination of a pair of jaws having handles and hinged to each other, gripping members detachably mounted in said jaws and adapted to be removed from the jaws in a direction transversely of the jaws, and a cap plate carried by one of said jaws whereby said gripping members are confined in the jaws, substantially as set forth.

3. In an implement of the character de-
scribed, the combination of a pair of jaws
having handles and hinged to each other,
gripping members having rabbeted inner
5 edges and detachably mounted in said jaws,
the jaws being each provided at a side there-
of with a ledge upon which the gripping
member corresponding to the jaw rests, and

a cap plate carried by one of said jaws where-
by the gripping members are confined in 10
the jaws.

FREDERICK WESTERBECK.

In the presence of—

H. G. COOK,
BLANCHE HOGAN.