


J. A. McCRAW.
MAIL POUCH.
APPLICATION FILED JULY 14, 1908.

919,745.

Patented Apr. 27, 1909.



Witnesses
James F. Brown
M. S. Skinner.

By

J. A. McCraw
Inventor
Nathan E. Coleman
Attorney

UNITED STATES PATENT OFFICE.

JOHN A. McCRAW, OF NATHALIE, VIRGINIA.

MAIL-POUCH.

No. 919,745.

Specification of Letters Patent.

Patented April 27, 1909.

Application filed July 14, 1908. Serial No. 443,514.

To all whom it may concern:

Be it known that I, JOHN A. McCRAW, a citizen of the United States, residing at Nathalie, in the county of Halifax and State of Virginia, have invented certain new and useful Improvements in Mail-Pouches, of which the following is a specification, reference being had to the accompanying drawings.

This invention relates to improvements in carrying receptacles and more particularly to a mail pouch especially adapted for the use of rural delivery mail carriers.

The object of the invention is to provide a simple, durable, convenient and inexpensive device of this character having a plurality of separate compartments for the mail matter and into which mail may be readily deposited and from which it may be as readily removed.

With the above and other objects in view, the invention consists of the novel features of construction and the combination and arrangement of parts hereinafter fully described and claimed, and illustrated in the accompanying drawings, in which—

Figure 1 is a perspective view of the improved mail pouch; Figs. 2 and 3 are vertical and horizontal sectional views through the same; and Fig. 4 is a detail view of one of the metal frames.

The invention comprises a plurality of rectangular metal frames 1, a plurality of bags 2 of canvas, leather, or the like and two end pieces 3 of similar material. Each of the bags 2 forms one of the pockets 4 of the pouch or receptacle and the several bags are united to each other by placing the frames 1 between their opposing sides and then sewing or stitching said sides together, as shown at 5, around said frames 1. The bags 2 as well as the frames 1 are of rectangular shape but they are of greater width and length than said frames and in making the pouch the latter have their upper ends arranged adjacent to the upper or open edges of the bags so that the projecting portions of the sides and bottoms of the bags form bellows-like folds 6 which permit the compartments 4 to be expanded or contracted according to the quantity of mail matter or the like placed in them. Any number of said bags may be united to each other and the endmost ones have the end pieces 3 sewed or stitched to them and around the endmost frames 1, which latter are placed upon the outer faces of the endmost bags, as will be readily understood upon

reference to the drawings. Each of the frames 1 is preferably formed from a single piece of wire by bending the same to form a bottom 7, two parallel sides 8 rising from the bottom and a top formed by inwardly extending ends 9 which overlap each other and may slide past each other to permit the upper ends of the frames 1 and, consequently, the tops or mouths of the pockets or compartments 4 to be contracted. The bags 2 may be of any suitable form and construction but, as illustrated, they are made of two similar shaped pieces secured around their side and bottom edges by sewing or stitching them, as shown at 9'.

For the purpose of retaining the mail matter within the pouch and permitting the latter to be conveniently carried, top and side fastening straps are provided. The top strap consists of two sections 10, 11, the former of which has one end attached to one of the end pieces 3 and its other end provided with a buckle 12. The other section 11 is attached to the other end piece 3 and is adapted to extend over the open upper ends of the compartments 4, its free end being provided with a series of openings to receive the tongue of the buckle 12. Each of the side fastening straps is similarly constructed and consists of two sections 13, 14 adjustably united by a buckle 15. Said straps 13, 14 are secured to the opposite end pieces 3 adjacent to the lower ends of the latter and they are adapted to extend over the bellows-folds 6, as clearly shown in Fig. 1. It will be seen that the section 11 of the top strap serves to prevent the mail matter from falling out of the pockets 4 and also serves as a handle for conveniently carrying the pouch. The side straps may be drawn as tight as desired to effectively bind the mail matter in the several pockets or compartments.

When the invention is used as a mail pouch for rural delivery service the several pockets or bags may be labeled with the names of the patrons along the route of the carrier who uses the pouch. One or more of such names may be provided upon the bellows-folds 6, as shown in Fig. 1, or they may be otherwise placed upon the pouch.

In using the invention, it will be seen that when the sections of the top and side straps are disconnected from each other the several compartments may be stretched to their open position so that the pouch will be of substantially rectangular form and will stand

by itself upon a desk or table while the mail matter is being placed in it. After the mail has been properly distributed in the several pockets of the pouch at the post office the
5 top and side straps may be fastened to prevent the mail matter from falling out and being lost and to permit the pouch to be conveniently carried. When the carrier is on his route the mail can be quickly and easily
10 removed from the pockets when the top strap is open.

Having thus described the invention what is claimed is:

1. A pouch of the character described
15 comprising a plurality of independent bags of substantially rectangular shape and constructed of flexible material, said bags being arranged side to side with their open tops uppermost, substantially rectangular
20 reinforcing frames of less width and length than the bags and arranged between the opposing sides of the latter nearer to the upper edges of said sides, stitching uniting the opposing sides of the bags and extending
25 around said frames, whereby the bags are united, the frames retained between the bags and bellows-like folds are provided at the sides and bottom of the pouch, similar reinforcing frames arranged upon the outer
30 sides of the endmost bags, sheet coverings

arranged over the last mentioned frames and stitched to said outermost bags around said frames, and two-part adjustably connected straps arranged on both sides and on the top of the pouch, the ends of the straps being secured to said sheet coverings, the strap at the top serving as a handle and also as a closure for the open upper tops of the bags, and the straps at the sides serving to adapt the pouch to the contents of the bags, substantially as described. 35 40

2. A pouch of the character described comprising a plurality of independent bags of flexible material arranged side to side and united to each other, reinforcing frames
45 between adjacent bags, and adjustable two-part straps arranged on both sides of the pouch and at its top, the ends of the straps being secured to the ends of the pouch, the side straps serving to adapt the pouch to
50 the contents of its bags and the top straps serving as a handle and as a means for retaining the contents of the bags therein.

Intestimony whereof I hereunto affix my signature in the presence of two witnesses. 55

JOHN A. McCRAW.

Witnesses:

E. D. BROOKS,
S. P. YOUNGUR.