

F. P. SHEK.


RACK.

APPLICATION FILED FEB. 13, 1909.

924,386.

Patented June 8, 1909.

2 SHEETS—SHEET 1.



WITNESSES

*W. Ruppelmann*  
*b. E. Mulvaney*

INVENTOR

Frank P. Shek

BY

*Edgar Tate & Co.*

ATTORNEYS

F. P. SHEK.


RACK.

APPLICATION FILED FEB. 13, 1909.

924,386.

Patented June 8, 1909.

2 SHEETS—SHEET 2.



WITNESSES

*A. Appleman*  
*b. E. Mubresny*

BY

*Edgar Tate & Co.*

ATTORNEYS

INVENTOR

*Frank P. Shek*



# UNITED STATES PATENT OFFICE.

FRANK P. SHEK, OF BROOKLYN, NEW YORK.

RACK.

No. 924,386.

Specification of Letters Patent.

Patented June 8, 1909.

Application filed February 13, 1909. Serial No. 477,530.

*To all whom it may concern:*

Be it known that I, FRANK P. SHEK, a citizen of the United States, and residing at Brooklyn, in the county of Kings and State of New York, have invented certain new and useful Improvements in Racks, of which the following is a specification, such as will enable those skilled in the art to which it appertains to make and use the same.

This invention relates to racks and more particularly to what are known as "pan-racks," commonly used by bakers and confectioners and others to cool, display or conveniently store their wares; and the object thereof is to provide an improved device of this class which may be conveniently folded together and packed in a small space when not in use, and which may be easily set up or placed in position for use whenever desired.

The invention is fully disclosed in the following specification, of which the accompanying drawings form a part, in which the separate parts of my improvement are designated by suitable reference characters in each of the views, and in which:—

Figure 1 is a perspective view of my improved rack, Fig. 2 a section on the line 2—2 of Fig. 1, Fig. 3 a section on the line 3—3 of Fig. 1, and;—Fig. 4 a view similar to Fig. 1, but showing a modification.

In the practice of my invention, I provide a device of the class specified composed of two main side parts  $a$ , each of which comprises an upright member  $a^2$  and a horizontal base or bottom member  $a^3$ , the upright member  $a^2$  being provided with horizontal arms  $b$ , the base members  $a^3$  being connected by diagonally or obliquely arranged cross bars or rods  $c$ , and the upright members  $a^2$  being connected by obliquely or diagonally arranged cross bars or rods  $d$  which are pivotally connected at  $d^2$ .

The upright members  $a^2$ , in the form of construction shown, are composed of T-rails, and the horizontal arms  $b$  are passed through the web portions of said rails and riveted or otherwise secured to said rails, the web members  $a^4$  being directed inwardly.

The bottom members  $a^3$  of the side parts  $a$  are composed of angle iron L-shaped in cross section, and the bottom rods or bars  $c$  are pivoted at one end to the horizontal web portions  $a^5$  of said members as shown at  $c^2$ , and the other ends of said rods or bars are provided with hooks  $c^3$  which are adapted

to be passed through holes  $c^4$  in the horizontal web portions  $a^5$  of the base members  $a^3$ , and said rods or bars  $c$  are pivotally connected at  $c^5$ .

The lower end portions of the cross bars or rods  $d$  are pivoted at  $d^3$  to the bottoms of the upright members  $a^2$ , or the inwardly directed webs  $a^4$  thereof, and said webs are provided at the tops of the upright members  $a^2$  with longitudinal slots  $e$  and the upper ends of the rods or bars  $d$  are provided with bolts or pins  $f$  which pass through said slots and are provided with crank handles  $g$  having heads  $g^2$  provided in one side with a cam recess  $g^3$ , and the web members  $a^4$  are provided on the side thereof adjacent to the crank handles  $g$  with cam lugs or projections  $g^4$ . The upright members  $a^2$  of the side portions of the device are also preferably connected with the base members  $a^3$  by braces  $h$ , and as thus constructed it will be seen that the separate parts of the device may be held as shown in Fig. 1, in which position a pan or other receptacle  $i$  may be supported by the horizontal arms  $b$  on both sides of the upright members  $a^2$ , and in this way a large number of such pans or receptacles may be supported on my improved rack, and said pans or receptacles may be used for holding or containing any kind or class of articles, and especially bakery products for cooling, drying or other purposes.

When the device is not intended for use the side portions  $a^2$  thereof may be compactly folded together and stored in a small space, and in order to do this all that is necessary is to disconnect the hooks  $c^3$  of the bottom rods or bars  $c$  from the base or bottom members  $a^3$  and turn the crank handles  $g$  upwardly. This operation will enable the bolts or pins  $f$  to slide freely in the slots  $e$  and the separate side members  $a^2$  of the device may be folded together as will be readily understood.

When the separate parts of the device are expanded for use as shown in Fig. 1, the crank handles  $g$  must be turned downwardly into the position shown in Fig. 1, and in this operation the rods or bars  $d$  are locked to the upright members  $a^2$  in the position shown in said figure.

In the construction shown in Fig. 4, the upright members  $a^2$  of the side frames  $a$  are provided with arms  $b$  at one side only and the bottom rods or bars  $c$  are connected with only one end or side part of the base mem-



bers  $a^3$ , and with these exceptions the two forms of construction are substantially the same and may be operated in the same manner.

5 The base members or parts  $a^3$  in both forms of construction are provided with casters or rollers  $j$ , whereby the device may be conveniently moved from one place to another if desired, and by means of my im-  
10 provement I provide a device of the class specified which is simple in construction and operation, and comparatively inexpensive and which may be conveniently used for the purposes specified, wherever desired,  
15 and also for other purposes.

Having fully described my invention, what I claim as new and desire to secure by Letters Patent, is:—

1. A rack of the class described comprising  
20 ing upright members connected with horizontal base members, the upright members being provided with laterally directed arms, and the upright members being connected by diagonally arranged rods or bars which are  
25 pivoted to the bottoms of said upright members and movable longitudinally of the top portions of said upright members and adapted to be locked thereto, said rods or bars being pivotally connected centrally thereof,  
30 and the base members of the device being also connected by diagonally or obliquely arranged rods or bars, said rods or bars being pivotally connected centrally thereof, and one end portion thereof being pivoted  
35 to said base members and the other end portions of said rods or bars being adapted to be connected with said base members at different points.

2. A rack of the class described comprising  
40 ing side portions composed of upright members and horizontal base members, the upright members being provided with laterally

directed arms, and said upright members be- 45  
ing connected at the top and bottom by diagonally or obliquely arranged rods or bars, said rods or bars being pivotally connected with the lower ends of the upright  
members and being movable longitudinally 50  
of the top portions thereof and adapted to be locked thereto, the base members being also connected by diagonally or obliquely  
arranged rods or bars, one end portion of  
said rods or bars being pivoted to the base 55  
members, and the other end portions thereof being adapted to be detachably connected therewith.

3. A rack of the class described comprising side portions composed of upright mem- 60  
bers and horizontal base members, the upright members being provided with laterally directed arms and the top and bottom portions of said upright members being connected by diagonally or obliquely arranged 65  
rods or bars which cross each other and are pivotally connected where crossed, the connection of said rods or bars with said upright members at one end being a pivotal  
connection, and at the other a longitudinally 70  
movable connection, the base members being also connected by diagonally or obliquely arranged rods or bars which cross each other and are pivotally connected where crossed,  
one end portion of said rods or bars being 75  
pivoted to the said base members, and the other end portion thereof being detachably connected with said base members.

In testimony that I claim the foregoing as  
my invention I have signed my name in pres- 80  
ence of the subscribing witnesses this 11th day of February 1909.

FRANK P. SHEK.

Witnesses:

C. E. MULREANY,  
HARRY R. CANFIELD.