

APPLIOATION FILED JULY 20, 1908.

Patented June 22, 1909.

19-1







Fig. 2



194

J. A. Brophy
New York Harbor

INVENTORS
Alderic F. Girouard
Ferdinand H. Perron
BY *Munn & Co*
ATTORNEYS

UNITED STATES PATENT OFFICE.

ALDERIC F. GIROUARD, OF LEOMINSTER, AND FERDINAND A. PERRON, OF FITCHBURG,
MASSACHUSETTS.

WINDOW-FIXTURE.

No. 925,893.

Specification of Letters Patent.

Patented June 22, 1909.

Application filed July 20, 1908. Serial No. 444,309.

To all whom it may concern:

Be it known that we, ALDERIC F. GIROUARD and FERDINAND A. PERRON, citizens of the United States, and residents, respectively, of Leominster, in the county of Worcester and State of Massachusetts, and of Fitchburg, in the county of Worcester and State of Massachusetts, have invented a new and Improved Window-Fixture, of which the following is a full, clear, and exact description.

The object of the invention is to provide a new and improved window fixture, combining means for supporting or holding a curtain pole, shade roller and blind, the fixture being simple and durable in construction, cheap to manufacture and easily applied to the window casing without the use of nails, screws or similar fastening devices.

The invention consists of novel features and parts and combinations of the same, which will be more fully described hereinafter and then pointed out in the claims.

A practical embodiment of the invention is represented in the accompanying drawings forming a part of this specification, in which similar characters of reference indicate corresponding parts in all the views.

Figure 1 is a reduced front elevation of the improvement as applied; Fig. 2 is a cross section of the same on the line 2—2 of Fig. 1; Fig. 3 is a sectional plan view of the same on the line 3—3 of Fig. 2; and Fig. 4 is a plan view of the shade roller supporting bar.

The window fixture consists essentially of brackets A, A, each made from a single piece of spring wire bent to form a vertical member B, adapted to rest on the front face of the top cross bar C of the window casing, as plainly indicated in Figs. 1 and 2. The upper end of the vertical member B terminates in a transversely-extending hook D, adapted to hook onto the top of the cross bar C (see Fig. 2), to support each bracket on the top cross bar. From the vertical member B extend forwardly the twisted portions E terminating in a bearing F for supporting the curtain pole G the desired distance from the window casing, as will be understood by reference to Figs. 1 and 2. The lower end of each vertical member B terminates in an open bearing H for supporting the bar I made in sections adjustable one on the other, the ends of the bar I being provided with the usual shade roller brackets J for receiving

the pintles of an ordinary spring shade roller K. By the arrangement described, the shade roller supporting bar I can be adjusted in the direction of its length to suit a shade roller of an ordinary size, it being understood that after the sections of the support are adjusted they are fastened in place by suitable set screws I', as indicated in Fig. 4.

Each of the bearings H terminate in a transversely-extending spring member L adapted to rest against the inner face of the corresponding side C' of the window casing and also against the under side of the cross bar C, so as to securely hold the hook D in engagement with the top of the cross bar C, as indicated in Fig. 2. The spring member L terminates at its inner end in a foot N, adapted to abut against the stop bead C² of the window casing, so as to limit the inward movement of the spring member L, and to insure a rigid attachment of each bracket on the window casing. The spring member L of each bracket A is provided with a sidewise extending bent portion O (see Figs. 1 and 3) having bearings P for the reception of the pintles Q' of a blind roller Q, extending within the opening of the window casing, as plainly indicated in the drawings. By having the bent portion O, the ends of the pintles Q' do not come in contact with the inner faces of the sides C' and hence are not liable to mar the same.

Now by the arrangement described, each bracket A is formed of a single piece of wire and forms supports for the curtain pole, the shade roller and a blind roller, and each bracket A is securely held in place without the use of screws, nails or similar fastening devices.

Having thus described our invention, we claim as new and desire to secure by Letters Patent:

1. A window fixture, comprising a pair of brackets, each made of a single piece of spring wire bent to form a vertical member provided at its upper end with a hook for engagement with the top of the cross bar of the window casing, a curtain pole support formed by twisting the wire and extending the same transversely from the said vertical member, the outer portion of the said support being formed into an open bearing for the curtain pole, a second open bearing at the lower end of the said vertical member,

and a spring extending from the said second bearing and adapted to engage the under side of the said top cross bar, the said spring member having a sidewise bent portion between the ends and a bearing for a blind roller formed in the said sidewise bent portion, and a shade roller supporting bar fitting into the said second open bearings of the two brackets.

10 2. A window fixture, comprising a pair of brackets, each made of a single piece of spring wire bent to form a vertical member provided at its upper end with a hook for engagement with the top of the cross bar
15 of the window casing, a curtain pole support formed by twisting the wire and extending the same transversely from the said vertical member, the outer portion of the said support being formed into an open
20 bearing for the curtain pole, a second open bearing at the lower end of the said vertical member, and a spring member extending transversely from the said second bearing and adapted to engage the under side of the
25 said top cross bar, the said spring member having a sidewise bent portion between its ends and a bearing for a blind roller formed in the said sidewise bent portion, a shade

roller supporting bar fitting into the said second open bearings of the two brackets, 30 the said shade roller supporting bar being made in sections slidably mounted one on the other, and means for securing the sections in place after the adjustment is made.

3. A window fixture comprising a pair of 35 brackets formed of a single piece of wire bent to form a vertical member having at its upper end a hook, and at its center a laterally extending curtain pole support, the wire at the bottom of the vertical member 40 being bent upward to form an open bearing for the curtain pole, and thence laterally in the opposite direction from the curtain pole support for engaging the under side of the window casing, an open bearing being formed 45 intermediate such laterally bent portion for receiving a blind roller.

In testimony whereof we have signed our names to this specification in the presence of two subscribing witnesses.

ALDERIC F. GIROUARD.
FERDINAND A. PERRON.

Witnesses:

ALVAH M. LEVY,
FREDERICK A. CORWIN.