


F. M. MORTON & W. H. DISMUKE.  
SLIPPER OR MUZZLE FOR DRAWING ON MACHINES FOR DRAWING ROLL COVERS.  
APPLICATION FILED APR. 2, 1908.

929,154.

Patented July 27, 1909.

2 SHEETS—SHEET 1.



Witnesses

Chas. L. Greibauer  
C. H. Greibauer

By


W. H. Dismuke and  
Frank M. Morton.

Attorneys

F. M. MORTON & W. H. DISMUKE.  
SLIPPER OR MUZZLE FOR DRAWING ON MACHINES FOR DRAWING ROLL COVERS.  
APPLICATION FILED APR. 2, 1908.

Patented July 27, 1909.  
2 SHEETS—SHEET 2.

929,154.



Witnesses  
*W. H. Dismuke*  
*E. O. Hilton*

Inventors  
*W. H. Dismuke*  
*Frank M. Morton*  
by *A. B. Wilson & Co.*  
Attorneys



# UNITED STATES PATENT OFFICE.

FRANK M. MORTON AND WILLIAM H. DISMUKE, OF PHOENIX, ALABAMA.

SLIPPER OR MUZZLE FOR DRAWING-ON MACHINES FOR DRAWING ROLL-COVERS.

No. 929,154.

Specification of Letters Patent.

Patented July 27, 1909.

Application filed April 2, 1908. Serial No. 424,729.

*To all whom it may concern:*

Be it known that we, FRANK M. MORTON and WILLIAM H. DISMUKE, citizens of the United States, residing at Phoenix city, in the county of Lee and State of Alabama, have invented certain new and useful Improvements in Slippers or Muzzles for Drawing-on Machines for Drawing Roll-Covers; and we do declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

This invention relates to an improved slipper or muzzle to be used on what is known as the drawing on machine for putting covers on spinning frame rollers.

The object of the invention is to provide improved clamping means for holding the removable fingers of a muzzle in proper position.

With this and other objects in view, the invention consists of certain novel features of construction, combination and arrangements of parts, as will be more fully described and particularly pointed out in the appended claims.

In the accompanying drawings, Figure 1 is a side elevation of a slipper or muzzle constructed in accordance with this invention; Fig. 2 is a longitudinal section thereof, Fig. 3 is a transverse section; Fig. 4 is a detail perspective view of the head. Fig. 5 is a side elevation of a drawing on machine showing this improved muzzle applied.

In the embodiment illustrated, a body portion 1 is shown comprising a base plate 2 having a tubular extension 3 and oppositely extending apertured lugs or ears as 4 arranged on opposite sides of said extension with the apertures therein screw threaded to receive connecting rods 5 and 6. This cylindrical extension 3 has a smooth inner bore and is provided on its outer face with spaced annular ribs 7 and 8 preferably located near its opposite ends and each being provided with spaced recesses or notches as 9 and 10 respectively, to receive the spring fingers as 11. An annular shoulder 12 is arranged at the base of the tubular extension 3 below the rib 7 and is designed to form a stop for limiting the inward movement of the fingers 11. This extension is also provided with a laterally extending

stop pin 13 preferably arranged at the base thereof for a purpose to be described.

A split clamping sleeve 14 encircles the tubular extension 3 and is preferably made of a width corresponding to the length of said extension and is provided on its inner face with annular shoulders 15 and 16 arranged in position to engage the outer edges of the annular ribs 7 and 8 when the parts are assembled to prevent longitudinal movement of said sleeve relative to said extension. This split sleeve 14 has outwardly projecting laterally extending apertured ears 17 and 18 at its opposite ends, the aperture in one of said ears being screw threaded to receive a clamping screw or bolt 19 preferably provided with an angular head to facilitate the screwing and unscrewing thereof to tighten or loosen the sleeve, said bolt when applied having its headed end arranged to bear against outer face of the ear having the unthreaded aperture. This sleeve is provided with a recess or notch 20 preferably formed in its lower edge at a point opposite its split portion. This recess 20 is adapted to fit over the stop pin 13 on the extension 3 and hold the clamping sleeve against rotation during the tightening or loosening operation.

It will be readily understood that after the fingers 11 have been inserted in the notches 9 and 10 of the ribs 7 and 8 and the sleeve 14 disposed therearound the screwing or unscrewing of the bolt 19 will operate to tighten or loosen said sleeve and vary its tension on the fingers 11.

In the use of this improved muzzle, it is connected with a drawing on machine of any suitable construction, preferably by passing the connecting rods 5 and 6 through apertured lugs as 26 and securing them in position by set screws as 27. The roller cover or cop (not shown) is then drawn on over the fingers 11 of the muzzle and the machine is operated to force a roller through the muzzle into the cover which is constructed to fit said roller closely.

From the foregoing description, taken in connection with the accompanying drawings, the construction and operation of the invention will be readily understood without requiring a more extended explanation.

Various changes in the form, proportion and the minor details of construction may be resorted to without departing from the



principle or sacrificing any of the advantages of the invention, as defined in the appended claims.

I claim as my invention:

- 5 1. A slipper or muzzle comprising a base plate having a tubular extension provided with spaced annular notched ribs on its outer face, a split clamping sleeve encircling said extension and provided with means for  
10 engagement with said ribs to prevent longitudinal movement of said sleeve relatively to said extension, means for holding said sleeve against rotation, and spring fingers arranged in said notched ribs.
- 15 2. A slipper or muzzle for drawing on machines provided with a plurality of removable fingers and a transversely split clamping sleeve encircling said fingers and provided with means for drawing the split  
20 ends thereof together for securing said fingers in operative position.
3. A slipper or muzzle comprising a tubular extension having longitudinally spaced annular ribs on its outer face pro-  
25 vided with spaced notches, fingers arranged in said notches, a laterally extending lug on said extension, a split clamping sleeve en-

circling said extension and having shoulders for engagement with said ribs to prevent longitudinal movement, a recess in said  
30 sleeve for engagement with said lug to hold said sleeve against rotation and means for tightening said sleeve relatively to said extension.

4. A slipper or muzzle comprising a  
35 tubular extension having longitudinally spaced annular ribs on its outer face provided with spaced notches, fingers arranged in said notches and a split clamping sleeve having outwardly extending apertured ears  
40 at its opposite ends, means for holding said sleeve against rotation and a bolt engaged with said apertured ears for tightening or loosening said sleeve relatively to said extension.

45 In testimony whereof we have hereunto set our hands in presence of two subscribing witnesses.

FRANK M. MORTON.  
WILLIAM H. DISMUKE.

Witnesses:

C. D. SMITH,  
EARL MORGAN.