
G. HENERY.

TOY.

APPLICATION FILED SEPT. 30, 1908.

939,022.

Patented Nov. 2, 1909.



UNITED STATES PATENT OFFICE.

GRANT HENERY, OF ZANESVILLE, OHIO.

TOY.

939,022.

Specification of Letters Patent.

Patented Nov. 2, 1909.

Application filed September 30, 1908. Serial No. 455,581.

To all whom it may concern:

Be it known that I, Grant Henery, a citizen of the United States, residing at Zanesville, in the county of Muskingum and State of Ohio, have invented new and useful Improvements in Toys, of which the following is a specification.

This invention relates to toys, the object in view being to provide a toy catapult delike and for shooting marbles, balls and the like and embodying a construction which insures simplicity, economy and reliability of operation while providing an attractive amusement device for children.

With the above and other objects in view, the invention consists in the novel construction, combination and arrangement hereinafter fully described, illustrated and claimed.

In the accompanying drawings:—Figure 1 is a side elevation of the improved toy. Fig. 2 is an inside elevation of one of the sections or halves of the toy. Fig. 3 is a front elevation of the toy. Fig. 4 is a rear elevation thereof. Fig. 5 is a cross section on the line 5—5 of Fig. 1.

The body or frame of the toy is made up of two similar and approximately equal sections 1 and 2 of the same general configuration, the sections being provided with marson ginal inturned flanges 3 so that when said sections are secured together by passing screws, rivets or their equivalent through the sections as shown at 4, an inclosed space is formed in which the operative parts of the mechanism are housed.

The shape of the frame or body pieces is such as to provide a hand-grip 5 which may be roughened or chased as shown at 6, a projecting half barrel or gutter 7 for holding a 40 ball or marble and directing the same when projected from the toy, and an overhanging arm 8 located above the barrel and adapted for the support of the marble or ball retainer. The ball retainer consists of a piece 45 of wire bent into inverted U-shape as shown in Figs. 3 and 4 and extending over the top of the arm 8 to which it is secured by means of a spring 9 the tendency of which is to hold the retainer downward but allow the 50 same to yield upward. The retainer is provided at the top with an eye or finger piece

10 by means of which it may be raised to insert a marble or ball. The arms 11 of the retainer are bent inward as shown at 12 to form inwardly converging jaws which obtain the necessary grip on the ball or marble to retain the same in the half barrel 7 close up to abutment shoulders 13 forming the inner confines of the ball or marble receiving space.

14 designates the projectile throwing spring which extends up and down within the hollow handle and has one end thereof permanently secured therein as shown at 15 while the other end is free to swing and 65 is provided with a terminal eye 16 to which may be attached a cord or elastic band, a ball being secured to the other end of said cord or, band. One of the sections is provided with a wedge shaped projection forming a 70 trigger engaging face 17 and an engaging shoulder 18 for the spring 14 when pulled back to a firing position.

19 designates the trigger which may be formed of a piece of wire, one end thereof 75 being provided with an eye which surrounds a pivot in the lower portion of the handle while the opposite hooked end 21 of the trigger is adapted to ride over a knob or projection 22 on one of the sections so as to 80 impart a lateral movement thereto and to the spring 14 which will push said spring from behind the shoulder 18 allowing said spring to snap forward and strike against the ball or marble shown at 23 which is 85 thereby projected a distance commensurate with the power of the spring 14.

I claim:—

1. A toy of the class described comprising a hollow sectional frame, a half barrel or 90 gutter projecting therefrom, a projectile retainer embodying inwardly converging spring arms which act to clasp the projectile at opposite sides of its vertical axis and hold the same against the half barrel, a 95 spring for throwing the projectile, means for holding the spring set, and a trigger for releasing the spring.

2. A toy of the class described comprising a hollow sectional frame, means for hold- 100 ing a projectile, a projectile throwing spring, a spring holdback shoulder with

which the spring is adapted to be engaged when set, a pivoted trigger embodying a spring arm, and means with which the trigger coöperates to impart a lateral movement to the spring arm, the latter acting on the throw spring to dislodge the same in a lateral position from behind said shoulder.

In testimony whereof I affix my signature in presence of two witnesses.

GRANT HENERY.

Witnesses:
E. F. O'NEAL,
MAY RARICK.