

J. F. MASTERS.

FLOORING.

APPLICATION FILED MAR. 15, 1909.

947,114.

Patented Jan. 18, 1910.

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.





Fig. 5.



Inventor

J. F. Masters.

Witnesses

C. H. Walker.
Albert Popkins

By *Sturtevant & Mason*

Attorneys

UNITED STATES PATENT OFFICE.

JOHN F. MASTERS, OF DURHAM, NORTH CAROLINA.

FLOORING.

947,114.

Specification of Letters Patent.

Patented Jan. 18, 1910.

Application filed March 15, 1909. Serial No. 483,572.

To all whom it may concern:

Be it known that I, JOHN F. MASTERS, a citizen of the United States, residing at Durham, in the county of Durham, State of North Carolina, have invented certain new and useful Improvements in Flooring, of which the following is a description, reference being had to the accompanying drawing and to the letters of reference marked thereon.

My invention relates to an improvement in flooring, and particularly to a construction whereby hard wood floors may be quickly and securely laid with comparatively little trouble and expense.

My invention consists primarily in a series of sections of flooring, each section composed of a number of boards permanently held together, and provided with permanent means secured thereto for the attachment of a succeeding section.

Further, it consists of the matters hereinafter described and referred to in the appended claims.

The invention is illustrated in the accompanying drawings, in which,—

Figure 1 is a plan view of two sections of flooring, constructed in accordance with my invention; Fig. 2 is an edge view; Fig. 3 is a section on line 3—3 of Fig. 1; Fig. 4 is a section on line 4—4 of Fig. 1; Fig. 5 is a sectional view, illustrating a modification.

In the drawings, A represents the sections of which the flooring is composed. Each section consists of a series of boards or planks *a*, arranged edge to edge. The boards are held together to form the sections, by means of threaded bolts or screws *b*, which pass transversely through one of the outer side boards, through the intermediate boards, and are threaded into the opposite outer side board of the section.

In order that the sections may be secured together, I have provided each section with a transverse opening which extends entirely through said section, and is adapted to receive a threaded bolt *c*. As shown in Figs. 1 and 4, the board adjacent the outer boards in one section, is cut away to form a recess to receive a nut *d*. This recess is located in line with the opening through the adjacent sections, and a similar opening is made through

the outer board, so that the bolt *c* for securing the sections together, not only passes entirely through one section, but through the opening formed in the outer board of the adjacent section, so that the bolt *c*, may be threaded into the nut *d*. It will be seen therefore, that the threaded bolts or screws *b*, serve to secure boards together, to form a section, and the threaded bolts *c*, not only serve to hold the sections together, but also aid in holding the boards together of the section through which they pass.

Instead of the nut *d*, an elongated hollow headed bolt may be used and embedded in the section, adjacent the edge thereof. In Fig. 5, I have shown a modification in which the hollow headed bolts are used, and the threaded bolts *c*, are screwed into the same.

On the under side of each section, adjacent the ends thereof, are reinforcing strips B. Said strips are preferably secured to the section crosswise the board, and beneath the securing bolts, so as to strengthen the section, and especially at the point where it may be weakened by reason of the openings through which the bolts pass.

Having thus particularly described my invention, what I claim as new and desire to secure by Letters Patent, is:—

1. A floor comprising a series of sections adapted to be secured together, each section being formed of a series of boards arranged edge to edge, fastening bolts for securing the boards together in each section, said fastening bolts extending through the outer board at one side of the section, through the intermediate boards, and being threaded into the outer board at the opposite side of said section, threaded bolts passing entirely through one of said sections, and into the adjacent section into which said last named bolts are threaded.

2. A floor comprising a series of sections, adapted to be secured together, each section being formed of a series of boards arranged edge to edge, fastening bolts for securing the boards together in each section, said fastening bolts extending through the outer board at one side of the section, through the intermediate boards, and being threaded into the outer board at the opposite side of said sec-

tion, threaded bolts passing entirely through
one of said sections, and into the adjacent
section, nuts embedded in said adjacent sec-
tion, into which said last named bolts are
5 threaded, and reinforcing strips secured to
the under side of each of said sections, at
points adjacent the securing bolts.

In testimony whereof I affix my signature,
in presence of two witnesses.

JOHN F. MASTERS.

Witnesses:

L. G. COLE,
C. T. THULEVEND.