
W. KRETZMANN.

IRON HEATER AND COVER.

APPLICATION FILED SEPT 15, 1000



## UNITED STATES PATENT OFFICE.

WILLIAM KRETZMANN, OF HARRISON, NEW JERSEY.

## IRON HEATER AND COVER.

951,568.

Specification of Letters Patent.

Patented Mar. 8, 1910.

Application filed September 15, 1908. Serial No. 453,170.

To all whom it may concern:

Be it known that I, WILLIAM KRETZMANN, a citizen of the United States, residing at Harrison, in the county of Hudson and 5 State of New Jersey, have invented certain new and useful Improvements in Iron Heaters and Covers; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will en-10 able others skilled in the art to which it appertains to make and use the same, reference being had to the accompanying drawings, and to figures of reference marked thereon, which form a part of this specifi-15 cation.

This invention relates to a heating attachment for stoves or ranges, and is adapted to provide a plate or platform to fit into the openings of a stove, the edges resting on 20 the edges of the opening and having a depressed portion to fit down into the stove so as to bring the heating surface near to the fire where it will be subjected to a more intense heat than if it were the height of the 25 lids from the fire, or the same heat can be secured by means of a smaller fire when this

depressed structure is used.

The invention also provides a cover to fit over the plate to confine the heat to the de-

30 pressed portion.

A further object of the invention is to furnish a device of this kind, the bottom of which is inclined so that it is adaptable to different sizes of stoves or ranges, in other 35 words in a structure where the fire-brick comes up comparatively near the lids, the higher edge of the bottom portion being placed toward the draft so as not to interfere therewith.

The invention is illustrated in the accom-

panying drawing, in which—

Figure 1 is a longitudinal section of a stove and a plate with its cover. Fig. 2 is a top view of the plate, and Fig. 3 is a section 45 at right angles to Fig. 1, but with the cover removed.

The device is adapted to fit any ordinary make of stove or range 10 and when it is to be used the lids 11, with the center piece 12, 50 are removed and a plate 13 is set down on the stove with its edges 14 bearing on the stove on the edges of the opening therein so as to support the plate and to make a tight fit so as not to hinder the draft. The plate 55 is provided with a depressed portion or well l

formed by the turned down portion of the plate forming ends 15 to which are secured the side pieces 16 and the bottom 17, either by riveting or any other form of securing, and the depth of this depression can be made 60 to suit the wants, and the device can be used for heating sad-irons and also for cooking purposes, and a slower fire can be used than when the lids are employed. This is particularly advantageous in the summer time, 65 when with a small fire the irons can be heated or the food cooked, whereas in the absence of this device enough fire must be built to heat the lids of the stove. This depressed portion of the plate is preferably 70 made so as to bring it over the center of the fire-box 18, the sides of which are formed with the usual fire-brick 19.

I prefer to make the bottom as shown in Fig. 3, that is slanted so that when the fire- 75 brick comes up fairly close to the top of the stove, as in this figure, the short side 20 of the depressed portion is placed toward the outlet of the draft so as not to interfere therewith, but if the fire-box was lower, the 80 device could be turned about as shown in dotted outline in Fig. 3 and no excess draft would be caused. This makes a device adaptable to different sizes of stoves, and there is no danger of cutting off the draft by the in- 85 sertion of this attachment. I can also use this plate in conjunction with a cover 21 which is made preferably oblong to fit the outlines of the depressed portion, and it sets on the top surface of the plate 13 whereby 90 the heat is confined to the depressed portion and the heating is quicker and more thorough than when the device is left open. A handle 22 is suitably placed so that the cover can be removed from the plate. This 95 structure may be cast, but it is preferably made of sheet iron and stamped up into shape, thus making an economical device to manufacture.

Having thus described my invention, what 100 I claim is:—

1. A heating attachment for stoves comprising a plate adapted to have its edge rest on the edges of an opening in a stove, the plate being perforated in its center and hav- 105 ing the material turned down to form the ends of a depressed heating portion, and a strip of metal secured to the plate at its ends and being depressed to form the side pieces and the bottom of the heating portion of 110

which the turned down portions of the plate form the ends.

2. A heating attachment for stoves comprising a plate adapted to have its edge rest 5 on the edges of an opening in a stove, portions of the plate being turned down and having their ends slanted to form the end pieces of a depressed heating portion, and a strip of metal secured to the plate and bent 10 to form a slanted bottom and unequal sides of the heating portion of which the turned down portions of the plate form the ends.

3. A heating attachment for stoves comprising a plate adapted to have its edge rest 15 on the edges of an opening in a stove, portions of the plate being turned down and having their ends slanted to form the end pieces of a depressed heating portion, a strip of metal secured to the plate and bent to 20 form a slanted bottom and unequal sides of the heating portion of which the turned down portions of the plate form the ends, a cover to fit around the edges of the depressed portion and to cover the same to con-

.

fine the heat thereto, and a handle on the 25

cover for its manual manipulation.

4. A heating attachment for stoves comprising a plate adapted to have its edges rest on the edges of an opening in a stove, the plate being perforated in its center and 30 having the metal turned down to form the ends of a depressed heating portion, and a strip of metal secured to the plate at its ends and being depressed to inclose the ends of the depressed heating portion and the 35 edges thereof, the ends of the strip being secured to the side edges of the plate adjacent to the perforation whereby the edges of the perforation are stiffened, and a detachable cover with a handle thereon adapted to fit 40 over and inclose the heating portion.

In testimony, that I claim the foregoing, I have hereunto set my hand this 5th day of

September 1908.

WILLIAM KRETZMANN.

Witnesses: WM. H. CAMFIELD, E. A. Pell.