C. S. WHIPPLE.

RECEPTACLE FOR MATCH BOXES, ASHES, AND THE LIKE. APPLICATION FILED AUG. 12, 1909.

952,160.

Patented Mar. 15, 1910.





FIG. 2



WITNESSES. J. R. Keller F. W. Xay

NITED STATES PATENT OFFICE.

CLYDE S. WHIPPLE, OF PORTLAND, INDIANA, ASSIGNOR TO A. H. HEISEY & CO., INC., A CORPORATION OF WEST VIRGINIA.

RECEPTACLE FOR MATCH-BOXES, ASHES, AND THE LIKE.

952,160.

Patented Mar. 15, 1910. Specification of Letters Patent.

Application filed August 12, 1909. Serial No. 512,588.

To all whom it may concern:

Be it known that I, CLYDE S. WHIPPLE, a resident of Portland, in the county of Jay and State of Indiana, have invented a new 5 and useful Improvement in Receptacles for Match-Boxes, Ashes, and the Like; and I do hereby declare the following to be a full, clear, and exact description thereof.

My invention relates to receptacles for 10 carrying match boxes, ashes and the like. Its object is to provide a neat and durable device of this nature which combines a base portion adapted to hold burned matches, ashes, cigar stubs, with a match safe re-15 movably attached thereto, so that the base portion can be made of ornamental glass or other breakable material, and can be replaced if broken, without the loss of the match safe proper.

set forth and claimed.

In the drawings Figure 1 is a perspective view of a receptacle showing my invention; 25 and Fig. 2 is a vertical section partly broken

off on the line 2—2 Fig. 1.

The base portion or ash receptacle 1 of my device is preferably constructed of glass, which may be suitably ornamented or em-30 bellished. It has the sides 2 which are provided with the top flanges 3. The end portions 4 extend preferably to only part of the height of the sides 2, leaving the openings 5 into which ashes or cigars or ciga-35 rettes can be conveniently put. The flanges 3 also extend preferably only a portion of the length of the sides 2, thus preferably leaving the openings 5 at a convenient angle or slope.

The match safe 7 has the match boxcarrying portion 8 of usual construction, provided preferably with the interior lifting | box and partially eject it, and having a botbox 9 to partially eject the matches from the ordinary safety match box 10 which fits 45 within the portion 8. The base member 6, upon which the match safe proper is fastened, is provided with the grooves or lips 12 formed by the curved overlapping flanges 13, which are constructed to fit the flanges

50 3 of the ash carrying receptacle 1. The match safe proper is constructed pref-

erably of thin sheet metal, and can be slid conveniently onto the receptacle 1, the flanges 13 registering with the correspond-

ing flanges 3 of the receptacle.

I thus provide a neat and convenient device which is adapted to carry the ordinary safety match box of standard size, having means for partially ejecting the matches therefrom, and which at the same time can 60 be used in connection with an ornamental receptacle constructed to carry it and ornamented in any desired manner. The match safe 7 may, moreover, be slid along the flanges 3 so as to leave a wider opening at 65 one end of the ash receptacle, for the reception of additional smoked cigars or the like.

What I claim is:

1. A match carrying receptacle compris- 70 To these ends it consists in the combined | ing a member having substantially vertical construction and improvements hereinafter | side walls, and end walls extending to only part of the height of said side walls and thereby leaving end openings in said member, in combination with a match safe slid- 75 ably attached to said side walls.

2. A match carrying receptacle comprising an ash receiving member having side walls each provided at its top with a longitudinal flange, in combination with a match 80 safe having a bottom portion extending

normally across said walls and thereby leaving an ash chamber beneath it, and being provided with lips adapted to slidably reg-

ister with said flanges.

3. A match carrying receptacle comprising a member having sides each provided with a longitudinal flange at its top and having openings at the ends beyond said flanges, and having an ash receptacle be- 90 tween said sides, in combination with a match safe having means to carry a match tom portion provided with lips adapted to slidably engage said flanges of aforesaid 95 member.

In testimony whereof I, the said CLYDE S. Whipple have hereunto set my hand. CLYDE S. WHIPPLE.

Witnesses:

E. A. OTTMON, RALPH NORPELL.