








J. KRAUS.
CORE BOX.
APPLICATION FILED JULY 7, 1909.

954,442.

Patented Apr. 12, 1910.



Witnesses
Margaret Beigle.
Vernie C. Hess.

Inventor
John Kraus
by H.C. Lord.
Attorney

UNITED STATES PATENT OFFICE.

JOHN KRAUS, OF ERIE, PENNSYLVANIA.

CORE-BOX.

954,442.

Specification of Letters Patent.

Patented Apr. 12, 1910.

Application filed July 7, 1909. Serial No. 506,383.

To all whom it may concern:

Be it known that I, JOHN KRAUS, a citizen of Austria-Hungary, residing at Erie, in the county of Erie and State of Pennsylvania, have invented new and useful Improvements in Core-Boxes, of which the following is a specification.

This invention relates to core boxes and consists in certain improvements in the construction thereof as will be hereinafter fully described and pointed out in the claims.

More particularly, the invention relates to core boxes for forming cores for pipe fittings, and in its preferable form relates to core boxes for forming cores for elbows.

The invention is illustrated in the accompanying drawings as follows:

Figure 1 shows a perspective view of one side of the core box for forming elbows. Fig. 2 a central section of the portion of the core box. Fig. 3 a perspective view of the opposite side of the core box. Fig. 4 an end view of the assembled parts shown in Figs. 1, 2 and 3. Fig. 5 a side view of the core box for forming T's. Fig. 6 a perspective view of the central portion of the core box. Fig. 7 the opposite side of the core box. Fig. 8 an end view of the assembled parts shown in Figs. 5, 6 and 7.

In the preferable construction, 1 marks the central portion of the core box. This is provided with a dowel pin opening 2 into which extends the dowel pins 3 on the sides 4. The central portion has on both sides of it the elbow core cavities 5. Two print cavities 6 extend out of the top of the core box, and the print cavity 7 connects the cavities 5—5 so that in the finished core there are provisions for two elbows which are joined together. The sides have the elbow cavities 8—8 corresponding with the cavities 5—5, and print extensions 9—9 corresponding with the print cavities 6—6, and the cavities 10 corresponding with the cavities 7. In this preferable construction, there are two features of importance. One consists in the connecting of the two elbow cores. By this means, the print portion of the core may be very much reduced,—that is, not only the part formed by the section 10 may be very much less than where the cavities are separate, but also the section formed by

the extensions 7 and 9. This is not only a saving of the pattern area, but also of the sand used. The other feature relates to the assembling of the two sets of cores with a single central portion 1. An operator with this type of core box can fill the two sets with about the same rapidity as is possible to fill a single set, thus increasing his output very materially.

In the alternative construction which is designed for forming T's, the feature of the two sided central piece with the two side pieces is utilized. The central piece is marked 11. It has the T cavity 15 with the print extensions 16 and 17. It is provided with the openings 12 into which the pins 13 on the sides 14 extend. The sides have the core cavities 18 with the print extensions 19 and 20 corresponding with the core cavity 15, and the print extensions 16 and 17 correspond in the central part.

What I claim as new is:

1. A core box for forming cores for pipe fitting elbows; said box being formed in parts, and having two elbow core cavities with a connecting print cavity.

2. A core box for forming cores for pipe fittings, said box being in three parts having a central portion having core cavities on both sides, and side portions having core cavities corresponding with the core cavities in the central portion, said cavities opening at one side of the box when the parts are together, and extending in a direction and in relation to each other to permit the condensing of the sand in the cavities by the same rapping of the box.

3. A core box for forming cores for pipe fitting elbows, said box being formed in three parts, and having two elbow cavities on each side of the central portion, and corresponding cavities on the side portion, said elbow cavities having connecting print cavities.

In testimony whereof I have hereunto set my hand in the presence of two subscribing witnesses.

JOHN KRAUS.

Witnesses:

JOHN S. SCHEER,
FRED. M. COYER.