


H. MIKOREY.  
PAINTING MACHINE.  
APPLICATION FILED JAN. 22, 1908.

955,344.

Patented Apr. 19, 1910.



*Witnesses:*

*Amos Weger.*  
*M. L. Grunberg.*

*Inventor:*

*Hans Mikorey*

# UNITED STATES PATENT OFFICE.

HANS MIKOREY, OF SCHÖNEBERG, NEAR BERLIN, GERMANY, ASSIGNOR TO THE FIRM  
OF MINIMAX CONSOLIDATED LIMITED, OF BERLIN, GERMANY.

## PAINTING-MACHINE.

955,344.

Specification of Letters Patent. Patented Apr. 19, 1910.

Application filed January 22, 1908. Serial No. 412,111.

*To all whom it may concern:*

Be it known that I, HANS MIKOREY, civil engineer, and a subject of the German Emperor, and a resident of 13 Wartburgstrasse, in the city of Schöneberg, near Berlin, Kingdom of Prussia, and German Empire, have invented a certain new and useful Painting-Machine, of which the following is a specification.

10 This invention has reference to a painting machine which can be moved on wheels, and provided with a hand operated air pump.

15 Upon the drawing the machine is illustrated by way of example.

Figure 1 is a side view of the machine; Fig. 2 is a plan view of the same and Fig. 3 is a horizontal section through the container for the painting liquid.

20 In the supporting frame *a*, the paint container *b* is exchangeably mounted. From this container the paint or coloring liquid is discharged at the bottom through the faucet *c* to which a tubing not shown on the  
25 drawing is connected at the end of which a sprayer or the like may be provided. From the container *b* the painting liquid is ejected by pressure. With this end in view compressed air is introduced into the container,  
30 this being done preferably in such a manner, that the compressed air serves at the same time for agitating the painting liquid. This is accomplished by allowing the air admission pipe *d* to reach down to the bot-  
35 tom of the container or near to the bottom, where it terminates by a swirl-like branch *e*. From this branch tube or tubes compressed air is discharged, it passes through the painting liquid, thereby stirring the  
40 same, and collects in the container *b* above the level of the liquid. Inasmuch as the container *b* can be tightly closed by a cover or lid *h*, provided with safety valve *f* and gage pipe *g*, the air which is retained in the  
45 container under pressure, causes the ejection of the paint through the faucet *c*, as soon as the latter is opened.

For the production of the compressed air an air pump *k* is provided which is also  
50 mounted in the supporting frame *a*, and which is actuated by the hand lever *i* and

which is connected by a pipe *m* to the inner air pipe *d* of the container *b*.

The supporting frame *a* is movable, and for this purpose it is provided with the  
55 wheel *n*. This wheel *n* and the supports *c* constitute the supporting points of the machine in the operation of the same. In order to facilitate the movement of the machine, the hand lever *i* of the air pump which is  
60 journaled at *p* in the frame *a*, may be securely connected to the supporting frame *a* by means of a grasping hook *q* engaging with cross bars *r* on the hand lever *i*, the lever serving then as a vehicle pole. A han-  
65 dle *s* provided on the frame *a*, facilitates the handling of the machine, when it is moved about.

What I claim and desire to secure by Letters Patent of the United States is:— 70

1. The combination, in a painting machine, of a closed paint container provided with pressure fluid admitting means leading the pressure fluid to the bottom of said  
75 container and with liquid discharging means arranged in the bottom of said container, with a movable supporting frame, in which the paint container is exchangeably mounted, and a compressing pump mounted in said  
80 supporting frame and connected to the pressure fluid admitting means of the paint container, substantially as described.

2. In a painting machine, the combination of a closed paint container provided with pressure fluid admitting means leading the  
85 pressure fluid to the bottom of said container and with liquid discharging means arranged in the bottom of said container, with a supporting frame movable on wheels and carrying the paint container and a compressing  
90 pump, the hand lever of which is mounted in the said frame, and grasping hooks mounted in the supporting frame and being able to bring the hand lever of the pump in rigid connection with the supporting frame,  
95 substantially as set forth.

In testimony whereof I affix my signature.

HANS MIKOREY.

In the presence of—

WOLDEMÉR HAUPT,  
HENRY HASPER.