
W. SCOTT, DEC'D.

I. & D. J. SCOTT, EXECUTORS.

DELIVERY MECHANISM.


PPLICATION FILED MAR. 6, 1906



W. SCOTT, DEC'D. I. & D. J. SCOTT, EXECUTORS. DELIVERY MECHANISM. APPLICATION FILED MAR. 6, 1905.

956,193.

Patented Apr. 26, 1910.





W. SCOTT, DEC'D. I. & D. J. SCOTT, EXECUTORS. DELIVERY MECHANISM. APPLICATION FILED MAR. 8, 1905.

956,193.

Patented Apr. 26, 1910.

4 SHEETS-SHEET 3.





Walter Scott Inventor By his Attorneys Decken Repaulding

W. SCOTT, DEC'D.


1. & D. J. SCOTT, EXECUTORS.

DELIVERY MECHANISM.

APPLICATION FILED MAR. 6, 1905.

956,193.

Patented Apr. 26, 1910.



UNITED STATES PATENT OFFICE.

WALTER SCOTT, OF PLAINFIELD, NEW JERSEY; ISABELLA SCOTT AND DAVID JOHN SCOTT EXECUTORS OF SAID WALTER SCOTT, DECEASED.

DELIVERY MECHANISM.

956,193.

Specification of Letters Patent. Patented Apr. 26, 1910.

Application filed March 6, 1905. Serial No. 248,589.

To all whom it may concern:

Be it known that I, Walter Scott, a citizen of the United States of America, and a resident of Plainfield, Union county, New 5 Jersey, have invented certain new and useful Improvements in Delivery Mechanisms, of which the following is a specification.

The present invention relates generally to delivery mechanisms for printing or other 10 machines, and has more particular reference to means for delivering the sheet with

the printed side down.

In delivering sheets of paper from a printing machine, a device known as a fly 15 is commonly used. This device acts to turn the sheets over and throws them down quickly on a receiving table forcing the air out underneath and causing the sheets to adhere to each other. This is especially true 20 when a fine quality of work is done, and a considerable amount of ink is used. The result of this adhesion is a smutting of the sheets, and a consequent deterioration in the quality of the work.

The object of the invention is to avoid this and to provide means whereby the sheets will fall gradually and easily upon the delivery board. To this end, it is proposed to interpose an intermediate means between the

30 fly and delivery board which acts to receive the turned sheet from the fly and to drop it onto the delivery board without force, allowing it to settle on the said board by

its own weight.

The structure disclosed in this application is characterized by a fly, a delivery board and a reciprocating sheet delivery mechanism, the latter preferably of a collapsible nature such as the well known collapsible

40 apron, although the invention is not necessarily limited to a construction involving the latter. In order to give as little shock to the sheet as possible, it is preferable that this reciprocating delivery should be in a

45 state of rest with relation to the sheet as it falls from the same. This is accomplished by moving the surface of the delivery in the opposite direction to that of the movement of the mechanism itself, these two motions

50 neutralizing each other. Some time necessarily elapses while the sheet is fed onto the fly, and the driving means for the latter are therefore arranged so that a dwell is given to the fly sufficient to allow the sheet to be

fly and reciprocating delivery must of course be operated in unison and the reciprocating delivery mechanism partakes of this dwell which is imparted to the fly. Preferably the fly and reciprocating delivery mechan- 60 ism are operated from the same cam.

Other features of construction and combinations of parts will appear as the specifica-

tion proceeds.

In the accompanying drawings there is 65 shown a structure embodying the invention in a concrete form, but this structure is not to be construed as an exact limitation of the invention.

In the said drawings: Figure 1 is a side 70 elevation of a machine, embodying the invention. Fig. 2 shows a modification. Fig. 3 is a plan view of the fly shaft and adjacent elements, with parts broken away and in section. Fig. 4 is a transverse vertical sec- 75 tional view through the shaft 6 of Fig. 1. Fig. 5 is a diagrammatic view of the parts showing the fly as having delivered the sheet to the reciprocating member. Fig. 6 is a plan view of a portion of the parts shown 80 in Fig. 2 showing the means for imparting motion to the tapes. Fig. 7 is a transverse vertical sectional detail view through shaft 6 of Fig. 2.

Similar characters of reference indicate 85 corresponding parts in the different views.

1 indicates a framework of a suitable construction properly mounting the parts comprising the machine.

2 is an impression or other cylinder, while 90 3 indicates the fly, 4 the receiving table, and 5 the reciprocating delivery mechanism.

The fly is of any suitable construction and is mounted on the rockshaft 6 carrying the segment 7 operated by means of the rack 8 95 sliding in the guide 9 and receiving its motion from the cam 10 by means of the lever 11 pivoted at 12 and carrying the roll 13. The connection between the lever 11 and rack 8 is effected by means of the rod 14 100 pivoted to the rack at 15 and connected to the lever 11 by means of a slot 16 and pin 17 in a well known manner. This cam 10 is geared with relation to the printing cylinder so as to make one revolution to each 105 two revolutions of the said impression cylinder.

Suitable sheet conveying means are of course interposed between the impression 55 fed properly into position on the same. The cylinder and fly. In the present instance 116

these means take the form of tapes 18 and the guide 19. These tapes pass over suitable rollers as 20 suitably operated from the gear 21 on the impression cylinder. The 5 parts are so arranged that the fly will be slightly below the level of the tapes when in position to receive the sheets. The cam is provided with a dwell in a well known manner so as to allow the sheets to be fed

10 onto the fly.

The reciprocating delivery mechanism consists of a carriage 22 sliding on tracks 23 on the framework by means of the hangers 24 and is provided with the racks 25 mesh-15 ing with the gears 26 on the shaft 27 which latter carries a pinion 28 meshing with the rack 8. The reciprocating carriage further carries a roller 29 on which is wound a collapsible apron 30 whose other end is at-20 tached to the fixed bar 31 and is constructed with a spring tension in a well known manner so as to cause the apron to rewind on the return stroke and to be drawn out on

the forward stroke of the carriage. 25 As the sheet comes from the impression cylinder it passes over the guide 19 and tapes 20 with the printed side up, the fly being

in the position shown in Fig. 1 and being maintained in this position, together with 30 the reciprocating delivery mechanism, by reason of the dwell on the cam 10. The fly now rises and the reciprocating delivery mechanism moves forward drawing out the collapsible apron 30. When the limit of

in dotted lines and in Fig. 5, the apron will be completely drawn out and will receive the overturned sheet from the fly. Upon the return stroke, the fly will rise to move

40 back to its original position and the reciprocating delivery mechanism will return thereby rewinding the apron and withdrawing it from underneath the sheet, thereby allowing the sheet to drop gently onto the receiv-

45 ing board with the printed side down. It will be understood that on this return stroke of the reciprocating delivery mechanism there is a double motion which results in a state of rest of the surface of the apron.

50 This is caused by the fact that the whole device moves bodily backward while the upper surface moves forwardly by reason of

the rewinding of the apron.

In Figs. 2, 6 and 7 there is shown a modi-55 fication which is identical with the foregoing construction except for the reciprocating delivery mechanism. In this instance, there is provided a set of tapes as 33 mounted on rollers 34 on the shafts 35 of the reciprocat-60 ing carriage. One of these shafts 35 is provided with a ratchet 36 mounted fast on the same and carries further a gear 37, loosely mounted, having the pawl 38 engaging with the said ratchet. The gear 37 is in mesh 65 with the stationary rack 39 on the frame-

work so that on the return stroke of the reciprecating carriage, motion will be imparted to the tapes in a forward direction whereby the surface on which the sheet lies will be at rest. If desired, this ratchet and 70 pawl mechanism could be dispensed with and the tapes driven both on the forward and return stroke. In this modification the fly will deposit the sheet on the reciprocating delivery mechanism (that is the tapes) and 75 on the return stroke the sheet will drop down on the delivery board.

The reciprocating delivery mechanism need not partake of the dwell which is imparted to the fly while the sheet is run out 80 over it, but may be driven by a crank movement and may be operated from a separate

cam.

The reciprocating delivery mechanism as shown in the modification may reach back 85 to the impression cylinder and be operated as shown in Patents #594,054 and 673,363 or as shown in Patent #591,223.

In some cases the sheet will run onto the fly by the momentum of the impression cylin- 90 der without the aid of tapes to support the sheet. Likewise, the sheet supporters could be a series of rods or the like with means to crowd off the sheet as shown in Patent

#610,491. What is claimed is:

1. In a printing machine, the combination of a fly, a delivery board, and a reciprocating delivery mechanism adapted to receive 35 this movement is reached as indicated at 32 | the sheet from the fly and to deliver it 100 printed side down to the delivery board.

2. In a printing machine, the combination of a fly, a delivery board, a reciprocating delivery mechanism adapted to receive the sheet from the fly and to deliver it to the 105 delivery board printed side down, and a sheet conveying means for conveying the

sheets to the fly. 3. In a printing machine, the combination of a fly, a delivery board, and a reciprocat- 110 ing delivery mechanism, the fly and delivery mechanism being mounted independent of each other, means for operating the fly and simultaneously therewith the reciprocating delivery mechanism whereby the latter 115 moves forward over the board so as to receive the sheet from the fly, and on its return stroke moves from underneath the sheet and delivers it to the delivery board.

4. In a printing machine, the combination 120 of a fly, a delivery board, and a reciprocating delivery mechanism, the fly and delivery mechanism being relatively stationary with respect to each other, means for operating the fly and simultaneously therewith the re- 125 ciprocating delivery mechanism whereby the latter moves forward over the board so as to receive the sheet from the fly, and on its return stroke moves from underneath the sheet and delivers it to the delivery board, 133

95

956,193 8

and a sheet conveying means for conveying the sheets to the fly.

5. In a printing machine, the combination of a fly, a delivery board, an intermediate 5 means adapted to receive the sheet from the fly printed side down, and means for withdrawing the said intermediate means from underneath the sheet thereby allowing it to

drop onto the delivery board.

10 6. In a printing machine, the combination of a fly, a delivery board, an intermediate means adapted to receive the sheet from the fly printed side down, means for withdrawing the said intermediate means from un-15 derneath the sheet thereby allowing it to drop onto the delivery board, and a sheet conveying means for conveying the sheets to the fly.

7. In a printing machine, the combination 20 of a fly, a reciprocating delivery mechanism adapted to receive sheets from the said fly, the fly being mounted independent of the delivery mechanism, a cam, and means for operating both the fly and reciprocating de-25 livery mechanism simultaneously from the

said cam.

8. In a printing machine, the combination of a fly, a reciprocating delivery mechanism, the fly and delivery mechanism being mount-30 ed independent of each other, means for imparting motion to both simultaneously, and for causing both to dwell while the fly receives the sheet.

9. In a printing machine, the combination 35 of a fly, a reciprocating delivery mechanism adapted to receive sheets from the said fly printed side down, means for imparting motion to both simultaneously, and for causing both to dwell while the fly receives the

40 sheet.

10. In a printing machine, the combination of a fly, a reciprocating delivery mechanism, the fly and delivery mechanism being mounted independent of each other, means 45 for imparting motion to both simultaneously, and for causing both to dwell while the fly receives the sheet, and a sheet conveying means for conveying the sheets to the fly.

11. In a printing machine, the combina-50 tion of a fly, a reciprocating delivery mechanism adapted to receive sheets from the said fly printed side down, means for imparting motion to both simultaneously, and for causing both to dwell while the fly receives the 55 sheet, and a sheet conveying means for con-

veying the sheets to the fly.

12. In a printing machine, the combination of a fly, a reciprocating delivery mechanism, said fly being mounted relatively 60 stationary with respect to the reciprocating delivery mechanism, means for operating the fly and reciprocating the delivery mechanism simultaneously, and means for moving the surface of the delivery mechanism on

which the sheet rests in a direction opposite 65 to that of the direction of movement of the mechanism itself.

13. In a printing machine, the combination of an impression cylinder, a sheet fly, a reciprocating delivery mechanism adapted to 70 receive the sheet from the fly printed side down and deliver it to a delivery board.

14. In a printing machine, the combination of an impression cylinder, a sheet fly, a sheet support to receive the sheet from the 75 fly printed side down, a receiving board and means rolling the support from under the sheet and allowing it to fall on the receiv-

ing board.

15. In a printing machine, the combina- 80 tion of a fly, a receiving board, an intermediate reciprocating sheet support receiving sheets from the fly, and on which the sheet rests without sliding thereon while being delivered to the receiving board the fly being 85 relatively stationary with respect to the reciprocating sheet support.

16. In a printing machine, the combination of a fly, a receiving board, an intermediate sheet support receiving sheets from the 90 fly with the printed side down, and on which the sheet rests without sliding thereon while being delivered to the receiving board.

17. In a printing machine, the combination of a fly, a receiving board, a sheet sup- 95 port on which the sheets are laid by the fly printed side down and remain at rest in the same relation thereto until they are delivered.

18. In a printing machine, the combina- 100 tion of a fly, a receiving board, an intermediate reciprocating sheet support which receives the sheet while at rest and supports the sheet without sliding under it while the sheet is being laid on the receiving board the 105 fly being relatively stationary with respect

to the reciprocating sheet support.

19. In a printing machine, the combination of a fly, a receiving table, a reciprocating sheet support adapted to receive the 110 sheet printed side down while it is at rest and having a roller at its outer end, the upper side of which revolves outwardly at the same speed as the carriage turns backwardly, whereby the sheets are delivered 115 without sliding over the roller said fly and sheet support being relatively stationary with respect to each other.

20. In a printing machine, the combination of a fly, and a reciprocating delivery 120 mechanism adapted to receive the sheet from

the fly printed side down.

21. In a printing machine, the combination of a fly, a reciprocating delivery mechanism adapted to receive the sheet from the 125 fly printed side down, and sheet conveying means for conveying sheets to the fly.

22. In a printing machine, the combina-

tion of a fly, and a collapsible apron adapted to receive the sheet from the fly printed side down.

23. In a printing machine, the combination of a fly, a collapsible apron adapted to receive the sheet from the fly printed side down, and sheet conveying means for conveying sheets to the fly.

24. In a printing machine, the combination of a fly, a delivery board, and a collapsible apron adapted to receive the sheet from the fly printed side down and to de-

liver it to the delivery board.

25. In a printing machine, the combination of a fly, a delivery board, a collapsible apron adapted to receive the sheet from the fly printed side down and to deliver it to the delivery board, and sheet conveying means for conveying sheets to the fly.

26. In a printing machine, the combination of a fly, a delivery board, a reciprocating delivery mechanism adapted to receive the sheet from the fly and to deliver it to the delivery board, the fly being relatively stationary with respect to the reciprocating delivery mechanism, a sheet conveying means for conveying the sheets to the fly, and means for operating the fly and for causing it to dwell while it receives the sheet.

27. In a printing machine, the combina- 30 tion of a fly, a reciprocating delivery mechanism adapted to receive the sheet from the fly, the fly being mounted independent of the delivery mechanism, sheet conveying means for conveying sheets to the fly, and 35 means for operating the fly and for causing it to dwell while it receives the sheet.

28. In a printing machine, the combination of a fly, a collapsible apron adapted to receive the sheet from the fly printed side 40 down, sheet conveying means for conveying sheets to the fly, and means for operating the fly and for causing it to dwell while it

receives the sheet.

29. In a printing machine, the combina- 45 tion of a fly, a delivery board, a collapsible apron adapted to receive the sheet from the fly printed side down and to deliver it to the delivery board, sheet conveying means for conveying sheets to the fly, and means 50 for operating the fly and for causing it to dwell while it receives the sheet.

Signed at New York this 2nd day of

March 1905.

WALTER SCOTT.

Witnesses:

Ivan Konigsberg, Geo. A. Hoffman.