


M. C. PARRISH.

BAG HOLDER.

APPLICATION FILED JAN. 21, 1910.

965,737.

Patented July 26, 1910.



Witnesses

J. H. M. Lee
H. J. Jones & Doyle

Inventor

Minnie C. Parrish.

By E. E. Frooman,
her Attorney.

UNITED STATES PATENT OFFICE.

MINNIE C. PARRISH, OF MONROE, INDIANA.

BAG-HOLDER.

965,737.

Specification of Letters Patent.

Patented July 26, 1910.

Application filed January 21, 1910. Serial No. 539,243.

To all whom it may concern:

Be it known that I, MINNIE C. PARRISH, a citizen of the United States of America, residing at Monroe, in the county of Adams and State of Indiana, have invented certain new and useful Improvements in Bag-Holders, of which the following is a specification, reference being had therein to the accompanying drawing.

This invention relates to holders for bags, strainers and the like, and the principal object of the same being to provide a holder that may be readily attached to an edge of a table, shelf, or the like so that the article supported by the holder may be suspended over the table or shelf.

In carrying out the object of the invention generally stated above it will be understood, of course, that the essential features thereof are necessarily susceptible of changes in details and structural arrangements, one preferred and practical embodiment of which is shown in the accompanying drawings, wherein:—

Figure 1 is a perspective view of the improved holder showing a bag supported thereby. Fig. 2 is a detail view in elevation of one of the suspending hooks that may be associated with the improved holder.

Referring to the accompanying drawing by numerals it will be seen that the improved holder may be formed of a single length of wire that is doubled and twisted to form an upwardly inclined body portion 1 from the lower portion of which the strands diverge at right angles to said body as indicated at 2 and are then abruptly bent downward, as indicated at 2^a thence rearwardly to provide the parallel clamping arms 3. The rear end portions of said jaws are bent downwardly as indicated at 4 and are coiled to provide the springs 5 from which the strands are projected forwardly to provide the clamping arms 6 that are parallel with clamp-arms 3 and have their outer ends connected by the end bar 7. From the upper end of the twisted body 1 one strand is projected upwardly to provide a guide loop 8 and then extended downward to provide a brace arm 9 that has its lower end 10 looped around one of the clamping arms 3. The other strand is bent outwardly from the upper end of body 1 and shaped to provide the annular holder 11 that projects at right angles to body 1, said strand being passed through and crimped in loop 8, and then extended downward to provide a

brace arm 12 whose lower end is looped about the clamping arm 3 opposite to the one to which brace arm 9 is connected.

A plurality of hooks 12^a are attached to holder 11, said hooks having an upper eye 13 that is loosely engaged over said holder so that they may be moved along said holder and also have pivotal movement thereon. A bag 14 has been shown suspended by said hooks.

It will be seen from the foregoing that the improved holder may be readily placed in detachable clamping engagement with a table or the like by means of the described clamping arms, the spring 5 obviously providing the necessary pressure to cause the arms to have a firm engagement.

The device is primarily intended for culinary use and it will therefore be readily understood that the holder 11 is well adapted for use in holding various types of straining vessels as for holding bags.

As thus described, the device may be formed of a single length of wire, and is preferably formed of comparatively heavy wire, but in the event of light wire being used it has been found advisable to employ additional bracing means such as the arms 15 whose upper ends are suitably fastened to opposite outer portions of holder 11, the lower ends thereof being suitably fastened to the divergent portions 2 of the strands adjacent the lower portion of the body 1.

What I claim as my invention is:—

1. A device of the character described comprising a reinforced body portion, upper and lower yieldably clamping arms at the lower end of said body, a holder projecting from the upper end of said body, and bracing means connecting said holder with the upper clamping arms.

2. A bag holder formed of a single length of resilient material shaped to provide a body, a holder at one end of said body, means at the other end for engaging a support, and a brace that connects said holder and said support engaging means.

3. A device of the character described comprising a twisted body, spaced-apart spring-pressed clamping arms at the lower end of said body, an outwardly projecting annular holder at the upper end of said body, and brace arms connecting said holder to one set of said clamping arms.

4. A device of the character described formed of a single length of wire bent upon

itself to provide an upwardly inclined
twisted body, the lower portion of said wire
being shaped to provide upper and lower
clamping arms, a spring connection between
5 the upper and lower arms, said wire having
one portion projected from the upper end
of said body to provide an outwardly pro-
jecting annular holder, and then extended
to and connected to one of said upper
10 clamping arms, the other portion of said
wire being looped over the end of said
holder and then extended down to and con-
nected to the opposite upper clamping arm.
5. A device of the character described

comprising a body, upper and lower resilient
clamping arms at the base thereof, an an-
nular holder projecting at right angles
from the upper end of said body, brace arms
connecting the rear of said holder with the
upper clamping arms, and auxiliary brace
arms connecting forward portions of said
holder with the base of said body. 2

In testimony whereof I hereunto affix my
signature in presence of two witnesses.

MINNIE C. PARRISH.

Witnesses:

M. F. PARRISH,
C. C. RAYL.