

B. J. CAGNOLI.
SAFETY ENVELOP.
APPLICATION FILED AUG. 1, 1908.

968,738.

Patented Aug. 30, 1910.

Fig. 1.




Fig. 2.





Fig. 3.



Attest:
Edw. L. Tolson.
Benjamin Stahl.

Inventor:
Bernardo J. Cagnoli,
by Wm. Wallace White
Attys.

UNITED STATES PATENT OFFICE.

BERNARDO J. CAGNOLI, OF MONTEVIDEO, URUGUAY.

SAFETY-ENVELOP.

968,738.

Specification of Letters Patent.

Patented Aug. 30, 1910.

Application filed August 1, 1908. Serial No. 446,411.

To all whom it may concern:

Be it known that I, BERNARDO J. CAGNOLI, a citizen of the Republic of Argentina, resident of Montevideo, in the Republic of Uruguay, have invented certain new and useful Improvements in Safety-Envelops, of which the following is a description.

My invention relates to an improvement in safety envelops, and the object is to provide devices by which the violation of the envelop is made impossible, if attempted to be opened in the ordinary way;—or the violation immediately and easily detected, should steam or any other means of unsealing the envelop be used.

To make this specification clearer I will describe it in relation to the accompanying drawings:—

Figure 1 is a flat view of the envelop, developed and unsealed. Fig. 2 shows the envelop sealed by three sides, ready to receive the letter, or whatever is to be therein inclosed. Fig. 3 shows the envelop sealed or closed, as will be used in the mails and for general purposes.

F and I are cuts made in the envelop material where a piece of fishglue veneer (*Cola piscis*) is placed. This fish glue H is placed on the outside, and bears an inscription made half in the paper and half in the glue, as is shown in Figs. 2 and 3.

E is a fold which fastens the strips of A, B and C together, as is shown in Fig. 2. G is a similar fold, gummed on both sides, which upon closing the envelop fastens to-

gether D to B and C, as is shown in Fig. 3.

J, K, and L are cuts in the material, which insure more adherence of the mucilage and envelop material.

Of course, paper, linen, or any other material may be used for the manufacture of the envelop, as also the same may be any color, or suitable shape, as desired.

The object of the inscription on the glue is that should steam be used for unsealing the envelop, the inscription would divide and show it.

Having fully described my invention what I claim as new and desire to secure by Letters' Patent is:—

A safety envelop having two end flaps and a top and bottom flap, said top and bottom flaps having folds E G and the end flaps having end extensions, said fold G being gummed on each side, said end flaps overlapping the bottom flap, and the fold E on the bottom flap overlapping the extended ends of said end flaps, and the top flap overlapping the end flaps and the fold G passing upwardly under the extended ends of the end flaps and said fold G being gummed to the bottom flap A and one of the extended ends of the end flaps.

In witness whereof I have hereunto set my hand in presence of two witnesses.

BERNARDO J. CAGNOLI.

Witnesses:

ELLA C. O'HARA,
DOROTEO GARCIA LAGO.