

## J. F. CUMMINGS. MOISTENING DEVICE. APPLICATION FILED OUT. 5, 1910.

982,939.

Patented Jan. 31, 1911.





WITNESSES

Joins R. Heinrichs A. M. Launer. John F. Cummings

334

Attorney

## UNITED STATES PATENT OFFICE.

JOHN F. CUMMINGS, OF PROVIDENCE, RHODE ISLAND.

MOISTENING DEVICE.

982,939.

Specification of Letters Patent.

Patented Jan. 31, 1911.

Application filed October 5, 1910. Serial No. 585,479.

To all whom it may concern:

Be it known that I, John F. Cummings, a citizen of the United States, residing at Providence, in the county of Providence and 5 State of Rhode Island, have invented certain new and useful Improvements in Moistening Devices, of which the following is a specification.

This invention relates to devices for mois-10 tening envelops and mail matter for the purpose of affixing postage stamps, and one of the principal objects of the invention is to provide a moistening device actuated by gravity to apply moisture to the upper sur-15 face of an envelop prior to the affixing of a

stamp thereto.

Another object of the invention is to provide a water container provided with an absorbent element extending through a tube 20 and through a moistener casing to apply moisture to the surface of an envelop, said water container being pivotally mounted upon a table or support for the envelop and the weight of the container serving to hold 25 the moistening element down upon the surface of the envelop as it is fed underneath the same on the table.

My present invention is designed to be used in connection with a stamp affixing ma-

30 chine of suitable construction.

The objects and advantages above referred to may be attained by means of the construction illustrated in the accompanying

drawing, in which,

Figure 1 is a perspective view of a moistening device made in accordance with my invention. Fig. 2 is a vertical section taken through the container, the tube leading therethrough and the moistener casing ex-

tended from the tube.

Referring to the drawing the numeral 1 designates a table properly supported upon the frame 2 of the stamp affixing machine, said table having a graduated scale 3 thereonto which the envelop or printed matter is moved in the moistening operation. A hollow water container 4 preferably but not necessarily of circular form is provided with a bearing lug 5 in which a perforation 6 is for for the reception of a pivot pin 7, said pin being secured in a lug 8 projecting from the table 1. A tube 9 communicates with the interior of the water container and extending at an angle to said tube 9 is a cas-55 ing 10 of a width slightly greater than a postage stamp. The casing 10 is provided

with a removable cover 11 secured in place by means of a set screw 12. The casing 10 is provided with sides 13, each having an enlargement 14 at its outer end. A feeding 60 device consisting of an absorbent element 15 extends from the water container through the tube 9 and through the moistener casing, said element having an enlarged contact end 16 adapted to normally lie on top of the table 65 owing to the superior weight of the moistener casing relatively to the water container. To adjust the bearing of the end 16 upon the table 1 a set screw 17 is secured in the frame 2 and may be turned to bear 70 against the projecting portion 18 of the moistener casing. A stopper 19 is fitted in a nozzle 20 in the water container to provide means whereby the container may be readily refilled whenever required.

The operation of my invention may be briefly described as follows: An envelop or other mail package is pushed underneath the end 16 of the moistening element and up to the scale 3, said envelop or mail package be- 80 ing moistened on its upper right hand corner in position to receive a stamp to be applied by the stamp affixing machine. In many pieces of mail matter it is necessary to affix two or more postage stamps, depending 85 upon the weight of the envelop or package. Provision is made for this contingency by the use of the graduated scale 3. The envelop or other piece of mail matter is pushed under the moistener until the end of the en- 90 velop registers with the first mark. If another stamp is to be applied the envelop is moved to the second mark and so on for any

number of stamps required.

From the foregoing it will be obvious that 95 a moistening device made in accordance with my invention will quickly moisten the surface of an envelop or other mail package, that the invention is simple in construction, cannot readily get out of order, can be ad- 100 justed for any required thickness of mail packages or envelops and can be produced at low cost.

I claim:

1. A device for moistening the surface of 105 envelops preparatory to affixing stamps thereto comprising a table, a water container pivotally connected to the table, a tube extending from the water container, a moistener casing communicating with the 110 tube, and an absorbent element extending from the casing through the tube and mois-

tener casing, said water container being pivoted at one side of its center whereby the contact end of said absorbent element will bear upon the surface of an envelop resting

5 upon the table.

2. A moistening device for moistening the surface of envelops or mail matter preparatory to affixing stamps thereto comprising a table having a stop, a moistener pivotally 10 mounted upon the table and adapted by gravity to hold a moistening element down upon the surface of the mail matter, and an adjustable stop for limiting the pivotal movement of the moistener.

3. A moistener for mail matter comprising a table having a stop thereon, a water i

container pivoted to the table, a tube extending from the container, a moistener casing extending from the tube and provided with a detachable cover, a moistening element ex- 20 tending from the container through the tube and casing, and provided with a contact end for applying moisture to the surface of the mail matter, and an adjustable stop for limiting the pivotal movement of the water con- 25 tainer.

In testimony whereof I affix my signature

in presence of two witnesses.

JOHN F. CUMMINGS.

Witnesses: JOHN L. FLETCHER, M. R. Mullen.