
W. N. JAY.


WRENCH.


APPLICATION FILED APR. 21, 1910.

983,447.

Patented Feb. 7, 1911.







Witnesses

Hebert Lawson

Milliam N. Jay,

Inventor

by Cachow to

Attornevs

UNITED STATES PATENT OFFICE.

WILLIAM N. JAY, OF MOSCOW, IDAHO.

WRENCH.

983,447.

Specification of Letters Patent.

Patented Feb. 7, 1911.

Application filed April 21, 1910. Serial No. 556,815.

To all whom it may concern:

Be it known that I, William N. Jay, a citizen of the United States, residing at slide 7 and said slide can therefore be Moscow, in the county of Latah and State | moved to shift jaw 9 toward or away from 5 of Idaho, have invented a new and useful | jaw 1. When the desired adjustment has 55 Wrench, of which the following is a specification.

This invention relates to wrenches and one of its objects is to provide a simple and 10 durable tool of this type which can be quickly adjusted to fit any size nut.

Another object is to provide novel means for locking the movable jaw in adjusted position.

With these and other objects in view the invention consists of certain novel details of construction and combinations of parts hereinafter more fully described and pointed out in the claims.

20 In the accompanying drawings forming part of this specification the preferred form of the invention has been shown.

In said drawings:—Figure 1 is a side elevation of the wrench. Fig. 2 is a longitu-25 dinal section therethrough. Fig. 3 is a section on line A—B Fig. 1.

Referring to the figures by characters of reference 1 designates the fixed jaw of the wrench the same being formed at one end 30 of a shank 2 there being transverse shoulders formed by the jaw as shown at 3, these shoulders constituting guides. A rib 4 is formed on one side of the shank 2 and close to and parallel with a shoulder 3. Screw 35 threads 5 are located upon the shank for a short distance and are adapted to be engaged by a nut 6 which may be circular as shown.

An elongated tapered slide 7 extends 40 transversely of and surrounds the shank, this slide bearing against the shoulders 3 and having a slot 8 for the reception of the rib 4. A movable jaw 9 extends from the slide and is similar to the jaw 1. Teeth 10 45 are formed on one face of the slide and are adapted to be engaged by similar teeth 11 formed on a wedge block 12 which is loosely mounted on the shank and between slide 7 and nut 6.

The operation of the wrench will be ob-

vious. By loosening nut 6 the teeth on wedge 12 will become disengaged from the been effected the movable jaw can be locked by screwing nut 6 against wedge 12. Said wedge will thus be clamped in engagement with the slide and hold it against displacement.

Importance is attached to the fact that the wrench can be quickly adjusted and set, only a very slight turn of the nut being necessary in either case.

Various changes can of course be made in 65 the construction and arrangement of the parts without departing from the spirit or sacrificing any of the advantages of the invention as defined in the appended claims.

What is claimed is:—

1. A wrench including a fixed jaw, a shank extending therefrom, a slide surrounding and movable transversely of the shank, a jaw upon the slide, a locking block movable longitudinally of the shank and 75 means adjustably engaging the shank for binding the block upon the slide.

2. A wrench including a fixed jaw, a shank extending therefrom, a locking block movable longitudinally of the shank, a wedge 80 shaped slide interposed between the block and the fixed jaw, a jaw extending from the small end of the slide, and means adjustably engaging the shank for binding the block upon the slide.

3. A wrench including a shank, a fixed jaw thereon, a locking block, a tapered sleeve interposed between the fixed jaw and block and shiftable transversely of the shank, a jaw upon the small end of the 90 sleeve, and means adjustably mounted on the shank for clamping the sleeve between the block and fixed jaw.

In testimony that I claim the foregoing as my own, I have hereto affixed my signa- 95 ture in the presence of two witnesses.

WILLIAM N. JAY.

Witnesses:

WM. HUNTER, HALSEY H. ORLAND.