

A. J. KETELSEN.  
GARMENT HANGER AND STRETCHER.  
APPLICATION FILED JUNE 14, 1910.

998,530.

Patented July 18, 1911.

2 SHEETS—SHEET 1.






Fig. 5.



Witnesses

*C. Everett Lancaster*  
*H. J. Woodruff*

Inventor  
Andrew J. Ketelsen




By *E. C. Hoorman,*  
his Attorney.

A. J. KETELSEN.  
GARMENT HANGER AND STRETCHER.  
APPLICATION FILED JUNE 14, 1910.

998,530.

Patented July 18, 1911.

2 SHEETS—SHEET 2.



Witnesses

Everett Lancaster  
H. Joseph Doyle

Inventor

Andrew J. Ketelsen

By

E. O. Vrooman,  
his Attorney.



# UNITED STATES PATENT OFFICE.

ANDREW J. KETELSEN, OF CHICAGO, ILLINOIS.

GARMENT HANGER AND STRETCHER.

998,530.

Specification of Letters Patent.

Patented July 18, 1911.

Application filed June 14, 1910. Serial No. 566,852.

*To all whom it may concern:*

Be it known that I, ANDREW J. KETELSEN, a citizen of the United States of America, residing at Chicago, in the county of Cook and State of Illinois, have invented certain new and useful Improvements in Garment Hangers and Stretchers, of which the following is a specification, reference being had therein to the accompanying drawing.

10 This invention relates to suit hangers for preserving the shape of coats, vests and trousers, and the principal object of the same is to provide the hanger with means whereby it may be expanded to stretch trousers, or  
15 adjusted to the length of the trousers to be placed therein, means being provided for locking the same in an adjusted position, and means also being provided to lock the hanger in a contracted position so that when the  
20 trousers stretching portion is not in use or the hanger not in use, but a small amount of storage space will be required.

In carrying out the objects of the invention generally stated above it will be understood, of course, that the essential features thereof are necessarily susceptible of changes in details and structural arrangements, one preferred and practical embodiment of which is shown in the accompanying drawings, wherein:—

30 Figure 1 is a perspective view of the improved hanger as it appears in use. Fig. 2 is a view in rear elevation showing the hanger contracted. Fig. 3 is a similar view  
35 of the rear of the hanger. Fig. 4 is a top plan view. Fig. 5 is a central vertical sectional view taken on the line 5—5, Fig. 2. Fig. 6 is a detail perspective view of the locking arm carried by the upper portion of  
40 the hanger.

Referring to the accompanying drawings by numerals, 1 designates the head of the improved hanger the upper edge of which is curved and provided with a flat strip 2 that  
45 overhangs the front and rear of said head. A suspending hook 3 is pivotally connected to the central portion of the front of said head and said strip 2 is provided with a central slot 4 through which said hook projects when rocked in position to engage a support 5. A clamping lever 6 has one end  
50 pivotally connected to one end of head 1, the other end of said lever being adapted to be engaged by a catch 7 pivotally mounted at the opposite end of said head. A locking  
55 arm 8 has one end pivotally connected to the

rear face of head 1, the free end of said arm provided with a laterally projecting lug 9.

The base of the hanger is composed of a horizontal bar 10 one end of which is provided with an offset abutment 11. A clamping lever 12 has one end pivotally connected to one end of bar 10, the other end of said lever adapted to be fitted behind the inner end of said abutment 11. A ring 13 carried  
60 by bar 10 slides over lever 12 to retain said bar 10 and lever 12 in clamping relation.

Head 1 and base bar 10 are connected by a system of toggle levers 14 which obviously permits relative adjustments of said bar and  
70 head. The upper members of said toggle levers are each provided with an opening 15 and when said openings are in alinement, the lug 9 of arm 8 may be engaged therewith to lock the hanger in an expanded position.  
75 The base members of the toggles are provided with similar openings 16 which aline when the hanger is contracted so that they may be engaged by lug 9 to lock the hanger in a contracted position as shown in Fig. 2.  
80 The said base members of the toggle levers 14 at their point of pivotal connection with the toggle, each carry a locking arm. Said arms are designated by the numerals 17 and 18. Arm 17 is provided with a laterally  
85 projecting lug 19, and arm 18 is provided with a longitudinal row of transverse openings 21 adapted to be selectively engaged by lug 19 to prevent the toggle being collapsed.

From the foregoing description, it will be  
90 seen that when the toggle is fully expanded, openings 15 are in alinement so that the end lug 9 of arm 8 can be engaged with said openings to lock the toggle in such position. When contracted, openings 16 are in aline-  
95 ment so that the said lug 9 can be engaged therewith to lock the toggle in its contracted position. It will also be seen that the arms 17 and 18, through the lug 19 and openings 21, permit the toggle to be locked in ad-  
100 justed positions.

What I claim as my invention is:—

1. A garment hanger and stretcher comprising a head provided with suspending means, trousers clamping means carried by  
105 said head, a base, trousers clamping means carried thereby, a toggle connection between said head and base, the upper and lower members of said toggle provided with openings, and a locking arm pivoted to said head  
110 and provided with a lug adapted to engage the opening of the upper members to retain



the toggle expanded and the openings of the lower members to retain the toggle contracted.

2. A garment hanger comprising a head, a  
5 base, a toggle connection therebetween, said  
toggle provided with sets of openings, the  
openings of one set being in alinement when  
the toggle is contracted and the openings of  
the other set being in alinement when the  
10 toggle is expanded, means for selectively en-  
gaging said alined openings to lock the tog-  
gle in extreme expanded and contracted posi-  
tion, and a pair of oppositely-disposed arms

carried by the toggle, one of said arms pro-  
vided with a row of openings, the other arm 15  
provided with a lug for selectively engaging  
said openings to lock the toggle in positions  
intermediate the extreme expanded and con-  
tracted position.

In testimony whereof I hereunto affix my 20  
signature in presence of two witnesses.

ANDREW J. KETELSEN.

Witnesses:

JOHN F. SCHMITT,

PHILIP BESELER.

Copies of this patent may be obtained for five cents each, by addressing the "Commissioner of Patents,  
Washington, D. C."