
## S. FRIEDMAN.


SNOW MELTING MACHINE AND METHOD OF OPERATING SAME.

APPLICATION FILED JAN. 12, 1911.

999,445.

Patented Aug. 1, 1911.





## STATES PATENT

SAMUEL FRIEDMAN, OF NEW YORK, N. Y.

SNOW-MELTING MACHINE AND METHOD OF OPERATING SAME.

999,445.

Specification of Letters Patent.

Patented Aug. 1, 1911.

Application filed January 12, 1911. Serial No. 602,181.

To all whom it may concern:

Be it known that I, Samuel Friedman, a citizen of the United States, and a resident of New York, in the county of New York 5 and State of New York, have invented certain new and useful Improvements in Snow-Melting Machines and Methods of Operating Same, of which the following is a

specification.

My invention relates to improvements in snow melting machines, and to an improved method of operating said machines, and the objects of the invention are to improve upon the construction of snow melting or snow 15 removing machines and the method of operating the same so that the snow or ice can readily be removed from the streets of cities and converted into a slush which can easily be removed from the machine at a very small 20 expense.

To the accomplishment of the above objects, and to such others as may hereinafter appear, the invention comprises means for feeding snow, ice and the like to a tank 25 which is arranged to receive from another tank water containing a small percentage of salt or similar substance which will convert the snow or ice into a slush and prevent the snow or ice as it mixes with the water in 30 the tank from adhering together to form lumps which are difficult to melt or to con-

moved.

I will now proceed to describe my inven-35 tion with reference to the accompanying drawings, and will then point out the novel features in claims.

vert into a slush so that the same can be re-

In the drawings: Figure 1 shows more or less diagrammatically a longitudinal verti-40 cal section of a machine embodying my invention. Fig. 2 shows a plan view of the

machine partly in section.

In the drawings 1 designates the receiving tank and 2 a chute having within it a 45 conveyer 3 for sweeping snow, ice or the like from the street into the chute and thence conveying same up the chute to the tank 1, which is arranged to hold a quantity of snow or ice dumped by the conveyer. From 50 experience it has been found that it is very difficult to turn the snow into water by means of heat alone, and it is also practically impossible to convert the snow or ice into a slush by dumping the snow or ice into water; 55 but I have found that if the snow or ice is sprayed with water which contains a small l

percentage of salt or analogous substance, the snow or ice sprayed with salt water will readily turn into slush and will not adhere together and form lumps as is the case when 60

water without salt is used.

In order to supply a suitable amount of salt water to the receiving tank, a spraying tank 4 is provided, which is situated in the top of the receiving tank 1, as clearly shown 65 in Fig. 1. The tank 4 is provided in the present instance with two outlets at the bottom which are designated 5 and 6, through which the salt solution contained in the tank 4 is sprayed into the receiving tank 1 so as 70 to come in contact with the snow or ice, which is dumped into the receiving tank by the conveyer, and turn the same into slush. In the present instance, the outlet 5 is provided with a universal connection so that the 75 outlet can be moved in different directions, a rod 7 being provided for controlling the movements of the same. The outlets are also provided with suitable controlling valves 8 operated through the medium of 80 suitable levers 9 and 10 by means of which the flow of the solution through the valves can be regulated. In the present instance the upper part of the spraying tank 4 is provided with a supply box 11 which is pro- 85 vided with a door 12, and is adapted to hold salt or other analogous substance 13 which in the present instance is made in the form of small blocks or bricks, which permit of the same being readily removed and inserted 90 in the tank 4 through the door 14 when it is desired to increase the strength of the liquid in the spraying tank 4.

The conveyer 3 used for delivering snow or ice to tank 1, in the present instance 95 comprises a plurality of plates 15 secured to an endless link chain or belt 16 the same being driven by means of an endless chain or belt 25. At its lower end, the chute 3 is provided with a plow 17 adapted to scrape 100 up snow, ice, etc., from the street so that the same can be engaged by the plates 15 of the conveyer as shown in Fig. 1. In the present instance the plow consists of a flat plate which is pivoted at its upper edge to 105 the end of the chute 2 by means of a suitable hinge 18, the plow being held in a vertical position by means of spring 19 connected to the same through the medium of the levers 20 and 21 which are pivoted to- 110 gether at 22 as shown in Fig. 1. From the above it will be seen that if the plow 17

meets an obstruction such as a car track or the like the plow will be forced backward against the action of the spring 19 until the obstruction has been passed whereupon the 5 plow will be returned to its original position.

From the above it will be seen that as the machine is moved along the street by any suitable means, the conveyer will elevate the 10 snow or ice to the tank 1, whereupon the person operating the spraying tank will permit the salt solution to be sprayed upon the snow or ice in the receiving tank and converts the same into a slush, it being cus-15 tomary for the operator who stands upon the stand 30 to stir the slush from time to time by means of a suitable tool which can be inserted through the door 31. When the tank is filled with slush the door 26 at the 20 back of the tank is opened and the slush permitted to run out, after which the door is closed and the tank again filled with snow or ice which is converted into slush as before described. If desired, the tank 1 <sup>25</sup> can be heated, suitable means 27 being provided for this purpose, but ordinarily I prefer to operate the machine without the addition of heat.

While the invention has been described 30 with particular reference to the details of construction and operation, the same is not-

to be considered as limited thereto, as many changes may be made and still fall within the scope of the following claims.

What I claim is:—

1. A snow removing apparatus comprising in combination a receiving tank, a chute, and means in said chute for conveying snow to said tank, a plow secured to the end of said chute, and spring acting means secured 40 to said plow to permit the same to pass obstructions, as and for the purposes set forth.

2. A snow removing apparatus comprising in combination a receiving tank, a chute, means in said chute for conveying snow to 45 said tank, another tank arranged in proximity to said receiving tank, arranged to hold a salt solution, and means for delivering said solution to the receiving tank, as and for the purposes set forth.

3. A method of converting snow into slush, which consists in imparting heat to the said snow and also adding salt thereto, and thereby preventing the formation of caked masses of snow.

In testimony whereof I have signed this specification in the presence of two subscribing witnesses.

SAMUEL FRIEDMAN.

Witnesses:

LEO J. MATTY, D. A. DAVIES.