



US010010738B2

(12) **United States Patent**
Gerschefske et al.

(10) **Patent No.:** **US 10,010,738 B2**
(45) **Date of Patent:** ***Jul. 3, 2018**

(54) **EXERCISE APPARATUS WITH RESILIENT FOOT SUPPORT**

(71) Applicant: **STAMINA PRODUCTS, INC.**,
Springfield, MO (US)

(72) Inventors: **Kevin Gerschefske**, Springfield, MO
(US); **Jack S. Barufka**, Reston, VA
(US)

(73) Assignee: **STAMINA PRODUCTS, INC.**,
Springfield, MO (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 111 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/035,473**

(22) Filed: **Sep. 24, 2013**

(65) **Prior Publication Data**

US 2014/0024509 A1 Jan. 23, 2014

Related U.S. Application Data

(60) Division of application No. 12/829,203, filed on Jul.
1, 2010, now Pat. No. 8,562,492, which is a
(Continued)

(51) **Int. Cl.**
A63B 21/068 (2006.01)
A63B 21/04 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **A63B 21/04** (2013.01); **A63B 5/00**
(2013.01); **A63B 5/11** (2013.01); **A63B 21/02**
(2013.01);

(Continued)

(58) **Field of Classification Search**
USPC 482/72, 77, 95, 96, 111, 121, 142
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

339,638 A 4/1886 Goldie
1,996,350 A * 4/1935 Schaff 482/96

(Continued)

OTHER PUBLICATIONS

Extended European Search Report, including the Search Opinion, as
issued for European Patent Application No. 11164238.5, dated Jul.
3, 2012.

(Continued)

Primary Examiner — Andrew S Lo


Assistant Examiner — Shila Jalalzadeh Abyan

(74) *Attorney, Agent, or Firm* — Pillsbury Winthrop Shaw
Pittman, LLP

(57) **ABSTRACT**

An exerciser including a movable body carriage mounted on
an exerciser frame for movement along tracks provided by
the frame. A resilient foot engaging assembly extends from
the exerciser frame. The resilient foot engaging assembly is
adapted to be engaged by the user's feet to absorb the energy
of movement in a first direction and to provide the user with
a bouncing movement, which the user may translate into a
movement of the movable body carriage in the opposite
direction. The resilient foot engaging assembly may be
provided as an attachment and retrofitted to existing exer-
cisers. The resilient foot engaging assembly includes a unit
mounting frame assembly and an independent usable exer-
cising unit, such as an inflated dome or trampoline unit,
removably secured thereon. The exerciser may include a
resilient resistance system coupled to the movable body
carriage and a set of pull lines with user grips trained over
pulleys carried by the exerciser frame. Also disclosed are
methods for enabling users to exercise in either one of two
different modes.

25 Claims, 21 Drawing Sheets



Related U.S. Application Data

continuation of application No. 11/702,672, filed on Feb. 6, 2007, now Pat. No. 7,806,805, and a continuation of application No. 11/592,139, filed on Nov. 3, 2006, now Pat. No. 7,771,328, said application No. 11/702,672 is a continuation-in-part of application No. 10/693,443, filed on Oct. 27, 2003, now Pat. No. 7,179,207, said application No. 11/592,139 is a continuation of application No. 10/693,443.

(51) **Int. Cl.**

- A63B 5/00* (2006.01)
- A63B 5/11* (2006.01)
- A63B 21/055* (2006.01)
- A63B 23/04* (2006.01)
- A63B 21/00* (2006.01)
- A63B 21/02* (2006.01)
- A63B 22/00* (2006.01)
- A63B 23/035* (2006.01)

(52) **U.S. Cl.**

- CPC *A63B 21/055* (2013.01); *A63B 21/068* (2013.01); *A63B 22/0087* (2013.01); *A63B 23/0405* (2013.01); *A63B 21/00065* (2013.01); *A63B 21/023* (2013.01); *A63B 21/0428* (2013.01); *A63B 21/0442* (2013.01); *A63B 21/0557* (2013.01); *A63B 22/0023* (2013.01); *A63B 23/0355* (2013.01); *A63B 23/03575* (2013.01); *A63B 2208/0252* (2013.01); *A63B 2208/0257* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

3,256,021	A	6/1966	Nissen et al.	
3,394,934	A	7/1968	Petros et al.	
3,770,267	A	11/1973	McCarthy	
3,837,643	A *	9/1974	Lee	A63B 5/11 482/29
4,077,623	A	3/1978	Clausell	
4,272,074	A	6/1981	Sferle	
4,340,216	A *	7/1982	Murphy	A61H 3/008 105/150
4,468,025	A	8/1984	Sferle	
4,477,070	A	10/1984	Appelbaum	
4,564,193	A *	1/1986	Stewart	A63B 17/00 482/102
4,685,669	A	8/1987	DeCloux	
4,700,946	A	10/1987	Breunig	
4,706,953	A	11/1987	Graham	
4,722,520	A	2/1988	Lee	
4,730,826	A *	3/1988	Sudmeier	A63B 5/11 482/28
4,796,882	A	1/1989	Jiumr	
4,828,255	A	5/1989	Lahman	
4,836,530	A	6/1989	Stanley, Jr.	
4,884,802	A	12/1989	Graham	
4,911,438	A	3/1990	Van Straaten	
4,928,957	A	5/1990	Lanier et al.	
4,974,840	A	12/1990	Welch	
5,066,005	A *	11/1991	Luecke	A63B 21/4029 482/130
5,017,115	A	12/1991	Welch	
5,071,115	A	12/1991	Welch	

5,160,305	A	11/1992	Lin	
5,169,363	A	12/1992	Campanaro et al.	
5,215,511	A	6/1993	Cheng	
5,312,315	A	5/1994	Mortensen et al.	
5,338,278	A	8/1994	Endelman	
5,364,327	A	11/1994	Graham	
5,385,518	A	1/1995	Turner	
5,445,583	A	8/1995	Habing	
D362,700	S	9/1995	Breibart et al.	
5,451,093	A *	9/1995	Petrie et al.	297/137
5,620,403	A	4/1997	Lundin	
5,622,527	A	4/1997	Watterson et al.	
5,634,870	A	6/1997	Wilkinson	
D382,319	S	8/1997	Gerschefske et al.	
5,788,606	A *	8/1998	Rich	482/27
5,792,033	A	8/1998	Merrithew	
5,897,459	A	4/1999	Habing et al.	
5,938,571	A *	8/1999	Stevens	482/96
5,967,955	A *	10/1999	Westfall et al.	482/142
6,010,434	A	1/2000	Hodges	
6,042,523	A	3/2000	Graham	
6,135,922	A	10/2000	Nissen	
6,162,061	A *	12/2000	Taylor	434/253
6,186,929	B1	2/2001	Endelman et al.	
6,206,809	B1	3/2001	Habing et al.	
6,280,367	B1	8/2001	Arsenault	
6,338,704	B1	1/2002	Endelman	
6,371,895	B1	4/2002	Endelman et al.	
6,422,983	B1	7/2002	Weck	
6,500,099	B1	12/2002	Eschenbach	
6,527,685	B2	3/2003	Endelman et al.	
6,547,701	B1	4/2003	Eschenbach	
6,551,219	B1	4/2003	Brown	
6,702,726	B2	3/2004	Lin	
6,752,745	B1	6/2004	Davis	
6,767,314	B2	7/2004	Thompson	
6,872,175	B2 *	3/2005	Lin	482/146
7,115,077	B2	10/2006	Yang	
7,163,498	B1 *	1/2007	Abelbeck	A63B 21/4049 482/142

7,179,207	B2	2/2007	Gerschefske	
7,381,172	B1	6/2008	Gehrke	
7,637,854	B2	12/2009	Jang	
7,682,297	B2	3/2010	Graham	
7,771,328	B2	8/2010	Gerschefske	
7,806,805	B2	10/2010	Barufka et al.	
7,967,736	B2	6/2011	D'Silva et al.	
2002/0058573	A1	5/2002	Endelman et al.	
2002/0183172	A1	12/2002	Chen	
2003/0125163	A1 *	7/2003	Plante	482/27
2003/0199372	A1	10/2003	Robinson et al.	
2004/0058781	A1	3/2004	Plante	
2004/0077464	A1	4/2004	Feldman et al.	
2004/0192522	A1	9/2004	Hippensteel	
2004/0209738	A1	10/2004	Crawford et al.	
2005/0202943	A1	9/2005	Branch et al.	
2005/0272566	A1	12/2005	Otsuka	
2006/0094573	A1	5/2006	Weck	
2007/0111866	A1	5/2007	McVay	
2008/0318738	A1	12/2008	Chen	
2009/0105046	A1	4/2009	Rudich	
2009/0181834	A1	7/2009	Campanaro et al.	

OTHER PUBLICATIONS

The Merriam Webster Dictionary, <http://www.merriam-webster.com/dictionary/snap?show=1&t?1293826366>, definition of "snap".

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6A




Fig. 6B




Fig. 6C




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23

EXERCISE APPARATUS WITH RESILIENT FOOT SUPPORT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a divisional of U.S. application Ser. No. 12/829,203, filed Jul. 1, 2010, which is a continuation of U.S. application Ser. No. 11/702,672, filed Feb. 6, 2007, now U.S. Pat. No. 7,806,805, and Ser. No. 11/592,139, filed Nov. 3, 2006, now U.S. Pat. No. 7,771,328. U.S. application Ser. No. 11/702,672 is a continuation-in-part of U.S. application Ser. No. 10/693,443, filed Oct. 27, 2003, now U.S. Pat. No. 7,179,207. U.S. application Ser. No. 11/592,139 is a continuation of U.S. application Ser. No. 10/693,443, filed Oct. 27, 2003, now U.S. Pat. No. 7,179,207, which in turn claims priority to U.S. Application No. 60/440,610, filed Jan. 17, 2003. The present application claims priority to all of the above applications. The entire content of each of the above applications is hereby incorporated by reference into the present specification.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to methods of exercising and to exercise apparatuses with resilient foot supports for carrying out those methods.

Description of Related Art

One of the consistent challenges in the fitness industry is devising exercise methods and apparatuses that allow the user to achieve maximum, diverse fitness effects by performing exercises in comfortable positions. For example, a type or set of exercises may be particularly attractive and beneficial to the user if it provides strengthening, toning and cardiovascular benefits. Exercise equipment used to perform fitness exercises should ideally be relatively simple in construction, flexible in the types of exercises allowed, and adaptable to a wide range of resistances and levels of exertion.

A popular type of exercise equipment provides a pair of generally parallel tracks, on which a carriage is mounted for sliding or rolling movement along the tracks. Depending on the particular variation, the carriage may be connected to a resistance system including one or more resilient members, such as springs or bungee cords, which bias the carriage towards a particular position. The carriage may also be connected to pull lines that are trained over a pulley system, allowing the user to move the carriage by pulling the pull lines. The user exercises with such an apparatus by using the arms or legs to move the carriage along the tracks.

Sliding-carriage multi-function exercise equipment of this type also typically includes a foot rest or foot bar which extends in a direction generally perpendicular to the rails. The foot rest or foot bar is operationally fixed in position, and allows a user to control the movement of the carriage by exerting his or her leg muscles against it. A foot rest typically includes a set of frame members or frame portions that are adapted to connect to either the rails of the apparatus or other appropriate structures provided for that purpose. The frame members may also be attached to a rigid member, such as a board. The board is typically covered with a layer of foam or other cushioning material, which may be enclosed in a layer of outer material, such as vinyl. The foam and outer material cushion the user's feet to some degree and provide traction.

Rather than a board, the rigid member may comprise a generally U-shaped foot bar, which is typically a hollow bar that is adapted to be connected to the exercise apparatus at its ends. The top portion of the foot bar is covered with a traction/cushioning material. The user typically places his or her hands or feet on the cushioned portion of the foot bar to control the movement of the carriage.

One variation of the above-described type of exercise apparatus is disclosed in U.S. Pat. No. 5,967,955, which is incorporated herein by reference in its entirety. The disclosed apparatus includes a movable carriage mounted on generally parallel tracks and a foot rest of the type described above. The apparatus does not use resilient members to provide resistance; instead, resistive bias is provided by inclining the tracks at one of a number of angular orientations, thereby allowing the user to move the carriage by working against a corresponding fraction of his or her own weight bias under the influence of gravity using a pulley system that is coupled to the carriage. As the angular orientation of the carriage changes, the fraction of the user's weight bias changes correspondingly, such that at greater inclinations, the weight bias that the user works against is greater.

Another variation of the above-described type of exercise apparatus is that sold under the general name Pilates Performer™ (Stamina Products, Inc., Springfield, Mo., United States) for use with the Pilates exercise system. An apparatus of this type is shown in U.S. Pat. No. D382,319 to Gerschefske et al., the contents of which are incorporated by reference in their entirety. The apparatus includes a frame having a pair of generally parallel tracks that support a movable carriage which is mounted on the tracks with rollers for rolling horizontal movement along the tracks. A set of tensile resilient resistance elements is connected to the frame at one end and to the carriage at the other, thereby biasing the carriage towards a particular position. A pulley system and associated pull lines are coupled to the carriage, such that the carriage may be moved by application of force to the pull lines. A foot bar is provided at one end of the frame, and shoulder blocks are provided at one end of the carriage, allowing the user to position him or herself in a supine position to move the carriage against the resilient bias provided by the tensile resilient resistance elements using the muscles of either the legs or the arms.

SUMMARY OF THE INVENTION

One aspect of the invention relates to a method of enabling a person to exercise. The method comprises providing a movable body support for the exercising person which supports the exercising person in a position which allows the body of the exercising person to move with the movable body support while the feet of the exercising person are free to be moved with respect to the movable body support and providing a movable foot support separate from the body support in a position to be engaged by the feet of the exercising person supported on the movable body support. The method also comprises providing for the absorption of the energy of the movement of the movable body support in a first direction away from the movable foot support by the exercising person supported thereon and the conversion of the absorbed energy to a movement of the movable body support with the exercising person supported thereon in a second direction toward the movable foot support. Additionally, the method comprises providing for the controlled yielding of the movable foot support caused by the engagement thereof by the feet of the exercising

3

person moving with the movable body support in the second direction and establishing as a result of the controlled yielding a bouncing movement by the movable foot support in the first direction, which the exercising person can translate into a movement of the movable body support in the first direction. The arrangement is such that the exercising person can control the repetition and magnitude of the movements of the movable body support by flexure of the legs at the knees.

Another aspect of the invention relates to an exerciser. The exerciser comprises a frame assembly, a movable body carriage supported by the frame assembly and constructed and arranged to support the body of an exercising person in a position which allows the body of the exercising person to move with the movable body carriage while enabling the feet of the exercising person to be moved with respect to the movable body carriage, and a resilient foot engaging assembly coupled with the frame assembly and constructed and arranged to be engaged by the feet of the exercising person supported on the movable body carriage, the movable body carriage being supported for movement in a first direction away from the resilient foot engaging assembly and a second direction toward the resilient foot engaging assembly, and the resilient foot engaging assembly being releasably fixed relative to the frame assembly and constructed and arranged to yield resiliently in response to the engagement of the feet of the exercising person moving with the movable body carriage in the second direction and to establish, as a result of the resilient yielding, a bouncing movement by the resilient foot engaging assembly in the first direction which can be translated by the exercising person into a movement of the movable body carriage in the first direction, the resilient foot engaging assembly being releasable from the fixed relation relative to said frame assembly and being constructed and arranged to independently function as a floor engaging exercising unit by itself.

A further aspect of the invention relates to an attachment for an exerciser of the type including a movable body support disposed on a frame assembly in a position to support the body of an exercising person in a position which allows the body of the exercising person to move with the movable body support while enabling the feet of the user to be free from the movable body support, a foot assembly adapted to be mounted on the frame assembly in a position to be engaged by the feet of the exercising person supported on said movable body support, and mounting structure disposed on the frame assembly, the mounting structure being constructed and arranged to detachably mount the foot assembly to the frame structure. The attachment comprises a movable foot support constructed and arranged to cooperate with the mounting structure to be mounted on the frame assembly in lieu of the foot assembly in a position to be engaged by the feet of a user supported on the movable body support. The movable foot support is constructed and arranged to yield resiliently in response to the engagement of the feet of the user supported on the movable body support therewith in a second direction toward the movable foot support and to establish, as a result of the resilient yielding, a bouncing movement by the movable foot support in a first direction which can be translated by the user into a movement in said first direction of said movable body support.

Another aspect of the invention relates to a dual mode exercising apparatus comprised of a resilient foot engaging unit including a unit frame having resilient foot engaging structure thereon, the unit frame being constructed and arranged to be supported on a horizontal floor surface in a

4

first angled position so as to enable a user to perform exercise movements in which the user moves downwardly on the resilient foot engaging structure which bouncingly returns an upward movement to the user, and an exerciser constructed and arranged to have the resilient foot engaging unit removably attached thereto in an operative position wherein the unit frame is supported in a second angled position disposed at an angle to the horizontal, the exerciser including a body carriage movable in opposite directions under a resistance system for supporting a user thereon in such a way that the user can, during a movement of the body carriage in one direction, engage the resilient foot engaging structure with the user's feet and use the bouncingly return movement thereof to effect a movement of the body carriage in a direction opposite the first direction.

Another aspect of the invention relates to an exerciser comprised of a track, a movable body carriage mounted on the track to enable movement of the movable body support along the track in opposite directions, an elastically deformable foot engaging assembly arranged to be engaged by feet of an exercising person supported by the movable body carriage, the movable body carriage being movable in a first direction away from the elastically deformable foot engaging assembly and a second direction toward the elastically deformable foot engaging assembly, the elastically deformable foot engaging assembly being elastically deformable upon receipt of force applied by engagement of the feet of the exercising person, wherein the elastic deformation of the elastically deformable foot engaging assembly applies a force against the feet of the exercising person to facilitate a movement of the movable body carriage in the first direction away from the elastically deformable foot engaging assembly, the elastically deformable foot engaging assembly including an inflated bladder.

Another aspect of the invention relates to an exercising apparatus comprised of a frame structure constructed and arranged to be supported on a horizontal surface, a foot engaging unit disposed on the frame structure, a movable body carriage mounted on the frame structure for movement toward and away from the foot engaging unit, and an electromechanical system between the frame structure and the movable body carriage for biasing the movable body carriage toward the foot engaging unit and for resisting movement of the movable body carriage away from the foot engaging unit, the electromechanical system including an electrical control circuit for electrically controlling the amount of bias and resistance provided by the electromechanical system.

Some improvements of the present invention are also based upon a dual concept. The first concept is that it can be beneficial to provide an attachment, which can be used both as the spring-biased attachment for the pilates-type exerciser and as an independently operable exerciser by itself. The second concept is that an inflatable dome-type exerciser can be used in practicing the first concept although the unit could be a small floor mounted trampoline or an inflatable exerciser ball as well. Examples of dome-type exercisers are disclosed in U.S. Pat. Nos. 6,702,726 and 6,422,983, the disclosures of which are hereby incorporated by reference into the present specification.

Accordingly, another aspect of the present invention is to provide a method of enabling a person to exercise in either one of two different modes comprising providing a resilient foot engaging unit and an exercising apparatus capable of selectively (1) coupling the resilient foot engaging unit with the exercising apparatus to provide the user with one mode of exercise and (2) releasing the resilient foot engaging unit

5

from the exercising apparatus for use by itself to provide the exercising person with a different mode of exercise.

In one embodiment, the resilient foot engaging structure comprises an inflated dome-shaped bladder.

Still another aspect of the present invention is to provide an improvement wherein the pilates-type of exerciser has a resilient foot engaging assembly of an independent floor supported exercising function releasably secured thereto in place of the usual inverted U-shaped foot bar.

Another aspect of the present invention is the provision of an electromechanical, and, in one embodiment, an electromagnetic system for providing biased movement and resistance to movement for the movable body carriage of the exerciser.

Other aspects of the invention will become apparent from the following description.

DESCRIPTION OF THE DRAWINGS

The invention will be described with reference to the following drawings, in which like numerals represent like features throughout the figures, and in which:

FIG. 1 is a perspective view of an exerciser according to an embodiment of the present invention;

FIG. 2 is an exploded perspective view of the exerciser of FIG. 1;

FIG. 3 is a side elevational view of the exerciser of FIG. 1;

FIG. 4 is an elevational view of one end of the exerciser of FIG. 1;

FIG. 5 is an elevational view of the other end of the exerciser of FIG. 1;

FIGS. 6A-6C are side elevational views of the exerciser of FIG. 1 in various operative positions;

FIG. 7 is a perspective view illustrating an exerciser foot rest attachment according to the invention;

FIG. 8 is a perspective view of an exerciser according to another embodiment of the invention;

FIG. 9 is a side elevational view of the exerciser of FIG. 8;

FIG. 10 is a side elevational view of an exerciser according to yet another embodiment of the invention;

FIG. 11 is a top plan view of the foot support portion of the exerciser of FIG. 10; and

FIG. 12 is a top plan view of a foot support portion according to another embodiment of the invention, the exerciser itself being generally the same as that shown in FIG. 10.

FIG. 13 is a perspective view of one embodiment of an exerciser constructed in accordance with the principles of the present invention;

FIG. 14 is a view similar to FIG. 13 showing the foot engaging assembly of the present invention in exploded perspective;

FIG. 15 is a fragmentary side elevational view of the foot end portion of the exerciser shown in FIG. 13 showing the foot engaging assembly in vertical section;

FIG. 16 is a side elevational view of the inflatable dome exercising unit forming a part of the foot engaging assembly;

FIG. 17 is a perspective view of the unit shown in FIG. 16 deployed for use as an independently functioning floor supported exerciser;

FIG. 18 is a perspective view of another embodiment of an exerciser constructed in accordance with the principles of the present invention;

6

FIG. 19 is a view similar to FIG. 18 showing the foot engaging assembly of the present invention in exploded perspective;

FIG. 20 is a fragmentary side elevational view of the foot end portion of the exerciser shown in FIG. 13 showing the foot engaging assembly in vertical section;

FIG. 21 is a side elevational view of the trampoline exercising unit forming a part of the foot engaging assembly; and

FIG. 22 is a perspective view of the unit shown in FIG. 16 deployed for use as an independently functioning floor supported exercising unit.

FIG. 23 is a view similar to FIG. 2 showing another carriage movement and return system, shown with a conventional inverted U-shaped foot engaging unit in lieu of the trampoline unit shown in FIG. 2, with parts broken away for purposes of clearer illustration.

DETAILED DESCRIPTION

FIG. 1 is a perspective view of an exerciser, generally indicated at 10, according to one embodiment of the invention. The exerciser 10 is generally of the type shown in U.S. Pat. No. Des. 382,319, which was incorporated by reference above. The exerciser 10 includes a frame assembly, generally indicated at 12, a movable body carriage or support, generally indicated at 14, disposed on the frame structure 12 in a position to support the body of the user in a position enabling the feet of the user to be free from the movable body support 14, and a resiliently movable foot support, generally indicated at 16, constructed and arranged to be mounted on the frame structure 12 in a position to be engaged by the feet of the user supported on the movable body support 14.

The frame assembly 12 includes a frame 18, which is adapted to support the movable body support 14, the foot support 16, and the user, as well as a stand 20, which is adapted to connect to the frame 18 to hold the frame 18 in a generally horizontal plane above floor level. As is shown in FIG. 2, an exploded perspective view of the exerciser 10, the stand 20 comprises a plurality of legs 22 connected at respective upper ends thereof by cross bars 24, such that the stand portion 20 is comprised of generally rectangular or trapezoidal segments having legs 22 disposed at the corners of the segments. End caps 26 of a rubber or other non-skid material may be provided at floor-contacting ends of the legs 22. Upper receptacle sections 28 of the stand 20 are adapted to receive corresponding mating structures provided on the underside of the frame 18 (not shown in the Figures), so as to operatively secure the frame 18 to the stand 20. The legs 22 of the stand 20 may be of any length that provides a convenient user height for the frame portion 18.

Depending on the embodiment, the frame 18 and stand 20 may be separable, so that the exerciser 10 can be stored easily. Additionally, the stand 20 may be omitted or sold separately, particularly if the height provided by the stand 20 is not required for the exercises that are to be performed. Moreover, it may be desirable to construct the stand 20 such that one end is wider than the other. A stand 20 with one wider end and one narrower end may be desirable if one end of the exerciser 10 requires a broader base of support to prevent lateral tipping, or if the exerciser 10 is constructed such that the stand 20 will only mate with the frame 18 if the frame 18 is in a particular orientation.

In one embodiment, the frame 18 may be comprised of two generally parallel support tracks 30, connected and braced by a number of cross members. Each of the support

tracks 30 has a generally C-shaped cross-section, such that each support track 30 defines an interior track 32, in the shape of a channel, which is adapted to receive engaging portions of the movable body support 14. The engaging portions of the movable body support 14 in this embodiment are rollers 33 (shown in phantom in FIG. 3) that rollingly engage interior tracks 32. The rollers 33 are mounted to the underside of the movable body support 14 on appropriately-sized bearings or projections, and allow the movable body support 14 to roll along the support tracks 30 between limiting portions of the support tracks 30. The limiting portions of the support tracks 30 define the extent of travel for the movable body support 14. In the exerciser 10, one of the limiting portions is a crossbar 34 that extends between the two support tracks 30; the other limiting portion is defined by an endpiece 36 of the frame portion 18. Alternatively, the limiting portions may simply be the ends of the grooves 32 in the support tracks 30.

Although rollers 33 are used in the illustrated embodiment, a number of other types of bearings and other movement support structures are known in the art, and any one of these known types of bearings may be used in place of the rollers. For example, instead of rollers, blocks of low-friction material may be used, and the inside tracks 32 in the support tracks 30 may be lubricated in order to facilitate sliding movement with reduced friction.

The support tracks 30, in one embodiment, may be continuous bars that run the length of the exerciser, or they may be comprised of sets of shorter bars which are secured together by welds or fasteners. As shown in FIG. 3, each support track is comprised of two shorter support bars 38, 40. At one end, each shorter support bar 38, 40 connects to an endpiece 36, 37 to form an end of the frame 18 of the exerciser 10. (The endpieces 36, 37 of the illustrated embodiments are bars covered with decorative plastic moldings, but they may be made in other configurations.) At the other ends of the shorter support bars 38, 40, cooperating hinge structure 42 is provided, such that the shorter support bars 38, 40 may be hingedly connected together in a manner which allows the exerciser 10 to be folded when not in use.

In alternative embodiments of the invention, the support tracks may have a substantially rectangular cross section, and a movable body support with rollers or other movement support structures may be configured so as to rest on top of the support tracks, rather than engaging inside tracks defined within them. The precise manner of engagement of the movable body support and the support tracks is not critical.

Several body-engaging components can be mounted on the movable body support 14 so as to facilitate the body positioning of the user. Two padded shoulder blocks 44, one on each side of the body support 14, extend vertically, and are positioned so as to engage the upper portion of the user's torso (i.e., at the collarbone or shoulder region) when the user is lying prone or supine on the movable body support 14, so as to prevent the user from sliding relative to the movable body support 14 in a direction away from the foot support 16. The shoulder blocks 44 may be removably attached to the movable body support 14, for example, by a threaded connection.

A padded head rest 46 can also be mounted on the movable body support 14. In the position illustrated in FIGS. 1 and 2, the head rest 46 is positioned such that its user-contacting surface is generally horizontal and co-planar with those of the movable body support 14. However, the head rest may be mounted on a multi-position bracket, such that its angular position may be adjusted relative to that of the movable body support so as to support the user's head in an

inclined position. In addition to the head rest 46, torso pad 48 is mounted on the movable body support 14 so as to cover a substantial portion of the movable body support 14 to provide traction and comfort.

When the user is lying on the movable body support 14 in either prone or supine position with his or her head on the head rest, the user's feet are free to move with respect to the movable body support 14, and extend in a direction toward the resiliently movable foot support 16. As can be seen in FIG. 1 and in the end elevational views of FIGS. 4-5, in one embodiment, the foot support 16 comprises a generally rectangular peripheral frame member 50 that extends vertically, perpendicular to the orientation of the movable body support 14. Resiliently attached to the peripheral frame member 50 is a flexible sheet member 52. In the illustrated embodiment, the peripheral frame member 50 has a generally circular cross section, and a fabric flexible sheet member 52 is attached to the peripheral frame member 50 by a series of elastomeric, resilient, extensible cords 53 that are wrapped around the peripheral frame member 50 and pass through eyelets 54 provided along the edges of the fabric flexible sheet member 52. The fabric flexible sheet member 52 may be nylon, canvas, or another suitable fabric capable of withstanding exercising use. The elastomeric, resilient, extensible cords 53 may comprise, for example, several strands of an elastomeric rubber encased in a fabric outer casing.

In addition to the arrangement shown in the figures and described above, the foot support 16 may be made in a variety of configurations and of a number of materials. For example, instead of being wrapped around the frame member, elastomeric cords or tension coil springs could be secured at first ends within the interior of a hollow peripheral frame member and could extend from it, being secured to the flexible sheet member at respective second ends. Alternatively, the flexible sheet member itself may be made of a resilient, elastomeric material, such as rubber, and may be secured to the frame member with adhesives or fasteners, without elastomeric cords. Moreover, the foot support could comprise an inflated resilient bladder supported by a peripheral frame or a rigid backing member, or it could comprise a board or other rigid member resiliently mounted on springs. In general, other embodiments of the invention would be designed to simulate the type of motion produced using the foot support 16. Other embodiments of the foot support will be described in more detail below.

In one embodiment, the exerciser 10 may also carry a resilient resistance system coupled to the movable body support 14. The crossbar 34 proximate to the footrest has several slots 60 formed in it. Each slot 60 in the crossbar is sized and adapted to accept one end of a tensile resilient resistance element 62. A bracket on the underside of the movable body support 14 (not shown in the figures) includes a corresponding set of slots 60, each slot 60 adapted to accept the other end of a tensile resilient resistance element 62. In this embodiment, the crossbar 34 and bracket of the movable body support 14 each include four slots 60; however, the number of slots 60 may be selected arbitrarily, depending on the total desired resistance, the width of the crossbar 34 and bracket, and the total amount of space required for each resilient resistance element 62. The exerciser 10 may be operated with any number of resilient resistance elements 62 installed in the slots.

The tensile resilient resistance elements 62 illustrated in FIGS. 1 and 2 are elastomeric cords with knobs 64 installed at the ends, so that the ends may be seated in the slots provided for them. The tensile resilient resistance elements

62 may also comprise tension coil springs, rubber bands, or similar structures. Depending on the type of resilient resistance elements 62, hooks or other receiving structures may be used instead of slots. As those of skill in the art will appreciate, one of the functions of the tensile resilient resistance elements 62 is to bias the movable body support 14 to return to a position proximate to the movable foot support 16 when moved by the user away from the movable foot support 16. However, particularly if the movable body support 14 is inclined and able to move under the influence of gravity, or if some other return mechanism is used, the resilient resistance system may be omitted.

The exerciser 10 of FIG. 1 also carries an arm exercise system. Two pull lines 56 are connected to the underside of the movable body support 14. From the underside of the movable body support 14, the pull lines 56 are trained over pulleys 58 that are carried by an upright bar 66 provided on the end of the exerciser opposite the foot support. The pulleys 58 are adapted to swivel, so as to allow the user to pull the pull lines 56 toward the foot support 16 in a variety of planes of motion. They pulleys 58 are also releasably mounted on the upright bar 66 by mounting structure 68 so that their angle and orientation can be changed by the user.

From the pulleys 58, the pull lines 56 extend towards the foot support 16, and are coupled to user grips 70 at their ends. Between the ends of the pull lines 56 and the user grips 70, take-up fittings 72 are provided. Each take-up fitting has a number of holes 74 formed in it, such that if the pull lines are too long, they may be wrapped around and through the take-up fittings 72 to reduce their effective lengths. When the user grips the user grips 70 and causes the pull lines 58 to extend, he or she is working against the force bias provided by the tensile resilient resistance elements 62. The arm exercise system, including the pull lines 56, pulleys 58 and associated structures is an optional feature, and may not be included in some embodiments of the invention.

The foot support 16 is constructed and adapted to yield in a controlled manner in response to the engagement of the user's feet therewith in a direction toward the foot support 16 and to establish, as a result of the controlled yielding, a bouncing movement by the foot support 16 in the opposite direction, which can be translated by the user into a movement of the movable body support 14 in that opposite direction. In this context, the term "bouncing movement" may refer to movements during which the feet of the user lose contact with the foot support 16, as well as resilient movements during which the feet of the user remain in contact with the foot support 16. The term "feet" may refer to both of the user's feet together or to one individual foot; the exercises shown described here may be performed with one foot, each foot alternately, or both feet simultaneously. The terms "controlled yielding" and "resilient yielding" imply that the foot support 16 or individual foot portions thereof yield in such a manner that they are biased to return to their original position.

By the operation of the resilient resistance system, the movable body support 14 is constructed and arranged to absorb the energy of movement of the user on the movable body support in a direction away from the foot support 16 and to convert that absorbed energy into a movement toward the foot support 16.

In one embodiment, the user may control the degree of resistive bias by changing the number of tensile resistive elements 62 that are connected between the crossbar 34 and the movable body support 14. The pull lines 56 are constructed and arranged such that forces applied in a direction toward the foot support 16 by the user's arms are converted

into movements of the movable body support 14 away from the foot support 16. Alternatively, the user may control the position of the movable body support 14 solely by flexure of the legs against the foot support 16.

One exemplary type of exercise that may be performed with the exerciser 10 is shown in FIGS. 6A-6C, although many types of exercises may be performed. As shown in FIG. 6A, the user P lies on the movable body support 14 in an essentially supine position, flexed at the knees, with the bottoms of his or her feet in contact with the flexible sheet member 52 of the foot support 16. In FIG. 6A, the user P is also gripping the user grips 70, and the pull lines 56 are extended forwardly. In the view of FIG. 6B, the user P has moved the movable body support 14 towards the foot support 16, causing the flexible sheet member 52 to deflect. In the view of FIG. 6C, the resiliency of the elastomeric cords 62 attached to the flexible sheet member 52 has caused the flexible sheet member 52 to rebound, creating a bouncing movement by the foot support 16 that the user P can translate into a movement of the movable body support 14. As shown in the FIG. 6C, the movable body support 14 has moved in a direction away from the foot support 16. The degree of bouncing shown in FIG. 6C is for illustrative purposes. The actual amount of bouncing or resiliency will vary with the type of flexible sheet member 52 and elastomeric cords 62 that are used, as well as the way in which the user P controls the movement. The movements illustrated in FIGS. 6A-6C may be repeated any desired number of times at any desired frequency.

During the movements illustrated in FIGS. 6A-6C, the feet of the user P may or may not lose contact with the foot support 16, depending on how the user P controls the movement. If the feet of the user P do lose contact with the foot support 16 during the bouncing movement, the separation distance may be at least partially controlled by the user P by exerting the muscles of the legs and/or abdomen appropriately when initially contacting the foot support 16 or thereafter.

The exerciser 10 may be used for a number of different types of exercise; the positions shown in FIGS. 6A-6C are merely exemplary. In particular, the user P may exercise using any combination of arm, leg, or arm and leg movements. If the user P uses both arm and leg movements during the exercise motions, as is shown in FIGS. 6A-6C, the effects of the arms and legs on the movement of the movable body support 14 are additive. The use of the foot support 16 may be particularly helpful in exercising the abdominal muscles, because the flexed-knee position of the user P will cause some of the exercising forces to be absorbed by and/or exerted by the abdominal muscles.

In addition to being installed on and included with an exercise machine like that shown in FIGS. 1-6, in one embodiment, a foot support may also be sold and used as a separate attachment constructed and arranged to be installed or retrofitted on an exercise apparatus in lieu of a conventional foot bar or foot support. FIG. 7 illustrates a foot support 100 as it might be sold or used as an attachment. The foot support 100 includes connecting structures or portions 102 for connecting the foot support 100 with appropriate receptacles provided in the exercise apparatus. Depending on the configuration of the exerciser, the connecting structures 102 may simply be the terminal portions of the frame member 50 of the foot support. Alternatively, they could be keyed or shaped shafts, or could include some other structure adapted to cooperate with the receptacles of the exerciser to lock the foot support 100 into position within the

11

exerciser. Additionally, a foot support attachment **100** may have any of the features described above with respect to the foot support **16**.

An exerciser **200** according to another embodiment is shown in the perspective view of FIG. **8**. The exerciser **200** may incorporate some or all of the structure and features described in U.S. Pat. No. 5,967,955, which was incorporated by reference above.

In general, the exerciser **200** includes a frame assembly, generally indicated at **202**, a movable body support, generally indicated at **204**, mounted on the frame assembly **202** for movement between limiting positions on the frame assembly **202**, and a resiliently movable foot support, generally indicated at **206**. The resiliently movable foot support **206** is essentially identical to the foot supports **16**, **100** described above, with the exception that it is particularly adapted to be inserted into an end crossmember **208** provided at the foot end of the frame structure **202**. Because the foot support **206** is essentially identical to the foot supports **16**, **100** described above, the description above will suffice to describe it.

In one embodiment, the exerciser **200** does not include a resilient resistance system; instead, as shown in the side elevational view of FIG. **9**, the frame assembly **202** includes two generally parallel support tracks **210**, which are supported on an inclined plane by a stand **212**. With this arrangement, the movable body support **204** is mounted for movement along the inclined plane defined by the tracks **210**. The tracks **210** of the exerciser **200** of this embodiment do not include interior tracks; instead, the movable body support **204** rests on top of the tracks **210**, and is supported by rollers **214**.

As supported by the stand **212** on the inclined plane, the movable body support **204** absorbs the energy of movement of a user supported thereon moving along the tracks **210** up the inclined plane because the user is working against the influence of gravity, and is thus storing potential energy. The movable body support **204** converts the absorbed energy into a movement along the tracks **210** down the inclined plane because the absorbed/stored potential energy is converted to kinetic energy.

In other words, the user is working against a portion of his or her own body weight, which provides the user with exercising resistance. The amount of exercising resistance may be varied by varying the incline of the tracks **210**. As shown, the stand **212** includes a connecting bracket **215** which may be supported at any one of a number of support points **216**. In the illustrated embodiment, the support points **216** are holes positioned at regular intervals along the height of the stand **212**. Each hole **216** is constructed and arranged to receive a pin inserted through a corresponding hole **217** in the connecting bracket. However, the support points **216** may be outwardly projecting members or any other type of structure capable of supporting the weight of the tracks **210** with the user positioned on them. In FIG. **9**, a second angular position of the tracks **210** is drawn in phantom. Despite the difference in resistive systems, the foot support **206** functions in essentially the same way as shown in FIGS. **6A-6C**.

The movable body support **204** is also connected to pull lines **56** which are trained over pulleys **58** carried by the frame assembly **202**, such that the pull lines **56** may be pulled forwardly, towards the foot support **206**, which movement moves the movable body support **204** in a direction away from the foot support **206**. The ends of the pull lines **56** are provided with grips **70**. As with the exerciser **10** of the previous embodiment, the user may use any combination of arm, leg, or arm and leg movements to

12

move the movable body support, and the effects of both arm and leg movements are additive.

It will be noted that in both the horizontal exerciser of FIGS. **1-6C** and the inclined exerciser of FIGS. **8-9**, the main weight of the user is borne by the body support **14**, **204**. In its broadest aspect, the invention contemplates a vertical orientation of the body support **14**, **204**, in which case the body of the user **P** is supported on the body support **14**, **204** to move with the body support **14**, **204** without significant body weight support.

In the exercisers described above, the foot support **16** is a unitary structure that provides a single surface for contacting both of the user's feet. However, in other embodiments of the invention, individual foot supports, or individual contact areas, may be provided for each foot.

An additional embodiment of the invention is shown in the side elevational view of FIG. **10**. FIG. **10** illustrates an exerciser **400** having a foot support **402** that comprises two individual foot contact portions **410** connected to a vertically extending support **406** by compression springs **408**. The foot contact portions **410** extend horizontally forward from the vertically extending support **406**. FIG. **11** is a top plan view of the foot support **402** showing the two individual foot contact portions **410**. Each foot contact portion **410** is sized to accommodate one of the user's feet. In another embodiment shown in the top plan view of FIG. **12**, a foot support **412** includes a unitary foot contact portion **416** sized to accommodate both feet. In each case, the foot support **402**, **412** would be provided with a layer of foam or other padding material **414** to provide comfort and traction for the user's feet. Those of skill in the art will note that the exercising motion enabled by the foot support **412** is similar to the exercising motion enabled by the foot support **16** described above. As will be apparent to those skilled in the art, the foot supports **402**, **412** of FIGS. **10-12** may also be used as attachments to be installed on or retrofit to existing exercises apparatuses.

Further embodiments of the invention may combine attributes of the exercisers **10**, **200**, **400** described above. Moreover, some embodiments may add additional features and levels of user adaptability that are desirable in professional exercise settings, such as gyms and exercise studios.

The exercisers according to the present invention provide several advantages. First, the user can perform exercises in a supine or prone position, which is usually at least perceived by the user to be more comfortable. Second, the type of exercises that can be performed on exercisers according to the invention may have cardiovascular, strength, and flexibility benefits. Third, as was described above, certain known types of exercises, such as Pilates exercises, may be performed on exercisers according to the invention, if desired by the user.

FIG. **13** is a perspective view of an exerciser, generally indicated at **510**, according to one embodiment of the invention. The exerciser **510** includes a mainframe assembly, generally indicated at **512**, a movable body carriage or support, generally indicated at **514**, disposed on the mainframe assembly **512** in a position to support the body of the user in a position enabling the feet of the user to be free from the movable body carriage **514**, and a resiliently movable foot engaging assembly, generally indicated at **516**, constructed and arranged to be mounted on the mainframe assembly **512** in a position to be engaged by the feet of the user supported on the movable body carriage **514**.

The frame assembly **512** includes an upper frame structure **518**, which is adapted to support the movable body carriage **14**, the foot engaging assembly **516**, and the user, on

lower floor engaging stand **520**. The stand **520** is adapted to connect to the frame structure **518** to hold the frame structure **518** in a generally horizontal plane above floor level. As is shown in FIGS. **13** and **14**, the stand **520** comprises a plurality of legs **522** connected at respective upper ends thereof by cross bars **524**, such that the stand portion **520** is comprised of generally rectangular or trapezoidal segments having legs **522** disposed at the corners of the segments. End caps **526** of a rubber or other non-skid material may be provided at floor-contacting ends of the legs **522**. Upper receptacle sections of the stand **520** (not shown in the figures) are adapted to receive corresponding mating structures provided on the underside of the frame structure **518** (not shown in the figures), so as to operatively secure the frame structure **518** to the stand **520**. The legs **522** of the stand **520** may be of any length that provides a convenient user height for the frame structure **518**.

Depending on the embodiment, the frame structure **518** and stand **520** may be separable, so that the exerciser **510** can be stored easily. Additionally, the stand **520** may be omitted or sold separately, particularly if the height provided by the stand **520** is not required for the exercises that are to be performed. Moreover, it may be desirable to construct the stand **520** such that one end is wider than the other. A stand **520** with one wider end and one narrower end may be desirable if one end of the exerciser **510** requires a broader base of support to prevent lateral tipping, or if the exerciser **510** is constructed such that the stand **520** will only mate with the frame structure **518** if the frame structure **518** is in a particular orientation.

The frame structure **518** may be comprised of two generally parallel support tracks **530**, connected and braced by a number of cross members. In one embodiment, each of the support tracks **530** has a generally C-shaped cross-section, such that each support track **530** defines an interior track **532**, in the shape of a channel, which is adapted to receive engaging portions of the movable body carriage **514**. The engaging portions of the movable body carriage **514** in this embodiment are rollers **533** (shown in dotted lines in FIG. **15**) that rollingly engage interior tracks **532**. The rollers **533** are mounted to the underside of the movable body carriage **514** on appropriately-sized bearings or projections, and allow the movable body carriage **514** to roll along the support tracks **530** between limiting portions of the support tracks **530**. The limiting portions of the support tracks **530** define the extent of travel for the movable body carriage **514**. In the exerciser **510**, one of the limiting portions is a crossbar **534** that extends between the two support tracks **530**; the other limiting portion is defined by an endpiece **536** of the frame portion **518**. Alternatively, the limiting portions may simply be the ends of the grooves **532** in the support tracks **530**.

Although rollers **533** are used in the illustrated embodiment, a number of bearings and other movement support structures are known in the art, and any one of these known types of bearings may be used in place of the rollers. For example, instead of rollers, blocks of low-friction material may be used, and the inside tracks **532** in the support tracks **530** may be lubricated in order to facilitate sliding movement with reduced friction.

The support tracks **530** may be continuous bars that run the length of the exerciser, or they may be comprised of sets of shorter bars which may be hingedly connected together in a manner which allows the exerciser **510** to be folded when not in use.

In alternative embodiments of the invention, the support tracks may have a substantially rectangular cross-section,

and a movable body carriage with rollers or other movement support structures may be configured so as to rest on top of the support tracks, rather than engaging inside tracks defined within them. The precise manner of engagement of the movable body carriage and the support tracks can take several different forms.

Several body engaging components may be mounted on the movable body carriage **514** so as to facilitate the body positioning of the user. Two padded shoulder blocks **544**, one on each side of the body support **514**, extend vertically, and are positioned so as to engage the upper portion of the user's torso (i.e., at the collarbone or shoulder region) when the user is lying prone or supine on the movable body carriage **514**, so as to prevent the user from sliding relative to the movable body carriage **514** in a direction away from the foot engaging assembly **516**. The shoulder blocks **544** may be removably attached to the movable body carriage **514**, for example, by a threaded connection.

A padded head rest **546** can also be mounted on the movable body carriage **514**. In the position illustrated in FIGS. **13** and **14**, the head rest **546** is positioned such that its user-contacting surface is generally horizontal and co-planar with those of the movable body carriage **514**. However, the head rest may be mounted on a multi-position bracket, such that its angular position may be adjusted relative to that of the movable body carriage so as to support the user's head in an inclined position. In addition to the head rest **546**, torso pad **548** is mounted on the movable body carriage **514** so as to cover a substantial portion of the movable body carriage **514** to provide traction and comfort.

When the user is lying on the movable body carriage **514** in either prone or supine position with his or her head on the head rest, the user's feet are free to move with respect to the movable body carriage **514**, and extend in a direction toward the resilient foot engaging assembly **516**.

The exerciser **510** may also carry a resilient resistance system coupled to the movable body carriage **514**. The crossbar **534** at the footend has several slots **560** formed in it. Each slot **560** in the crossbar **534** is sized and adapted to accept one end of a tensile resilient resistance element **562**. A bracket on the underside of the movable body carriage **514** (not shown in the figures) includes a corresponding set of slots **560**, each slot **560** adapted to accept the other end of a tensile resilient resistance element **562**. In this embodiment, the crossbar **534** and bracket of the movable body carriage **514** each include four slots **560**; however, the number of slots **560** may be selected arbitrarily, depending on the total desired resistance, the width of the crossbar **534** and bracket, and the total amount of space required for each resilient resistance element **562**. The exerciser **510** may be operated with any number of resilient resistance elements **562** installed in the slots.

The tensile resilient resistance elements **562** illustrated in FIGS. **13** and **14** are elastomeric cords ("bungee cords") with knobs **564** installed at the ends, so that the ends may be seated in the slots **560** provided for them. The tensile resilient resistance elements **562** may also comprise tension coil springs, rubber bands, or similar structures. Depending on the type of resilient resistance elements **562**, hooks or other receiving structures may be used instead of slots. As those of skill in the art will appreciate, one of the functions of the tensile resilient resistance elements **562** is to bias the movable body carriage **514** to return to a position proximate to the movable foot support **516** by virtue of the energy stored when moved away from the resilient foot engaging assembly **516**.

The exerciser **510** of FIG. **13** also carries an arm exercise system. Two pull lines **556** are connected to the underside of the movable body carriage **514**. From the underside of the movable body carriage **514**, the pull lines **556** are trained over pulleys **558** that are carried by an upright bar **566** provided on the head end of the exerciser **510** opposite the foot end. The pulleys **558** are adapted to swivel, so as to allow the user to pull the pull lines **556** toward the resilient foot engaging assembly **516** in a variety of planes of motion. They pulleys **558** are also releasably mounted on the upright bar **566** by mounting structure **568** so that their angle and orientation can be changed by the user.

From the pulleys **558**, the pull lines **556** extend towards the resilient foot engaging assembly **516**, and are coupled to user grips **570** at their ends. Between the ends of the pull lines **556** and the user grips **570**, take-up fittings **572** are provided. Each take-up fitting has a number of holes **574** formed in it, such that if the pull lines are too long, they may be wrapped around and through the take-up fittings **572** to reduce their effective lengths. When the user grips the user grips **570** and causes the pull lines **558** to extend, he or she is working against the force bias provided by the tensile resilient resistance elements **562**. The arm exercise system, including the pull lines **556**, pulleys **558** and associated structures is an optional feature, and may not be included in some embodiments of the invention.

In the embodiment shown in FIGS. **13-17**, the resilient foot engaging assembly **516** comprises a unit frame assembly, generally indicated at **580**, constructed and arranged to be mounted on the pilates exerciser **510** in lieu of the normal inverted U-shaped foot bar thereof, and a resilient foot engaging unit, generally indicated at **582**, constructed and arranged to be deployed by itself as an independently functioning exerciser. As previously indicated, the unit frame assembly **580** is constructed and arranged to be mounted on the pilates exerciser **510** in lieu of the normal inverted U-shaped foot bar thereof. To this end, the unit frame assembly **580** includes a pair of transversely-spaced depending tubular mounting elements **584** configured to securely engage within the sockets within which the normal inverted U-shaped foot bar is engaged.

The unit frame assembly **580** is also constructed and arranged to selectively (1) embody the resilient foot engaging unit **582** in the pilates exerciser **510** so as to provide the user with the exercising movements hereinafter described with respect to the exerciser **510**, and (2) releasing the resilient foot engaging unit **582** for use as an independent exerciser by itself so as to provide the user with the different exercising movements attributable to the unit **582** per se. To this end, the unit frame assembly **580** includes a lower frame section **586** which embodies therein the depending mounting elements **584** and an upwardly facing semi-circular unit mounting member **88** of upwardly opening U-shaped cross-sectional configuration.

The unit frame assembly **580** also includes a separate upper frame section **590** which provides a downwardly mating upper unit mounting member **592** of mating U-shaped cross-sectional configuration.

The separate upper frame section **590** is constructed and arranged to be releasably secured in mating relation to the lower frame section **586** by any suitable means. As shown, the lower frame section **586** provides two transversely-spaced upwardly opening sockets **594** configured to securely receive therein a pair of transversely-spaced tube ends **596** depending from the upper frame section **590** on opposite sides of the upper unit mounting member **592**. Removable pins **598**, insertable through the sockets **594** and tube ends

596, serve to detachably secure the upper frame section **590** to the lower frame section **586** so that the upper and lower mating unit mounting members **592** and **588** form a complete circular mounting structure for the unit **582**.

The unit **582**, as shown in FIGS. **13-17**, may include structures and features as disclosed in U.S. Pat. No. 6,702,726 ("the '726 patent"), hereby incorporated by reference in its entirety. The details of the construction taught in the '726 patent can be understood by reference to the disclosure of that patent. For present purposes, it is sufficient to note that the unit **582** includes a peripheral frame **600** constructed and arranged to be stably supported on a horizontal floor surface and an inflated dome forming bladder **602** fixedly secured on the peripheral frame **600**, by interlaced elongated flexible elements **604**, so as to provide an upwardly facing resilient dome to be engaged by the feet and other portions of the users' body when the peripheral frame **600** is mounted on a floor surface. The various exercising movements provided by the floor mounted unit **582** are fully disclosed in the aforesaid '726 patent to which reference can be made. For present purposes, it is sufficient to note that these exercising movements are different from those provided when the unit **582** is mounted on the pilates exerciser **510** by the unit frame assembly **580**.

As can be appreciated from the above description, mounting is accomplished by first fitting the upper and lower unit mounting members **592** and **588** around the peripheral frame **600** so that the peripheral frame **600** is seated within the U-shaped cross-sectional configurations of the members **592** and **588** and then inserting removable pins **598**. With the unit **582** thus secured to the unit frame assembly **580**, the mounting elements **584** of the latter can now be mounted in the sockets normally provided for the inverted U-shaped foot bar of the pilates exerciser **510**.

The resilient foot engaging assembly **516** is constructed and adapted to yield in a controlled manner in response to the engagement of the user's feet therewith in a direction toward the foot assembly **516** and to establish, as a result of the controlled yielding, a bouncing movement by the foot assembly **516** in the opposite direction, which can be translated by the user into a movement of the movable body carriage **514** in that opposite direction. In this context, the term "bouncing movement" may refer to movements during which the feet of the user lose contact with the foot assembly **516**, as well as resilient movements during which the feet of the user remain in contact with the foot assembly **516**. The term "feet" may refer to both of the user's feet together or to one individual foot; the exercises shown described here may be performed with one foot, each foot alternately, or both feet simultaneously. The terms "controlled yielding" and "resilient yielding" imply that the foot assembly **516** or individual foot portions thereof yield in such a manner that they are biased to return to their original position.

By the operation of the resilient resistance system, the movable body carriage **514** is constructed and arranged to absorb the energy of movement of the user on the movable body carriage **514** in a direction away from the foot assembly **516** and to convert that absorbed energy into a movement toward the foot assembly **516**.

The user may control the degree of resistive bias by changing the number of tensile resistive elements **562** that are connected between the crossbar **534** and the movable body carriage **514**. The pull lines **556** are constructed and arranged such that forces applied in a direction toward the foot support **516** by the user's arms are converted into movements of the movable body carriage **514** away from the foot assembly **516**. Alternatively, the user may control the

position of the movable body carriage **514** solely by flexure of the legs against the foot assembly **516**.

In one exemplary type of exercise that may be performed with the exerciser **510**, the user lies on the movable body carriage **514** in an essentially supine position, flexed at the knees, with the bottoms of his or her feet in contact with the dome provided by the inflated bladder **602** of the foot assembly **516**. The user may also grip the user grips **570**, and extend the pull lines **556** forwardly. As the user moves the movable body carriage **514** towards the foot assembly **516**, the dome-shaped bladder **602** is caused to deflect. The resiliency of the inflated bladder **602** caused the dome-shaped bladder **602** to rebound, creating a bouncing movement by the foot assembly **516** that the user can translate into a movement of the movable body carriage **514**. The actual amount of bouncing or resiliency will vary with the inflation pressure of the bladder **602**, as well as the way in which the user controls the movement.

Other exercising movements that can be performed on the exerciser **510** equipped with the inflatable bladder **602** are the same as those disclosed in the '433 application to which reference may be had.

An exerciser **700** according to another embodiment of the invention is shown in the perspective view of FIG. **18**. The exerciser **700** may incorporate all or some of the structures and features disclosed in U.S. Pat. No. 5,967,955, which was incorporated by reference above.

In general, the exerciser **700** includes a frame assembly, generally indicated at **702**, a movable body carriage or support, generally indicated at **704**, mounted on the frame assembly **702** for movement between limiting positions on the frame assembly **702**, and a resilient foot engaging assembly, generally indicated at **706**.

In one embodiment, the exerciser **700** does not include a resilient resistance system; instead, the frame assembly **702** includes two generally parallel support tracks **710**, which are supported on an inclined plane by a stand **712**. With this arrangement, the movable body carriage **704** is mounted for movement along the inclined plane defined by the tracks **710**. The tracks **710** of the exerciser **700** of this embodiment do not include interior tracks; instead, the movable body carriage **704** is supported by four roller assemblies **714** which roll along the upper surface of the tracks **710**.

As supported by the stand **712** on the inclined plane, the movable body carriage **704** absorbs the energy of movement of a user supported thereon moving along the tracks **710** up the inclined plane because the user is working against the influence of gravity, and is thus storing potential energy. The movable body carriage **704** converts the absorbed energy into a movement along the tracks **710** down the inclined plane because the absorbed/stored potential energy is converted by gravity to kinetic energy.

In other words, the user is working against all or a portion of his or her own body weight, which provides the user with exercising resistance. The amount of exercising resistance may be varied by varying the incline of the tracks **710**. As shown, the stand **712** includes a connecting bracket **716** which may be supported at any one of a number of support points **718**. In the illustrated embodiment, the support points **718** are holes positioned at regular intervals along the height of the stand **712**. Each support point hole **718** is constructed and arranged to receive a removable pin **720** inserted through a corresponding hole **722** in the connecting bracket **716**. However, the support points may be outwardly projecting members or any other type of structure capable of supporting the weight of the tracks **710** with the user positioned on them. Despite the difference in resistive sys-

tems and the resilient foot engaging assembly **706** as hereinafter described, the exerciser **700** functions in essentially the same way as previously described in the description of the exerciser **510**.

The movable body carriage **704** may also be connected to pull lines **556** which are trained over pulleys **558** carried by the frame assembly **702**, such that the pull lines **556** may be pulled forwardly, towards the resilient foot engaging assembly **706**, which movement moves the movable body carriage **704** in a direction away from the resilient foot engaging assembly **706**. The ends of the pull lines **556** are provided with grips **570**. As with the exerciser **510** of the previous embodiment, the user may use any combination of arm, leg, or arm and leg movements to move the movable body carriage, and the effects of both arm and leg movements are additive.

The exerciser frame assembly **702** includes an end member **724** having a pair of transversely-spaced tubular sockets **726** fixed on opposite ends thereof. The sockets **726** can receive an inverted U-shaped foot bar of the type embodied in a usual pilates exerciser. As with the exerciser **510**, the usual inverted U-shaped foot bar becomes one attachment that can be used instead of the resilient foot engaging assembly **706**. The resilient inflated dome foot engaging assembly **516** of the exerciser **510** can also be fitted as an attachment to the exerciser **700**, as well as the exerciser **510**.

As shown in FIGS. **20-22**, the resilient foot engaging assembly **706**, is similar to the resilient foot engaging assembly **516** in that it is comprised of a unit frame assembly, generally indicated at **728**, and resilient foot engaging unit, generally indicated at **730**.

The foot engaging unit **730**, in one embodiment, is a circular floor engaging trampoline unit sized for individual use. Briefly, the unit **730** includes a circular tubular frame **732** which is apertured along its interior periphery to enable outer hooked ends of a series of annularly-spaced coil springs **734** (see FIG. **20**) to be anchored thereto. The coil springs **734** extend radially inwardly from the circular frame **732** and have inner ends hooked and anchored to the outer periphery of a flexible circular sheet member **736**. A resilient circular cover **738** of J-shaped cross-sectional configuration is extended in covering relation over the circular frame **732** and coil springs **734**. A series (4) of legs **740** are fixed to the circular frame **732** and extend axially therefrom in one direction.

The trampoline unit **730** can be used by an individual with the unit **730** supported by the legs **740** on a horizontal floor surface. It, like the inflated dome unit **582**, is resiliently deformably engageable by one or both feet on other body parts of the user and capable of bouncingly returning the deformation movement.

The unit frame assembly **728** is similar to the unit frame assembly **582** except that it is configured to accommodate the different trampoline unit **730**. The unit frame assembly **728** includes a similar pair of upper and lower cooperating mounting elements **742**, and similar upper and lower frame sections **744** and **746** releasably interconnected by tube ends **748** fitted and pinned in sockets **750**. The upper and lower frame sections **744** and **746** carry upper and lower unit mounting members **752** and **754** which are configured differently to accommodate the different frame and leg configuration of the trampoline unit **730**.

In one embodiment of FIGS. **13-22**, it should be appreciated that the unit frame assemblies may be integrally formed with the associated resilient foot engaging assemblies (e.g., inflated bladder unit, trampoline unit, etc.) so that they are removable together from the Pilates unit. In fact, the

structure for mounting any one of the resilient foot engaging assemblies can be any structure that enables the resilient foot engaging assembly to be releasably fixed relative to the main frame and/or tracks on which the movable body support or carriage is supported.

FIG. 23 illustrates another embodiment of the present invention which may utilize a conventional inverted, rigid U-shaped bar **810** serving as the foot engaging unit rather than the trampoline type unit **16** of FIG. 2. It should be appreciated that either the U-shaped bar **810**, the trampoline unit **16** or any other foot engaging structure disclosed herein (e.g., **206**, **402**, **412**, **516**, **706**, **730**, etc.), can be used for the foot engaging structure in this embodiment. The foot engaging structure (e.g., **810** or **16**) can be permanently fixed as part of the exerciser **10**, or can be interchangeable with one another or with the other foot engaging structures disclosed herein. In FIG. 23, reference numbers shown that also appear in FIG. 2 are of like construction and need not be discussed in particular detail again here. The embodiment of FIG. 23 relates to the use of an electromechanical system, and in one embodiment, an electromagnetic system, for returning the movable body carriage **14**, back towards the foot engaging structure, in lieu of the bungee cords **62** shown in FIG. 2 or the inclined gravity return arrangement of FIG. 8.

As shown, an elongated solenoid coil unit **820** has one end thereof fixed to the central portion of the cross member **36** at a level between the tracks **30**. The solenoid coil unit **820** extends longitudinally away from the cross member **36** and has its opposite end fixed to the frame **12** as by a cross brace member **822** fixed to the undersides of the track or rails **30** and extending thereacross. A solenoid plunger member **824** has a free end portion thereof slidably mounted for linear movement through the solenoid coil unit **820** and an opposite end fixed to move with the body carriage **14**. For example, the opposite end of plunger **824** may be fixed to a cross brace member **826**, fixed to the bottom of carriage **14** and extending between the roller brackets **829** fixed in depending relation at the foot end of the carriage **14**.

The coil of the solenoid coil unit **820** is electronically connected to a battery or A/C powered central circuit, shown schematically at **828** in FIG. 23. The control circuit **828** includes a manually adjustable input dial **830**, which can be turned to adjust the resistance of the circuit connected with the solenoid coil **820** and hence the amount of current traveling through the solenoid coils. The amount of current through the coils of the solenoid coil unit **820** will dictate the amount of force applied to the plunger **824** for driving the plunger **824** and carriage **14** towards the foot engaging structure.

The solenoid coil unit **820** and solenoid plunger **824** operate like a conventional solenoid assembly. The plunger **824** is made from a material sensitive to the magnetic force generated by coil unit **820**. Energization of the coil of the solenoid coil unit **820** biases the solenoid plunger **824** in a direction longitudinally outward of the solenoid coil unit **820**. In the embodiment shown, the solenoid plunger **824** extends outwardly of the solenoid coil unit **820** a maximum amount when the coil is energized and the body carriage **14** is not in use, as shown in FIG. 23. The electrical field created by the energization of the coil of the solenoid coil unit **820** provides a resistance to the movement of the solenoid plunger **824** inwardly into coil unit **820** which, in turn, creates a bias or force that moves the body carriage **14** connected to plunger **824** in a direction away from cross member **36** and toward the foot engaging support, while also generating a resistance to the movement away from the foot

engaging support **16** or **810** when the user drives the body carriage **14** away from the foot engaging support during exercise.

As can be appreciated from the discussion above, the bias toward foot support and resistance away from the foot support is a function of the amount of electrical power transmitted to the coil of the solenoid coil unit **820** and hence the amount of bias toward and resistance away from can be easily controlled by manual movement of the dial **830**. The control circuit **828** can also include a computer control in accordance with known practices.

In essence the solenoid coil unit **820** and solenoid plunger **824** arrangement as described above is another way of biasing the carriage **14**, as in contrast with the manner of biasing achieved by the bias of the bungee cord **62** and by the inclined gravity bias, for example. Consequently, this feature of the present invention is useful with resilient type foot engaging units disclosed, as well as with a conventional inverted, rigid U-shaped foot bar **810** shown. In another embodiment, the solenoid coil and plunger arrangement **820/824** can be used in addition to the bungee cord and/or gravitation (inclined) return, thus giving the user various alternatives or combined (working in concert) return mechanisms.

While FIG. 23 and the description above has the solenoid coil unit **820** fixed and the solenoid plunger **824** moving, it is within the contemplation of the present invention to fix the solenoid plunger to frame **12** and move the solenoid coil unit with the carriage **14**.

Other electromechanical systems include the provision of an electric motor driving the pinion of a rack and pinion gear system mounted between the carriage **14** and frame **12**. A control circuit is provided for the electric motor which controls the electricity supplied to the coils of the motor defining the flux field. When energized in one direction, the electric motor is driven as an electric motor biasing the carriage **14** to move toward the foot engaging unit and when the energization is changed, resistance to the movement in the opposite direction away from the foot engaging unit can be accomplished.

Bi-directional electrical motors operating in two directions are a well known way of providing variable resistance to the movement of the exercising apparatus. By varying the electric power transmitted to the flux coils, variability can be easily achieved electrically. For example, the reverse operated electric motor can be connected directly to one of the rollers of a treadmill or the crank member of an elliptical exerciser. It is within the contemplation of the present invention to provide variability with the use of a reverse operated electric motor connected to a pinion of a rack and pinion gear system between the frame **12** and carriage **14**, rather than connecting and disconnecting bungee cords or changing the height of the inclination of the frame.

The present invention is not limited to the above disclosure, but also includes all subject matter covered by the following claims and equivalents thereof.

What is claimed:

1. An exercise device comprising:
 - a frame including a track;
 - a body support mounted for movement on the track;
 - a foot support disposed towards one end of the track, the foot support comprising a fabric flexible sheet supported by a sheet support frame, the sheet support frame comprising laterally spaced portions, the fabric flexible sheet extending over an area between the

21

laterally spaced portions such that the fabric flexible sheet is restrained in tension by the sheet support frame; and

tensile resilient elements that bias the body support toward the flexible fabric sheet, wherein the fabric flexible sheet supported by the sheet support frame is oriented relative to the track so as to be engaged by a user's feet moving towards the flexible fabric sheet as a result of the bias during exercise.

2. The exercise device of claim 1, wherein the sheet support frame comprises a peripheral frame.

3. The exercise device of claim 2, wherein the peripheral frame surrounds all sides of the fabric flexible sheet.

4. The exercise device of claim 2, wherein the peripheral frame comprises a closed loop.

5. The exercise device of claim 2, wherein the peripheral frame comprises a cross member, two side members, and two connecting shaft portions extending generally perpendicular to the cross member and generally parallel to the side members.

6. The exercise device of claim 2, wherein the peripheral frame is configured to attach to all edges of the fabric flexible sheet.

7. The exercise device of claim 1, wherein the fabric flexible sheet is connected to the laterally spaced portions.

8. The exercise device of claim 7, wherein the sheet support frame further comprises a cross member joining the laterally spaced portions.

9. The exercise device of claim 1, wherein the body support is mounted for movement relative to the track along an inclined direction.

10. The exercise device of claim 9, wherein an extent of inclination of the inclined direction is user-adjustable to enable the user to adjust an amount of gravity-based exercising resistance.

11. The exercise device of claim 1, wherein the fabric flexible sheet is resiliently connected to the sheet support frame.

12. The exercise device of claim 1, wherein the frame is configured to position the track in an inclined position so that the force of gravity biases the body support along the track toward the foot support.

13. The exercise device of claim 1, wherein the fabric flexible sheet is made from a resilient material.

14. The exercise device of claim 1, further comprising a headrest to support a head of the user, the headrest being mounted for movement with the body support relative to the track.

15. The exercise device of claim 1, further comprising a padded shoulder block mounted for movement with the body support relative to the track.

22

16. The exercise device of claim 1, wherein the body support is shaped and configured to support the user when the user lies on the body support during use of the exercise device.

17. The exercise device of claim 1, further comprising a torso pad mounted for movement with the body support relative to the track, the torso pad being shaped and configured to provide traction and comfort to the user when the user lies on the movable body support during use of the exercise device.

18. The exercise device of claim 1, wherein the body support is mounted for movement relative to the track along a horizontal direction.

19. The exercise device of claim 1, wherein the tensile resilient elements are oriented in a tensile direction that extends along a direction of movement of the body support relative to the track.

20. The exercise device of claim 1, wherein the tensile resilient elements are configured to bias the body support to return to a position proximate to the foot support.

21. The exercise device of claim 1, wherein the body support is mounted for movement relative to the track along a fixed path.

22. The exercise device of claim 1, wherein the sheet support frame comprises an upside-down "U" shape in which the laterally spaced portions of the sheet support frame define laterally spaced sides of the "U" shape.

23. The exercise device of claim 1, wherein the fabric flexible sheet is oriented in a direction perpendicular to a direction of movement of the body support relative to the track.

24. The exercise device of claim 1, wherein the sheet support frame is oriented in a direction perpendicular to a direction of movement of the body support relative to the track.

25. An exercise device comprising:
a frame including an inclined track;
a body support mounted for movement on the inclined track; and
a foot support disposed towards one end of the inclined track, the foot support comprising a fabric flexible sheet supported by a sheet support frame, the body support being biased by gravity towards the fabric flexible sheet, the sheet support frame comprising laterally spaced portions, the fabric flexible sheet extending over an area between the laterally spaced portions such that the fabric flexible sheet is restrained in tension by the sheet support frame, wherein the fabric flexible sheet supported by the sheet support frame is oriented relative to the inclined track so as to be engaged by a user's feet moving towards the flexible fabric sheet as a result of the bias during exercise.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 10,010,738 B2
APPLICATION NO. : 14/035473
DATED : July 3, 2018
INVENTOR(S) : Kevin Gerschefske et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

Under Related U.S. Application Data:

Replace “(60) Division of application No. 12/829,203, filed on Jul. 1, 2010, now Pat. No. 8,562,492, which is a continuation of application No. 11/702,672, filed on Feb. 6, 2007, now Pat. No. 7,806,805, and a continuation of application No. 11/592,139, filed on Nov. 3, 2006, now Pat. No. 7,771,328, said application No. 11/702,672 is a continuation-in-part of application No. 10/693,443, filed on Oct. 27, 2003, now Pat. No. 7,179,207, said application No. 11/592,139 is a continuation of application No. 10/693,443.”


With --(62) Division of application No. 12/829,203, filed on Jul. 1, 2010, now Pat. No. 8,562,492, which is a continuation of application No. 11/702,672, filed on Feb. 6, 2007, now Pat. No. 7,806,805, and a continuation of application No. 11/592,139, filed on Nov. 3, 2006, now Pat. No. 7,771,328, said application No. 11/702,672 is a continuation-in-part of application No. 10/693,443, filed on Oct. 27, 2003, now Pat. No. 7,179,207, said application No. 11/592,139 is a continuation of application No. 10/693,443.--

Under Related U.S. Application Data:

Please add the following:

--(60) Provisional application No. 60/440,610, filed on Jan. 17, 2003.--

Signed and Sealed this
Twenty-first Day of August, 2018



Andrei Iancu
Director of the United States Patent and Trademark Office