

US010020884B2

(12) **United States Patent**  
**DeDobbelaere et al.**

(10) **Patent No.:** **US 10,020,884 B2**  
(45) **Date of Patent:** **\*Jul. 10, 2018**

(54) **METHOD AND SYSTEM FOR A BI-DIRECTIONAL MULTI-WAVELENGTH RECEIVER FOR STANDARD SINGLE-MODE FIBER BASED ON GRATING COUPLERS**

(58) **Field of Classification Search**  
CPC ..... H04B 10/2503; H04B 10/40; G02B 6/12007; G02B 6/124; G02B 6/34;  
(Continued)

(71) Applicant: **Luxtera, Inc.**, Carlsbad, CA (US)

(56) **References Cited**

(72) Inventors: **Peter DeDobbelaere**, San Diego, CA (US); **Christopher Bergey**, San Jose, CA (US); **Attila Mekis**, Carlsbad, CA (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Luxtera, Inc.**, Carlsbad, CA (US)

7,136,546 B2 \* 11/2006 Kish, Jr. .... B82Y 20/00  
372/50.1  
8,594,503 B2 \* 11/2013 Roelkens ..... G02B 6/12007  
385/15

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

This patent is subject to a terminal disclaimer.

*Primary Examiner* — Tesfaldet Bocure

(74) *Attorney, Agent, or Firm* — McAndrews, Held & Malloy

(21) Appl. No.: **15/676,197**

(57) **ABSTRACT**

(22) Filed: **Aug. 14, 2017**

(65) **Prior Publication Data**

US 2017/0346567 A1 Nov. 30, 2017

**Related U.S. Application Data**

(63) Continuation of application No. 14/612,496, filed on Feb. 3, 2015, now Pat. No. 9,735,869.

(Continued)

(51) **Int. Cl.**

**H04J 14/02** (2006.01)

**H04B 10/25** (2013.01)

(Continued)


(52) **U.S. Cl.**

CPC ..... **H04B 10/2503** (2013.01); **G02B 6/124** (2013.01); **G02B 6/12007** (2013.01);

(Continued)

Methods and systems for a bi-directional receiver for standard single-mode fiber based on grating couplers may include, in an integrated circuit comprising an optoelectronic transceiver, a multi-wavelength grating coupler, and first and second optical sources coupled to the integrated circuit: coupling first and second source optical signals at first and second wavelengths into the photonically-enabled integrated circuit using the first and second optical sources, where the second wavelength is different from the first wavelength, receiving a first optical data signal at the first wavelength from an optical fiber coupled to the multi-wavelength grating coupler, and receiving a second optical data signal at the second wavelength from the optical fiber. Third and fourth optical data signals at the first and second wavelengths may be communicated out of the optoelectronic transceiver via the multi-wavelength grating coupler.

**20 Claims, 6 Drawing Sheets**




- Related U.S. Application Data**
- (60) Provisional application No. 61/965,611, filed on Feb. 3, 2014, provisional application No. 62/122,718, filed on Oct. 28, 2014.
- (51) **Int. Cl.**  
*G02B 6/124* (2006.01)  
*G02B 6/12* (2006.01)  
*G02B 6/30* (2006.01)  
*G02B 6/34* (2006.01)  
*H04B 10/40* (2013.01)
- (52) **U.S. Cl.**  
 CPC ..... *G02B 6/305* (2013.01); *G02B 6/34* (2013.01); *H04B 10/40* (2013.01); *H04J 14/0202* (2013.01)
- (58) **Field of Classification Search**  
 CPC .. *G02B 6/305*; *H04J 14/0202*; *H04J 14/0213*; *H04J 14/02*; *H02B 6/29383*

See application file for complete search history.

- References Cited**
- U.S. PATENT DOCUMENTS
- 9,467,227 B2 \* 10/2016 Masini ..... H04B 10/40  
 2008/0025350 A1 \* 1/2008 Arbore ..... G02B 6/12011  
 372/20  
 2010/0322555 A1 \* 12/2010 Vermeulen ..... G02B 6/12007  
 385/28  
 2011/0305416 A1 \* 12/2011 Mekia ..... G02B 6/43  
 385/28  
 2012/0301149 A1 \* 11/2012 Pinguet ..... H01L 21/84  
 398/115  
 2014/0241721 A1 \* 8/2014 Xia ..... H04J 14/02  
 398/51  
 2015/0219847 A1 \* 8/2015 Mack ..... G02B 6/4286  
 385/14  
 2015/0381273 A1 \* 12/2015 Gloeckner ..... H04B 10/40  
 398/16  
 2016/0036550 A1 \* 2/2016 Welch ..... G02B 6/4215  
 398/87  
 2016/0119057 A1 \* 4/2016 Mekis ..... H04J 14/02  
 398/51  
 2016/0156999 A1 \* 6/2016 Liboiron-  
 Ladouceur ..... H04Q 11/0005  
 398/51  
 2016/0238793 A1 \* 8/2016 Frankel ..... G02B 6/305  
 2016/0246018 A1 \* 8/2016 Pinguet ..... H01L 21/84  
 2016/0320576 A1 \* 11/2016 Mack ..... G02B 6/4286  
 2016/0349544 A1 \* 12/2016 Mekis ..... G02F 1/313

\* cited by examiner



130




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3




FIG. 4



1

**METHOD AND SYSTEM FOR A  
BI-DIRECTIONAL MULTI-WAVELENGTH  
RECEIVER FOR STANDARD SINGLE-MODE  
FIBER BASED ON GRATING COUPLERS**

CROSS-REFERENCE TO RELATED  
APPLICATIONS/INCORPORATION BY  
REFERENCE

This application is a continuation of U.S. patent application Ser. No. 14/612,496 filed on Feb. 3, 2015, now U.S. Pat. No. 9,735,869, which claims priority to and the benefit of U.S. Provisional Application No. 61/965,611 filed on Feb. 3, 2014, and U.S. Provisional Application No. 62/122,718 filed on Oct. 28, 2014, each of which is hereby incorporated herein by reference in its entirety.

## FIELD

Certain embodiments of the disclosure relate to semiconductor photonics. More specifically, certain embodiments of the disclosure relate to a method and system for a bi-directional multi-wavelength transceiver for standard single-mode fiber based on grating couplers.

## BACKGROUND

As data networks scale to meet ever-increasing bandwidth requirements, the shortcomings of copper data channels are becoming apparent. Signal attenuation and crosstalk due to radiated electromagnetic energy are the main impediments encountered by designers of such systems. They can be mitigated to some extent with equalization, coding, and shielding, but these techniques require considerable power, complexity, and cable bulk penalties while offering only modest improvements in reach and very limited scalability. Free of such channel limitations, optical communication has been recognized as the successor to copper links.

Further limitations and disadvantages of conventional and traditional approaches will become apparent to one of skill in the art, through comparison of such systems with the present disclosure as set forth in the remainder of the present application with reference to the drawings.

## BRIEF SUMMARY

A system and/or method for a bi-directional multi-wavelength transceiver for standard single-mode fiber based on grating couplers, substantially as shown in and/or described in connection with at least one of the figures, as set forth more completely in the claims.

Various advantages, aspects and novel features of the present disclosure, as well as details of an illustrated embodiment thereof, will be more fully understood from the following description and drawings.

BRIEF DESCRIPTION OF SEVERAL VIEWS OF  
THE DRAWINGS

FIG. 1A is a block diagram of a photonically-enabled integrated circuit with a bi-directional multi-wavelength transceiver, in accordance with an example embodiment of the disclosure.

FIG. 1B is a diagram illustrating an exemplary photonically-enabled integrated circuit with bi-directional multi-wavelength grating couplers, in accordance with an exemplary embodiment of the disclosure.

2

FIG. 1C is a diagram illustrating a photonically-enabled integrated circuit coupled to an optical fiber cable, in accordance with an example embodiment of the disclosure.

FIG. 2 illustrates a bi-directional multi-wavelength transceiver for standard single-mode fiber, in accordance with an example embodiment of the disclosure.

FIG. 3 illustrates a triple grating coupler, in accordance with an example embodiment of the disclosure.

FIG. 4 illustrates another example of a triple grating coupler, in accordance with an example embodiment of the disclosure.

## DETAILED DESCRIPTION

Certain aspects of the disclosure may be found in a method and system for a bi-directional multi-wavelength transceiver for standard single-mode fiber based on grating couplers. Exemplary aspects of the disclosure may comprise, a photonically-enabled integrated circuit comprising an optoelectronic transceiver, and first and second grating couplers, where the photonically-enabled integrated circuit is operable to: communicate a first optical data signal from the optoelectronic transceiver into a first fiber coupled to the first grating coupler, receive a second optical data signal from the first optical fiber coupled to the first grating coupler, communicate a third optical data signal from the optoelectronic transceiver into a second optical fiber coupled to the second grating coupler, and receive a fourth optical data signal from the second optical fiber coupled to the second grating coupler. The first and third optical data signals may be at a first wavelength, and the second and fourth optical data signals may be at a second wavelength different from the first wavelength. The photonically-enabled integrated circuit may comprise a complementary metal-oxide semiconductor (CMOS) chip. The first and second optical fibers may comprise single mode fibers. The first optical data signal may be generated utilizing a first optical source assembly coupled to the photonically-enabled integrated circuit and the second optical data signal may be generated utilizing a second optical source assembly coupled to the photonically-enabled integrated circuit.

FIG. 1A is a block diagram of a photonically-enabled integrated circuit with a bi-directional multi-wavelength transceiver, in accordance with an example embodiment of the disclosure. Referring to FIG. 1A, there is shown optoelectronic devices on a photonically-enabled integrated circuit **130** comprising optical modulators **105A-105D**, photodiodes **111A-111D**, monitor photodiodes **113A-113H**, and optical devices comprising couplers **103A-103J**, optical terminations **115A-115D**, and grating couplers **117A-117D**. There are also shown electrical devices and circuits comprising amplifiers **107A-107D**, analog and digital control circuits **109**, and control sections **112A-112D**. The amplifiers **107A-107D** may comprise transimpedance and limiting amplifiers (TIA/LAs), for example. In an example scenario, the photonically-enabled integrated circuit **130** comprises a CMOS photonics die.

Optical signals are communicated between optical and optoelectronic devices via optical waveguides **110** fabricated in the photonically-enabled integrated circuit **130**. Single-mode or multi-mode waveguides may be used in photonic integrated circuits. Single-mode operation enables direct connection to optical signal processing and networking elements. The term "single-mode" may be used for waveguides that support a single mode for each of the two polarizations, transverse-electric (TE) and transverse-magnetic (TM), or for waveguides that are truly single mode and

only support one mode whose polarization is TE, which comprises an electric field parallel to the substrate supporting the waveguides. Two typical waveguide cross-sections that are utilized comprise strip waveguides and rib waveguides. Strip waveguides typically comprise a rectangular cross-section, whereas rib waveguides comprise a rib section on top of a waveguide slab.

The optical modulators **105A-105D** comprise Mach-Zehnder or ring modulators, for example, and enable the modulation of the continuous-wave (CW) laser input signal. The optical modulators **105A-105D** may comprise high-speed and low-speed phase modulation sections and are controlled by the control sections **112A-112D**. The high-speed phase modulation section of the optical modulators **105A-105D** may modulate a CW light source signal with a data signal. The low-speed phase modulation section of the optical modulators **105A-105D** may compensate for slowly varying phase factors such as those induced by mismatch between the waveguides, waveguide temperature, or waveguide stress and is referred to as the passive phase, or the passive biasing of the MZI.

The outputs of the modulators **105A-105D** may be optically coupled via the waveguides **110** to the grating couplers **117A-117D**. The couplers **103C-103J** may comprise four-port optical couplers, for example, and may be utilized to sample or split the optical signals generated by the optical modulators **105A-105D**, with the sampled signals being measured by the monitor photodiodes **113A-113H**. The unused branches of the directional couplers **103C-103J** may be terminated by optical terminations **115A-115D** to avoid back reflections of unwanted signals.

The grating couplers **117A-117H** comprise optical gratings that enable coupling of light into and out of the photonic-enabled integrated circuit **130**. The grating couplers **117A-117D** may be utilized to couple light received from optical fibers into and out of the photonic-enabled integrated circuit **130**. The grating couplers **117A-117D** may comprise single polarization grating couplers (SPGC), polarization splitting grating couplers (PSGC), demultiplexing grating couplers (DMGC), and/or bi-wavelength polarization-multiplexing grating couplers (PMGC). Example PSGC and PMGC structures are described in incorporated application Ser. No. 62/122,718 filed on Oct. 28, 2014. In instances where a PSGC or a PMGC is utilized, two input, or output, waveguides may be utilized. In instances where a DMGC is utilized, four input, or output, waveguides may be utilized.

The optical fibers may be epoxied, for example, to the CMOS chip, and may be aligned at an angle from normal to the surface of the photonic-enabled integrated circuit **130** to optimize coupling efficiency. In an example embodiment, the optical fibers may comprise single-mode fiber (SMF) and/or polarization-maintaining fiber (PMF).

In an example embodiment, optical signals may be generated by the CW laser In **101A** and **101B**, which may comprise an assembly mounted to the photonic-enabled integrated circuit **130**, and may generate different wavelengths for multi-wavelength operation of the photonic-enabled integrated circuit **130**. For example, 1310 nm and 1490 nm wavelength optical signals may be generated in the CW laser In **101A** and **101B**, respectively. Accordingly, the grating couplers **103A** and **103B** may be configured for a desired wavelength. In another example scenario, each CW laser In **101A** and **101B** may comprise multiple wavelength outputs and the grating couplers **103A** and **103B** may be configured to receive multiple wavelengths.

The photodiodes **111A-111D** may convert optical signals received from the grating couplers **117A-117D** into electrical signals that are communicated to the amplifiers **107A-107D** for processing. In another embodiment of the disclosure, the photodiodes **111A-111D** may comprise high-speed heterojunction phototransistors, for example, and may comprise germanium (Ge) in the collector and base regions for absorption in the 1.3-1.6  $\mu\text{m}$  optical wavelength range, and may be integrated on a CMOS silicon-on-insulator (SOI) wafer.

The analog and digital control circuits **109** may control gain levels or other parameters in the operation of the amplifiers **107A-107D**, which may then communicate electrical signals off the photonic-enabled integrated circuit **130**. The control sections **112A-112D** comprise electronic circuitry that enable modulation of the CW laser signal received from the splitters **103A** and **103B**. The optical modulators **105A-105D** may require high-speed electrical signals to modulate the refractive index in respective branches of a Mach-Zehnder interferometer (MZI), for example. In an example embodiment, the control sections **112A-112D** may include sink and/or source driver electronics that may enable a bidirectional link utilizing a single laser.

In operation, the photonic-enabled integrated circuit **130** may be operable to transmit and/or receive and process optical signals. Optical signals may be received from optical fibers by the grating couplers **117A-117D** and converted to electrical signals by the photodetectors **111A-111D**. The electrical signals may be amplified by transimpedance amplifiers in the amplifiers **107A-107D**, for example, and subsequently communicated to other electronic circuitry (not shown) in the photonic-enabled integrated circuit **130**.

An integrated transceiver may comprise at least three optical interfaces, including two transmitter input ports to interface to the CW light sources, labeled as CW Laser In **101A** and **101B**; and a transmitter/receiver input/output port to interface to the fiber carrying the optical signal, labeled Optical Signals In/Out.

Integrated photonics platforms allow the full functionality of an optical transceiver to be integrated on a single chip. An optical transceiver chip contains optoelectronic circuits that create and process the optical/electrical signals on the transmitter (Tx) and the receiver (Rx) sides, as well as optical interfaces that couple the optical signals to and from a fiber. The signal processing functionality may include modulating the optical carrier, detecting the optical signal, splitting or combining data streams, and multiplexing or demultiplexing data on carriers with different wavelengths.

In an example embodiment of the disclosure, external continuous-wave (CW) light sources are used. This architecture allows heat sinking and temperature control of the source separately from the photonic-enabled integrated circuit **130**. External light sources may also be connected to the photonic-enabled integrated circuit **130** via a fiber interface. The light source assemblies may be attached to the photonic-enabled integrated circuit **130**.

In an example scenario, a method is disclosed for a multi-wavelength bi-directional transceiver. Grating couplers that receive and transmit more than one wavelength may be utilized to launch a plurality of wavelengths down a single fiber. Additionally, optical signals may travel in either direction through grating couplers, i.e., the optical signals may be received from a fiber and communicated to waveguides on the photonic-enabled integrated circuit **130** or optical signals received from waveguides may be launched

in the photonic-enabled integrated circuit **130** and launched into an optical fiber.

FIG. **1B** is a diagram illustrating an exemplary photonic-enabled integrated circuit with bi-directional multi-wavelength grating couplers, in accordance with an exemplary embodiment of the disclosure. Referring to FIG. **1B**, there is shown the photonic-enabled integrated circuit **130** comprising electronic devices/circuits **131**, optical and optoelectronic devices **133**, light source interfaces **135A** and **135B**, a chip front surface **137**, an optical fiber interface **139**, and a CMOS guard ring **141**.

The light source interfaces **135A/135B** and the optical fiber interface **139** comprise grating couplers, for example, that enable coupling of light signals via the CMOS chip surface **137**, as opposed to the edges of the chip as with conventional edge-emitting/receiving devices. Coupling light signals via the chip surface **137** enables the use of the CMOS guard ring **141** which protects the chip mechanically and prevents the entry of contaminants via the chip edge.

The electronic devices/circuits **131** comprise circuitry such as the amplifiers **107A-107D** and the analog and digital control circuits **109** described with respect to FIG. **1A**, for example. The optical and optoelectronic devices **133** comprise devices such as the couplers **103A-103K**, optical terminations **115A-115D**, grating couplers **117A-117H**, optical modulators **105A-105D**, high-speed heterojunction photodiodes **111A-111D**, and monitor photodiodes **113A-113I**, described with respect to FIG. **1A**, for example.

In an example scenario, the light source interfaces **135A/135B** and the optical fiber interface **139** may be bi-directional, so that optical signals may be communicated in either direction, i.e., received from a source external to the chip or communicated from the chip to an external device. In addition, the light source interfaces **135A/135B** and the optical fiber interface **139** may comprise grating couplers that are configured for two or more wavelengths. In an example scenario, the grating couplers may be operable to couple both 1310 nm and 1490 nm optical signals.

FIG. **1C** is a diagram illustrating a photonic-enabled integrated circuit coupled to an optical fiber cable, in accordance with an example embodiment of the disclosure. Referring to FIG. **1C**, there is shown the photonic-enabled integrated circuit **130** comprising the chip surface **137**, and the CMOS guard ring **141**. There is also shown a fiber-to-chip coupler **145**, an optical fiber cable **149**, and an optical source assemblies **147A** and **147B**.

The photonic-enabled integrated circuit **130** comprising the electronic devices/circuits **131**, the optical and optoelectronic devices **133**, the light source interfaces **135A/B**, the chip surface **137**, and the CMOS guard ring **141** may be as described with respect to FIG. **1B**.

In an example embodiment, the optical fiber cable may be affixed, via epoxy for example, to the CMOS chip surface **137**. The fiber chip coupler **145** enables the physical coupling of the optical fiber cable **149** to the photonic-enabled integrated circuit **130** and may be configured to place the optical fibers in the optical fiber cable **149** at an angle from normal to the chip surface **137** for optimum coupling efficiency into the grating coupler. The angle may be defined by the grating coupler design and wavelength of light to be coupled, for example.

In an example scenario, the optical source assemblies **147A** and **147B** may communicate optical signals at a plurality of wavelengths. In one example, each optical source assembly **147A** and **147B** generates a different wavelength, such as 1310 nm and 1490 nm, for example.

FIG. **2** illustrates a bi-directional multi-wavelength transceiver for standard single-mode fiber, in accordance with an example embodiment of the disclosure. FIG. **2** may share any aspects of FIGS. **1A-1C**. Referring to FIG. **2**, there is shown bi-directional multi-wavelength transceiver **200** that may be integrated on a chip, such as the photonic-enabled integrated circuit **130**. The bi-directional multi-wavelength transceiver **200** may comprise an electronic interface **201**, light source assemblies **203A** and **203B**, a transmitter module **205**, a receiver module **207**, and grating couplers **209A** and **209B**.

The electronic interface **201** may comprise suitable circuitry, logic, and/or code that is/are operable to receive and transmit electrical signals from external devices and also to and from the transmitter module **205** and receiver module **207**. In an example scenario, the electronic interface **201** may comprise the electronic interface for a quad small form-factor pluggable package (QSFP) using 4×26 GB/s electronics thereby generating 100 GB/sec signals but with 26 GB/s electronics.

The light source assemblies **203A** and **203B** may comprise one or more lasers in an assembly that may be bonded to the top surface of the chip comprising the bi-directional multi-wavelength transceiver **200**. The assemblies may comprise lenses, rotators, reflectors, and polarizers, for example. Each of the light source assemblies **203A** and **203B** may comprise a laser with a different wavelength, 1310 nm and 1490 nm, for example. In this manner, two wavelengths may be processed by the bi-directional multi-wavelength transceiver **200**, doubling the system speed without requiring double-speed electronics.

The Tx module **205** may comprise optical, optoelectronic, and/or electronic devices for receiving electrical signals from the electronic interface **201** and communicating modulated optical signals at wavelengths  $\lambda_1$  and  $\lambda_2$  to the grating couplers **209A** and **209B**. Accordingly, the Tx module **205** may comprise elements from FIG. **1A**, such as the optical modulators **105A-105C**, waveguides **110**, control modules **112A-112D**, and analog and digital control circuits **109**, for example.

Similarly, the Rx module **207** may comprise optical, optoelectronic, and/or electronic devices for receiving modulated optical signals at wavelengths  $\lambda_1$  and  $\lambda_2$  from the grating couplers **209A** and **209B** and communicating electrical signals to the electronic interface **201**. Accordingly, the Rx module **207** may comprise elements from FIG. **1A**, such as the photodiodes **111A-111D**, amplifiers **107A-107D**, and analog and digital control circuits **109**.

Since the grating couplers **209A** and **209B** communicate optical signals of different wavelength into and out of the chip, the Tx module **205** and the Rx module **207** therefore support duplex operation, making the transceiver **200** a bi-directional multi-wavelength transceiver that can communicate 100 GB/s over two single-mode fibers. With the multi-wavelength bi-directional operation there is no need to split the optical signal from the laser and thus no speed degradation with only pulse amplitude modulation (PAM) penalty and combiner loss. Similarly, there is no need to multiplex/demultiplex with tuning, relevant to power consumption and control loops, for example.

While FIG. **2** shows each grating coupler **209A** and **209B** receiving one wavelength optical signal and communicating the other wavelength signal out of the bi-directional multi-wavelength transceiver **200**, the disclosure is not so limited.

Each grating coupler may be operable to communicate optical signals in either direction at one or more wavelengths, as illustrated by the grating couplers in FIGS. 3 and 4, for example.

The diffractive grating used in grating couplers can also be used as a demultiplexer by taking advantage of the special property of the grating that different wavelengths can be directed into different scattering orders, therefore spatially separated, by the grating. One example of this is a demultiplexing grating coupler. A 1D DMGC comprises a one-dimensionally periodic grating. If the fiber above the grating coupler is tilted by a small angle with respect to the normal, along the direction of periodicity, two wavelengths from the fiber can be coupled into the plane of the chip in opposite directions.

FIG. 3 illustrates a triple grating coupler, in accordance with an example embodiment of the disclosure. Referring to FIG. 3, there is shown triple grating coupler 300 with a fiber 301 and waveguides 303A-303C. FIG. 3 may share any aspects of FIGS. 1A-2. The fiber 301 may comprise a single mode fiber, for example, that may be operable to communicate signals into, and receive signals from, the triple grating coupler 300. The angle at which the fiber 301 shown in FIG. 3 is for illustrative purposes only, as the fiber 301 may be closer to perpendicular to the surface, or at a larger angle, depending on the design on the triple grating coupler 300.

Similarly, the waveguides 303A-303C may be operable to communicate optical signals into the triple grating coupler 300 from the chip 130 and/or may receive optical signals from the triple grating coupler 300 via the fiber 301 to communicate to other components in the transceiver. The grates in the regions of the triple grating coupler 300 closest to each of the waveguides 303A-303C may configure the wavelength of the optical signal that is received from the fiber in that waveguide. In an example scenario, the grates may comprise curved waveguide sections, each configured for a desired wavelength. The focusing gratings in each section may be designed appropriately by taking into account the phase matching condition between the fiber mode and the grating mode in each direction. After the proper phase matching is computed, the orientation of the lines making up the 1D grating components is altered. For instance, the grating becomes slightly tilted from the horizontal direction to cause the mode incoming from the vertical direction to be scattered into the fiber. Other relative orientations between the fiber and the two waveguides are also conceivable.

In addition, the waveguides 303A-303C may communicate optical signals at an appropriate wavelength to the corresponding arm of the triple grating coupler 300, determined by which laser source generates the signal.

FIG. 4 illustrates another example of a triple grating coupler, in accordance with an example embodiment of the disclosure. FIG. 4 may share any aspects of FIGS. 1A-3. Referring to FIG. 4, there is shown triple grating coupler 400, a fiber 401, and waveguides 403A-403C. The triple grating coupler 400 may comprise a 2D array of scattering elements. One typical 2D grating structure is based on a combination of two one-dimensionally periodic gratings. The two gratings direct light arriving at it from approximately perpendicular directions, and therefore the 2D grating is topologically similar to a square lattice, where the scatterers are placed at the intersections of the two 1D gratings. A 2D grating with a triangular/hexagonal symmetry, one example of which is shown in FIG. 4, allows the

multiplexing of more than two wavelengths. It is based on a combination of three one-dimensionally periodic gratings.

In an example scenario, the three input waveguides 403A-403C are at approximately 120° angle with each other. The scatterers may be placed at the vertices of the lattice. The periodicity of the grating in the three different directions corresponds to the three wavelengths  $\lambda_1$ ,  $\lambda_2$ , and  $\lambda_3$ , of the light being coupled to the fiber, according to the phase matching conditions at each wavelength. As in previous figures, the angle at which the fiber 401 is placed with respect to the plane of the triple grating coupler 400 is merely an example for clarity of the figure, and may be configured at a desired angle based on the design of the grates in the triple grating coupler 400.

In operation, the triple grating coupler 400 may receive optical signals at three wavelengths,  $\lambda_1$ ,  $\lambda_2$ , and  $\lambda_3$ , via the optical fiber 401 and communicate each wavelength to a separate waveguide 403A-403C. In addition, optical signals of any of the three wavelengths may be communicated from the waveguides 403A-403C to the triple grating coupler 400 and into the optical fiber 401, thereby supporting full duplex operation in a single fiber at multiple wavelengths.

In an example embodiment, a method and system are disclosed for a bi-directional multi-wavelength transceiver for standard single-mode fiber based on grating couplers. In this regard, aspects of the disclosure may comprise, in a photonically-enabled integrated circuit comprising an optoelectronic transceiver, a multi-wavelength grating coupler, and first and second optical source assemblies coupled to the photonically-enabled integrated circuit: coupling a first source optical signal at a first wavelength into the photonically-enabled integrated circuit using the first optical source assembly, coupling a second source optical signal at a second wavelength different from the first wavelength into the photonically-enabled integrated circuit using the second optical source assembly, receiving a first optical data signal at the first wavelength from an optical fiber coupled to the multi-wavelength grating coupler, and receiving a second optical data signal at the second wavelength from the optical fiber.

A third optical data signal at the first wavelength may be communicated out of the optoelectronic transceiver via the multi-wavelength grating coupler. A fourth optical data signal at the second wavelength may be communicated out of the optoelectronic transceiver via the multi-wavelength grating coupler. The photonically-enabled integrated circuit may comprise a complementary metal-oxide semiconductor (CMOS) chip. The optical fiber may comprise a single mode fiber. The multi-wavelength grating coupler may comprise sections of curved waveguides, a first section configured for the first wavelength and a second section configured for the second wavelength. The multi-wavelength grating coupler may comprise a two-dimensional array of scattering elements located at intersections of three one-dimensionally periodic gratings.

As utilized herein the terms “circuits” and “circuitry” refer to physical electronic components (i.e. hardware) and any software and/or firmware (“code”) which may configure the hardware, be executed by the hardware, and or otherwise be associated with the hardware. As used herein, for example, a particular processor and memory may comprise a first “circuit” when executing a first one or more lines of code and may comprise a second “circuit” when executing a second one or more lines of code. As utilized herein, “and/or” means any one or more of the items in the list joined by “and/or”. As an example, “x and/or y” means any element of the three-element set  $\{(x), (y), (x, y)\}$ . In other

words, “x and/or y” means “one or both of x and y”. As another example, “x, y, and/or z” means any element of the seven-element set  $\{(x), (y), (z), (x, y), (x, z), (y, z), (x, y, z)\}$ . In other words, “x, y and/or z” means “one or more of x, y and z”. As utilized herein, the term “exemplary” means serving as a non-limiting example, instance, or illustration. As utilized herein, the terms “e.g.,” and “for example” set off lists of one or more non-limiting examples, instances, or illustrations. As utilized herein, circuitry is “operable” to perform a function whenever the circuitry comprises the necessary hardware and code (if any is necessary) to perform the function, regardless of whether performance of the function is disabled or not enabled (e.g., by a user-configurable setting, factory trim, etc.).

While the disclosure has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the present disclosure. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the present disclosure without departing from its scope. Therefore, it is intended that the present disclosure not be limited to the particular embodiments disclosed, but that the present disclosure will include all embodiments falling within the scope of the appended claims.

What is claimed is:

**1.** A method for communication, the method comprising: in an integrated circuit comprising an optoelectronic transceiver, a multi-wavelength grating coupler, and first and second optical sources coupled to the integrated circuit:

coupling a first source optical signal at a first wavelength into the integrated circuit using the first optical source;

coupling a second source optical signal at a second wavelength different from the first wavelength into the integrated circuit using the second optical source; receiving a first optical data signal at the first wavelength from an optical fiber coupled to the multi-wavelength grating coupler; and

receiving a second optical data signal at the second wavelength from the optical fiber coupled to the multi-wavelength grating coupler.

**2.** The method according to claim **1**, comprising communicating a third optical data signal at the first wavelength out of the optoelectronic transceiver via the multi-wavelength grating coupler.

**3.** The method according to claim **2**, comprising communicating a fourth optical data signal at the second wavelength out of the optoelectronic transceiver via a second multi-wavelength grating coupler.

**4.** The method according to claim **1**, wherein the integrated circuit comprises a complementary metal-oxide semiconductor (CMOS) chip.

**5.** The method according to claim **1**, wherein the optical fiber comprises a single mode fiber.

**6.** The method according to claim **1**, wherein the multi-wavelength grating coupler comprises sections of curved waveguides, a first section configured for the first wavelength and a second section configured for the second wavelength.

**7.** The method according to claim **1**, wherein the multi-wavelength grating coupler comprises a two-dimensional array of scattering elements located at intersections of two one-dimensionally periodic gratings.

**8.** A system for communication, the system comprising: an integrated circuit comprising an optoelectronic transceiver, a multi-wavelength grating coupler, and first and second optical sources coupled to the integrated circuit, said integrated circuit being operable to:

couple a first source optical signal at a first wavelength into the integrated circuit using the first optical source;

couple a second source optical signal at a second wavelength different from the first wavelength into the integrated circuit using the second optical source; receive a first optical data signal at the first wavelength from an optical fiber coupled to the multi-wavelength grating coupler; and

receive a second optical data signal at the second wavelength from the optical fiber coupled to the multi-wavelength grating coupler.

**9.** The system according to claim **8**, wherein the integrated circuit is operable to communicate a third optical data signal at the first wavelength out of the optoelectronic transceiver via the multi-wavelength grating coupler.

**10.** The system according to claim **8**, wherein the integrated circuit is operable to communicate a fourth optical data signal at the second wavelength out of the optoelectronic transceiver via a second multi-wavelength grating coupler.

**11.** The system according to claim **8**, wherein the integrated circuit comprises a complementary metal-oxide semiconductor (CMOS) chip.

**12.** The system according to claim **8**, wherein the optical fiber comprises a single mode fiber.

**13.** The system according to claim **8**, wherein the multi-wavelength grating coupler comprises sections of curved waveguides, a first section configured for the first wavelength and a second section configured for the second wavelength.

**14.** The system according to claim **8**, wherein the multi-wavelength grating coupler comprises a two-dimensional array of scattering elements located at intersections of two one-dimensionally periodic gratings.

**15.** A system for communication, the system comprising: an integrated circuit comprising an optoelectronic transceiver, and first and second grating couplers, said photonically-enabled integrated circuit being operable to:

communicate a first optical data signal from the optoelectronic transceiver into a first fiber coupled to the first grating coupler;

receive a second optical data signal from the first optical fiber coupled to the first grating coupler;

communicate a third optical data signal from the optoelectronic transceiver into a second optical fiber coupled to the second grating coupler; and

receive a fourth optical data signal from the second optical fiber coupled to the second grating coupler.

**16.** The system according to claim **15**, wherein the first and third optical data signals are at a first wavelength.

**17.** The system according to claim **16**, wherein the second and fourth optical data signals are at a second wavelength different from the first wavelength.

**18.** The system according to claim **15**, wherein the integrated circuit comprises a complementary metal-oxide semiconductor (CMOS) chip.

**19.** The system according to claim **15**, wherein the first and second optical fibers comprise single mode fibers.

**20.** The system according to claim **15**, comprising generating the first optical data signal utilizing a first optical

source coupled to the integrated circuit and the second optical data signal utilizing a second optical source coupled to the integrated circuit.

\* \* \* \* \*