



US010022742B2

(12) **United States Patent**  
**Goodwin et al.**

(10) **Patent No.:** **US 10,022,742 B2**  
(45) **Date of Patent:** **Jul. 17, 2018**

(54) **APPLICATOR WITH COLLAPSIBLE WAND**

USPC ..... 239/332; 222/333, 383.3, 527, 530, 533,  
222/538, 381, 380, 372

(71) Applicant: **OMS Investments, Inc.**, Los Angeles,  
CA (US)

See application file for complete search history.

(72) Inventors: **Randy M. Goodwin**, Grove City, OH  
(US); **Paul Havlovitz**, Dublin, OH  
(US); **Sean David Montag**, Westerville,  
OH (US); **Jay F. Perkins**, Pickerington,  
OH (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

241,307 A	5/1881	Corwin
260,829 A	7/1882	Bradley
337,268 A	3/1886	Keedy
557,987 A	4/1896	Frank
813,254 A	2/1906	Sweeney
1,264,503 A	4/1918	Griffin
1,456,408 A	5/1923	Scherer
1,521,831 A	1/1925	Olvawitsz
1,544,503 A	6/1925	Wayne

(Continued)

(73) Assignee: **OMS Investments, Inc.**, Los Angeles,  
CA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **15/828,079**

EP	591601 A1	4/1994
EP	677401 A2	10/1995

(22) Filed: **Nov. 30, 2017**

(Continued)

(65) **Prior Publication Data**

US 2018/0085770 A1 Mar. 29, 2018

OTHER PUBLICATIONS

**Related U.S. Application Data**

Air Wick Odor Stop Product Promotion retrieved from the Internet  
at [www.winwithairwick.co.nz/airwick\\_entry\\_form.pdf](http://www.winwithairwick.co.nz/airwick_entry_form.pdf), 2006.

(63) Continuation of application No. 13/038,208, filed on  
Mar. 1, 2011.

(Continued)

(51) **Int. Cl.**

<b>B05B 15/652</b>	(2018.01)
<b>B05B 15/06</b>	(2006.01)
<b>B05B 9/08</b>	(2006.01)
<b>B05B 9/04</b>	(2006.01)

*Primary Examiner* — Chee-Chong Lee

(74) *Attorney, Agent, or Firm* — Ulmer & Berne LLP

(52) **U.S. Cl.**

CPC ..... **B05B 15/652** (2018.02); **B05B 9/0861**  
(2013.01); **B05B 15/066** (2013.01); **B05B**  
**9/0426** (2013.01)


(57) **ABSTRACT**

An applicator comprises a housing having a liquid input, a  
pump, a motor, and a power source; a trigger for providing  
selective control over the pump; a wand hingedly connected  
to the housing; and a nozzle coupled to the wand for  
discharging liquid from the applicator. The nozzle and the  
liquid input are in fluid communication via the pump and  
various conduits of the applicator.

(58) **Field of Classification Search**

CPC .... B05B 9/03; B05B 9/01; B05B 1/00; B05B  
15/066; B05B 9/0861; B05B 9/0426;  
B05B 15/652

**51 Claims, 10 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

1,595,231 A	8/1926	Dryer	4,527,740 A	7/1985	Gunzel, Jr. et al.
1,631,951 A	6/1927	McAnsh	D281,899 S	12/1985	Gunzel, Jr. et al.
1,912,759 A	6/1933	Clark	D281,900 S	12/1985	Gunzel, Jr. et al.
1,982,094 A	11/1934	Gessler	4,618,099 A	10/1986	Nagao et al.
2,006,437 A	7/1935	Burgess et al.	4,624,413 A	11/1986	Corsette
2,050,522 A	8/1936	Evans et al.	4,651,930 A	3/1987	Magaha, Jr.
2,135,665 A	11/1938	Hoban	4,664,301 A	5/1987	Hoyt
2,246,211 A	6/1941	Kilich	4,706,888 A	11/1987	Dobbs
2,248,701 A	7/1941	Fowler	4,785,850 A	11/1988	Sanchez
2,293,390 A	8/1942	Hengesbach	D298,848 S	12/1988	Chow et al.
2,348,205 A	5/1944	Chater	4,811,870 A	3/1989	Bianco
2,388,445 A	11/1945	Stewart	4,826,085 A	5/1989	Chow et al.
2,416,719 A	3/1947	Stockdale	4,878,619 A	11/1989	Norman
2,460,545 A	2/1949	Spreng	4,890,340 A	1/1990	Lovitt
2,485,723 A	10/1949	Fitzgerald	4,890,792 A	1/1990	Martin et al.
2,536,361 A	1/1951	Flanders	4,901,923 A	2/1990	McRoskey et al.
2,580,629 A	1/1952	Wenzel	4,901,976 A	2/1990	Smith
2,599,678 A	6/1952	Walker	4,925,105 A	5/1990	Lin
2,603,388 A	7/1952	Bryant	4,982,896 A	1/1991	Crow
2,647,798 A	8/1953	Ballard	D322,838 S	12/1991	Hagedorn
2,673,664 A	3/1954	Boysen	5,069,389 A	12/1991	Bitsakos
2,711,928 A	6/1955	Randa	5,097,540 A	3/1992	Lovitt
2,754,152 A	7/1956	Gilmour	5,110,231 A	5/1992	Monteith et al.
2,760,820 A	8/1956	Cirese	5,143,294 A	9/1992	Lintvedt
2,788,244 A	4/1957	Gilmour	5,203,468 A	4/1993	Hsu
2,788,245 A	4/1957	Gilmour	5,205,424 A	4/1993	Gaspar
2,951,645 A	9/1960	Price et al.	5,213,264 A	5/1993	Styne
2,961,335 A	11/1960	Shepard	5,213,265 A	5/1993	Englhard et al.
2,981,284 A	4/1961	Putnam	5,263,646 A	11/1993	McCauley et al.
2,991,939 A	7/1961	Packard	5,277,343 A	1/1994	Parsonage
3,088,679 A	5/1963	Ford	5,279,461 A	1/1994	Darroch
3,104,823 A	9/1963	Hayes	5,332,158 A	7/1994	Styne et al.
3,123,253 A	3/1964	Lambton	5,335,858 A	8/1994	Dunning et al.
3,140,018 A	7/1964	Miller	5,346,081 A	9/1994	Lin
D200,960 S	4/1965	Beinert	5,356,076 A	10/1994	Bishop
3,181,797 A	5/1965	Hayes	5,375,769 A	12/1994	Schultz
3,185,358 A	5/1965	Marler	5,388,712 A	2/1995	Brody
3,207,443 A	9/1965	Gilmour	5,413,280 A	5/1995	Taylor
3,233,783 A	2/1966	Thornton	5,469,993 A	11/1995	Hauf et al.
3,253,788 A	5/1966	McHugh et al.	5,484,106 A	1/1996	Gilmond
3,254,844 A	6/1966	Blasnik et al.	5,499,766 A	3/1996	Foster et al.
3,255,924 A	6/1966	Modderno	5,522,547 A	6/1996	Dobbs et al.
3,319,893 A	5/1967	Rodgers	5,526,985 A	6/1996	Martin
3,323,685 A	6/1967	Schultz	5,590,837 A	1/1997	Grogan
3,372,846 A	3/1968	Berkus	5,593,094 A	1/1997	Barriac et al.
3,381,899 A	5/1968	Forsman	5,628,461 A	5/1997	Foster et al.
3,401,840 A	9/1968	McConnell et al.	5,641,125 A	6/1997	Martin et al.
3,443,726 A	5/1969	Muller et al.	5,673,824 A	10/1997	Evans
3,445,067 A	5/1969	Sheldall	5,678,768 A	10/1997	Gager et al.
3,447,753 A	6/1969	Proctor et al.	5,685,487 A	11/1997	Ellis
3,467,314 A	9/1969	Grubb	5,711,251 A	1/1998	Green et al.
3,499,606 A	3/1970	Smith	5,727,736 A	3/1998	Tryon
3,632,046 A	1/1972	Hengensbach	5,738,282 A	4/1998	Grogan
3,655,099 A	4/1972	Hazard	5,755,384 A	5/1998	Foster et al.
3,764,074 A	10/1973	James	5,864,895 A	2/1999	Ota et al.
3,770,205 A	11/1973	Proctor et al.	5,868,321 A	2/1999	Haruch
3,800,786 A	4/1974	Kovach	5,878,959 A	3/1999	Smolen, Jr. et al.
3,833,177 A	9/1974	Pasley et al.	5,881,955 A	3/1999	Styne
D234,952 S	4/1975	Rouquie	5,890,628 A	4/1999	Simpson et al.
D235,063 S	5/1975	Gunzel, Jr. et al.	5,918,621 A	7/1999	Gilmore
3,940,069 A	2/1976	Gunzel, Jr. et al.	5,954,272 A	9/1999	Liao
3,964,689 A	6/1976	Horvath	5,964,415 A	10/1999	Hadar
3,993,245 A	11/1976	Smith	5,975,164 A	11/1999	Whaley et al.
4,027,822 A	6/1977	Usher	5,996,858 A	12/1999	Tapp et al.
4,058,259 A	11/1977	Schantz	6,126,090 A	10/2000	Wadsworth et al.
D251,793 S	5/1979	DeGelder	6,131,774 A	10/2000	Thomas et al.
4,153,184 A	5/1979	Parish et al.	6,170,706 B1	1/2001	Havlovitz
4,250,911 A	2/1981	Kratz	6,186,366 B1	2/2001	Good et al.
4,291,814 A	9/1981	Conn	6,213,410 B1	4/2001	Spitznagel
4,349,157 A	9/1982	Beiswenger et al.	6,223,999 B1	5/2001	Lemelshtich et al.
4,382,552 A	5/1983	Lubsen et al.	6,279,773 B1	8/2001	Kiyota
4,396,356 A	8/1983	Thompson	D447,791 S	9/2001	Robidoux
4,418,869 A	12/1983	Healy	D448,450 S	9/2001	Lawson et al.
4,442,977 A	4/1984	Beiswenger et al.	6,293,294 B1	9/2001	Loeb et al.
4,491,254 A	1/1985	Viets et al.	6,390,335 B1	5/2002	Lawson et al.
			D459,438 S	6/2002	Knowles
			6,402,053 B1	6/2002	Chih
			6,415,956 B1	7/2002	Havlovitz
			6,419,166 B1	7/2002	Brzezinski et al.



(56)

References Cited

U.S. PATENT DOCUMENTS

6,422,485 B1 7/2002 Hsu  
 6,453,953 B1 9/2002 Adriansens et al.  
 6,511,001 B1 1/2003 Huang  
 6,536,684 B1 3/2003 Wei  
 6,546,949 B1 4/2003 Gilmore  
 D476,558 S 7/2003 Cho et al.  
 6,595,437 B1 7/2003 Lawson et al.  
 6,604,546 B1 8/2003 Gilmore  
 6,609,733 B2 8/2003 Gilmore  
 6,612,506 B1 9/2003 Huang  
 6,712,292 B1 3/2004 Gosis et al.  
 6,715,698 B2 4/2004 Foster et al.  
 6,726,123 B2 4/2004 Wang  
 D489,970 S 5/2004 Nelson et al.  
 6,761,324 B2 7/2004 Chang  
 6,851,632 B2 2/2005 Ferrazza et al.  
 6,896,203 B1 5/2005 Restive  
 D507,493 S 7/2005 Nelson et al.  
 6,976,640 B2 12/2005 Chen  
 6,976,644 B2 12/2005 Troudt  
 6,978,946 B2 12/2005 Sweeton  
 6,988,675 B2 1/2006 Hubmann et al.  
 7,017,833 B2 3/2006 Foster  
 7,021,571 B1 4/2006 Lawson et al.  
 D524,906 S 7/2006 Birrenkott et al.  
 7,083,125 B2 8/2006 Westphal et al.  
 7,086,610 B2 8/2006 Hubmann et al.  
 D529,575 S 10/2006 Birrenkott et al.  
 7,156,324 B2 1/2007 Birrenkott et al.  
 7,168,629 B2 1/2007 Timmes et al.  
 D537,359 S 2/2007 Butler et al.  
 7,182,280 B2 2/2007 Ye et al.  
 D539,142 S 3/2007 Butler et al.  
 D559,682 S 1/2008 Meeker et al.  
 D561,301 S 2/2008 Troyer  
 7,337,989 B1 3/2008 Penner et al.  
 D569,478 S 5/2008 Cichy et al.  
 D582,272 S 12/2008 Cichy  
 D619,215 S 7/2010 Havlovitz et al.  
 7,837,132 B2 11/2010 Mazooji et al.  
 8,003,121 B1 8/2011 Dingeldein et al.  
 D670,982 S 11/2012 Goodwin et al.  
 D736,577 S 8/2015 Goodwin et al.  
 D779,898 S 2/2017 Goodwin et al.  
 D797,529 S 9/2017 Goodwin et al.

2004/0007633 A1 1/2004 Simmons  
 2004/0050959 A1 3/2004 Mazooji et al.  
 2004/0222246 A1 11/2004 Bates et al.  
 2005/0145270 A1 7/2005 Ray  
 2005/0173452 A1 8/2005 Brown et al.  
 2006/0013709 A1 1/2006 Hudson et al.  
 2006/0255183 A1 11/2006 Burdsall et al.  
 2007/0125878 A1 6/2007 Hahn et al.  
 2007/0170285 A1 7/2007 Schouten  
 2007/0228187 A1 10/2007 Nelson et al.  
 2008/0011882 A1 1/2008 Foster et al.  
 2008/0061167 A1 3/2008 Gansebom  
 2010/0044454 A1 2/2010 Karazniewicz  
 2010/0163646 A1 7/2010 Havlovitz et al.  
 2010/0170964 A1 7/2010 Fedorov  
 2012/0223160 A1 9/2012 Goodwin et al.  
 2013/0068857 A1 3/2013 Hite

FOREIGN PATENT DOCUMENTS

EP 798158 A2 10/1997  
 EP 1022060 A2 7/2000  
 FR 2708569 A1 2/1995  
 GB 1329788 A 9/1973  
 GB 1386186 A 3/1975  
 GB 2018626 A 10/1979  
 GB 2286109 A 8/1995  
 WO 0209783 A1 2/2002  
 WO 2012118949 A2 9/2012

OTHER PUBLICATIONS

International Search Report for International Patent Application No. PCT/US2006/026119, dated Jan. 5, 2007.  
 International Search Report for International Patent Application No. PCT/US2009/069396, dated Mar. 1, 2010.  
 Extended European Search Report for European Application No. 06774502.6, dated Jul. 23, 2009.  
 International Search Report and Written Opinion for International Patent Application No. PCT/US2012/027242, dated Jun. 6, 2012.  
 Extended Search Report for European Application No. 12752589.7, dated Oct. 14, 2014.  
 Search Report for Chinese Application No. 201280021146.3, dated Jul. 3, 2015.  
 Supplementary Search Report for Chinese Application No. 201280021146.3, dated Jul. 13, 2016.






FIG. 1b




FIG. 1c




FIG. 2a






FIG. 2b






FIG. 2c




FIG. 3a




FIG. 3b






FIG. 4a




FIG. 4b



**APPLICATOR WITH COLLAPSIBLE WAND**CROSS-REFERENCE TO RELATED  
APPLICATION

The present application is a continuation of U.S. application Ser. No. 13/038,208, entitled "APPLICATOR WITH COLLAPSIBLE WAND", filed Mar. 1, 2011, the disclosure of which is hereby incorporated by reference in its entirety.

## BACKGROUND

## 1. Field of the Art

The present invention relates to an applicator, and more particularly to an applicator with a collapsible wand and a rotatable nozzle for dispensing ready-to-use liquid products, such as fertilizer or pesticide (e.g., herbicides, fungicides, and insecticides) compositions

## 2. Description of Related Art

There are many known applicators for dispensing chemicals or other products to maintain lawns, gardens, yards, trees, shrubs, or plants. Most applicators are used with ready-to-use ("RTU") liquids, such as fertilizers, herbicides, insecticides, and fungicides, which can be dispensed directly from the applicator. Indeed, many handheld spray devices for spraying RTU liquid currently exist. The most common spray devices have an integrated, all-in-one design where a bottle is integrally formed with or removably connected to an applicator. Such all-in-one spray devices, however, have limited functionality and usefulness. For example, the weight of the RTU liquid in the bottle can be tiring to a user when holding typical handheld spray devices.

Many conventional applicators are manually actuated or "pump-type" sprayers that rely upon the user to squeeze an actuation trigger to discharge the liquid from the sprayer. These types of sprayers often possess several drawbacks. For example, such "pump-type" sprayers require the manually actuated trigger and the nozzle to be in close proximity to one another to achieve satisfactory spray pressures and fluid velocities. This configuration reduces design flexibility and inhibits the ability to provide applicators having a nozzle located at an extended distance from the actuation trigger. Furthermore, most manually actuated sprayers do not allow the nozzle, and, in particular, the spray angle of the nozzle, to be adjusted dynamically in relation to the actuator. Instead, conventional manually actuated sprayers have a fixed nozzle at a fixed location relative to the actuator. Additionally, manually actuated sprayers tend to result in operator fatigue because such sprayers require continuous actuation of a pumping mechanism.

Other conventional applicators for dispensing RTU liquids incorporate an automatic pump, typically powered by battery. These applicators have many of the same drawbacks of the manually actuated sprayers described above. For instance, many battery powered applicators have a RTU liquid reservoir that is integrated with the applicator. Again, this requires a user to lift and carry the weight of the RTU liquid while using the applicator.

In other instances, conventional applicators may comprise a short nozzle that is proximate to where a user grips the sprayer. This configuration results in an increased risk of contact with chemical product in the event of leakage from

the nozzle. Further, this configuration results in compromised aiming and spray targeting when the user operates the device.

Other battery powered applicators may be separate from a reservoir, but these applicators also have disadvantages. For example, U.S. Published Patent Application No. 2006/0013709 by Hudson et al. ("Hudson") describes a battery-powered spray wand having a reservoir remote from the applicator. The Hudson applicator is configured such that the housing is divided into two portions. Generally, a lower housing contains a power supply, while an upper housing contains a nozzle, motor, transmission and a pump portion. The upper housing pivots relative to the lower portion, such that a user may modify the spray angle of the nozzle by pivoting the entire top portion of the housing. The Hudson applicator has several specific disadvantages. First, the nozzle is coupled directly to the upper housing. Because the upper housing is only pivotable relative to the lower housing, the movement of the nozzle is limited to the range of pivot of the upper housing. In this configuration of the Hudson applicator, the nozzle, therefore, is only pivotable to approximately 90 degrees. The Hudson applicator is unable to provide further movement. Moreover, Hudson's pivoting housing configuration is difficult to produce and expensive to manufacture. Further, the Hudson applicator is configured such that the power source is housed in a separate housing from the pump, motor, and transmission. This configuration creates potential reliability issues, as the liquid that is sprayed may leak into either the upper or lower housing, thereby interfering with the electrical circuitry within the applicator.

Notwithstanding the number of applicators that currently exist, most fail to provide for a reliable, user-friendly device that is cost-effective to manufacture and ship, easy to use and safe for a user to operate. The present invention, as demonstrated by the several exemplary embodiments described herein, provides an applicator with a collapsible arm with beneficial features that achieve improved functionality over conventional applicators. The applicator of the present invention offers numerous advantages, including: (1) a single housing incorporating a power source, motor, transmission, and pump, (2) a nozzle that is movable independent of and relative to the housing, and (3) a collapsible arm for connecting in fluid communication the nozzle to the housing.

The description herein of certain advantages and disadvantages of known methods and devices is not intended to limit the scope of the present invention. Indeed, the exemplary embodiments may include some or all of the features described above without suffering from the same disadvantages.

## SUMMARY

In accordance with one embodiment, an applicator is provided comprising a housing having a liquid input, a pump, a motor, and a power source; a trigger for providing selective control over the pump; a wand hingedly connected to the housing; and a nozzle coupled to the wand for discharging liquid from the applicator. The nozzle and the liquid input are in fluid communication via the pump and various conduits of the applicator.

## BRIEF DESCRIPTION OF THE DRAWINGS

Purposes and advantages of the exemplary embodiments will be apparent to those of ordinary skill in the art from the



following detailed description together with the appended drawings, in which like reference numerals are used to indicate like elements:

FIG. 1a depicts a perspective view of an applicator in accordance with an exemplary embodiment.

FIG. 1b depicts a perspective view of an applicator with an extended wand in accordance with an exemplary embodiment.

FIG. 1c depicts a perspective view of an applicator having a collapsed wand in accordance with an exemplary embodiment.

FIG. 2a depicts a cross-sectional view of an applicator.

FIG. 2b depicts a cross-sectional view of an applicator nozzle.

FIG. 2c depicts a cross-sectional view of an applicator having multiple conduits.

FIG. 3a depicts a perspective view of an applicator and applicator clip assembly.

FIG. 3b depicts a perspective view of an applicator clip.

FIG. 4a depicts a container, in accordance with an exemplary embodiment.

FIG. 4b depicts a container, an applicator clip, and an applicator assembly.

These and other exemplary embodiments and advantages will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the various exemplary embodiments.

#### DETAILED DESCRIPTION

The following description is intended to convey a thorough understanding of the embodiments by providing a number of specific embodiments and details involving an applicator with a collapsible wand. It is understood, however, that the invention is not limited to these specific embodiments and details, which are exemplary only. It is further understood that one possessing ordinary skill in the art, in light of known devices, systems and methods, would appreciate the use of the invention for its intended purposes and benefits in any number of alternative embodiments as required on specific design or other need.

Terminology used for describing particular embodiments is not intended to limit the scope of an exemplary embodiment. As used throughout this disclosure, the singular forms “a,” “an,” and “the” include the plural, unless the context clearly dictates otherwise. Thus, for example, a reference to a “conduit” includes a plurality of conduits, or other equivalents or variations known to those skilled in the art. Furthermore, if in describing some embodiments or features permissive language (e.g., “may”) is used, that does not suggest that embodiments or features described using other language (e.g., “is,” “are”) are required. Unless defined otherwise, all terms have the same commonly understood meaning that one of ordinary skill in the art to which this invention belongs would expect them to have.

The accompanying figures and following description depict and describe exemplary embodiments of an applicator for discharging liquid. As used throughout this description, the terms “applicator,” “sprayer” or other like terms are meant to encompass a structure adapted to discharge, dispense, project, spray, etc., liquid. In exemplary embodiments, the liquid to be discharged may be a fertilizer, a pesticide (e.g., herbicide, insecticide, fungicide, etc.), or combinations thereof. It should be appreciated, however, that the exemplary embodiments of the applicator described throughout are not limited to any specific embodiment or

detail that is disclosed. Moreover, one of ordinary skill in the art will appreciate the use of the exemplary embodiments for their intended purposes and benefits in a number of alternative embodiments as required by specific design or other needs.

With regard to the exemplary embodiments of the applicator described herein, any part that fastens, mounts, attaches, or connects any component to form the sprayer shall not be limited to any particular type and is instead intended to encompass all known and conventional fasteners like screws, nut and bolt connectors, threaded connectors, snap rings, detent arrangements, clamps, rivets, toggles, etc. Fastening may also be accomplished by other known fittings like leak-tight seals or sealing devices. Components may also be connected by adhesives, glues, welding, ultrasonic welding, and friction fitting or deformation. Of course, combinations of these fitment systems might be used.

Unless otherwise specifically disclosed, materials for making components of the present invention may be selected from appropriate materials, such as metal, metal alloys, natural or manmade fibers, composites, vinyl, plastics, silicone, rubber, and so on. Any and all appropriate manufacturing or production methods, such as casting, pressing, extruding, molding, or machining may be used to construct the exemplary embodiments or their components.

Lastly, when describing exemplary embodiments of the sprayer, any reference to front and back or rear, top and bottom, right and left, upper and lower, etc., is intended for the convenience of describing such embodiments only. Such references do not limit the exemplary embodiments or its components to any specific positional or spacial orientation.

Exemplary embodiments of the sprayer will now be described more fully with reference to the accompanying drawings, in which some, but not all, embodiments are illustrated.

With reference to FIGS. 1a-4b, exemplary embodiments of an applicator in accordance with the present invention are shown. Each of the exemplary embodiments generally includes a housing having a liquid input, a pump in fluid connection with the liquid input, an electric motor for driving the pump, and a power source for providing power to the electric motor; a trigger in electronic communication with the power source and the electric motor, wherein the trigger provides selective control over the pump; a wand hingedly connected to the housing, wherein the wand is rotatable relative to the housing; a wand conduit in fluid communication with the liquid input and the pump; and a nozzle coupled to the wand for discharging liquid from the applicator, wherein the nozzle is in fluid communication with the wand conduit, the pump, and the liquid input. Other embodiments, however, may include a rotating nozzle, which may be further described herein, for providing a variety of spray patterns. Another embodiment may include any suitable trigger mechanism for actuating a standard pumping mechanism housed inside of the applicator. Each of these parts generally referred to here will be described in more detail below.

FIG. 1a illustrates an exemplary embodiment of an applicator 100. It should be appreciated that all of the figures herein illustrate a simplified view of an exemplary applicator 100, and its components, and that applicator 100 may include additional elements that are not depicted. The applicator 100 may generally have a housing 105 with a grip portion 110 and a trigger 120. The applicator 100 may also have a wand hinge 115, a wand 125 and a nozzle 130. Generally, the applicator 100 may be configured such that a user may grip the grip portion 110 of housing 105 while



actuating the trigger 120. The wand 125 may be coupled to the housing 105 via wand hinge 115, so that the wand 125 and nozzle 130 may be rotatable relative to the housing 105, the grip portion 110, and the trigger 120.

The grip portion 110 of housing 105 may be ergonomically shaped to allow a user to comfortably grasp the applicator 100. In an exemplary embodiment, the grip portion 110 may include one or more ergonomic gripping pads or grooves (not shown). The gripping pads or grooves (not shown) may be shaped to accommodate the natural orientation of a user's grip. In one embodiment, the gripping pads or grooves (not shown) may extend along the entire grip area 110 in a substantially elongated shape. The gripping pads or grooves (not shown) may have a varied length and width and may also be changed to conform to the various designs of housing 105 and grip portion 110.

Moreover, the housing 105 may also include a liquid input 140 for coupling with a liquid conduit, such as liquid conduit 260 depicted with reference to FIG. 2c. Liquid may enter the applicator 100 via liquid input 140, where it may pass through the various conduits, chambers, valves, and pumps of the applicator 100 before being discharged via the liquid outlet 135 of nozzle 130. The nozzle 130 and liquid outlet 135 may be configured to discharge liquid in any number of ways according to any number of patterns. For example, the nozzle 130 may spray liquid in a fan, jet, or shower pattern. In an exemplary embodiment, the nozzle 130 may be adjustable to permit a user to change the liquid spray patterns by twisting or rotating the nozzle 130. In other exemplary embodiments, the nozzle 130 may regulate the spray flow, droplet size, and spray pattern of liquid as it is discharged from the applicator 100. The nozzle 130 may also be adapted to discharge liquid in any number of spray patterns, including stream jet pattern and full-cone pattern, depending upon user preference. It should be appreciated that nozzle 130 may be configured in any number of ways to support any number of applications.

Liquid input 140 may be located anywhere within the housing 105 and may be configured to couple with a liquid conduit in any number of ways. For example, liquid input 140 permanently house a liquid conduit. In another exemplary embodiment, the liquid input 140 may be threaded so that a threaded liquid conduit may be removably attached to the liquid input 140. Liquid input 140 may be removably connected to a conduit in any appropriate matter, like through threaded connectors, snap rings, detent arrangements, etc. It should be appreciated that liquid input 140 may be configured in any number of ways to provide fluid communication between applicator 100 and a liquid container, such as liquid container 400, described below with reference to FIG. 4.

Trigger 120 may be located on the housing 105. The trigger 120 may provide a user with control over the discharge of liquid from nozzle 130. The location of the trigger 120 and the grip portion 110 may be configured to permit a user to grip the grip portion 110 and activate the trigger 120 with one hand. In other exemplary embodiments, the trigger 120 may be ergonomically shaped or may include gripping pads or grooves to allow a user to easily and comfortably actuate the trigger 120 when desired. When actuated, the trigger 120 may be configured to control the operation of various internal components of the applicator 100 in order to affect the discharge of liquid from the nozzle 130. Exemplary configurations for such internal components are described below with regard to FIGS. 2a and 2c.

The wand hinge 115 may connect the wand 125 to the housing 105. FIG. 1a depicts an embodiment in which the

wand 125 is folded to be proximate to and parallel with the housing 105. In other embodiments, the wand 125 may be folded to be at any angle relative the housing 105. The configuration depicted in FIG. 1a may be desirable for a user that wishes to conserve space when storing the applicator 100. Such a configuration may also provide benefits to a manufacturer, distributor or retailer, as the compact configuration minimizes space occupied by the applicator 100 during packaging, shipping, and on-shelf display. The wand hinge 115 may be rotatable so that the wand 125 may extend away from the housing 105, depending upon a user's desired operating position.

It should be understood that embodiments describing a "wand hinge" are exemplary only, and that in other exemplary embodiments the wand 125 may be hingedly connected to the housing 105. In other exemplary embodiments, the wand 125 may have hinge members (not shown) integrally molded onto it in order to facilitate motion relative to the housing 105. In another exemplary embodiment, the housing 105 may have hinge member (not shown) integrally molded onto it in order to facilitate motion relative to the wand 125. Those with skill in the art will understand that there are many other ways to configure the wand 125 and the housing 105 in order to facilitate the above-described motion of the wand 125 relative to the housing 105.

FIG. 1b depicts an exemplary embodiment of an applicator 100 with an extended wand 125. In this exemplary embodiment, the wand hinge 115 has rotated 180 degrees relative to the housing 105, such that the wand 125 is fully extended. In this exemplary embodiment, the extended wand 125 provides a user with increased range when using the applicator 100 to spray a liquid product, for example, a RTU liquid.

FIG. 1c depicts an exemplary embodiment of an applicator 100 with a collapsed wand 125. In this exemplary embodiment, the wand hinge 115 has rotated so that the wand 125 has collapsed to be proximate to and parallel with the housing 105. In this exemplary embodiment, as discussed above with regard to the exemplary embodiment of FIG. 1a, the collapsed wand 125 provides a compact configuration to enable more efficient shipping and storage of the applicator 100. Of course, it should be appreciated that FIGS. 1b and 1c depict only two of any number of applicator configurations. The wand hinge 115 may be configured to provide any degree of rotation between the wand 125 and the housing 105.

FIGS. 2a and 2c illustrate cross sectional views of applicator 100. Generally, the housing 105 may have any number of internal components, including, but not limited to, power source 205, motor 210, pump 215, and housing conduit 255. Applicator 100 may also have a wand 125 having a wand conduit 225. Housing conduit 255 and wand conduit 225 may be fluidly connected via hinge conduit 220, which may be housed within wand hinge 115. In an exemplary embodiment, housing conduit 255, wand conduit 225, and hinge conduit 220 may be configured to form one, continuous conduit to provide fluid connection from liquid input 140 to nozzle 130. In another exemplary embodiment, housing conduit 255, wand conduit 225 and hinge conduit 220 may be separate conduits that are fluidly connected. In one exemplary embodiment, the housing conduit 255, the wand conduit 225, and the hinge conduit 220 may be flexible tubes.

Housing conduit 255 may be configured to provide fluid communication between liquid input 140 and pump 215. Housing conduit 255 may also provide a fluid connection between pump 215 and the remaining conduits of applicator



100. Housing conduit 255 and pump 215 may be configured in any number of ways so that pump 215 may operate to pump liquid from liquid input 140, through the various conduits of applicator 100, to the nozzle 130, where the liquid may be discharged from the applicator 100 via the liquid outlet 135. Those with skill in the art will understand that any number of standard pumping mechanisms may be employed to circulate the flow of liquid through the various conduits of applicator 100. Suitable pumps include centrifugal, vane, lobe, diaphragm, positive displacement, or rotary gear pumps. While there are many different types of pumps for pumping fluid from the liquid input 140, a rotary gear pump may be effective due to its stable, non-pulsing motion, which ensures static flow during operation. The pump 215 may comprise either external gear pumps or internal gear pumps. As is commonly understood in the art, the pump 215 may use the meshing of gears to pump liquid, by displacement, from a liquid source connected to the liquid input 140. In an exemplary embodiment, the liquid source may be container 400, as described below with regard to FIG. 4a. It should be understood, as previously mentioned, that the applicator 100 is not limited to any particular type of pump mechanism.

As depicted in FIG. 2a, the applicator 100 may have a pump 215, which may be electronically coupled and driven by a motor 210. The motor 210, in turn, may be powered by power source 205. The power source 205 may be a rechargeable battery, one-time disposable battery (or batteries), or battery pack. In an exemplary embodiment, the power supply will be of sufficient voltage to adequately supply power to the internal electrical components of the motor 210 and the pump 215. The pump 215 may be actuated by the trigger 120, which may be connected to the motor 210. Once activated, liquid may then enter the pump 215 after it flows through the housing conduit 255. The stream of liquid may continue as long as the trigger 120 is depressed and the motor 210 is driving the pump 215. Release of the trigger 120 ceases operation of the motor 210, which, in turn, ceases operation of the pump 215. Therefore, as trigger 120 is released, the flow of liquid through the various conduits of applicator 100 ceases.

When liquid product, for example, RTU liquid product, is dispensed—i.e., when the pump 215 is activated by the trigger 120—RTU liquid is drawn from a container, such as container 400 described below with regard to FIG. 4 into the liquid input 140 of the applicator 100. The RTU liquid then passes through the pump 215, housing conduit 255, hinge conduit 220, wand conduit 225, and the nozzle 130 before being discharged via liquid outlet 135. When the trigger 120 is released, the pump ceases operation and the RTU liquid is no longer drawn from the container, ending the discharge of liquid via liquid outlet 135.

FIG. 2b depicts a cross-sectional view of an exemplary nozzle 130. The nozzle 130 may have a first outer portion 230 and a second outer portion 235. The second outer portion 235 may be rotatable relative to first outer portion 230 and the rotation of the second outer portion 235 may provide a variety of spray patterns in which the liquid may be discharged via liquid outlet 135. The nozzle 130 may also have a first nozzle conduit 240 and a plurality of second nozzle conduits 245. The first nozzle conduit 240 may be in fluid communication with the wand conduit 225, second nozzle conduits 245 and the liquid outlet 135. Moreover, the first outer portion 230 may have an anchor portion 250, for mating with the wand 125.

The plurality of second nozzle conduits 245 may be formed in various configurations within second outer portion

235. In an exemplary embodiment, one or more of the plurality of second nozzle conduits 245 are configured to be in fluid communication with the first nozzle conduit 240. In other exemplary embodiments, the second outer portion 235 may be rotatable relative to first outer portion 230, such that the one or more of the plurality of second nozzle conduits 245 are configured to be in selective fluid communication with the first nozzle conduit 240, depending upon the rotation of the second outer portion 235 relative to the first outer portion 230.

FIG. 2c depicts a cross sectional view of an applicator 100 having a housing conduit 255, a hinge conduit 220, a wand conduit 225 and a liquid conduit 260. FIG. 2c also depicts a liquid conduit cap 265 for coupling with a container, such as container 400, which is described in more detail below with regard to FIG. 4a. It should be understood that FIGS. 2a and 2c depict exemplary embodiments of an applicator 100 and that the various conduits of applicator 100 may be configured in any number of ways to facilitate fluid communication between the various components of applicator 100, as described in more detail above with regard to FIG. 2a.

FIG. 3a depicts a perspective view of an applicator clip 300. The applicator clip 300 may have a clip portion 305, a container attachment 310, and a conduit guide 315. The clip portion 305 may be configured to receive an applicator, such as applicator 100. Those with skill in the art will understand that the clip portion 305 may be configured according to any number of corresponding configurations of an applicator. In an exemplary embodiment, clip portion 305 is configured such that applicator 100 can be easily fastened and removed from applicator clip 300 by a user. The container attachment 310 may be configured to couple with an appropriately configured clip attachment, such as clip attachment 420 described below with reference to FIG. 4a. Moreover, the conduit guide 315 may be configured to house a conduit that fluidly connects an applicator, such as applicator 100, to a container, such as container 400, which is described in more detail below with reference to FIG. 4a.

FIG. 3b depicts an exemplary embodiment of an applicator 100 coupled to an applicator clip 300. In addition to clip portion 305 and conduit guide 315, applicator clip 300 may also include a clasp 320. As depicted in FIG. 3b, the clasp 320 may be configured to secure the applicator 100 to the applicator clip 300. Further, a user may remove the clasp 320 in order to remove the applicator 100 from the applicator clip 300. In another exemplary embodiment, the clasp 320 may comprise a safety mechanism (not shown) in order to prevent a child from removing the applicator 100 from the applicator clip 300.

FIG. 4a depicts an exemplary embodiment of the container 400 for the applicator 100 (not shown). As seen in FIG. 4a, the container 400 may comprise a base 405, a cylindrical neck 425, a handle 415, a container opening 410, and a clip attachment 420. A standard bottle cap (not shown) may be configured to attach to the cylindrical neck 425. The standard bottle cap (not shown) may have receiving grooves on its inside surface so that it can be threaded and secured onto the cylindrical neck 425 of the container 400 to seal the contents of the container 400. Overall, the container 400 may define a hollow compartment to store liquid products, for example, RTU liquid products, such as fertilizers, herbicides, insecticides, fungicides, and combinations thereof. A typical container 400 may contain, for example, a gallon of liquid product, but may also hold any other amount. The handle 415 may have a plurality of ergonomic recesses or



raised grips spaced around the handle **415**. The container **400** may further be translucent in order to monitor the RTU liquid levels.

Referring now to both FIGS. **2c** and **4a**, the liquid conduit **260** may be configured to have a liquid conduit cap **265**, which may be configured to fasten over the cylindrical neck **425** in order to provide fluid communication between the liquid in liquid container **400** and liquid conduit **260**. The liquid conduit cap **265** may be configured to seal the contents of container **400**, except for the liquid that may flow from the container **400** to the applicator **100** when the liquid conduit **260** and the liquid conduit cap **265** when the container **400** is attached thereto. The container **400** may also include a clip attachment **420** for providing an anchor point for the clip assembly **300**.

FIG. **4b** illustrates an exemplary embodiment of a clip assembly **300** coupled to a container **400**. In the exemplary embodiment depicted in FIG. **4b**. The applicator **100** is secured within the clip assembly **300**. This exemplary configuration is beneficial because it conserves space and provides efficiencies related to packaging, manufacturing, shipping and storage.

In the preceding specification, various exemplary embodiment have been described with reference to the accompanying drawings. It will, however, be evidence that various modifications and changes may be made thereto, and additional exemplary embodiments may be implemented, without departing from the broader scope of the embodiments as set forth in the claims that follow. The specification and drawings are accordingly to be regarded in an illustrative rather than restrictive sense.

The invention claimed is:

**1.** An applicator configured to dispense liquid comprising: a housing, comprising:

- a pump,
- an electric motor for driving the pump,
- a power source for providing power to the electric motor, and
- a flexible housing conduit in fluid communication with the pump;

a trigger in electronic communication with the power source and the electric motor, wherein the trigger provides manual selective control over the pump such that when the trigger is depressed, the pump is actuated and when the trigger is released, the pump ceases operation;

a wand connected to the housing via a wand hinge that is configured to allow the wand to be collapsed against the housing in a first position and extended away from the housing in a second position, the wand hinge comprises a hinge conduit engaging the flexible housing conduit and that curves around a pivot point of the wand hinge such that when the wand is collapsed against the housing in the first position, the hinge conduit keeps the flexible housing conduit apart from the pivot point of the wand hinge;

a nozzle coupled to the wand for discharging liquid from the applicator, wherein the nozzle is in fluid communication with the pump; and

a liquid conduit having a proximal end in fluid communication with the pump and a distal end that extends externally from the housing, the distal end is configured to connect to a container that is external to and separate from the housing such that when the distal end of the liquid conduit is connected to the container, the con-

tainer is coupled to the housing by the liquid conduit such that the container remains external to and separate from the housing.

**2.** The applicator of claim **1**, wherein the nozzle comprises:

- a first nozzle portion having a first nozzle conduit; and
- a second nozzle portion having several second nozzle conduits;

wherein the second nozzle portion is rotatable relative to the first nozzle portion and wherein one or more of the several second nozzle conduits align with the first nozzle conduit depending upon a position of the second nozzle portion relative to the first nozzle portion.

**3.** The applicator of claim **2**, wherein a configuration of the several second nozzle conduits creates a variety of liquid spray patterns depending upon the position of the second nozzle portion.

**4.** The applicator of claim **2**, wherein the second nozzle portion and the several second nozzle conduits are configured such that none of the several second nozzle conduits align with the first nozzle conduit when the second nozzle portion is rotated to a particular position relative to the first nozzle portion.

**5.** The applicator of claim **2**, further comprising a single liquid outlet in fluid communication with the several second nozzle conduits for discharging liquid from the nozzle.

**6.** The applicator of claim **1**, wherein the wand is rotatable via the wand hinge through an arc up to about 180 degrees between the first position and the second position.

**7.** The applicator of claim **1**, wherein the housing further comprises a curved grip portion.

**8.** The applicator of claim **1**, wherein the housing and the trigger are configured such that a user may grip the housing and actuate the trigger with only one hand.

**9.** The applicator of claim **1**, wherein the power source comprises at least one battery.

**10.** The applicator of claim **1**, further comprising a clip coupled to the container, wherein the housing and the clip are configured to be removably attached to one another.

**11.** The applicator of claim **1**, wherein a plane, defined by an arc through which the wand swings between the first position and the second position, intersects the housing.

**12.** The applicator of claim **1**, wherein the pivot point of the wand hinge is located internal to the housing.

**13.** The applicator of claim **1**, further comprising a liquid conduit cap configured to be connected to the liquid conduit, the liquid conduit cap for providing a sealing interface between the container and the liquid conduit to facilitate fluid communication between the container and the pump.

**14.** The applicator of claim **1**, wherein the wand comprises a wand conduit in fluid communication with the pump.

**15.** The applicator of claim **14**, wherein the flexible housing conduit provides fluid communication between the pump and the wand conduit.

**16.** The applicator of claim **14**, wherein the nozzle is in fluid communication with the pump via the wand conduit, the hinge conduit, and the flexible housing conduit.

**17.** The applicator of claim **16**, wherein the flexible housing conduit, the wand conduit, and the hinge conduit form a continuous conduit to provide the fluid communication from the pump to the nozzle.

**18.** The applicator of claim **16**, wherein one of the wand conduit and the hinge conduit comprises a flexible tube.

**19.** The applicator of claim **1**, wherein the housing further comprises a liquid input; and



## 11

wherein the pump is in fluid communication with the liquid conduit via the liquid input.

**20.** A system for dispensing liquid comprising:

a container containing a ready-to-use liquid product and comprising a cylindrical neck and a container opening; and

a housing, comprising:

a pump,

an electric motor for driving the pump,

a power source for providing power to the electric motor, and

a flexible housing conduit in fluid communication with the pump;

a trigger in electronic communication with the power source and the electric motor, wherein the trigger provides manual selective control over the pump such that when the trigger is depressed, the pump is actuated and when the trigger is released, the pump ceases operation;

a wand connected to the housing via a wand hinge that is configured to allow the wand to be collapsed against the housing in a first position and extended away from the housing in a second position, the wand hinge comprises a hinge conduit engaging the flexible housing conduit and that curves around a pivot point of the wand hinge such that when the wand is collapsed against the housing in the first position, the hinge conduit keeps the flexible housing conduit apart from the pivot point of the wand hinge;

a nozzle coupled to the wand for discharging liquid from the system, wherein the nozzle is in fluid communication with the pump; and

a liquid conduit having a proximal end in fluid communication with the pump and a distal end that extends externally from the housing and connects to the container via a liquid conduit cap such that when the distal end of the liquid conduit is connected to the container, the container is coupled to the housing by the liquid conduit such that the container remains external to and separate from the housing;

wherein the liquid conduit cap providing a sealing interface between the container opening and the liquid conduit to facilitate fluid communication between the container opening and the pump.

**21.** The system of claim **20**, wherein the ready-to-use liquid product comprises one of a fertilizer or pesticide.

**22.** The system of claim **20**, wherein the nozzle comprises:

a first nozzle portion having a first nozzle conduit; and

a second nozzle portion having several second nozzle conduits;

wherein the second nozzle portion is rotatable relative to the first nozzle portion and wherein one or more of the several second nozzle conduits align with the first nozzle conduit depending upon a position of the second nozzle portion relative to the first nozzle portion.

**23.** The system of claim **22**, wherein the second nozzle portion and the several second nozzle conduits are configured such that none of the several second nozzle conduits align with the first nozzle conduit when the second nozzle portion is rotated to a particular position relative to the first nozzle portion.

**24.** The system of claim **22**, further comprising a single liquid outlet in fluid communication with the several second nozzle conduits for discharging liquid from the nozzle.

**25.** The system of claim **20**, wherein the pivot point of the wand hinge is located internal to the housing.

## 12

**26.** The system of claim **20**, wherein the wand is rotatable via the wand hinge through an arc up to about 180 degrees between the first position and the second position.

**27.** The system of claim **20**, wherein the housing further comprises a curved grip portion.

**28.** The system of claim **20**, further comprising a clip coupled to the container, wherein the housing and the clip are configured to be removably attached to one another.

**29.** The system of claim **20**, wherein the wand comprises a wand conduit in fluid communication with the pump; and wherein the flexible housing conduit provides fluid communication between the pump and the wand conduit.

**30.** The system of claim **20**, wherein the wand comprises a wand conduit in fluid communication with the pump; and wherein the nozzle is in fluid communication with the pump via the wand conduit, the hinge conduit, and the flexible housing conduit.

**31.** The system of claim **30**, wherein the flexible housing conduit, the wand conduit, and the hinge conduit form a continuous conduit to provide the fluid communication from the pump to the nozzle.

**32.** The system of claim **30**, wherein one of the wand conduit and the hinge conduit comprises a flexible tube.

**33.** The system of claim **20**, wherein the housing further comprises a liquid input; and wherein the pump is in fluid communication with the liquid conduit via the liquid input.

**34.** A system for dispensing liquid comprising:

a container containing a ready-to-use liquid product and comprising a cylindrical neck and a container opening; and

a housing, comprising:

a pump,

an electric motor for driving the pump,

a power source for providing power to the electric motor, and

a flexible housing conduit in fluid communication with the pump;

a trigger in electronic communication with the power source and the electric motor, wherein the trigger provides manual selective control over the pump such that when the trigger is depressed, the pump is actuated and when the trigger is released, the pump ceases operation;

a wand connected to the housing via a wand hinge, the wand comprising a wand conduit;

the wand hinge is configured to allow the wand to be collapsed against the housing in a first position and extended away from the housing in a second position, the wand hinge comprises a hinge conduit that engages and is in fluid communication with the flexible housing conduit and the wand conduit, the hinge conduit curves around a pivot point of the wand hinge such that when the wand is collapsed against the housing in the first position, the hinge conduit keeps the flexible housing conduit apart from the pivot point of the wand hinge;

a nozzle coupled to the wand for discharging liquid from the system, wherein the nozzle is in fluid communication with the wand conduit; and

a liquid conduit having a proximal end in fluid communication with the pump and a distal end that extends externally from the housing and connects to the container via a liquid conduit cap such that when the distal end of the liquid conduit is connected to the container, the container is coupled to the housing by the liquid conduit such that the container remains external to and separate from the housing;



## 13

wherein the liquid conduit cap providing a sealing interface between the container opening and the liquid conduit to facilitate fluid communication between the container opening and the pump.

35. The system of claim 34, wherein the wand is rotatable via the wand hinge through an arc up to about 180 degrees between the first position and the second position.

36. The system of claim 34, wherein the pivot point of the wand hinge is located internal to the housing.

37. The system of claim 34, wherein the nozzle is in fluid communication with the pump via the wand conduit, the hinge conduit, and the flexible housing conduit.

38. The system of claim 37, wherein the flexible housing conduit, the wand conduit, and the hinge conduit form a continuous conduit to provide the fluid communication from the pump to the nozzle.

39. An applicator configured to dispense a liquid comprising:

a housing comprising:

a pump,

an electric motor for driving the pump,

a power source for providing power to the electric motor, and

a flexible housing conduit in fluid communication with the pump;

a trigger in electronic communication with the power source and the electric motor, wherein the trigger provides manual selective control over the pump such that when the trigger is depressed, the pump is actuated and when the trigger is released, the pump ceases operation;

a wand connected to the housing via a wand hinge that is configured to allow the wand to be collapsed against the housing in a first position and extended away from the housing in a second position, the wand hinge comprises a hinge conduit engaging the flexible housing conduit and that curves around a pivot point of the wand hinge such that when the wand is collapsed against the housing in the first position, the hinge conduit keeps the flexible housing conduit apart from the pivot point of the wand hinge;

a nozzle coupled to the wand for discharging liquid from the applicator, wherein the nozzle is in fluid communication with the pump; and

a liquid conduit having a proximal end and a distal end, at least a portion of the proximal end of the liquid conduit is within the housing and is in fluid communication with the pump, the distal end of the liquid conduit extends externally from the housing and is

## 14

configured to connect to a container that is external to and separate from the housing.

40. The applicator of claim 39, wherein the nozzle comprises:

a first nozzle portion having a first nozzle conduit; and  
a second nozzle portion having several second nozzle conduits;

wherein the second nozzle portion is rotatable relative to the first nozzle portion and wherein one or more of the several second nozzle conduits align with the first nozzle conduit depending upon a position of the second nozzle portion relative to the first nozzle portion.

41. The applicator of claim 40, wherein the second nozzle portion and the several second nozzle conduits are configured such that none of the several second nozzle conduits align with the first nozzle conduit when the second nozzle portion is rotated to a particular position relative to the first nozzle portion.

42. The applicator of claim 40, further comprising a single liquid outlet in fluid communication with the several second nozzle conduits for discharging liquid from the nozzle.

43. The applicator of claim 39, wherein the wand is rotatable via the wand hinge through an arc up to about 180 degrees between the first position and the second position.

44. The applicator of claim 39, wherein the housing further comprises a curved grip portion.

45. The applicator of claim 39, wherein the pivot point of the wand hinge is located internal to the housing.

46. The applicator of claim 39, wherein the wand comprises a wand conduit in fluid communication with the pump.

47. The applicator of claim 46, wherein the flexible housing conduit provides fluid communication between the pump and the wand conduit.

48. The applicator of claim 46, wherein the nozzle is in fluid communication with the pump via the wand conduit, the hinge conduit, and the flexible housing conduit.

49. The applicator of claim 48, wherein the flexible housing conduit, the wand conduit, and the hinge conduit form a continuous conduit to provide the fluid communication from the pump to the nozzle.

50. The applicator of claim 48, wherein one of the wand conduit and the hinge conduit comprises a flexible tube.

51. The applicator of claim 39, wherein the housing further comprises a liquid input; and

wherein the pump is in fluid communication with the liquid conduit via the liquid input.

\* \* \* \* \*