

US010023304B2

(12) **United States Patent**
Dickman et al.

(10) **Patent No.:** **US 10,023,304 B2**
(45) **Date of Patent:** **Jul. 17, 2018**

(54) **TAIL ROTOR ACTUATION SYSTEM**

(71) Applicant: **Bell Helicopter Textron Inc.**, Fort Worth, TX (US)
(72) Inventors: **Corey Dickman**, Tyrone, PA (US); **Carlos A. Fenny**, Arlington, TX (US); **David Schultz**, Grand Prairie, TX (US)
(73) Assignee: **Bell Helicopter Textron Inc.**, Fort Worth, TX (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 88 days.

(21) Appl. No.: **14/286,197**
(22) Filed: **May 23, 2014**

(65) **Prior Publication Data**
US 2016/0200430 A1 Jul. 14, 2016

(51) **Int. Cl.**
B64C 27/12 (2006.01)
B64C 13/50 (2006.01)
B64C 27/82 (2006.01)
B64C 27/14 (2006.01)

(52) **U.S. Cl.**
CPC **B64C 13/503** (2013.01); **B64C 27/14** (2013.01); **B64C 27/82** (2013.01)

(58) **Field of Classification Search**
CPC B64C 27/82; B64C 27/52; B64C 27/605; B64C 27/58; B64C 27/59; B64C 27/78; B64C 27/72; B64C 27/12; B64C 13/503; F01D 7/00; F15B 18/00
USPC 244/17.19
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|--------------|------|---------|---------------------------|-------------|
| 3,199,601 | A * | 8/1965 | Dean | B64C 27/32 |
| | | | | 244/17.21 |
| 3,411,410 | A * | 11/1968 | Westbury et al. | 91/1 |
| 4,340,335 | A * | 7/1982 | Cheney | B64C 27/82 |
| | | | | 416/138 |
| 4,516,476 | A * | 5/1985 | Beaton | B23Q 1/0009 |
| | | | | 901/50 |
| 4,699,043 | A * | 10/1987 | Violante De Dionigi | 91/182 |
| 5,607,122 | A * | 3/1997 | Hicks | B64C 27/78 |
| | | | | 244/17.13 |
| 8,657,229 | B2 * | 2/2014 | Schank | B64C 27/615 |
| | | | | 244/213 |
| 2004/0075019 | A1 * | 4/2004 | Collins | B64C 13/30 |
| | | | | 244/99.9 |
| 2008/0145221 | A1 * | 6/2008 | Sun | B64C 27/615 |
| | | | | 416/23 |


* cited by examiner


Primary Examiner — Medhat Badawi
Assistant Examiner — Vicente Rodriguez


(57) **ABSTRACT**




In some embodiments, an actuation system includes a an actuator assembly, a yoke, and a control rod. The actuator assembly comprises a first actuator. The first actuator is configured to extend in a first direction and retract in a second direction opposite of the first direction. The yoke is coupled to the first actuator at a first actuator end proximate to the first direction. The control rod is coupled to the yoke at a first control rod end and extends in the second direction past the actuator assembly to a second end in mechanical communication with an output device.

16 Claims, 3 Drawing Sheets









1**TAIL ROTOR ACTUATION SYSTEM**

TECHNICAL FIELD

This invention relates generally to actuation systems, and more particularly, to a tail rotor actuation system.

BACKGROUND

A rotorcraft may include one or more rotor systems. One example of a rotorcraft rotor system is a main rotor system. A main rotor system may generate aerodynamic lift to support the weight of the rotorcraft in flight and thrust to counteract aerodynamic drag and move the rotorcraft in forward flight. Another example of a rotorcraft rotor system is a tail rotor system. A tail rotor system may generate thrust in the same direction as the main rotor system's rotation to counter the torque effect created by the main rotor system.

SUMMARY

Particular embodiments of the present disclosure may provide one or more technical advantages. A technical advantage of one embodiment may include the capability to improve packaging of a tail rotor actuation system. A technical advantage of one embodiment may include the capability to add redundancy to a tail rotor actuation system, especially in a fly-by-wire control system.

Certain embodiments of the present disclosure may include some, all, or none of the above advantages. One or more other technical advantages may be readily apparent to those skilled in the art from the figures, descriptions, and claims included herein.

BRIEF DESCRIPTION OF THE DRAWINGS

To provide a more complete understanding of the present invention and the features and advantages thereof, reference is made to the following description taken in conjunction with the accompanying drawings, in which:

FIG. 1 shows a rotorcraft according to one example embodiment; and

FIGS. 2A-2F show a tail rotor actuation system according to one example embodiment that may be installed on the rotorcraft of FIG. 1.

DETAILED DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a rotorcraft **100** according to one example embodiment. Rotorcraft **100** features a rotor system **110**, blades **120**, a fuselage **130**, a landing gear **140**, and an empennage **150**. Rotor system **110** may rotate blades **120**. Rotor system **110** may include a control system for selectively controlling the pitch of each blade **120** in order to selectively control direction, thrust, and lift of rotorcraft **100**. In some embodiments, the control system may include a swashplate; moving the swashplate may change the pitch of one or more blades **120** and cause the aircraft to change direction.

Fuselage **130** represents the body of rotorcraft **100** and may be coupled to rotor system **110** such that rotor system **110** and blades **120** may move fuselage **130** through the air. Landing gear **140** supports rotorcraft **100** when rotorcraft **100** is landing and/or when rotorcraft **100** is at rest on the ground. Empennage **150** represents the tail section of the aircraft and features components of a rotor system **110** and blades **120'**. Blades **120'** may provide thrust in the same

2

direction as the rotation of blades **120** so as to counter the torque effect created by rotor system **110** and blades **120**. Teachings of certain embodiments relating to rotor systems described herein may apply to rotor system **110** and/or other rotor systems, such as other tilt rotor and helicopter rotor systems. It should also be appreciated that teachings regarding rotorcraft **100** may apply to aircraft and vehicles other than rotorcraft, such as airplanes and unmanned aircraft, to name a few examples.

As stated above, a control system may selectively control the pitch of each blade **120** and/or **120'** in order to selectively control direction, thrust, and lift of rotorcraft **100**. In some embodiments, a control system may receive inputs (e.g., from a pilot, flight computer, and/or other flight control equipment) and change the pitch of each blade **120** and/or **120'** based on these inputs by, for example, changing the swashplate position. Example embodiments of a control system for selectively controlling the pitch of blades **120** and/or **120'** may include equipment from mechanical, fly-by-wire, and/or other flight control systems.

Different control systems may offer different benefits. For example, some control systems may include redundant components to improve safety and operation in the event of a failure. As another example, some control systems may have smaller packaging sizes or include components that can be moved to more convenient areas of rotorcraft **100**. As yet another example, some control system components may work with fly-by-wire flight control systems, which may offer lower weight and greater controllability as compared to mechanical flight control systems.

Teachings of certain embodiments recognize the capability to provide some or all of these benefits. For example, FIGS. 2A-2F show a tail rotor actuation system **200** according to one example embodiment. FIG. 2A shows a perspective view of tail rotor actuation system **200**, FIG. 2B shows a perspective view of tail rotor actuation system **200** installed on empennage **150** of rotorcraft **100** (with blades **120'** removed), FIG. 2C shows an end view of tail rotor actuation system **200**, FIG. 2D shows a cross-section view of the tail rotor actuation system **200** of FIG. 2C, FIG. 2E shows the cross-section view of FIG. 2D when tail rotor actuation system **200** is extended, and FIG. 2F shows the cross-section view of FIG. 2D when tail rotor actuation system **200** is retracted.

As seen in the example of FIG. 2A, tail rotor actuation system **200** may include an actuator assembly **210**, a yoke **220**, and a control rod **230**. Tail rotor actuation system **200** may be controlled by a variety of flight control systems, such as mechanical, fly-by-wire, and/or other flight control systems. In one example embodiment, tail rotor actuation system **200** may be controlled in a fly-by-wire flight control configuration. For example, flight control inputs from a pilot may be converted to actuation inputs to actuator assembly **210** in order to cause selective actuation of yoke **220** and control rod **230**. In an alternative embodiment, an unmanned flight control system is used in lieu of the pilot.

In the example of FIG. 2A, actuator assembly **210** features three actuators **210a**, **210b**, and **210c**. In this example embodiment, actuator assembly **210** may also be referred to as a triplex actuator because it includes three piston/cylinder pairs. Each actuator is coupled to yoke **220** and configured to extend and retract yoke **220**, which causes yoke **220** to translate control rod **230**. Teachings of certain embodiments recognize that providing a triplex actuator may improve performance in the event of an actuator failure. For example, the failure of a single piston/cylinder assembly only results in a one-third loss of power in the triplex actuator. As

another example, each piston/cylinder assembly within an individual triplex actuator may be separately powered by a hydraulic power pack (discussed below), thus further realizing an increased level of safety.

In some embodiments, actuator assembly **210** may include a manifold associated with each actuator **210a-210c**. Each manifold may be in hydraulic communication with a hydraulic power pack to provide hydraulic fluid to the actuators. Each hydraulic power pack may include a pump and a reservoir in one package. One or more flight control computers (FCCs) may control each manifold and/or hydraulic power pack.

In some embodiments, each manifold may include an integrated three function valve (ITFV) configured to allow actuator assembly **210** to operate even after a failure of one or two of actuators **210a-210c**. For example, ITFV may be used to quickly inert a malfunctioning actuator so that the remaining healthy actuators can continue to operate without fighting the malfunctioning actuator. Further, ITFV may allow a single actuator to be in bypass while allowing actuator assembly **210** to be supplied energy via other hydraulic power packs. Each manifold may also include an electro-hydraulic servo-valve (EHSV). An ITFV and EHSV are disclosed in U.S. Pat. No. 7,003,949, titled "Integrated Three Function Valve," issued 28 Feb. 2006, to Fenny, et al. (Fenny '949). Fenny '949 is incorporated herein by reference.

As seen in the example of FIGS. 2D-2F, control rod **230** may be coupled to yoke **220** at one end and coupled via a roller bearing **244** to a cross-head **242** at an opposite end such that the ends of control rod **230** are on opposite sides of empennage **150**. In this example, control rod **230** passes through an opening in actuator assembly **210**, through an opening in gearbox **152** (coupled to empennage **150** in FIG. 2B), and through a mast assembly **240**. Teachings of certain embodiments recognize that passing control rod **230** through some or all of these components may achieve packaging benefits. For example, providing actuator assembly **210** on one side of gearbox **152** and providing blades **120'** and the opposite side of gearbox **152** may reduce the distance between blades **120'** and gearbox **152**.

During operation, according to one example embodiment, gearbox **152** provides rotational energy to a rotating mast portion **240a** of mast **240**. Mast portion **240a** transfers at least some of this rotational energy to hub **248**, which causes each blade **120'** to rotate. In the example of FIGS. 2D-2F, each blade **120'** is coupled to hub **248** via a CF bearing **122'**.

Also during operation, according to this example embodiment, actuator assembly **210** extends and retracts yoke **220**, which causes control rod **230** to translate linearly. Linear translation of control rod **230** causes extension and retraction of cross-head **242**, which is coupled to control rod **230** via roller bearing **244**. In the example of FIGS. 2D-2F, mast **240** also includes a mast portion **240b** that rotates with mast portion **240a** and translates with control rod **230**. In this example, mast portion **240b** is coupled to cross-head **242** and causes cross-head **242** to rotate with hub **248**.

A pitch link **246** couples cross-head **242** to hub **248** and/or blade **120'**. In some embodiments, a pitch link **246** may be provided for each blade **120'**, although teachings of certain embodiments recognize that more or fewer pitch links may be used. In operation, extension or retraction of cross-head **242** may cause pitch link **246** to change the deflection angle of blade **120'**. FIG. 2E shows an example of how actuator extension changes the deflection angle of blade **120'**, and FIG. 2F shows an example of how actuator retraction changes the deflection angle of blade **120'**.

Modifications, additions, or omissions may be made to the systems and apparatuses described herein without departing from the scope of the invention. The components of the systems and apparatuses may be integrated or separated. Moreover, the operations of the systems and apparatuses may be performed by more, fewer, or other components. The methods may include more, fewer, or other steps. Additionally, steps may be performed in any suitable order.

Although several embodiments have been illustrated and described in detail, it will be recognized that substitutions and alterations are possible without departing from the spirit and scope of the present invention, as defined by the appended claims.

To aid the Patent Office, and any readers of any patent issued on this application in interpreting the claims appended hereto, applicants wish to note that they do not intend any of the appended claims to invoke paragraph 6 of 35 U.S.C. § 112 as it exists on the date of filing hereof unless the words "means for" or "step for" are explicitly used in the particular claim.

What is claimed is:

1. A rotorcraft, comprising:

a body including an empennage;

a power train coupled to the body and comprising an engine and a drive shaft coupled to the engine;

a rotor system coupled to the power train, the rotor system comprising at least one tail rotor blade and a tail rotor gearbox in mechanical communication with the at least one tail rotor blade and coupled to the empennage; and an actuation system in mechanical communication with the rotor system, the actuation system comprising:

an actuator assembly comprising a first actuator, the first actuator having a first end, a second end, and a body portion disposed between the first end and the second end, the first actuator configured to extend in a first direction and retract in a second direction opposite of the first direction;

a yoke coupled to the first end of the first actuator such that the body portion of the first actuator is oriented away from the yoke, and such that the yoke translates as the first actuator extends in the first direction and retracts in the second direction;

a control rod having a first end, a second end, and a body portion disposed between the first end and the second end, the first end of the control rod coupled to the yoke such that the body portion of the control rod is oriented away from the yoke in the same direction as the body portion of the first actuator, wherein the control rod extends through an opening in the tail rotor gearbox such that the first and second control rod ends extend through opposite sides of the empennage, and

wherein when the first actuator extends in the first direction and retracts in the second direction, a pitch angle of the at least one rotor blade is changed.

2. The rotorcraft of claim 1, wherein the actuator assembly and the at least one tail rotor blade are located on opposite sides of the empennage.

3. The rotorcraft of claim 1, the rotor system further comprising:

a cross-head coupled to the second end of the control rod; and

a pitch link coupled to the cross-head and in mechanical communication with the at least one tail rotor blade.

4. The rotorcraft of claim 3, the cross-head and pitch link operable to change the pitch angle of the at least one tail

5

rotor blade in response to movement of the control rod in the first direction or in the second direction.

5. The rotorcraft of claim 1, the rotor system further comprising a tail rotor mast, the tail rotor mast comprising:

a first portion configured to transfer rotational energy 5
from the tail rotor gearbox to the at least one tail rotor blade; and

a second portion configured to rotate in response to rotation of the cross-head and translate in response to translations of the control rod. 10

6. The rotorcraft of claim 1, further comprising a tail rotor control system operable to change a position of the first actuator in response to a request to change the pitch angle of the at least one tail rotor blade.

7. The rotorcraft of claim 1, wherein the actuator assembly 15
comprises a second actuator and a third actuator, the second actuator and the third actuator coupled to the yoke and configured to extend in the first direction and retract in the second direction opposite of the first direction.

8. A method of actuating a rotor system of a rotorcraft, 20
comprising:

receiving an input; and

changing an actuator output position of an actuator assembly 25
in response to the received input, wherein:

the rotor system comprises at least one tail rotor blade and 25
a tail rotor gearbox coupled to an empennage and in mechanical communication with the at least one tail rotor blade;

the actuator assembly comprises a first actuator, the first 30
actuator having a first end, a second end, and a body portion disposed between the first end and the second end, the first actuator configured to extend in a first direction and retract in a second direction opposite of the first direction;

a yoke is coupled to the first end of the first actuator such 35
that the body portion of the first actuator is oriented away from the yoke;

a control rod has a first end, a second end, and a body portion disposed between the first end and the second end, the first end of the control rod is coupled to the

6

yoke such that the body portion of the control rod is oriented away from the yoke in the same direction as the body portion of the first actuator; and

the second end of the control rod is in mechanical communication with the rotor system such that when the first actuator extends in the first direction and retracts in the second direction, a pitch angle of the at least one rotor blade is changed,

wherein the control rod extends through an opening in the tail rotor gearbox such that the first and second control rod ends extend through opposite sides of the empennage.

9. The method of claim 8, wherein the actuator assembly and the at least one tail rotor blade are located on opposite sides of the empennage.

10. The method of claim 8, wherein the actuator assembly comprises a second actuator and a third actuator, the second actuator and the third actuator coupled to the yoke and configured to extend in the first direction and retract in the second direction opposite of the first direction.

11. The rotorcraft of claim 1, wherein the body portion of the first actuator is substantially adjacent to and substantially parallel to the body portion of the control rod.

12. The method of claim 8, wherein the body portion of the first actuator is substantially adjacent to and substantially parallel to the body portion of the control rod.

13. The rotorcraft of claim 1, wherein the control rod translates as the first actuator extends in the first direction and retracts in the second direction.

14. The method of claim 8, wherein the control rod translates as the first actuator extends in the first direction and retracts in the second direction.

15. The rotorcraft of claim 1, wherein the body portion of the control rod is disposed at least partially within the actuator assembly.

16. The method of claim 8, wherein the body portion of the control rod is disposed at least partially within the actuator assembly.

* * * * *