



US010031523B2

(12) **United States Patent**  
**Ricci et al.**

(10) **Patent No.:** **US 10,031,523 B2**  
(45) **Date of Patent:** **Jul. 24, 2018**

(54) **METHOD AND SYSTEM FOR BEHAVIORAL SHARING IN AUTONOMOUS VEHICLES**

(56) **References Cited**

(71) Applicant: **NIO USA, Inc.**, San Jose, CA (US)

(72) Inventors: **Christopher P. Ricci**, Saratoga, CA (US); **Abhishek Singhal**, Santa Clara, CA (US)

(73) Assignee: **NIO USA, Inc.**, San Jose, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/393,137**

(22) Filed: **Dec. 28, 2016**

(65) **Prior Publication Data**

US 2018/0129204 A1 May 10, 2018

**Related U.S. Application Data**

(60) Provisional application No. 62/418,620, filed on Nov. 7, 2016.

(51) **Int. Cl.**  
**G05D 1/00** (2006.01)  
**G01C 21/26** (2006.01)  
**G05D 1/02** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G05D 1/0088** (2013.01); **G01C 21/26** (2013.01); **G05D 1/0287** (2013.01)

(58) **Field of Classification Search**  
CPC .. G05D 1/0088; G05D 1/0287; G05D 1/0274; G05D 1/0251; G05D 1/0027; G01C 21/26  
USPC ..... 701/23, 301, 28  
See application file for complete search history.

U.S. PATENT DOCUMENTS

4,361,202 A	11/1982	Minovitch
4,476,954 A	10/1984	Johnson et al.
4,754,255 A	6/1988	Sanders et al.
4,875,391 A	10/1989	Leising et al.
5,136,498 A	8/1992	McLaughlin et al.
5,204,817 A	4/1993	Yoshida
5,363,306 A	11/1994	Kuwahara et al.
5,508,689 A	4/1996	Rado et al.
5,521,815 A	5/1996	Rose
5,529,138 A	6/1996	Shaw et al.
5,531,122 A	7/1996	Chatham et al.
5,572,450 A	11/1996	Worthy
5,610,821 A	3/1997	Gazis et al.
5,648,769 A	7/1997	Sato et al.
5,710,702 A	1/1998	Hayashi et al.
5,794,164 A	8/1998	Beckert et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN	1417755	5/2003
CN	1847817	10/2006

(Continued)

OTHER PUBLICATIONS

“Self-Driving: Self-Driving Autonomous Cars,” available at <http://www.automotivetechologies.com/autonomous-self-driving-cars>, accessed Dec. 2016, 9 pages.


(Continued)

*Primary Examiner* — Marthe Y Marc-Coleman  
(74) *Attorney, Agent, or Firm* — Sheridan Ross P.C.

(57) **ABSTRACT**

Systems of an electrical vehicle and the operations thereof are provided that augments learned behaviors of one vehicle with learned behaviors of other vehicles.

**20 Claims, 13 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,797,134 A	8/1998	McMillan et al.	7,295,921 B2	11/2007	Spencer et al.
5,812,067 A	9/1998	Bergholz et al.	7,313,547 B2	12/2007	Mocek et al.
5,825,283 A	10/1998	Camhi	7,333,012 B1	2/2008	Nguyen
5,838,251 A	11/1998	Brinkmeyer et al.	7,343,148 B1	3/2008	O'Neil
5,847,661 A	12/1998	Ricci	7,386,376 B2	6/2008	Basir et al.
5,890,080 A	3/1999	Coverdill et al.	7,386,799 B1	6/2008	Clanton et al.
5,928,294 A	7/1999	Zelinkovsky	7,432,829 B2	10/2008	Poltorak
5,949,345 A	9/1999	Beckert et al.	7,474,264 B2	1/2009	Bolduc et al.
5,983,161 A	11/1999	Lemelson et al.	7,493,140 B2	2/2009	Michmerhuizen et al.
5,986,575 A	11/1999	Jones et al.	7,526,539 B1	4/2009	Hsu
6,038,426 A	3/2000	Williams, Jr.	7,548,815 B2	6/2009	Watkins et al.
6,081,756 A	6/2000	Mio et al.	7,566,083 B2	7/2009	Vitito
D429,684 S	8/2000	Johnson	7,606,660 B2	10/2009	Diaz et al.
6,128,003 A	10/2000	Smith et al.	7,606,867 B1	10/2009	Singhal et al.
6,141,620 A	10/2000	Zyburt et al.	7,643,913 B2	1/2010	Taki et al.
6,148,261 A	11/2000	Obradovich et al.	7,650,234 B2	1/2010	Obradovich et al.
6,152,514 A	11/2000	McLellen	7,671,764 B2	3/2010	Uyeki et al.
6,157,321 A	12/2000	Ricci	7,680,596 B2	3/2010	Uyeki et al.
6,198,996 B1	3/2001	Berstis	7,683,771 B1	3/2010	Loeb
6,199,001 B1	3/2001	Ohta et al.	7,711,468 B1	5/2010	Levy
6,202,008 B1	3/2001	Beckert et al.	7,734,315 B2	6/2010	Rathus et al.
6,252,544 B1	6/2001	Hoffberg	7,748,021 B2	6/2010	Obradovich et al.
6,267,428 B1	7/2001	Baldas et al.	RE41,449 E	7/2010	Krahnstoever et al.
6,302,438 B1	10/2001	Stopper, Jr. et al.	7,791,499 B2	9/2010	Mohan et al.
6,310,542 B1	10/2001	Gehlot	7,796,190 B2	9/2010	Basso et al.
6,317,058 B1	11/2001	Lemelson et al.	7,802,832 B2	9/2010	Carnevali
6,339,826 B2	1/2002	Hayes, Jr. et al.	7,821,421 B2	10/2010	Tamir et al.
6,356,838 B1	3/2002	Paul	7,832,762 B2	11/2010	Breed
6,388,579 B1	5/2002	Adcox et al.	7,864,073 B2	1/2011	Lee et al.
6,480,224 B1	11/2002	Brown	7,872,591 B2	1/2011	Kane et al.
6,502,022 B1	12/2002	Chastain et al.	7,873,471 B2	1/2011	Gieseke
6,519,519 B1	2/2003	Stopczynski	7,881,703 B2	2/2011	Roundtree et al.
6,557,752 B1	5/2003	Yacoub	7,891,004 B1	2/2011	Gelvin et al.
6,563,910 B2	5/2003	Menard et al.	7,891,719 B2	2/2011	Carnevali
6,587,739 B1	7/2003	Abrams et al.	7,899,610 B2	3/2011	McClellan
6,598,227 B1	7/2003	Berry et al.	7,966,678 B2	6/2011	Ten Eyck et al.
6,607,212 B1	8/2003	Reimer et al.	7,969,290 B2	6/2011	Waeler et al.
6,617,981 B2	9/2003	Basinger	7,969,324 B2	6/2011	Chevion et al.
6,662,077 B2	12/2003	Haag	8,060,631 B2	11/2011	Collart et al.
6,675,081 B2	1/2004	Shuman et al.	8,064,925 B1	11/2011	Sun et al.
6,678,747 B2	1/2004	Goossen et al.	8,066,313 B2	11/2011	Carnevali
6,681,176 B2	1/2004	Funk et al.	8,098,170 B1	1/2012	Szczerba et al.
6,690,260 B1	2/2004	Ashihara	8,113,564 B2	2/2012	Carnevali
6,690,940 B1	2/2004	Brown et al.	8,131,419 B2	3/2012	Ampunan et al.
6,724,920 B1	4/2004	Berenz et al.	8,157,310 B2	4/2012	Carnevali
6,754,580 B1	6/2004	Ask et al.	8,162,368 B2	4/2012	Carnevali
6,757,593 B2	6/2004	Mori et al.	8,175,802 B2	5/2012	Forstall et al.
6,762,684 B1	7/2004	Camhi	8,233,919 B2	7/2012	Haag et al.
6,765,495 B1	7/2004	Dunning et al.	8,245,609 B1	8/2012	Greenwald et al.
6,778,888 B2	8/2004	Cataldo et al.	8,306,514 B1	11/2012	Nunally
6,782,240 B1	8/2004	Tabe	8,334,847 B2	12/2012	Tomkins
6,785,531 B2	8/2004	Lepley et al.	8,346,233 B2	1/2013	Aaron et al.
6,816,783 B2	11/2004	Hashima et al.	8,346,432 B2	1/2013	Van Wiemeersch et al.
6,816,971 B2	11/2004	Schmidt et al.	8,350,721 B2	1/2013	Carr
6,820,259 B1	11/2004	Kawamata et al.	8,352,282 B2	1/2013	Jensen et al.
6,944,533 B2	9/2005	Obradovich et al.	8,369,263 B2	2/2013	Dowling et al.
6,950,022 B2	9/2005	Breed	8,417,449 B1	4/2013	Denise
6,958,707 B1	10/2005	Siegel	8,432,260 B2	4/2013	Talty et al.
6,992,580 B2	1/2006	Kotzin et al.	8,442,389 B2	5/2013	Kashima et al.
7,019,641 B1	3/2006	Lakshmanan et al.	8,442,758 B1	5/2013	Rovik et al.
7,020,544 B2	3/2006	Shinada et al.	8,467,965 B2	6/2013	Chang
7,021,691 B1	4/2006	Schmidt et al.	8,497,842 B2	7/2013	Tomkins et al.
7,042,345 B2	5/2006	Ellis	8,498,809 B2	7/2013	Bill
7,047,129 B2	5/2006	Uotani	8,509,982 B2	8/2013	Montemerlo et al.
7,058,898 B2	6/2006	McWalter et al.	8,521,410 B2	8/2013	Mizuno et al.
7,096,431 B2	8/2006	Tambata et al.	8,527,143 B2	9/2013	Tan
7,142,696 B1	11/2006	Engelsberg et al.	8,527,146 B1	9/2013	Jackson et al.
7,164,117 B2	1/2007	Breed et al.	8,532,574 B2	9/2013	Kirsch
7,187,947 B1	3/2007	White et al.	8,543,330 B2	9/2013	Taylor et al.
7,203,598 B1	4/2007	Whitsell	8,547,340 B2	10/2013	Sizelove et al.
7,233,861 B2	6/2007	Van Buer et al.	8,548,669 B2	10/2013	Naylor
7,239,960 B2	7/2007	Yokota et al.	8,559,183 B1	10/2013	Davis
7,277,454 B2	10/2007	Mocek et al.	8,577,600 B1	11/2013	Pierfelice
7,284,769 B2	10/2007	Breed	8,578,279 B2	11/2013	Chen et al.
7,289,645 B2	10/2007	Yamamoto et al.	8,583,292 B2	11/2013	Preston et al.
			8,589,073 B2	11/2013	Guha et al.
			8,600,611 B2	12/2013	Seize
			8,613,385 B1	12/2013	Hulet et al.
			8,621,645 B1	12/2013	Spackman

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,624,727 B2	1/2014	Saigh et al.	9,235,941 B2	1/2016	Ricci et al.
8,634,984 B2	1/2014	Sumizawa	9,240,018 B2	1/2016	Ricci
8,644,165 B2	2/2014	Saarimaki et al.	9,296,299 B2	3/2016	Ricci
8,660,735 B2	2/2014	Tengler et al.	9,305,411 B2	4/2016	Ricci
8,671,068 B2	3/2014	Harber et al.	9,317,983 B2	4/2016	Ricci
8,688,372 B2	4/2014	Bhogal et al.	9,324,234 B2	4/2016	Ricci et al.
8,705,527 B1	4/2014	Addepalli et al.	9,330,567 B2	5/2016	Ricci
8,706,143 B1	4/2014	Elias	9,349,234 B2	5/2016	Ricci
8,718,797 B1	5/2014	Addepalli et al.	9,373,207 B2	6/2016	Ricci et al.
8,725,311 B1	5/2014	Breed	9,378,601 B2	6/2016	Ricci
8,730,033 B2	5/2014	Yarnold et al.	9,378,602 B2	6/2016	Ricci et al.
8,737,986 B2	5/2014	Rhoads et al.	9,384,609 B2	7/2016	Ricci
8,761,673 B2	6/2014	Sakata	9,412,273 B2	8/2016	Ricci
8,774,842 B2	7/2014	Jones et al.	9,524,597 B2	12/2016	Ricci
8,779,947 B2	7/2014	Tengler et al.	9,536,361 B2	1/2017	Ricci
8,782,262 B2	7/2014	Collart et al.	2001/0010516 A1	8/2001	Roh et al.
8,793,034 B2	7/2014	Ricci	2001/0015888 A1	8/2001	Shaler et al.
8,793,065 B2	7/2014	Seltzer et al.	2002/0009978 A1	1/2002	Dukach et al.
8,798,918 B2	8/2014	Onishi et al.	2002/0023010 A1	2/2002	Rittmaster et al.
8,805,110 B2	8/2014	Rhoads et al.	2002/0026278 A1	2/2002	Feldman et al.
8,812,171 B2	8/2014	Fillev et al.	2002/0045484 A1	4/2002	Eck et al.
8,817,761 B2	8/2014	Gruberman et al.	2002/0065046 A1	5/2002	Mankins et al.
8,818,725 B2	8/2014	Ricci	2002/0077985 A1	6/2002	Kobata et al.
8,825,031 B2	9/2014	Aaron et al.	2002/0095249 A1	7/2002	Lang
8,825,277 B2	9/2014	McClellan et al.	2002/0097145 A1	7/2002	Tumey et al.
8,825,382 B2	9/2014	Liu	2002/0103622 A1	8/2002	Burge
8,826,261 B1	9/2014	Anand et al.	2002/0105968 A1	8/2002	Pruzan et al.
8,831,826 B2	9/2014	Ricci	2002/0126876 A1	9/2002	Paul et al.
8,838,088 B1	9/2014	Henn et al.	2002/0128774 A1	9/2002	Takezaki et al.
8,862,299 B2	10/2014	Ricci	2002/0143461 A1	10/2002	Burns et al.
8,862,317 B2	10/2014	Shin et al.	2002/0143643 A1	10/2002	Catan
8,919,848 B2	12/2014	Ricci	2002/0152010 A1	10/2002	Colmenarez et al.
8,922,393 B2	12/2014	Ricci	2002/0154217 A1	10/2002	Ikeda
8,949,823 B2	2/2015	Ricci	2002/0169551 A1	11/2002	Inoue et al.
8,977,408 B1	3/2015	Cazanas et al.	2002/0174021 A1	11/2002	Chu et al.
8,979,159 B2	3/2015	Ricci	2003/0004624 A1	1/2003	Wilson et al.
8,983,718 B2	3/2015	Ricci	2003/0007227 A1	1/2003	Ogino
8,995,982 B2	3/2015	Ricci	2003/0055557 A1	3/2003	Dutta et al.
9,008,856 B2	4/2015	Ricci et al.	2003/0060937 A1	3/2003	Shinada et al.
9,008,906 B2	4/2015	Ricci	2003/0065432 A1	4/2003	Shuman et al.
9,014,911 B2	4/2015	Ricci	2003/0101451 A1	5/2003	Bentolila et al.
9,020,491 B2	4/2015	Ricci	2003/0109972 A1	6/2003	Tak
9,020,697 B2	4/2015	Ricci et al.	2003/0125846 A1	7/2003	Yu et al.
9,043,016 B2	5/2015	Filippov et al.	2003/0132666 A1	7/2003	Bond et al.
9,043,073 B2	5/2015	Ricci	2003/0149530 A1	8/2003	Stopczynski
9,043,130 B2	5/2015	Ricci	2003/0158638 A1	8/2003	Yakes et al.
9,046,374 B2	6/2015	Ricci	2003/0182435 A1	9/2003	Redlich et al.
9,055,022 B2	6/2015	Ricci	2003/0202683 A1	10/2003	Ma et al.
9,058,703 B2	6/2015	Ricci	2003/0204290 A1	10/2003	Sadler et al.
9,079,497 B2	7/2015	Ricci	2003/0230443 A1	12/2003	Cramer et al.
9,081,653 B2	7/2015	Ricci et al.	2004/0017292 A1	1/2004	Reese et al.
9,082,238 B2	7/2015	Ricci	2004/0024502 A1	2/2004	Squires et al.
9,082,239 B2	7/2015	Ricci	2004/0036622 A1	2/2004	Dukach et al.
9,088,572 B2	7/2015	Ricci	2004/0039500 A1	2/2004	Amendola et al.
9,098,367 B2	8/2015	Ricci	2004/0039504 A1	2/2004	Coffee et al.
9,105,051 B2	8/2015	Ricci	2004/0068364 A1	4/2004	Zhao et al.
9,116,786 B2	8/2015	Ricci	2004/0070920 A1	4/2004	Flueli
9,117,318 B2	8/2015	Ricci	2004/0093155 A1	5/2004	Simonds et al.
9,123,058 B2	9/2015	Ricci	2004/0117494 A1	6/2004	Mitchell et al.
9,123,186 B2	9/2015	Ricci	2004/0128062 A1	7/2004	Ogino et al.
9,135,764 B2	9/2015	Ricci	2004/0153356 A1	8/2004	Lockwood et al.
9,140,560 B2	9/2015	Ricci	2004/0162019 A1	8/2004	Horita et al.
9,142,071 B2	9/2015	Ricci	2004/0180653 A1	9/2004	Royalty
9,142,072 B2	9/2015	Ricci	2004/0182574 A1	9/2004	Adnan et al.
9,147,296 B2	9/2015	Ricci	2004/0193347 A1	9/2004	Harumoto et al.
9,147,297 B2	9/2015	Ricci	2004/0203974 A1	10/2004	Seibel
9,147,298 B2	9/2015	Ricci	2004/0204837 A1	10/2004	Singleton
9,153,084 B2	10/2015	Ricci	2004/0209594 A1	10/2004	Naboulsi
9,159,232 B2	10/2015	Ricci	2004/0217850 A1	11/2004	Perttunen et al.
9,173,100 B2	10/2015	Ricci	2004/0225557 A1	11/2004	Phelan et al.
9,176,924 B2	11/2015	Ricci	2004/0255123 A1	12/2004	Noyama et al.
9,183,685 B2	11/2015	Ricci	2004/0257208 A1	12/2004	Huang et al.
9,218,698 B2	12/2015	Ricci	2004/0260470 A1	12/2004	Rast
9,229,905 B1	1/2016	Penilla et al.	2005/0012599 A1	1/2005	DeMatteo
9,230,379 B2	1/2016	Ricci	2005/0031100 A1	2/2005	Iggulden et al.
			2005/0038598 A1	2/2005	Oesterling et al.
			2005/0042999 A1	2/2005	Rappaport
			2005/0065678 A1	3/2005	Smith et al.
			2005/0065711 A1	3/2005	Dahlgren et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2005/0086051	A1	4/2005	Brulle-Drews	2007/0276596	A1	11/2007	Solomon et al.
2005/0093717	A1	5/2005	Lilja	2007/0280505	A1	12/2007	Breed
2005/0097541	A1	5/2005	Holland	2008/0005974	A1	1/2008	Delgado Vazquez et al.
2005/0114864	A1	5/2005	Surace	2008/0023253	A1	1/2008	Prost-Fin et al.
2005/0122235	A1	6/2005	Teffer et al.	2008/0027337	A1	1/2008	Dugan et al.
2005/0124211	A1	6/2005	Diessner et al.	2008/0033635	A1	2/2008	Obradovich et al.
2005/0130744	A1	6/2005	Eck et al.	2008/0042824	A1	2/2008	Kates
2005/0144156	A1	6/2005	Barber	2008/0051957	A1	2/2008	Breed et al.
2005/0149752	A1	7/2005	Johnson et al.	2008/0052627	A1	2/2008	Oguchi
2005/0153760	A1	7/2005	Varley	2008/0071465	A1	3/2008	Chapman et al.
2005/0159853	A1	7/2005	Takahashi et al.	2008/0082237	A1	4/2008	Breed
2005/0159892	A1	7/2005	Chung	2008/0086455	A1	4/2008	Meisels et al.
2005/0192727	A1	9/2005	Shostak et al.	2008/0090522	A1	4/2008	Oyama
2005/0197748	A1	9/2005	Holst et al.	2008/0104227	A1	5/2008	Birnie et al.
2005/0197767	A1	9/2005	Nortrup	2008/0119994	A1	5/2008	Kameyama
2005/0251324	A1	11/2005	Wiener et al.	2008/0129475	A1	6/2008	Breed et al.
2005/0261815	A1	11/2005	Cowelchuk et al.	2008/0143085	A1	6/2008	Breed et al.
2005/0278093	A1	12/2005	Kameyama	2008/0147280	A1	6/2008	Breed
2005/0283284	A1	12/2005	Grenier et al.	2008/0148374	A1	6/2008	Spaur et al.
2006/0015819	A1	1/2006	Hawkins et al.	2008/0154712	A1	6/2008	Wellman
2006/0036358	A1	2/2006	Hale et al.	2008/0154957	A1	6/2008	Taylor et al.
2006/0044119	A1	3/2006	Egelhaaf	2008/0161986	A1	7/2008	Breed
2006/0047386	A1	3/2006	Kanevsky et al.	2008/0164985	A1	7/2008	Iketani et al.
2006/0058948	A1	3/2006	Blass et al.	2008/0169940	A1	7/2008	Lee et al.
2006/0059229	A1	3/2006	Bain et al.	2008/0174451	A1	7/2008	Harrington et al.
2006/0125631	A1	6/2006	Sharony	2008/0212215	A1	9/2008	Schofield et al.
2006/0130033	A1	6/2006	Stoffels et al.	2008/0216067	A1	9/2008	Villing
2006/0142933	A1	6/2006	Feng	2008/0228358	A1	9/2008	Wang et al.
2006/0173841	A1	8/2006	Bill	2008/0234919	A1	9/2008	Ritter et al.
2006/0175403	A1	8/2006	McConnell et al.	2008/0252487	A1	10/2008	McClellan et al.
2006/0184319	A1	8/2006	Seick et al.	2008/0253613	A1	10/2008	Jones et al.
2006/0212909	A1	9/2006	Girard et al.	2008/0255721	A1	10/2008	Yamada
2006/0241836	A1	10/2006	Kachouh et al.	2008/0255722	A1	10/2008	McClellan et al.
2006/0243056	A1	11/2006	Sundermeyer et al.	2008/0269958	A1	10/2008	Filev et al.
2006/0250272	A1	11/2006	Puamau	2008/0281508	A1	11/2008	Fu
2006/0253307	A1	11/2006	Warren et al.	2008/0300778	A1	12/2008	Kuznetsov
2006/0259210	A1	11/2006	Tanaka et al.	2008/0305780	A1	12/2008	Williams et al.
2006/0274829	A1	12/2006	Siemens et al.	2008/0319602	A1	12/2008	McClellan et al.
2006/0282204	A1	12/2006	Breed	2009/0006525	A1	1/2009	Moore
2006/0287807	A1	12/2006	Teffer	2009/0024419	A1	1/2009	McClellan et al.
2006/0287865	A1	12/2006	Cross et al.	2009/0037719	A1	2/2009	Sakthikumar et al.
2006/0288382	A1	12/2006	Vitito	2009/0040026	A1	2/2009	Tanaka
2006/0290516	A1	12/2006	Muehlsteff et al.	2009/0055178	A1	2/2009	Coon
2007/0001831	A1	1/2007	Raz et al.	2009/0082951	A1	3/2009	Graessley
2007/0002032	A1	1/2007	Powers et al.	2009/0099720	A1	4/2009	Elgali
2007/0010942	A1	1/2007	Bill	2009/0112393	A1	4/2009	Maten et al.
2007/0015485	A1	1/2007	DeBiasio et al.	2009/0112452	A1	4/2009	Buck et al.
2007/0028370	A1	2/2007	Seng	2009/0119657	A1	5/2009	Link, II
2007/0032225	A1	2/2007	Konicek et al.	2009/0125174	A1	5/2009	Delean
2007/0057781	A1	3/2007	Breed	2009/0132294	A1	5/2009	Haines
2007/0061057	A1	3/2007	Huang et al.	2009/0138336	A1	5/2009	Ashley et al.
2007/0067614	A1	3/2007	Berry et al.	2009/0144622	A1	6/2009	Evans et al.
2007/0069880	A1	3/2007	Best et al.	2009/0157312	A1	6/2009	Black et al.
2007/0083298	A1	4/2007	Pierce et al.	2009/0158200	A1	6/2009	Palahnuk et al.
2007/0088488	A1	4/2007	Reeves et al.	2009/0180668	A1	7/2009	Jones et al.
2007/0103328	A1	5/2007	Lakshmanan et al.	2009/0189373	A1	7/2009	Schramm et al.
2007/0115101	A1	5/2007	Creekbaum et al.	2009/0189979	A1	7/2009	Smyth
2007/0118301	A1	5/2007	Andarawis et al.	2009/0195370	A1	8/2009	Huffman et al.
2007/0120697	A1	5/2007	Ayoub et al.	2009/0210257	A1	8/2009	Chalfant et al.
2007/0135995	A1	6/2007	Kikuchi et al.	2009/0216935	A1	8/2009	Flick
2007/0156317	A1	7/2007	Breed	2009/0222200	A1	9/2009	Link et al.
2007/0182625	A1	8/2007	Kerai et al.	2009/0224931	A1	9/2009	Dietz et al.
2007/0182816	A1	8/2007	Fox	2009/0224942	A1	9/2009	Goudy et al.
2007/0185969	A1	8/2007	Davis	2009/0234578	A1	9/2009	Newby et al.
2007/0192486	A1	8/2007	Wilson et al.	2009/0241883	A1	10/2009	Nagoshi et al.
2007/0194902	A1	8/2007	Blanco et al.	2009/0254446	A1	10/2009	Chernyak
2007/0194944	A1	8/2007	Galera et al.	2009/0264849	A1	10/2009	La Croix
2007/0195997	A1	8/2007	Paul et al.	2009/0275321	A1	11/2009	Crowe
2007/0200663	A1	8/2007	White et al.	2009/0278750	A1	11/2009	Man et al.
2007/0208860	A1	9/2007	Zellner et al.	2009/0278915	A1	11/2009	Kramer et al.
2007/0213090	A1	9/2007	Holmberg	2009/0279839	A1	11/2009	Nakamura et al.
2007/0228826	A1	10/2007	Jordan et al.	2009/0284359	A1	11/2009	Huang et al.
2007/0233341	A1	10/2007	Logsdon	2009/0287405	A1	11/2009	Liu et al.
2007/0250228	A1	10/2007	Reddy et al.	2009/0299572	A1	12/2009	Fujikawa et al.
2007/0257815	A1	11/2007	Gunderson et al.	2009/0312998	A1	12/2009	Berckmans et al.
				2009/0319181	A1	12/2009	Khosravy et al.
				2010/0008053	A1	1/2010	Osternack et al.
				2010/0023204	A1	1/2010	Basir et al.
				2010/0035620	A1	2/2010	Naden et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2010/0036560	A1	2/2010	Wright et al.
2010/0042498	A1	2/2010	Schalk
2010/0052945	A1	3/2010	Breed
2010/0057337	A1	3/2010	Fuchs
2010/0066498	A1	3/2010	Fenton
2010/0069115	A1	3/2010	Liu
2010/0070338	A1	3/2010	Siotia et al.
2010/0077094	A1	3/2010	Howarter et al.
2010/0087987	A1	4/2010	Huang et al.
2010/0090817	A1	4/2010	Yamaguchi et al.
2010/0097178	A1	4/2010	Pisz et al.
2010/0097239	A1	4/2010	Campbell et al.
2010/0097458	A1	4/2010	Zhang et al.
2010/0106344	A1	4/2010	Edwards et al.
2010/0106418	A1	4/2010	Kindo et al.
2010/0118025	A1	5/2010	Smith et al.
2010/0121570	A1	5/2010	Tokue et al.
2010/0121645	A1	5/2010	Seitz et al.
2010/0125387	A1	5/2010	Sehyun et al.
2010/0125405	A1	5/2010	Chae et al.
2010/0125811	A1	5/2010	Moore et al.
2010/0127847	A1	5/2010	Evans et al.
2010/0131300	A1	5/2010	Collopy et al.
2010/0134958	A1	6/2010	Disaverio et al.
2010/0136944	A1	6/2010	Taylor et al.
2010/0137037	A1	6/2010	Basir
2010/0144284	A1	6/2010	Chutorash et al.
2010/0145700	A1	6/2010	Kennewick et al.
2010/0145987	A1	6/2010	Harper et al.
2010/0152976	A1	6/2010	White et al.
2010/0169432	A1	7/2010	Santori et al.
2010/0174474	A1	7/2010	Nagase
2010/0179712	A1	7/2010	Pepitone et al.
2010/0185341	A1	7/2010	Wilson et al.
2010/0188831	A1	7/2010	Ortel
2010/0197359	A1	8/2010	Harris
2010/0202346	A1	8/2010	Sitzes et al.
2010/0211259	A1	8/2010	McClellan
2010/0211282	A1	8/2010	Nakata et al.
2010/0211300	A1	8/2010	Jaffe et al.
2010/0211304	A1	8/2010	Hwang et al.
2010/0211441	A1	8/2010	Sprigg et al.
2010/0217458	A1	8/2010	Schweiger et al.
2010/0222939	A1	9/2010	Namburu et al.
2010/0228404	A1	9/2010	Link et al.
2010/0234071	A1	9/2010	Shabtay et al.
2010/0235042	A1	9/2010	Ying
2010/0235744	A1	9/2010	Schultz
2010/0235891	A1	9/2010	Oglesbee et al.
2010/0250071	A1	9/2010	Pala et al.
2010/0253493	A1	10/2010	Szczerba et al.
2010/0256836	A1	10/2010	Mudalige
2010/0265104	A1	10/2010	Zlojutro
2010/0268426	A1	10/2010	Pathak et al.
2010/0274410	A1	10/2010	Tsien et al.
2010/0280751	A1	11/2010	Breed
2010/0287303	A1	11/2010	Smith et al.
2010/0289632	A1	11/2010	Seder et al.
2010/0289643	A1	11/2010	Trundle et al.
2010/0291427	A1	11/2010	Zhou
2010/0295676	A1	11/2010	Khachaturov et al.
2010/0304640	A1	12/2010	Sofman et al.
2010/0305807	A1	12/2010	Basir et al.
2010/0306080	A1	12/2010	Trandal et al.
2010/0306309	A1	12/2010	Santori et al.
2010/0306435	A1	12/2010	Nigoghosian et al.
2010/0315218	A1	12/2010	Cades et al.
2010/0321151	A1	12/2010	Matsuura et al.
2010/0325626	A1	12/2010	Greschler et al.
2010/0332130	A1	12/2010	Shimizu et al.
2011/0015853	A1	1/2011	DeKock et al.
2011/0018736	A1	1/2011	Carr
2011/0021213	A1	1/2011	Carr
2011/0021234	A1	1/2011	Tibbits et al.
2011/0028138	A1	2/2011	Davies-Moore et al.
2011/0035098	A1	2/2011	Goto et al.
2011/0035141	A1	2/2011	Barker et al.
2011/0040438	A1	2/2011	Kluge et al.
2011/0050589	A1	3/2011	Yan et al.
2011/0053506	A1	3/2011	Lemke et al.
2011/0077808	A1	3/2011	Hyde et al.
2011/0078024	A1	3/2011	Messier et al.
2011/0080282	A1	4/2011	Kleve et al.
2011/0082615	A1	4/2011	Small et al.
2011/0084824	A1	4/2011	Tewari et al.
2011/0090078	A1	4/2011	Kim et al.
2011/0092159	A1	4/2011	Park et al.
2011/0093154	A1	4/2011	Moinzadeh et al.
2011/0093158	A1	4/2011	Theisen et al.
2011/0093438	A1	4/2011	Poulsen
2011/0093846	A1	4/2011	Moinzadeh et al.
2011/0105097	A1	5/2011	Tadayon et al.
2011/0106375	A1	5/2011	Sundaram et al.
2011/0112717	A1	5/2011	Resner
2011/0112969	A1	5/2011	Zaid et al.
2011/0117933	A1	5/2011	Andersson
2011/0119344	A1	5/2011	Eustis
2011/0130915	A1	6/2011	Wright et al.
2011/0134749	A1	6/2011	Speks et al.
2011/0137520	A1	6/2011	Rector et al.
2011/0145331	A1	6/2011	Christie et al.
2011/0172873	A1	7/2011	Szwabowski et al.
2011/0175754	A1	7/2011	Karpinsky
2011/0183658	A1	7/2011	Zellner
2011/0187520	A1	8/2011	Filev et al.
2011/0193707	A1	8/2011	Ngo
2011/0193726	A1	8/2011	Szwabowski et al.
2011/0195699	A1	8/2011	Tadayon et al.
2011/0197187	A1	8/2011	Roh
2011/0205047	A1	8/2011	Patel et al.
2011/0209079	A1	8/2011	Tarte et al.
2011/0210867	A1	9/2011	Benedikt
2011/0212717	A1	9/2011	Rhoads et al.
2011/0221656	A1	9/2011	Haddick et al.
2011/0224865	A1	9/2011	Gordon et al.
2011/0224898	A1	9/2011	Scotfield et al.
2011/0225527	A1	9/2011	Law et al.
2011/0227757	A1	9/2011	Chen et al.
2011/0231091	A1	9/2011	Gourlay et al.
2011/0234369	A1	9/2011	Cai et al.
2011/0245999	A1	10/2011	Kordonowy
2011/0246210	A1	10/2011	Matsur
2011/0247013	A1	10/2011	Feller et al.
2011/0251734	A1	10/2011	Schepp et al.
2011/0257973	A1	10/2011	Chutorash et al.
2011/0267204	A1	11/2011	Chuang et al.
2011/0267205	A1	11/2011	McClellan et al.
2011/0286676	A1	11/2011	El Dokor
2011/0291886	A1	12/2011	Krieter
2011/0291926	A1	12/2011	Gokturk et al.
2011/0298808	A1	12/2011	Rovik
2011/0301844	A1	12/2011	Aono
2011/0307354	A1	12/2011	Erman et al.
2011/0307570	A1	12/2011	Speks
2011/0309926	A1	12/2011	Eikelenberg et al.
2011/0309953	A1	12/2011	Petite et al.
2011/0313653	A1	12/2011	Lindner
2011/0320089	A1	12/2011	Lewis
2012/0006610	A1	1/2012	Wallace et al.
2012/0010807	A1	1/2012	Zhou
2012/0016581	A1	1/2012	Mochizuki et al.
2012/0029852	A1	2/2012	Goff et al.
2012/0030002	A1	2/2012	Bous et al.
2012/0030512	A1	2/2012	Wadhwa et al.
2012/0038489	A1	2/2012	Goldshmidt
2012/0046822	A1	2/2012	Anderson
2012/0047530	A1	2/2012	Shkedi
2012/0053793	A1	3/2012	Sala et al.
2012/0053888	A1	3/2012	Stahlin et al.
2012/0059789	A1	3/2012	Sakai et al.
2012/0065815	A1	3/2012	Hess
2012/0065834	A1	3/2012	Senart
2012/0068956	A1	3/2012	Jira et al.
2012/0071097	A1	3/2012	Matsushita et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2012/0072244	A1	3/2012	Collins et al.	2013/0083805	A1	4/2013	Lu et al.
2012/0074770	A1	3/2012	Lee	2013/0085787	A1	4/2013	Gore et al.
2012/0083960	A1	4/2012	Zhu et al.	2013/0086164	A1	4/2013	Wheeler et al.
2012/0083971	A1	4/2012	Preston	2013/0099915	A1	4/2013	Prasad et al.
2012/0084773	A1	4/2012	Lee et al.	2013/0103196	A1	4/2013	Monceaux et al.
2012/0089299	A1	4/2012	Breed	2013/0116882	A1	5/2013	Link et al.
2012/0092251	A1	4/2012	Hashimoto et al.	2013/0116915	A1	5/2013	Ferreira et al.
2012/0101876	A1	4/2012	Truvey et al.	2013/0139140	A1	5/2013	Rao et al.
2012/0101914	A1	4/2012	Kumar et al.	2013/0144459	A1	6/2013	Ricci
2012/0105613	A1	5/2012	Weng et al.	2013/0144657	A1	6/2013	Ricci
2012/0106114	A1	5/2012	Caron et al.	2013/0145065	A1	6/2013	Ricci
2012/0109446	A1	5/2012	Yousefi et al.	2013/0145279	A1	6/2013	Ricci
2012/0109451	A1	5/2012	Tan	2013/0145297	A1	6/2013	Ricci et al.
2012/0110356	A1	5/2012	Yousefi et al.	2013/0145360	A1	6/2013	Ricci
2012/0113822	A1	5/2012	Letner	2013/0145401	A1	6/2013	Ricci
2012/0115446	A1	5/2012	Guatama et al.	2013/0145482	A1	6/2013	Ricci et al.
2012/0116609	A1	5/2012	Jung et al.	2013/0151065	A1	6/2013	Ricci
2012/0116678	A1	5/2012	Witmer	2013/0151088	A1	6/2013	Ricci
2012/0116696	A1	5/2012	Wank	2013/0151288	A1	6/2013	Bowne et al.
2012/0146766	A1	6/2012	Geisler et al.	2013/0152003	A1	6/2013	Ricci et al.
2012/0146809	A1	6/2012	Oh et al.	2013/0157640	A1	6/2013	Aycock
2012/0149341	A1	6/2012	Tadayon et al.	2013/0157647	A1	6/2013	Kolodziej
2012/0150651	A1	6/2012	Hoffberg et al.	2013/0158778	A1	6/2013	Tengler et al.
2012/0155636	A1	6/2012	Muthaiah	2013/0166096	A1	6/2013	Jotanovic
2012/0158436	A1	6/2012	Bauer et al.	2013/0166098	A1	6/2013	Lavie et al.
2012/0173900	A1	7/2012	Diab et al.	2013/0166152	A1	6/2013	Butterworth
2012/0173905	A1	7/2012	Diab et al.	2013/0166208	A1	6/2013	Forstall et al.
2012/0179325	A1	7/2012	Faenger	2013/0173531	A1	7/2013	Rinearson et al.
2012/0179547	A1	7/2012	Besore et al.	2013/0179689	A1	7/2013	Matsumoto et al.
2012/0188876	A1	7/2012	Chow et al.	2013/0190978	A1	7/2013	Kato et al.
2012/0197523	A1	8/2012	Kirsch	2013/0194108	A1	8/2013	Lapiotis et al.
2012/0197669	A1	8/2012	Kote et al.	2013/0197796	A1	8/2013	Obradovich et al.
2012/0204166	A1	8/2012	Ichihara	2013/0198031	A1	8/2013	Mitchell et al.
2012/0210160	A1	8/2012	Fuhrman	2013/0200991	A1	8/2013	Ricci et al.
2012/0215375	A1	8/2012	Chang	2013/0203400	A1	8/2013	Ricci
2012/0217928	A1	8/2012	Kulidjian	2013/0204455	A1	8/2013	Chia et al.
2012/0218125	A1	8/2012	Demirdjian et al.	2013/0204457	A1	8/2013	King
2012/0226413	A1	9/2012	Chen et al.	2013/0205026	A1	8/2013	Ricci
2012/0238286	A1	9/2012	Mallavarapu et al.	2013/0205412	A1	8/2013	Ricci
2012/0239242	A1	9/2012	Uehara	2013/0207794	A1	8/2013	Patel et al.
2012/0242510	A1	9/2012	Choi et al.	2013/0212065	A1	8/2013	Rahnama
2012/0254763	A1	10/2012	Protopapas et al.	2013/0212659	A1	8/2013	Maher et al.
2012/0254804	A1	10/2012	Shema et al.	2013/0215116	A1	8/2013	Siddique et al.
2012/0259951	A1	10/2012	Schalk et al.	2013/0218445	A1	8/2013	Basir
2012/0265359	A1	10/2012	Das	2013/0219039	A1	8/2013	Ricci
2012/0274459	A1	11/2012	Jaisimha et al.	2013/0226365	A1	8/2013	Brozovich
2012/0274481	A1	11/2012	Ginsberg et al.	2013/0226371	A1	8/2013	Rovik et al.
2012/0284292	A1	11/2012	Rechsteiner et al.	2013/0226392	A1	8/2013	Schneider et al.
2012/0289217	A1	11/2012	Reimer et al.	2013/0226449	A1	8/2013	Rovik et al.
2012/0289253	A1	11/2012	Haag et al.	2013/0226622	A1	8/2013	Adamson et al.
2012/0296567	A1	11/2012	Breed	2013/0231784	A1	9/2013	Rovik et al.
2012/0313771	A1	12/2012	Wottliff, III	2013/0231800	A1	9/2013	Ricci
2012/0316720	A1	12/2012	Hyde et al.	2013/0232142	A1	9/2013	Nielsen et al.
2012/0317561	A1	12/2012	Aslam et al.	2013/0238165	A1	9/2013	Garrett et al.
2012/0323413	A1	12/2012	Kedar-Dongarkar et al.	2013/0241720	A1	9/2013	Ricci et al.
2012/0327231	A1	12/2012	Cochran et al.	2013/0245882	A1	9/2013	Ricci
2013/0005263	A1	1/2013	Sakata	2013/0250933	A1	9/2013	Yousefi et al.
2013/0005414	A1	1/2013	Bindra et al.	2013/0261871	A1	10/2013	Hobbs et al.
2013/0013157	A1	1/2013	Kim et al.	2013/0261966	A1	10/2013	Wang et al.
2013/0019252	A1	1/2013	Haase et al.	2013/0265178	A1	10/2013	Tengler et al.
2013/0024060	A1	1/2013	Sukkarie et al.	2013/0274997	A1	10/2013	Chien
2013/0030645	A1	1/2013	Divine et al.	2013/0279111	A1	10/2013	Lee
2013/0030811	A1	1/2013	Olleon et al.	2013/0279491	A1	10/2013	Rubin et al.
2013/0031540	A1	1/2013	Throop et al.	2013/0282238	A1	10/2013	Ricci et al.
2013/0031541	A1	1/2013	Wilks et al.	2013/0282357	A1	10/2013	Rubin et al.
2013/0035063	A1	2/2013	Fisk et al.	2013/0282946	A1	10/2013	Ricci
2013/0046624	A1	2/2013	Calman	2013/0288606	A1	10/2013	Kirsch
2013/0050069	A1	2/2013	Ota	2013/0293364	A1	11/2013	Ricci et al.
2013/0055096	A1	2/2013	Kim et al.	2013/0293452	A1	11/2013	Ricci et al.
2013/0059607	A1	3/2013	Herz et al.	2013/0293480	A1	11/2013	Kritt et al.
2013/0063336	A1	3/2013	Sugimoto et al.	2013/0295901	A1	11/2013	Abramson et al.
2013/0066512	A1	3/2013	Willard et al.	2013/0295908	A1	11/2013	Zeinstra et al.
2013/0067599	A1	3/2013	Raje et al.	2013/0295913	A1	11/2013	Matthews et al.
2013/0075530	A1	3/2013	Shander et al.	2013/0300554	A1	11/2013	Braden
2013/0079964	A1	3/2013	Sukkarie et al.	2013/0301584	A1	11/2013	Addepalli et al.
				2013/0304371	A1	11/2013	Kitatani et al.
				2013/0308265	A1	11/2013	Arnouse
				2013/0309977	A1	11/2013	Heines et al.
				2013/0311038	A1	11/2013	Kim et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0325453 A1 12/2013 Levien et al.  
 2013/0325568 A1 12/2013 Mangalvedkar et al.  
 2013/0329372 A1 12/2013 Wilkins  
 2013/0332023 A1 12/2013 Bertosa et al.  
 2013/0338914 A1 12/2013 Weiss  
 2013/0339027 A1 12/2013 Dokor et al.  
 2013/0345929 A1 12/2013 Bowden et al.  
 2014/0028542 A1 1/2014 Lovitt et al.  
 2014/0032014 A1 1/2014 DeBiasio et al.  
 2014/0054957 A1 2/2014 Bellis  
 2014/0058672 A1 2/2014 Wansley et al.  
 2014/0066014 A1 3/2014 Nicholson et al.  
 2014/0067201 A1 3/2014 Visintainer et al.  
 2014/0067564 A1 3/2014 Yuan  
 2014/0070917 A1 3/2014 Protopapas  
 2014/0081544 A1 3/2014 Fry  
 2014/0088798 A1 3/2014 Himmelstein  
 2014/0096068 A1 4/2014 Dewan et al.  
 2014/0097955 A1 4/2014 Lovitt et al.  
 2014/0109075 A1 4/2014 Hoffman et al.  
 2014/0120829 A1 5/2014 Bhamidipati et al.  
 2014/0121862 A1 5/2014 Zarrella et al.  
 2014/0125802 A1 5/2014 Beckert et al.  
 2014/0143839 A1 5/2014 Ricci  
 2014/0164611 A1 6/2014 Molettiere et al.  
 2014/0168062 A1 6/2014 Katz et al.  
 2014/0168436 A1 6/2014 Pedicino  
 2014/0169621 A1 6/2014 Burr  
 2014/0171752 A1 6/2014 Park et al.  
 2014/0172727 A1 6/2014 Abhyanker et al.  
 2014/0188533 A1 7/2014 Davidson  
 2014/0195272 A1 7/2014 Sadiq et al.  
 2014/0198216 A1 7/2014 Zhai et al.  
 2014/0200737 A1 7/2014 Lortz et al.  
 2014/0207328 A1 7/2014 Wolf et al.  
 2014/0220966 A1 8/2014 Muetzel et al.  
 2014/0222298 A1 8/2014 Gurin  
 2014/0223384 A1 8/2014 Graumann  
 2014/0240089 A1 8/2014 Chang  
 2014/0244078 A1 8/2014 Downey et al.  
 2014/0244111 A1 8/2014 Gross et al.  
 2014/0244156 A1 8/2014 Magnusson et al.  
 2014/0245277 A1 8/2014 Petro et al.  
 2014/0245278 A1 8/2014 Zellen  
 2014/0245284 A1 8/2014 Alrabady et al.  
 2014/0252091 A1 9/2014 Morse et al.  
 2014/0257627 A1 9/2014 Hagan, Jr.  
 2014/0267035 A1 9/2014 Schalk et al.  
 2014/0277936 A1 9/2014 El Dokor et al.  
 2014/0278070 A1 9/2014 McGavran et al.  
 2014/0278071 A1 9/2014 San Filippo et al.  
 2014/0281971 A1 9/2014 Isbell, III et al.  
 2014/0282161 A1 9/2014 Cash  
 2014/0282278 A1 9/2014 Anderson et al.  
 2014/0282470 A1 9/2014 Buga et al.  
 2014/0282931 A1 9/2014 Protopapas  
 2014/0292545 A1 10/2014 Nemoto  
 2014/0292665 A1 10/2014 Lathrop et al.  
 2014/0303899 A1 10/2014 Fung  
 2014/0306799 A1 10/2014 Ricci  
 2014/0306814 A1 10/2014 Ricci  
 2014/0307724 A1 10/2014 Ricci  
 2014/0309789 A1 10/2014 Ricci  
 2014/0309790 A1 10/2014 Ricci  
 2014/0309804 A1 10/2014 Ricci  
 2014/0309813 A1 10/2014 Ricci  
 2014/0309839 A1 10/2014 Ricci et al.  
 2014/0309849 A1 10/2014 Ricci  
 2014/0309852 A1 10/2014 Ricci  
 2014/0309853 A1 10/2014 Ricci  
 2014/0309862 A1 10/2014 Ricci  
 2014/0309863 A1 10/2014 Ricci  
 2014/0309864 A1 10/2014 Ricci  
 2014/0309865 A1 10/2014 Ricci  
 2014/0309866 A1 10/2014 Ricci

2014/0309867 A1 10/2014 Ricci  
 2014/0309868 A1 10/2014 Ricci  
 2014/0309871 A1 10/2014 Ricci  
 2014/0309872 A1 10/2014 Ricci  
 2014/0309873 A1 10/2014 Ricci  
 2014/0309876 A1 10/2014 Ricci  
 2014/0309878 A1 10/2014 Ricci  
 2014/0309879 A1 10/2014 Ricci  
 2014/0309880 A1 10/2014 Ricci  
 2014/0309885 A1 10/2014 Ricci  
 2014/0309886 A1 10/2014 Ricci  
 2014/0309893 A1 10/2014 Ricci  
 2014/0309913 A1 10/2014 Ricci et al.  
 2014/0309919 A1 10/2014 Ricci  
 2014/0309921 A1 10/2014 Ricci et al.  
 2014/0309930 A1 10/2014 Ricci  
 2014/0309934 A1 10/2014 Ricci  
 2014/0309935 A1 10/2014 Ricci  
 2014/0309982 A1 10/2014 Ricci  
 2014/0310031 A1 10/2014 Ricci  
 2014/0310075 A1 10/2014 Ricci  
 2014/0310103 A1 10/2014 Ricci  
 2014/0310186 A1 10/2014 Ricci  
 2014/0310277 A1 10/2014 Ricci  
 2014/0310379 A1 10/2014 Ricci et al.  
 2014/0310594 A1 10/2014 Ricci et al.  
 2014/0310610 A1 10/2014 Ricci  
 2014/0310702 A1 10/2014 Ricci et al.  
 2014/0310788 A1 10/2014 Ricci  
 2014/0322676 A1 10/2014 Raman  
 2014/0347207 A1 11/2014 Zeng et al.  
 2014/0347265 A1 11/2014 Allen et al.  
 2015/0007155 A1 1/2015 Hoffman et al.  
 2015/0012186 A1 1/2015 Horseman  
 2015/0032366 A1 1/2015 Man et al.  
 2015/0032670 A1 1/2015 Brazell  
 2015/0057839 A1 2/2015 Chang et al.  
 2015/0081133 A1 3/2015 Schulz  
 2015/0081167 A1 3/2015 Pisz et al.  
 2015/0088423 A1 3/2015 Tuukkanen  
 2015/0088515 A1 3/2015 Beaumont et al.  
 2015/0116200 A1 4/2015 Kurosawa et al.  
 2015/0158499 A1 6/2015 Koravadi  
 2015/0178034 A1 6/2015 Penilla et al.  
 2016/0008985 A1 1/2016 Kim et al.  
 2016/0070527 A1 3/2016 Ricci  
 2016/0086391 A1 3/2016 Ricci  
 2016/0269456 A1 9/2016 Ricci  
 2016/0269469 A1 9/2016 Ricci  
 2016/0358475 A1 12/2016 Prokhorov  
 2016/0358477 A1\* 12/2016 Ansari ..... G08G 1/167  
 2017/0129335 A1 5/2017 Lu et al.  
 2017/0136842 A1 5/2017 Anderson et al.  
 2017/0171375 A1 7/2017 Kamata  
 2017/0352215 A1 12/2017 Maiwand et al.

FOREIGN PATENT DOCUMENTS

CN 101303878 11/2008  
 CN 102467827 5/2012  
 EP 1223567 7/2002  
 EP 1484729 12/2004  
 EP 2192015 6/2010  
 JP 2004-284450 10/2004  
 KR 2006-0128484 12/2006  
 WO WO 2007/126204 11/2007  
 WO WO 2012/102879 8/2012  
 WO WO 2013/074866 5/2013  
 WO WO 2013/074867 5/2013  
 WO WO 2013/074868 5/2013  
 WO WO 2013/074897 5/2013  
 WO WO 2013/074899 5/2013  
 WO WO 2013/074901 5/2013  
 WO WO 2013/074919 5/2013  
 WO WO 2013/074981 5/2013  
 WO WO 2013/074983 5/2013  
 WO WO 2013/075005 5/2013  
 WO WO 2013/181310 12/2013  
 WO WO 2014/014862 1/2014

(56)

**References Cited**

## FOREIGN PATENT DOCUMENTS

WO	WO 2014/143563	9/2014
WO	WO 2014/158667	10/2014
WO	WO 2014/158672	10/2014
WO	WO 2014/158766	10/2014
WO	WO 2014/172312	10/2014
WO	WO 2014/172313	10/2014
WO	WO 2014/172316	10/2014
WO	WO 2014/172320	10/2014
WO	WO 2014/172322	10/2014
WO	WO 2014/172323	10/2014
WO	WO 2014/172327	10/2014
WO	WO 2016/145073	9/2016
WO	WO 2016/145100	9/2016

## OTHER PUBLICATIONS

Clark, "How Self-Driving Cars Work: The Nuts and Bolts Behind Google's Autonomous Car Program," Feb. 21, 2015, available at <http://www.makeuseof.com/tag/how-self-driving-cars-work-the-nuts-and-bolts-behind-googles-autonomous-car-program/>, 9 pages.

Guizzo, Erico, "How Google's Self-Driving Car Works," Oct. 18, 2011, available at <https://spectrum.ieee.org/automaton/robotics/artificial-intelligence/how-google-self-driving-car-works>, 5 pages.

Stephens, Leah, "How Driverless Cars Work," Interesting Engineering, Apr. 28, 2016, available at <https://interestingengineering.com/driverless-cars-work/>, 7 pages.

Official Action for U.S. Appl. No. 15/394,489, dated Oct. 6, 2017, 13 pages.

U.S. Appl. No. 61/567,962, filed Dec. 7, 2011, Baarman et al.

U.S. Appl. No. 15/393,028, filed Dec. 28, 2016, Ricci.

U.S. Appl. No. 15/393,054, filed Dec. 28, 2016, Ricci.

U.S. Appl. No. 15/394,489, filed Dec. 29, 2016, Ricci et al.

"Automatic vehicle location," wikipedia.org, available at [https://en.m.wikipedia.org/wiki/Automotive\\_vehicle\\_location](https://en.m.wikipedia.org/wiki/Automotive_vehicle_location), accessed Dec. 2016, 7 pages.

"Automotive navigation system," wikipedia.org, available at [https://en.m.wikipedia.org/wiki/Automotive\\_navigation\\_system](https://en.m.wikipedia.org/wiki/Automotive_navigation_system), accessed Dec. 2016, 15 pages.

"Global positioning system," wikipedia.org, available at [https://en.m.wikipedia.org/wiki/Global\\_Positioning\\_System](https://en.m.wikipedia.org/wiki/Global_Positioning_System), accessed Dec. 2016, 50 pages.

"Map database management," wikipedia.org, available at [https://en.m.wikipedia.org/wiki/Map\\_database\\_management](https://en.m.wikipedia.org/wiki/Map_database_management), accessed Dec. 2016, 9 pages.

"Nexus 10 Guidebook for Android," Google Inc., © 2012, Edition 1.2, 166 pages.

"Wireless ad hoc Network," wikipedia.org, available at [https://en.m.wikipedia.org/wiki/Wireless\\_ad\\_hoc\\_network](https://en.m.wikipedia.org/wiki/Wireless_ad_hoc_network), accessed Dec. 2016, 15 pages.

Armor-Segan et al., "Towards the Self Healing Vehicle," Automotive Electronics, Jun. 2007, 2007 3rd Institution of Engineering and Technology Conference, 7 pages.

Bennett, "Meet Samsung's Version of Apple AirPlay," CNET.com, Oct. 10, 2012, 11 pages.

Cairnie et al., "Using Finger-Pointing to Operate Secondary Controls in Automobiles," Proceedings of the IEEE Intelligent Vehicles Symposium 2000, Oct. 3-5, 2000, 6 pages.

Deaton et al., "How Driverless Cars Will Work," Jul. 1, 2008, HowStuffWorks.com. <<http://auto.howstuffworks.com/under-the-hood/trends-innovations/driverless-car.htm>> Sep. 18, 2017, 10 pages.

Dumbaugh, "Safe Streets, Livable Streets: A Positive Approach to urban Roadside Design," Ph.D. dissertation for School of Civil & Environ Engr., Georgia Inst. Of Technology, Dec. 2005, 235 pages.

Fei et al., "A QoS-aware Dynamic Bandwidth Allocation Algorithm for Relay Stations in IEEE 802.16j-based Vehicular Networks," Proceedings of the 2010 IEEE Global Telecommunications Conference, Dec. 10, 2010, 10 pages.

Ge et al., "Optimal Relay Selection in IEEE 802.16j Multihop Relay Vehicular Networks," IEEE Transactions on Vehicular Technology, 2010, vol. 59(5), pp. 2198-2206.

Heer et al., "ALPHA: An Adaptive and Lightweight Protocol for Hop-by-hop Authentication," Proceedings of CoNEXT 2008, Dec. 2008, pp. 1-12.

Jahnich et al., "Towards a Middleware Approach for a Self-Configurable Automotive Embedded System," International Federation for Information Processing, 2008, pp. 55-65.

Persson "Adaptive Middleware for Self-Configurable Embedded Real-Time Systems," KTH Industrial Engineering and Management, 2009, pp. iii-71 and references.

Raychaudhuri et al., "Emerging Wireless Technologies and the Future Mobile Internet," p. 48, Cambridge Press, 2011, 3 pages.

Stoller, "Leader Election in Distributed Systems with Crash Failures," Indiana University, 1997, pp. 1-15.

Strunk et al., "The Elements of Style," 3d ed., Macmillan Publishing Co., 1979, 3 pages.

Suwatthikul, "Fault detection and diagnosis for in-vehicle networks," Intech, 2010, pp. 283-286 [retrieved from: [www.intechopen.com/books/fault-detection-and-diagnosis-for-in-vehicle-networks](http://www.intechopen.com/books/fault-detection-and-diagnosis-for-in-vehicle-networks)].

Walter et al., "The smart car seat: personalized monitoring of vital signs in automotive applications," Personal and Ubiquitous Computing, Oct. 2011, vol. 15, No. 7, pp. 707-715.

Wolf et al., "Design, Implementation, and Evaluation of a Vehicular Hardware Security Module," ICISC'11 Proceedings of the 14th Int'l Conf. Information Security & Cryptology, Springer-Verlag Berlin, Heidelberg, 2011, pp. 302-318.

Official Action for U.S. Appl. No. 15/393,028, dated Jun. 29, 2017, 15 pages.

Notice of Allowance for U.S. Appl. No. 15/393,028, dated Jan. 3, 2018, 24 pages.

\* cited by examiner





Fig. 1



212  
208  
Fig. 2




Fig. 3






Fig. 5




Fig. 6





Fig. 7



**FIG. 8**







FIG. 9





**FIG. 10**

**FIG. 11**



**FIG. 12**

**FIG. 13**



**Fig. 14**

**1****METHOD AND SYSTEM FOR BEHAVIORAL SHARING IN AUTONOMOUS VEHICLES****CROSS REFERENCE TO RELATED APPLICATIONS**

The present application claims the benefits of and priority, under 35 U.S.C. § 119(e), to U.S. Provisional Application Ser. No. 62/418,620, filed Nov. 7, 2016, entitled “Self-Driving Control Systems for the Next Generation Vehicle,” the entire disclosure of which is hereby incorporated by reference, in its entirety, for all that it teaches and for all purposes.

**FIELD**

The present disclosure is generally directed to vehicle systems, in particular, toward electric and/or hybrid-electric vehicles.

**BACKGROUND**

In recent years, transportation methods have changed substantially. This change is due in part to a concern over the limited availability of natural resources, a proliferation in personal technology, and a societal shift to adopt more exterior environmentally friendly transportation solutions. These considerations have encouraged the development of a number of new flexible-fuel vehicles, hybrid-electric vehicles, and electric vehicles.

While these vehicles appear to be new they are generally implemented as a number of traditional subsystems that are merely tied to an alternative power source. In fact, the design and construction of the vehicles is limited to standard frame sizes, shapes, materials, and transportation concepts. Among other things, these limitations fail to take advantage of the benefits of new technology, power sources, and support infrastructure. In particular, the implementation of an artificially intelligent vehicle has lagged far behind the development vehicle subsystems.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 shows a vehicle in accordance with embodiments of the present disclosure;

FIG. 2 shows a plan view of the vehicle in accordance with at least some embodiments of the present disclosure;

FIG. 3 is a block diagram of an embodiment of a communication environment of the vehicle in accordance with embodiments of the present disclosure;

FIG. 4 shows an embodiment of the instrument panel of the vehicle according to one embodiment of the present disclosure;

FIG. 5 is a block diagram of an embodiment of a communications subsystem of the vehicle;

FIG. 6 is a block diagram of a computing environment associated with the embodiments presented herein;

FIG. 7 is a block diagram of a computing device associated with one or more components described herein;

FIG. 8 is block diagram of a computational system in a vehicle and associated with one or more components described herein;

FIG. 9 is a block diagram of an autonomous driving vehicle system according to an embodiment;

FIG. 10 is a flow chart associated with one or more embodiments presented herein;

**2**

FIG. 11 is a flow chart associated with one or more embodiments presented herein;

FIG. 12 is a flow chart associated with one or more embodiments presented herein;

FIG. 13 is a flow chart associated with one or more embodiments presented herein; and

FIG. 14 is a block diagram of a computing system associated with one or more components described herein.

**DETAILED DESCRIPTION**

Embodiments of the present disclosure will be described in connection with a vehicle, and in some embodiments, an electric vehicle, rechargeable electric vehicle, and/or hybrid-electric vehicle and associated systems.

Embodiments can provide an intelligent autonomous vehicle control system that augments the learned behaviors from autonomous vehicle driving operations with temporally, spatially, or event-limited behaviors received from the intelligent autonomous vehicle control system. The temporally, spatially, or event-limited behaviors can be learned by the control system monitoring the behaviors of multiple autonomous vehicles.

As will be appreciated, a “behavior” is the collection of a selected set of the executions of the instructions of a software program. It can be defined in many ways, including event-based and/or input-output based observations.

FIG. 1 shows a perspective view of a vehicle **100** in accordance with embodiments of the present disclosure. The electric vehicle **100** comprises a vehicle front **110**, vehicle aft or rear **120**, vehicle roof **130**, at least one vehicle side **160**, a vehicle undercarriage **140**, and a vehicle interior **150**. In any event, the vehicle **100** may include a frame **104** and one or more body panels **108** mounted or affixed thereto. The vehicle **100** may include one or more interior components (e.g., components inside an interior space **150**, or user space, of a vehicle **100**, etc.), exterior components (e.g., components outside of the interior space **150**, or user space, of a vehicle **100**, etc.), drive systems, controls systems, structural components, etc.

Although shown in the form of a car, it should be appreciated that the vehicle **100** described herein may include any conveyance or model of a conveyance, where the conveyance was designed for the purpose of moving one or more tangible objects, such as people, animals, cargo, and the like. The term “vehicle” does not require that a conveyance moves or is capable of movement. Typical vehicles may include but are in no way limited to cars, trucks, motorcycles, busses, automobiles, trains, railed conveyances, boats, ships, marine conveyances, submarine conveyances, airplanes, space craft, flying machines, human-powered conveyances, and the like.

In some embodiments, the vehicle **100** may include a number of sensors, devices, and/or systems that are capable of assisting in driving operations. Examples of the various sensors and systems may include, but are in no way limited to, one or more of cameras (e.g., independent, stereo, combined image, etc.), infrared (IR) sensors, radio frequency (RF) sensors, ultrasonic sensors (e.g., transducers, transceivers, etc.), RADAR sensors (e.g., object-detection sensors and/or systems), LIDAR systems, odometry sensors and/or devices (e.g., encoders, etc.), orientation sensors (e.g., accelerometers, gyroscopes, magnetometer, etc.), navigation sensors and systems (e.g., GPS, etc.), and other ranging, imaging, and/or object-detecting sensors. The sensors may be disposed in an interior space **150** of the vehicle **100** and/or on an outside of the vehicle **100**. In some

embodiments, the sensors and systems may be disposed in one or more portions of a vehicle **100** (e.g., the frame **104**, a body panel, a compartment, etc.).

The vehicle sensors and systems may be selected and/or configured to suit a level of operation associated with the vehicle **100**. Among other things, the number of sensors used in a system may be altered to increase or decrease information available to a vehicle control system (e.g., affecting control capabilities of the vehicle **100**). Additionally or alternatively, the sensors and systems may be part of one or more advanced driver assistance systems (ADAS) associated with a vehicle **100**. In any event, the sensors and systems may be used to provide driving assistance at any level of operation (e.g., from fully-manual to fully-autonomous operations, etc.) as described herein.

The various levels of vehicle control and/or operation can be described as corresponding to a level of autonomy associated with a vehicle **100** for vehicle driving operations. For instance, at Level 0, or fully-manual driving operations, a driver (e.g., a human driver) may be responsible for all the driving control operations (e.g., steering, accelerating, braking, etc.) associated with the vehicle. Level 0 may be referred to as a “No Automation” level. At Level 1, the vehicle may be responsible for a limited number of the driving operations associated with the vehicle, while the driver is still responsible for most driving control operations. An example of a Level 1 vehicle may include a vehicle in which the throttle control and/or braking operations may be controlled by the vehicle (e.g., cruise control operations, etc.). Level 1 may be referred to as a “Driver Assistance” level. At Level 2, the vehicle may collect information (e.g., via one or more driving assistance systems, sensors, etc.) about an environment of the vehicle (e.g., surrounding area, roadway, traffic, ambient conditions, etc.) and use the collected information to control driving operations (e.g., steering, accelerating, braking, etc.) associated with the vehicle. In a Level 2 autonomous vehicle, the driver may be required to perform other aspects of driving operations not controlled by the vehicle. Level 2 may be referred to as a “Partial Automation” level. It should be appreciated that Levels 0-2 all involve the driver monitoring the driving operations of the vehicle.

At Level 3, the driver may be separated from controlling all the driving operations of the vehicle except when the vehicle makes a request for the operator to act or intervene in controlling one or more driving operations. In other words, the driver may be separated from controlling the vehicle unless the driver is required to take over for the vehicle. Level 3 may be referred to as a “Conditional Automation” level. At Level 4, the driver may be separated from controlling all the driving operations of the vehicle and the vehicle may control driving operations even when a user fails to respond to a request to intervene. Level 4 may be referred to as a “High Automation” level. At Level 5, the vehicle can control all the driving operations associated with the vehicle in all driving modes. The vehicle in Level 5 may continually monitor traffic, vehicular, roadway, and/or exterior environmental conditions while driving the vehicle. In Level 5, there is no human driver interaction required in any driving mode. Accordingly, Level 5 may be referred to as a “Full Automation” level. It should be appreciated that in Levels 3-5 the vehicle, and/or one or more automated driving systems associated with the vehicle, monitors the driving operations of the vehicle and the driving environment.

As shown in FIG. 1, the vehicle **100** may, for example, include at least one of a ranging and imaging system **112**

(e.g., LIDAR, etc.), an imaging sensor **116A**, **116F** (e.g., camera, IR, etc.), a radio object-detection and ranging system sensors **116B** (e.g., RADAR, RF, etc.), ultrasonic sensors **116C**, and/or other object-detection sensors **116D**, **116E**. In some embodiments, the LIDAR system **112** and/or sensors may be mounted on a roof **130** of the vehicle **100**. In one embodiment, the RADAR sensors **116B** may be disposed at least at a front **110**, aft **120**, or side **160** of the vehicle **100**. Among other things, the RADAR sensors may be used to monitor and/or detect a position of other vehicles, pedestrians, and/or other objects near, or proximal to, the vehicle **100**. While shown associated with one or more areas of a vehicle **100**, it should be appreciated that any of the sensors and systems **116A-K**, **112** illustrated in FIGS. 1 and **2** may be disposed in, on, and/or about the vehicle **100** in any position, area, and/or zone of the vehicle **100**.

Referring now to FIG. 2, a plan view of a vehicle **100** will be described in accordance with embodiments of the present disclosure. In particular, FIG. 2 shows a vehicle sensing environment **200** at least partially defined by the sensors and systems **116A-K**, **112** disposed in, on, and/or about the vehicle **100**. Each sensor **116A-K** may include an operational detection range  $R$  and operational detection angle  $\alpha$ . The operational detection range  $R$  may define the effective detection limit, or distance, of the sensor **116A-K**. In some cases, this effective detection limit may be defined as a distance from a portion of the sensor **116A-K** (e.g., a lens, sensing surface, etc.) to a point in space offset from the sensor **116A-K**. The effective detection limit may define a distance, beyond which, the sensing capabilities of the sensor **116A-K** deteriorate, fail to work, or are unreliable. In some embodiments, the effective detection limit may define a distance, within which, the sensing capabilities of the sensor **116A-K** are able to provide accurate and/or reliable detection information. The operational detection angle  $\alpha$  may define at least one angle of a span, or between horizontal and/or vertical limits, of a sensor **116A-K**. As can be appreciated, the operational detection limit and the operational detection angle  $\alpha$  of a sensor **116A-K** together may define the effective detection zone **216A-D** (e.g., the effective detection area, and/or volume, etc.) of a sensor **116A-K**.

In some embodiments, the vehicle **100** may include a ranging and imaging system **112** such as LIDAR, or the like. The ranging and imaging system **112** may be configured to detect visual information in an environment surrounding the vehicle **100**. The visual information detected in the environment surrounding the ranging and imaging system **112** may be processed (e.g., via one or more sensor and/or system processors, etc.) to generate a complete 360-degree view of an environment **200** around the vehicle. The ranging and imaging system **112** may be configured to generate changing 360-degree views of the environment **200** in real-time, for instance, as the vehicle **100** drives. In some cases, the ranging and imaging system **112** may have an effective detection limit **204** that is some distance from the center of the vehicle **100** outward over 360 degrees. The effective detection limit **204** of the ranging and imaging system **112** defines a view zone **208** (e.g., an area and/or volume, etc.) surrounding the vehicle **100**. Any object falling outside of the view zone **208** is in the undetected zone **212** and would not be detected by the ranging and imaging system **112** of the vehicle **100**.

Sensor data and information may be collected by one or more sensors or systems **116A-K**, **112** of the vehicle **100** monitoring the vehicle sensing environment **200**. This information may be processed (e.g., via a processor, computer-vision system, etc.) to determine targets (e.g., objects, signs,

people, markings, roadways, conditions, etc.) inside one or more detection zones **208**, **216A-D** associated with the vehicle sensing environment **200**. In some cases, information from multiple sensors **116A-K** may be processed to form composite sensor detection information. For example, a first sensor **116A** and a second sensor **116F** may correspond to a first camera **116A** and a second camera **116F** aimed in a forward traveling direction of the vehicle **100**. In this example, images collected by the cameras **116A**, **116F** may be combined to form stereo image information. This composite information may increase the capabilities of a single sensor in the one or more sensors **116A-K** by, for example, adding the ability to determine depth associated with targets in the one or more detection zones **208**, **216A-D**. Similar image data may be collected by rear view cameras (e.g., sensors **116G**, **116H**) aimed in a rearward traveling direction vehicle **100**.

In some embodiments, multiple sensors **116A-K** may be effectively joined to increase a sensing zone and provide increased sensing coverage. For instance, multiple RADAR sensors **116B** disposed on the front **110** of the vehicle may be joined to provide a zone **216B** of coverage that spans across an entirety of the front **110** of the vehicle. In some cases, the multiple RADAR sensors **116B** may cover a detection zone **216B** that includes one or more other sensor detection zones **216A**. These overlapping detection zones may provide redundant sensing, enhanced sensing, and/or provide greater detail in sensing within a particular portion (e.g., zone **216A**) of a larger zone (e.g., zone **216B**). Additionally or alternatively, the sensors **116A-K** of the vehicle **100** may be arranged to create a complete coverage, via one or more sensing zones **208**, **216A-D** around the vehicle **100**. In some areas, the sensing zones **216C** of two or more sensors **116D**, **116E** may intersect at an overlap zone **220**. In some areas, the angle and/or detection limit of two or more sensing zones **216C**, **216D** (e.g., of two or more sensors **116E**, **116J**, **116K**) may meet at a virtual intersection point **224**.

The vehicle **100** may include a number of sensors **116E**, **116G**, **116H**, **116J**, **116K** disposed proximal to the rear **120** of the vehicle **100**. These sensors can include, but are in no way limited to, an imaging sensor, camera, IR, a radio object-detection and ranging sensors, RADAR, RF, ultrasonic sensors, and/or other object-detection sensors. Among other things, these sensors **116E**, **116G**, **116H**, **116J**, **116K** may detect targets near or approaching the rear of the vehicle **100**. For example, another vehicle approaching the rear **120** of the vehicle **100** may be detected by one or more of the ranging and imaging system (e.g., LIDAR) **112**, rear-view cameras **116G**, **116H**, and/or rear facing RADAR sensors **116J**, **116K**. As described above, the images from the rear-view cameras **116G**, **116H** may be processed to generate a stereo view (e.g., providing depth associated with an object or environment, etc.) for targets visible to both cameras **116G**, **116H**. As another example, the vehicle **100** may be driving and one or more of the ranging and imaging system **112**, front-facing cameras **116A**, **116F**, front-facing RADAR sensors **116B**, and/or ultrasonic sensors **116C** may detect targets in front of the vehicle **100**. This approach may provide critical sensor information to a vehicle control system in at least one of the autonomous driving levels described above. For instance, when the vehicle **100** is driving autonomously (e.g., Level 3, Level 4, or Level 5) and detects other vehicles stopped in a travel path, the sensor detection information may be sent to the vehicle control system of the vehicle **100** to control a driving operation (e.g., braking, decelerating, etc.) associated with the vehicle **100**

(in this example, slowing the vehicle **100** as to avoid colliding with the stopped other vehicles). As yet another example, the vehicle **100** may be operating and one or more of the ranging and imaging system **112**, and/or the side-facing sensors **116D**, **116E** (e.g., RADAR, ultrasonic, camera, combinations thereof, and/or other type of sensor), may detect targets at a side of the vehicle **100**. It should be appreciated that the sensors **116A-K** may detect a target that is both at a side **160** and a front **110** of the vehicle **100** (e.g., disposed at a diagonal angle to a centerline of the vehicle **100** running from the front **110** of the vehicle **100** to the rear **120** of the vehicle). Additionally or alternatively, the sensors **116A-K** may detect a target that is both, or simultaneously, at a side **160** and a rear **120** of the vehicle **100** (e.g., disposed at a diagonal angle to the centerline of the vehicle **100**).

FIG. 3 is a block diagram of an embodiment of a communication environment **300** of the vehicle **100** in accordance with embodiments of the present disclosure. The communication system **300** may include one or more vehicle driving vehicle sensors and systems **304**, sensor processors **340**, sensor data memory **344**, vehicle control system **348**, communications subsystem **350**, control data **364**, computing devices **368**, display devices **372**, and other components **374** that may be associated with a vehicle **100**. These associated components may be electrically and/or communicatively coupled to one another via at least one bus **360**. In some embodiments, the one or more associated components may send and/or receive signals across a communication network **352** to at least one of a navigation source **356A**, a control source **356B**, or some other entity **356N**.

In accordance with at least some embodiments of the present disclosure, the communication network **352** may comprise any type of known communication medium or collection of communication media and may use any type of protocols, such as SIP, TCP/IP, SNA, IPX, AppleTalk, and the like, to transport messages between endpoints. The communication network **352** may include wired and/or wireless communication technologies. The Internet is an example of the communication network **352** that constitutes an Internet Protocol (IP) network consisting of many computers, computing networks, and other communication devices located all over the world, which are connected through many telephone systems and other means. Other examples of the communication network **104** include, without limitation, a standard Plain Old Telephone System (POTS), an Integrated Services Digital Network (ISDN), the Public Switched Telephone Network (PSTN), a Local Area Network (LAN), such as an Ethernet network, a Token-Ring network and/or the like, a Wide Area Network (WAN), a virtual network, including without limitation a virtual private network ("VPN"); the Internet, an intranet, an extranet, a cellular network, an infra-red network; a wireless network (e.g., a network operating under any of the IEEE 802.9 suite of protocols, the Bluetooth® protocol known in the art, and/or any other wireless protocol), and any other type of packet-switched or circuit-switched network known in the art and/or any combination of these and/or other networks. In addition, it can be appreciated that the communication network **352** need not be limited to any one network type, and instead may be comprised of a number of different networks and/or network types. The communication network **352** may comprise a number of different communication media such as coaxial cable, copper cable/wire, fiber-optic cable, antennas for transmitting/receiving wireless messages, and combinations thereof.

The driving vehicle sensors and systems **304** may include at least one navigation **308** (e.g., global positioning system

(GPS), etc.), orientation **312**, odometry **316**, LIDAR **320**, RADAR **324**, ultrasonic **328**, camera **332**, infrared (IR) **336**, and/or other sensor or system **338**. These driving vehicle sensors and systems **304** may be similar, if not identical, to the sensors and systems **116A-K**, **112** described in conjunction with FIGS. **1** and **2**.

The navigation sensor **308** may include one or more sensors having receivers and antennas that are configured to utilize a satellite-based navigation system including a network of navigation satellites capable of providing geolocation and time information to at least one component of the vehicle **100**. Examples of the navigation sensor **308** as described herein may include, but are not limited to, at least one of Garmin® GLO™ family of GPS and GLONASS combination sensors, Garmin® GPS 15x™ family of sensors, Garmin® GPS 16x™ family of sensors with high-sensitivity receiver and antenna, Garmin® GPS 18x OEM family of high-sensitivity GPS sensors, Dewetron DEWE-VGPS series of GPS sensors, GlobalSat 1-Hz series of GPS sensors, other industry-equivalent navigation sensors and/or systems, and may perform navigational and/or geolocation functions using any known or future-developed standard and/or architecture.

The orientation sensor **312** may include one or more sensors configured to determine an orientation of the vehicle **100** relative to at least one reference point. In some embodiments, the orientation sensor **312** may include at least one pressure transducer, stress/strain gauge, accelerometer, gyroscope, and/or geomagnetic sensor. Examples of the navigation sensor **308** as described herein may include, but are not limited to, at least one of Bosch Sensortec BMX 160 series low-power absolute orientation sensors, Bosch Sensortec BMX055 9-axis sensors, Bosch Sensortec BMI055 6-axis inertial sensors, Bosch Sensortec BMI160 6-axis inertial sensors, Bosch Sensortec BMF055 9-axis inertial sensors (accelerometer, gyroscope, and magnetometer) with integrated Cortex M0+ microcontroller, Bosch Sensortec BMP280 absolute barometric pressure sensors, Infineon TLV493D-A1B6 3D magnetic sensors, Infineon TLI493D-W1B6 3D magnetic sensors, Infineon TL family of 3D magnetic sensors, Murata Electronics SCC2000 series combined gyro sensor and accelerometer, Murata Electronics SCC1300 series combined gyro sensor and accelerometer, other industry-equivalent orientation sensors and/or systems, and may perform orientation detection and/or determination functions using any known or future-developed standard and/or architecture.

The odometry sensor and/or system **316** may include one or more components that is configured to determine a change in position of the vehicle **100** over time. In some embodiments, the odometry system **316** may utilize data from one or more other sensors and/or systems **304** in determining a position (e.g., distance, location, etc.) of the vehicle **100** relative to a previously measured position for the vehicle **100**. Additionally or alternatively, the odometry sensors **316** may include one or more encoders, Hall speed sensors, and/or other measurement sensors/devices configured to measure a wheel speed, rotation, and/or number of revolutions made over time. Examples of the odometry sensor/system **316** as described herein may include, but are not limited to, at least one of Infineon TLE4924/26/27/28C high-performance speed sensors, Infineon TL4941plusC(B) single chip differential Hall wheel-speed sensors, Infineon TL5041plusC Giant Magnetoresistance (GMR) effect sensors, Infineon TL family of magnetic sensors, EPC Model 25SP Accu-CoderPro™ incremental shaft encoders, EPC Model 30M compact incremental encoders with advanced

magnetic sensing and signal processing technology, EPC Model 925 absolute shaft encoders, EPC Model 958 absolute shaft encoders, EPC Model MA36S/MA63S/SA36S absolute shaft encoders, Dynapar™ F18 commutating optical encoder, Dynapar™ HS35R family of phased array encoder sensors, other industry-equivalent odometry sensors and/or systems, and may perform change in position detection and/or determination functions using any known or future-developed standard and/or architecture.

The LIDAR sensor/system **320** may include one or more components configured to measure distances to targets using laser illumination. In some embodiments, the LIDAR sensor/system **320** may provide 3D imaging data of an environment around the vehicle **100**. The imaging data may be processed to generate a full 360-degree view of the environment around the vehicle **100**. The LIDAR sensor/system **320** may include a laser light generator configured to generate a plurality of target illumination laser beams (e.g., laser light channels). In some embodiments, this plurality of laser beams may be aimed at, or directed to, a rotating reflective surface (e.g., a mirror) and guided outwardly from the LIDAR sensor/system **320** into a measurement environment. The rotating reflective surface may be configured to continually rotate 360 degrees about an axis, such that the plurality of laser beams is directed in a full 360-degree range around the vehicle **100**. A photodiode receiver of the LIDAR sensor/system **320** may detect when light from the plurality of laser beams emitted into the measurement environment returns (e.g., reflected echo) to the LIDAR sensor/system **320**. The LIDAR sensor/system **320** may calculate, based on a time associated with the emission of light to the detected return of light, a distance from the vehicle **100** to the illuminated target. In some embodiments, the LIDAR sensor/system **320** may generate over 2.0 million points per second and have an effective operational range of at least 100 meters. Examples of the LIDAR sensor/system **320** as described herein may include, but are not limited to, at least one of Velodyne® LiDAR™ HDL-64E 64-channel LIDAR sensors, Velodyne® LiDAR™ HDL-32E 32-channel LIDAR sensors, Velodyne® LiDAR™ PUCK™ VLP-16 16-channel LIDAR sensors, Leica Geosystems Pegasus: Two mobile sensor platform, Garmin® LIDAR-Lite v3 measurement sensor, Quanergy M8 LiDAR sensors, Quanergy S3 solid state LiDAR sensor, LeddarTech® LeddarVU compact solid state fixed-beam LIDAR sensors, other industry-equivalent LIDAR sensors and/or systems, and may perform illuminated target and/or obstacle detection in an environment around the vehicle **100** using any known or future-developed standard and/or architecture.

The RADAR sensors **324** may include one or more radio components that are configured to detect objects/targets in an environment of the vehicle **100**. In some embodiments, the RADAR sensors **324** may determine a distance, position, and/or movement vector (e.g., angle, speed, etc.) associated with a target over time. The RADAR sensors **324** may include a transmitter configured to generate and emit electromagnetic waves (e.g., radio, microwaves, etc.) and a receiver configured to detect returned electromagnetic waves. In some embodiments, the RADAR sensors **324** may include at least one processor configured to interpret the returned electromagnetic waves and determine locational properties of targets. Examples of the RADAR sensors **324** as described herein may include, but are not limited to, at least one of Infineon RASIC™ RTN7735PL transmitter and RRN7745PL/46PL receiver sensors, Autoliv ASP Vehicle RADAR sensors, Delphi L2C0051TR 77 GHz ESR Electronically Scanning Radar sensors, Fujitsu Ten Ltd. Auto-

motive Compact 77 GHz 3D Electronic Scan Millimeter Wave Radar sensors, other industry-equivalent RADAR sensors and/or systems, and may perform radio target and/or obstacle detection in an environment around the vehicle **100** using any known or future-developed standard and/or architecture.

The ultrasonic sensors **328** may include one or more components that are configured to detect objects/targets in an environment of the vehicle **100**. In some embodiments, the ultrasonic sensors **328** may determine a distance, position, and/or movement vector (e.g., angle, speed, etc.) associated with a target over time. The ultrasonic sensors **328** may include an ultrasonic transmitter and receiver, or transceiver, configured to generate and emit ultrasound waves and interpret returned echoes of those waves. In some embodiments, the ultrasonic sensors **328** may include at least one processor configured to interpret the returned ultrasonic waves and determine locational properties of targets. Examples of the ultrasonic sensors **328** as described herein may include, but are not limited to, at least one of Texas Instruments TIDA-00151 automotive ultrasonic sensor interface IC sensors, MaxBotix® MB8450 ultrasonic proximity sensor, MaxBotix® ParkSonar™-EZ ultrasonic proximity sensors, Murata Electronics MA40H1S-R open-structure ultrasonic sensors, Murata Electronics MA40S4R/S open-structure ultrasonic sensors, Murata Electronics MA58MF14-7N waterproof ultrasonic sensors, other industry-equivalent ultrasonic sensors and/or systems, and may perform ultrasonic target and/or obstacle detection in an environment around the vehicle **100** using any known or future-developed standard and/or architecture.

The camera sensors **332** may include one or more components configured to detect image information associated with an environment of the vehicle **100**. In some embodiments, the camera sensors **332** may include a lens, filter, image sensor, and/or a digital image processor. It is an aspect of the present disclosure that multiple camera sensors **332** may be used together to generate stereo images providing depth measurements. Examples of the camera sensors **332** as described herein may include, but are not limited to, at least one of ON Semiconductor® MT9V024 Global Shutter VGA GS CMOS image sensors, Teledyne DALSA Falcon2 camera sensors, CMOSIS CMV50000 high-speed CMOS image sensors, other industry-equivalent camera sensors and/or systems, and may perform visual target and/or obstacle detection in an environment around the vehicle **100** using any known or future-developed standard and/or architecture.

The infrared (IR) sensors **336** may include one or more components configured to detect image information associated with an environment of the vehicle **100**. The IR sensors **336** may be configured to detect targets in low-light, dark, or poorly-lit environments. The IR sensors **336** may include an IR light emitting element (e.g., IR light emitting diode (LED), etc.) and an IR photodiode. In some embodiments, the IR photodiode may be configured to detect returned IR light at or about the same wavelength to that emitted by the IR light emitting element. In some embodiments, the IR sensors **336** may include at least one processor configured to interpret the returned IR light and determine locational properties of targets. The IR sensors **336** may be configured to detect and/or measure a temperature associated with a target (e.g., an object, pedestrian, other vehicle, etc.). Examples of IR sensors **336** as described herein may include, but are not limited to, at least one of Opto Diode lead-salt IR array sensors, Opto Diode OD-850 Near-IR LED sensors, Opto Diode SA/SHA727 steady state IR emitters and IR detectors, FLIR® LS microbolometer sen-

sors, FLIR® TacFLIR 380-HD InSb MWIR FPA and HD MWIR thermal sensors, FLIR® VOx 640x480 pixel detector sensors, Delphi IR sensors, other industry-equivalent IR sensors and/or systems, and may perform IR visual target and/or obstacle detection in an environment around the vehicle **100** using any known or future-developed standard and/or architecture.

In some embodiments, the driving vehicle sensors and systems **304** may include other sensors **338** and/or combinations of the sensors **308-336** described above. Additionally or alternatively, one or more of the sensors **308-336** described above may include one or more processors configured to process and/or interpret signals detected by the one or more sensors **308-336**. In some embodiments, the processing of at least some sensor information provided by the vehicle sensors and systems **304** may be processed by at least one sensor processor **340**. Raw and/or processed sensor data may be stored in a sensor data memory **344** storage medium. In some embodiments, the sensor data memory **344** may store instructions used by the sensor processor **340** for processing sensor information provided by the sensors and systems **304**. In any event, the sensor data memory **344** may be a disk drive, optical storage device, solid-state storage device such as a random access memory (“RAM”) and/or a read-only memory (“ROM”), which can be programmable, flash-updateable, and/or the like.

The vehicle control system **348** may receive processed sensor information from the sensor processor **340** and determine to control an aspect of the vehicle **100**. Controlling an aspect of the vehicle **100** may include presenting information via one or more display devices **372** associated with the vehicle, sending commands to one or more computing devices **368** associated with the vehicle, and/or controlling a driving operation of the vehicle. In some embodiments, the vehicle control system **348** may correspond to one or more computing systems that control driving operations of the vehicle **100** in accordance with the Levels of driving autonomy described above. In one embodiment, the vehicle control system **348** may operate a speed of the vehicle **100** by controlling an output signal to the accelerator and/or braking system of the vehicle. In this example, the vehicle control system **348** may receive sensor data describing an environment surrounding the vehicle **100** and, based on the sensor data received, determine to adjust the acceleration, power output, and/or braking of the vehicle **100**. The vehicle control system **348** may additionally control steering and/or other driving functions of the vehicle **100**.

The vehicle control system **348** may communicate, in real-time, with the driving sensors and systems **304** forming a feedback loop. In particular, upon receiving sensor information describing a condition of targets in the environment surrounding the vehicle **100**, the vehicle control system **348** may autonomously make changes to a driving operation of the vehicle **100**. The vehicle control system **348** may then receive subsequent sensor information describing any change to the condition of the targets detected in the environment as a result of the changes made to the driving operation. This continual cycle of observation (e.g., via the sensors, etc.) and action (e.g., selected control or non-control of vehicle operations, etc.) allows the vehicle **100** to operate autonomously in the environment.

In some embodiments, the one or more components of the vehicle **100** (e.g., the driving vehicle sensors **304**, vehicle control system **348**, display devices **372**, etc.) may communicate across the communication network **352** to one or more entities **356A-N** via a communications subsystem **350** of the vehicle **100**. Embodiments of the communications

subsystem **350** are described in greater detail in conjunction with FIG. **5**. For instance, the navigation sensors **308** may receive global positioning, location, and/or navigational information from a navigation source **356A**. In some embodiments, the navigation source **356A** may be a global navigation satellite system (GNSS) similar, if not identical, to NAVSTAR GPS, GLONASS, EU Galileo, and/or the BeiDou Navigation Satellite System (BDS) to name a few.

In some embodiments, the vehicle control system **348** may receive control information from one or more control sources **356B**. The control source **356** may provide vehicle control information including autonomous driving control commands, vehicle operation override control commands, and the like. The control source **356** may correspond to an autonomous vehicle control system, a traffic control system, an administrative control entity, and/or some other controlling server. It is an aspect of the present disclosure that the vehicle control system **348** and/or other components of the vehicle **100** may exchange communications with the control source **356** across the communication network **352** and via the communications subsystem **350**.

Information associated with controlling driving operations of the vehicle **100** may be stored in a control data memory **364** storage medium. The control data memory **364** may store instructions used by the vehicle control system **348** for controlling driving operations of the vehicle **100**, historical control information, autonomous driving control rules, and the like. In some embodiments, the control data memory **364** may be a disk drive, optical storage device, solid-state storage device such as a random access memory (“RAM”) and/or a read-only memory (“ROM”), which can be programmable, flash-updateable, and/or the like.

In addition to the mechanical components described herein, the vehicle **100** may include a number of user interface devices. The user interface devices receive and translate human input into a mechanical movement or electrical signal or stimulus. The human input may be one or more of motion (e.g., body movement, body part movement, in two-dimensional or three-dimensional space, etc.), voice, touch, and/or physical interaction with the components of the vehicle **100**. In some embodiments, the human input may be configured to control one or more functions of the vehicle **100** and/or systems of the vehicle **100** described herein. User interfaces may include, but are in no way limited to, at least one graphical user interface of a display device, steering wheel or mechanism, transmission lever or button (e.g., including park, neutral, reverse, and/or drive positions, etc.), throttle control pedal or mechanism, brake control pedal or mechanism, power control switch, communications equipment, etc.

FIG. **4** shows one embodiment of the instrument panel **400** of the vehicle **100**. The instrument panel **400** of vehicle **100** comprises a steering wheel **410**, a vehicle operational display **420** (e.g., configured to present and/or display driving data such as speed, measured air resistance, vehicle information, entertainment information, etc.), one or more auxiliary displays **424** (e.g., configured to present and/or display information segregated from the operational display **420**, entertainment applications, movies, music, etc.), a heads-up display **434** (e.g., configured to display any information previously described including, but in no way limited to, guidance information such as route to destination, or obstacle warning information to warn of a potential collision, or some or all primary vehicle operational data such as speed, resistance, etc.), a power management display **428** (e.g., configured to display data corresponding to electric power levels of vehicle **100**, reserve power, charging status,

etc.), and an input device **432** (e.g., a controller, touchscreen, or other interface device configured to interface with one or more displays in the instrument panel or components of the vehicle **100**. The input device **432** may be configured as a joystick, mouse, touchpad, tablet, 3D gesture capture device, etc.). In some embodiments, the input device **432** may be used to manually maneuver a portion of the vehicle **100** into a charging position (e.g., moving a charging plate to a desired separation distance, etc.).

While one or more of displays of instrument panel **400** may be touch-screen displays, it should be appreciated that the vehicle operational display may be a display incapable of receiving touch input. For instance, the operational display **420** that spans across an interior space centerline **404** and across both a first zone **408A** and a second zone **408B** may be isolated from receiving input from touch, especially from a passenger. In some cases, a display that provides vehicle operation or critical systems information and interface may be restricted from receiving touch input and/or be configured as a non-touch display. This type of configuration can prevent dangerous mistakes in providing touch input where such input may cause an accident or unwanted control.

In some embodiments, one or more displays of the instrument panel **400** may be mobile devices and/or applications residing on a mobile device such as a smart phone. Additionally or alternatively, any of the information described herein may be presented to one or more portions **420A-N** of the operational display **420** or other display **424**, **428**, **434**. In one embodiment, one or more displays of the instrument panel **400** may be physically separated or detached from the instrument panel **400**. In some cases, a detachable display may remain tethered to the instrument panel.

The portions **420A-N** of the operational display **420** may be dynamically reconfigured and/or resized to suit any display of information as described. Additionally or alternatively, the number of portions **420A-N** used to visually present information via the operational display **420** may be dynamically increased or decreased as required, and are not limited to the configurations shown.

FIG. **5** illustrates a hardware diagram of communications componentry that can be optionally associated with the vehicle **100** in accordance with embodiments of the present disclosure.

The communications componentry can include one or more wired or wireless devices such as a transceiver(s) and/or modem that allows communications not only between the various systems disclosed herein but also with other devices, such as devices on a network, and/or on a distributed network such as the Internet and/or in the cloud and/or with other vehicle(s).

The communications subsystem **350** can also include inter- and intra-vehicle communications capabilities such as hotspot and/or access point connectivity for any one or more of the vehicle occupants and/or vehicle-to-vehicle communications.

Additionally, and while not specifically illustrated, the communications subsystem **350** can include one or more communications links (that can be wired or wireless) and/or communications busses (managed by the bus manager **574**), including one or more of CANbus, OBD-II, ARCINC 429, Byteflight, CAN (Controller Area Network), D2B (Domestic Digital Bus), FlexRay, DC-BUS, IDB-1394, IEBus, I2C, ISO 9141-1/-2, J1708, J1587, J1850, J1939, ISO 11783, Keyword Protocol 2000, LIN (Local Interconnect Network), MOST (Media Oriented Systems Transport), Multifunction

Vehicle Bus, SMARTwireX, SPI, VAN (Vehicle Area Network), and the like or in general any communications protocol and/or standard(s).

The various protocols and communications can be communicated one or more of wirelessly and/or over transmission media such as single wire, twisted pair, fiber optic, IEEE 1394, MIL-STD-1553, MIL-STD-1773, power-line communication, or the like. (All of the above standards and protocols are incorporated herein by reference in their entirety).

As discussed, the communications subsystem **350** enables communications between any of the inter-vehicle systems and subsystems as well as communications with non-located resources, such as those reachable over a network such as the Internet.

The communications subsystem **350**, in addition to well-known componentry (which has been omitted for clarity), includes interconnected elements including one or more of: one or more antennas **504**, an interleaver/deinterleaver **508**, an analog front end (AFE) **512**, memory/storage/cache **516**, controller/microprocessor **520**, MAC circuitry **522**, modulator/demodulator **524**, encoder/decoder **528**, a plurality of connectivity managers **534**, **558**, **562**, **566**, GPU **540**, accelerator **544**, a multiplexer/demultiplexer **552**, transmitter **570**, receiver **572** and wireless radio **578** components such as a Wi-Fi PHY/Bluetooth® module **580**, a Wi-Fi/BT MAC module **584**, transmitter **588** and receiver **592**. The various elements in the device **350** are connected by one or more links/busses **5** (not shown, again for sake of clarity).

The device **350** can have one or more antennas **504**, for use in wireless communications such as multi-input multi-output (MIMO) communications, multi-user multi-input multi-output (MU-MIMO) communications Bluetooth®, LTE, 4G, 5G, Near-Field Communication (NFC), etc., and in general for any type of wireless communications. The antenna(s) **504** can include, but are not limited to one or more of directional antennas, omnidirectional antennas, monopoles, patch antennas, loop antennas, microstrip antennas, dipoles, and any other antenna(s) suitable for communication transmission/reception. In an exemplary embodiment, transmission/reception using MIMO may require particular antenna spacing. In another exemplary embodiment, MIMO transmission/reception can enable spatial diversity allowing for different channel characteristics at each of the antennas. In yet another embodiment, MIMO transmission/reception can be used to distribute resources to multiple users for example within the vehicle **100** and/or in another vehicle.

Antenna(s) **504** generally interact with the Analog Front End (AFE) **512**, which is needed to enable the correct processing of the received modulated signal and signal conditioning for a transmitted signal. The AFE **512** can be functionally located between the antenna and a digital baseband system in order to convert the analog signal into a digital signal for processing and vice-versa.

The subsystem **350** can also include a controller/microprocessor **520** and a memory/storage/cache **516**. The subsystem **350** can interact with the memory/storage/cache **516** which may store information and operations necessary for configuring and transmitting or receiving the information described herein. The memory/storage/cache **516** may also be used in connection with the execution of application programming or instructions by the controller/microprocessor **520**, and for temporary or long term storage of program instructions and/or data. As examples, the memory/storage/cache **520** may comprise a computer-readable device, RAM, ROM, DRAM, SDRAM, and/or other storage device(s) and media.

The controller/microprocessor **520** may comprise a general purpose programmable processor or controller for executing application programming or instructions related to the subsystem **350**. Furthermore, the controller/microprocessor **520** can perform operations for configuring and transmitting/receiving information as described herein. The controller/microprocessor **520** may include multiple processor cores, and/or implement multiple virtual processors. Optionally, the controller/microprocessor **520** may include multiple physical processors. By way of example, the controller/microprocessor **520** may comprise a specially configured Application Specific Integrated Circuit (ASIC) or other integrated circuit, a digital signal processor(s), a controller, a hardwired electronic or logic circuit, a programmable logic device or gate array, a special purpose computer, or the like.

The subsystem **350** can further include a transmitter **570** and receiver **572** which can transmit and receive signals, respectively, to and from other devices, subsystems and/or other destinations using the one or more antennas **504** and/or links/busses. Included in the subsystem **350** circuitry is the medium access control or MAC Circuitry **522**. MAC circuitry **522** provides for controlling access to the wireless medium. In an exemplary embodiment, the MAC circuitry **522** may be arranged to contend for the wireless medium and configure frames or packets for communicating over the wired/wireless medium.

The subsystem **350** can also optionally contain a security module (not shown). This security module can contain information regarding but not limited to, security parameters required to connect the device to one or more other devices or other available network(s), and can include WEP or WPA/WPA-2 (optionally+AES and/or TKIP) security access keys, network keys, etc. The WEP security access key is a security password used by Wi-Fi networks. Knowledge of this code can enable a wireless device to exchange information with an access point and/or another device. The information exchange can occur through encoded messages with the WEP access code often being chosen by the network administrator. WPA is an added security standard that is also used in conjunction with network connectivity with stronger encryption than WEP.

In some embodiments, the communications subsystem **350** also includes a GPU **540**, an accelerator **544**, a Wi-Fi/BT/BLE PHY module **580** and a Wi-Fi/BT/BLE MAC module **584** and wireless transmitter **588** and receiver **592**. In some embodiments, the GPU **540** may be a graphics processing unit, or visual processing unit, comprising at least one circuit and/or chip that manipulates and changes memory to accelerate the creation of images in a frame buffer for output to at least one display device. The GPU **540** may include one or more of a display device connection port, printed circuit board (PCB), a GPU chip, a metal-oxide-semiconductor field-effect transistor (MOSFET), memory (e.g., single data rate random-access memory (SDRAM), double data rate random-access memory (DDR) RAM, etc., and/or combinations thereof), a secondary processing chip (e.g., handling video out capabilities, processing, and/or other functions in addition to the GPU chip, etc.), a capacitor, heatsink, temperature control or cooling fan, motherboard connection, shielding, and the like.

The various connectivity managers **534**, **558**, **562**, **566** manage and/or coordinate communications between the subsystem **350** and one or more of the systems disclosed herein and one or more other devices/systems. The connectivity managers **534**, **558**, **562**, **566** include a charging connectivity manager **534**, a vehicle database connectivity

manager **558**, a remote operating system connectivity manager **562**, and a sensor connectivity manager **566**.

The charging connectivity manager **534** can coordinate not only the physical connectivity between the vehicle **100** and a charging device/vehicle, but can also communicate with one or more of a power management controller, one or more third parties and optionally a billing system(s). As an example, the vehicle **100** can establish communications with the charging device/vehicle to one or more of coordinate interconnectivity between the two (e.g., by spatially aligning the charging receptacle on the vehicle with the charger on the charging vehicle) and optionally share navigation information. Once charging is complete, the amount of charge provided can be tracked and optionally forwarded to, for example, a third party for billing. In addition to being able to manage connectivity for the exchange of power, the charging connectivity manager **534** can also communicate information, such as billing information to the charging vehicle and/or a third party. This billing information could be, for example, the owner of the vehicle, the driver/occupant(s) of the vehicle, company information, or in general any information usable to charge the appropriate entity for the power received.

The vehicle database connectivity manager **558** allows the subsystem to receive and/or share information stored in the vehicle database. This information can be shared with other vehicle components/subsystems and/or other entities, such as third parties and/or charging systems. The information can also be shared with one or more vehicle occupant devices, such as an app (application) on a mobile device the driver uses to track information about the vehicle **100** and/or a dealer or service/maintenance provider. In general any information stored in the vehicle database can optionally be shared with any one or more other devices optionally subject to any privacy or confidentially restrictions.

The remote operating system connectivity manager **562** facilitates communications between the vehicle **100** and any one or more autonomous vehicle systems. These communications can include one or more of navigation information, vehicle information, other vehicle information, weather information, occupant information, or in general any information related to the remote operation of the vehicle **100**.

The sensor connectivity manager **566** facilitates communications between any one or more of the vehicle sensors (e.g., the driving vehicle sensors and systems **304**, etc.) and any one or more of the other vehicle systems. The sensor connectivity manager **566** can also facilitate communications between any one or more of the sensors and/or vehicle systems and any other destination, such as a service company, app, or in general to any destination where sensor data is needed.

In accordance with one exemplary embodiment, any of the communications discussed herein can be communicated via the conductor(s) used for charging. One exemplary protocol usable for these communications is Power-line communication (PLC). PLC is a communication protocol that uses electrical wiring to simultaneously carry both data, and Alternating Current (AC) electric power transmission or electric power distribution. It is also known as power-line carrier, power-line digital subscriber line (PDSL), mains communication, power-line telecommunications, or power-line networking (PLN). For DC environments in vehicles PLC can be used in conjunction with CAN-bus, LIN-bus over power line (DC-LIN) and DC-BUS.

The communications subsystem can also optionally manage one or more identifiers, such as an IP (internet protocol) address(es), associated with the vehicle and one or other

system or subsystems or components therein. These identifiers can be used in conjunction with any one or more of the connectivity managers as discussed herein.

FIG. **6** illustrates a block diagram of a computing environment **600** that may function as the servers, user computers, or other systems provided and described herein. The computing environment **600** includes one or more user computers, or computing devices, such as a vehicle computing device **604**, a communication device **608**, and/or more **612**. The computing devices **604**, **608**, **612** may include general purpose personal computers (including, merely by way of example, personal computers, and/or laptop computers running various versions of Microsoft Corp.'s Windows® and/or Apple Corp.'s Macintosh® operating systems) and/or workstation computers running any of a variety of commercially-available UNIX® or UNIX-like operating systems. These computing devices **604**, **608**, **612** may also have any of a variety of applications, including for example, database client and/or server applications, and web browser applications. Alternatively, the computing devices **604**, **608**, **612** may be any other electronic device, such as a thin-client computer, Internet-enabled mobile telephone, and/or personal digital assistant, capable of communicating via a network **352** and/or displaying and navigating web pages or other types of electronic documents. Although the exemplary computing environment **600** is shown with two computing devices, any number of user computers or computing devices may be supported.

The computing environment **600** may also include one or more servers **614**, **616**. In this example, server **614** is shown as a web server and server **616** is shown as an application server. The web server **614**, which may be used to process requests for web pages or other electronic documents from computing devices **604**, **608**, **612**. The web server **614** can be running an operating system including any of those discussed above, as well as any commercially-available server operating systems. The web server **614** can also run a variety of server applications, including SIP (Session Initiation Protocol) servers, HTTP(s) servers, FTP servers, CGI servers, database servers, Java servers, and the like. In some instances, the web server **614** may publish operations available operations as one or more web services.

The computing environment **600** may also include one or more file and/or application servers **616**, which can, in addition to an operating system, include one or more applications accessible by a client running on one or more of the computing devices **604**, **608**, **612**. The server(s) **616** and/or **614** may be one or more general purpose computers capable of executing programs or scripts in response to the computing devices **604**, **608**, **612**. As one example, the server **616**, **614** may execute one or more web applications. The web application may be implemented as one or more scripts or programs written in any programming language, such as Java™, C, C#®, or C++, and/or any scripting language, such as Perl, Python, or TCL, as well as combinations of any programming/scripting languages. The application server(s) **616** may also include database servers, including without limitation those commercially available from Oracle®, Microsoft®, Sybase®, IBM® and the like, which can process requests from database clients running on a computing device **604**, **608**, **612**.

The web pages created by the server **614** and/or **616** may be forwarded to a computing device **604**, **608**, **612** via a web (file) server **614**, **616**. Similarly, the web server **614** may be able to receive web page requests, web services invocations, and/or input data from a computing device **604**, **608**, **612** (e.g., a user computer, etc.) and can forward the web page

requests and/or input data to the web (application) server **616**. In further embodiments, the server **616** may function as a file server. Although for ease of description, FIG. 6 illustrates a separate web server **614** and file/application server **616**, those skilled in the art will recognize that the functions described with respect to servers **614**, **616** may be performed by a single server and/or a plurality of specialized servers, depending on implementation-specific needs and parameters. The computer systems **604**, **608**, **612**, web (file) server **614** and/or web (application) server **616** may function as the system, devices, or components described in FIGS. 1-6.

The computing environment **600** may also include a database **618**. The database **618** may reside in a variety of locations. By way of example, database **618** may reside on a storage medium local to (and/or resident in) one or more of the computers **604**, **608**, **612**, **614**, **616**. Alternatively, it may be remote from any or all of the computers **604**, **608**, **612**, **614**, **616**, and in communication (e.g., via the network **610**) with one or more of these. The database **618** may reside in a storage-area network (“SAN”) familiar to those skilled in the art. Similarly, any necessary files for performing the functions attributed to the computers **604**, **608**, **612**, **614**, **616** may be stored locally on the respective computer and/or remotely, as appropriate. The database **618** may be a relational database, such as Oracle 20I®, that is adapted to store, update, and retrieve data in response to SQL-formatted commands.

FIG. 7 illustrates one embodiment of a computer system **700** upon which the servers, user computers, computing devices, or other systems or components described above may be deployed or executed. The computer system **700** is shown comprising hardware elements that may be electrically coupled via a bus **704**. The hardware elements may include one or more central processing units (CPUs) **708**; one or more input devices **712** (e.g., a mouse, a keyboard, etc.); and one or more output devices **716** (e.g., a display device, a printer, etc.). The computer system **700** may also include one or more storage devices **720**. By way of example, storage device(s) **720** may be disk drives, optical storage devices, solid-state storage devices such as a random access memory (“RAM”) and/or a read-only memory (“ROM”), which can be programmable, flash-updateable and/or the like.

The computer system **700** may additionally include a computer-readable storage media reader **724**; a communications system **728** (e.g., a modem, a network card (wireless or wired), an infra-red communication device, etc.); and working memory **736**, which may include RAM and ROM devices as described above. The computer system **700** may also include a processing acceleration unit **732**, which can include a DSP, a special-purpose processor, and/or the like.

The computer-readable storage media reader **724** can further be connected to a computer-readable storage medium, together (and, optionally, in combination with storage device(s) **720**) comprehensively representing remote, local, fixed, and/or removable storage devices plus storage media for temporarily and/or more permanently containing computer-readable information. The communications system **728** may permit data to be exchanged with a network and/or any other computer described above with respect to the computer environments described herein. Moreover, as disclosed herein, the term “storage medium” may represent one or more devices for storing data, including read only memory (ROM), random access memory (RAM), magnetic RAM, core memory, magnetic disk stor-

age mediums, optical storage mediums, flash memory devices and/or other machine readable mediums for storing information.

The computer system **700** may also comprise software elements, shown as being currently located within a working memory **736**, including an operating system **740** and/or other code **744**. It should be appreciated that alternate embodiments of a computer system **700** may have numerous variations from that described above. For example, customized hardware might also be used and/or particular elements might be implemented in hardware, software (including portable software, such as applets), or both. Further, connection to other computing devices such as network input/output devices may be employed.

Examples of the processors **340**, **708** as described herein may include, but are not limited to, at least one of Qualcomm® Snapdragon® 800 and 801, Qualcomm® Snapdragon® 620 and 615 with 4G LTE Integration and 64-bit computing, Apple® A7 processor with 64-bit architecture, Apple® M7 motion coprocessors, Samsung® Exynos® series, the Intel® Core™ family of processors, the Intel® Xeon® family of processors, the Intel® Atom™ family of processors, the Intel Itanium® family of processors, Intel® Core® i5-4670K and i7-4770K 22 nm Haswell, Intel® Core® i5-3570K 22 nm Ivy Bridge, the AMD® FX™ family of processors, AMD® FX-4300, FX-6300, and FX-8350 32 nm Vishera, AMD® Kaveri processors, Texas Instruments® Jacinto C6000™ automotive infotainment processors, Texas Instruments® OMAP™ automotive-grade mobile processors, ARM® Cortex™-M processors, ARM® Cortex-A and ARM926EJ-S™ processors, other industry-equivalent processors, and may perform computational functions using any known or future-developed standard, instruction set, libraries, and/or architecture.

Embodiments can provide an intelligent autonomous vehicle control system that augments the learned behaviors from autonomous vehicle driving operations with temporally, spatially, or event-limited identified behaviors and other autonomous driving information received from the intelligent autonomous vehicle control system. The temporally, spatially, or event-limited identified behaviors and other autonomous driving information can be learned by the control system monitoring the behaviors of multiple autonomous vehicles or other objects whose behavior is to be modeled by passing autonomous vehicles. The behaviors can be published by the control source by being pushed to selected vehicles and/or attached to navigation information. In this way, the learned behaviors of multiple vehicles can be shared via the control source, thereby decreasing accident rates and increasing vehicle safety.

The intelligent autonomous vehicle control system can embed identified autonomous driving information, such as commands, requests, warnings, logic, instructions, rules, references, identifiers, observed driving behaviors, or links to locally or remote stored autonomous driving rules, logic or instructions, in the navigation information provided by the navigation source **356A**. A flag can be included in the navigation information to indicate the existence of such embedded identified autonomous driving information.

A similar ad hoc network can be formed for the purpose of transmitting collected information to the navigation source **356A** or control source **356B**. A designated or master vehicle in the ad hoc network can transmit certain types of collected information common to multiple vehicles in the network, such as sensed object information and environmental information that are substantially duplicative from vehicle-to-vehicle, to the navigation source **356A** or control

source **356B** while uncommon types of collected information, such as sensed occupant information and vehicle-related information that are not duplicative vehicle-to-vehicle, are transmitted by each vehicle separately.

The intelligent autonomous vehicle control system (e.g., the master vehicle) can form an ad hoc wireless network with surrounding vehicles (e.g., the slave vehicles) and provide the embedded identified autonomous driving information to the networked vehicles. This can reduce significantly the bandwidth requirements to provide by the control source **356B** to provide navigation information and embedded identified autonomous driving information to each of the surrounding vehicles. Membership of the ad hoc wireless network and member role can change dynamically as vehicles move in and out of proximity to each other.

With reference to FIGS. **3** and **8-9**, the vehicle **100** is in wireless communication, via network **352**, with navigation source **356A** comprising a map database manager **812** and associated map database **816** and the control source **356B** having an associated control source database **824**.

The map database manager **812** and map database **816** interact with the navigation sensor **308** (which is part of the automatic vehicle location system **908** discussed below) in the vehicle **100** to provide navigation or map output to an autonomous driving agent **904** in the vehicle **100**.

The map database manager **812** stores and recalls navigation information from the map database **816**.

Maps are commonly stored as graphs, or two or three dimensional arrays of objects with attributes of location and category, where some common categories include parks, roads, cities, and the like. A map database commonly represents a road network along with associated features, with the road network corresponding to a selected road network model. Commonly, such a model comprises basic elements (nodes, links and areas) of the road network and properties of those elements (location coordinates, shape, addresses, road class, speed range, etc.). The basic elements are referred to as features and the properties as attributes. Other information associated with the road network can also be included, such as points of interest, waypoints, building shapes, and political boundaries. Geographic Data Files (GDF) is a standardized description of such a model. Each node within a map graph represents a point location of the surface of the Earth and can be represented by a pair of longitude (lon) and latitude (lat) coordinates. Each link can represent a stretch of road between two nodes, and be represented by a line segment (corresponding to a straight section of road) or a curve having a shape that is generally described by intermediate points (called shape points) along the link. However, curves can also be represented by a combination of centroid (point or node), with a radius, and polar coordinates to define the boundaries of the curve. Shape points can be represented by longitude and latitude coordinates as are nodes, but shape points generally do not serve the purpose of connecting links, as do nodes. Areas are generally two- or three-dimensional shapes that represent things like parks, cities, blocks and are defined by their boundaries (usually formed by a closed polygon).

Auxiliary data can be attached by the map database manager **812** to the features and/or attributes. The auxiliary data can be not only various navigational functions, involving active safety, and driver assistance but also identified autonomous driving information relating to an autonomous vehicle or other object to be sensed by passing autonomous vehicles, such as observed behaviors of other autonomous vehicles or an object at the map location, to be applied at the corresponding geographic locations. The auxiliary data, for

example, can comprise identified embedded autonomous driving information, such as commands to the receiving autonomous driving agent, requests to the receiving autonomous driving agent, warnings to the receiving autonomous driving agent, (e.g., of potential hazards such as potholes, hazardous objects in or near the roadway, poor roadway conditions (such as icy or wet), heavy traffic warning, emergency vehicle or personnel-related warning, vehicle wreck warning, road construction warning, bridge or roadway out warning, high water or flood warning, and the like) logic, instructions or rules to be employed by the receiving autonomous driving agent, references, identifiers, observed behaviors, or links to locally or remote stored autonomous driving rules, logic or instructions to be employed the receiving autonomous driving agent, in the navigation information provided by the navigation source **356A**.

The identified autonomous driving information embedded in the navigation information as auxiliary data can include temporal, spatial, or event-limitations learned by the control system monitoring the behaviors of multiple autonomous vehicles. The identified autonomous driving information can be limited in application by temporal limitations (e.g., identified behavior application start and end times), spatial limitations (e.g., sets of geographical coordinates defining an area in or location at which the identified autonomous driving information is to be applied), or event limitations (e.g., a defined event (such as a weather storm event, ambient temperature range (such as below freezing), set of road conditions, etc.) during which the identified autonomous driving information is to be applied but after which the autonomous driving information is not to be applied).

The auxiliary data fields can include a flag to indicate the existence of such identified embedded autonomous driving information relating to an autonomous vehicle or other object to be sensed by passing autonomous vehicles. When the flag is set, the autonomous vehicle driving agent accesses the field(s) dedicated to identified embedded autonomous driving information and, when the flag is not set, the autonomous vehicle driving agent does not access the field (s) as they are deemed not to contain identified autonomous driving information.

The functions and other auxiliary data can be cross-referenced with the entities and attributes of the main map database **816**. Since the auxiliary data is not necessarily compiled with the main map database **816** some other means is generally needed to establish cross-referencing, or attaching of the auxiliary data. The common approaches are function-specific referencing tables and generic referencing.

Function-specific referencing tables provide a technique for attaching function-specific data, such as embedded identified autonomous driving information relating to an autonomous vehicle or other object to be sensed by passing autonomous vehicles, to the map database **816**. Such a table can be collaboratively produced by the navigation source **356A** and control source **356B** to support a specific function or class of functions involving location-based behaviors or embedded identified autonomous driving information. It will generally include a list of map elements of a specific type (e.g., links, intersections, point-of-interest locations, etc.) along with identifying attributes (e.g., street names, longitude/latitude coordinates, etc.). Additionally, each entry in the table can be assigned a unique identifier. As a practical matter, the result will represent a small subset of the elements of the given type that are available in the map databases and will include those that are more important to the application area.

Generic referencing attaches data, such as observed behaviors and embedded identified autonomous driving information relating to an autonomous vehicle or other object to be sensed by passing autonomous vehicles, to any map database by discovering reference information through a form of map matching. The function-specific data items can be assigned to elements, such as points, links or areas, that likely only approximate the corresponding map elements in a specific map database **816**. A search of the map database can be made for the best fit. To enhance the search process, neighboring elements can be strategically appended to each given element to help ensure that the correct solution is found in each case. For example, if the map element is a link connecting two intersections, then one or both cross streets could be appended for the sake of the search thereby making an incorrect match unlikely.

By way of illustration, the Navigation Data Standard (NDS) is a standardized format for automotive-grade navigation databases. NDS uses the SQLite Database File Format. An NDS database can have several product databases, and each product database may be divided further into update regions. This concept supports a flexible and consistent versioning concept for NDS databases and makes it possible to integrate databases from different database suppliers into one NDS database. The inner structure of databases complying with Navigation Data Standard is further characterized by building blocks, levels and the content itself. An update region represents a geographic area in a database that can be subject to an update. All navigation data in an NDS database belongs a specific building block. Each building block addresses specific functional aspects of navigation, such as names for location input, routing, or map display.

Alternatively, the control source **356B** can push the identified autonomous driving information directly to the autonomous driving agent based on the selected vehicle location and not incorporate or reference the identified autonomous driving information in the navigation information.

The control source **356B** and control source database **824** interact with the autonomous driving agent **904** in each vehicle **100** to receive various types of information regarding vehicle behavior and the behaviors of nearby objects, such as other vehicles and pedestrians, identify specific behaviors and other autonomous driving information, and directly or indirectly provide the autonomous driving information to selected vehicles for use in determining and selecting various autonomous vehicle commands or settings, particularly acceleration rate of the vehicle, deceleration (e.g., braking) rate of the vehicle, steering angle of the vehicle (e.g., for turns and lane changes), and inter-object spacing (e.g., end-to-end or side-to-side spacing between the vehicle and a nearby object).

The map and control source databases **816** and **824** can be constructed according to any data model, whether conceptual, logical, or physical, such as a flat model, hierarchical model, network model, relational model, object-relational model, star schema, entity-relationship model, geographic model, generic model, semantic model, and the like.

Each learned or identified behavior (or other autonomous driving information) is described typically by output behavior and associated with a corresponding set of limitations. By way of illustration, the output behavior is typically a driving behavior of the car, such as use a specified lane, slow to a selected speed, gently apply brakes, turn lights on, use inter-vehicle spacing of X meters, transition from a lower level of automation to a higher level or vice versa, and the

like. The learned or identified behavior can be further described with reference to a set of sensed inputs.

The sensed inputs can vary by corresponding object type but include one or more of geographic or spatial vehicle location, sensed object information **970** (with examples being animate objects such as animals and attributes thereof (e.g., animal type, current spatial location, current activity, etc.), and pedestrians and attributes thereof (e.g., identity, age, sex, current spatial location, current activity, etc.), and the like and inanimate objects and attributes thereof such as other vehicles (e.g., current vehicle state or activity (parked or in motion or level of automation currently employed), occupant or operator identity, vehicle type (truck, car, etc.), vehicle spatial location, etc.), curbs (topography and spatial location), potholes (size and spatial location), lane division markers (type or color and spatial locations), signage (type or color and spatial locations such as speed limit signs, yield signs, stop signs, and other restrictive or warning signs), traffic signals (e.g., red, yellow, blue, green, etc.), buildings (spatial locations), walls (height and spatial locations), barricades (height and spatial location), and the like), sensed occupant information **916** (with examples being number and identities of occupants and attributes thereof (e.g., seating position, age, sex, gaze direction, biometric information, authentication information, preferences, historic behavior patterns (such as current or historical user driving behavior, historical user route, destination, and waypoint preferences), nationality, ethnicity and race, language preferences (e.g., Spanish, English, Chinese, etc.), current occupant role (e.g., operator or passenger), occupant priority ranking (e.g., vehicle owner is given a higher ranking than a child occupant), electronic calendar information (e.g., Outlook™), medical information and history, etc.), selected vehicle-related information **982** (with examples being vehicle manufacturer, type, model, year of manufacture, current geographic location, current vehicle state or activity (parked or in motion or level of automation currently employed), vehicle specifications and capabilities, currently sensed operational parameters for the vehicle, and other information), exterior environmental information **986** (with examples being road type (pavement, gravel, brick, etc.), road condition (e.g., wet, dry, icy, snowy, etc.), weather condition (e.g., outside temperature, pressure, humidity, wind speed and direction, etc.), ambient light conditions (e.g., time-of-day), degree of development of vehicle surroundings (e.g., urban or rural), and the like), occupant commands or other input, and other information.

The identified behavior or other autonomous driving information can be based on observations of repetitive behavior of multiple vehicles observed at a specific map location or area or in response to an event (e.g., any of the sensed object information **970** or sensed environmental information **986**) or during a specified time-of-day.

The application or usage of the identified behavior can be limited temporally, spatially, or by occurrence or duration of an event. While the application or usage of the identified behavior is permitted by the corresponding limitation, the identified behavior and other autonomous driving information is used instead of learned behaviors and other autonomous driving information of the vehicle. When the application or usage of the identified behavior and other autonomous driving information is not permitted by the corresponding limitation (e.g., the vehicle is outside the spatially limited area, the time duration of the behavior is expired, or the event has terminated or otherwise ended), the learned behavior and other autonomous driving information of the vehicle is employed.

With reference to FIG. 9, an on board autonomous driving system 900 in the vehicle 100 is depicted that employs one or more of the foregoing features. The autonomous driving system 900 includes an autonomous driving agent 904 in communication with an automatic vehicle location system 908, sensor connectivity manager 566 and associated first, second, . . . Mth sensors 912a-M, user interface 920, and authentication system 978, and having access via working memory 736 or communication systems 728 to the sensed object information 970, sensed occupant information 916, learned autonomous driving information 974, vehicle-related information 982, exterior environmental information 986, and navigation information 924.

The automatic vehicle location system 908 is in communication with the GPS/Nav sensor 308 to acquire current vehicle position coordinates, which position coordinates are then correlated by the map database manager 812 to a position on a road. Dead reckoning using distance data from one or more sensors attached to the drive train, a gyroscope sensor 312 and/or an accelerometer sensor 312 can be used for greater reliability, as GPS signal loss and/or multipath can occur due to the map database manager 812, such as due to a cellular signal dead or low signal strength area or passage of the vehicle through a tunnel.

The first, second, . . . mth sensors 912a-m can collect the sensed object information 970, sensed occupant information 916, vehicle-related information 982, and exterior environmental information 986. The first, second, . . . mth sensors 912a-m include the sensors or systems 116A-K, 112, 312, 316, 320, 324, 328, 332, 336, and 338 discussed above, a camera to capture images of interior objects (such as occupants), a seat belt sensor to determine seat belt settings (e.g., closed or open), a seat weight sensor settings, a microphone to capture audio within the vehicle (such as occupant comments which are then input into a speech-to-text engine to determine or identify one or more words spoken by an occupant), a wireless network node that receives unique identifiers of occupant portable computing devices (which identifiers can be associated with a corresponding occupant to identify the occupant), and the like. In some applications, a portable computing device of the occupant can be employed as a sensor that tracks occupant behavior while the occupant is in the vehicle. The information collected by the sensors is received by the sensor connectivity manager 566 and provided to the autonomous driving agent 904 and/or to the control source 356B.

The user interface 920 receives user commands and other input, such as user selections, preferences, and settings that are used in configuring, determining, and selecting vehicle parameters, settings, or operations, such as navigation route selection, acceptable rates of acceleration and deceleration, acceptable minimum inter-object spacing distance, and acceptable steering lines, and stimuli or events triggering associated rule-based actions. The user interface 920 can be one or more of vehicle instrument panel 400, vehicle operational display 420, heads-up display 434, and power management display 428. It can also be a portable computational or communication device of an occupant.

The behavior selector 978 determines which behavior logic and other autonomous driving information is to be employed by the vehicle. The behavior selector 978 can determine therefore which locally stored (e.g., in working memory 736) learned behavior or other autonomous driving information 974 is to be executed or implemented and which identified or learned behavior of other autonomous driving information is to be executed or implemented.

The autonomous driving agent 904 controls the driving behavior of the vehicle, such as whether to execute an accelerate event, acceleration rate, decelerate event, deceleration rate, steering angle selected relative to a selected reference axis, and selected inter-object spacing magnitude in response to the current vehicle location, sensed object information 970, sensed occupant information 916, vehicle-related information 982, exterior environmental information 986, and navigation information 924 in accordance with the autonomous driving information selected by the behavior selector 978 and implemented by the autonomous driving agent 904. In a typical implementation, the autonomous driving agent, based on feedback from certain sensors, specifically the LIDAR and radar sensors positioned around the circumference of the vehicle, constructs a three-dimensional map in spatial proximity to the vehicle that enables the autonomous driving agent to identify and spatially locate animate and inanimate objects. Other sensors, such as inertial measurement units, gyroscopes, wheel encoders, sonar sensors, motion sensors to perform odometry calculations with respect to nearby moving objects, and exterior facing cameras (e.g., to perform computer vision processing) can provide further contextual information for generation of a more accurate three-dimensional map. The navigation information is combined with the three-dimensional map to provide short, intermediate and long range course tracking and route selection. The autonomous driving system processes real-world information as well as GPS data, and driving speed to determine accurately the precise position of each vehicle, down to a few centimeters all while making corrections for nearby animate and inanimate objects.

The autonomous driving agent 904 processes in real time the aggregate mapping information and models behavior of occupants of the current vehicle and other nearby animate objects relying on the behavior selector's selected autonomous driving information. The autonomous driving information can be generically applied to multiple types, models, and manufacturer of vehicles or specific to a specific type, model, or manufacturer of vehicle. The applicability of the respective set of identified autonomous driving information can be stored as part of the data structures comprising the identified autonomous driving information.

In some applications, the behavior selector 978 selects between learned and identified autonomous driving information for a nearby object in the sensed object information 970. The selected autonomous driving information is used to model the behavior of the nearby object and therefore determining a behavior of the selected vehicle to be implemented by the autonomous driving agent.

The autonomous driving agent, based on the learned and autonomous driving information, issues appropriate commands regarding implementing an accelerate event, acceleration rate, deceleration event, deceleration rate, inter-object spacing distance, and steering angle magnitude. While some commands are hard-coded into the vehicle, such as stopping at red lights and stop signs, other responses are learned and recorded by the control source or autonomous driving agent based on previous driving experiences.

The learning ability of the control source is based on monitoring the behavior of multiple vehicles and of the autonomous driving agent is based on monitoring the behavior of the selected vehicle hosting the autonomous driving agent. Examples of learned behavior include a slow-moving or stopped vehicle or emergency vehicle in a right lane suggests a higher probability that the car following it will attempt to pass, a pot hole, rock, or other foreign object in the roadway equates to a higher probability that a driver will

swerve to avoid it, and traffic congestion in one lane means that other drivers moving in the same direction will have a higher probability of passing in an adjacent lane or by driving on the shoulder.

As more and more vehicles drive the selected route of the selected vehicle, sensor collected information of the vehicle can be provided in substantial real time to the map database manager 812 to enable it to generate a detailed three-dimensional map as the navigation information. This in effect uses each vehicle as a mapping information source to enable detailed and accurate three dimensional maps to be developed. If every vehicle were to provide this collected information, however, bandwidth constraints and limitations would create problems not only for transmission of the collected information but also for other communication services, such as cell phone bandwidth.

One solution is to form ad hoc wireless networks of vehicles to reduce the bandwidth consumed by reporting of the collected information by multiple nearby vehicles. The ad hoc wireless network can be formed to accommodate peer-to-peer communications not only for the purpose of transmitting collected information to but also receiving navigation information and autonomous driving information from the navigation source 356A and/or control source 356B. A designated or master vehicle in the ad hoc network can transmit certain types collected information common to multiple vehicles in the network, such as sensed object information and environmental information that are substantially duplicative from vehicle-to-vehicle, to the navigation source 356A or control source 356B while uncommon types of collected information, such as sensed occupant information and vehicle-related information that are not duplicative vehicle-to-vehicle, are transmitted by each vehicle separately. Likewise, the designated or master vehicle in the ad hoc network can receive the navigation information or autonomous driving information and transmit all or part of it to multiple vehicles in the network.

As will be appreciated, a wireless ad hoc network (WANET) is a decentralized type of wireless network. It is ad hoc because it does not rely on a pre-existing infrastructure. A wireless ad-hoc network, also known as IBSS—Independent Basic Service Set, is a computer network in which the communication links are wireless. The network is ad-hoc because each node can forward data for other nodes, and so the determination of which nodes forward data is made dynamically based on a number of factors, such as token possession, network connectivity, spatial location, and the like.

By way of example, the wireless ad hoc network can be a vehicular ad hoc network or VANET. VANETs can provide communication between vehicles. Intelligent vehicular ad hoc networks (InVANETs) are a kind of artificial intelligence that helps vehicles to behave in an intelligent manner or cooperatively. Radio waves can be used to enable vehicle inter-communication but other wireless communication modalities, channels, and protocols can be employed.

The wireless ad hoc network can be based on other mechanisms, such as mobile ad hoc networks (MANETs), smartphone ad hoc networks (SPANs), and Internet-based mobile ad hoc networks (iMANETs). Wireless ad hoc networks can beneficially provide networking that does not require expensive infrastructure, that uses an unlicensed frequency spectrum, that provides a quick distribution of information, and that does not have a single point of failure.

To overcome problems caused by the frequent breakage or disconnection and reconnection of links due to the high mobility of the nodes a cross-layer design can be provided

that deviates from the traditional network design approach in which each layer of the stack would be made to operate independently. A modified transmission power can help a node to dynamically vary its propagation range at the physical layer. This is because the propagation distance is generally directly proportional to transmission power. This information is passed from the physical layer to the network layer so that it can make optimal decisions in routing protocols. This protocol can allow access of information between physical layer and top layers (MAC and network layer).

Different routing protocols can be employed. In distance vector routing, each vehicle or node maintains one or more dynamically updated routing tables. Distance-vector protocols are based on calculating the direction and distance to any link in a network. “Direction” usually means the next hop address and the exit interface. “Distance” is a measure of the cost to reach a certain node. The least cost route between any two nodes is the route with minimum distance. Each node maintains a vector (table) of minimum distance to every node. The cost of reaching a destination is calculated using various route metrics. RIP uses the hop count of the destination whereas IGRP takes into account other information such as node delay and available bandwidth. In reactive routing, the node finds a route based on user and traffic demand by flooding the network with Route Request or Discovery packets. Clustering of the vehicles can be used to limit flooding. In flooding, every incoming packet is sent through every outgoing link except the one it arrived on. In hybrid routing, routing is initially established with some proactively prospected routes and then serves the demand from additionally activated nodes through reactive flooding. In position-based routing, information on the exact locations of the nodes is obtained for example via a GPS receiver. Based on the exact location, the best path between source and destination nodes can be determined.

To reduce collisions caused by nodes competing for the shared wireless medium, centralized scheduling or distributed contention access protocols can be used. Using cooperative wireless communications can improve immunity to interference by having the destination node combine self-interference and other-node interference to improve decoding of the desired signals.

The ad hoc wireless network can be formed in many ways. For example, the particular vehicles in the network at any time can be based on one or more factors, including spatial location or proximity, received signal strength for signals received from other vehicles to be included in the network, direction of travel, nature of roadway (e.g., divided or not, number of lanes, etc.), vehicle type, model or manufacturer, and other factors appreciated by one of skill in the art.

To avoid inter-vehicle conflicts as to which vehicle in the network is the master vehicle within the ad hoc network, an arbitration process can be employed. The arbitration process can be based on any technique known in the art for other applications, including ownership of a token, earliest timestamp of receiving selected navigation or autonomous driving information, oldest timestamp of membership in the network, nearest vehicle to the relevant feature or location for the selected navigation or autonomous driving information, vehicle route selected, and the like.

Membership of the ad hoc wireless network and member role can change dynamically as vehicles move in and out of proximity to each other. Vehicles therefore can send notifications that they are leaving the network or requests to be admitted to the network. The network can be substantially

fixed at a set of spatial map coordinates or move with a designated master vehicle. As will be appreciated, multiple ad hoc networks generally exist at any one time involving different sets of vehicles with different sets of members. A vehicle is generally a member of only one of the many ad hoc networks used by the control source and navigation source

To avoid duplication, the master vehicle sends notifications to the navigation source **356A** or control source **356B** identifying (by electronic address or other unique identifier) which vehicles in the ad hoc wireless network (a) acknowledged receipt of the selected navigation information or autonomous driving information to avoid duplicate transmission of the information by the appropriate one of the navigation source and control source or (b) acknowledged receipt of notification that certain types of collected information would be transmitted by the master vehicle and not by the other vehicle in the network.

The autonomous driving agent can be configured to handle other autonomous operations, regardless of automation level. Examples include adaptive cruise control, lane keeping, parking functions, and the like.

The operations of the various executable modules will now be discussed with reference to FIGS. **10-13**.

With reference to FIG. **10**, the autonomous driving agent **904**, in step **1000**, detects a stimulus, such as any set forth above, and commences execution of the instructions. Exemplary stimuli include, for example, detection of a change in any of the previously sensed vehicle location, sensed object information **970**, sensed occupant information **916**, vehicle-related information **982**, exterior environmental information **986**, and/or navigation information **924** and/or in learned autonomous driving information **974**.

In step **1004**, the autonomous driving agent **904** determines from the automatic vehicle location system **908** the current geographical location of the vehicle **100**.

In step **1008**, the autonomous driving agent **904** collects vehicle-related information **982** from the sensor connectivity manager **566**.

In step **1012**, the autonomous driving agent **904** collects occupant-related information **916**, such as the information set forth above. This includes, for example, the identities of the vehicle occupants, the roles of each identified occupant (e.g., driver or passenger), a current activity of each occupant (e.g., operating vehicle, operating portable computing device, interacting with an on board vehicle user interface, and the like), gaze detection of an occupant, and the like.

In step **1016**, the autonomous driving agent **904** collects sensed exterior environmental information **986** from the sensor connectivity manager **566**.

In step **1020**, the autonomous driving agent **908** collects sensed animate and inanimate object information **970** from the sensor connectivity manager **566**.

In step **1024**, the autonomous driving agent **908** forwards all or part of the foregoing collected information, via communications subsystem **350** and network **352**, to the navigation or control source as appropriate. As noted, how much of the collected information is transmitted can depend on whether or not the vehicle of the autonomous driving agent is the master or slave vehicle in the ad hoc network comprising the vehicle. In general, the types of collected information unique to the vehicle, including sensed occupant information **916**, vehicle location, and vehicle-related information **982** is always transmitted by the vehicle, whether acting as a master or slave vehicle, while the types of collected information that are common to the vehicles in the network, including sensed object information **970** and envi-

ronmental information **986**, is generally transmitted by the master vehicle and not the slave vehicles.

With reference to FIG. **11**, the navigation source and/or control source, in step **1100**, receives the collected information from the autonomous driving agent of the selected vehicle along with a unique identifier of the vehicle (such as an identity of the owner, electronic address of the vehicle, serial number or vehicle identification number of the vehicle, and the like).

In step **1104**, the navigation source and/or control source stores the collected information in the control source database along with the unique vehicle identifier and/or an identifier of an occupant of the vehicle **100**.

In step **1108**, the control source identifies autonomous driving information for publication to other autonomous vehicles and selects limitation(s), if any, on the identified autonomous driving information. This step can be based on recognition of a novel behavior by the reporting vehicle, a previously unknown hazard or object encountered by the reporting vehicle at all map locations or at the respective map location, at least a minimum frequency of usage of the behavior by multiple vehicles, including the reporting vehicle, at the respective map location, and the like.

In step **1112**, the control source determines whether to select other autonomous vehicles to receive the identified autonomous driving information or to embed autonomous driving information in navigation information provided by the navigation source. This determination can be based for instance on one or more of the criteria referenced in step **1108**.

In step **1116**, the control source causes the identified autonomous driving information to be pushed to selected autonomous vehicles or included by the navigation source in navigation information.

With reference to FIG. **12**, the autonomous driving agent **904**, in step **1200**, detects a stimulus, such as any set forth above, and commences execution of the instructions. Exemplary stimuli include, for example, activation of a level of autonomous operation, increase to a higher or decrease to a lower level of autonomous operation (e.g., from Level 0 to Level 1, Level 1 to Level 2, Level 2 to Level 3, or Level 3 to Level 4), sensed vehicle location having a certain set of values, user input, or detection of a change in any of the previously sensed vehicle location, sensed object information **970**, sensed occupant information **916**, vehicle-related information **982**, exterior environmental information **986**, and/or navigation information **924**.

In step **1204**, the behavior selector retrieves or receives learned and identified autonomous driving information and determines which of the learned and identified autonomous driving information is to be employed for the current vehicle and in modeling behavior of nearby objects.

In step **1208**, the autonomous driving agent **904** determines from the automatic vehicle location system **908** a current location of the selected vehicle and receives from the sensor connectivity manager **966** current vehicle-related and occupant-related information **982** and **916** and exterior environmental and object information **986** and **970**.

In step **1212**, the autonomous driving agent **904** processes the determined information to provide contextual information identifying nearby objects, relevant map information, signage, and other factors.

In step **1216**, the autonomous driving agent **904**, based on the contextual information and learned or identified autonomous driving information, predicts a behavior of the nearby objects.

In step 1220, the autonomous driving agent, based on current vehicle- and occupant-related information 982 and 916, exterior environmental and object information 986 and 970, and other contextual information and the predicted behavior of nearby objects and the selected one of the learned and identified autonomous driving information, determines acceleration events, deceleration events, acceleration rate, deceleration rate, steering angle and inter-object spacing.

In step 1224, the autonomous driving agent then issues appropriate commands to other vehicle components, such as steering, braking, and throttle assemblies, to execute the determined instructions.

With reference to FIG. 13, the autonomous driving agent, in step 1300, detects a stimulus, such as any set forth above, and commences execution of the instructions. Exemplary stimuli include, for example, activation of a level of autonomous operation, increase to a higher or decrease to a lower level of autonomous operation (e.g., from Level 0 to Level 1, Level 1 to Level 2, Level 2 to Level 3, or Level 3 to Level 4), sensed vehicle location having a certain set of values, user input, or detection of a change in any of the previously sensed vehicle location, sensed object information 970, sensed occupant information 916, vehicle-related information 982, exterior environmental information 986, and/or navigation information 924.

In step 1304, the autonomous driving agent determines a current vehicle location.

In step 1308, the autonomous driving agent, when not currently in an ad hoc network, identifies nearby vehicles.

In optional step 1312, the autonomous driving agent determines whether an ad hoc network already includes one or more of the identified nearby vehicles and, if so, joins the appropriate ad hoc network.

In optional step 1316, the autonomous driving agent determines that no ad hoc network has yet been formed and determines which nearby vehicles to include in a newly formed ad hoc network.

In optional step 1320, the autonomous driving agent forms the ad hoc network.

In step 1324, the autonomous determines which vehicle in the existing or newly formed ad hoc network is or should be the master vehicle and which vehicle(s) are the slave vehicles and adopts and implements the appropriate role in the ad hoc network.

With reference to FIG. 14, the logical instructions are executed by an arithmetic/logic unit (“ALU”), which performs mathematical operations, such as addition, subtraction, multiplication, and division, machine instructions, an address bus (that sends an address to memory), a data bus (that can send data to memory or receive data from memory), a read and write line to tell the memory whether to set or get the addressed location, a clock line that enables a clock pulse to sequence the processor, and a reset line that resets the program counter to zero or another value and restarts execution. The arithmetic/logic unit can be a floating point processor that performs operations on floating point numbers. The autonomous driving agent 904, behavior selector, control source and/or navigation source further includes first, second, and third registers that are typically configured from flip-flops, an address latch, a program counter (which can increment by “1” and reset to “0”), a test register to hold values from comparisons performed in the arithmetic/logic unit (such as comparisons in any of the steps in FIGS. 10-13), plural tri-state buffers to pass a “1” or “0” or disconnect its output (thereby allowing multiple outputs to connect to a wire but only one of them to actually

drive a “1” or “0” into the line), and an instruction register and decoder to control other components. Control lines, in the autonomous driving agent 904, behavior selector, control source and/or navigation source, from the instruction decoder can: command the first register to latch the value currently on the data bus, command the second register to latch the value currently on the data bus, command the third register to latch the value currently output by the ALU, command the program counter register to latch the value currently on the data bus, command the address register to latch the value currently on the data bus, command the instruction register to latch the value currently on the data bus, command the program counter to increment, command the program counter to reset to zero, activate any of the plural tri-state buffers (plural separate lines), command the ALU what operation to perform, command the test register to latch the ALU’s test bits, activate the read line, and activate the write line. Bits from the test register and clock line as well as the bits from the instruction register come into the instruction decoder. Hardware similar or identical to that of FIG. 14 is in each of the autonomous driving agent 904, behavior selector, control source and/or navigation source for executing the instructions of FIGS. 10-13. The ALU executes instructions for a random or pseudo-random number generation algorithm and generates the recipient identifier using the appropriate seed values.

Any of the steps, functions, and operations discussed herein can be performed continuously and automatically.

The exemplary systems and methods of this disclosure have been described in relation to vehicle systems and electric vehicles. However, to avoid unnecessarily obscuring the present disclosure, the preceding description omits a number of known structures and devices. This omission is not to be construed as a limitation of the scope of the claimed disclosure. Specific details are set forth to provide an understanding of the present disclosure. It should, however, be appreciated that the present disclosure may be practiced in a variety of ways beyond the specific detail set forth herein.

Furthermore, while the exemplary embodiments illustrated herein show the various components of the system collocated, certain components of the system can be located remotely, at distant portions of a distributed network, such as a LAN and/or the Internet, or within a dedicated system. Thus, it should be appreciated, that the components of the system can be combined into one or more devices, such as a server, communication device, or collocated on a particular node of a distributed network, such as an analog and/or digital telecommunications network, a packet-switched network, or a circuit-switched network. It will be appreciated from the preceding description, and for reasons of computational efficiency, that the components of the system can be arranged at any location within a distributed network of components without affecting the operation of the system.

Furthermore, it should be appreciated that the various links connecting the elements can be wired or wireless links, or any combination thereof, or any other known or later developed element(s) that is capable of supplying and/or communicating data to and from the connected elements. These wired or wireless links can also be secure links and may be capable of communicating encrypted information. Transmission media used as links, for example, can be any suitable carrier for electrical signals, including coaxial cables, copper wire, and fiber optics, and may take the form of acoustic or light waves, such as those generated during radio-wave and infra-red data communications.

While the flowcharts have been discussed and illustrated in relation to a particular sequence of events, it should be

appreciated that changes, additions, and omissions to this sequence can occur without materially affecting the operation of the disclosed embodiments, configuration, and aspects.

A number of variations and modifications of the disclosure can be used. It would be possible to provide for some features of the disclosure without providing others.

In yet another embodiment, the systems and methods of this disclosure can be implemented in conjunction with a special purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit element(s), an ASIC or other integrated circuit, a digital signal processor, a hard-wired electronic or logic circuit such as discrete element circuit, a programmable logic device or gate array such as PLD, PLA, FPGA, PAL, special purpose computer, any comparable means, or the like. In general, any device(s) or means capable of implementing the methodology illustrated herein can be used to implement the various aspects of this disclosure. Exemplary hardware that can be used for the present disclosure includes computers, handheld devices, telephones (e.g., cellular, Internet enabled, digital, analog, hybrids, and others), and other hardware known in the art. Some of these devices include processors (e.g., a single or multiple microprocessors), memory, nonvolatile storage, input devices, and output devices. Furthermore, alternative software implementations including, but not limited to, distributed processing or component/object distributed processing, parallel processing, or virtual machine processing can also be constructed to implement the methods described herein.

In yet another embodiment, the disclosed methods may be readily implemented in conjunction with software using object or object-oriented software development environments that provide portable source code that can be used on a variety of computer or workstation platforms. Alternatively, the disclosed system may be implemented partially or fully in hardware using standard logic circuits or VLSI design. Whether software or hardware is used to implement the systems in accordance with this disclosure is dependent on the speed and/or efficiency requirements of the system, the particular function, and the particular software or hardware systems or microprocessor or microcomputer systems being utilized.

In yet another embodiment, the disclosed methods may be partially implemented in software that can be stored on a storage medium, executed on programmed general-purpose computer with the cooperation of a controller and memory, a special purpose computer, a microprocessor, or the like. In these instances, the systems and methods of this disclosure can be implemented as a program embedded on a personal computer such as an applet, JAVA® or CGI script, as a resource residing on a server or computer workstation, as a routine embedded in a dedicated measurement system, system component, or the like. The system can also be implemented by physically incorporating the system and/or method into a software and/or hardware system.

Although the present disclosure describes components and functions implemented in the embodiments with reference to particular standards and protocols, the disclosure is not limited to such standards and protocols. Other similar standards and protocols not mentioned herein are in existence and are considered to be included in the present disclosure. Moreover, the standards and protocols mentioned herein and other similar standards and protocols not mentioned herein are periodically superseded by faster or more effective equivalents having essentially the same func-

tions. Such replacement standards and protocols having the same functions are considered equivalents included in the present disclosure.

The present disclosure, in various embodiments, configurations, and aspects, includes components, methods, processes, systems and/or apparatus substantially as depicted and described herein, including various embodiments, sub-combinations, and subsets thereof. Those of skill in the art will understand how to make and use the systems and methods disclosed herein after understanding the present disclosure. The present disclosure, in various embodiments, configurations, and aspects, includes providing devices and processes in the absence of items not depicted and/or described herein or in various embodiments, configurations, or aspects hereof, including in the absence of such items as may have been used in previous devices or processes, e.g., for improving performance, achieving ease, and/or reducing cost of implementation.

The foregoing discussion of the disclosure has been presented for purposes of illustration and description. The foregoing is not intended to limit the disclosure to the form or forms disclosed herein. In the foregoing Detailed Description for example, various features of the disclosure are grouped together in one or more embodiments, configurations, or aspects for the purpose of streamlining the disclosure. The features of the embodiments, configurations, or aspects of the disclosure may be combined in alternate embodiments, configurations, or aspects other than those discussed above. This method of disclosure is not to be interpreted as reflecting an intention that the claimed disclosure requires more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive aspects lie in less than all features of a single foregoing disclosed embodiment, configuration, or aspect. Thus, the following claims are hereby incorporated into this Detailed Description, with each claim standing on its own as a separate preferred embodiment of the disclosure.

Moreover, though the description of the disclosure has included description of one or more embodiments, configurations, or aspects and certain variations and modifications, other variations, combinations, and modifications are within the scope of the disclosure, e.g., as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It is intended to obtain rights, which include alternative embodiments, configurations, or aspects to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges, or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures, functions, ranges, or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

Embodiments include a vehicle comprising:

- a vehicle interior for receiving one or more occupants;
- a plurality of sensors to collect sensed information associated with the vehicle interior and an exterior of the vehicle;
- an automatic vehicle location system to determine a current spatial location of the vehicle;
- a computer readable medium to store learned autonomous driving information describing a behavioral response of the vehicle to prior sensed information when the vehicle is in an autonomous mode of operation and identified autonomous driving information describing a behavioral response of other vehicles to sensed information collected by the other vehicles when in an autonomous mode of operation; and
- a microprocessor, coupled to the plurality of sensors, automatic vehicle location system, and computer readable medium, that, when in the autonomous mode of operation

and for current sensed information by the plurality of sensors, selects between one of the learned and identified autonomous driving information to be executed based on the current sensed information.

Embodiments include a method that includes the steps:

collecting, by a plurality of sensors of a vehicle, sensed information associated with the vehicle interior and an exterior of the vehicle;

storing, by the microprocessor in a computer readable medium, learned autonomous driving information describing a behavioral response of the vehicle to prior sensed information when the vehicle is in an autonomous mode of operation and identified autonomous driving information describing a behavioral response of other vehicles to sensed information collected by other vehicles when in an autonomous mode of operation; and

for current sensed information collected by the plurality of sensors, selecting, by the microprocessor and when in the autonomous mode of operation, one of the learned and identified autonomous driving information to be executed by the microprocessor based on the current sensed information.

Embodiments include a method that includes the steps:

monitoring, by a microprocessor, behaviors of plural vehicles, operating in an autonomous mode of operation, in response to sensed information collected by sensors of a respective one of the plural vehicles;

identifying, by the microprocessor, a behavior of one or more of the plural vehicles in response to the respective sensed information; and

providing, by the microprocessor, the identified behavior to vehicle different from the plural vehicles and operating in the autonomous mode of operation, for execution by a microprocessor of the different vehicle.

Aspects of the above vehicle or method can include one or more of: the learned and identified autonomous driving information produces different behaviors of the vehicle when in the autonomous mode based on the current sensed information, the behaviors correspond to one or more of an acceleration event, an acceleration rate, a deceleration event, a deceleration rate, a steering angle relative to a reference axis, and a spacing distance between an exterior surface of the vehicle and a nearby object, and the sensed information further comprises one or more of sensed object information associated with objects in spatial proximity to the vehicle, sensed occupant information for the vehicle, sensed vehicle-related information, and exterior environmental information regarding an environment of the vehicle.

Aspects of the above vehicle or method can include one or more of: the identified autonomous driving information has a corresponding application limitation defining when the identified autonomous driving information is to be used instead of the learned autonomous driving information, and wherein the corresponding application limitation is one or more of a temporal limitation, a spatial limitation, and an event duration limitation.

Aspects of the above vehicle or method can include one or more of: the current sensed information comprises navigation information, wherein the navigation information comprises a dimensional array of features, each feature having an attribute of location and category, and wherein the navigation information comprises or references the identified autonomous driving information.

Aspects of the above vehicle or method can include the identified autonomous driving information comprises one or more of a command to the microprocessor, request to the microprocessor, warning of a hazard, instruction to be performed by the microprocessor, rule to be applied by the

microprocessor, and link to one or more of the command, request, warning, instruction or rule.

Aspects of the above vehicle or method can include the microprocessor or a remotely located profile database manager using the sensed information to update one or more fields of the one or more occupant profiles.

Aspects of the above vehicle or method can include one or more of: the vehicle comprising multiple occupants, each occupant having a corresponding occupant profile, the microprocessor combining parts of the occupant profiles to form a composite profile describing behavior for the multiple occupants, the microprocessor's selection of the one or more of an acceleration event, an acceleration rate, a deceleration event, a deceleration rate, a steering angle relative to a reference axis, and a spacing distance between an exterior surface of the vehicle and a nearby object being based, at least in part, on the composite profile, each of the occupant profiles being created by predictive analytics and/or behavioral segmentation, and the autonomous mode of operation being at least level 2 or higher.

Aspects of the above vehicle or method can include the navigation information comprises a flag field to indicate whether or not the navigation information comprises identified autonomous driving information.

Aspects of the above vehicle or method can include the microprocessor forward the identified autonomous driving information to at least one other autonomous vehicle in spatial proximity to the autonomous vehicle for possible execution by a microprocessor of the at least one other autonomous vehicle and the autonomous mode of operation is at least level 2 or higher.

Any one or more of the aspects/embodiments as substantially disclosed herein.

Any one or more of the aspects/embodiments as substantially disclosed herein optionally in combination with any one or more other aspects/embodiments as substantially disclosed herein.

One or means adapted to perform any one or more of the above aspects/embodiments as substantially disclosed herein.

The phrases "at least one," "one or more," "or," and "and/or" are open-ended expressions that are both conjunctive and disjunctive in operation. For example, each of the expressions "at least one of A, B and C," "at least one of A, B, or C," "one or more of A, B, and C," "one or more of A, B, or C," "A, B, and/or C," and "A, B, or C" means A alone, B alone, C alone, A and B together, A and C together, B and C together, or A, B and C together.

The term "a" or "an" entity refers to one or more of that entity. As such, the terms "a" (or "an"), "one or more," and "at least one" can be used interchangeably herein. It is also to be noted that the terms "comprising," "including," and "having" can be used interchangeably.

The term "automatic" and variations thereof, as used herein, refers to any process or operation, which is typically continuous or semi-continuous, done without material human input when the process or operation is performed. However, a process or operation can be automatic, even though performance of the process or operation uses material or immaterial human input, if the input is received before performance of the process or operation. Human input is deemed to be material if such input influences how the process or operation will be performed. Human input that consents to the performance of the process or operation is not deemed to be "material."

Aspects of the present disclosure may take the form of an embodiment that is entirely hardware, an embodiment that is

entirely software (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as a “circuit,” “module,” or “system.” Any combination of one or more computer-readable medium(s) may be utilized. 5 The computer-readable medium may be a computer-readable signal medium or a computer-readable storage medium.

A computer-readable storage medium may be, for example, but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, or device, or any suitable combination of the foregoing. More specific examples (a non-exhaustive list) of the computer-readable storage medium would include the following: an electrical connection having one or more wires, a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, a portable compact disc read-only memory (CD-ROM), an optical storage device, a magnetic storage device, or any suitable combination of the foregoing. 20 In the context of this document, a computer-readable storage medium may be any tangible medium that can contain or store a program for use by or in connection with an instruction execution system, apparatus, or device.

A computer-readable signal medium may include a propagated data signal with computer-readable program code embodied therein, for example, in baseband or as part of a carrier wave. Such a propagated signal may take any of a variety of forms, including, but not limited to, electromagnetic, optical, or any suitable combination thereof. A computer-readable signal medium may be any computer-readable medium that is not a computer-readable storage medium and that can communicate, propagate, or transport a program for use by or in connection with an instruction execution system, apparatus, or device. Program code 35 embodied on a computer-readable medium may be transmitted using any appropriate medium, including, but not limited to, wireless, wireline, optical fiber cable, RF, etc., or any suitable combination of the foregoing.

The terms “determine,” “calculate,” “compute,” and variations thereof, as used herein, are used interchangeably and include any type of methodology, process, mathematical operation or technique. 40

The term “electric vehicle” (EV), also referred to herein as an electric drive vehicle, may use one or more electric motors or traction motors for propulsion. An electric vehicle may be powered through a collector system by electricity from off-vehicle sources, or may be self-contained with a battery or generator to convert fuel to electricity. An electric vehicle generally includes a rechargeable electricity storage system (RESS) (also called Full Electric Vehicles (FEV)). Power storage methods may include: chemical energy stored on the vehicle in on-board batteries (e.g., battery electric vehicle or BEV), on board kinetic energy storage (e.g., flywheels), and/or static energy (e.g., by on-board double-layer capacitors). Batteries, electric double-layer capacitors, and flywheel energy storage may be forms of rechargeable on-board electrical storage. 50

The term “hybrid electric vehicle” refers to a vehicle that may combine a conventional (usually fossil fuel-powered) powertrain with some form of electric propulsion. Most hybrid electric vehicles combine a conventional internal combustion engine (ICE) propulsion system with an electric propulsion system (hybrid vehicle drivetrain). In parallel hybrids, the ICE and the electric motor are both connected to the mechanical transmission and can simultaneously transmit power to drive the wheels, usually through a 60

conventional transmission. In series hybrids, only the electric motor drives the drivetrain, and a smaller ICE works as a generator to power the electric motor or to recharge the batteries. Power-split hybrids combine series and parallel characteristics. A full hybrid, sometimes also called a strong hybrid, is a vehicle that can run on just the engine, just the batteries, or a combination of both. A mid hybrid is a vehicle that cannot be driven solely on its electric motor, because the electric motor does not have enough power to propel the vehicle on its own. 10

The term “rechargeable electric vehicle” or “REV” refers to a vehicle with on board rechargeable energy storage, including electric vehicles and hybrid electric vehicles.

What is claimed is:

1. An autonomous vehicle, comprising:

a vehicle interior for receiving one or more occupants; a plurality of sensors to collect vehicle-related information, occupant-related information, and exterior environmental and object information associated with the vehicle; 20

an automatic vehicle location system to determine a current spatial location of the vehicle;

a computer readable medium to store selected information;

an arithmetic logic unit that performs mathematical operations;

a data bus that, at the request of the arithmetic logic unit, sends data to or receives data from the computer readable medium;

an address bus that, at the request of the arithmetic logic unit, sends an address to the computer readable medium;

a read and write line that, at the request of the arithmetic logic unit, commands the computer readable medium whether to set or retrieve a location corresponding to the address; 30

one or more registers to latch a value on the data bus or output by the arithmetic logic unit; and

one or more buffers, wherein the arithmetic logic unit is coupled to the plurality of sensors, automatic vehicle location system, and computer readable medium, and: determines a current spatial location of the vehicle, receives current vehicle-related information, current occupant-related information, and exterior environmental and object information, 45

generates, from the exterior environmental and object information, a three-dimensional map comprising exterior animate objects in spatial proximity to the vehicle, the exterior animate objects comprising a selected exterior animate object,

models from the three-dimensional map a first predicted behavior of the selected exterior animate object,

receives a different second predicted behavior of the selected exterior animate object generated by another vehicle, and 55

based on the three-dimensional map and the first and second predicted behaviors of the selected exterior animate object, issues a command to a vehicle component to perform a vehicle driving operation,

wherein the first and second predicted behaviors, each executed alone by the arithmetic logic unit, cause the arithmetic logic unit to produce different commands.

2. The vehicle of claim 1, wherein the different commands are different than the issued command, wherein the behaviors correspond to one or more of an acceleration event, an acceleration rate, a deceleration event, a deceleration rate, a 65

steering angle relative to a reference axis, and a spacing distance between an exterior surface of the vehicle and a nearby exterior object in the three-dimensional map.

3. The vehicle of claim 1, wherein the second predicted behavior has a corresponding application limitation defining when the second predicted behavior is to be used instead of the first predicted behavior, and wherein the corresponding application limitation is one or more of a temporal limitation, a spatial limitation, and an event duration limitation.

4. The vehicle of claim 1, wherein the second predicted behavior is received as part of navigation information comprising a dimensional array of features, each feature having an attribute of location and category and wherein the navigation information comprises or references the second predicted behavior, wherein the navigation information further comprises one or more of a command to the vehicle arithmetic logic unit, request to the vehicle arithmetic logic unit, warning of a hazard, instruction to be performed by the vehicle arithmetic logic unit, rule to be applied by the vehicle arithmetic logic unit, and link to one or more of the command, request, warning, instruction or rule, wherein the navigation information comprises a flag field to indicate whether or not the navigation information comprises a predicted behavior to be considered by the vehicle, and wherein the microprocessor forward the identified autonomous driving information to at least one other autonomous vehicle in spatial proximity to the autonomous vehicle for possible execution by a microprocessor of the at least one other autonomous vehicle, and wherein an autonomous mode of operation of the vehicle is at least level 2 or higher.

5. The vehicle of claim 1, wherein the vehicle forms an ad hoc network with a different vehicle, wherein the vehicle communicates to the different vehicle not to transmit to a remote control source or navigation source exterior environmental and object information collected by a respective plurality of sensors of the different vehicle in temporal proximity to the vehicle collection of the exterior environmental and object information, and wherein the vehicle transmits, to a remote control source or navigation source, the current vehicle-related information and current occupant-related information, three-dimensional map, current spatial location of the vehicle, and predicted behavior of one or more of the exterior animate objects and/or one or more of the vehicle occupants.

6. The vehicle of claim 5, wherein the different vehicle transmits current vehicle-related information and current occupant-related information collected by the respective plurality of sensors of the different vehicle to the remote control source or navigation source but does not transmit to the remote control source or navigation source exterior environmental and object information collected by a respective plurality of sensors of the different vehicle.

7. The vehicle of claim 5, wherein the microprocessor transmits the predicted behaviors of the one or more exterior animate objects to the different vehicle for execution by a microprocessor of the different vehicle.

8. The vehicle of claim 5, wherein the microprocessor transmits the predicted behaviors of the one or more occupants of the vehicle to the different vehicle for execution by a microprocessor of the different vehicle.

9. The vehicle of claim 1, wherein the plurality of sensors comprise a lidar sensor, radar sensor, ultrasonic sensor, camera, and infrared sensor, wherein the command is one or more of an acceleration rate of the vehicle, a deceleration rate of the vehicle, a steering angle of the vehicle, and an inter-object spacing of the vehicle relative to an exteriorly located object, and wherein the vehicle transmits to the

control source or navigation source an identifier associated with the vehicle and different vehicle in connection with the exterior environmental and object information.

10. The vehicle of claim 1, wherein what vehicles are in the ad hoc network is based on one or more of spatial location or proximity of potentially networked vehicles, received signal strength by one potentially networked vehicle of a signal transmitted by another potentially networked vehicle, directions of travel of potentially networked vehicles, roadway type traveled by potentially networked vehicles, types of potentially networked vehicles, models of potentially networked vehicles, and manufacturers of potentially networked vehicles and wherein which vehicles are members of the ad hoc network change in response to vehicle movement.

11. A method for autonomous operation of a vehicle, comprising:

providing a vehicle comprising a vehicle interior for receiving one or more occupants, a plurality of sensors to collect vehicle-related information, occupant-related information, and exterior environmental and object information associated with the vehicle, an automatic vehicle location system to determine a current spatial location of the vehicle, a computer readable medium to store selected information, an arithmetic logic unit that performs mathematical operations, a data bus that, at the request of the arithmetic logic unit, sends data to or receives data from the computer readable medium, an address bus that, at the request of the arithmetic logic unit, sends an address to the computer readable medium, a read and write line that, at the request of the arithmetic logic unit, commands the computer readable medium whether to set or retrieve a location corresponding to the address, one or more registers to latch a value on the data bus or output by the arithmetic logic unit, and one or more buffers;

determining, by the arithmetic logic unit, a current spatial location of the vehicle;

receiving, by the arithmetic logic unit, current vehicle-related information, current occupant-related information, and exterior environmental and object information;

generating, by the arithmetic logic unit and from the exterior environmental and object information, a three-dimensional map comprising exterior animate objects in spatial proximity to the vehicle, the exterior animate objects comprising a selected exterior animate object; modeling, by the arithmetic logic unit and from the three-dimensional map, a first predicted behavior of the selected exterior animate object;

receiving, by the arithmetic logic unit, a different second predicted behavior of the selected exterior animate object generated by another vehicle; and

based on the three-dimensional map and the first and second predicted behaviors of the selected exterior animate object, issuing, by the arithmetic logic unit, a command to a vehicle component to perform a vehicle driving operation,

wherein the first and second predicted behaviors, each executed alone by the arithmetic logic unit, cause the arithmetic logic unit to produce different commands.

12. The method of claim 11, wherein different commands are different than the issued command, wherein the behaviors correspond to one or more of an acceleration event, an acceleration rate, a deceleration event, a deceleration rate, a steering angle relative to a reference axis, and a spacing

distance between an exterior surface of the vehicle and a nearby exterior object in the three-dimensional map.

**13.** The method of claim **11**, wherein the second predicted behavior has a corresponding application limitation defining when the second predicted behavior is to be used instead of the first predicted behavior, and wherein the corresponding application limitation is one or more of a temporal limitation, a spatial limitation, and an event duration limitation.

**14.** The method of claim **11**, wherein the second predicted behavior is received as part of navigation information comprising a dimensional array of features, each feature having an attribute of location and category and wherein the navigation information comprises or references the second predicted behavior, wherein the navigation information further comprises one or more of a command to the vehicle arithmetic logic unit, request to the vehicle arithmetic logic unit, warning of a hazard, instruction to be performed by the vehicle arithmetic logic unit, rule to be applied by the vehicle arithmetic logic unit, and link to one or more of the command, request, warning, instruction or rule, wherein the navigation information comprises a flag field to indicate whether or not the navigation information comprises a predicted behavior to be considered by the vehicle, and wherein the microprocessor forward the identified autonomous driving information to at least one other autonomous vehicle in spatial proximity to the autonomous vehicle for possible execution by a microprocessor of the at least one other autonomous vehicle, and wherein an autonomous mode of operation of the vehicle is at least level 2 or higher.

**15.** The method of claim **11**, wherein the vehicle forms an ad hoc network with a different vehicle, wherein the vehicle communicates to the different vehicle not to transmit to a remote control source or navigation source exterior environmental and object information collected by a respective plurality of sensors of the different vehicle in temporal proximity to the vehicle collection of the exterior environmental and object information, and wherein the vehicle transmits, to a remote control source or navigation source, the current vehicle-related information and current occupant-related information, three-dimensional map, current spatial location of the vehicle, and predicted behavior of one or more of the exterior animate objects and/or one or more of the vehicle occupants.

**16.** The method of claim **15**, wherein the different vehicle transmits current vehicle-related information and current occupant-related information collected by the respective plurality of sensors of the different vehicle to the remote control source or navigation source but does not transmit to the remote control source or navigation source exterior environmental and object information collected by a respective plurality of sensors of the different vehicle.

**17.** The method of claim **15**, wherein the microprocessor transmits the predicted behaviors of the one or more exterior animate objects to the different vehicle for execution by a microprocessor of the different vehicle and wherein the microprocessor transmits the predicted behaviors of the one or more occupants of the vehicle to the different vehicle for execution by a microprocessor of the different vehicle.

**18.** The method of claim **15**, wherein the plurality of sensors comprise a lidar sensor, radar sensor, ultrasonic sensor, camera, and infrared sensor, wherein the command is one or more of an acceleration rate of the vehicle, a deceleration rate of the vehicle, a steering angle of the vehicle, and an inter-object spacing of the vehicle relative to an exteriorly located object, and wherein the vehicle transmits to the control source or navigation source an identifier associated with the vehicle and different vehicle in connec-

tion with the exterior environmental and object information, wherein what vehicles are in the ad hoc network is based on one or more of spatial location or proximity of potentially networked vehicles, received signal strength by one potentially networked vehicle of a signal transmitted by another potentially networked vehicle, directions of travel of potentially networked vehicles, roadway type traveled by potentially networked vehicles, types of potentially networked vehicles, models of potentially networked vehicles, and manufacturers of potentially networked vehicles and wherein which vehicles are members of the ad hoc network change in response to vehicle movement.

**19.** A method for autonomous operation of a vehicle, comprising:

providing a vehicle comprising a vehicle interior for receiving one or more occupants, a plurality of sensors to collect vehicle-related information, occupant-related information, and exterior environmental and object information associated with the vehicle, an automatic vehicle location system to determine a current spatial location of the vehicle, a computer readable medium to store selected information, an arithmetic logic unit that performs mathematical operations, a data bus that, at the request of the arithmetic logic unit, sends data to or receives data from the computer readable medium, an address bus that, at the request of the arithmetic logic unit, sends an address to the computer readable medium, a read and write line that, at the request of the arithmetic logic unit, commands the computer readable medium whether to set or retrieve a location corresponding to the address, one or more registers to latch a value on the data bus or output by the arithmetic logic unit, and one or more buffers;

determining, by the arithmetic logic unit, a current spatial location of the vehicle;

receiving, by the arithmetic logic unit, current vehicle-related information, current occupant-related information, and exterior environmental and object information;

generating, by the arithmetic logic unit and from the exterior environmental and object information, a three-dimensional map comprising exterior animate objects in spatial proximity to the vehicle, the exterior animate objects comprising the selected exterior animate object;

modeling, by the arithmetic logic unit and from the three-dimensional map, a first predicted behavior of a selected exterior animate object;

receiving, by the arithmetic logic unit, a different second predicted behavior of the selected exterior animate object generated by another vehicle; and based on the three-dimensional map and the first and second predicted behaviors of the selected exterior animate object, issuing, by the arithmetic logic unit, a command to a vehicle component to perform a vehicle driving operation,

wherein the first and second predicted behaviors, each executed alone by the arithmetic logic unit, produce different commands, wherein the behaviors correspond to one or more of an acceleration event, an acceleration rate, a deceleration event, a deceleration rate, a steering angle relative to a reference axis, and a spacing distance between an exterior surface of the vehicle and a nearby exterior object in the three-dimensional map.

**20.** The method of claim **19**, wherein the second predicted behavior has a corresponding application limitation defining when the second predicted behavior is to be used instead of the first predicted behavior, and wherein the corresponding

41

application limitation is one or more of a temporal limitation, a spatial limitation, and an event duration limitation, wherein the second predicted behavior is received as part of navigation information comprising a dimensional array of features, each feature having an attribute of location and category and wherein the navigation information comprises or references the second predicted behavior, wherein the navigation information further comprises one or more of a command to the vehicle arithmetic logic unit, request to the vehicle arithmetic logic unit, warning of a hazard, instruction to be performed by the vehicle arithmetic logic unit, rule to be applied by the vehicle arithmetic logic unit, and link to one or more of the command, request, warning, instruction or rule, wherein the navigation information comprises a flag field to indicate whether or not the navigation information comprises a predicted behavior to be considered by the vehicle, and wherein the microprocessor forward the identified autonomous driving information to at least one other

42

autonomous vehicle in spatial proximity to the autonomous vehicle for possible execution by a microprocessor of the at least one other autonomous vehicle, wherein an autonomous mode of operation of the vehicle is at least level 2 or higher, wherein the vehicle forms an ad hoc network with a different vehicle, wherein the vehicle communicates to the different vehicle not to transmit to a remote control source or navigation source exterior environmental and object information collected by a respective plurality of sensors of the different vehicle in temporal proximity to the vehicle collection of the exterior environmental and object information, and wherein the vehicle transmits, to a remote control source or navigation source, the current vehicle-related information and current occupant-related information, three-dimensional map, current spatial location of the vehicle, and predicted behavior of one or more of the exterior animate objects and/or one or more of the vehicle occupants.

\* \* \* \* \*