



US010036196B2

(12) **United States Patent**
Chen et al.

(10) **Patent No.:** **US 10,036,196 B2**
(45) **Date of Patent:** **Jul. 31, 2018**

(54) **AUTOMATIC CLOSING STRUCTURE FOR SLATS OF SASH**

USPC 49/82.1, 183, 73.1, 506, 81.1, 80.1, 74.1,
49/386, 379, 381, 86.1, 89.1, 163, 161;
52/473

(71) Applicant: **NIEN MADE ENTERPRISE CO., LTD.**, Taichung (TW)

See application file for complete search history.

(72) Inventors: **Lin Chen**, Taichung (TW); **Keng-Hao Nien**, Taichung (TW)

(56) **References Cited**

(73) Assignee: **NIEN MADE ENTERPRISE CO., LTD.**, Taichung (TW)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 370 days.

6,701,669	B1 *	3/2004	Yorgason	E06B 7/096
					49/82.1
7,434,353	B2 *	10/2008	Nien	E06B 7/086
					49/403
9,038,314	B2 *	5/2015	Chen	E06B 7/096
					49/82.1
2005/0252086	A1 *	11/2005	Yorgason	E06B 7/096
					49/82.1
2005/0257429	A1 *	11/2005	Yorgason	E06B 7/096
					49/82.1
2008/0178526	A1 *	7/2008	Browne	F24F 13/1426
					49/82.1
2008/0250717	A1 *	10/2008	Vasquez	E06B 7/096
					49/74.1
2009/0149123	A1 *	6/2009	Blagg	F24F 13/1426
					454/258
2013/0118082	A1 *	5/2013	Colson	E06B 7/096
					49/82.1

(21) Appl. No.: **14/963,006**

(22) Filed: **Dec. 8, 2015**

(65) **Prior Publication Data**

US 2017/0081907 A1 Mar. 23, 2017

(30) **Foreign Application Priority Data**

Sep. 17, 2015 (CN) 2015 2 0721707 U

(51) **Int. Cl.**
E06B 7/096 (2006.01)
E05F 11/04 (2006.01)
E06B 3/48 (2006.01)

(52) **U.S. Cl.**
CPC **E06B 7/096** (2013.01); **E05F 11/04** (2013.01); **E06B 3/481** (2013.01)

(58) **Field of Classification Search**
CPC E06B 7/096; E06B 3/481; E06B 7/084; E06B 7/086; E06B 9/386; E06B 3/48; E06B 3/9647; E06B 9/266; E06B 9/388; E06B 2009/322; E06B 2009/3225; E06B 9/68; E06B 7/09; E05F 11/04; Y10S 160/902

(Continued)


Primary Examiner — Chi Q Nguyen

(74) *Attorney, Agent, or Firm* — Tracy Heims; Apex Juris, pllc.

(57) **ABSTRACT**

An automatic closing structure is disclosed, which is installed between a sash and a corresponding object, wherein the sash is pivotable relative to the corresponding object; the sash includes a frame and a plurality of turnable slats which are arranged in parallel in the frame; the automatic closing structure has a cord which is adapted to automatically close the slats, wherein the cord can be easily assembled into the automatic closing structure, and a tightness thereof can be adjusted.

28 Claims, 14 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0033610 A1* 2/2014 Watkins E06B 7/086
49/82.1
2014/0166219 A1* 6/2014 Chen E06B 9/266
160/368.1

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG.11




FIG.12




FIG.13




FIG.14

AUTOMATIC CLOSING STRUCTURE FOR SLATS OF SASH

The current application claims a foreign priority to application number 201520721707.1 filed on Sep. 17, 2015 in China.

BACKGROUND OF THE INVENTION

1. Technical Field

The present invention relates generally to a sash, and more particularly to an automatic closing structure for slats of the sash.

2. Description of Related Art

Typically, a sash is composed of a frame and a plurality of slats, which are horizontally arranged in the space surrounded by the frame, wherein the slats are pivotally connected to the frame, and are therefore turnable. By adjusting the angle of the slats between a horizontal direction and a vertical direction, the amount of light from outside and the degree of ventilation can be appropriately regulated.

In other to increase the amount of light from outside and the degree of ventilation, some sashes are designed to have the frame pivotally connected to a window frame of a building. In this way, the opening of the building where such a movable sash is installed can be fully opened by opening the sash completely, which facilitates light and air to enter the room. However, the edges of slats of this kind of movable sash tend to be damaged if the slats are adjusted to the horizontal direction while the sash is being opened toward a wall of the building, or while two sashes are being moved toward each other. Therefore, the conventional movable sashes still have room for improvement.

BRIEF SUMMARY OF THE INVENTION

In view of the above, the primary objective of the present invention is to provide an automatic closing structure, which is able to automatically close slats of a sash. Moreover, the cord included in the structure is easy to be installed, and the tightness of the cord is adjustable.

The present invention provides an automatic closing structure, which is installed between a sash and a corresponding object, wherein the sash is pivotable relative to the corresponding object, and the sash comprises a frame and a plurality of turnable slats which are arranged in parallel in the frame. The automatic closing structure includes a follower assembly, a linkage device, and a plurality of rotary members, wherein each of the rotary members is respectively provided at an end of each of the slats; the follower assembly is movably provided in the frame, and comprises a first linkage member to be engaged with the rotary members; the linkage device is adapted to move the follower assembly, which moves the rotary members relative to the first linkage member. The follower assembly comprises a second linkage member, which is controllable to move the first linkage member in a linear direction. The linkage device comprises a cord, which has a first stop portion, a second stop portion, and a cord portion located between the first stop portion and the second stop portion, wherein the first stop portion is connected to the second linkage member, and the second stop portion is connected to the corresponding object.

The present invention further provides an automatic closing structure, which is installed between a sash and a corresponding object, wherein the sash is pivotable relative to the corresponding object, and the sash comprises a frame and a plurality of turnable slats which are arranged in parallel in the frame. The automatic closing structure includes a follower assembly, a linkage device, and a plurality of rotary members, wherein each of the rotary members is respectively provided at an end of each of the slats; the follower assembly is movably provided in the frame, and comprises a first linkage member to be engaged with the rotary members; the linkage device is adapted to move the follower assembly, which moves the rotary members relative to the first linkage member. The automatic closing structure comprises a rack fixedly provided in the frame. The follower assembly comprises a gear, a movable block, and a second linkage member, wherein the gear is rotatably provided in the movable block, and meshes with the rack; the second linkage member has a flat teeth meshing with the gear at a side opposite to the rack; the second linkage member is controllable to move the movable block, and to consequently move the first linkage member in a linear direction.

The present invention further provides an automatic closing structure, which is installed between a sash and a corresponding object, wherein the sash is pivotable relative to the corresponding object, and the sash comprises a frame and a plurality of turnable slats which are arranged in parallel in the frame. The automatic closing structure includes a follower assembly, a linkage device, and a plurality of rotary members, wherein each of the rotary members is respectively provided at an end of each of the slats; the follower assembly is movably provided in the frame, and comprises a first linkage member to be engaged with the rotary members; the linkage device is adapted to move the follower assembly, which moves the rotary members relative to the first linkage member. The automatic closing structure comprises a locating seat and an adjusting member, wherein the locating seat is fixed on the corresponding object, and has a bore; the adjusting member has a mobile block movably provided on the locating seat. The linkage device comprises a cord passing through the bore of the locating seat; the cord has a first stop portion, a second stop portion, and a cord portion located between the first stop portion and the second stop portion, wherein the first stop portion is connected to the follower assembly, and the second stop portion is connected to the mobile block.

Whereby, the cord can be easily and conveniently installed or even replaced, and the movable block which is connected to the gear is moved over a shorter distance than the second linkage member being moved upward by the cord, which prevents the slats from being excessively closed, and makes the tightness of the cord adjustable.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

The present invention will be best understood by referring to the following detailed description of some illustrative embodiments in conjunction with the accompanying drawings, in which

FIG. 1 is a perspective view, showing a building opening covering structure includes two sashes;

FIG. 2 is a perspective view, showing the sashes of the building opening covering structure are moved to be arranged in parallel with each other;

3

FIG. 3 is a perspective view, showing the relation between an automatic closing structure of a preferred embodiment of the present invention and the aforementioned sashes;

FIG. 4 is a perspective view, showing the automatic closing structure of the preferred embodiment of the present invention;

FIG. 5 is an exploded view, showing some components of the automatic closing structure of the preferred embodiment of the present invention;

FIG. 6 is a perspective view, showing the locating seat and the adjusting member of the automatic closing structure of the preferred embodiment of the present invention;

FIG. 7 is a perspective view, showing base and the follower block of the automatic closing structure of the preferred embodiment of the present invention;

FIG. 8 is a sectional view, showing inner structure of the base of the automatic closing structure of the preferred embodiment of the present invention;

FIG. 9 is a schematic view, showing the follower assembly of the automatic closing structure of the preferred embodiment of the present invention is located at the bottom of the base;

FIG. 10 is a schematic view, showing the follower assembly of the automatic closing structure of the preferred embodiment of the present invention is moved upward;

FIG. 11 is a schematic view, showing the follower assembly of the automatic closing structure of the preferred embodiment of the present invention is moved upward and approaching the top of the base;

FIG. 12 is a schematic view, showing the mobile block and screw rod of the adjusting member of the automatic closing structure of the preferred embodiment of the present invention;

FIG. 13 is a perspective view, showing some components of an automatic closing structure of an alternative preferred embodiment of the present invention; and

FIG. 14 is a schematic view, showing the follower assembly of the automatic closing structure of the aforementioned alternative preferred embodiment of the present invention is moved upward.

DETAILED DESCRIPTION OF THE INVENTION

As shown in FIG. 1 and FIG. 2, a building opening covering structure includes a first sash 100 and a second sash 200 installed in a window frame 300, wherein the first sash 100 is pivotally connected to the window frame 300 with a side thereof, and another side of the first sash 100 is pivotally connected to the second sash 200, whereby the first sash 100 and the second sash 200 can block the opening of the building when expanded, and open the opening of the building when folded together (i.e., arranged in parallel with each other). The aforementioned first sash 100 and second sash 200 have the same structure, each of which includes a frame 101 (201) and a plurality of slats 102 (202), wherein the slats 102 (202) are horizontally arranged in the frame 101 (201), and are turnable to change the degree of coverage.

In a preferred embodiment, the present invention includes two automatic closing structures, which are installed between the aforementioned first sash 100 and second sash 200, wherein one of the two automatic closing structures is used to automatically close the slats 102 of the first sash 100, while the other automatic closing structure is used to automatically close the slats 202 of the second sash 200. For purpose of illustration, herein we take the automatic closing

4

structure applied for the first sash 100 as an example. In this case, the second sash 200 is deemed to be a corresponding object of the first sash 100.

As shown in FIG. 3 to FIG. 8, the automatic closing structure of the preferred embodiment includes a base 10, a lateral lid 12, a locating seat 14, an adjusting member, a plurality of rotary members 22, a follower assembly, and a linkage device.

The base 10 is embedded and fixed into the frame 101 of the first sash 100 through a lateral surface thereof. A side of the base 10 has a longitudinal guide rail 10a, and another side thereof has a trough 10b recessed from a side surface thereof. The guide rail 10a communicates with the trough 10b, wherein a bottom of the trough 10b is provided with a longitudinal rack 10c, which is fixed and unmovable, and each of two lateral walls of the trough 10b respectively has a longitudinal and recessed guideway 10d. The lateral lid 12 is fixedly connected to the base 10 to enclose the trough 10b, wherein the lateral lid 12 has a bore 12a; a direction changing wheel 12b and a direction changing block 13 are provided inside the lateral lid 12; a direction changing wheel 13a is further provided inside the direction changing block 13.

The locating seat 14 is embedded and fixed into the frame 201 of the second sash 200 through a lateral surface thereof. The locating seat 14 has a perforation (not shown) and a bore 14a, and further has a lead rail 14b on a rear surface thereof extending outwardly. The adjusting member includes a mobile block 16, a screw rod 18, and a C-shaped buckle 20, wherein the mobile block 16 is movably disposed in the lead rail 14b of the locating seat 14. The mobile block 16 has a threaded hole 16a and a positioning aperture 16b. The screw rod 18 is screwed into the threaded hole 16a of the mobile block 16 after passing through the perforation of the locating seat 14. The screw rod 18 has an annular limiting groove 18a on a body portion thereof, wherein the limiting groove 18a is buckled by the C-shaped buckle 20 so that the screw rod 18 can only rotate in situ. In other words, by using a tool (e.g., a screw driver) to rotate the screw rod 18 clockwise or counterclockwise, the mobile block 16 can be moved forwardly or backwardly in the lead rail 14b of the locating seat 14 along the screw rod 18.

The rotary members 22 are gears which are respectively provided at a side corresponding to the slats 102. The follower assembly is movably disposed in the frame 101, and includes a first linkage member 24, a follower block 26, a gear 28, a movable block 30, a second linkage member 32, and a biasing member 34. Except for the first linkage member 24, which is disposed outside of the base 10, and the follower block 26, which is movably engaged within the guide rail 10a of the base 10, the other components, i.e., the gear 28, the movable block 30, the second linkage member 32, and the biasing member 34 are all received in the trough 10b of the base 10.

As shown in FIG. 3, the first linkage member 24 is a rack, and there is another fixed and unmovable rack 36 provided directly in front of teeth of the first linkage member 24, wherein the first linkage member 24 and the rack 36 are parallel to each other, and the rotary members 22 mesh with the teeth of the first linkage member 24 and the rack 36 at the same time. In other words, the rotary members 22 can be rotated simultaneously to consequently turn the slats 102 by simply moving the first linkage member 24 upward or downward.

The follower block 26 of the follower assembly has a short rack 26a on a left side surface thereof, wherein the short rack 26a extends out of the base 10, and is located

between the first linkage member **24** and the rack **36**. The short rack **26a** meshes with the teeth of the first linkage member **24**. The follower block **26** has a first protrusion **26b** on a right side thereof, wherein the first protrusion **26b** extends into the trough **10b**. The gear **28** is provided in the movable block **30**, and is rotatable therein, wherein the gear **28** meshes with the rack **10c** inside the base **10**. The movable block **30** has a second protrusion **30a** abutting against a bottom surface of the first protrusion **26b**. As for the second linkage member **32**, it mainly meshes with the gear **28** through flat teeth **32d** thereof, and is located at another side opposite to the rack **10c** of the base **10**. The second linkage member **32** has two guide block **32a**, each of which is respectively projected from one of two lateral walls thereof, wherein each of the guide blocks **32a** is located in one of the guideways **10d** of the base **10**. The second linkage member **32** further has a longitudinal slit **32b**, and has an extended portion **32c** at a bottom thereof. The biasing member **34** is a spring which fits around a post **30b** on a top of the movable block **30**, wherein the biasing member **34** abuts against an inner wall of a top of the base **10** with an end thereof, and abuts against the top of the movable block **30** with another end thereof. Whereby, the biasing force is exerted on the movable block **30**, which not only keeps pushing the movable block **30** downwardly, but also helps to eliminate gaps formed between the rack **10c**, the gear **28**, and the second linkage member **32**. As a result, the rack **10c**, the gear **28**, and the second linkage member **32** can maintain a good contact relation between each other.

With the aforementioned design, when the movable block **30** is moved upward, the follower block **26** will be pushed upward as well. At this time, the follower block **26** further brings the first linkage member **24** together to rotate the rotary members **22**. The method of moving the movable block **30** upward is to move the second linkage member **32** upward along the guideway **10d** of the base **10**, and by doing so, the second linkage member **32** drives the gear **28** to rotate upward along the fixed rack **10c**. In other words, to turn the slats **102**, the second linkage member **32** has to eventually move the first linkage member **24** along a linear direction with the gear **28**, the movable block **30**, and the follower block **26** as intermediate components.

The linkage device is used to move the follower assembly, so that the rotary members **22** are moved relative to the first linkage member **24**. In the preferred embodiment, the linkage device includes a cord **38**, wherein two ends of the cord **38** are respectively a first stop portion **38a** and a second stop portion **38b**, which are both knots, wherein the cord **38** has a cord portion **38c** between the first stop portion **38a** and the second stop portion **38b**. The cord portion **38c** passes through the bore **12a** of the lateral lid **12** and the bore **14a** of the locating seat **14**, and runs around the direction changing wheel **12b** and the direction changing wheel **13a**, wherein a part of the cord portion **38c** is further located in the positioning aperture **16b** of the mobile block **16** and the slit **32b** of the second linkage member **32**. The first stop portion **38a** abuts against a bottom surface of the second linkage member **32**, and also abuts against the extended portion **32c** through the guiding of the slit **32b**, which prevents the cord **38** from being disengaged from the second linkage member **32**. Therefore, the first stop portion **38a** is firmly connected to the follower assembly. As for the second stop portion **38b**, it abuts against a rear surface of the mobile block **16** to prevent from disengaging. In other words, the second stop portion **38b** is connected to the second sash **200** through the mobile block **16**.

Since a length of the cord portion **38c** is fixed, when the first sash **100** and the second sash **200** are arranged side by side to close the opening of the building, and when the slats **102** (**202**) are arranged horizontally, the follower assembly is located at a bottom of the base **10** as shown in FIG. **9**. During the process of opening the opening of the building, the second linkage member **32** is pulled by the cord **38** and therefore moved upward, as illustrated in FIG. **10**. It can be understood from the above description that, the second linkage member **32** moves the first linkage member **24** to rotate the rotary members **22** with the gear **28**, the movable block **30**, and the follower block **26** as intermediate components; meanwhile, the slats **102** automatically and gradually close the opening of the building till the follower assembly is moved to be located near a top of the base **10**, as illustrated in FIG. **11**, wherein the slats **102** completely close the opening at this time.

Because there are two automatic closing structures included in the preferred embodiment, and these two automatic closing structures are installed in opposite ways, the slats of the first sash **100** and the second sash **200** are automatically turned from a horizontal direction to a vertical direction while these sashes **100**, **200** are being opened. In this way, the slats of each sash **100**, **200** won't collide with each other, and therefore the first sash **100** and the second sash **200** can be smoothly folded and arranged in parallel. Even if the sash is moved to against a wall, the vertically arranged slats won't collide with the wall, and therefore won't be damaged or cause harm to others.

In the above description, the opening of the building is covered by two sashes. However, in practice, there can be only one sash applied to cover the opening of the building. In the case of having only one sash, of course only one automatic closing structure is needed. In other words, the locating seat **14** and the adjusting member are installed in the window frame, and the components including the base **10**, the lateral lid **12**, and the follower assembly are provided inside the frame of the sash.

In the above description, the slit **32b** of the second linkage member **32** has an open surface, and therefore while assembling the cord **38**, the cord portion **38c** can be easily disposed in the slit **32b**. Similarly, in order to quickly assembly the cord portion **38c**, the positioning aperture **16b** of the mobile block **16** can be alternatively designed to have an open lateral surface. With such design, the knots at two ends of the cord **38** can be used as means of preventing disengagement, which also improves the efficiency of assembling the components. In addition, if the cord **38** is required to be replaced, a user only needs to disassemble the lateral lid **12** and the locating seat **14**, then the cord **38** can be easily replaced, which is simple and convenient.

After the cord **38** is disposed in place, if it needs to be tightened or loosened, a user can rotate the screw rod **18** with a tool to move the mobile block **16** which is engaged with the cord **38** forward or backward, as shown in FIG. **12**, to tighten or to loosen the cord **38**. In the preferred embodiment, a top surface of the screw rod **18** has a single slot, which can be screwed with a flathead screwdriver.

It is worth mentioning that, because the rack **10c** is fixed and unmovable, the gear **28** meshes with the rack **10c**, and then the second linkage member **32** meshes with the gear **28** with the flat teeth **32d** thereof, when the gear **28** is rotated and moved, the second linkage member **32** is moved outward relative to the gear **28**. With this clever design, the operation is efficient, because the moving distance of the movable block **30** is shorter than the upward moving distance of the second linkage member **32** while it is pulled by

the cord **38**. In addition, by precisely designing the moving distances of the second linkage member **32** and the movable block **30**, the rotary members **22** are prevented from being extensively rotated, which ensures the slats don't push each other too much.

As it can be seen from the above description, the cord **38** of the automatic closing structure provided in the present invention can be easily and conveniently assembled and even replaced. Furthermore, the tightness of the cord **38** can be adjusted to meet different requirements. In addition to these two advantages, the cleverly designed arrangement between the rack **10c**, the gear **28**, and the second linkage member **32** helps to prevent the slats from being excessively closed, and therefore ensures the slats are not damaged by such cause.

In the aforementioned preferred embodiment, the slats can be turned through the gear (i.e., the rotary member **22**) provided at a side of each sash, wherein the gears can be rotated by moving the rack (i.e., the first linkage member **24**). However, in practice, there is an alternative way to turn the slats, and this alternative preferred embodiment is illustrated in FIG. **13** and FIG. **14**. The main difference is that, a first linkage member of the alternative preferred embodiment is a first long shaft **40** which has no teeth, and each of rotary members **44** is a block, which has a pivot **44a** provided at an end thereof corresponding to the first long shaft **40**, wherein the pivot **44a** is inserted into the first long shaft **40**. Each of the rotary members **44** is connected to a corresponding slat **102** through an external connector **46**. This alternative preferred embodiment has a special design: the rotary member **44** and the external connector **46** are disengagably connected to each other through a rectangular countersink and a rectangular post, whereby the external connector **46** can be moved by the rotary member **44** to rotate relative to the frame **101**. To better simultaneously rotate the rotary members, a second long shaft **42** can be further provided in practice as illustrated in FIG. **13** and FIG. **14**, which is parallel to the first long shaft **40**, and also has no teeth. Each of the rotary members **44** has two pivots **44a** at two ends thereof, which respectively corresponds to the first long shaft **40** and the second long shaft **42**, wherein the pivots **44a** are respectively inserted into the second long shaft **42** and the first long shaft **40**.

In addition, the follower block **48** has a rod **48a** on a side thereof, wherein the rod **48a** is inserted into a connecting hole **40a** of the first long shaft **40**. Whereby, when the follower block **48** is moved due to the indirect control of the cord, the first long shaft **40** is moved upward or downward, and therefore the rotary members **44** are rotated. As a result, the external connectors **46** are also rotated to turn the slats **102**. It must be pointed out that the embodiments described above are only some preferred embodiments of the present invention. All equivalent structures which employ the concepts disclosed in this specification and the appended claims should fall within the scope of the present invention.

What is claimed is:

1. An automatic closing structure, which is installed between a sash and a corresponding object, wherein the sash is pivotable relative to the corresponding object, and the sash comprises a frame and a plurality of turnable slats which are arranged in parallel in the frame; comprising a follower assembly, a linkage device, and a plurality of rotary members, wherein each of the rotary members is respectively provided at an end of each of the slats; the follower assembly is movably provided in the frame, and comprises a first linkage member to be engaged with the rotary members; the

linkage device is adapted to move the follower assembly, which moves the rotary members relative to the first linkage member; wherein:

the follower assembly comprises a second linkage member, which is controllable to move the first linkage member in a linear direction; and

the linkage device comprises a cord, which has a first stop portion, a second stop portion, and a cord portion located between the first stop portion and the second stop portion, wherein the first stop portion is connected to the second linkage member, and the second stop portion is connected to the corresponding object.

2. The automatic closing structure of claim **1**, wherein the second linkage member has a slit; a part of the cord portion which is near the first stop portion passes through the slit, so that the first stop portion is guided to abut against the second linkage member.

3. The automatic closing structure of claim **1**, further comprising a rack, which is fixedly provided in the frame, wherein the follower assembly comprises a gear and a movable block; the gear is rotatably provided in the movable block, and meshes with the rack; the second linkage member has a flat teeth meshing with the gear at a side opposite to the rack; the second linkage member is adapted to be pulled by the cord, which moves the movable block to consequently move the first linkage member.

4. The automatic closing structure of claim **3**, wherein the follower assembly comprises a follower block, which has a short rack meshing with teeth of the first linkage member; each of the rotary members comprises a gear meshing with the teeth of the first linkage member, so that the rotary member is adapted to be relatively moved by the first linkage member.

5. The automatic closing structure of claim **4**, wherein the follower block has a first protrusion, and the movable block has a second protrusion; the second protrusion abuts against a bottom surface of the first protrusion, so that the movable block is adapted to push the follower block upward, which consequently moves the first linkage member upward.

6. The automatic closing structure of claim **5**, further comprises a locating seat and an adjusting member, wherein the locating seat is fixed on the corresponding object, and the adjusting member has a mobile block movably provided on the locating seat; the locating seat has a perforation; and the mobile block of the adjusting member has a threaded hole; the adjusting member comprises a screw rod, which is screwed into the threaded hole of the mobile block through the perforation, wherein the screw rod is rotatable in situ, and the mobile block is movable on the locating seat along the screw rod.

7. The automatic closing structure of claim **3**, wherein the first linkage member of the follower assembly is a first long shaft; each of the rotary members has a pivot, which is respectively inserted into the first linkage member.

8. The automatic closing structure of claim **7**, wherein the follower assembly further comprises a follower block; the first linkage member has a connecting hole, and the follower block has a rod, which is inserted into the connecting hole, so that the first linkage member and the follower block are adapted to be moved together.

9. The automatic closing structure of claim **8**, wherein the follower block has a first protrusion, and the movable block has a second protrusion; the second protrusion abuts against a bottom surface of the first protrusion, so that the movable block is adapted to push the follower block upward, which consequently moves the first linkage member upward.

10. The automatic closing structure of claim **9**, further comprises a locating seat and an adjusting member, wherein the locating seat is fixed on the corresponding object, and the adjusting member has a mobile block movably provided on the locating seat; the locating seat has a perforation; and the mobile block of the adjusting member has a threaded hole; the adjusting member comprises a screw rod, which is screwed into the threaded hole of the mobile block through the perforation, wherein the screw rod is rotatable in situ, and the mobile block is movable on the locating seat along the screw rod.

11. An automatic closing structure, which is installed between a sash and a corresponding object, wherein the sash is pivotable relative to the corresponding object, and the sash comprises a frame and a plurality of turnable slats which are arranged in parallel in the frame; comprising a follower assembly, a linkage device, and a plurality of rotary members, wherein each of the rotary members is respectively provided at an end of each of the slats; the follower assembly is movably provided in the frame, and comprises a first linkage member to be engaged with the rotary members; the linkage device is adapted to move the follower assembly, which moves the rotary members relative to the first linkage member; wherein:

the automatic closing structure comprises a rack fixedly provided in the frame; and

the follower assembly comprises a gear, a movable block, and a second linkage member, wherein the gear is rotatably provided in the movable block, and meshes with the rack; the second linkage member has a flat teeth meshing with the gear at a side opposite to the rack;

the second linkage member is controllable to move the movable block, and to consequently move the first linkage member in a linear direction.

12. The automatic closing structure of claim **11**, wherein the follower assembly further comprises a follower block, which has a short rack meshing with teeth of the first linkage member; the rotary member comprises a gear meshing with the teeth of the first linkage member; the follower block has a first protrusion, and the movable block has a second protrusion; the second protrusion abuts against a bottom surface of the first protrusion, so that the movable block is adapted to push the follower block upward, which consequently moves the first linkage member upward.

13. The automatic closing structure of claim **12**, wherein the linkage device comprises a cord, which has a first stop portion, a second stop portion, and a cord portion located between the first stop portion and the second stop portion, wherein the first stop portion is connected to the second linkage member, and the second stop portion is connected to the corresponding object.

14. The automatic closing structure of claim **13**, further comprises a locating seat and an adjusting member, wherein the locating seat is fixed on the corresponding object, and the adjusting member has a mobile block movably provided on the locating seat; the locating seat has a perforation; and the mobile block of the adjusting member has a threaded hole; the adjusting member comprises a screw rod, which is screwed into the threaded hole of the mobile block through the perforation, wherein the screw rod is rotatable in situ, and the mobile block is movable on the locating seat along the screw rod.

15. The automatic closing structure of claim **13**, wherein the second linkage member has a slit; a part of the cord

portion which is near the first stop portion passes through the slit, so that the first stop portion is guided to abut against the second linkage member.

16. The automatic closing structure of claim **11**, wherein the follower assembly further comprises a follower block; the first linkage member of the follower assembly is a first long shaft, each of the rotary members has a pivot, which is respectively inserted into the first linkage member; the follower block has a first protrusion, and the movable block has a second protrusion; the second protrusion abuts against a bottom surface of the first protrusion, so that the movable block is adapted to push the follower block upward, which consequently moves the first linkage member upward.

17. The automatic closing structure of claim **16**, wherein the first linkage member has a connecting hole, and the follower block has a rod inserted into the connecting hole, so that the first linkage member and the follower block are adapted to be moved together.

18. The automatic closing structure of claim **16**, wherein the linkage device comprises a cord, which has a first stop portion, a second stop portion, and a cord portion located between the first stop portion and the second stop portion, wherein the first stop portion is connected to the second linkage member, and the second stop portion is connected to the corresponding object.

19. The automatic closing structure of claim **18**, further comprises a locating seat and an adjusting member, wherein the locating seat is fixed on the corresponding object, and the adjusting member has a mobile block movably provided on the locating seat; the locating seat has a perforation; and the mobile block of the adjusting member has a threaded hole; the adjusting member comprises a screw rod, which is screwed into the threaded hole of the mobile block through the perforation, wherein the screw rod is rotatable in situ, and the mobile block is movable on the locating seat along the screw rod.

20. The automatic closing structure of claim **18**, wherein the second linkage member has a slit; a part of the cord portion which is near the first stop portion passes through the slit, so that the first stop portion is guided to abut against the second linkage member.

21. An automatic closing structure, which is installed between a sash and a corresponding object, wherein the sash is pivotable relative to the corresponding object, and the sash comprises a frame and a plurality of turnable slats which are arranged in parallel in the frame; comprising a follower assembly, a linkage device, and a plurality of rotary members, wherein each of the rotary members is respectively provided at an end of each of the slats; the follower assembly is movably provided in the frame, and comprises a first linkage member to be engaged with the rotary members; the linkage device is adapted to move the follower assembly, which moves the rotary members relative to the first linkage member; wherein:

the automatic closing structure comprises a locating seat and an adjusting member, wherein the locating seat is fixed on the corresponding object, and has a bore; the adjusting member has a mobile block movably provided on the locating seat; and

the linkage device comprises a cord passing through the bore of the locating seat; the cord has a first stop portion, a second stop portion, and a cord portion located between the first stop portion and the second stop portion, wherein the first stop portion is connected to the follower assembly, and the second stop portion is connected to the mobile block.

11

22. The automatic closing structure of claim 21, wherein the locating seat has a perforation; the mobile block of the adjusting member has a threaded hole, and the adjusting member comprises a screw rod, which is screwed into the threaded hole through the perforation, and is rotatable in situ.

23. The automatic closing structure of claim 21, wherein the follower assembly comprises a second linkage member, which is controllable to move the first linkage member in a linear direction.

24. The automatic closing structure of claim 23, wherein the second linkage member has a slit; a part of the cord portion which is near the first stop portion passes through the slit, so that the first stop portion is guided to abut against the second linkage member.

25. The automatic closing structure of claim 23, further comprising a rack, which is fixedly provided in the frame, wherein the follower assembly comprises a gear and a movable block; the gear is rotatably provided in the movable block, and meshes with the rack; the second linkage member has a flat teeth meshing with the gear at a side opposite to the rack; the second linkage member is adapted to be pulled by the cord, which moves the movable block to consequently move the first linkage member.

26. The automatic closing structure of claim 25, wherein the follower assembly comprises a follower block, which

12

has a short rack meshing with teeth of the first linkage member; each of the rotary members comprises a gear meshing with the teeth of the first linkage member; the follower block has a first protrusion, and the movable block has a second protrusion; the second protrusion abuts against a bottom surface of the first protrusion, so that the movable block is adapted to push the follower block upward, which consequently moves the first linkage member upward.

27. The automatic closing structure of claim 25, wherein the follower assembly comprises a follower block; the first linkage member of the follower assembly is a first long shaft; each of the rotary members has a pivot, which is respectively inserted into the first linkage member; the follower block has a first protrusion, and the movable block has a second protrusion; the second protrusion abuts against a bottom surface of the first protrusion, so that the movable block is adapted to push the follower block upward, which consequently moves the first linkage member upward.

28. The automatic closing structure of claim 27, wherein the first linkage member has a connecting hole, and the follower block has a rod, which is inserted into the connecting hole, so that the first linkage member and the follower block are adapted to be moved together.

* * * * *