



US010036931B2

(12) **United States Patent**
Chan et al.

(10) **Patent No.:** **US 10,036,931 B2**
(45) **Date of Patent:** **Jul. 31, 2018**

(54) **COLOR DISPLAY DEVICE**

USPC 359/296; 345/107; 430/32; 204/600
See application file for complete search history.

(71) Applicant: **E Ink California, LLC.**, Fremont, CA (US)

(56) **References Cited**

(72) Inventors: **Bryan Hans Chan**, San Francisco, CA (US); **Craig Lin**, Oakland, CA (US); **Hui Du**, Milpitas, CA (US); **HongMei Zang**, Fremont, CA (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **E INK CALIFORNIA, LLC**, Fremont, CA (US)

3,756,693 A	9/1973	Ota
3,892,568 A	7/1975	Ota
4,298,448 A	11/1981	Muller
5,378,574 A	1/1995	Winnik
5,980,719 A	11/1999	Cherukuri
6,017,584 A	1/2000	Albert
6,198,809 B1	3/2001	Disanto
6,337,761 B1	1/2002	Rogers
6,373,461 B1	4/2002	Hasegawa
6,486,866 B1	11/2002	Kuwahara et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **15/337,272**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Oct. 28, 2016**

CN	1705907	12/2005
JP	2006343458	12/2006

(65) **Prior Publication Data**

(Continued)

US 2017/0045798 A1 Feb. 16, 2017

Related U.S. Application Data

OTHER PUBLICATIONS

(63) Continuation of application No. 14/596,160, filed on Jan. 13, 2015, now Pat. No. 9,513,527.

Seigou Kawaguchi, et al (2000) Synthesis of polyethylene macromonomers and their radical copolymerizations with methyl methacrylate in homogeneous and oligoethylene melts media. *Designed Monomers and Polymers* 2000, vol. 3, No. 3, pp. 263-277.

(60) Provisional application No. 61/927,418, filed on Jan. 14, 2014.

(Continued)

(51) **Int. Cl.**

Primary Examiner — William Choi

G02B 26/00 (2006.01)
G09G 3/34 (2006.01)
G02F 1/167 (2006.01)
G02F 1/133 (2006.01)

(74) *Attorney, Agent, or Firm* — Brian D. Bean

(52) **U.S. Cl.**

(57) **ABSTRACT**


CPC **G02F 1/167** (2013.01); **G02F 1/13306** (2013.01); **G09G 3/344** (2013.01); **G02F 2001/1678** (2013.01); **G02F 2203/34** (2013.01)

The present invention provides a full color display device in which each pixel can display multiple high-quality color states. More specifically, an electrophoretic fluid is provided which comprises four types of particles, dispersed in a solvent or solvent mixture and each pixel can display at least five different color states.

(58) **Field of Classification Search**

CPC . G02F 1/167; G02F 2001/1678; G09G 3/344; G09F 9/372

14 Claims, 16 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,517,618 B2	2/2003	Foucher	7,679,599 B2	3/2010	Kawai
6,525,866 B1	2/2003	Lin	7,684,108 B2	3/2010	Wang
6,538,801 B2	3/2003	Jacobson	7,686,463 B2	3/2010	Goto
6,545,797 B2	4/2003	Chen	7,760,419 B2	7/2010	Lee
6,600,534 B1	7/2003	Tanaka	7,782,292 B2	8/2010	Miyasaka
6,650,462 B2	11/2003	Katase	7,791,789 B2	9/2010	Albert
6,664,944 B1	12/2003	Albert	7,800,813 B2	9/2010	Wu
6,680,726 B2	1/2004	Gordon, II	7,808,696 B2	10/2010	Lee
6,693,620 B1	2/2004	Herb	7,821,702 B2	10/2010	Liang
6,704,133 B2	3/2004	Gates	7,830,592 B1	11/2010	Sprague
6,724,521 B2	4/2004	Nakao	7,839,564 B2	11/2010	Whitesides et al.
6,729,718 B2	5/2004	Goto	7,848,009 B2	12/2010	Machida
6,751,007 B2	6/2004	Liang	7,852,547 B2	12/2010	Kim
6,751,008 B2	6/2004	Liang	7,852,548 B2	12/2010	Roh
6,781,745 B2	8/2004	Chung	7,907,327 B2	3/2011	Jang
6,788,452 B2	9/2004	Liang	7,910,175 B2	3/2011	Webber
6,829,078 B2	12/2004	Liang	7,911,681 B2	3/2011	Ikegami
6,850,357 B2	2/2005	Kaneko	7,952,790 B2	5/2011	Honeyman
6,864,875 B2	3/2005	Drzaic	7,956,841 B2	6/2011	Albert
6,876,486 B2	4/2005	Hiraoka	7,982,941 B2	7/2011	Lin
6,914,714 B2	7/2005	Chen	8,040,594 B2	10/2011	Paolini, Jr.
6,930,818 B1	8/2005	Liang	8,054,526 B2	11/2011	Bouchard
6,947,203 B2	9/2005	Kanbe	8,067,305 B2	11/2011	Zafiropoulo
6,967,762 B2	11/2005	Machida	8,072,675 B2	12/2011	Lin
6,972,893 B2	12/2005	Chen et al.	8,081,375 B2	12/2011	Komatsu
6,987,503 B2	1/2006	Inoue	8,089,686 B2	1/2012	Addington
6,987,605 B2	1/2006	Liang	8,098,418 B2	1/2012	Paolini, Jr.
7,009,756 B2	3/2006	Kishi	8,115,729 B2	2/2012	Danner
7,019,889 B2	3/2006	Katase	8,120,838 B2	2/2012	Lin
7,034,987 B2	4/2006	Schlangen	8,159,636 B2	4/2012	Sun
7,038,655 B2	5/2006	Herb	8,164,823 B2	4/2012	Ikegami
7,038,656 B2	5/2006	Liang	8,169,690 B2	5/2012	Lin
7,038,670 B2	5/2006	Liang	8,174,492 B2	5/2012	Kim
7,046,228 B2	5/2006	Liang	8,213,076 B2	7/2012	Albert
7,050,218 B2	5/2006	Kanbe	8,237,892 B1	8/2012	Sprague
7,052,571 B2	5/2006	Wang	8,243,013 B1	8/2012	Sprague
7,057,600 B2	6/2006	Goden	8,355,196 B2	1/2013	Yan
7,057,798 B2	6/2006	Ukigaya	8,363,299 B2	1/2013	Paolini, Jr.
7,075,502 B1	7/2006	Drzaic	8,395,836 B2	3/2013	Lin
7,116,466 B2	10/2006	Whitesides et al.	8,422,116 B2	4/2013	Sprague
7,167,155 B1	1/2007	Albert et al.	8,441,713 B2	5/2013	Kawashima
7,226,550 B2	6/2007	Hou	8,441,714 B2	5/2013	Paolini, Jr.
7,259,744 B2	8/2007	Arango	8,441,716 B2	5/2013	Paolini, Jr.
7,271,947 B2	9/2007	Liang	8,466,852 B2	6/2013	Drzaic
7,283,119 B2	10/2007	Kishi	8,477,404 B2	7/2013	Moriyama
7,292,386 B2	11/2007	Kanbe	8,477,405 B2	7/2013	Ishii
7,303,818 B2	12/2007	Minami	8,503,063 B2	8/2013	Sprague
7,304,987 B1	12/2007	James	8,520,296 B2	8/2013	Wang
7,312,916 B2	12/2007	Pullen	8,537,104 B2	9/2013	Markvoort
7,342,556 B2	3/2008	Oue	8,565,522 B2	10/2013	Swic
7,345,810 B2	3/2008	Chopra	8,570,272 B2	10/2013	Hsieh
7,352,353 B2	4/2008	Albert	8,570,639 B2	10/2013	Masuzawa
7,365,732 B2	4/2008	Matsuda	8,574,937 B2	11/2013	Shi
7,382,351 B2	6/2008	Kishi	8,576,470 B2	11/2013	Paolini, Jr.
7,385,751 B2	6/2008	Chen	8,576,475 B2	11/2013	Huang
7,411,719 B2	8/2008	Paolini, Jr. et al.	8,593,721 B2	11/2013	Albert
7,417,787 B2	8/2008	Chopra	8,599,120 B2	12/2013	Kanou
7,420,549 B2	9/2008	Jacobson	8,605,354 B2	12/2013	Zhang
7,433,113 B2	10/2008	Chopra	8,610,998 B2	12/2013	Baisch
7,443,570 B2	10/2008	Chopra	8,629,832 B2	1/2014	Tanabe
7,474,295 B2	1/2009	Matsuda	8,649,084 B2	2/2014	Wang
7,492,505 B2	2/2009	Liang	8,670,174 B2	3/2014	Sprague
7,495,821 B2	2/2009	Yamakita	8,674,978 B2	3/2014	Komatsu
7,502,162 B2	3/2009	Lin	8,681,191 B2	3/2014	Yang
7,545,557 B2	6/2009	Iftime	8,687,265 B2	4/2014	Ahn
7,548,291 B2	6/2009	Lee	8,704,754 B2	4/2014	Machida
7,557,981 B2	7/2009	Liang	8,704,756 B2	4/2014	Lin
7,580,025 B2	8/2009	Nakai	8,717,662 B2	5/2014	Komatsu
7,605,972 B2	10/2009	Kawai	8,717,664 B2	5/2014	Wang
7,609,435 B2	10/2009	Moriyama	8,786,935 B2	7/2014	Sprague
7,626,185 B2	12/2009	Krak	8,797,258 B2	8/2014	Sprague
7,636,076 B2	12/2009	Hung	8,797,634 B2	8/2014	Paolini, Jr.
7,652,656 B2	1/2010	Chopra	8,797,636 B2	8/2014	Yang
7,656,576 B2	2/2010	Suwabe	8,797,637 B2	8/2014	Fujishiro
7,667,684 B2	2/2010	Jacobson et al.	8,810,899 B2	8/2014	Sprague
			8,830,559 B2	9/2014	Honeyman
			8,873,129 B2	10/2014	Paolini, Jr.
			8,902,153 B2	12/2014	Bouchard
			8,902,491 B2	12/2014	Wang

(56)

References Cited

U.S. PATENT DOCUMENTS

8,917,439 B2 12/2014 Wang
 8,964,282 B2 2/2015 Wang
 8,976,444 B2 3/2015 Zhang
 9,013,783 B2 4/2015 Sprague
 9,052,564 B2 6/2015 Sprague
 9,116,412 B2 8/2015 Lin
 9,140,952 B2 9/2015 Sprague
 9,146,439 B2 9/2015 Zhang
 9,164,207 B2 10/2015 Honeyman et al.
 9,170,467 B2 10/2015 Whitesides
 9,170,468 B2 10/2015 Lin
 9,182,646 B2 11/2015 Paolini, Jr.
 9,195,111 B2 11/2015 Anseth
 9,199,441 B2 12/2015 Danner
 9,251,736 B2 2/2016 Lin
 9,268,191 B2 2/2016 Paolini, Jr.
 9,285,649 B2 3/2016 Du
 9,293,511 B2 3/2016 Jacobson
 9,341,916 B2 5/2016 Telfer et al.
 9,360,733 B2 6/2016 Wang
 9,361,836 B1 6/2016 Telfer et al.
 9,383,623 B2 7/2016 Lin
 9,423,666 B2 8/2016 Wang
 9,460,666 B2 10/2016 Sprague
 2001/0035926 A1 11/2001 Yamaguchi
 2004/0085619 A1 5/2004 Wu
 2007/0002008 A1 1/2007 Tam
 2007/0080928 A1 4/2007 Ishii
 2007/0273637 A1 11/2007 Zhou
 2008/0042928 A1 2/2008 Schlangen
 2008/0043318 A1 2/2008 Whitesides
 2008/0048970 A1 2/2008 Drzaic
 2008/0062159 A1 3/2008 Roh
 2008/0117165 A1 5/2008 Machida
 2008/0174531 A1 7/2008 Sah
 2009/0153942 A1 6/2009 Daniel
 2009/0167754 A1 7/2009 Hatta
 2009/0184897 A1 7/2009 Miyamoto
 2009/0225398 A1 9/2009 Duthaler
 2009/0311484 A1 12/2009 McLellan
 2010/0156780 A1 6/2010 Jacobson
 2011/0043543 A1 2/2011 Chen
 2011/0175939 A1 7/2011 Moriyama
 2011/0199671 A1 8/2011 Amundson
 2011/0217639 A1 9/2011 Sprague
 2011/0234557 A1 9/2011 Yang

2012/0299947 A1 11/2012 Tsuda
 2012/0326957 A1 12/2012 Drzaic
 2013/0242378 A1 9/2013 Paolini, Jr.
 2013/0278995 A1 10/2013 Drzaic
 2014/0011913 A1 1/2014 Du
 2014/0055840 A1 2/2014 Zang
 2014/0078576 A1 3/2014 Sprague
 2014/0340430 A1 11/2014 Telfer
 2014/0340736 A1 11/2014 Lin
 2014/0362213 A1 12/2014 Tseng
 2015/0103394 A1 4/2015 Wang
 2015/0118390 A1 4/2015 Rosenfeld
 2015/0124345 A1 5/2015 Rosenfeld
 2015/0198858 A1 7/2015 Chan
 2015/0234250 A1 8/2015 Lin
 2015/0241754 A1 8/2015 Du
 2015/0268531 A1 9/2015 Wang
 2015/0301246 A1 10/2015 Zang
 2016/0011484 A1 1/2016 Chan
 2016/0026062 A1 1/2016 Zhang
 2016/0048054 A1 2/2016 Danner
 2016/0116816 A1 4/2016 Paolini
 2016/0116818 A1 4/2016 Du
 2016/0140909 A1 5/2016 Lin
 2016/0260372 A1 9/2016 Wang

FOREIGN PATENT DOCUMENTS

JP 2007033710 2/2007
 JP 2008033000 2/2008
 JP 2008209589 9/2008
 JP 2009116041 5/2009
 JP 2009192637 8/2009
 JP 2009244635 10/2009
 JP 2011158783 8/2011
 KR 1020070082680 8/2007
 KR 1020110103765 9/2011
 TW 201122697 7/2011
 TW 201237529 9/2012
 WO 1999053373 10/1999

OTHER PUBLICATIONS

PCT/US2015/011237, PCT Notification of Transmittal of The International Search Report and The Written Opinion of The International Searching Authority, or The Declaration, dated Apr. 10, 2015. European Patent Office; EP Appl. No. 15737734.2; Extended European Search Report; dated Jun. 6, 2017, Jun. 6, 2017.




Figure 1




Figure 2-1




Figure 2-2




Figure 2-3

Viewing Side




Figure 2-4




Figure 3




Fig. 4A

Fig. 4B

Fig. 4C




Fig. 5A

Fig. 5B

Fig. 5C




Figure 6-1




Figure 6-2




Figure 6-3




Figure 6-4




Fig. 7A

Fig. 7B

Fig. 7C




Fig. 8A

Fig. 8B

Fig. 8C




Figure 9A




Figure 9B

COLOR DISPLAY DEVICE

REFERENCE TO RELATED APPLICATIONS

This application is a continuation of copending application Ser. No. 14/596,160, filed Jan. 13, 2015 (Publication No. 2015/0198858), which claims benefit of Application Ser. No. 61/927,418, filed Jan. 14, 2014. The entire contents of these applications are incorporated by reference in their entirety.

BACKGROUND OF INVENTION

The present invention is directed to a full color display device in which each pixel can display multiple high-quality color states, and an electrophoretic fluid for such an electrophoretic display.

In order to achieve a color display, color filters are often used. The most common approach is to add color filters on top of black/white sub-pixels of a pixellated display to display the red, green and blue colors. When a red color is desired, the green and blue sub-pixels are turned to the black state so that the only color displayed is red. When a green color is desired, the red and blue sub-pixels are turned to the black state so that the only color displayed is green. When a blue color is desired, the green and red sub-pixels are turned to the black state so that the only color displayed is blue. When the black state is desired, all three-sub-pixels are turned to the black state. When the white state is desired, the three sub-pixels are turned to red, green and blue, respectively, and as a result, a white state is seen by the viewer.

The biggest disadvantage of such a technique is that since each of the sub-pixels has a reflectance of about one third of the desired white state, the white state is fairly dim. To compensate this, a fourth sub-pixel may be added which can display only the black and white states, so that the white level is doubled at the expense of the red, green or blue color level (where each sub-pixel is only one fourth of the area of the pixel). Brighter colors can be achieved by adding light from the white pixel, but this is achieved at the expense of color gamut to cause the colors to be very light and unsaturated. A similar result can be achieved by reducing the color saturation of the three sub-pixels. Even with this approach, the white level is normally substantially less than half of that of a black and white display, rendering it an unacceptable choice for display devices, such as e-readers or displays that need well readable black-white brightness and contrast.

SUMMARY OF INVENTION

One aspect of the present invention is directed to an electrophoretic display, comprising

- (a) a plurality of pixels; and
- (b) an electrophoretic fluid in which a first type of particles, a second type of particles, a third type of particles and a fourth type of particles are dispersed in a solvent or solvent mixture and the first and second types of particles carry a high level of charge and are oppositely charged and the third and fourth types of particles carry a low level of charge and are oppositely charged,

wherein each of the pixels is capable of displaying at least five different color states.

In one embodiment, the first and second type of articles are of the white and red colors, respectively. In one embodiment, the third and fourth types of particles are of the blue and green colors, respectively. In one embodiment, each of

the pixels is capable of displaying white, red, green, blue and black color states. In another embodiment, each of the pixels is capable of displaying yellow, magenta and cyan color states.

In one embodiment, the third and fourth types of particles are of the blue and yellow colors, respectively. In one embodiment, each of the pixels is capable of displaying white, red, yellow, blue and black color states. In one embodiment, each of the pixels is capable of displaying green, orange and purple color states.

In one embodiment, the low level of charge is less than about 50% of the high level of charge. In another embodiment, the low level of charge is less than about 75% of the high level of charge.

In one embodiment, the electrophoretic fluid further comprises substantially uncharged neutral buoyancy particles. In another embodiment, the substantially uncharged neutral buoyancy particles are non-charged.

Another aspect of the present invention is directed to a display layer comprising an electrophoretic fluid and having first and second surfaces on opposed sides thereof, the electrophoretic fluid comprising high positive particles, high negative particles, low positive particles and low negative particles, all dispersed in a solvent or solvent mixture, the four type of particles having respectively optical characteristics differing from one another, such that:

- (a) application of an electric field which has the same polarity as the high positive particles will cause the optical characteristics of the high positive particles to be displayed at the first surface; or
- (b) application of an electric field which has the same polarity as high negative particles will cause the optical characteristic of the high negative particles to be displayed at the first surface; or
- (c) once the optical characteristic of the high positive particles is displayed at the first surface, application of an electric field which has the same polarity as low negative particles, but is not strong enough to overcome the attraction force between the high positive particles and the high negative particles, but sufficient to overcome the attraction forces between other oppositely charged particles will cause the optical characteristic of the low negative particles to be displayed at the first surface; or
- (d) once the optical characteristic of the high negative particles is displayed at the first surface, application of an electric field which has the same polarity as the low positive particles, but is not strong enough to overcome the attraction force between the high positive particles and the high negative particles, but sufficient to overcome the attraction forces between other oppositely charged particles will cause the optical characteristic of the low positive particles to be displayed at the first surface; or
- (e) application of a shaking waveform will cause a fifth optical characteristic to be displayed at the first surface.

In one embodiment of this aspect of the invention, the four types of particles are red, green, blue and white. In another embodiment, the four types of particles are red, yellow, blue and white. In a further embodiment, the four types of particles are cyan, magenta, yellow and white.

In one embodiment, none of the four types of particles is black particles and the fifth optical characteristic is a black color state.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 depicts an electrophoretic display device of the present invention.

FIGS. 2-1 to 2-4 illustrate an example of the present invention.

FIG. 3 shows a shaking waveform.

FIGS. 4A-4C and 5A-5C show how yellow, magenta and cyan color states may be displayed by a display device of FIG. 2.

FIGS. 6-1 to 6-4 illustrate another example of the present invention.

FIGS. 7A-7C and 8A-8C show how purple, orange and green color states may be displayed by a display device of FIG. 6.

FIGS. 9A and 9B, respectively, demonstrate display cells aligned or unaligned with pixel electrodes.

DETAILED DESCRIPTION

The electrophoretic fluid of the present invention comprises four types of particles dispersed in a dielectric solvent or solvent mixture. For ease of illustration, the four types of pigment particles may be referred to as the first type (11), the second type (12), the third type (13) and the fourth type (14) of particles, as shown in FIG. 1. However, with only four types of pigment particles, a display device utilizing the electrophoretic fluid may display at least five different color states, which leads to a full color display.

Generally, the four types of particles are divided into two groups—high charge group and low charge group. In the two groups of oppositely charged particles, one group carries a stronger charge than the other group. Therefore the four types of pigment particles may also be referred to as high positive particles, high negative particles, low positive particles and low negative particles.

As an example, red particles (R) and white particles (W) may be the first group of oppositely charged particles, and in this group, the red particles are the high positive particles and the white particles are the high negative particles. The blue particles (B) and the green particles (G) may be the second group of oppositely charged particles and in this group, the blue particles are the low positive particles and the green particles are the low negative particles.

In another example, red particles may be the high positive particles; white particles may be the high negative particles; blue particles may be the low positive particles and yellow particles may be the low negative particles.

It is understood that the scope of the invention broadly encompasses particles of any colors as long as the four types of particles have visually distinguishable colors.

For the white particles, they may be formed from an inorganic pigment, such as TiO_2 , ZrO_2 , ZnO , Al_2O_3 , Sb_2O_3 , BaSO_4 , PbSO_4 or the like.

For the black particles, if present, they may be formed from CI pigment black 26 or 28 or the like (e.g., manganese ferrite black spinel or copper chromite black spinel) or carbon black. 321 Particles of other colors (non-white and non-black) are independently of a color such as red, green, blue, magenta, cyan or yellow. The pigments for color particles may include, but are not limited to, CI pigment PR 254, PR122, PR149, PG36, PG58, PG7, PB28, PB15:3, PY83, PY138, PY150, PY155 or PY20. Those are commonly used organic pigments described in color index handbooks, "New Pigment Application Technology" (CMC Publishing Co, Ltd, 1986) and "Printing Ink Technology" (CMC Publishing Co, Ltd, 1984). Specific examples include Clariant Hostaperm Red D3G 70-EDS, Hostaperm Pink E-EDS, PV fast red D3G, Hostaperm red D3G 70, Hostaperm Blue B2G-EDS, Hostaperm Yellow H4G-EDS, Novoperm Yellow HR-70-EDS, Hostaperm Green GNX,

BASF Irgazine red L 3630, Cinquasia Red L 4100 HD, and Irgazin Red L 3660 HD; Sun Chemical phthalocyanine blue, phthalocyanine green, diarylide yellow or diarylide AAOT yellow.

The non-black and non-white color particles may also be inorganic pigments, such as red, green, blue and yellow pigments. Examples may include, but are not limited to, CI pigment blue 28, CI pigment green 50 and CI pigment yellow 227.

In addition to the colors, the four types of particles may have other distinct optical characteristics, such as optical transmission, reflectance, and luminescence or, in the case of displays intended for machine reading, pseudo-color in the sense of a change in reflectance of electromagnetic wavelengths outside the visible range.

As also shown in FIG. 1, a display layer utilizing the display fluid of the present invention has two surfaces, a first surface (17) on the viewing side and a second surface (18) on the opposite side of the first surface (17). The display fluid is sandwiched between the two surfaces. On the side of the first surface (17), there is a common electrode (15) which is a transparent electrode layer (e.g., ITO), spreading over the entire top of the display layer. On the side of the second surface (18), there is an electrode layer (16) which comprises a plurality of pixel electrodes (16A).

The pixel electrodes are described in U.S. Pat. No. 7,046,228, the content of which is incorporated herein by reference in its entirety. It is noted that while active matrix driving with a thin film transistor (TFT) backplane is mentioned for the layer of pixel electrodes, the scope of the present invention encompasses other types of electrode addressing as long as the electrodes serve the desired functions.

Each space between two dotted vertical lines in FIG. 1 denotes a pixel. As shown, each pixel has a corresponding pixel electrode. An electric field is created for a pixel by the potential difference between a voltage applied to the common electrode and a voltage applied to the corresponding pixel electrode.

The percentages of the four types of particles in the fluid may vary. For example, one type of particles may take up 0.1% to 50%, preferably 0.5% to 15%, by volume of the electrophoretic fluid.

The solvent in which the four types of particles are dispersed is clear and colorless. It preferably has a low viscosity and a dielectric constant in the range of about 2 to about 30, preferably about 2 to about 15 for high particle mobility. Examples of suitable dielectric solvent include hydrocarbons such as isopar, decahydronaphthalene (DECALIN), 5-ethylidene-2-norbornene, fatty oils, paraffin oil, silicon fluids, aromatic hydrocarbons such as toluene, xylene, phenylxylylethane, dodecylbenzene or alkyl-naphthalene, halogenated solvents such as perfluorodecalin, perfluorotoluene, perfluoroxylene, dichlorobenzotrifluoride, 3,4,5-trichlorobenzotrifluoride, chloropentafluorobenzene, dichlorononane or pentachlorobenzene, and perfluorinated solvents such as FC-43, FC-70 or FC-5060 from 3M Company, St. Paul Minn., low molecular weight halogen containing polymers such as poly(perfluoropropylene oxide) from TCI America, Portland, Oreg., poly(chlorotrifluoroethylene) such as Halocarbon Oils from Halocarbon Product Corp., River Edge, N.J., perfluoropolyalkylether such as Galden from Ausimont or Krytox Oils and Greases K-Fluid Series from DuPont, Del., polydimethylsiloxane based silicone oil from Dow-corning (DC-200).

In one embodiment, the charge carried by the "low charge" particles may be less than about 50%, or about 5%

to about 30%, of the charge carried by the “high charge” particles. In another embodiment, the “low charge” particles may be less than about 75%, or about 15% to about 55%, the charge carried by the “high charge” particles. In a further embodiment, the comparison of the charge levels as indicated applies to two types of particles having the same charge polarity.

The charge intensity may be measured in terms of zeta potential. In one embodiment, the zeta potential is determined by Colloidal Dynamics AcoustoSizer IIM with a CSPU-100 signal processing unit, ESA EN# Attn flow through cell (K:127). The instrument constants, such as density of the solvent used in the sample, dielectric constant of the solvent, speed of sound in the solvent, viscosity of the solvent, all of which at the testing temperature (25° C.) are entered before testing. Pigment samples are dispersed in the solvent (which is usually a hydrocarbon fluid having less than 12 carbon atoms), and diluted to between 5-10% by weight. The sample also contains a charge control agent (Solsperse 17000®, available from Lubrizol Corporation, a Berkshire Hathaway company; “Solsperse” is a Registered Trade Mark), with a weight ratio of 1:10 of the charge control agent to the particles. The mass of the diluted sample is determined and the sample is then loaded into the flow through cell for determination of the zeta potential.

The magnitudes of the “high positive” particles and the “high negative” particles may be the same or different. Likewise, the magnitudes of the “low positive” particles and the “low negative” particles may be the same or different.

It is also noted that in the same fluid, the two groups of high-low charge particles may have different levels of charge differentials. For example, in one group, the low positively charged particles may have a charge intensity which is 30% of the charge intensity of the high positively charged particles and in another group, the low negatively charged particles may have a charge intensity which is 50% of the charge intensity of the high negatively charged particles.

The charge polarities and levels of charge for the particles may be tuned, according to the method described in US Publication No. 2014-0011913, the contents of which are incorporated herein by reference in its entirety.

It is also noted that the four types of particles may have different particle sizes. For example, smaller particles may have a size which ranges from about 50 nm to about 800 nm. Larger particles may have a size which is about 2 to about 50 times, and more preferably about 2 to about 10 times, the sizes of the smaller particles.

EXAMPLE 1

This example is demonstrated in FIG. 2. The fluid in this example has red, green, blue and white pigment particles. The red particles (R) carry a high positive charge, the white particles (W) carry a high negative charge, the blue (B) particles carry a low positive charge and the green particles (G) carry a low negative charge.

In FIG. 2-1, when a high negative voltage potential difference (e.g., -15V) is applied to a pixel, the white particles (W) are pushed to the common electrode (21) side and the red particles (R) are pulled to the pixel electrode (22A) side. The blue (B) and green (G) particles, due to their lower charge level, move slower than the higher charged white and red particles and therefore they stay in the middle of the pixel, with green particles above the blue particles. As a result, the white color is seen at the viewing side (State (a) in FIG. 2-1).

In FIG. 2-1, when a high positive voltage potential difference (e.g., +15V) is applied to the pixel, the particle distribution would be opposite of State (a) and as a result, the red color is seen at the viewing side (State (b) in FIG. 2-1).

In FIG. 2-2, when a lower positive voltage potential difference (e.g., +3V) is applied to the pixel in State (a) (that is, driven from the white state), the white particles (W) move towards the pixel electrode (22A) while the red particles (R) move towards the common electrode (21). When they meet while moving, because of their strong attraction to each other, they stop moving and remain in the middle of the pixel. In other words, the electric field generated by the low positive voltage potential difference is not strong enough to separate the white and red particles.

However, the electric field is strong enough to separate the lower charged blue and green particles and also strong enough to overcome the attraction forces between the oppositely charged high-low particle pairs (white/blue and red/green). As a result, the lower charged (positive) blue particles (B) move all the way to the common electrode (21) side (i.e., the viewing side) and the lower charged (negative) green particles (G) move to the pixel electrode (22A) side. Consequently, the blue color is seen at the viewing side (State (c) in FIG. 2-2).

In FIG. 2-3, when a lower negative voltage potential difference (e.g., -3V) is applied to the pixel in State (b) (that is, driven from the red state), the red particles (R) move towards the pixel electrode (22A) while the white particles (W) move towards the common electrode (21). When the white and red particles meet, because of their strong attraction to each other, they stop moving and remain in the middle of the pixel. In other words, the electric field generated by the low negative voltage potential difference is not strong enough to separate the white and red particles.

However, the electric field is strong enough to separate the lower charged blue and green particles and also strong enough to overcome the attraction forces between the oppositely charged high-low particle pairs (white/blue and red/green). As a result, the lower charged (negative) green particles (G) move all the way to the common electrode side (i.e., the viewing side) and the lower charged (positive) blue particles (B) move to the pixel electrode side. Consequently, the green color is seen at the viewing side (State (d) in FIG. 2-3).

In FIG. 2-4, State (e), a black color is seen from the viewing side. This may be achieved by applying a shaking waveform when a pixel is in the red color state (State (b)) to cause the red, green and blue particles to be mixed in the upper part of the pixel, leading to the black state to be seen at the viewing side.

A shaking waveform consists of repeating a pair of opposite driving pulses for many cycles. For example, the shaking waveform may consist of a +15V pulse for 20 msec and a -15V pulse for 20 msec and such a pair of pulses is repeated for 50 times. The total time of such a shaking waveform would be 2000 msec (see FIG. 3).

In practice, there may be at least 10 repetitions (i.e., ten pairs of positive and negative pulses).

After the shaking waveform is applied, the optical state would be from a mixture of the particles, seen to be black in the present example.

Each of the driving pulse in the shaking waveform is applied for not exceeding 50% (or not exceeding 30%, 10% or 5%) of the driving time required from the full white state to the full red state in the example. For example, if it takes 300 msec to drive a pixel from a full white state to a red yellow state or vice versa, the shaking waveform may

consist of positive and negative pulses, each applied for not more than 150 msec. In practice, it is preferred that the pulses are shorter.

It is also noted that the lower voltage potential difference applied to reach the color States (c) and (d) may be about 5% to about 50% of the full driving voltage potential difference required to drive the pixel from the red state to the white state or from the white state to the red state.

While Example 2 demonstrates the possibility of a pixel exhibiting black, white, red, green or blue color state, the present invention also provides the possibility for a pixel to exhibit yellow, magenta or cyan color state.

In FIGS. 4A-4C, each pixel has two sub-pixels. In FIG. 4A, a yellow state is displayed when one sub-pixel displays a red color and the other sub-pixel displays a green color. In FIG. 4B, one sub-pixel displays a red color and the other sub-pixel displays a blue color, leading the pixel to display a magenta state. In FIG. 4C, a pixel displays a cyan color state while one of the sub-pixels displays a blue color and the other sub-pixel displays a green color.

To display a brighter yellow, magenta or cyan color state, a pixel may consist of three sub-pixels. This is shown in FIGS. 5A-5C wherein a third sub-pixel is added, which third sub-pixel displays only the white color state.

EXAMPLE 2

This example is demonstrated in FIGS. 6-1 to 6-4. The fluid in this example has red, yellow, blue and white pigment particles. The red particles (R) carry a high positive charge, the white particles (W) carry a high negative charge, the blue (B) particles carry a low positive charge and the yellow particles (Y) carry a low negative charge.

In FIG. 6-1, when a high negative voltage potential difference (e.g., -15V) is applied to a pixel, the white particles (W) are pushed to the common electrode (61) side and the red particles (R) are pulled to the pixel electrode (62A) side. The blue (B) and yellow (Y) particles, due to their lower charge level, move slower than the higher charged white and red particles and therefore they stay in the middle of the pixel, with yellow particles above the blue particles. As a result, the white color is seen at the viewing side (State (a) in FIG. 6-1).

Also in FIG. 6-1, when a high positive voltage potential difference (e.g., +15V) is applied to the pixel, the particle distribution would be opposite of State (a) and as a result, the red color is seen at the viewing side (State (b) in FIG. 6-1).

In FIG. 6-2, when a lower positive voltage potential difference (e.g., +3V) is applied to the pixel in State (that is, driven from the white state), the white particles (W) move towards the pixel electrode (62A) while the red particles (R) move towards the common electrode (61). When they meet while moving, because of their strong attraction to each other, they stop moving and remain in the middle of the pixel. In other words, the electric field generated by the low positive voltage potential difference is not strong enough to separate the white and red particles.

However, the electric field is strong enough to separate the lower charged blue and yellow particles and also strong enough to overcome the attraction forces between the oppositely charged high-low particle pairs (white/blue and red/yellow). As a result, the lower charged (positive) blue particles (B) move all the way to the common electrode (61) side (i.e., the viewing side) and the lower charged (negative) yellow particles (Y) move to the pixel electrode (62A) side. Consequently, the blue color is seen at the viewing side (State (c) in FIG. 6-2).

In FIG. 6-3, when a lower negative voltage potential difference (e.g., -3V) is applied to the pixel in State (b) (that is, driven from the red state), the red particles (R) move towards the pixel electrode (62A) while the white particles (W) move towards the common electrode (61). When the white and red particles meet, because of their strong attraction to each other, they stop moving and remain in the middle of the pixel. In other words, the electric field generated by the low negative voltage potential difference is not strong enough to separate the white and red particles.

However, the electric field is strong enough to separate the lower charged blue and yellow particles and also strong enough to overcome the attraction forces between the oppositely charged high-low particle pairs (white/blue and red/yellow). As a result, the lower charged (negative) yellow particles (Y) move all the way to the common electrode side (i.e., the viewing side) and the lower charged (positive) blue particles (B) move to the pixel electrode side. Consequently, the yellow color is seen at the viewing side (State (d) in FIG. 6-3).

In FIG. 6-4, a black color is seen from the viewing side. This may be achieved by applying a shaking waveform when a pixel is in the red color state (State (b)), leading to the black color state to be seen at the viewing side (State (e) in FIG. 6-4).

Similarly as described in Example 2, the lower voltage potential difference applied to reach the color States (c) and (d) may be about 5% to about 50% of the full driving voltage potential difference required to drive the pixel from the red state to the white state or from the white state to the red state.

While Example 2 demonstrates the possibility of a pixel exhibiting black, white, red, yellow or blue color state, the present invention also provides the possibility for a pixel to exhibit purple, orange or green color state.

In FIGS. 7A-7C, each pixel has two sub-pixels. In FIG. 7A, a purple state is displayed when one sub-pixel displays a red color and the other sub-pixel displays a blue color. Likewise, in FIG. 7B, one sub-pixel displays a red color and the other sub-pixel displays a yellow color, leading the pixel to display an orange state. In FIG. 7C, a pixel displays a green color state while one of the sub-pixels displays a blue color and the other sub-pixel displays a yellow color.

To display a brighter purple, orange or green color state, a pixel may consist of three sub-pixels. This is shown in FIGS. 8A-8C wherein a third sub-pixel is added, which third sub-pixel displays only the white color state.

Although in the two examples, particles of specific colors are demonstrated to be utilized, in practice as stated above, the particles carrying a high positive charge, or a high negative charge, or a low positive charge or a low negative charge may be of any colors. All of these variations are intended to be within the scope of this application. For example, the four types of particles may be cyan, magenta, yellow and white.

In a further aspect of the present invention, the fluid may further comprise substantially uncharged neutral buoyancy particles.

The term "substantially uncharged" refers to the particles which are either uncharged or carry a charge which is less than 5% of the average charge carried by the charged particles. In one embodiment, the neutral buoyancy particles are non-charged.

The term "neutral buoyancy" refers to particles which do not rise or fall with gravity. In other words, the particles would float in the fluid between the two electrode plates. In one embodiment, the density of the neutral buoyancy par-

ticles may be the same as the density of the solvent or solvent mixture in which they are dispersed.

The concentration of the substantially uncharged neutral buoyancy particles in the display fluid is preferably in the range of about 0.1 to about 10% by volume, more preferably in the range of about 0.1 to about 5% by volume.

The substantially uncharged neutral buoyancy particles may be formed from a polymeric material. The polymeric material may be a copolymer or a homopolymer.

Examples of the polymeric material for the substantially uncharged neutral buoyancy particles may include, but are not limited to, polyacrylate, polymethacrylate, polystyrene, polyaniline, polypyrrole, polyphenol and polysiloxane. Specific examples of the polymeric material may include, but are not limited to, poly(pentabromophenyl methacrylate), poly(2-vinylnaphthalene), poly(naphthyl methacrylate), poly(alpha-methylstyrene), poly(N-benzyl methacrylamide) and poly(benzyl methacrylate).

More preferably, the substantially uncharged neutral buoyancy particles are formed from a polymer which is not soluble in the solvent of the display fluid, and also has a high refractive index. In one embodiment, the refractive index of the substantially uncharged neutral buoyancy particles is different from that of the solvent or solvent mixture in which the particles are dispersed. However, typically the refractive index of the substantially uncharged neutral buoyancy particles is higher than that of the solvent or solvent mixture. In some cases, the refractive index of the substantially uncharged neutral buoyancy particles may be above 1.45.


In one embodiment, the materials for the substantially uncharged neutral buoyancy particles may comprise an aromatic moiety.

The substantially uncharged neutral buoyancy particles may be prepared from monomers through polymerization techniques, such as suspension polymerization, dispersion polymerization, seed polymerization, soap-free polymerization, emulsion polymerization or physical method, including inverse emulsification-evaporation process. The monomers are polymerized in the presence of a dispersant. The presence of the dispersant allows the polymer particles to be formed in a desired size range and the dispersant may also form a layer physically or chemically bonded to the surface of the polymer particles to prevent the particles from agglomeration.

The dispersant preferably has a long chain (of at least eight atoms), which may stabilize the polymer particles in a hydrocarbon solvent. Such dispersants may be an acrylate-terminated or vinyl-terminated macromolecule, which are suitable because the acrylate or vinyl group can co-polymerize with the monomer in the reaction medium.

One specific example of the dispersant is acrylate terminated polysiloxane (Gelest, MCR-M17, MCR-M22),

Another type of suitable dispersants is polyethylene macromonomers, as shown below:



The backbone of the macromonomer may be a polyethylene chain and the integer “n” may be 30-200. The synthesis of this type of macromonomers may be found in Seigou Kawaguchi et al, *Designed Monomers and Polymers*, 2000, 3, 263.

If the fluid system is fluorinated, the dispersants are then preferably also fluorinated.

Alternatively, the substantially uncharged neutral buoyancy particles may also be formed from a core particle

coated with a polymeric shell and the shell may be formed, for example, from any of the polymeric material identified above.

The core particle may be of an inorganic pigment such as TiO₂, ZrO₂, ZnO, Al₂O₃, CI pigment black 26 or 28 or the like (e.g., manganese ferrite black spinel or copper chromite black spinel), or an organic pigment such as phthalocyanine blue, phthalocyanine green, diarylide yellow, diarylide AAOT yellow, and quinacridone, azo, rhodamine, perylene pigment series from Sun Chemical, Hansa yellow G particles from Kanto Chemical, and Carbon Lampblack from Fisher, or the like.

In the case of core-shell substantially uncharged neutral buoyancy particles, they may be formed by a microencapsulation method, such as coacervation, interfacial polycondensation, interfacial cross-linking, in-suit polymerization or matrix polymerization.

The size of the substantially uncharged neutral buoyancy particles is preferably in the range of about 100 nanometers to about 5 microns.

In one embodiment of this aspect of the present invention, the substantially uncharged neutral buoyancy particles added to the fluid may have a color substantially the same visually to the color of one of the four types of charged particles. For example, in a display fluid, there may be charged red, green, blue and white particles and substantially uncharged neutral buoyancy particles, and in this case, the substantially uncharged neutral buoyancy particles may be red, green, blue or white.

In another embodiment, the substantially uncharged neutral buoyancy particles may have a color substantially different from the color of either one of the four types of charged particles.

The presence of the substantially uncharged neutral buoyancy particles in the fluid increases reflection of incident light, thus also improving the contrast ratio, especially if they are formed from a reflective material.

The image stability may also be improved by the addition of the substantially uncharged neutral buoyancy particles in the four particle fluid system. The substantially uncharged neutral buoyancy particles can fill in the gaps resulted from the charged particles being over packed on the surface of an electrode under an electrical field, thus preventing the charged particles from settling due to the gravitational force.

In addition, if the substantially uncharged neutral buoyancy particles are white, they may enhance the reflectivity of the display. If they are black, they may enhance the blackness of the display.

In any case, the substantially uncharged neutral buoyancy particles do not affect the driving behavior of the four types of charged particles in the fluid.

The electrophoretic fluid as described above is filled in display cells. The display cells may be cup-like microcells as described in U.S. Pat. No. 6,930,818, the content of which is incorporated herein by reference in its entirety. The display cells may also be other types of micro-containers, such as microcapsules, microchannels or equivalents, regardless of their shapes or sizes. All of these are within the scope of the present application.

As shown in FIGS. 9A and 9B, the display cells (90), in the present invention, and the pixel electrodes (92A) may be aligned or un-aligned.

The term “about”, throughout this application, is intended to mean $\pm 5\%$ of an indicated value.

While the present invention has been described with reference to the specific embodiments thereof, it should be understood by those skilled in the art that various changes

11

may be made and equivalents may be substituted without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation, materials, compositions, processes, process step or steps, to the objective, spirit and scope of the present invention. All such modifications are intended to be within the scope of the claims appended hereto.

The invention claimed is:

1. An electrophoretic display comprising:
 - (a) a plurality of pixels; and
 - (b) an electrophoretic medium comprising a first type of particle having a first optical characteristic and a positive zeta potential, a second type of particle having a second optical characteristic and a negative zeta potential, a third type of particle having a third optical characteristic and a positive zeta potential lower than that of the first type of particle, and a fourth type of particle having a fourth optical characteristic and a negative zeta potential lower than that of the second type of particle, the first, second, third and fourth optical characteristics being different from one another and none of them being a black color, wherein each of the pixels is capable of displaying the first, second, third and fourth optical characteristics and a black color.
2. The display of claim 1 wherein two of the first, second, third and fourth optical characteristics are white and red.
3. The display of claim 2 wherein the remaining two of the first, second, third and fourth optical characteristics are blue and either green or yellow.
4. The display of claim 1 wherein the zeta potential of the third and fourth types of particles is less than about 75 per cent of the zeta potential of the first and second types of particles respectively.
5. The display of claim 4 wherein the zeta potential of the third and fourth types of particles is less than about 50 per cent of the zeta potential of the first and second types of particles respectively.
6. The display of claim 1 wherein the electrophoretic medium further comprises substantially uncharged neutral buoyancy particles.
7. The electrophoretic display of claim 1 having a viewing surface and wherein:
 - (a) application to the electrophoretic medium of a first electric field having a polarity driving the first type of particle towards the viewing surface will cause the first optical characteristic to be displayed at the viewing surface;
 - (b) application to the electrophoretic medium of a second electric field having a polarity driving the second type of particle towards the viewing surface will cause the second optical characteristic to be displayed at the viewing surface;
 - (c) once the first optical characteristic is displayed at the viewing surface, application to the electrophoretic medium of a third electric field having the same polarity as the second electric field but a smaller magnitude will cause the fourth optical characteristic to be displayed at the viewing surface; and
 - (d) once the second optical characteristic is displayed at the viewing surface, application to the electrophoretic medium of a fourth electric field having the same polarity as the first electric field but a smaller magni-

12

tude will cause the third optical characteristic to be displayed at the viewing surface.

8. The electrophoretic display of claim 7 wherein application of a shaking waveform to the electrophoretic medium will cause a black color to be displayed at the viewing surface.

9. The display of claim 8 wherein the zeta potential of the third and fourth types of particles is less than about 75 per cent of the zeta potential of the first and second types of particles respectively.

10. The display of claim 9 wherein the zeta potential of the third and fourth types of particles is less than about 50 per cent of the zeta potential of the first and second types of particles respectively.

11. A method of driving an electrophoretic medium, the medium having a viewing surface and comprising a first type of particle having a first optical characteristic and a positive zeta potential, a second type of particle having a second optical characteristic and a negative zeta potential, a third type of particle having a third optical characteristic and a positive zeta potential lower than that of the first type of particles, and a fourth type of particle having a fourth optical characteristic and a negative zeta potential lower than that of the second type of particle, the first, second, third and fourth optical characteristics being different from one another and none of them being a black color, the method comprising, in any order:

- (a) applying to the electrophoretic medium a first electric field having a polarity driving the first type of particle towards the viewing surface, thereby causing the first optical characteristic to be displayed at the viewing surface;
- (b) applying to the electrophoretic medium a second electric field having a polarity driving the second type of particle towards the viewing surface, thereby causing the second optical characteristic to be displayed at the viewing surface;
- (c) once the first optical characteristic is displayed at the viewing surface, applying to the electrophoretic medium a third electric field having the same polarity as the second electric field but a smaller magnitude, thereby causing the fourth optical characteristic to be displayed at the viewing surface;
- (d) once the second optical characteristic is displayed at the viewing surface, applying to the electrophoretic medium a fourth electric field having the same polarity as the first electric field but a smaller magnitude, thereby causing the third optical characteristic to be displayed at the viewing surface; and
- (e) applying a shaking waveform to the electrophoretic medium, thereby causing a black color to be displayed at the viewing surface.

12. The method of claim 11 wherein two of the first, second, third and fourth optical characteristics are white and red.

13. The method of claim 12 wherein the remaining two of the first, second, third and fourth optical characteristics are blue and either green or yellow.

14. The method of claim 11 wherein the magnitudes of the third and fourth electric fields are from about 5 to about 50 per cent of the magnitudes of the second and first electric fields respectively.