



US010039608B2

(12) **United States Patent**  
**Yeung**

(10) **Patent No.: US 10,039,608 B2**  
(45) **Date of Patent: Aug. 7, 2018**

(54) **ROBOTIC DEVICES AND SYSTEMS FOR PERFORMING SINGLE INCISION PROCEDURES AND NATURAL ORIFICE TRANSLUMENAL ENDOSCOPIC SURGICAL PROCEDURES, AND METHODS OF CONFIGURING ROBOTIC DEVICES AND SYSTEMS**

(58) **Field of Classification Search**  
CPC ..... A61B 34/37; A61B 34/76; A61B 90/361; A61B 90/50; A61B 2034/305; A61B 2090/3612; A61B 17/3421; A61B 1/3132  
See application file for complete search history.

(71) Applicant: **BIO-MEDICAL ENGINEERING (HK) LIMITED**, Hong Kong SAR (CN)

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
9,060,798 B2 6/2015 Harper et al.  
9,737,372 B2 \* 8/2017 Yeung ..... A61B 34/30  
(Continued)

(72) Inventor: **Chung-Kwong Yeung**, Hong Kong SAR (CN)

**FOREIGN PATENT DOCUMENTS**

(73) Assignee: **BIO-MEDICAL ENGINEERING (HK) LIMITED**, Hong Kong (CN)

AU 2013245548 A1 11/2013  
CN 102100573 A 6/2011  
(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

**OTHER PUBLICATIONS**

(21) Appl. No.: **15/662,921**

International Search Report and Written Opinion, PCT/CN2016/076376, dated May 25, 2016, 10 pages.

(22) Filed: **Jul. 28, 2017**

*Primary Examiner* — Timothy J Neal

(65) **Prior Publication Data**

(74) *Attorney, Agent, or Firm* — Baker & McKenzie, LLP

US 2017/0325902 A1 Nov. 16, 2017

(57) **ABSTRACT**


**Related U.S. Application Data**

Example embodiments relate to surgical devices, systems, and methods. The system may include a first end section and second end section. The first end section includes a first end channel and first gate assembly. The first gate assembly is configurable to transition between an open position to allow access through the first end channel and closed position to prevent access through the first end channel. The second end section includes a second end channel. The second end channel is substantially aligned with the first end channel. The second end section also includes a second gate assembly configurable to transition between an open position to allow access through the second end channel and closed position to prevent access through the second end channel. The second end section also includes an anchor port configurable  
(Continued)

(60) Division of application No. 15/044,889, filed on Feb. 16, 2016, now Pat. No. 9,737,372, which is a (Continued)

(51) **Int. Cl.**  
**A61B 34/30** (2016.01)  
**A61B 34/37** (2016.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **A61B 34/30** (2016.02); **A61B 17/3421** (2013.01); **A61B 34/37** (2016.02);  
(Continued)



to securable to a surgical instrument. The first end section is configurable to secure to an external anchor.

**23 Claims, 25 Drawing Sheets**

**Related U.S. Application Data**

continuation-in-part of application No. 14/693,207, filed on Apr. 22, 2015.

(60) Provisional application No. 61/982,717, filed on Apr. 22, 2014.

- (51) **Int. Cl.**
- A61B 90/00* (2016.01)
- A61B 17/34* (2006.01)
- A61B 34/00* (2016.01)
- A61B 1/00* (2006.01)
- A61B 1/313* (2006.01)
- A61B 17/00* (2006.01)
- A61B 90/30* (2016.01)
- A61B 90/50* (2016.01)

- (52) **U.S. Cl.**
- CPC ..... *A61B 34/76* (2016.02); *A61B 90/361* (2016.02); *A61B 1/00087* (2013.01); *A61B 1/3132* (2013.01); *A61B 90/50* (2016.02); *A61B 2017/00283* (2013.01); *A61B 2017/345* (2013.01); *A61B 2017/3445* (2013.01); *A61B 2034/305* (2016.02); *A61B 2090/309* (2016.02); *A61B 2090/3612* (2016.02); *Y10S 901/02* (2013.01); *Y10S 901/27* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 2007/0175961 A1 8/2007 Shelton, IV et al.
- 2010/0036198 A1 2/2010 Tacchino et al.
- 2011/0118736 A1 5/2011 Harper et al.
- 2015/0282875 A1 10/2015 Harper et al.

FOREIGN PATENT DOCUMENTS

- CN 101400293 B 7/2011
- CN 201968771 U 9/2011
- CN 102614006 A 8/2012
- CN 202505440 U 10/2012
- CN 203290975 U 11/2013

\* cited by examiner




FIG. 1A




FIG. 1B





FIG. 2A






FIG. 3A




FIG. 3B






FIG. 4A




FIG. 4B




FIG. 4C








FIG. 4D








FIG. 6C




FIG. 6D





FIG. 7








FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 8G





FIG. 8H






FIG. 8J




FIG. 8K




FIG. 9A








FIG. 9B





1

**ROBOTIC DEVICES AND SYSTEMS FOR  
PERFORMING SINGLE INCISION  
PROCEDURES AND NATURAL ORIFICE  
TRANSLUMENAL ENDOSCOPIC SURGICAL  
PROCEDURES, AND METHODS OF  
CONFIGURING ROBOTIC DEVICES AND  
SYSTEMS**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a divisional application of U.S. application Ser. No. 15/044,889 (filed on Feb. 16, 2016, which is a continuation-in-part of U.S. application Ser. No. 14/693,207, filed on Apr. 22, 2015, which claims priority to U.S. Provisional Application No. 61/982,717, filed on Apr. 22, 2014), the contents of all of which are hereby expressly incorporated by reference in their entirety, including the contents and teachings of any references contained therein.

BACKGROUND

The present disclosure relates generally to systems, devices, and methods, and more specifically, relates to systems, devices, and methods for use in performing procedures via a single incision or a natural orifice.

Conventional surgical procedures will generally require one or more large incisions to a patient in order for the surgical team to perform a surgical action. With the advancement of medical science and technology, most conventional open surgical procedures have been largely replaced with minimally invasive surgery (MIS) procedures. Recent developments in respect to computer-assisted and/or robotic surgical technology have contributed to advancements in MIS, including the ability to translate a surgeon's desired actions into movements of robotic instruments inside the body cavity of a patient.

BRIEF SUMMARY

Despite recent developments in modern medical science and technology, it is recognized in the present disclosure that one or more problems are encountered in modern surgical technology and methodology. For example, a typical MIS procedure requires multiple incisions to a patient in order to allow access via the incisions for the insertion of a camera and various other laparoscopic instruments into the body cavity of the patient.

As another example, surgical robotic devices oftentimes encounter difficulties during surgical procedures due to insufficient anchoring and/or reactive forces to stabilize against forces that are desired and/or necessary to be applied during surgical actions.

It is also recognized in the present disclosure that surgical robotic systems face difficulties in providing an instrument, such as a cutting or gripping instrument attached to the end of a surgical robotic arm, with access to all or even most parts, areas, and/or quadrants of abdominal cavity of a patient. That is, after the surgical robotic arm is inserted in the abdominal cavity of the patient and ready to perform a surgical action, the instrument attached to the end of the surgical robotic arm is typically limited to access only certain parts, areas, and quadrants of the abdominal cavity of the patient.

In yet another example, known surgical robotic systems typically provide only between one to two surgical robotic arms per access or opening (such as an incision or a natural

2

orifice) of the patient. In this regard, one or more additional incisions will be required for the insertion of a camera and various laparoscopic instruments into the abdominal cavity of the patient.

As another example, while known surgical robotic systems have been designed for use in an abdominal cavity of a patient to perform forward-directed surgical procedures, such systems have not been designed for and may encounter problems when applied in situations requiring reverse-directed surgical procedures. For example, such known surgical robotic systems have not been designed for deployment through a natural orifice, such as a rectum or vagina, for performing natural orifice transluminal endoscopic surgery (or NOTES), such as pelvic gynecological and/or urological procedures. Such systems may encounter one or more problems, such as the inability to access certain organs, tissues, or other surgical sites upon insertion into the natural orifice.

Present example embodiments relate generally to systems, devices, and methods for addressing one or more problems in surgical robotic systems, devices, and methods, including those described above and herein.

In an exemplary embodiment, a port assembly is described in the present disclosure. The port assembly includes a first end section and second end section. The first end section may include a first end channel and a first gate assembly. The first gate assembly may be configurable to transition between an open position to allow access through the first end channel and a closed position to prevent access through the first end channel. The second end section may include a second end channel, a second gate assembly, and an anchor port. The second end channel may be substantially aligned with the first end channel. The second gate assembly may be configurable to transition between an open position to allow access through the second end channel and a closed position to prevent access through the second end channel. The anchor port may be configurable to be securable to a surgical instrument. The first end section may be configurable to secure to an external anchor.

In another exemplary embodiment, a port assembly is described. The port assembly may include a main body. The main body may be a hollow elongated body. The main body may have a center channel formed through the elongated body. The main body may include a first gate assembly and a second gate assembly. The first gate assembly may be provided in the center channel at a first end of the main body. The first gate assembly may be configurable to transition between an open position to allow access through the first gate assembly and a closed position to prevent access through the first gate assembly. The second gate assembly may be provided in the center channel at a second end of the main body. The second end of the main body may be opposite to the first end of the main body. The second gate assembly may be configurable to transition between an open position to allow access through the second gate assembly and a closed position to prevent access through the second gate assembly.

In another exemplary embodiment, a port assembly is described. The port assembly may include a main body. The main body may be an elongated body having a first end and a second end opposite to the first end. The main body may include a center channel formed throughout the elongated body between the first end and second end. The main body may include a gate assembly provided in the center channel. The gate assembly may be configurable to transition between an open position to allow access through the gate assembly and a closed position to prevent access through the

gate assembly. The gate assembly may include an expandable portion. The expandable portion may be configurable to expand when the gate assembly is configured to the closed position.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present disclosure, example embodiments, and their advantages, reference is now made to the following description taken in conjunction with the accompanying drawings, in which like reference numbers indicate like features, and:

FIG. 1A is illustration of a perspective view of an example embodiment of an external anchor;

FIG. 1B is another illustration of a perspective view of an example embodiment of an external anchor attached to an example embodiment of a port assembly;

FIG. 2A is an illustration of a perspective view of an example embodiment of a surgical device configured in a reverse-directed position with one port assembly, one instrument arm assembly, and one image capturing assembly;

FIG. 2B is an illustration of a perspective view of an example embodiment of a surgical device configured in a forward-directed position with one port assembly, one instrument arm assembly, and one image capturing assembly;

FIG. 3A is another illustration of a perspective view of another example embodiment of a surgical device configured in a reverse-directed position with one port assembly, one instrument arm assembly, and one image capturing assembly;

FIG. 3B is another illustration of a perspective view of another example embodiment of a surgical device configured in a forward-directed position with one port assembly, one instrument arm assembly, and one image capturing assembly;

FIG. 4A is an illustration of a perspective exploded view of an example embodiment of a port assembly;

FIG. 4B is an illustration of a side view of an example embodiment of a port assembly;

FIG. 4C is an illustration of a cross-sectional view of an example embodiment of a port assembly with a first or second gate assembly in the open position;

FIG. 4D is an illustration of a cross-sectional view of an example embodiment of a port assembly with a first or second gate assembly in the closed position;

FIG. 5A is an illustration of a side view of an example embodiment of an instrument arm assembly;

FIG. 5B is another illustration of a side view of an example embodiment of an instrument arm assembly;

FIG. 6A is an illustration of a perspective view of an example embodiment of an image capturing assembly;

FIG. 6B is an illustration of a cross sectional view of another example embodiment of an image capturing assembly having an internal temperature control assembly;

FIG. 6C is an illustration of perspective views of another example embodiment of an image capturing assembly having internal temperature control assemblies;

FIG. 6D is an illustration of a perspective view of the system in operation in a cavity of a patient, including a second image capturing assembly;

FIG. 7 is a flow diagram of an exemplary method for configuring a surgical device;

FIGS. 8A-E are illustrations of a side view of an example embodiment of a method of configuring a surgical device in a forward-directed position;

FIGS. 8F-K are illustrations of a side view of an example embodiment of a method of configuring a surgical device in a reverse-directed position;

FIG. 9A is an illustration of a perspective view of an example embodiment of a surgical device system;

FIG. 9B is an illustration of a perspective view of another example embodiment of a surgical device system;

FIG. 10A is an illustration of a perspective view of an example embodiment of an external anchor; and

FIG. 10B is an illustration of a perspective view of another example embodiment of an external anchor.

Although similar reference numbers may be used to refer to similar elements in the figures for convenience, it can be appreciated that each of the various example embodiments may be considered to be distinct variations.

#### DETAILED DESCRIPTION

Example embodiments will now be described with reference to the accompanying drawings, which form a part of the present disclosure, and which illustrate example embodiments which may be practiced. As used in the present disclosure and the appended claims, the terms “example embodiment,” “exemplary embodiment,” and “present embodiment” do not necessarily refer to a single embodiment, although they may, and various example embodiments may be readily combined and/or interchanged without departing from the scope or spirit of example embodiments. Furthermore, the terminology as used in the present disclosure and the appended claims is for the purpose of describing example embodiments only and is not intended to be limitations. In this respect, as used in the present disclosure and the appended claims, the term “in” may include “in” and “on,” and the terms “a,” “an” and “the” may include singular and plural references. Furthermore, as used in the present disclosure and the appended claims, the term “by” may also mean “from,” depending on the context. Furthermore, as used in the present disclosure and the appended claims, the term “if” may also mean “when” or “upon,” depending on the context. Furthermore, as used in the present disclosure and the appended claims, the words “and/or” may refer to and encompass any and all possible combinations of one or more of the associated listed items.

It is recognized in the present disclosure that, despite recent developments in medical science and technology, one or more problems are encountered in modern surgical technology and methodology, including MIS. For example, a typical MIS procedure requires multiple incisions to a patient in order to allow access via the incisions for the insertion of a camera and various other laparoscopic instruments into the body cavity of the patient.

In addition to the aforementioned disadvantages pertaining to the multiple and rather large incisions, it is recognized in the present disclosure that surgical robotic systems, including surgical robotic arms (and those instruments attached to them), developed for performing robotic-assisted MIS surgical procedures also suffer from one or more problems. For example, it is recognized herein that a major technical challenge for a surgical robotic system is the difficulty in providing sufficient anchoring and/or reactive forces to stabilize against forces that are desired and/or necessary to be applied to the patient by the surgical robotic system during a surgical action. In this regard, certain surgical actions for known surgical robotic systems may require tremendous effort and time, and may not be performed properly or at all as a result of the problem of insufficient anchoring and/or reactive forces.

Another example of a problem recognized in the present disclosure as being encountered by surgical robotic systems is the difficulty in providing an instrument, such as a cutting and/or gripping instrument attached to the end of a surgical robotic arm, with access to all or even most parts, areas, and quadrants of an abdominal cavity of a patient after the surgical robotic system has been set up (or installed) and is ready to perform a surgery. That is, after the surgical robotic arm of the system has been inserted, attached, and properly set up in the abdominal cavity of the patient and is ready to perform a surgical action, the instrument attached to the end of the surgical robotic arm is typically limited to access only certain parts, areas, and quadrants of the abdominal cavity of the patient. It is recognized in the present disclosure that such problems result in large from the limited number of possible degrees of freedom that can be provided by known surgical robotic systems and arms, and more specifically, the limited number of in vivo degrees of freedom (i.e. the degrees of freedom provided within an abdominal cavity of a patient) of known surgical robotic systems and arms. In this regard, surgical robotic systems typically provide only between 2 to 4 in vivo degrees of freedom for each surgical robotic arm.

As another example, while known surgical robotic systems have been designed for use in an abdominal cavity of a patient to perform forward-directed surgical procedures, such systems have not been designed for and may encounter problems when applied in situations requiring reverse-directed surgical procedures. For example, such known surgical robotic systems have not been designed for deployment through a natural orifice, such as a rectum or vagina, for performing natural orifice transluminal endoscopic surgery (or NOTES), such as trans-vaginal gynecological procedures in women and trans-rectal urological procedures in men. Such systems may encounter one or more problems, such as the inability to access certain organs, tissues, or other surgical sites upon insertion into the natural orifice.

Surgical systems, devices, and methods, including those for use in MIS and natural orifice transluminal endoscopic surgery (or NOTES), are described in the present disclosure for addressing one or more problems of known surgical systems, devices, and methods, including those described above and in the present disclosure. It is to be understood that the principles described in the present disclosure can be applied outside of the context of MIS and/or NOTES, such as performing scientific experiments and/or procedures in environments that are not readily accessible by humans, including in a vacuum, in outer space, and/or under toxic and/or dangerous conditions, without departing from the teachings of the present disclosure.

The Surgical System (e.g., Surgical Device **200**)

An illustration of an example embodiment of a surgical device or system (e.g., surgical device or system **200**) operable to be inserted into an abdominal cavity of a patient through a single access or opening (e.g., a single incision (such as an incision in or around the umbilical area) or through a natural orifice (such as a rectum or vagina, for performing natural orifice transluminal endoscopic surgery (or NOTES), hereinafter referred to as an “opening”) of the patient is depicted in FIG. 2A and FIG. 2B. The surgical device may then be anchored so as to position the surgical device **200** in the opening. The surgical device **200** may comprise a port assembly **210** and an instrument arm assembly **230**. The surgical device **200** may also comprise other elements, such as one or more other instrument arm assemblies, one or more image capturing assemblies, one or more assistant arm assemblies, etc.

As illustrated in FIG. 1A and FIG. 1B, the surgical device **200** may be provided with an external anchor **1** attachable to the port assembly **210**. The external anchor **1** may comprise a configurable assembly of segments **2**, **6**, **10**, and **14** in communication with one another via joints or connecting portions **4**, **8**, and **12**, and external anchor connector **16**. The external anchor **1** may be operable to securely fix the position and/or orientation (hereinafter “position”) of the port assembly **210** in or about the single opening of the patient, and may also be operable to provide sufficient anchoring and/or reactive forces to stabilize against forces desired and/or necessary to be applied by at least one or more elements of the surgical device **200**, including the instrument arm assembly **230**, during a surgical action or procedure. The external anchor **1**, which may also be in the form of the controllable swivel assembly **1000** illustrated in FIG. 10A and FIG. 10B, may be operable to cooperate with the port assembly **210** to provide one or more in vitro degrees of freedom. For example, the external anchor **1** may be configurable to provide 3 in vitro degrees of freedom. In example embodiments, the one or more in vitro degrees of freedom may include a torsional movement, pivotal movement, telescopic movement, and/or other movements of the port assembly **210** relative to the external anchor **1**. For example, a torsional movement of the port assembly **210**, as illustrated by arrow A in FIG. 1B, may allow one or more attached instruments, including an instrument arm assembly **230**, to re-position during a surgical procedure (i.e. after set up or installation) so as to access other parts, areas, and/or all quadrants of the abdominal cavity of the patient. As another example, a pivotal movement of the port assembly **210**, as illustrated by arrow B in FIG. 1B, may allow the port assembly **210** to be positioned in one of a plurality of angles with respect to opening of the patient, and may also allow attached instruments, including the instrument arm assembly **230**, to re-position during a surgical procedure (i.e. after set up or installation) so as to access distal areas of the abdominal cavity of the patient. The other joint portions of the external anchor **1** may also be operable to cooperate and/or assist in desired movements of the port assembly **210**. The external anchor **1** may be anchored to one or more stationary or fixedly positioned objects, such as a side rail **300** of a surgical table/bed illustrated in FIG. 1A. FIGS. 10A and 10B illustrate other example movements that provide for additional in vitro degrees of freedom via an example embodiment of the external anchor (controllable swivel assembly) **1000**. The controllable swivel assembly **1000** will be further described below in at least the section “(1) Providing the external anchor and installing the port assembly.”

The surgical device **200** may further comprise one or more additional instrument arm assemblies, such as a second instrument arm assembly **240** illustrated in FIGS. 3A and 3B, attachable to the port assembly **210**. One or more of the instrument arm assemblies, including the first instrument arm assembly **230**, the second instrument arm assembly **240**, a third instrument arm assembly (not shown), a fourth instrument arm assembly (not shown), etc., may be attachable or securable to the port assembly **210**. Such instrument arm assemblies may be operable to access and perform one or more surgical actions in/on any and all parts, areas, and/or quadrants within a cavity of the patient. For example, surgical device **200** may be configurable to perform surgical actions in a forward direction (or “forward-directed position” or “forward position”) (e.g., as illustrated in FIGS. 2B and 3B). As another example, surgical device **200** may be configurable to perform surgical actions in a reverse direc-

tion (or “reverse-directed position” or “reverse position”) (e.g., as illustrated in FIGS. 2A and 3A).

The surgical device 200 may also comprise one or more image capturing assemblies, such as image capturing assembly 220. The surgical device 200 may further comprise one or more assistant arm assemblies, such as a retractor arm assembly 250, as illustrated in FIGS. 2A, 2B, 3A, and 3B. Furthermore, the surgical device 200 may comprise one or more other instrument arm assemblies, such as suction/irrigation assembly 260, illustrated in FIGS. 2A, 2B, 3A, and 3B, that can be inserted into the opening of the patient via the port assembly 210 before, during, and/or after performing a surgical action or procedure. It is to be understood in the present disclosure that the surgical device 200 may be configurable in a plurality of configurations and arrangements, including having more or less than two instrument arm assemblies (such as third, fourth, fifth, etc. instrument arm assemblies), more than one image capturing assembly (such as second, third, etc. image capturing assemblies), more or less than one assistant arm assembly (such as second, third, etc. assistant arm assemblies), and/or more or less than one other laparoscopic tool in example embodiments without departing from the teachings of the present disclosure.

The Port Assembly (E.G., Port Assembly 210)

An example embodiment of the port assembly (e.g., port assembly 210) is illustrated in FIGS. 2A, 2B, 3A, 3B, FIG. 4A, FIG. 4B, FIG. 4C, and FIG. 4D. The port assembly 210 may be configurable to be inserted in or about a single opening of the patient (such as a single incision or a natural orifice) and fixed in position by at least the external anchor (such as the external anchor 1 illustrated in FIGS. 1A and 1B and the controllable swivel assembly 1000 illustrated in FIGS. 10A and 10B).

The port assembly 210 may be an elongated structure having a central access channel 210a formed through the port assembly 210. The central access channel 210a may be for use in inserting and removing instruments, such as one or more instrument arm assemblies 230, 240, one or more image capturing assemblies 220, one or more assistant arm assemblies 250, 260, etc. In an example embodiment, the port assembly 210 may include a first end section 212 and a second end section 214. The first end section 212 and second end section 214 may be fixably attachable to one another or formed as a unitary article. The port assembly 210 may also include a mid section 213 between the first end section 212 and the second end section 214. The first end section 212, second end section 214, and mid section 213 may be fixably attachable to one another, as illustrated in FIGS. 4A and 4B, or two or more of these sections may be formed as a unitary article. In an example embodiment, the first end section 212 may be the portion of the port assembly 210 that is secured to the external anchor 1, and the port assembly 210 may be fixed in position at an angle  $\theta$  relative to the single opening of the patient of between about 0 to  $\pm 90$  degrees. These and other elements of the port assembly 210 will now be described below and with reference to FIGS. 2A, 2B, 3A, 3B, and 4A-D.

As illustrated in at least FIGS. 4A and 4B, the port assembly 210 may comprise a first end section 212. The first end section 212 may have a first end channel 212a formed through the first end section 212. The first end channel 212a may be considered as a part of the central access channel 210a. The first end section 212 may also include a portion operable to be secured to the external anchor 1, such as a portion on an exterior portion of the first end section 212.

The first end section 212 may also include a first gate assembly 212b, as illustrated in FIGS. 4A, 4C, and 4D. The first gate assembly 212 may be configurable to control access through the first end channel 212a. For example, the first gate assembly 212b may be configurable to be in an open position, as illustrated in FIG. 4C, so as to allow access through the first end channel 212a. The first gate assembly 212b may also be configurable to be in a closed position, as illustrated in FIG. 4D, so as to prevent or restrict access through the first end channel 212a. The first gate assembly 212b may also be configurable to be in a partially closed (or partially opened) position (not shown). The first gate assembly 212b may also be configurable to transition between the closed position and the open position.

In an example embodiment, the first gate assembly 212b may be provided within the first end section 212 in such a way that, when the first gate assembly 212b is configured to be in the open position, as illustrated in FIG. 4C, the first end channel 212a is substantially or completely unobstructed by the first gate assembly 212b. The first gate assembly 212b may be configured to be in the open position when a surgeon desires to insert (or remove) an instrument into (or out of) the cavity of the patient via the first end channel 212a (and the rest of the central access channel 210a).

Similarly, the first gate assembly 212b may be provided within the first end section 212 in such a way that, when the first gate assembly 212b is configured to be in the closed position, as illustrated in FIG. 4D, the first end channel 212a is substantially or completely obstructed by the first gate assembly 212b. The first gate assembly 212b may be configured to be in the closed position when a surgeon desires to maintain an insufflation of the cavity of the patient and/or when the surgeon does not need to insert (or remove) an instrument into (or out of) the cavity of the patient via the first end channel 212a.

The first gate assembly 212b may include a first expandable portion 212b configurable to expand when the first gate assembly 212b is configured to the closed position, as illustrated in FIG. 4D. When the first gate assembly 212b is configured to the closed position, the first expandable portion 212b may be operable to substantially or completely block, among other things, a gas medium (and/or other medium) from passing through the first end channel 212a. For example, if the cavity of the patient is being insufflated using a gas, such as carbon dioxide ( $\text{CO}_2$ ), the first gate assembly 212b (i.e., the first expandable portion 212b) may be configurable to substantially prevent the carbon dioxide gas from leaving the cavity of the patient through the first end channel 212a.

The first expandable portion 212b may include one or more first expandable members. For example, the first expandable portion 212b may include six expandable members, as illustrated in FIGS. 4C and 4D. It is to be understood that the first expandable portion 212b may include more or less than six expandable members without departing from the teachings of the present disclosure. Some or all of the first expandable members may be integrated together and/or in communication with one another, such as in a manner where some or all of the first expandable members are operable to receive pressure (i.e., gas medium) from a common or same first source 212b'. For example, when the first gate assembly 212b is configured to the closed position, the first source 212b' may be configurable to provide a positive pressure (i.e., a supply of gas) so as to cause some or all of the first expandable members to expand and block the first end channel 212a (e.g., hermetically block the first end channel 212a). Similarly, when the first gate assembly

**212b** is configured to the open position, the first source **212b'** may be configurable to provide a negative pressure (i.e., remove gas) so as to cause one or more (or all) of the first expandable members to not expand (and/or contract) and unblock the first end channel **212a**. It is to be understood that more than one first sources **212b'** may provide the positive pressure and negative pressure to the one or more expandable members without departing from the teachings of the present disclosure.

It is recognized in the present disclosure that the first gate assembly **212b** may also include a valve (not shown), or the like, in addition to or in replacement of the first expandable portion **212b**. The valve may be configurable to perform substantially the same actions of blocking the first end channel **212a** when the first gate assembly **212b** is configured to the closed position and unblocking the first end channel **212a** when the first gate assembly **212b** is configured to the open position. The valve may be any type of valve configurable to perform the actions described above and in the present disclosure. The valve may include, but is not limited to including, a ball valve, gate valve, etc., so long as the valve is configurable to substantially block/unblock the first end channel **212a** and prevent a gas medium from passing through the first end channel **212a**.

The port assembly **210** may also include the second end section **214**, as illustrated in at least FIGS. **4A** and **4B**. The second end section **214** may have a second end channel **214a** formed through the second end section **214**. The second end channel **214a** may be substantially or completely aligned with the first end channel **212a**. The second end channel **214a**, as well as the first end channel **212a**, may be considered as a part of the central access channel **210a** in example embodiments. The second end section **214** may also include an insufflation port (not shown) for use in providing insufflation to the cavity of the patient.

The second end section **214** may also include a second gate assembly **214b**, as illustrated in FIGS. **4A**, **4C**, and **4D**. The second gate assembly **214b** may be configurable to control access through the second end channel **214a**. For example, the second gate assembly **214b** may be configurable to be in an open position, as illustrated in FIG. **4C**, so as to allow access through the second end channel **214a**. The second gate assembly **214b** may also be configurable to be in a closed position, as illustrated in FIG. **4D**, so as to prevent or restrict access through the second end channel **214a**. The second gate assembly **214b** may also be configurable to be in a partially closed (or partially opened) position (not shown). The second gate assembly **214b** may also be configurable to transition between the closed position and the open position.

In an example embodiment, the second gate assembly **214b** may be provided within the second end section **212** in such a way that, when the second gate assembly **214b** is configured to be in the open position, as illustrated in FIG. **4C**, the second end channel **214a** is substantially or completely unobstructed by the second gate assembly **214b**. The second gate assembly **214b** may be configured to be in the open position when a surgeon desires to insert (or remove) an instrument into (or out of) the cavity of the patient via the second end channel **214a** (and the rest of the central access channel **210a**).

Similarly, the second gate assembly **214b** may be provided within the second end section **214** in such a way that, when the second gate assembly **214b** is configured to be in the closed position, as illustrated in FIG. **4D**, the second end channel **214a** is substantially or completely obstructed by the second gate assembly **214b**. The second gate assembly

**214b** may be configured to be in the closed position when a surgeon desires to maintain an insufflation of the cavity of the patient and/or when the surgeon does not need to insert (or remove) an instrument into (or out of) the cavity of the patient via the second end channel **214a**.

The second gate assembly **214b** may include a second expandable portion **214b** configurable to expand when the second gate assembly **214b** is configured to the closed position, as illustrated in FIG. **4D**. When the second gate assembly **214b** is configured to the closed position, the second expandable portion **214b** may be operable to substantially or completely block, among other things, a gas medium (and/or other medium) from passing through the second end channel **214a**. For example, if the cavity of the patient is being insufflated using a gas, such as carbon dioxide (CO<sub>2</sub>), the second gate assembly **214b** (i.e., the second expandable portion **214b**) may be configurable to substantially prevent the carbon dioxide gas from leaving the cavity of the patient through the second end channel **214a**.

The second expandable portion **214b** may include one or more second expandable members. For example, the second expandable portion may include six expandable members, as illustrated in FIGS. **4C** and **4D**. It is to be understood that the second expandable portion **214b** may include more or less than six expandable members without departing from the teachings of the present disclosure. Some or all of the second expandable members may be integrated together and/or in communication with one another, such as in a manner where some or all of the second expandable members are operable to receive pressure (i.e., gas medium) from a common or same second source **214b'**. For example, when the second gate assembly **214b** is configured to the closed position, the second source **214b'** may be configurable to provide a positive pressure (i.e., a supply of gas) so as to cause some or all of the second expandable members to expand and block the second end channel **214a** (e.g., hermetically block the second end channel **214a**). Similarly, when the second gate assembly **214b** is configured to the open position, the second source **214b'** may be configurable to provide a negative pressure (i.e., remove gas) so as to cause some or all of the second expandable members to not expand (and/or contract) and unblock the second end channel **214a**. It is to be understood that more than one second sources **214b'** may provide the positive pressure and negative pressure to the one or more expandable members without departing from the teachings of the present disclosure. It is also to be understood in the present disclosure that one or more of the first sources **212b'** and one or more of the second sources **214b'** may be the same or different sources.

It is recognized in the present disclosure that the second gate assembly **214b** may also include a valve (not shown), or the like, in addition to or in replacement of the second expandable portion **214b**. The valve may be configurable to perform substantially the same actions of blocking the second end channel **214a** when the second gate assembly **214b** is configured to the closed position and unblocking the second end channel **214a** when the second gate assembly **214b** is configured to the open position. The valve may be any type of valve configurable to perform the actions described above and in the present disclosure. The valve may include, but is not limited to including, a ball valve, gate valve, etc., so long as the valve is configurable to substantially block/unblock the second end channel **214a** and prevent a gas medium from passing through the second end channel **214a**.



The second end section **214** may also include one or more anchor ports **216**, as illustrated in FIGS. **4A** and **4B**. Each of the anchor ports **216** may be operable to enable an instrument arm assembly **230** or **240**, image capturing assembly **220**, and/or assistant arm assemblies **250** or **260** to be secured to and unsecured from the port assembly **210**. Each of the anchor ports **216** may be formed in any one or more of a plurality of shapes, holes, slots, indentations, protrusions, hooks, fasteners, magnets, buckles, or the like, including those described above and in the present disclosure. For example, as illustrated in FIGS. **4A** and **4B**, one or more of the anchor ports **216** may include one or more slots, or the like, operable to allow a shoulder section **231** of an instrument arm assembly **230** or **240** to be inserted into and attached.

In example embodiments, the port assembly **210** may also include the mid section **213**, as illustrated in at least FIGS. **4A** and **4B**. The mid section **213** may have a mid section channel **213a** formed through the mid section **213**. The mid section channel **213a** may be substantially or completely aligned with the first end channel **212a** and/or the second end channel **214a**. In this regard, the mid section channel **213a**, as well as the first end channel **212a** and/or the second end channel **214a**, may be considered as a part of the central access channel **210a** in example embodiments. The mid section **213** may also include an insufflation port (not shown) in addition to or in replacement of the insufflation port (not shown) of the second end section **214**. In some example embodiments, the mid section **213** may also include a mid section gate assembly (not shown) similar to that of the first gate assembly **212** and second gate assembly **214** described above and in the present disclosure.

In example embodiments, the mid section channel **213a** may be operable to cooperate with the first gate assembly **212b** and the second gate assembly **214b** to function as or like an isolation chamber for instruments, such as the instrument arm assembly **230** or **240**, image capturing assembly **220**, assistant arm assembly **250** or **260**, etc. For example, when an instrument, such as the instrument arm assembly **230**, needs to be inserted into the cavity of the patient via the port assembly **210** (or central access channel **210a**) and an insufflation of the cavity of the patient needs to be maintained, the first gate assembly **212b** may be configured to the open position to allow the instrument to be inserted into the mid section channel **213a**. After the instrument (or most of it) passes through the first gate assembly **212b**, the first gate assembly **212b** may be configured to the closed position. The second gate assembly **214b** may then be configured to the open position to allow the instrument to be further inserted through the port assembly **210**. After the instrument (or most of it) passes through the second gate assembly **214b**, the second gate assembly **214b** may be configured to the closed position.

In respect to the central access channel **210a**, the central access channel **210a** may include or be formed by the first end channel **212a**, the second end channel **214a**, and/or the mid section channel **213a**. The central access channel **210a** may be operable to provide an access port (i.e. a passageway or channel) to allow an insertion (or removal) of one or more instruments, such as one or more instrument arm assemblies **230** or **240**, one or more image capturing assemblies **220**, one or more assistant arm assemblies **250** or **260**, etc.

In an example embodiment, the first end section **212**, the second end **214**, and/or the mid section **213** may be substantially cylindrical in shape. The first end section **212**, the second end section **214**, and/or the mid section **213** may also

be formed in any one of a plurality of other shapes, sizes, and/or dimensions without departing from the teachings of the present disclosure.

In example embodiments, an outer diameter of the first end section **212**, the second end **214**, and/or the mid section **213** may be between about 28 to 35 mm and an inner diameter (unblocked) of the first end section **212**, the second end **214**, and/or the mid section **213** may be between about 16 to 21 mm. In an example embodiment, the outer diameter of the first end section **212**, the second end **214**, and/or the mid section **213** may be about 33 mm and the inner diameter (unblocked) of the first end section **212**, the second end **214**, and/or the mid section **213** may be about 19 mm. The length of the first end section **212** may be between about 80 to 100 mm, the length of the second end section **214** may be between about 80 to 200 mm, and the length of the mid section **213** may be between about 60 to 80 mm. The overall length of the port assembly **210** may be between about 320 to 380 mm. It is to be understood in the present disclosure that the above dimensions are merely an illustration of example embodiments, and as such the dimensions may be smaller or larger than those recited above without departing from the teachings of the present disclosure.

The port assembly **210**, including the first end section **212**, the second end section **214**, the mid section **213**, and/or the anchor ports **216**, may be formed using any one or more of a plurality of materials, such as surgical-grade metals, high-strength aluminum alloys, stainless steel (such as 304/304L, 316/316L, and 420), pure titanium, titanium alloys (such as Ti6Al4V, NiTi), and cobalt-chromium alloys. The first gate assembly **212b** and the second gate assembly **214b** may be formed using any one or more of a plurality of materials, such as bio-compatible materials (such as silicone rubber and polyurethane). It is to be understood in the present disclosure that other materials may also be used without departing from the teachings of the present disclosure. It is to be understood in the present disclosure that the above materials are merely an illustration of example embodiments, and these and other materials and compositions may be used without departing from the teachings of the present disclosure.

The Image Capturing Assembly (E.G., Image Capturing Assembly **220**)

In an example embodiment, the surgical device **200** may comprise one or more image capturing assemblies (e.g., image capturing assembly **220**) configurable to be inserted into and attach to the port assembly **210**. One or more of the image capturing assemblies **220** may comprise an image capturing body **224**, a multi-curved body **222**, and an anchoring portion **220a**.

As illustrated in FIG. **6A**, the image capturing body **224** may include one or more cameras **227**. Each camera **227** may include a standard and/or high definition 2-dimensional (2D) and/or 3-dimensional (3D) camera operable to capture imaging, such as 2D and/or stereoscopic and/or autostereoscopic 3D imaging, including images, video, and/or audio, and provide in real-time via wired and/or wireless communication the captured imaging, including images, video, and/or audio, to the computing device (or controller or system) of one or more nearby and/or remotely located surgical teams **904**, as described above and in the present disclosure. The computing device (or controller or system) may comprise one or more processors, one or more computer-human interfaces, one or more graphical displays (such as computer screens, television screens, portable devices, wearable devices such as glasses, etc.), and/or other devices and/or systems, an example of which is illustrated in

FIGS. 9A and 9B. The one or more nearby and/or remotely located surgical teams 904 may be operable to view, hear, sense, analyze, and control (such as pan, zoom, process, adapt, mark, change resolution, etc.) the imaging displayed or represented on one or more standard and/or high definition 2D and/or 3D graphical displays 902, such as shown in the illustration of FIGS. 9A and 9B, and/or portable and/or wearable devices adapted to receive 2D and/or 3D imaging (not shown). The image capturing body 224 may also comprise one or more illumination sources 229, such as an LED, or the like, operable to illuminate or sense at least one or more parts, sections, and/or quadrants of the cavity of the patient, including instruments provided in the cavity of the patient. The image capturing body 224 may further comprise one or more internal temperature control assemblies operable to control (such as reduce) the temperature of one or more components of the image capturing body 224.

As illustrated in the example embodiment of FIG. 6A, one or more of the image capturing assemblies 220 may comprise a multi-curvable body 222 attached to the image capturing body 224. The multi-curvable body 222 may be any elongated multi-curvable, multi-bendable, multi-articulate, and/or snake-like (hereinafter “multi-curvable”) body that can be controlled/configured by the surgical team (such as via the computing device/controller) to, among other things, straighten and/or curve (and hold such a straightness and/or curvature) at one or more of a plurality of locations along the multi-curvable body 222, curve (and hold such a curvature) in one or more of a plurality of curvatures, and/or straighten and/or curve (and hold such a straightness and/or curvature) in one or more of a plurality of directions. For example, as illustrated in FIG. 8H, the multi-curvable body 222 may be controllable/configurable by the surgical team (such as via the computing device/controller) to curve at two different locations 222a and 222b along the multi-curvable body 222, and each of the curves may include any curvature and in any direction. It is to be understood that the multi-curvable body 222 may be configurable to curve in more or less than two locations along the multi-curvable body 222 without departing from the teachings of the present disclosure. It is also to be understood that, when the multi-curvable body 222 is configured to curve at any location along the multi-curvable body 222, the curve may be held and/or released (or configured to uncurve, curve less, or straighten) by the surgical team (such as via the computing device/controller).

The multi-curvable body 222 may be formed in any one or more ways known in the art including. For example, the multi-curvable body 222 may include a plurality of segments, each segment linked to an adjacent segment in such a way that the segment may be controlled/configured to be pivotally positioned in a plurality of positions relative to the adjacent segment. As another example, the multi-curvable body 222 may include a plurality of wires, cables, or the like, distributed throughout the multi-curvable body 222 in such a way that a pulling/releasing, shortening/lengthening, tightening/loosening, etc. of one or a combination of cables enables the above-mentioned curving of one or more locations of the multi-curvable body 222 in one or more curvatures and in one or more directions. As another example, the multi-curvable body 222 may include a plurality of springs, gears, motors, etc. for achieving the above-mentioned curving. It is to be understood in the present disclosure that the multi-curvable body 222 may also include a combination of one or more of the above-mentioned approaches.

One or more internal temperature control assemblies (not shown) may be provided for each image capturing assembly

220. Each internal temperature control assembly may be operable to control (such as reduce) the temperature and/or heat emission of the aforementioned camera(s) 227, illumination source(s) 229, and/or multi-curvable body 222. In an example embodiment, the one or more internal temperature control assemblies may be operable to perform such temperature control using one or more gases, liquids, and/or solids. For example, the gases and/or liquids may be fed, maintained, and/or regulated using an external source via one or more tubes, or the like. The one or more tubes used to provide, regulate, and/or discharge the gases and/or liquids may have a diameter between about 0.5 mm to 3 mm in example embodiments, but the dimensions of such tubes may also be more or less. It is to be understood in the present disclosure that the one or more tubes (if used), as well as any solids (if used), may be provided through an interior of the image capturing assembly 220 without increasing dimensions (such as diameter) of the image capturing assembly 220 and/or affecting the controllability/configurability of the multi-curvable body 222.

When the internal temperature control assembly utilizes gases, or the like, example embodiments may also be operable to provide such gases into the body cavity and/or discharge or recycle such gases outside of the body cavity via one or more tubes, or the like. The gases may comprise carbon dioxide, oxygen, and/or other gases in example embodiments. Such gases may be further operable to assist in providing and/or maintaining insufflation of the cavity of the patient during a surgical procedure. When the internal temperature control assembly utilizes liquids, or the like, example embodiments may be operable to discharge or recycle such liquids outside of the body cavity. When the internal temperature control assembly utilizes solids, or the like, such solids may possess properties that enable the surgical team to change the temperature of the solids, such as by applying electricity or other form of energy, so as to control (such as reduce) the temperature and/or heat emission of one or more components of the image capturing assembly 220. In example embodiments, the internal temperature control assembly may utilize a combination of gases, liquids, solids, and/or the like without departing from the teachings of the present disclosure.

The image capturing assembly 220 may be secured to the port assembly 210 in one or more of a plurality of ways, including those described above and in the present disclosure for the instrument arm assemblies 230 or 240 and/or the assistant arm assemblies 250 or 260. For example, the image capturing assembly 220 may also comprise an anchoring portion 220a (e.g., similar to the securing portion 231a of the instrument arm assembly 220) operable to attach (or secure) the image capturing assembly 220 to one or more anchor ports 216 of the port assembly 210.

In an example embodiment, the image capturing body 224 and the multi-curvable body 222 may each be substantially cylindrical in shape. The image capturing body 224 and the multi-curvable body 222 may also be formed in any one of a plurality of other shapes, sizes, and/or dimensions without departing from the teachings of the present disclosure.

In an example embodiment, the length of the multi-curvable body 222 may be between about 50 to 150 mm. In example embodiments, a length of multi-curvable body 222 may also be adjustable by the surgical team 904 before, during, and/or after insertion of the camera arm assembly into the cavity of the patient. The outer diameter of the multi-curvable body 222 may be between about 5 to 7 mm. It is to be understood in the present disclosure that the above dimensions are merely an illustration of example embodi-

ments, and as such the dimensions may be smaller or larger than those recited above without departing from the teachings of the present disclosure.

The multi-curvable body **222** may be formed using any one or more of a plurality of materials, such as stainless steel, etc. It is to be understood in the present disclosure that other materials may also be used without departing from the teachings of the present disclosure. It is to be understood in the present disclosure that the above materials are merely an illustration of example embodiments, and these and other materials and compositions may be used without departing from the teachings of the present disclosure.

As illustrated in FIG. 6B and FIG. 6C, the image capturing assembly **220** may further comprise a gas shield **228** located nearby one or more lenses of the camera **227**. The image capturing assembly **220** may further comprise a gas shield **228** located nearby one or more of the illumination sources **229** and/or any other sensors (such as temperature sensors, pressure sensors, humidity sensors, etc.) provided by the image capturing assembly **220**. The gas shield **228** may comprise one or more openings or the like, one or more external gas sources **228**, and one or more tubes, channels, or the like, between the one or more external gas sources and the one or more openings of the gas shield **228**. In operation, the gas shield **228** may be operable to provide pressurized gases (and/or liquids), such as carbon dioxide, oxygen, other gases or liquids, or combinations thereof, via the one or more openings of the gas shield **228** to an area in front of the camera **227** (as well as in front of the illumination sources **229** and/or other sensors).

The overall system may also include one or more separate image capturing assemblies, such as the separate image capturing assembly **320** illustrated in FIG. 6D. The separate image capturing assembly **320** may be magnetically anchored by a magnetic anchor **310** to an internal wall of the cavity of the patient, such as via a permanent magnet, electromagnet, or the like. In some example embodiments, the magnetic anchor **310** may also be secured/held in position via an external anchor (not shown). The separate image capturing assembly **320** may include one or more cameras **327**, and may also include one or more illumination sources **329**.

The separate image capturing assembly **320** may be operable to provide one or more of a variety of views, including, but not limited to, a normal view, zoomed view, wide-angled view, and/or panoramic view of the cavity of the patient. The separate image capturing assembly **320** may be positioned in such a way as to provide the surgical team **904** with an unobstructed view of areas of interest within the cavity of the patient. In respect to positioning and securing the separate image capturing assembly **320** in place, as illustrated in FIG. 6D, the separate image capturing assembly **320** may be inserted through the central access channel **210a** of the port assembly **210** and to the desired location of the interior wall of the cavity of the patient in one or more of a plurality of ways, including using a surgical tool (not shown), attaching the separate image capturing assembly **320** to a multi-curvable body (not shown) similar to that of the image capturing assembly **220** (as illustrated in FIGS. 2A, 2B, 3A, 3B, and 6D), etc.

The Instrument Arm Assembly (e.g., Instrument Arm Assembly **230, 240**)

In an example embodiment, the surgical device **200** may comprise one or more instrument arm assemblies (e.g., first instrument arm assembly **230**, second instrument arm assembly **240**, third instrument arm assembly (not shown),

fourth instrument arm assembly (not shown), etc.), each configurable to attach to the port assembly **210**.

One or more of the instrument arm assemblies (such as **230, 240**) may comprise a configurable serial (or linear) arrangement of a plurality of instrument arm segments and joint portions, and at least one end instrument (or end effector) **239** integrated into and/or connected to one or more of the instrument arm segments and/or joint portions. The end effector **239** may be any instrument suitable for use in surgical procedures, such as a cutting and/or gripping instrument. One or more of the instrument arm assemblies (such as **230, 240**) may also comprise one or more illumination sources (not shown), such as an LED, or the like, operable to illuminate one or more parts of the end effector **239**, instrument arm assemblies, and/or parts, sections, and/or quadrants of the abdominal cavity of the patient.

One or more of the instrument arm assemblies (such as **230, 240**) may also comprise one or more integrated motors operable to provide at least one degree of freedom for the instrument arm assembly. One or more of the instrument arm assemblies may also include an integrated haptic and/or force feedback subsystem (not shown) in communication with one or more of the integrated motors and/or other sensors and/or instruments operable to provide to the surgical team (such as via computing device/controller) with one or more of a plurality of feedback responses and/or measurements, including those pertaining to position (including orientation), applied force, proximity, temperature, pressure, humidity, etc., of, by, and/or nearby to the instrument arm assembly. For example, the surgical team **904** may be provided with a master input device having manipulators, or the like, having haptic and/or force feedback and designed to map and sense the surgical team's **904** delicate finger-twisting, wrist-bending, and/or other arm/shoulder movements into movements of the instrument arm (such as **230, 240**) with high precision, high dexterity, and minimum burden, while also providing feedback of contact resistance (such as tissue resistance).

When an instrument arm assembly (such as **230, 240**) comprises one or more illumination sources, cameras, haptic and/or force feedback instruments, and/or other sensors and/or instruments, as described above and in the present disclosure, the instrument arm assembly may also comprise a gas shield, such as the gas shield described above for the image capturing assembly **220**. One or more of the instrument arm assemblies (such as **230, 240**) may further comprise one or more internal temperature control assemblies operable to control (such as reduce or increase) the temperature of one or more components of the instrument arm assembly.

As illustrated in the example embodiment of FIGS. 2A, 2B, 3A, 3B, FIG. 5A, and FIG. 5B, each of the instrument arm assemblies, including the first instrument arm assembly **230**, may comprise a first instrument arm segment (or shoulder section) **231**, a second instrument arm segment (or first arm section) **233**, a third instrument arm segment (or second arm section) **235**, and a fourth instrument arm segment (or hand section) **237**. The instrument arm assembly **230** may also comprise a first joint portion (or shoulder joint section) **232**, a second joint portion (or elbow section) **234**, a third joint portion (or wrist section) **236**, and an end effector joint portion **238**. Each of the aforementioned joint portions may be configurable, either manually and/or via the computing device (or system), to provide an attached instrument arm segment (and the end effector **239**) with one or more in vivo degrees of freedom when the instrument arm assembly is provided in the abdominal cavity of the patient.

For example, the first joint portion (or shoulder joint section) **232** may be operable to provide the second instrument arm segment (or first arm section) **233** with one or two degrees of freedom resembling the one or two degrees of freedom of the human shoulder. As another example, the second joint portion (or elbow section) **234** may be operable to provide the third instrument arm segment (or second arm section) **235** with one or two degrees of freedom resembling the one or two degrees of freedom of the human elbow. As another example, the third joint portion (or wrist section) **236** may be operable to provide the fourth instrument arm segment (or hand section) **237** with one or two degrees of freedom resembling the one or two degrees of freedom of the human wrist. As another example, the end effector joint portion **238** may be operable to provide the end effector **239** with one or more degrees of freedom. Accordingly, one or more of the instrument arm assemblies may be configurable, either manually and/or via the computing device/controller, to provide seven or more in vivo degrees of freedom and, together with the at least one to three or more in vitro degree of freedom provided by the port assembly **210** and the controllable swivel assembly **1000** (see FIGS. **10A** and **10B**), the one or more of the instrument arm assemblies may be configurable, either manually and/or via the computing device/controller, to provide a total of eight to ten or more degrees of freedom. It is recognized herein that the aforementioned at least seven in vivo degrees of freedom for the instrument arm assembly enables at least the full range of natural movements by a surgeon's arm (via a controller/computer-human interface/manipulator/master input device, such as the example illustrated in FIGS. **9A** and **9B**) to be substantially directly mapped and/or translated to the instrument arm assembly.

Each joint portion, including joint portions **232**, **234**, and **236** and instrument joint portion **238** may comprise any one or more configurations of gears and/or gear assemblies, including straight gear configurations, planetary gear configurations, beveled gear configurations, spiral beveled gear configurations, hypoid gear configurations, helical gear configurations, worm gear configurations, and/or any other gear configuration without departing from the teachings of the present disclosure. In example embodiments, each instrument arm assembly may also comprise one or more internal integrated motors, or the like, operable to actuate the gears of each joint portion, including joint portions **232**, **234**, and **236** and/or the instrument arm segments **231**, **233**, **235**, and **237**. In this regard, each of the abovementioned integrated motors, joint portions, and/or instrument arm segments may be operable to communicate, such as receive control commands and/or transmit information, from and/or to the computing device/controller of one or more nearby and/or remotely located surgical teams **904** via wired and/or wireless communication in example embodiments. Furthermore, each of the abovementioned integrated motors, joint portions, and/or instrument arm segments may be operable to receive power from an external power source and/or the computing device/controller via wired and/or wireless transmissions in example embodiments.

Each of the instrument arm assemblies may be securable to (and unsecured from) the anchor ports **216** of the port assembly **210** via a securing portion **231a** of the shoulder section **231**. It is recognized in the present disclosure that the instrument arm assembly **230**, **240** may be secured to the anchor port **216** of the port assembly **210** in the forward-directed position (e.g., as illustrated in FIGS. **2B** and **3B**) and/or the reverse-directed position (e.g., as illustrated in FIGS. **2A** and **3A**). Furthermore, in example embodiments,

the instrument arm assembly **230**, **240** may or may not be transitioned between the forward-directed position and the reverse-directed position. In example embodiments where the instrument arm assembly **230**, **240** is transitionable between the forward-directed position and the reverse-directed position, such transition may be performable before, during, and/or after the securing of the shoulder section **231** to the anchor port **216** of the port assembly **210**. For example, in such embodiments, the securing portion **231a** may be adjustably changed in position relative to the shoulder section **231**, such as from the forward-directed position illustrated in FIG. **5A** to the reverse-directed position illustrated in FIG. **5B**, and vice versa.

One or more internal temperature control assemblies (not shown) may be provided for each of the one or more instrument arm assemblies **230**, **240**. Each internal temperature control assembly may be operable to control (such as reduce) the temperature and/or heat emission of the aforementioned gears and/or gear assemblies, motors, instrument joint portions (such as **232**, **234**, and **236**), and/or instrument arm segments (such as **231**, **233**, **235**, and **237**). The one or more internal temperature control assemblies may also be operable to control (such as increase or decrease) the temperature of the end effector **239** (which may be desirable when the end effector **239** is a cutting tool, or the like). In an example embodiment, the one or more internal temperature control assemblies may be operable to perform such temperature control using one or more gases, liquids, and/or solids. For example, the gases and/or liquids may be fed, maintained, and/or regulated using an external source via one or more tubes, or the like. The one or more tubes used to provide, regulate, and/or discharge the gases and/or liquids may have a diameter between about 0.5 mm to 3 mm in example embodiments, but the dimensions of such tubes may also be more or less. It is to be understood in the present disclosure that the one or more tubes (if used), as well any solids (if used), may be provided through an interior of the instrument arm assembly without increasing dimensions (such as diameter) of the instrument arm assembly.

When the internal temperature control assembly utilizes gases, or the like, example embodiments may also be operable to provide such gases into the body cavity and/or discharge or recycle such gases outside of the body cavity via one or more tubes, or the like. The gases may comprise carbon dioxide, oxygen, and/or other gases in example embodiments. Such gases may be further operable to assist in providing and/or maintaining insufflation of the body cavity, such as via an opening (not shown). When the internal temperature control assembly utilizes liquids, or the like, example embodiments may be operable to discharge or recycle such liquids outside of the body cavity. When the internal temperature control assembly utilizes solids, or the like, such solids may possess properties that enable the surgical team to change the temperature of the solids, such as by applying electricity or other form of energy, so as to control (such as reduce) the temperature and/or heat emission of one or more components of the instrument arm assembly **230**, **240**.

In example embodiments, the internal temperature control assembly may utilize a combination of gases, liquids, solids, and/or the like without departing from the teachings of the present disclosure.

After the instrument arm assembly **230**, **240** has been inserted and attached (or secured) to the port assembly **210**, the end effector **239** may be configurable, either manually and/or via the computing device (or system), to apply between about 0 to 20 N of force when performing surgical

actions and procedures, such as clipping and/or grasping actions. Furthermore, the end effector **239** may be configurable, either manually and/or via the computing device/controller, to apply between about 0 to 10 N of force when performing other surgical actions and procedures, such as translational, twisting, pulling, and/or pushing actions. It is to be understood in the present disclosure that the above range of applicable force are merely an illustration of example embodiments, and as such the range of applicable force may be smaller or larger than those recited above without departing from the teachings of the present disclosure.

In an example embodiment, the instrument arm segments, including the first instrument arm segment **231**, the second instrument arm segment **233**, the third instrument arm segment **235**, and/or the fourth instrument arm segment **237**, may be substantially cylindrical in shape. The instrument arm segments, including the first instrument arm segment **231**, the second instrument arm segment **233**, the third instrument arm segment **235**, and/or the fourth instrument arm segment **237**, may also be formed in any one of a plurality of other shapes, sizes, and/or dimensions without departing from the teachings of the present disclosure.

As described above, the instrument arm assembly **230**, **240** may also include one or more securing portions **231a**. The securing portion **231a** may be attachable or attached to the first instrument arm segment **231**, a part of the first instrument arm segment **231**, and/or formed as a unitary article with the first instrument arm segment **231**. Such securing portions **231a** may be for use in securing the instrument arm assembly **230**, **240** to the anchor ports **216**. Such securing portions **231a** may also be for use in performing or assisting in performing the process of inserting the instrument arm assembly **230**, **240** into and securing onto the port assembly **210** in example embodiments.

After the instrument arm assembly **230** is inserted through the port assembly **210** and into the cavity of a patient (such as a vagina or rectum), the securing portion **231a** of the first instrument arm segment (or shoulder section) **231** may be securely received by the anchor port **216** of the port assembly **210**.

In an example embodiment, the length of the securing portion **231a** may be between about 350 to 450 mm, the length of the first instrument arm segment **231** may be between about 15 to 40 mm, the length of the second instrument arm segment **233** may be between about 80 to 105 mm, the length of the third instrument arm segment **235** may be between about 65 to 90 mm, the length of the fourth instrument arm segment **237** may be between about 5 to 30 mm, and the overall length of the collective instrument arm may be between about 165 to 265 mm. In example embodiments, the length of the securing portion **231a** may be between about 340 to 400 mm, the length of the first instrument arm segment **231** may be between about 15 to 25 mm, the length of the second instrument arm segment **233** may be between about 90 to 100 mm, the length of the third instrument arm segment **235** may be between about 75 to 85 mm, the length of the fourth instrument arm segment **237** may be between about 15 to 25 mm, and the overall length of the collective instrument arm may be between about 195 to 235 mm. In example embodiments, a length of one or more of the instrument arm segments, the securing portion **231a**, and/or the end effector **239** may also be adjustable by the computing device (or system) of one or more nearby and/or remotely located surgical teams **904** before, during, and/or after insertion of the instrument arm assembly into the cavity of the patient. The outer diameter of one or more

of the instrument arm segments may be about 10 to 16 mm. In an example embodiment, the outer diameter of one or more of the instrument arm segments may be about 16 mm.

Each of the instrument arm assemblies, including the securing portion **231a**, the first instrument arm segment **231**, the second instrument arm segment **233**, the third instrument arm segment **235**, the fourth instrument arm segment **237**, the end effector **239**, the first joint portion **232**, the second joint portion **234**, the third joint portion **236**, and/or the instrument joint **238**, may be formed using any one or more of a plurality of materials, such as surgical-grade metals, high-strength aluminum alloys, stainless steel (such as 304/304L, 316/316L, and 420), pure titanium, titanium alloys (such as Ti6Al4V, NiTi), and cobalt-chromium alloys. It is to be understood in the present disclosure that other materials may also be used without departing from the teachings of the present disclosure.

The Assistant Arm Assemblies (e.g., Assistant Arm Assembly **250**, **260**)

In an example embodiment, the surgical device **200** may comprise one or more assistant arm assemblies (e.g., assistant arm assembly **250** or **260**) configurable to be inserted into and attach to the port assembly **210**. As illustrated in FIGS. **2A**, **2B**, **3A**, and **3B**, one or more of the assistant arm assemblies may be a suction/irrigation assembly **250** or an assistant instrument arm assembly such as a retractor arm assembly **260**, and each of them may include a multi-curvable body **252** or **262**, respectively, and an anchoring portion, respectively (e.g., similar to the multi-curvable body **222** and anchoring portion **220a** of the image capturing assembly **220**).

As illustrated in FIGS. **2A**, **2B**, **3A**, and **3B**, the suction/irrigation assembly **250** may include an end having a suction port **259** for applying a suction or negative pressure, which may be for use in removing liquids (e.g., blood, etc.) from the cavity of the patient. In respect to the assistant instrument arm assembly **260**, the assistant instrument arm assembly **260** may include an end having an instrument **269**, such as a gripper, retractor, cutter, needle, or the like, which may be for use in assisting the one or more instrument arm assemblies **230** and/or **240** in performing the surgical action.

As illustrated in the example embodiment of FIGS. **2A**, **2B**, **3A**, and **3B**, the assistant arm assemblies **250** and/or **260** may comprise a multi-curvable body **252** and/or **262**, respectively, attached to their ends (suction port or instrument, respectively). The multi-curvable body **252** or **262** may be any elongated multi-curvable body similar to that of the image capturing assembly **220** described above and in the present disclosure that can be controlled/configured by the surgical team **904** (such as via the computing device/controller/manipulator/master input device) to, among other things, straighten and/or curve (and hold such a straightness and/or curvature) at one or more of a plurality of locations along the multi-curvable body **252** or **262**, curve (and hold such a curvature) in one or more of a plurality of curvatures, and/or straighten and/or curve (and hold such a straightness and/or curvature) in one or more of a plurality of directions. It is to be understood that, when the multi-curvable body **252** or **262** is configured to curve at any location along the multi-curvable body **252** or **262**, the curve may be held and/or released (or configured to uncurve, curve less, or straighten) by the surgical team **904** (such as via the computing device/controller/manipulator/master input device).

The multi-curvable body **252** or **262** may be formed in any one or more ways known in the art. For example, the multi-curvable body **252** or **262** may be a unitary or substantially unitary elongated body having a plurality of wires,

cables, or the like, distributed/run throughout the multi-curved body **252** or **262** in such a way that a manipulating, such as a pulling/releasing, shortening/lengthening, tightening/loosening, etc., of one or a combination of such wires, cables, or the like enables the above-mentioned curving of one or more locations of the multi-curved body **252** or **262** in one or more curvatures and in one or more directions. As another example, the multi-curved body **252** or **262** may include a plurality of segments, each segment linked to an adjacent segment in such a way that the segment may be controlled/configured to be pivotly positioned in a plurality of positions relative to the adjacent segment. As another example, the multi-curved body **252** or **262** may include a plurality of springs, gears, motors, etc. for achieving the above-mentioned curving of one or more locations of the multi-curved body **252** or **262** in one or more curvatures and in one or more directions. It is to be understood in the present disclosure that the multi-curved body **252** or **262** may also include a combination of one or more of the above-mentioned approaches.

The assistant arm assembly **250** or **260** may be secured to the port assembly **210** in one or more of a plurality of ways, including those described above and in the present disclosure for the instrument arm assemblies **230**, **240** and/or the image capturing assembly **220**. For example, the assistant arm assembly **250** or **260** may also comprise an anchoring portion (e.g., similar to the anchoring portion **220a** of the image capturing assembly **220** and/or the securing portion **231a** of the instrument arm assembly **220**), respectively, operable to attach (or secure) the assistant arm assembly **250** or **260** to one or more anchor ports **216** of the port assembly **210**.

In an example embodiment, the multi-curved body **252** or **262** may each be substantially cylindrical in shape. The multi-curved body **252** or **262** may also be formed in any one of a plurality of other shapes, sizes, and/or dimensions without departing from the teachings of the present disclosure.

In an example embodiment, the length of the multi-curved body **252** or **262** may be between about 170 to 270 mm. In example embodiments, a length of multi-curved body **252** or **262** may also be adjustable by the surgical team **904** before, during, and/or after insertion of the camera arm assembly into the cavity of the patient. The outer diameter of the multi-curved body **252** or **262** may be between about 5 to 7 mm. It is to be understood in the present disclosure that the above dimensions are merely an illustration of example embodiments, and as such the dimensions may be smaller or larger than those recited above without departing from the teachings of the present disclosure.

#### Controller

In example embodiments, the surgical system may include a controller (or computing device, manipulator, and/or master input device). The controller may be configurable to perform one or more of a plurality of operations in and on the surgical system **200**. For example, the controller may be configurable to communicate with and/or control one or more elements of the surgical system **200**, such as the external anchor **1** or **1000**, the port assembly **210**, the instrument arm assemblies **230** or **240**, the image capturing assembly **220**, and/or the assistant arm assemblies **250** or **260**. The controller may be accessible and/or controllable by the surgical team **904**, and the surgical team may be able to communicate with and/or control the configuring and/or operation of the one or more elements of the surgical system **200**. For example, the controller may be configurable to control a movement and action of some or all parts of the

instrument arm assemblies **230** or **240**, the first gate assembly **212b**, the second gate assembly **214b**, the movement and action of some or all parts of the image capturing assembly **220** (including the image capturing, temperature control, etc.), the movement and action of some or all parts of the multi-curved body **222** of the image capturing assembly **220**, the movement and action of some or all parts of the multi-curved body **252** or **262** of the assistant arm assemblies, the movement and action of some or all parts of the assistant arm assemblies **250** or **260**, and the like.

Method of Setting up the Surgical Device **200** in a Forward-Directed Position (E.G., Method **700**)

As illustrated in FIG. 7 and FIGS. 8A-E, example embodiments of the surgical device **200** may be configurable to perform a forward-directed surgical action or procedure in one of a plurality of ways. In an example embodiment, the external anchor **1** may be provided and installed/anchored to the stationary object. The port assembly **210** may be provided (e.g., action **702**), and the instrument arm assembly may be provided (e.g., action **704**). A second instrument arm assembly may be provided, as well as the image capturing assembly **220** and/or **320** and any of the assistant arm assemblies **250** and/or **260** required. The port assembly **210** may be inserted (e.g., action **706**) into the opening (and cavity) of the patient and anchored in position using the external anchor **1** (e.g., action **708**), and a workable volume/space in the cavity may be formed, such as via insufflation using CO<sub>2</sub> and/or other gases, vacuum suction tools, and/or retractable hook tools. The controllable swivel assembly **1000** may also be used in example embodiments. For example, a workable abdominal cavity of about 10-12 cm in height may be provided for the patient. Thereafter, one or more image capturing assemblies **220**, one or more assistant arm assemblies (e.g., action **710**), and one or more assistant arm assemblies **250** or **260** (if needed) may be inserted into the port assembly **210** via the central access channel **210a**, secured to the anchor ports **216**, and configured in the cavity of the patient. A surgical action or procedure may then be performed in any part, area, and/or quadrant of the cavity of the patient using the surgical device **200**. These processes will now be described below with references to at least FIGS. 7, 8A-E, 9B, and 10B.

(1) Providing the External Anchor and Installing the Port Assembly.

In an example embodiment, the external anchor **1** may be provided and installed/anchored to one or more stationary objects, such as a side rail **300** of a surgical table/bed, as illustrated in FIGS. 1A and 1B. One or more segments **2**, **6**, **10**, and **14** of the external anchor **1** may cooperate using one or more joints **4**, **8**, **12**, and **16** of the external anchor **1** to fix the position (including orientation) of the port assembly **210** in or about the opening of the patient.

In an example embodiment, as illustrated in FIGS. 10A and 10B, the external anchor **1** may comprise a controllable swivel assembly **1000** operable to provide one or more additional in vitro degrees of freedom, such as via a first swivel portion **1002**, second swivel portion **1004**, and/or third swivel portion **1006**. The controllable swivel assembly **1000** may further comprise a motor **1002a** for the first swivel portion **1002**, a motor **1004a** for the second swivel portion **1004**, a motor **1006a** for the third swivel portion **1006**, one or more supporting arms **1008**, and one or more locks **1010**.

The first swivel portion **1002** may be operable to provide, as one of the in vitro degrees of freedom, a translational movement of the port assembly **210** along an axis defined by the elongated length of the port assembly **210**, as illustrated by the arrow A. In example embodiments, the translational

movement, as illustrated by arrow A, provided by the first swivel portion **1002** may be between about 0 to 50 mm.

The controllable swivel assembly **1000** may further comprise a second swivel portion **1004** operable to provide, as another one of the in vitro degrees of freedom, a torsional or rotational movement of the port assembly **210** about an axis depicted by axis Y. In example embodiments, the torsional or rotational movement, as illustrated by the arrow B, provided by the second swivel portion **1004** may be between about  $\pm 180$  degrees.

The controllable swivel assembly **1000** may further comprise a third swivel portion **1006** operable to provide, as another one of the in vitro degrees of freedom, a pivotal or rotational movement of the port assembly **210** about an axis perpendicular to the Y-axis, such as the axis depicted by axis Z (which comes out of the page). In example embodiments, the Z-axis or the center of rotation may be located at about opening of the patient, such as at the mid-point of the abdominal wall. In example embodiments, the pivotal or rotational movement, as illustrated by the arrow C, provided by the third swivel portion **1006** may be between about  $\pm 80$  degrees.

It is recognized in the present disclosure that the controllable swivel assembly **1000** may comprise the first swivel portion **1002**, second swivel portion **1004**, and/or third swivel portion **1006** in example embodiments. The controllable swivel assembly **1000** may further comprise other swivel portions (not shown) when more than three in vitro degrees of freedom and/or movements/rotations other than those providable by the first swivel portion **1002**, second swivel portion **1004**, and third swivel portion **1006** are desired and/or required.

The controllable swivel assembly **1000**, including the first swivel portion **1002**, the second swivel portion **1004**, and/or the third swivel portion **1006**, may be controllable either locally or remotely by the surgical team.

In an example embodiment, the port assembly **210** may be installed and secured to the external anchor **1** or **1000**. As illustrated in FIGS. 8A-E, the second end **214** of the port assembly **210** may be inserted into the opening of the patient and into the cavity of the patient and the first end **212** of the port assembly **210** may be secured to the external anchor **1** or **1000**. Thereafter, a workable volume/space in the cavity may be formed in the cavity of the patient, such as via insufflation using CO<sub>2</sub> and/or other gases, vacuum suction tools, and/or retractable hook tools. Before doing so, the first gate assembly **212b** and the second gate assembly **214b** may be expanded to the closed position. Insufflation of the cavity may be achieved in one or more of a plurality of ways. For example, the insufflation port of the port assembly **210** may be used to provide the required insufflation.

(2) Inserting and Attaching the Image Capturing Assembly.

After the workable volume/space in the cavity has been formed and the port assembly **210** is secured in position, as illustrated in FIG. 8A, the image capturing assembly **220** may be inserted through the central access channel **210a** and secured to the anchor port **216** of the port assembly **210**. To do so while maintaining the workable volume/space, the first gate assembly **212b** may be configured to the open position while the second gate assembly **214b** is configured to the closed position. Once the first gate assembly **212b** is in the open position, the image capturing assembly **220** may be inserted into the mid section **213**. The first gate assembly **212b** may then be configured to the closed position after the image capturing assembly **220** passes through the first gate assembly **212b**. The second gate assembly **214b** may then be

configured to the open position. It is recognized in the present disclosure that the workable volume/space in the cavity is maintained via the insufflation since the first gate assembly **212b** is configured to the closed position. Once the second gate assembly **214b** is in the open position, the image capturing assembly **220** may be inserted into the cavity of the patient and the anchor portion **220a** secured to an anchor port **216**. The second gate assembly **214b** may then be configured to the closed position after the image capturing assembly **220** passes through the second gate assembly **214b**. The multi-curable body **222** of the image capturing assembly **220** may then be configured/controlled to curve in one or more locations along the multi-curable body **222** so that the image capturing assembly **220** can be directed in a forward-directed position (as illustrated in FIGS. 2B and 3B).

The separate image capturing assembly **320** may also be inserted through the port assembly **210** in a similar manner as described above. Once inserted through the port assembly **210** and into the cavity of the patient, the separate image capturing assembly **320** may then be attached/secured to the interior wall of the cavity of the patient via the magnetic anchor **310**.

(3) Inserting and Attaching a First Instrument Arm Assembly.

The instrument arm assembly **230** may be inserted through the central access channel **210a** and secured to the anchor port **216** of the port assembly **210**. To do so while maintaining the workable volume/space, the first gate assembly **212b** may again be configured to the open position while the second gate assembly **214b** is configured to the closed position. Once the first gate assembly **212b** is in the open position, the instrument arm assembly **230** may be inserted into the mid section **213**, as illustrated in FIG. 8B. The first gate assembly **212b** may then be configured to the closed position after the instrument arm assembly **230** passes through the first gate assembly **212b** and into the mid section **213**, as illustrated in FIG. 8C. The second gate assembly **214b** may then be configured to the open position, as illustrated in FIG. 8D. Once the second gate assembly **214b** is in the open position, the instrument arm assembly **230** may be inserted into the cavity of the patient and the securing portion **231a** secured to an anchor port **216**, as illustrated in FIG. 8E. The second gate assembly **214b** may then be configured to the closed position after the instrument arm assembly **230** passes through the second gate assembly **214b**.

(5) Inserting and Attaching One or More Additional Instrument Arm Assemblies, One or More Assistant Arm Assemblies, and/or One or More Additional Camera Arm Assemblies.

One or more additional instrument arm assemblies **240**, one or more assistant arm assemblies **250** or **260**, and/or one or more additional image capturing assemblies (not shown) may also be inserted into the port assembly **210** via the central access channel **210a** in the same manner as described above for the image capturing assembly **220** and the instrument arm assembly **230**.

(6) Unattaching and Removing the Instrument Arm Assembly, Image Capturing Assembly, and Assistant Arm Assemblies.

The instrument arm assembly **230**, image capturing assembly **220**, other instrument arm assembly **240** (if provided), other image capturing assembly (if provided), and the one or more other assistant arm assemblies **250** or **260** (if provided) may be unattached (or unsecured) from the anchor ports **216** and removed from the cavity of the patient

via the central access channel **210a** of the port assembly **210** in a substantially reverse manner as described above for the inserting and attaching.

Method of Setting up the Surgical Device **200** in a Reverse-Directed Position (e.g., Method **700**)

As illustrated in FIGS. **7** and **8F-K**, example embodiments of the surgical device **200** may be configurable to perform a reverse-directed surgical action or procedure in one of a plurality of ways. In an example embodiment, the external anchor **1** may be provided and installed/anchored to the stationary object in a similar manner as described above and in the present disclosure. The port assembly **210** may be provided (e.g., action **702**), and the instrument arm assembly may be provided (e.g., action **704**). A second instrument arm assembly may be provided, as well as the image capturing assembly **220** and/or **320** and any of the assistant arm assemblies **250** and/or **260** required. The port assembly **210** may be inserted (e.g., action **706**) into the opening (and cavity) of the patient and anchored in position using the external anchor **1** (e.g., action **708**), and a workable volume/space in the cavity may be formed, such as via insufflation using CO<sub>2</sub> and/or other gases, vacuum suction tools, and/or retractable hook tools. The controllable swivel assembly **1000** may also be used in example embodiments. For example, a workable abdominal cavity of about 10-12 cm in height may be provided for the patient. Thereafter, one or more image capturing assemblies **220**, one or more assistant arm assemblies (e.g., action **710**), and one or more assistant arm assemblies **250** or **260** (if needed) may be inserted into the port assembly **210** via the central access channel **210a**, secured to the anchor ports **216**, and configured in the cavity of the patient. For the inserting, each of the image capturing assemblies **220**, instrument arm assemblies **230** and/or **240**, and assistant arm assemblies **250** and/or **260** are inserted in reverse orientation as compared to the forward-directed position described above and in the present disclosure. A surgical action or procedure may then be performed in any part, area, and/or quadrant of the cavity of the patient using the surgical device **200**. These processes will now be described below with references to at least FIGS. **7**, **8F-K**, **9B**, and **10B**.

(1) Providing the External Anchor and Installing the Port Assembly.

In an example embodiment, the port assembly **210** may be installed and secured to the external anchor **1** or **1000**. As illustrated in FIGS. **8A-E**, the second end **214** of the port assembly **210** is inserted into the opening of the patient and into the cavity of the patient and the first end **212** of the port assembly **210** is secured to the external anchor **1** or **1000**. Thereafter, a workable volume/space in the cavity may be formed in the cavity of the patient, such as via insufflation using CO<sub>2</sub> and/or other gases, vacuum suction tools, and/or retractable hook tools. Before doing so, the first gate assembly **212b** and the second gate assembly **214b** may be expanded to the closed position. Insufflation of the cavity may be achieved in one or more of a plurality of ways. For example, the insufflation port of the port assembly **210** may be used to provide the required insufflation.

(2) Inserting and Attaching the Image Capturing Assembly.

After the workable volume/space in the cavity has been formed and the port assembly **210** is secured in position, as illustrated in FIG. **8F**, the image capturing assembly **220** may be inserted with the image capturing body **224** inserted last through the central access channel **210a** and secured to the anchor port **216** of the port assembly **210**. To do so while maintaining the workable volume/space, the first gate

assembly **212b** may be configured to the open position while the second gate assembly **214b** is configured to the closed position. Once the first gate assembly **212b** is in the open position, the image capturing assembly **220** may be inserted into the mid section **213**. The first gate assembly **212b** may then be configured to the closed position after the image capturing assembly **220** passes through the first gate assembly **212b**. The second gate assembly **214b** may then be configured to the open position. It is recognized in the present disclosure that the workable volume/space in the cavity is maintained via the insufflation since the first gate assembly **212b** is configured to the closed position. Once the second gate assembly **214b** is in the open position, the image capturing assembly **220** may be inserted completely into the cavity of the patient with the image capturing body **224** being closest to the anchor port **216**. The multi-curvable body **222** of the image capturing assembly **220** may then be configured/controlled to curve in one or more locations along the multi-curvable body **222** so that the image capturing assembly **220** can be directed in a reverse-directed position next to the outer surface of the port assembly **210** (as illustrated in FIGS. **2A** and **3A**). The image capturing assembly **220** may then be provided adjacent to the outer surface of the port assembly **210** so that the anchoring portion **220a** of the image capturing assembly **220** is adjacent to the anchor port **216**. The anchoring portion **220a** of the image capturing assembly **220** may then be secured to the anchor port **216**. The second gate assembly **214b** may be configured to the closed position after the image capturing assembly **220** passes through the second gate assembly **214b**.

The separate image capturing assembly **320** may also be inserted through the port assembly **210** in a similar manner as described above. Once inserted through the port assembly **210** and into the cavity of the patient, the separate image capturing assembly **320** may then be attached/secured to the interior wall of the cavity of the patient via the magnetic anchor **310**.

(3) Inserting and Attaching a First Instrument Arm Assembly.

To insert the instrument arm assembly **230** through the central access channel **210a** and secure it to the anchor port **216** of the port assembly **210** while maintaining the workable volume/space, the first gate assembly **212b** may again be configured to the open position while the second gate assembly **214b** is configured to the closed position. Once the first gate assembly **212b** is in the open position, the instrument arm assembly **230** may be inserted with the end effector **239** inserted last into the mid section **213**, as illustrated in FIG. **8G**. The first gate assembly **212b** may then be configured to the closed position after the instrument arm assembly **230** passes through the first gate assembly **212b** and into the mid section **213**, as illustrated in FIG. **8H**. The second gate assembly **214b** may then be configured to the open position, as illustrated in FIG. **8I**. Once the second gate assembly **214b** is in the open position, the instrument arm assembly **230** may be inserted completely into the cavity of the patient with the end effector **239** being closest to the anchor port **216**, as illustrated in FIG. **8J**. The instrument arm assembly **230** may then be turned 180 degrees (if needed) and/or moved so that the instrument arm assembly **230** can be brought next to the outer surface of the port assembly **210**. The instrument arm assembly **230** may then be pulled adjacent to the outer surface of the port assembly **210** so that the securing portion **231a** of the shoulder section **231** of the instrument arm assembly **230** is adjacent to the anchor port **216**. The securing portion **231a**



of the instrument arm assembly **230** may then be secured to the anchor port **216**, as illustrated in FIG. **8K**. The second gate assembly **214b** may be configured to the closed position at any time after at least the end effector **230** of the instrument arm assembly **230** passes through the second gate assembly **214b**.

(5) Inserting and Attaching One or More Additional Instrument Arm Assemblies, One or More Assistant Arm Assemblies, and/or One or More Additional Camera Arm Assemblies.

One or more additional instrument arm assemblies **240**, one or more assistant arm assemblies **250** or **260**, and/or one or more additional image capturing assemblies (not shown) may also be inserted and installed in a reverse-directed manner via the central access channel **210a** of the port assembly **210** in the same manner as described above for the image capturing assembly **220** and the instrument arm assembly **230**.

(6) Unattaching and Removing the Instrument Arm Assembly, Image Capturing Assembly, and Assistant Arm Assemblies.

The instrument arm assembly **230**, image capturing assembly **220**, other instrument arm assembly **240** (if provided), other image capturing assembly (if provided), and the one or more other assistant arm assemblies **250** or **260** (if provided) may be unattached (or unsecured) from the anchor ports **216** and removed from the cavity of the patient via the central access channel **210a** of the port assembly **210** in a substantially reverse manner as described above for the inserting and attaching in the reverse-directed manner.

While various embodiments in accordance with the disclosed principles have been described above, it should be understood that they have been presented by way of example only, and are not limiting. Thus, the breadth and scope of the example embodiments described in the present disclosure should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the claims and their equivalents issuing from this disclosure. Furthermore, the above advantages and features are provided in described embodiments, but shall not limit the application of such issued claims to processes and structures accomplishing any or all of the above advantages.

For example, “assembly,” “device,” “portion,” “segment,” “member,” “body,” or other similar terms should generally be construed broadly to include one part or more than one part attached or connected together.

Various terms used herein have special meanings within the present technical field. Whether a particular term should be construed as such a “term of art” depends on the context in which that term is used. “Connected,” “connecting,” “attached,” “attaching,” “anchored,” “anchoring,” “in communication with,” “communicating with,” “associated with,” “associating with,” or other similar terms should generally be construed broadly to include situations where attachments, connections, and anchoring are direct between referenced elements or through one or more intermediaries between the referenced elements. These and other terms are to be construed in light of the context in which they are used in the present disclosure and as one of ordinary skill in the art would understand those terms in the disclosed context. The above definitions are not exclusive of other meanings that might be imparted to those terms based on the disclosed context.

As referred to in the present disclosure, a computing device, controller, manipulator, master input device, a processor, and/or a system may be a virtual machine, computer, node, instance, host, and/or device in a networked or non-

networked computing environment. A networked computing environment may be a collection of devices connected by communication channels that facilitate communications between devices and allow devices to share resources. Also as referred to in the present disclosure, a computing device may be a device deployed to execute a program operating as a socket listener and may include software instances.

Resources may encompass any type of resource for running instances including hardware (such as servers, clients, mainframe computers, networks, network storage, data sources, memory, central processing unit time, scientific instruments, and other computing devices), as well as software, software licenses, available network services, and other non-hardware resources, or a combination thereof.

A networked computing environment may include, but is not limited to, computing grid systems, distributed computing environments, cloud computing environment, etc. Such networked computing environments include hardware and software infrastructures configured to form a virtual organization comprised of multiple resources that may be in geographically disperse locations.

Furthermore, the coverage of the present application and any patents issuing from the present application may extend to one or more communications protocols, including TCP/IP.

Words of comparison, measurement, and timing such as “at the time,” “equivalent,” “during,” “complete,” and the like should be understood to mean “substantially at the time,” “substantially equivalent,” “substantially during,” “substantially complete,” etc., where “substantially” means that such comparisons, measurements, and timings are practicable to accomplish the implicitly or expressly stated desired result.

Additionally, the section headings herein are provided for consistency with the suggestions under 37 C.F.R. 1.77 or otherwise to provide organizational cues. These headings shall not limit or characterize the invention(s) set out in any claims that may issue from this disclosure. Specifically, a description of a technology in the “Background” is not to be construed as an admission that technology is prior art to any invention(s) in this disclosure. Furthermore, any reference in this disclosure to “invention” in the singular should not be used to argue that there is only a single point of novelty in this disclosure. Multiple inventions may be set forth according to the limitations of the multiple claims issuing from this disclosure, and such claims accordingly define the invention(s), and their equivalents, that are protected thereby. In all instances, the scope of such claims shall be considered on their own merits in light of this disclosure, but should not be constrained by the headings herein.

What is claimed is:

1. A port assembly, the port assembly comprising:
  - a first end section, the first end section having a first end channel and a first gate assembly, the first gate assembly configurable to transition between an open position to allow access through the first end channel and a closed position to prevent access through the first end channel; and
  - a second end section, the second end section having:
    - a second end channel, the second end channel being substantially aligned with the first end channel;
    - a second gate assembly, the second gate assembly configurable to transition between an open position to allow access through the second end channel and a closed position to prevent access through the second end channel; and
    - an anchor port;

29

wherein the anchor port is configurable to be securable to a surgical instrument;  
wherein the first end section is configurable to secure to an external anchor.

2. The port assembly of claim 1, wherein the first gate assembly is configurable to transition to the closed position in such a way that the first gate assembly is operable to substantially prevent a gas from passing through the first gate assembly.

3. The port assembly of claim 1, wherein the second gate assembly is configurable to transition to the closed position in such a way that the second gate assembly is operable to substantially prevent a gas from passing through the second gate assembly.

4. The port assembly of claim 1, wherein:  
the first gate assembly includes a first expandable portion, the first expandable portion configurable to expand when the first gate assembly is configured to the closed position; and  
when the first gate assembly is configured to the closed position, the first expandable portion is operable to substantially block a gas from passing through the first gate assembly.

5. The port assembly of claim 4, wherein:  
the first expandable portion includes a plurality of first expandable members arranged around a portion of the first end channel; and  
the plurality of first expandable members are operable to cooperate to substantially block the gas from passing through the first gate assembly when the first gate assembly is configured to the closed position.

6. The port assembly of claim 1, wherein:  
the second gate assembly includes a second expandable portion, the second expandable portion configurable to expand when the second gate assembly is configured to the closed position; and  
when the second gate assembly is configured to the closed position, the second expandable portion is operable to substantially block a gas from passing through the second gate assembly.

7. The port assembly of claim 6, wherein:  
the second expandable portion comprises a plurality of second expandable members arranged around a portion of the second end channel; and  
the plurality of second expandable members are operable to cooperate to substantially block the gas from passing through the second gate assembly when the second gate assembly is configured to the closed position.

8. The port assembly of claim 1, further comprising a mid section between the first end section and the second end section, the mid section having a mid section channel substantially aligned with the first end channel and the second end channel;

wherein the mid section channel is operable to cooperate with the first gate assembly and the second gate assembly to function as an isolation chamber for an instrument when the instrument is transported between the first end section and second end section.

9. The port assembly of claim 1, further comprising a controller, the controller operable to configure one or more of the following:

the first gate assembly to be in the closed position and/or open position; and/or  
the second gate assembly to be in the closed position and/or open position.

30

10. The port assembly of claim 1, further comprising an external anchor assembly, the external anchor assembly configurable to secure to the first end section.

11. A port assembly, the port assembly comprising:  
an elongated structure having a center channel formed through the elongated structure, the elongated structure having:

a first gate assembly provided in the center channel at a first end of the elongated structure, the first gate assembly configurable to transition between an open position to allow access through the first gate assembly and a closed position to prevent access through the first gate assembly; and

a second gate assembly provided in the center channel at a second end of the elongated structure, the second end of the elongated structure opposite to the first end of the elongated structure, the second gate assembly configurable to transition between an open position to allow access through the second gate assembly and a closed position to prevent access through the second gate assembly.

12. The port assembly of claim 11, wherein the first gate assembly is configurable to transition to the closed position in such a way that the first gate assembly is operable to substantially prevent a gas from passing through the first gate assembly.

13. The port assembly of claim 11, wherein the second gate assembly is configurable to transition to the closed position in such a way that the second gate assembly is operable to substantially prevent a gas from passing through the second gate assembly.

14. The port assembly of claim 11, wherein:  
the first gate assembly includes a first expandable portion, the first expandable portion configurable to expand when the first gate assembly is configured to the closed position; and

when the first gate assembly is configured to the closed position, the first expandable portion is operable to substantially block a gas from passing through the first gate assembly.

15. The port assembly of claim 14, wherein:  
the first expandable portion includes a plurality of first expandable members arranged around an interior of the center channel; and

the plurality of first expandable members are operable to cooperate to substantially block the gas from passing through the first gate assembly when the first gate assembly is configured to the closed position.

16. The port assembly of claim 11, wherein:  
the second gate assembly includes a second expandable portion, the second expandable portion configurable to expand when the second gate assembly is configured to the closed position; and

when the second gate assembly is configured to the closed position, the second expandable portion is operable to substantially block a gas from passing through the second gate assembly.

17. The port assembly of claim 16, wherein:  
the second expandable portion comprises a plurality of second expandable members arranged around an interior of the center channel; and

the plurality of second expandable members are operable to cooperate to substantially block the gas from passing through the second gate assembly when the second gate assembly is configured to the closed position.

## 31

18. The port assembly of claim 11, further comprising a controller, the controller operable to configure one or more of the following:

the first gate assembly to be in the closed position and/or open position; and/or

the second gate assembly to be in the closed position and/or open position.

19. A port assembly, the port assembly comprising:

an elongated structure having a first end and a second end opposite to the first end, the elongated structure having a center channel formed throughout the elongated structure between the first end and second end, the elongated structure having:

a gate assembly provided in the center channel, the gate assembly configurable to transition between an open position to allow access through the gate assembly and a closed position to prevent access through the gate assembly;

wherein the gate assembly includes an expandable portion, the expandable portion configurable to expand when the gate assembly is configured to the closed position.

## 32

20. The port assembly of claim 19, wherein the gate assembly is provided at the first end of the elongated structure.

21. The port assembly of claim 19, wherein the gate assembly is configurable to transition to the closed position in such a way that the gate assembly is operable to substantially prevent a gas from passing through the gate assembly.

22. The port assembly of claim 19, wherein:

the expandable portion includes a plurality of expandable members arranged around an interior of the center channel; and

the plurality of expandable members are operable to cooperate to substantially block a gas from passing through the gate assembly when the gate assembly is configured to the closed position.

23. The port assembly of claim 19, further comprising a controller, the controller operable to configure the gate assembly to be in the closed position and/or open position.

\* \* \* \* \*