



US010054572B2

(12) **United States Patent**
Stark

(10) **Patent No.:** **US 10,054,572 B2**
(45) **Date of Patent:** **Aug. 21, 2018**

(54) **AIR PURIFYING SYSTEM AND A METHOD OF USING THE SAME**

(71) Applicant: **Carrier Corporation**, Farmington, CT (US)

(72) Inventor: **Michael M. Stark**, Boulder, CO (US)

(73) Assignee: **CARRIER CORPORATION**, Farmington, CT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 344 days.

(21) Appl. No.: **14/938,507**

(22) Filed: **Nov. 11, 2015**

(65) **Prior Publication Data**

US 2016/0178586 A1 Jun. 23, 2016

Related U.S. Application Data

(60) Provisional application No. 62/094,738, filed on Dec. 19, 2014.

(51) **Int. Cl.**

G01N 33/00 (2006.01)

B01D 46/44 (2006.01)

(52) **U.S. Cl.**

CPC **G01N 33/0004** (2013.01); **B01D 46/442** (2013.01)

(58) **Field of Classification Search**

CPC B01D 46/442; G05F 1/66; G01N 33/0004
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,406,367 B1 6/2002 Chou et al.
7,201,787 B2 4/2007 Choi et al.

7,292,338 B2 11/2007 Itagaki
7,366,588 B2 4/2008 Kim et al.
7,632,178 B2 12/2009 Meneely, Jr.
7,679,879 B2 3/2010 Furuhashi et al.
8,157,892 B2 4/2012 Meirav
8,211,208 B2 7/2012 Chan et al.
8,596,078 B2 12/2013 Williams et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 102636621 A 8/2012
CN 202802276 U 3/2013

(Continued)

OTHER PUBLICATIONS

Product page on www.grainger.com for the Dayton Humidifier Control, Plug in, 120 V, dated Oct. 18, 2014, retrieved by the Internet Archive Wayback Machine.*

(Continued)

Primary Examiner — Robert Clemente


(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(57)

ABSTRACT

An air quality sensor assembly including a controller, a switching device in communication with the controller, a power receptacle in communication with the switching device, and at least one air quality sensor in communication with the controller, wherein the at least one air quality sensor is configured to measure an air quality value. A method of operating an air purifying system within an interior space of a structure, the method comprising the steps of: operating the controller to create an air purifying condition, determining whether the air purifying condition is present, operating the switching device in a first state if the air purifying condition is present.

23 Claims, 3 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

8,607,616	B2	12/2013	Marra	
2008/0092745	A1	4/2008	Tsao et al.	
2013/0038470	A1	2/2013	Niemeyer et al.	
2013/0174646	A1	7/2013	Martin	
2013/0178987	A1	7/2013	Meirav et al.	
2013/0295835	A1	11/2013	Fleischer et al.	
2013/0309154	A1	11/2013	Call et al.	
2014/0260692	A1	9/2014	Sharp	
2014/0266669	A1	9/2014	Fadell et al.	
2014/0277625	A1	9/2014	Gettings et al.	
2015/0088331	A1*	3/2015	Fiedler	G05F 1/66 700/295

FOREIGN PATENT DOCUMENTS

CN	203036776	U	7/2013
CN	203258769	U	10/2013
CN	203414451	U	1/2014
CN	203552012	U	4/2014
CN	103925676	A	7/2014
CN	203687231	U	7/2014

OTHER PUBLICATIONS

Wayback Machine search results for the Dayton Humidifier Control, Plug In, 120 V product page showing archived date of Oct. 18, 2014.*

Friedrich, 5-Stage Air Purifier, Retail Air Purifier Brochure, 2014.
FELLOWES®, Portable Room Air Cleaners (Air Purifiers) : Fellowes AeraMax 100 Air Purifier, Cert. No. AAFC:1209/13/08/01/2080, Feb. 22, 2013.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

1

AIR PURIFYING SYSTEM AND A METHOD OF USING THE SAME

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is related to, and claims the priority benefit of, U.S. Provisional Patent Application Ser. No. 62/094,738 filed Dec. 19, 2014, the contents of which are hereby incorporated in their entirety into the present disclosure.

TECHNICAL FIELD OF THE DISCLOSED EMBODIMENTS

The presently disclosed embodiments generally relate to air purification systems, and more particularly, to an air purifying system and a method of using the same.

BACKGROUND OF THE DISCLOSED EMBODIMENTS

Generally, air purifiers and air purification systems designed to remove particulate matter from the air do not naturally provide feedback to a user as it relates to effectiveness. Generally, particulate removal equipment lack a natural feedback and users desire to have acknowledgment that the air purification system is properly operating. There is therefore a need for an air purification system that provides a natural feedback of proper operation.

SUMMARY OF THE DISCLOSED EMBODIMENTS

In one aspect, an air quality sensor assembly is provided. The air quality sensor assembly includes a controller, a switching device in communication with the controller, a power receptacle in communication with the switching device, and at least one air quality sensor in communication with the controller, wherein the at least one air quality sensor is configured to measure an air quality value

In one embodiment, the air quality sensor assembly is configured to operate the switching device when an air purifying condition is present. In one embodiment, the air quality sensor assembly includes a display in communication with the controller.

In one aspect, an air purifying system is provided. The air purifying system includes an air purifying device operably coupled to the air quality sensor assembly. In one embodiment, the air purifying device includes a power plug, wherein the power plug is configured to engage the power receptacle of the air quality sensor assembly.

In one aspect, a method of operating the air purifying system is provided. The method includes the step of operating the controller to create an air purifying condition. In one embodiment, the air purifying condition is based at least in part on a desired air quality value. In one embodiment the desired air quality value is adjustable. In another embodiment, the air purifying condition is based at least in part on at least one user defined time. In one embodiment, the at least one user defined time is adjustable.

The method further includes the step of determining whether an air purifying condition is present. In one embodiment, determining whether the air purifying condition is present includes operating the at least one air quality sensor to measure an interior space air quality value; then, the air purifying condition is present when the interior space air

2

quality value is greater than or equal to the desired air quality value. If the air purifying condition is present, the method proceeds to step of operating the switching device in a first state. In one embodiment, operating the switching device in a first state includes allowing power to flow to the power receptacle.

If the air purifying condition is not present, the method proceeds to the step of operating the switching device in a second state. In one embodiment, operating the switching device in a second state includes removing power from the power receptacle.

BRIEF DESCRIPTION OF THE DRAWINGS

The embodiments and other features, advantages and disclosures contained herein, and the manner of attaining them, will become apparent and the present disclosure will be better understood by reference to the following description of various exemplary embodiments of the present disclosure taken in conjunction with the accompanying drawings, wherein:

FIG. 1 illustrates a schematic diagram of an air quality sensor assembly according to an embodiment of the present disclosure; assembly;

FIG. 2 illustrates a schematic diagram of an air purifying system according to an embodiment of the present disclosure; and

FIG. 3 illustrates a schematic block diagram of a method of operating an air purifying system within an interior space of a structure to an embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE DISCLOSED EMBODIMENTS

For the purposes of promoting an understanding of the principles of the present disclosure, reference will now be made to the embodiments illustrated in the drawings, and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of this disclosure is thereby intended.

FIG. 1 illustrates an embodiment of an air quality sensor assembly, generally indicated at 10. The air quality sensor assembly 10 includes a controller 12, at least one air quality sensor 14 in communication with the controller 12, and a switching device 16 in communication with the controller 12. The air quality sensor assembly 10 further includes a power receptacle 18 including a first mating end 20 and a second mating end (not shown), wherein the power receptacle 18 is in communication with the switching device 16. The power receptacle 18 is configured to engage a power plug through the first mating end 20, and engage a wall outlet plug through the second mating end (not shown) to provide power to an air purifying device 36 (See FIG. 2).

The controller 12 is configured to send and receive electrical signals to other components within the air quality sensor assembly 10. The controller 12 is also configured to allow a user to set a desired air quality value. In one embodiment, the desired air quality value is adjustable.

The at least one air quality sensor 14 is configured to detect and measure an air quality value based at least in part on the number of particles detected within the general vicinity of the at least one air quality sensor 14. For example, the at least one air quality sensor 14 may detect and measure dust and volatile organic compounds to name a couple of non-limiting examples. It will be appreciated that the at least one air quality sensor 14 may include an optical sensor for detecting particles. It will also be appreciated that the at least

one air quality sensor **14** may detect any such particles that deteriorate the air quality within the interior space **32** (See FIG. **2**). The at least one air quality sensor **12** communicates the measured air quality value to the controller **12** in order to determine whether to operate the switching device **16**. The switching device **16** is configured to alternate between an open and closed state to provide electrical power to the power receptacle **18**. For example, when the measured air quality value is greater than or equal to the desired air quality value, the at least one air quality sensor **14** sends a signal to the controller **12**, the controller **12** then sends a signal to the switching device **16** to change from an open state to a closed state. When the measured air quality value becomes lower than to the desired air quality value, the at least one air particle sensor **14** sends a signal to the controller **12**, the controller **12** then sends a signal to the switching device **16** to change from a closed to an open state. It will be appreciated that the at least one air quality sensor **14** may send a signal directly to the switching device **16**.

In one embodiment, the air quality sensor assembly **10** includes a display **22** in communication with the controller **12**. The display **22** is configured to provide an indication to an occupant of the structure **34** (See FIG. **2**) of the current level of particles within the interior space **32**. For example, the display **22** may include a liquid crystal display (LCD) to provide a numerical value indicative of number of particles within the interior space **32**, or the display **22** may include a colored light emitting diode (LED) to indicate whether the measured particles within the interior space are above or below the desired air quality value, to name a couple of non-limiting examples. The display **22** may also be used to provide a visual feedback to the user when setting the desired air quality value.

FIG. **2** illustrates an embodiment of an air purifying system generally indicated at **30**. The air purifying system **30** is configured to improve the indoor air quality of an interior space **32** within a structure **34**. The air purifying system **30** includes an air purifying device **36** operably coupled to the air quality sensor assembly **10**. The air purifying device **36** is configured to allow air within the interior space **32** to circulate therethrough. The air purifying system **10** further includes an power receptacle **18** in communication with the air purifying device **16**. In one embodiment, the air purifying device **36** includes a power plug **38** in electrical communication with the air purifying device **36** via a power cord **40**, wherein the power plug **38** is configured to engage the power receptacle **18** of the air quality sensor assembly **10**. For example, the power plug **38** may be plugged into the first mating end **20** of the power receptacle **18**; the second mating end (not shown) is plugged into a wall outlet to provide power. It will be appreciated that the air purifying device **36** may be a portable air purifier. This configuration allows for a more flexible solution to remove particles within a particular interior space **32**.

FIG. **3** illustrates a schematic flow diagram of a method **100** of operating the air purifying system **30** within an interior space **32** of a structure **34**. The method **100** includes the step **102** of operating the controller **20** to create an air purifying condition. In one embodiment, the air purifying condition is based at least in part one a desired air quality value. In one embodiment the desired air quality value is adjustable. For example, a user sets a desired air quality value, via the controller **12** within the air quality sensor assembly **10**, indicative of the user's preference of the amount of particles present in the interior space **32**. The desired air quality value may be shown to the user via the display **22**. In another embodiment, the air purifying con-

dition is based at least in part on at least one user defined time. In one embodiment, the at least one user defined time is adjustable. It will be appreciated that the at least one user defined time may include a time of day and/or duration of time, and/or predetermined intervals. For example, the user may set the desired air quality value in accordance to a particular time of day. The user may desire to a lower desired air quality value during periods of time when interior space **32** is occupied, and conversely have a higher desired air quality value when the interior space **32** is unoccupied. In another example, the user may desire to have a higher desired air quality value during sleeping hours such that air purifying device **36** doesn't operate to disrupt the sleep of the user, or the user may desire for the air purifying device **36** to operate at 6:00 pm for a duration of 2 hours, or the user may desire for the air purifying device **36** to operate every 3 hours for 30 minutes.

The method **100** further includes the step **104** of determining whether an air purifying condition is present. In one embodiment, determining whether the air purifying condition is present includes operating the at least one air quality sensor to measure an interior space air quality value; then, the air purifying condition is present when the interior space air quality value is greater than or equal to the desired air quality value. For example value is greater than or equal to the desired air quality value. In another embodiment, the controller **12** compares the measured interior space air quality value to the desired air quality value. If the interior space air quality value is greater than or equal to the desired air quality value, it is an indication that the number of particles within the interior space are outside the user's tolerable threshold.

As a result, the method proceeds to step **106** of operating the switching device **16** in a first state. In one embodiment, operating the switching device **16** in a first state includes allowing power to flow to the power receptacle **18**. For example, when the interior space air quality value is greater than or equal to the desired air quality value, the switching device **16** changes from an open state to a closed state to provide power to the power receptacle **18**. When the air purifying device **36** is plugged into the air quality sensor assembly **10**, air will circulate through the air purifying device **36**; thus, removing particles from the interior space **36**. The method returns to step **104**, until the interior space air quality value is less than the desired air quality value.

If the interior space air quality value is less than the desired air quality value, it is an indication that the number of particles within the interior space are within the user's tolerable threshold, or if the air purifying condition is not present, the method proceeds to step **108** of operating the switching device **16** in a second state. In one embodiment, operating the operating the switching device **16** in a second state includes removing power from the power receptacle **18**. For example, when the interior space air quality value is less than the desired air quality value, the switching device **26** changes from a closed state to an open state to remove power from the power receptacle **18**. The method returns to step **104** to continue determining whether the air purifying condition is present.

It will therefore be appreciated that the present embodiments include an air quality sensor assembly **10** including a switching device **16** in communication with a power receptacle **18** to allow an air purifying device **36** to be plugged in within any interior space **32** to provide a purification system, on an as needed basis, based on particulate or VOC particles detected in an interior space **32**.

5

While the invention has been illustrated and described in detail in the drawings and foregoing description, the same is to be considered as illustrative and not restrictive in character, it being understood that only certain embodiments have been shown and described and that all changes and modifications that come within the spirit of the invention are desired to be protected.

What is claimed is:

1. An air quality sensor assembly comprising:
a controller;
a switching device in communication with the controller;
a power receptacle in communication with the switching device; and
at least one air quality sensor in communication with the controller, wherein the at least one air quality sensor is configured to measure an air quality value based on a number of particles detected by the at least one air quality sensor.
2. The air quality sensor assembly of claim 1, wherein the air quality sensor assembly is configured to operate the switching device when the air quality value is greater than or equal to a desired air quality value.
3. The air quality sensor assembly of claim 1, wherein the air quality sensor assembly is configured to operate the switching device based upon at least one user defined time.
4. The air quality sensor assembly of claim 1, further comprising a display in communication with the controller.
5. The air quality sensor assembly of claim 2, wherein the desired air quality value is adjustable.
6. The air quality sensor assembly of claim 3, wherein the at least one user defined time is adjustable.
7. An air purifying system comprising:
an air purifying device; and
an air quality sensor assembly operably coupled to the air purifying device, the air quality sensor assembly comprising:
a controller;
a switching device in communication with the controller;
a power receptacle in communication with the switching device;
at least one air quality sensor in communication with the controller, wherein the at least one air quality sensor is configured to measure an air quality value based on a number of particles detected by the at least one air quality sensor.
8. The air purifying system of claim 7, wherein the air quality sensor assembly is configured to operate the switching device when the air quality value is greater than or equal to a desired air quality value.
9. The air purifying system of claim 8, wherein the air quality sensor assembly is configured to operate the switching device based upon at least one user defined time.

6

10. The air purifying system of claim 8, wherein the air quality sensor assembly further comprises a display in communication with the controller.

11. The air purifying system of claim 7, wherein the air purifying device comprises a power plug, wherein the power plug is configured to engage the power receptacle.

12. The air purifying system of claim 8, wherein the desired air quality value is adjustable.

13. The air purifying system of claim 9, wherein the at least one user defined time is adjustable.

14. A method of operating an air purifying system within an interior space of a structure, wherein the air purifying system includes an air purifying device operably coupled to an air quality sensor assembly, the air quality sensor assembly including a controller, a switching device in communication with the controller, a power receptacle in communication with the switching device, and at least one air quality sensor in communication with the controller, wherein the at least one air quality sensor is configured to measure an air quality value, the method comprising the steps of:

- (a) operating the controller to create an air purifying condition;
- (b) determining whether the air purifying condition is present based on a number of particles detected by the at least one air quality sensor; and
- (c) operating the switching device in a first state if the air purifying condition is present.

15. The method of claim 14, further comprising:

- (d) operating the switching device in a second state if the air purifying condition is not present.

16. The method of claim 14, wherein the air purifying condition is based at least in part on a desired air quality value.

17. The method of claim 16, wherein the desired air quality value is adjustable.

18. The method of claim 17, wherein the step (b) further comprises operating the at least one air quality sensor to measure an interior space air quality value.

19. The method of claim 18 wherein the air purifying condition is present when the interior space air quality value is greater than or equal to the desired air quality value.

20. The method of claim 14, wherein the air purifying condition is based at least in part on at least one user defined time.

21. The method of claim 20, wherein the at least one user defined time is adjustable.

22. The method of claim 14, wherein operating the switching device in a first state comprises allowing power to flow to the power receptacle.

23. The method of claim 15, wherein operating the switching device in a second state comprises removing power from the power receptacle.

* * * * *