

US010055798B2

(12) **United States Patent**  
**Bowles et al.**

(10) **Patent No.:** **US 10,055,798 B2**  
(45) **Date of Patent:** **Aug. 21, 2018**

(54) **KIOSK FOR RECYCLING ELECTRONIC DEVICES**

(58) **Field of Classification Search**  
CPC . H04M 1/24; G06Q 10/30; B03C 1/03; G07F 17/3297

(75) Inventors: **Mark Vincent Bowles**, La Jolla, CA (US); **Thomas L. Tullie**, Rancho Santa Fe, CA (US); **John Andrew Beane**, San Diego, CA (US); **Jeff Ploetner**, San Diego, CA (US); **John Miller**, San Diego, CA (US); **Neil Vesco**, San Diego, CA (US)

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,808,439 A 4/1974 Renius  
4,248,334 A 2/1981 Hanley et al.  
(Continued)

(73) Assignee: **ecoATM, LLC**, San Diego, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

CN 1365479 8/2002  
CN 2708415 7/2005  
(Continued)

(21) Appl. No.: **13/438,924**

(22) Filed: **Apr. 4, 2012**

(65) **Prior Publication Data**

US 2012/0191562 A1 Jul. 26, 2012

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 12/785,465, filed on May 23, 2010, now Pat. No. 8,200,533, (Continued)

(51) **Int. Cl.**  
**G06Q 50/00** (2012.01)  
**G06Q 10/00** (2012.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **G06Q 50/00** (2013.01); **G06Q 10/00** (2013.01); **G06Q 10/30** (2013.01); **G06Q 30/00** (2013.01);  
(Continued)

OTHER PUBLICATIONS

PCT Intl. Search Report and Written Report for PCT/US2013/023717 filed Jan. 30, 2013.  
(Continued)


*Primary Examiner* — Jan P Mincarelli

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(57) **ABSTRACT**

A recycling kiosk for recycling and financial remuneration for submission of an electronic device such as a mobile phone is disclosed herein. The recycling kiosk includes electrical connectors and an inspection area with an upper chamber, a lower chamber, a transparent plate and at least one camera in order to perform a visual analysis and an electrical analysis of the electronic device for determination of a value of the electronic device. The recycling kiosk also includes a processor and a display for user interaction.

**25 Claims, 15 Drawing Sheets**



**Related U.S. Application Data**

which is a continuation-in-part of application No. 12/727,624, filed on Mar. 19, 2010, now Pat. No. 7,881,965, which is a continuation-in-part of application No. 12/573,089, filed on Oct. 2, 2009, now Pat. No. 8,195,511.

- (60) Provisional application No. 61/472,611, filed on Apr. 6, 2011, provisional application No. 61/102,304, filed on Oct. 2, 2008, provisional application No. 61/183,510, filed on Jun. 2, 2009.

(51) **Int. Cl.**

**G06Q 30/00** (2012.01)

**G06Q 30/02** (2012.01)

**G06Q 30/08** (2012.01)

**H04M 1/02** (2006.01)

**G07F 7/06** (2006.01)

**H04M 1/24** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G06Q 30/0278** (2013.01); **G06Q 30/08** (2013.01); **G07F 7/06** (2013.01); **H04M 1/0287** (2013.01); **H04M 1/24** (2013.01); **Y02W 90/20** (2015.05)

(58) **Field of Classification Search**

USPC ..... 705/1.1

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,519,522 A \* 5/1985 McElwee ..... G07F 11/54  
221/13

4,593,820 A 6/1986 Antonie et al.

4,870,357 A 9/1989 Young et al.

4,878,736 A 11/1989 Hekker et al.

4,927,051 A \* 5/1990 Falk et al. .... 221/12

4,951,308 A 8/1990 Bishop et al.

5,077,462 A \* 12/1991 Newell ..... G07F 11/52  
235/375

5,091,773 A 2/1992 Fouche et al.

5,105,149 A 4/1992 Tokura

5,280,170 A 1/1994 Baldwin et al.

5,339,096 A 8/1994 Beaufort et al.

5,419,438 A \* 5/1995 Squyres ..... B07C 5/3427  
209/3.1

5,570,920 A 11/1996 Crisman et al.

5,572,444 A 11/1996 Lentz et al.

5,610,710 A 3/1997 Canfield et al.

5,717,780 A 2/1998 Mitsumune et al.

5,748,084 A 5/1998 Isikoff

5,775,806 A 7/1998 Allred

5,839,058 A 11/1998 Phillips et al.

5,949,901 A 9/1999 Nichani et al.

5,965,858 A \* 10/1999 Suzuki ..... G07C 3/00  
209/630

5,966,654 A 10/1999 Croughwell et al.

5,987,159 A 11/1999 Nichani

5,988,431 A \* 11/1999 Roe ..... G11B 17/24  
221/123

6,029,851 A 2/2000 Jenkins et al.

6,041,229 A 3/2000 Turner et al.

6,100,986 A 8/2000 Rydningen

6,228,008 B1 \* 5/2001 Pollington ..... B23Q 3/15526  
211/1.52

6,259,827 B1 7/2001 Nichani

6,264,104 B1 7/2001 Jenkins et al.

6,330,354 B1 12/2001 Companion et al.

6,330,958 B1 12/2001 Ruskin et al.

6,393,095 B1 5/2002 Robinson et al.

6,462,644 B1 10/2002 Howell et al.

6,529,837 B1 \* 3/2003 Kang ..... 702/36

6,535,637 B1 3/2003 Wootton et al.

6,587,581 B1 7/2003 Matsuyama et al.

6,595,684 B1 7/2003 Casagrande et al.

6,633,377 B1 10/2003 Weiss et al.

6,667,800 B1 12/2003 Larsson et al.

6,748,296 B2 6/2004 Banerjee et al.

6,754,637 B1 6/2004 Stenz

6,758,370 B2 7/2004 Cooke et al.

6,798,528 B1 9/2004 Hartman

6,822,422 B2 \* 11/2004 Sagawa ..... 320/109

6,842,596 B2 1/2005 Morii et al.

6,854,656 B2 2/2005 Matsumori

7,069,236 B1 6/2006 Tsunenari

7,076,449 B2 7/2006 Tsunenari et al.

7,234,609 B2 6/2007 DeLazzer et al.

7,251,458 B2 7/2007 O'Connell

7,268,345 B2 \* 9/2007 Schultz ..... 250/235

7,334,729 B2 2/2008 Brewington et al.

7,520,666 B2 4/2009 Pevzner et al.

7,567,344 B2 7/2009 LeBlanc et al.

7,646,193 B2 1/2010 Suzuki et al.

7,702,108 B2 4/2010 Amon et al.

7,735,125 B1 6/2010 Alvarez et al.

7,761,331 B2 7/2010 Low et al.

7,783,379 B2 8/2010 Beane et al.

7,848,833 B2 12/2010 Li et al.

7,881,965 B2 2/2011 Bowles et al.

8,019,588 B1 9/2011 Wohlberg et al.

8,025,229 B2 \* 9/2011 Hammond et al. .... 235/385

8,031,930 B2 10/2011 Wang et al.

8,107,243 B2 \* 1/2012 Guccione et al. .... 361/728

8,112,325 B2 2/2012 Foy et al.

8,195,511 B2 6/2012 Bowles et al.

8,200,736 B2 6/2012 Shi et al.

8,215,546 B2 7/2012 Lin et al.

8,239,262 B2 8/2012 Bowles et al.

8,254,883 B2 8/2012 Uchida

8,266,008 B1 9/2012 Siegel et al.

8,423,404 B2 4/2013 Bowles et al.

8,463,646 B2 6/2013 Bowles et al.

8,718,717 B2 5/2014 Vaknin et al.

8,743,215 B1 6/2014 Lee

8,806,280 B2 8/2014 Stephenson et al.

8,823,794 B2 9/2014 Waring et al.

9,043,026 B2 5/2015 Lien et al.

9,189,911 B2 11/2015 Kavli et al.

9,317,989 B2 4/2016 Grow et al.

2001/0039531 A1 11/2001 Aoki

2002/0014577 A1 2/2002 Ulrich et al.

2002/0035515 A1 3/2002 Moreno

2002/0067184 A1 6/2002 Smith et al.

2002/0087413 A1 7/2002 Mahaffy et al.

2002/0112177 A1 8/2002 Voltmer et al.

2002/0157033 A1 10/2002 Cox

2002/0162966 A1 11/2002 Yoder

2002/0186878 A1 12/2002 Hoon et al.

2003/0025476 A1 2/2003 Trela

2003/0036866 A1 2/2003 Nair et al.

2003/0061150 A1 3/2003 Kocher et al.

2003/0146898 A1 8/2003 Kawasaki et al.

2003/0170529 A1 9/2003 Sagawa

2003/0191675 A1 10/2003 Murashita

2003/0204289 A1 \* 10/2003 Banerjee et al. .... 700/241

2004/0012825 A1 1/2004 Tesavis

2004/0088231 A1 5/2004 Davis

2004/0114153 A1 6/2004 Andersen et al.

2004/0141320 A1 \* 7/2004 Bock et al. .... 362/253

2004/0150815 A1 8/2004 Sones et al.

2004/0156557 A1 8/2004 Van Der Weij

2004/0156667 A1 8/2004 Van Der Weij et al.

2004/0186744 A1 9/2004 Lux

2004/0189812 A1 9/2004 Gustavsson et al.

2004/0200902 A1 10/2004 Ishioroshi

2004/0205015 A1 10/2004 DeLaCruz

2004/0235513 A1 11/2004 O'Connell

2004/0242216 A1 12/2004 Boutsikakis

2004/0262521 A1 12/2004 Devitt et al.

2005/0128551 A1 \* 6/2005 Yang ..... 359/214



# US 10,055,798 B2

Page 3

(56)

## References Cited

### U.S. PATENT DOCUMENTS

2005/0143149 A1 6/2005 Becker et al.  
 2005/0167620 A1 8/2005 Cho et al.  
 2005/0187657 A1 8/2005 Hashimoto et al.  
 2005/0216120 A1 9/2005 Rosenberg et al.  
 2005/0222690 A1 10/2005 Wang et al.  
 2005/0231595 A1 10/2005 Wang et al.  
 2005/0240958 A1 10/2005 Nguyen et al.  
 2006/0167580 A1 1/2006 Whittier  
 2006/0038114 A9 2/2006 Cofer et al.  
 2006/0085158 A1 4/2006 Cakiner  
 2006/0184379 A1 8/2006 Tan et al.  
 2006/0195384 A1 8/2006 Bauer et al.  
 2006/0229108 A1 10/2006 Gehelnik  
 2006/0235747 A1 10/2006 Hammond et al.  
 2006/0279307 A1\* 12/2006 Wang et al. .... 324/763  
 2006/0280356 A1 12/2006 Yamagashi  
 2007/0057815 A1 3/2007 Foy et al.  
 2007/0129906 A1 6/2007 Stoecker et al.  
 2007/0133844 A1 6/2007 Waehner et al.  
 2007/0140310 A1 6/2007 Rolton et al.  
 2007/0150403 A1\* 6/2007 Mock et al. .... 705/37  
 2007/0205751 A1 9/2007 Suzuki et al.  
 2007/0263099 A1 11/2007 Motta et al.  
 2007/0276911 A1 11/2007 Bhumkar et al.  
 2007/0281734 A1\* 12/2007 Mizrachi ..... 455/550.1  
 2008/0004828 A1 1/2008 Mizrachi  
 2008/0027581 A1 1/2008 Saether et al.  
 2008/0033596 A1 2/2008 Fausak et al.  
 2008/0097770 A1 4/2008 Low et al.  
 2008/0109746 A1 5/2008 Mayer  
 2008/0111989 A1 5/2008 Dufour et al.  
 2008/0149720 A1 6/2008 Colville et al.  
 2008/0177598 A1 7/2008 Davie  
 2008/0207198 A1 8/2008 Juric  
 2008/0231113 A1 9/2008 Guccione et al.  
 2008/0255901 A1 10/2008 Carroll et al.  
 2008/0256008 A1 10/2008 Kwok  
 2008/0281691 A1 11/2008 Pearson et al.  
 2008/0296374 A1 12/2008 Gonen et al.  
 2008/0303915 A1 12/2008 Omi  
 2009/0051907 A1\* 2/2009 Li et al. .... 356/218  
 2009/0078775 A1 3/2009 Giebel et al.  
 2009/0079388 A1 3/2009 Reddy  
 2009/0177319 A1 7/2009 Garibaldi et al.  
 2009/0184865 A1 7/2009 Valo et al.  
 2009/0187491 A1 7/2009 Bull et al.  
 2009/0190142 A1 7/2009 Taylor et al.  
 2009/0247133 A1 10/2009 Holmen et al.  
 2009/0251815 A1\* 10/2009 Wang ..... G01N 21/95  
 360/31  
 2009/0262341 A1 10/2009 Konopa et al.  
 2009/0265035 A1 10/2009 Jenkinson et al.  
 2009/0299543 A1 12/2009 Cox et al.  
 2009/0312009 A1\* 12/2009 Fishel ..... 455/425  
 2009/0321511 A1 12/2009 Browne  
 2010/0005004 A1 1/2010 Hudak et al.  
 2010/0051695 A1 3/2010 Yepez et al.  
 2010/0063894 A1 3/2010 Lundy et al.  
 2010/0088192 A1 4/2010 Bowles et al.  
 2010/0110174 A1 5/2010 Leconte et al.  
 2010/0115887 A1 5/2010 Schroeder et al.  
 2010/0147953 A1\* 6/2010 Barkan ..... 235/462.41  
 2010/0161397 A1 6/2010 Gauthier et al.  
 2010/0169231 A1 7/2010 Bowles et al.  
 2010/0219234 A1 9/2010 Forbes  
 2010/0228676 A1 9/2010 Librizzi et al.  
 2010/0235198 A1 9/2010 Fini et al.  
 2010/0237854 A1 9/2010 Kumhyr et al.  
 2010/0262481 A1 10/2010 Baker et al.  
 2011/0060641 A1 3/2011 Grossman et al.  
 2011/0067520 A1 3/2011 Ihrke et al.  
 2011/0235853 A1 9/2011 Bowles et al.  
 2012/0016518 A1 1/2012 Saario et al.  
 2012/0029985 A1 2/2012 Wilson et al.  
 2012/0030097 A1 2/2012 Hagan et al.

2012/0054113 A1 3/2012 Jayaraman et al.  
 2012/0078413 A1\* 3/2012 Baker, Jr. .... G07F 17/12  
 700/232  
 2012/0117001 A1\* 5/2012 Gventer ..... G06F 17/30073  
 705/500  
 2012/0146956 A1 6/2012 Jenkinson  
 2012/0254046 A1 10/2012 Librizzi et al.  
 2012/0280934 A1 11/2012 Ha et al.  
 2012/0301009 A1 11/2012 Dabic  
 2013/0046611 A1 2/2013 Bowles et al.  
 2013/0046699 A1 2/2013 Bowles et al.  
 2013/0124426 A1 5/2013 Bowles et al.  
 2013/0126741 A1 5/2013 Srivastava et al.  
 2013/0144797 A1 6/2013 Bowles et al.  
 2013/0173434 A1 7/2013 Hartman  
 2013/0191236 A1 7/2013 Bowles  
 2013/0198089 A1 8/2013 Bowles  
 2013/0198144 A1 8/2013 Bowles  
 2013/0226679 A1 8/2013 Bowles  
 2013/0253700 A1\* 9/2013 Carson ..... G07F 9/006  
 700/236  
 2013/0275314 A1 10/2013 Bowles  
 2013/0284805 A1 10/2013 Kraft et al.  
 2013/0290146 A1 10/2013 West et al.  
 2013/0297388 A1 11/2013 Kyle, Jr. et al.  
 2014/0012643 A1 1/2014 Behrisch  
 2014/0067710 A1 3/2014 Gventer et al.  
 2014/0080550 A1 3/2014 Ino et al.  
 2014/0143161 A1 5/2014 Ahn  
 2014/0156883 A1 6/2014 Bowles  
 2014/0214505 A1 7/2014 Shuster-Arechiga et al.  
 2015/0066677 A1 3/2015 Bowles et al.  
 2016/0284019 A1 9/2016 Bowles et al.  
 2016/0328684 A1 11/2016 Bowles et al.

### FOREIGN PATENT DOCUMENTS

CN 1864088 11/2006  
 CN 1957320 5/2007  
 CN 200965706 Y 10/2007  
 CN 102246384 11/2011  
 CN 202351953 U 7/2012  
 CN 202394296 U 8/2012  
 CN 102654927 A 9/2012  
 CN 102812500 12/2012  
 CN 102930642 A 2/2013  
 CN 102976004 A 3/2013  
 CN 103198562 A 7/2013  
 CN 103226870 A 7/2013  
 CN 203242065 U 10/2013  
 CN 103440607 A 12/2013  
 CN 103544772 A 1/2014  
 CN 203408902 U 1/2014  
 CN 103662541 A 3/2014  
 CN 103679147 A 3/2014  
 CN 203520502 U 4/2014  
 CN 203588366 U 5/2014  
 EP 1168253 A1 1/2002  
 EP 1703436 9/2006  
 JP 07-112801 5/1995  
 JP H07334583 A 12/1995  
 JP 2000-121564 A 4/2000  
 JP 2002019147 A 1/2002  
 JP 2002183286 A 6/2002  
 JP 2002-259528 A 9/2002  
 JP 2002302252 A 10/2002  
 JP 2002324264 A 11/2002  
 JP 2002358354 A 12/2002  
 JP 2003139516 5/2003  
 JP 2003230229 8/2003  
 JP 2003242243 A 8/2003  
 JP 2003-267509 A 9/2003  
 JP 2003264007 A 9/2003  
 JP 2004021569 A 1/2004  
 JP 2004-303102 A 10/2004  
 JP 2004288143 A 10/2004  
 JP 2004341681 A 12/2004  
 JP 2006127308 A 5/2006  
 JP 2006195814 A 7/2006



(56)

**References Cited**

## FOREIGN PATENT DOCUMENTS

JP	2006227764	A	8/2006	
JP	2006260246	A	9/2006	
JP	2007141266	A	6/2007	
JP	2007155455		6/2007	
JP	2007179516	A	7/2007	
JP	2007-265340	A	10/2007	
JP	2008522299	A	6/2008	
JP	2008293391	A	12/2008	
JP	2007-086725		4/2009	
JP	2009245058	A	10/2009	
JP	2009250971		10/2009	
JP	2010177720	A	8/2010	
JP	2012058932	A	3/2012	
JP	2013033361	A	2/2013	
JP	2013037441	A	2/2013	
JP	2013531823		8/2013	
KR	20000064168		11/2000	
KR	20130085255	A	7/2013	
KR	20140037543	A	3/2014	
WO	0115096		3/2001	
WO	WO-01/15096	A1	3/2001	
WO	0205176		1/2002	
WO	WO-2002039357	A1	5/2002	
WO	WO-2003012717	A1	2/2003	
WO	WO-2003014994	A1	2/2003	
WO	WO-2004021114	A2	3/2004	
WO	WO04114490	A1 *	12/2004	..... H02G 11/02
WO	2005008566		1/2005	
WO	WO-2005101346	A1	10/2005	
WO	2006058601		6/2006	
WO	WO-2006080851	A2	8/2006	
WO	09128173		10/2009	
WO	2009128173		10/2009	
WO	2009129526		10/2009	
WO	WO-2010/040116	A1	4/2010	
WO	WO-2010128267	A1	11/2010	
WO	WO-2010128315	A1	11/2010	
WO	WO-2011131016	A1	10/2011	
WO	WO-2012/138679	A1	10/2012	
WO	WO-2013074819	A1	5/2013	

## OTHER PUBLICATIONS

PCT International Search Report for PCT Application PCT/US2012/061587, Intl. Filing Date Oct. 24, 2012.

Evegenii Masunov, Mar. 25, 2010.

Rehg et al., Vision for a Smart Kiosk, 1997 IEEE Computer Society Conference on Computer Vision and Pattern Recognition.

PCT International Search Report for PCT Application No. PCT/US2011/028251, Intl. Filing Date Mar. 13, 2011.

Rolf Steinhilper, "Remanufacturing: The Ultimate Form of Recycling", Fraunhofer IRB Verlag, 1998, parts 1-3, [http://www.reman.org/Publications\\_main.htm](http://www.reman.org/Publications_main.htm).

PCT International Search Report and Written Opinion for PCT Application No. PCT/US09/59461, Intl. Filing Date Oct. 2, 2009.

PCT International Search Report for PCT Application PCT/US2012/032042, Intl. Filing Date Apr. 4, 2012.

Aftermarket Cellular Accessories, "Cellular Phone Model Identification," retrieved from <http://web.archive.org/web/20060328064957/http://aftermarketcellular.com/ic/identification.html> on Mar. 16, 2014, published Mar. 28, 2006, 3 pages.

Altec Lansing User's Guide 2007, 8 pages.

Business Wire, "The World's First Office Photography Machine" at CES 2008 Launched by Ortery technologies, Jan. 7, 2008, 3 pages.

Examination Report for Canadian Application No. 2,739,633, dated Dec. 6, 2013, 3 pages.

International Numbering Plan, [www.numberingplans.com](http://www.numberingplans.com), 2 pages.

Office Action dated Apr. 8, 2013 or Chinese Application No. 200980148240.3, 12 pages.

Office Action dated Jan. 13, 2014 or Chinese Application No. 200980148240.3, 13 pages.

Office Action dated Aug. 6, 2013 in Japanese Patent Application No. 2011530284, 7 pages.

Office Action dated Jul. 1, 2014 in Japanese Patent Application No. 2011530284, 4 pages.

Office Action dated Sep. 3, 2012 in European Patent Application No. 09818605.9, 7 pages.

PCT International Search Report and Written Opinion dated Apr. 3, 2014 for PCT/US2013/072697 filed Dec. 2, 2013, 7 pages.

PCT International Search Report and Written Opinion dated Jul. 18, 2014 for PCT Application No. PCT/US2014/024551, filed Mar. 12, 2014, 11 pages.

Rawson, Chris, "TUAW: 25 Ways to Check the Hardware on Your iPhone 4", published Aug. 13, 2010, retrieved at <http://www.tuaw.com/2010/08/13/hardware-test-your-iphone-4/> on Feb. 28, 2014.

Yahoo! Answers, "What is a clean ESN?" published Jun. 23, 2009, retrieved from <http://web.archive.org/web/20090623215042/http://answers.yahoo.com/question/inde,8020US?qid=20080318061012AANFRco> on Apr. 3, 2014.

Co-pending U.S. Appl. No. 14/498,763, filed Sep. 26, 2014.

Co-pending U.S. Appl. No. 14/500,739, filed Sep. 29, 2014.

Co-pending U.S. Appl. No. 14/506,449, filed Oct. 3, 2014.

Co-pending U.S. Appl. No. 14/568,051, filed Dec. 11, 2014.

2006 Florida Statutes Title XXXIII, Chapter 538, Sections 538.03 and 538.04, 7 pages.

GSM Arena Glossary, "LCD (Liquid Crystal Display)", retrieved from <http://www.gsmarena.com/glossary.php3?term=lcd> on Apr. 28, 2016, 1 page.

Perng et al., "A Novel Vision System for CRT Panel Auto-Inspection", Proceedings of the 2005 IEEE International Conference on Mechatronics, Jul. 10-12, 2005, pp. 4.

Perng et al., "A Novel Vision System for CRT Panel Auto-Inspection", Journal of the Chinese Institute of Industrial Engineers, vol. 24, No. 5, pp. 341-350 (2007).

Office Action dated Mar. 14, 2016 in Japanese Application No. 2014-503922, 11 pages.

Office Action dated Mar. 15, 2016 in China Application No. 201280027565.8, 34 pages.

CNET, "Tackling LCD 'burn ins', and dead/stick Pixels", published Sep. 2, 2009, retrieved from <http://www.cnet.com/news/tackling-lcd-burn-ins-and-deadstuck-pixels/>.

Geekanoids, You Tube Video, "Apple iPhone 3GS Unboxing and Review", uploaded on Jun. 19, 2009, retrieved from <http://www.youtube.com/watch?v=GCEi9QAeDqk> on Sep. 2, 2009.

Lambert, Emily, "Use It Up, Wear It Out", Forbes 175.5 (2005): 77-78. Business Source Complete. Web. Jan. 6, 2015, 3 pages.

Littleton Partners with Donations Ink (Jan. 19, 2006) US Fed News Service, Including US State News. Web. Jan. 6, 2015, 1 page.

MobileGazette.com, "2006 in Review: The Good, the Bad and the Ugly", published Dec. 2006, retrieved from <http://www.mobilegazette.com/2006-review-06x12x22.htm> on Nov. 11, 2015.

PC World, "Wipe Your Cell Phone's Memory Before Giving it Away", published Jan. 2006, retrieved from <http://www.washingtonpost.com/wp-dyn/content/article/2006/01/30/AR2006013001144.html> on Nov. 10, 2015.

SimplySellular, "Get Cash for your Old Cell Phone", published Apr. 2, 2010, retrieved from <http://simplysellular.com/conditions.php> on Jan. 6, 2015, 2 pages.

Wilson, Doug, "Liquid Crystal Display (LCD) Inspection System", National Instruments Case Study, available May 10, 2009, retrieved from <http://sine.ni.com/cs/app/cod/p/id/cs-345> on Jan. 5, 2015, 2 pages.

RMS Communications Group, "RMS Communications Group Inc. opens cell phone kiosk at Ocean City Mall in Toms River, N.J.", retrieved from <http://www.prweb.com/releases/2004/11/prweb177351.htm>, Nov. 12, 2004, 2 pages.

Co-Pending U.S. Appl. No. 15/630,460, filed Jun. 22, 2017.

Co-Pending U.S. Appl. No. 15/641,122, filed Jul. 3, 2017.

Co-Pending U.S. Appl. No. 15/641,145, filed Jul. 3, 2017.

Co-Pending U.S. Appl. No. 15/672,157, filed Aug. 8, 2017.

Notice of Allowance dated Jul. 13, 2017 in U.S. Appl. No. 13/792,030, 9 pages.

Notice of Allowance dated Jul. 5, 2017 in U.S. Appl. No. 13/862,395, 9 pages.

(56)

**References Cited**

OTHER PUBLICATIONS

Notice of Allowance dated Sep. 27, 2017 in U.S. Appl. No. 15/641,122, 5 pages.

Notice of Allowance dated Dec. 14, 2017 in U.S. Appl. No. 13/792,030, 5 pages.

Office Action dated Jul. 29, 2013 in U.S. Appl. No. 13/862,395, 19 pages.

Office Action dated Apr. 9, 2014 in U.S. Appl. No. 13/862,395, 26 pages.

Office Action dated Sep. 18, 2015 in U.S. Appl. No. 13/862,395, 29 pages.

Office Action dated Feb. 25, 2016 in U.S. Appl. No. 13/794,816, 76 pages.

Office Action dated Mar. 3, 2017 in U.S. Appl. No. 13/913,408, 29 pages.

Office Action dated Mar. 6, 2015 in U.S. Appl. No. 13/862,395, 29 pages.

Office Action dated Sep. 1, 2017 in U.S. Appl. No. 15/630,460, 23 pages.

Office Action dated Sep. 1, 2017 in U.S. Appl. No. 15/641,145, 20 pages.

Office Action dated Sep. 5, 2017 in U.S. Appl. No. 15/641,122, 7 pages.

Office Action dated Oct. 10, 2017 in U.S. Appl. No. 15/672,157, 18 pages.

Office Action dated Nov. 2, 2017 in U.S. Appl. No. 13/794,816, 75 pages.

Office Action dated Feb. 1, 2018 in U.S. Appl. No. 15/630,460, 24 pages.

\* cited by examiner






FIG. 1




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2






FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3




FIG. 3A






FIG. 3B




FIG. 3C




FIG. 4




FIG. 4A




FIG. 4B






FIG. 4C




FIG. 5






FIG. 6




FIG. 7




FIG. 8




FIG. 9






FIG. 10




FIG. 11




FIG. 12






FIG. 13

## KIOSK FOR RECYCLING ELECTRONIC DEVICES

### CROSS REFERENCES TO RELATED APPLICATIONS

The present application claims priority to U.S. Provisional Patent Application 61/472,611 filed on Apr. 6, 2011, and is also a continuation-in-part application of U.S. patent application Ser. No. 12/785,465 filed on May 23, 2010, which is a continuation-in-part application of U.S. patent application Ser. No. 12/727,624, filed on Mar. 19, 2010, now U.S. Pat. No. 7,881,965, which issued on Feb. 1, 2011, which is a continuation-in-part application of U.S. patent application Ser. No. 12/573,089, filed on Oct. 2, 2009, which claims priority to U.S. Provisional Patent Application 61/102,304 filed on Oct. 2, 2008, now abandoned, and 61/183,510 filed on Jun. 2, 2009, now abandoned, all of which are herein incorporated by reference in their entireties.

### STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not Applicable

### BACKGROUND OF THE INVENTION

#### Field of the Invention

The present invention generally relates to recycling of consumer electronic devices.

#### Description of the Related Art

There has been a large increase in the number of electronic devices used by the typical consumer. These devices include cell phones, PDA's, MP3 players, GPS devices, cameras, beepers, remote controls, cordless phones, calculators, etc. The rapid pace at which new technology and models of electronic devices are introduced creates a situation where many consumers upgrade or replace one or more recyclable device on a frequent basis. Often, the consumer does not dispose of the prior electronic device, but rather just stops using it and begins using the new device. This may happen over several generations of such devices.

In addition to the electronic devices mentioned above, there are many other types of devices that have relatively high frequency replacement rates, including portable mobile electronic devices, such as cell phones, MP3 players, etc, and non-portable electronic devices, such as computers, printers, and the like. In addition to electronic devices, there are content based digital media such as games on CD, DVD, or cartridge, or entertainment mass storage items such as CDs, DVDs, BluRay, etc. There is a need for handling of such items in an ecologically friendly manner, both via recycling or by proper disposal procedures. It has not been convenient for owners of electronic devices to either recycle such devices or to properly dispose of such devices. There is currently little incentive for a device owner to "do the right thing" with a used device. When the owner just stops using a device and simply puts it in storage: the opportunity for recycling or re-use by another party is lost. If the owner just throws the device away in normal trash containers, the proper recycling or safe disposing of the device is thwarted.

One particular problem associated with this phenomenon can be illustrated by an example of mobile phones. There are more than 3.6 billion mobile phone users in the world with an annual growth of 10% per annum. The replacement rate of mobile handsets is roughly every 18 months as new models have more features and new standards evolve. Wire-

less carriers also offer new phones below cost, or free, as incentives to get customers to sign lucrative two-year service contracts ensuring a constant build-up of old mobile phones. Old mobile phones and other mobile devices (pagers, PDAs) present a growing threat to the environment. As of 2007, there are more than 750 million mobile phones waiting to be recycled in the US, either in drawers or already in the waste stream. Another 150+ million or so are added every year. Once in the waste stream, these devices may leak Lead, Mercury, Cadmium, Arsenic and other toxic substances into the water supply. Municipalities often incinerate their waste, instantly putting these toxic elements into the air, and they return to earth in rain water. A problem that needs to be solved is to make it easy and accessible for the public to recycle or resell their mobile phones and other recyclable devices. Two reasons why mobile phones are not being recycled or resold are difficult access to recycling or reselling facilities, and secondly security concerns about the information stored on the mobile phone. In addition to mobile phones, the same problems apply to many other electronic devices.

Technology has not yet provided a resolution to this problem. One invention is Bishop, U.S. Pat. No. 4,951,308 for Automated Vending Of Cellular Hand-Held Telephones And Cellular Telephone Services, which discloses a vending machine that dispenses cellular telephones purchased by consumers through the vending machine. Bishop essentially adds to the problem by making it easier to acquire mobile phones.

Taylor et al., U.S. Patent Publication Number 2009/0190142, for a Method And System For Connecting A Data Storage Device To A Kiosk, discloses a kiosk with a docking port and an optical recognition device for identifying a data port on a data storage device. Taylor is directed at printing digital images at a photo kiosk.

The prior art has failed to recognize the problems associated with recycling mobile phones in a manner that is enticing to a consumer yet financially rewarding to the recycler.

### BRIEF SUMMARY OF THE INVENTION

The present invention enables one to securely recycle, donate, trade-in, and/or sell electronic devices in a publicly accessible location.

One aspect of the present invention is a kiosk for recycling electronic devices such as mobile phones, tablet computers, e-readers, MP3 players, and the like. The kiosk preferably has a housing with a touch screen display for user interaction. The kiosk also has an inspection area defined by an upper chamber, a lower chamber and a transparent plate for transporting an electronic device into the inspection area. The upper and lower chambers preferably have mirrors on interior surfaces along with imaging components such as cameras in order to obtain multi-angled views, or even a 3-D profile, of an electronic device within the inspection area. The kiosk also preferably has a carousel with multiple different electrical connectors in order to electrically connect to an electronic device. The kiosk also preferably has a mechanism for automatically binning the electronic device. The kiosk also has a processor configured to perform visual analysis for identification of the electrical device and to determine a condition of the electrical device, especially a LCD display of the electronic device. Further, the processor is configured to perform an electrical analysis of the electronic device.



3

Another aspect of the present invention a method for analysis of a mobile communication device and financial remuneration to a user for submission of the mobile communication device. The method comprises identifying a mobile communication device, soliciting bids for a used model of the mobile communication device and receiving bids for the used model of the mobile communication device from a plurality of bidders. The method further comprises setting a purchase price to pay for the used model of the mobile communication device based on the plurality of bids received from the plurality of bidders and identifying a used model of the mobile communication device at a recycling kiosk for the mobile communication device. The method further comprises verifying the integrity of the used model of the mobile communication device at the recycling kiosk and offering the purchase price for the used model of the mobile communication device at the kiosk. Additionally, the method comprises purchasing the used model of the mobile communication device. Preferably, the method further comprises automatically binning the mobile communication device after purchasing the used model of the mobile communication device. The method may further comprise instructing the user to erase the data of the used model of the mobile communication device prior to positioning the mobile communication device in the recycling kiosk.

The kiosk of the method comprises a housing, the housing comprising a user interface on an exterior surface of the housing for the user to input information, an upper dome and a lower dome, wherein the upper dome and the lower dome comprise a plurality of mirrors. The kiosk further comprises an upper chamber camera, a lower chamber camera and a transparent surface. The kiosk further comprises a processor within the housing and in communication with the at least one camera, the processor configured to identify the brand and model number of the mobile communication device based on at least one of the information from the user and the images from the at least one camera, the processor configured to determine a purchase price for the used model of the mobile communication device.

Yet another aspect of the present invention is a method for analysis of a mobile electronic device and financial remuneration to a user for submission of the mobile electronic device. The method includes identifying a mobile communication device and a predetermined condition of the mobile communication device. The method also includes soliciting bids for a used model of the mobile communication device in the predetermined condition. The method also includes receiving bids for the used model of the mobile communication device from a plurality of bidders. The method also includes setting a purchase price to pay for the used model of the mobile communication device based on the plurality of bids received from the plurality of bidders. The method also includes identifying a used model of the mobile communication device at a recycling kiosk for the mobile electronic device. The method also includes verifying the integrity of the used model of the mobile communication device at the recycling kiosk. The method also includes offering the purchase price for the used model of the mobile communication device at the kiosk. The method also includes purchasing the used model of the mobile communication device. The method also includes delivering the mobile communication device to a winning bidder.

Yet another aspect of the present invention is a method for analysis of a mobile electronic device and financial remuneration to a user for submission of the mobile electronic device. The method includes establishing a plurality of pre-acquisition purchase prices, each of the plurality of

4

pre-acquisition purchase prices established for a recycled electronic device in a predetermined condition. Each of the pre-acquisition purchase prices established by a winning bid from a bidder of a plurality of bidders for a recycled electronic device. The method also includes positioning an electronic device in an inspection area of a kiosk, the inspection area having at least one camera. The method also includes imaging the electronic device. The method also includes analyzing the electronic device for identification of the electronic device and a condition of the electronic device. The method also includes selecting a matching pre-acquisition purchase price from the plurality of pre-acquisition purchase prices for the electronic device. The method also includes offering a consumer the pre-acquisition purchase price for the electronic device.

Another aspect of the present invention is a method for analysis of an electronic device and financial remuneration to a user for submission of the electronic device. The method comprises positioning an electronic device in an inspection area of a kiosk, the inspection area having a camera. The method further comprises imaging a screen shot of a about page of the electronic device, and inspecting the screen shot of the about page of the electronic device obtained by at least one camera disposed in the inspection area to determine if the electronic device has any defects. The method further comprises determining a value for electronic device. Lastly the method comprises determining a value for the electronic device.

The kiosk of the method comprises a housing, a user interface on an exterior surface of the housing for the user to input information, an upper dome and a lower dome, wherein the upper dome and the lower dome comprise a plurality of mirrors. The kiosk further comprises an upper chamber camera, a lower chamber camera and a transparent surface. The kiosk also comprises a processor within the housing and in communication with the at least one camera, the processor configured to identify the brand and model number of the electronic device based on at least one of the information from the user and the images from the at least one camera, the processor configured to determine a financial remuneration value for the electronic device. Preferably, the method further comprises comparing information derived from the barcode sticker to information derived from the about page.

Yet another aspect of the present invention is a dome shaped apparatus, the dome shaped apparatus comprising an upper dome, a lower dome and the upper and lower dome comprising a plurality of walls, wherein the plurality of walls are composed of mirrors. The dome shaped apparatus further comprises a transparent surface and at least one camera, the camera capable of obtaining a 360 degree view of an electronic device placed within the dome shaped apparatus. The upper dome preferably comprises an upper chamber camera. The lower dome preferably comprises a lower chamber camera. Preferably, a combination of the each of the upper dome and lower dome cameras and the plurality of mirrors allow for an image of the device placed on the transparent surface. Preferably, the combination of the each of the upper dome and lower dome cameras and the plurality of mirrors allow for a 360 degree of the electronic device placed on the transparent surface.

In another aspect of the present invention, the invention comprises a method for analysis of an electronic device and financial remuneration to a user for submission of the electronic device. The method comprises positioning an electronic device in an inspection area of a recycling kiosk 100, wherein the inspection area has a plurality of mirrors.



## 5

The method further comprises placing the electronic device in an illuminated mode wherein a LCD screen of the electronic device is illuminated to visually enhance the appearance of any defects in the LCD screen and inspecting an image of the LCD screen of the electronic device obtained by at least one camera disposed in the inspection area to determine if the LCD screen of the electronic device has any defects. The method further comprises defining an analyzed electronic device. Lastly, the method comprises determining a value for the analyzed electronic device.

In one embodiment of the present invention, the method further comprises performing an electrical analysis of the electronic device. In an alternative embodiment of the present invention, the method further comprises powering up the electronic the device. In yet another embodiment of the present invention the method further comprises measuring the luminescence from the LCD screen of the electronic device.

In one embodiment of the present invention, the method further comprises automatically binning the electronic device after a visual inspection and electrical inspection. Further, the method comprises completing the visual inspection and electrical inspection within an illumination period. The illumination period comprises the time from when the LCD of the phone is initially illuminated to the time the display screen transitions into an energy conserving mode, evidenced by the screen blacking out.

In yet another embodiment, the method comprises positioning an electronic device in an inspection area of a recycling kiosk **100**, powering up the electronic device and inputting a term on the electronic device. The inputted term comprises a plurality of characters and the term is displayed on the LCD screen of the electronic device. The method further comprises inspecting an image of the LCD screen of the electronic device obtained by at least one camera disposed in the inspection area utilizing an optical character recognition program of the recycling kiosk to determine if the LCD screen of the electronic device has any defects. The term is preferably a telephone number, a word or number.

Another aspect of the invention is a dome shaped apparatus comprising a plurality of walls, wherein the plurality of walls composed of mirrors and at least one camera, wherein the camera is capable of obtaining a multiple views of an electronic device placed within the dome shaped apparatus. The invention optionally comprises an electrical connector dispensing device. The electrical connecting dispensing device comprises a cartridge containing a plurality of cables, wherein each of the plurality of cables have an interchangeable connector and wherein each of the cables is automatically retracted after an electrical analysis of an electronic device.

Having briefly described the present invention, the above and further objects, features and advantages thereof will be recognized by those skilled in the pertinent art from the following detailed description of the invention when taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. **1** is a perspective view of a recycling kiosk.  
 FIG. **1A** is a front view of the recycling kiosk of FIG. **1**.  
 FIG. **1B** is an isolated view of a front of the recycling kiosk of FIG. **1**.  
 FIG. **1C** is an isolated view of a front of the recycling kiosk of FIG. **1**.

## 6

FIG. **2** is an isolated view of an electrical connector wheel.

FIG. **2A** is an isolated view of an electrical connector is a staging area.

FIG. **2B** is an isolated view of an electrical connector in a detached position.

FIG. **2C** is an isolated view of an electrical connector being detached.

FIG. **2D** is an isolated view of an electrical connector being retracted.

FIG. **3** is a perspective view of internal components of a kiosk.

FIG. **3A** is a perspective view of internal components of a kiosk.

FIG. **3B** is a perspective view of internal components of a kiosk.

FIG. **3C** is a perspective view of internal components of a kiosk.

FIG. **4** is an isolated view of a phone an inspection plate of a kiosk.

FIG. **4A** is an isolated view of a phone being transferred in the kiosk.

FIG. **4B** is an isolated view of a phone being transferred in the kiosk.

FIG. **4C** is an isolated view of a phone being binned in the kiosk.

FIG. **5** is a block diagram of components of a recycling kiosk.

FIG. **6** is a block diagram of components of a recycling kiosk.

FIG. **7** is an isolated view of an inspection area of a kiosk.

FIG. **8** is an isolated view of a camera in a dome of a kiosk.

FIG. **9** is an isolated view of a phone in an inspection area of a kiosk.

FIG. **10** is a front view of a phone.

FIG. **11** is a front view of a phone connected to an electrical connector.

FIG. **12** is a flow chart for recycling an electronic device.

FIG. **13** is a flow chart for a pre-acquisition auction method.

#### DETAILED DESCRIPTION OF THE INVENTION

As shown in FIGS. **1**, **1A**, **1B** and **1C**, a kiosk for recycling electronic devices and providing financial remuneration is generally designated **100**. The electronic device may be a Smart Phone, mobile phone, tablet computer, IPOD® device, MP3 Player, GPS device, e-reader, etc. The kiosk **100** has a housing **105** in a pseudo-rectangular cube shape. A header **103** allows for marketing and videos. An access door **130** in a front body area **131** provides access to an inspection area **106** for electronic devices. The front of the housing **105** has a display screen **115** for providing information to a user, and acts as a user interface in a touch screen embodiment. The exterior of the housing **105** also preferably has a label printer **125**, a voucher dispenser **126**, a receipt printer **127**, and a cash or card dispenser **128**. The exterior housing may also have a thumbprint reader.

The kiosk **100** allows for automatic visual analysis of an electronic device to identify the electronic device and to determine electronic device is damaged in order to ascertain a value for recycling the electronic device. Further, the kiosk **100** also allows for electrical analysis of the electronic device.



As shown in FIGS. 2, 2A, 2B, 2C and 2D, the kiosk 100 comprises a carousel 500 containing a plurality of electrical connectors 505a-505y. Each of the electrical connectors 505 has a unique connection plug for removable connection to an electronic device. Each of the electrical connectors 505a-505y has a cartridge removeably secured in the carousel 500. Thus, new electrical connectors 505 can be substituted for older electrical connectors 505. Further, the kiosk 100 is designed to allow for automatic removal of the electrical connector 505 using detachment mechanism 511. In FIG. 2A, the electrical connector 505 is in a staging area, where it would be connected to a port of an electrical device (as shown FIG. 11). Next, as shown in FIGS. 2B and 2C, hinged arms 512 of the detachment mechanism 511 engage a moveable member of the electrical connector 505 to force the outward movement of the moveable member and the disconnection of the electrical connector 505 from a port of an electronic device (as shown in FIG. 11). As shown in FIG. 2D, the electrical connector 505 is retracted by a cable from the detachment mechanism 511.

As shown in FIGS. 3, 3A, 3B and 3C, the internal mechanism 101 of the kiosk 100 includes an upper chamber 520, a lower chamber 530, a binning plate 540, a transparent plate 545, tracks 557, a door 550, a bin 555 and the carousel 500. Preferably, the carousel 500 is able to hold approximately 25 electrical connectors 505, wherein the electrical connectors 505 are interchangeable to easily adapt to the variations in USB and other like connections. As shown in FIG. 3B, a mobile phone 150 is placed on the transparent plate 545 and transferred to an inspection area 106 within upper chamber 520 and lower chamber 530. Both the upper chamber and the lower chamber preferably have a bell-like shape. As shown in FIG. 3C, the mobile phone is moved between the upper chamber 520 and the lower chamber 530 for visual analysis. The transparent plate, preferably composed of glass or a transparent plastic material, allows for imaging components within the upper chamber 520 and lower chamber 530 to obtain multiple view images of the mobile phone 150. Preferably, a 3-D profile of the mobile phone is generated in order to provide visual analysis for identification and condition of the mobile phone. Once the visual analysis is complete, the transparent plate 545 moves out from between the upper chamber 520 and lower chamber 530.

FIGS. 4, 4A, 4B, and 4C, show the automatic transport and binning of an electronic device 150 within the internal mechanism 101 of the kiosk 100. As shown in FIG. 4, the door 550 is lowered to reside above the transparent plate 545, which is then moved inward with the mobile phone 150 thereon. As shown in FIG. 4A, as the transparent plate 545 is moved inward, the mobile phone is blocked by the door 550 and engages binning plate 540 as the mobile phone begins to fall into an opening created by the inward movement of the transparent plate 545. As shown in FIG. 4B, once the mobile phone is on the binning plate 540, the binning plate 540 is slowly lowered on one side to open into the bin 555. As shown in FIG. 4C, the mobile phone 150 slowly falls through an opening 556 into the bin 555 to secure the mobile phone 150 and for collection at a later time. The entire process performed at a rate of speed to prevent damage to the electronic device being recycled.

The kiosk 100 is of a typical size and shape of a vending machine, such as a soda machine, coin changing machine, can recycling machine, or other vending machines. The housing 105 of the kiosk 100 protects the internal mechanism 101 and secures electronic devices submitted for recycling. The housing 105 is preferably constructed of a

metal material, such as steel or aluminum, to prevent unauthorized access to the kiosk 100.

The inspection area 106 is preferably designed to permit a detailed visual inspection of an electronic device such as a mobile phone, tablet computer, e-reader, MP3 players, PDA. The walls of the inspection area are preferably white and/or mirrored to provide imaging of the electronic device.

The couplings from the kiosk 100 and to a remote computer are preferably a single coupling to a communications network such as the internet via wired LAN, wireless LAN, cellular or any other proprietary communications system. The Kiosk 100 preferably includes a processor 160 for processing the information obtained from the mobile phone and for controlling the components of the kiosk 100. Preferably, the processor 160 is a standard personal computer ("PC") or other type of embedded computer running any operating system such as Linux or MAC OS. The processor 160 is most preferably a small form factor PC with integrated hard disk drive ("HDD"), central processing unit ("CPU") and universal serial bus ("USB") ports to communicate with the other components of the kiosk 100. One most preferred CPU is a DELL PC OPTIPLEX 780. Alternatively, the processing means is a microprocessor with a standalone motherboard which interfaces to a discrete HDD, power supply and the other components of the kiosk 100. The kiosk 100 preferably includes a memory 161 or other storage device, such as a disk drive, that stores the executable applications, test software, databases and other software required to operate the recycling kiosk 100.

The external communication component for the kiosk 100 preferably includes a wired Ethernet to provide connection to the internet, or alternatively the external communication component includes a wireless modem such as GSM, CDMA, 3G and 4G technologies for data communications.

As shown in FIGS. 7-9, the visual inspection of an electronic device such as a mobile phone 150 in the inspection area 106 is preferably performed by at least one camera 610 within the upper chamber 520. The lower chamber 530 also preferably has at least one camera or other imaging component such as a scanner. Alternatively, the visual inspection is performed by multiple cameras. A preferred camera 610 is a 1 megapixel machine vision camera. If a single camera 610 is utilized in the inspection area 106, the camera 610 preferably is movable to increase a field of view of the inspection area 106 to inspect the electronic device 150 such as a mobile phone placed on the transparent plate 545. The camera 161 is preferably movable. Preferably the camera 610 is positioned to image a LCD screen 153 of the electronic device 150 to determine if the LCD screen 153 is damaged. The interior surfaces of the upper chamber 520 and lower chamber 530 preferably include mirrors 615 in order to optimize viewing of an electronic device positioned within the inspection area 106. As shown in FIG. 9, a reflection 150' of a mobile phone 150 is illustrated. The camera 610 is also preferably movable to image a data port of the electronic device to determine the type of electrical connector 505 for the electronic device in order to perform an electrical analysis of the electronic device. Alternatively, the entire interior surfaces of the upper chamber 520 and the lower chamber 530 are mirrored for optimization of imaging of the electronic device. The camera(s) alternatively are CCD or CMOS.

Also, time is of the essence when inspecting the electronic device. The analysis is completed within an illumination period of the electronic device, wherein the illumination device comprises the time from when the display screen of the electronic device is illuminated to the time the display



screen converts to an energy conserving mode, evidences by the screen blacking out. During the inspection, the brightness of the illumination is also measured. The lighting preferably comprises LED based lighting with beam splitters, or alternatively UV lighting.

The transparent plate optionally operates as a weight scale to obtain a mass of the electronic device for use in determining a remuneration value. For example, if the mass of the electronic device **150** is less than set forth in a vendor specification for the electronic device, then one or more components of the electronic device may be missing, such as the battery for the electronic device **150**.

Preferably, visual inspection and recognition software is utilized by the kiosk **100** to analyze an electronic device. In one preferred method, a recognition algorithm is applied to a specific make and model of a electronic device. The visual inspection and recognition software determines the borders of a electronic device **150** under inspection to determine the external dimensions of the electronic device **150**. The external dimensions are utilized to determine a subset of possible mobile phones from a master database of mobile phones stored in the memory **161** of the kiosk **100** or available online to the kiosk **100** using external communications. The visual inspection and recognition software then preferably uses a set of secondary and tertiary features to further distinguish the electronic device **150**. These secondary and tertiary features can include placement and size of the display screen, placements and size of the keyboard, unique buttons, placement of ports, and other distinguishing features. Once an exact make and model of the electronic device is determined, the visual inspection and recognition software subtracts an image of the electronic device **150** from an image of a perfect electronic device for the same make and model. The result of the subtraction is preferably a quantifiable number of pixels that are calibrated into categories of broken or missing parts, cracked screen, and low, medium or high wear.

Alternatively, the visual inspection is performed using neural network pattern recognition techniques to identify the mobile phone **150**, then filter algorithms are utilized to determine defects such as cracked screens. Further, those skilled in the pertinent art will recognize that other visual inspection techniques may be employed without departing from the scope and spirit of the present invention.

The electrical analysis of an electronic device **150** is preferably performed using an electrical connector **505** connected to a data port of a electronic device **150** as discussed above in reference to FIGS. **2**, **2A**, **2B**, **2C** and **2D**. Once the make and model of the electronic device **150** is determined, either by visual inspection or user input using a user interface such as touch screen display **115**, the correct electrical connector **505** is dispensed by the carousel **500** for connection to the data port of the electronic device **150**. The connection of the electrical connector **505** to the electronic device **150** is preferably performed automatically by the kiosk **100**. Alternatively, the proper choice of electrical connector **505** is rotated into position on the carousel **500** and illuminated or in some other way presented to the consumer for manual connection of the electrical connector **505** to the data port of the electronic device **150**. Electrical analysis software is preferably utilized by the kiosk **100** to interact with the electronic device **150**. The electrical analysis preferably determines if the mobile phone is capable of activation, maintaining a charge, performing correctly, powering a display screen of the electronic device **150**, providing

make, model, serial number and other pertinent information about the electronic device **150**, and other relevant information.

The touch screen display **115** preferably includes a keypad, user selection buttons, soft keys, and other similar components. The touch screen display **118** is used to enable quick and easy access to various features and functions of the recycling kiosk **100**. The recycling kiosk **100** preferably dispenses various forms of payment, including cash, credit cards, debit cards, chip cards, gift cards from the kiosk's host location or other gift cards, and other magnetic striped cards or electronic payment methods. The kiosk **100** also uses the barcode reader to read the barcode identification on the inside of the battery pack. A UV detector is used for reading "invisible" barcodes in use by certain vendors such as Apple and others. The bar code reader, camera, and/or UV detector of the kiosk **100** is another technique used to identify the product model, IMEI #, and/or FCC ID. Alternatively, the kiosk **100** communicates with the electronic device **150** using wireless communications to test and if necessary erase data from the electronic device **150**.

FIG. **6** is a block diagram of the main components of the kiosk **100**. A processor **160** is preferably in communication with the other components of the kiosk **100**. The memory **161** preferably contains a database of information on multiple mobile phones including images, physical characteristics, prices and other similar information. The external communications **167** preferably communicates through a wireless connection or Ethernet with a network to receive and transmit information to a remote site. The power supply **170** is preferably received through a plug-in connection to a wall outlet. The mechanical components **165** include the electrical connector carousel **500**, the transparent plate **545**, the binning plate **540**, the door **550**, and other similar components. The camera **610** or cameras, electrical connectors, and a user interface interact with the processor **160** as discussed above. FIG. **5** illustrates an internal back of a recycling kiosk **100**. As shown a processor **160** is preferably a personal computer having a battery backup **170a**, a wireless connection **167** for external communications, an electrical connection **140**, a receipt dispenser **104** and a display screen **115**.

The processor **160** identifies the electronic device **150** submitted for recycling using information from the visual inspection and user interface. The processor **160** also determines the proper electrical connector **505** for connection to the data port of the electronic device **150** using information obtained during the visual inspection or from the user interface. The processor **160** also directs and receives information from the electrical analysis of the electronic device **150** performed using the electrical connector **505** connected to the data port of the electronic device **150**. The processor also preferably determines a financial remuneration for the submitted electronic device **150** based on the visual inspection, optionally the electrical analysis and data stored in the memory **161** of the kiosk or information provided externally through the external communication component **167**.

A flow chart for a preferred recycling method is shown in FIG. **12**. At step **301** a customer elects to sell or recycle an electronic device. The customer checks to see if the electronic device is supported for sale/refurbishing from a list on the screen of the kiosk. The customer activates the on-screen menu system and either enters the phone model directly or goes through a series of menus to determine if the electronic device is eligible for sale or only for recycling. At decision block **302** it is determined if the electronic device is only available for recycling. If yes, (i.e. it is not on the list of



## 11

electronic device available for reselling) the customer can insert the electronic device into receptacle at step 303 and the electronic device falls into bin 112 for recycling.

If the electronic device is supported for refurbishment/ resale the customer is then encouraged to engage the testing/ rating operation of the system. At step 304, the system has determined the correct connector to couple to the electronic device. Connectivity options and are not limited to cable, standard or proprietary connectors, hard docks, reading removable or external physical memory or other wireless methods like WiFi, Bluetooth, RFID, NFC, and the like. At step 305 the electronic device is connected and inserted into inspection area 106. If this has been done correctly, the customer is given some indication (e.g. a green light) and the system proceeds to step 306. At step 306 the electronic device is tested for operation using diagnostics and operating via, for example, the OMSI interface. The diagnostics preferably includes electrical and physical testing including testing the electronic device's battery, screen, memory, button functionality and structural integrity.

Preferably, the electronic device is imaged and analysis software is used to identify scratches, cracks, wear patterns, dents, broken or missing pieces, inclusion of features such as lenses, buttons, connectors, badges, labeling and/or branding. Identification may be done by image comparison or other similar methods where the image taken of the electronic device is normalized and compared to a reference image. Other inspection methods may be used in conjunction with visual and/or electrical testing including weighing to determine specific weight and use that data to further refine verification of manufacturer and verification of exact device model. In another embodiment, the photographic image is used to identify the correct manufacturer and model number/product number. Visual identification could include any combination of the following: calculations based upon measurement, physical (e.g., mm, inches), pixel count or other. Identification based upon electronic device dimensions, location/size of buttons, LCD and other physical characteristics. One camera or multiple cameras may be used to determine height, width, depth as needed. Identification based on OCR (Optical Character Recognition) of identifiers such as Carrier (for phone and tablet computers), brand, model, serial number, other identifiers. Identification based upon barcodes. Consumer may be asked to orient CE on its front, back, side and then asked to change orientation as needed. Consumer may even be asked to remove CE cover(s), batteries and the like in order to gain access to identifiable items, such alphanumeric or barcode data. The kiosk 100 provides a way to use visual inspection with electrical inspection to identify a device, determine its value, and reduce possible fraud.

In one embodiment, the kiosk 100 communicates with the carrier associated with a mobile phone to collect any information that could be germane to the device, including, for example, validation or authentication, registered ownership, account status, time in service, and the like. In some cases, when the customer's identification information does not match the registered owner information, the kiosk 100 automatically contacts the assumed owner in some manner (automated telephone call, email, text message, etc.) to alert the owner of the phone of the possible transaction.

Another feature of an embodiment of the kiosk 100 is to determine if there is personal information on the electronic device. This is determined by the presence of data in particular storage registers in the memory (e.g., quick-key stored numbers) or by looking at file types (jpegs, mp3's, etc.), or just assuming all non-default storage locations must

## 12

contain personal data. The customer is offered the chance to erase the data from the phone. One option allows the customer to request that the data be first downloaded and then sent to a location designated by the customer (e.g., email address, website, etc.). In another embodiment, there is a slot for the customer to enter a memory card (e.g. USB drive, memory stick, etc.) whereupon the kiosk 100 uploads the data to the memory device. In still another embodiment, the kiosk 100 offers a web location from which the user retrieves the data at some later time if desired. In another embodiment, the user elects to have the data placed in another electronic device purchased by the customer at the kiosk 100 or in the location of the kiosk 100 or some other store. The customer preferably selects a user name and password to access the system provided storage location.

Once the value is determined, the value is provided at step 307 to the kiosk. The kiosk 100 then offers the customer a price or other remuneration for the phone that is typically less than the resale value. In other embodiments, the kiosk 100 offers the customer a price or remuneration that is at the current real-time market price. At step 308 it is determined if the user wishes to accept the offer. If not, the kiosk 100 proceeds to step 309 and opens the door and releases the electronic device back to the customer. If the user wishes to accept the offer, the kiosk 100 proceeds to step 310. At a point where the user accepts a price, the kiosk 100 may then lock down the inspection area to prevent further access to the electronic device by the user. The kiosk 100 then disconnects any cables that have been attached. At step 310, the user indicates acceptance of the decision by confirming on the keypad or touch-screen. At this point the kiosk 100 proceeds with deleting the personal data from the electronic device. In addition, once the transaction is confirmed, the kiosk 100 tags the electronic device with a transaction number that is associated with the diagnostic data and the transaction itself. This is preferably a printed adhesive label that is affixed physically to the phone and/or the loading of electronic data corresponding to the transaction number onto the phone itself for traceability purposes.

At step 311, the kiosk 100 completes any additional testing and diagnostics of the electronic device, disconnects the cable from the electronic device, and prints a receipt for the customer. Transfer of funds may be authorized via the kiosk 100 by crediting a customer credit card or account by dispensing cash, or by dispensing a voucher or coupon. At step 312 the kiosk 100 updates its inventory database and transmits the update via a communications network to a kiosk server.

One preferred method for a pre-acquisition auction is illustrated in the flow chart of FIG. 13. A method for analysis of an electronic device and financial remuneration to a user for submission of the electronic device is generally designated 1000. At block 1001, an electronic device is identified. At block 1002, bids are solicited for a used model of the electronic device in a predetermined condition. The bids are preferably solicited online through a website and the bidders are preferably pre-qualified. At block 1003, bids for the used model of the electronic device are received from a plurality of bidders. At block 1004, a purchase price to pay for the used model of the electronic device is set based on the plurality of bids received from the plurality of bidders. Typically, the purchase price is based on the winning bid. The shipping information for the winning bidder is preferably obtained at this time. At block 1005, a used model of the electronic device is identified at a recycling kiosk for the electronic device. Preferably, a consumer desires to recycle the electronic device. At 1006, the integrity of the used



13

model of the electronic device is verified at the recycling kiosk. Preferably, the condition of the electronic device is established at the kiosk, with the kiosk determining any damage to the electronic device based on visual and electronic analysis of the electronic device. At block 1007, the electronic device is evaluated and graded. At block 1008, the purchase price for the used model of the electronic device is offered to a consumer at the kiosk. At block 1009, the electronic device is automatically binned after purchasing the used model of the electronic device from the consumer at the kiosk. At block 1010, the electronic device is shipped to the winning bidder.

Preferably, the kiosk 100 of the method comprises a housing 105, the housing 105 comprising a user interface on an exterior surface of the housing for the user to input information, an upper dome and a lower dome, wherein the upper dome and the lower dome comprise a plurality of mirrors. The kiosk 100 further comprises an upper chamber camera, a lower chamber camera and a transparent surface. The kiosk 100 further comprises a processor 160 within the housing and in communication with the at least one camera, the processor 160 configured to identify the brand and model number of the mobile communication device based on at least one of the information from the user and the images from the at least one camera, the processor 160 configured to determine a purchase price for the used model of the mobile communication device.

An alternative method for a pre-acquisition auction begins with a mobile communication device identified for acquisition. Bids are solicited for a used model of the mobile communication device. Bids for the used model of the mobile communication device are received from a plurality of bidders. A purchase price to pay for the used model of the mobile communication device is set based on the plurality of bids received from the plurality of bidders. A used model of the mobile communication device is identified at a recycling kiosk for the mobile communication device. The integrity of the used model of the mobile communication device is verified at the recycling kiosk. The purchase price for the used model of the mobile communication device is offered to a consumer at the kiosk. The mobile communication device is automatically binned after purchasing the used model of the mobile communication device from the consumer at the kiosk. The mobile communication device is shipped to the winning bidder.

Another alternative method for a pre-acquisition auction begins with establishing a plurality of pre-acquisition purchase prices. Each of the plurality of pre-acquisition purchase prices is established for a recycled electronic device in a predetermined condition. Each of the pre-acquisition purchase prices is established by a winning bid from a bidder of a plurality of bidders for a recycled electronic device. An electronic device is positioned in an inspection area of a kiosk. The inspection area has at least one camera. The electronic device or a portion thereof is imaged. The image of the electronic device obtained by the at least one camera disposed in the inspection area is inspected to determine if the electronic device has any defects. The electronic device is identified and a condition of the electronic device is determined. A matching pre-acquisition purchase price is selected from the plurality of pre-acquisition purchase prices for the electronic device. A consumer is offered the pre-acquisition purchase price for the electronic device.

From the foregoing it is believed that those skilled in the pertinent art will recognize the meritorious advancement of this invention and will readily understand that while the present invention has been described in association with a

14

preferred embodiment thereof, and other embodiments illustrated in the accompanying drawings, numerous changes modification and substitutions of equivalents may be made therein without departing from the spirit and scope of this invention which is intended to be unlimited by the foregoing except as may appear in the following appended claims. Therefore, the embodiments of the invention in which an exclusive property or privilege is claimed are defined in the following appended claims.

We claim as our invention the following:

1. An apparatus for recycling electronic devices, the apparatus comprising:

an inspection area having a surface configured to support an electronic device;

a carousel rotatably mounted adjacent to the inspection area in a non-horizontal orientation and configured to rotate about a non-vertical axis;

a plurality of electrical connectors carried by the carousel and disposed around a periphery of the carousel, at least one electrical connector of the plurality of electrical connectors configured to connect to the electronic device when the at least one electrical connector is rotated into position adjacent to an edge portion of the surface via the carousel; and

a processor in communication with the carousel and the at least one electrical connector, wherein the processor is configured to rotate the carousel about the non-vertical axis to position the at least one electrical connector adjacent to the edge portion of the surface for connection to the electronic device.

2. The apparatus of claim 1 wherein the electronic device is a mobile phone, and wherein the at least one electrical connector is configured to connect to the mobile phone.

3. The apparatus of claim 1 wherein each of the plurality of electrical connectors has the same shape, and wherein the plurality of electrical connectors are interchangeably carried by the carousel.

4. The apparatus of claim 1 wherein the plurality of electrical connectors includes at least a first electrical connector and a second electrical connector, wherein the first electrical connector is operably coupled to a first cartridge removably secured in the carousel, wherein the second electrical connector is operably coupled to a second cartridge removably secured in the carousel, and wherein the second cartridge is interchangeable with the first cartridge.

5. An apparatus for recycling electronic devices, the apparatus comprising:

an inspection area configured to receive the electronic device;

a carousel rotatably mounted adjacent to the inspection area; and

a plurality of electrical connectors carried by the carousel, at least one electrical connector of the plurality of electrical connectors configured to connect to the electronic device, wherein each of the electrical connectors includes a movable member and a unique connection plug for connection to a corresponding electronic device, and wherein the movable member is configured to move outwardly relative to the electrical connector to automatically disconnect the connection plug from the corresponding electronic device.

6. The apparatus of claim 1, further comprising a detachment mechanism positioned proximate the carousel, wherein the detachment mechanism is configured to releasably engage the at least one electrical connector while the processor is performing an electrical inspection of the electronic device.



## 15

7. The apparatus of claim 1, further comprising a detachment mechanism positioned proximate the carousel, wherein the detachment mechanism is configured to releasably engage the at least one electrical connector, and wherein the detachment mechanism is further configured to automatically disconnect the at least one electrical connector from the electronic device.

8. An apparatus for recycling electronic devices, the apparatus comprising:

- an inspection area configured to receive the electronic device;
- a carousel rotatably mounted adjacent to the inspection area;
- a plurality of electrical connectors carried by the carousel, at least one electrical connector of the plurality of electrical connectors configured to connect to the electronic device, wherein electrical connectors of the plurality of electrical connectors are interchangeable and include at least a first electrical connector and a second electrical connector, wherein the first electrical connector carries a first connection plug and the second electrical connector carries a second connection plug that is different than the first connection plug, wherein the first connection plug is configured to be removably connected to a first model of electronic device, and wherein the second connection plug is configured to be removably connected to a second model of electronic device that is different than the first model of electronic device; and
- a detachment mechanism positioned proximate the inspection area and separate from the carousel, wherein the detachment mechanism is configured to releasably engage the first electrical connector when the first connection plug is removably connected to the first electronic device at a first time, and wherein the detachment mechanism is further configured to releasably engage the second electrical connector when the second connection plug is removably connected to the second electronic device at a second time different than the first time.

9. The apparatus of claim 5, further comprising a detachment mechanism positioned proximate to the inspection area and separate from the carousel, wherein the detachment mechanism is configured to engage the at least one electrical connector, and wherein the detachment mechanism is further configured to drive the corresponding movable member outwardly relative to the at least one electrical connector to automatically disconnect the connection plug from the corresponding electronic device.

10. The apparatus of claim 5, further comprising a detachment mechanism positioned proximate to the inspection area and separate from the carousel, wherein the detachment mechanism is configured to engage the at least one electrical connector, and wherein the detachment mechanism includes a pair of hinged arms configured to engage the corresponding movable member and drive the movable member outwardly relative to the at least one electrical connector to automatically disconnect the connection plug from the corresponding electronic device.

11. The apparatus of claim 5, further comprising a detachment mechanism positioned proximate to the inspection area and separate from the carousel,

- wherein the detachment mechanism is configured to engage the at least one electrical connector,
- wherein the detachment mechanism is also configured to drive the corresponding movable member outwardly relative to the at least one electrical connector to

## 16

automatically disconnect the connection plug from the corresponding electronic device while holding the at least one electrical connector stationary relative to the inspection area, and

wherein the detachment mechanism is further configured to release the at least one electrical connector and let the electrical connector retract onto the carousel after the disconnecting the connection plug from the corresponding electronic device.

12. The apparatus of claim 8 wherein the first electrical connector has the same shape as the second electrical connector, and wherein the apparatus further comprises a plurality of cables carried by the carousel, the plurality of cables including at least a first cable and a second cable,

wherein a distal end of the first cable is operably connected to a first side of the first electrical connector and the first connection plug extends outwardly from an opposite second side of the first electrical connector, and

wherein a distal end of the second cable is operably connected to a first side of the second electrical connector and the second connection plug extends outwardly from an opposite second side of the second electrical connector.

13. The apparatus of claim 8, further comprising a plurality of cables carried by the carousel,

wherein the plurality of cables include at least a first cable and a second cable,

wherein a distal end of the first cable is operably connected to the first electrical connector and a distal end of the second cable is operably connected to the second electrical connector,

wherein the detachment mechanism is configured to release the first electrical connector after the first connection plug has been disconnected from the first electronic device, and release the second electrical connector after the second connection plug has been disconnected from the second electronic device,

wherein the first cable is configured to automatically retract the first connector from the detachment mechanism after the detachment mechanism has released the first connector, and

wherein the second cable is configured to automatically retract the second connector from the detachment mechanism after the detachment mechanism has released the second connector.

14. An apparatus for recycling electronic devices, the apparatus comprising:

- a housing;
- an inspection area within the housing;
- a carousel rotatably mounted within the housing;
- an electrical connector carried by the carousel, wherein the carousel is configured to dispense the electrical connector for connection to an electronic device within the inspection area; and
- a detachment mechanism configured to automatically detach the electrical connector from the electronic device.

15. The apparatus of claim 14 wherein the electronic device is a mobile phone.

16. The apparatus of claim 14 wherein the electrical connector is removably connected to the carousel.

17. The apparatus of claim 14 wherein the electrical connector includes:

- a cartridge;
- a plug at a distal end portion of the cartridge; and
- a cable extending proximally from the cartridge.



**17**

**18.** The apparatus of claim **14**, further comprising a retraction mechanism configured to automatically retract the electrical connector after the detachment mechanism automatically detaches the electrical connector from the electronic device.

**19.** The apparatus of claim **14** wherein:  
the electrical connector includes a movable member; and  
the detachment mechanism is configured to engage the movable member to disconnect the electrical connector from the electronic device.

**20.** The apparatus of claim **19** wherein:  
the electrical connector includes

a cartridge,  
a plug at a distal end portion of the cartridge, and  
a cable extending proximally from the cartridge; and  
the movable member is at the distal end portion of the cartridge.

**21.** The apparatus of claim **19** wherein the detachment mechanism is configured to move the movable member distally to disconnect the electrical connector from the electronic device.

**22.** The apparatus of claim **19** wherein the detachment mechanism includes hinged arms configured to engage the movable member to disconnect the electrical connector from the electronic device.

**23.** The apparatus of claim **19** wherein:  
the electrical connector includes a plug configured to connect to the electronic device within the inspection area;

**18**

the electrical connector has a first state in which the plug extends distally beyond the movable member at a distal end portion of the electrical connector;

the electrical connector has a second state in which the movable member extends distally beyond the plug at the distal end portion of the electrical connector; and  
the detachment mechanism is configured to move the electrical connector from the first state to the second state.

**24.** The apparatus of claim **14** wherein:

the electrical connector is a first electrical connector;  
the apparatus further comprises a second electrical connector carried by the carousel; and  
the first and second electrical connectors are interchangeable.

**25.** The apparatus of claim **24** wherein:

the first electrical connector includes a first plug configured to connect to the electronic device within the inspection area;

the first plug is of a first type;

the second electrical connector includes a second plug configured to connect to a different electronic device within the inspection area; and

the second plug is of a second type different than the first type.

\* \* \* \* \*