

US010068727B2

(12) **United States Patent**
Chang et al.

(10) **Patent No.:** **US 10,068,727 B2**
(45) **Date of Patent:** **Sep. 4, 2018**

(54) **KEY SURFACE LIGHTING**
(71) Applicant: **Apple Inc.**, Cupertino, CA (US)
(72) Inventors: **Ray L. Chang**, Cupertino, CA (US);
Robert M. Proie, Jr., Cupertino, CA (US)

5,746,308 A 5/1998 Lin
5,960,942 A 10/1999 Thornton
5,986,227 A 11/1999 Hon
5,997,196 A 12/1999 Hu
6,040,540 A 3/2000 Tsai et al.
6,229,684 B1 5/2001 Cowen et al.
(Continued)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 340 days.

FOREIGN PATENT DOCUMENTS

CN 102280292 12/2011
JP 2007-519317 7/2007
(Continued)

(21) Appl. No.: **14/817,316**
(22) Filed: **Aug. 4, 2015**

OTHER PUBLICATIONS

U.S. Appl. No. 13/407,910, filed Feb. 29, 2012, Niu et al.
(Continued)

(65) **Prior Publication Data**
US 2017/0040127 A1 Feb. 9, 2017

Primary Examiner — Karabi Guharay
(74) *Attorney, Agent, or Firm* — Brownstein Hyatt Farber Schreck, LLP

(51) **Int. Cl.**
H01H 13/83 (2006.01)
F21V 23/06 (2006.01)
(52) **U.S. Cl.**
CPC **H01H 13/83** (2013.01); **H01H 2219/037** (2013.01)


(57) **ABSTRACT**
An illuminator may be coupled to the key cap of a key. The key cap may include a portion that is operable to be illuminated and one or more illuminators may be coupled thereto. In particular embodiments, keys may include power delivery systems that are operable to wirelessly transmit power from a power source to illuminators. Such power delivery systems can include inductive transmitters and/or receivers, ultrasonic transmitters and/or receivers, laser diodes and photodiodes, electrodes that capacitively couple to wirelessly transfer power, and so on. In various embodiments, keys may include interconnects that connect an illuminator with a power source. The interconnect may be a flexible material that includes one or more traces and is configured with a shape that bends and twists to allow movement without stretching. The interconnect may also be part of a movement or support mechanism of a key.

(58) **Field of Classification Search**
CPC G06F 3/0202; H01H 13/83; H01H 13/84; F21V 23/06
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

17 Claims, 11 Drawing Sheets

5,278,371 A 1/1994 Watanabe et al.
5,619,005 A 4/1997 Shibukawa et al.
5,742,242 A 4/1998 Sellers
5,745,376 A 4/1998 Barker et al.



(56)

References Cited

U.S. PATENT DOCUMENTS

6,351,205 B1 2/2002 Armstrong
 6,648,530 B2 11/2003 Kamei et al.
 6,802,016 B2 10/2004 Liu
 6,990,867 B2 1/2006 Okada
 7,239,303 B2 7/2007 Liao et al.
 7,460,050 B2 12/2008 Alvarado et al.
 7,842,895 B2 11/2010 Lee
 7,880,247 B2 2/2011 Vaganov et al.
 7,903,166 B2 3/2011 Daly
 8,110,764 B2 2/2012 Hsu et al.
 8,207,872 B2 6/2012 Huang et al.
 8,446,264 B2 5/2013 Tanase
 8,912,458 B2 12/2014 Peterson et al.
 8,957,337 B2 2/2015 Niu et al.
 8,981,243 B2 3/2015 Leong et al.
 9,093,229 B2 7/2015 Leong et al.
 2006/0181511 A1 8/2006 Woolley et al.
 2007/0200823 A1 8/2007 Bytheway et al.
 2010/0108486 A1 5/2010 Yoshida
 2011/0155552 A1 6/2011 Wang
 2011/0260978 A1 10/2011 Larsen
 2012/0091794 A1 4/2012 Campanella et al.

2013/0161172 A1 6/2013 Leong et al.
 2014/0118264 A1* 5/2014 Leong G06F 3/0202
 345/168
 2014/0126176 A1* 5/2014 Yao G02B 6/006
 362/23.03
 2014/0176352 A1 6/2014 Hussain et al.
 2015/0022995 A1 1/2015 Peterson et al.
 2015/0061901 A1 3/2015 Casparian et al.

FOREIGN PATENT DOCUMENTS

JP 2007-532069 11/2007
 WO WO 99/024962 5/1999
 WO WO 10/095075 8/2010
 WO WO 11/000910 1/2011
 WO WO 11/152826 12/2016

OTHER PUBLICATIONS

U.S. Appl. No. 13/722,993, filed Dec. 20, 2012, Leong et al.
 U.S. Appl. No. 13/723,033, filed Dec. 20, 2012, Leong et al.
 U.S. Appl. No. 13/723,054, filed Dec. 20, 2012, Leong et al.

* cited by examiner




FIG. 1




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8




FIG. 9






FIG. 10

**FIG. 11****FIG. 12**

1**KEY SURFACE LIGHTING**

FIELD

The described embodiments relate generally to lighting. More particularly, the present embodiments relate to providing power to surface mounted lights on keyboard keys.

BACKGROUND

Many electronic devices include illuminated surfaces. For example, some keyboards illuminate keys so that the keyboard can be used in low or no lighting conditions. Additionally, keys may be illuminated simply to aid users in understanding the functions associated with various keys, such as by illuminating a legend on a surface of a key.

This surface lighting is generally implemented by mounting a light emitting diode (LED) on a printed circuit board (and/or flexible circuits and/or wires connected thereto) under a key. Due to this placement, light guide panels and/or other structures are often used in order to distribute light from the LED evenly as well as prevent or reduce "hot spots" (areas of comparative brightness corresponding to the actual location of an LED).

Such light guide panels or other structures occupy space in a key stack, making key stack dimensions larger than they otherwise would be and/or limiting the components that could otherwise be included. Further, even with such light guide panels or other structures, greater amounts of power may be provided to an LED than would otherwise be used with the LED alone in order to obtain a desired illumination level due to the position of the LED or other structures, distance from the key cap, the diffusion of light, and so on.

SUMMARY

The present disclosure relates to surface illumination. One or more illuminators may be coupled to the key cap of a key. Additionally, a key cap may include a portion that is operable to be illuminated and one or more illuminators may be coupled to that portion. These techniques may enable distribution of illumination without light guides and/or other structures and may prevent other key stack structures from interfering with light distribution.

In particular embodiments, key stacks may include power delivery systems that are operable to wirelessly transmit power from a power source to illuminators coupled to the key caps. Such power delivery systems can include inductive transmitters and/or receivers, ultrasonic transmitters and/or receivers, laser diodes and photodiodes, electrodes that capacitively couple to wirelessly transfer power, and so on. In various embodiments, key stacks of keys may include interconnects that connect illuminators coupled to the key caps with power sources. In some implementations, the interconnect may be a flexible material that includes one or more traces and is configured with a shape that bends and twists to allow movement of the key cap without stretching. In various implementations, the interconnect may be part of a movement or support mechanism of a key, such as where a support mechanism includes a conductive moveable strut that connects the illuminator and power source or where the support mechanism is a fabric web in which the key cap is mounted and the interconnect is one or more traces disposed thereon.

In various embodiments, a keyboard may include a printed circuit board and a number of keys coupled to the printed circuit board. Each key may include an actuator, a

2

movement mechanism coupled to the actuator that biases the actuator towards an un-depressed position and allows movement of the actuator towards a depressed position to activate the respective key, a light emitting diode coupled to the actuator, and a power receiver coupled to the light emitting diode that is operable to provide power wirelessly received from the printed circuit board to the light emitting diode.

In some examples, the power receiver may be at least one of an inductive receiver, an ultrasonic receiver, a photodiode, or a first electrode that wirelessly receives power by capacitively coupling to a second electrode.

In various examples, the actuator may include a first region that is operable to be illuminated and a second region that is not operable to be illuminated and the light emitting diode may be coupled to the first region. In some examples, the light emitting diode may be multiple light emitting diodes coupled to the first region.

In some embodiments, a key stack may include a substrate having a switch and a power conduit, a key cap disposed above the switch, a support mechanism moveably coupling the key cap to the substrate and configured to move the key cap into a depressed position to actuate the switch, an illuminator coupled to the key cap, and a power delivery system operable to wirelessly transmit power from the power conduit to the illuminator.

In various examples, the power delivery system may be an inductive receiver coupled to the illuminator and operable to inductively receive power from an inductive transmitter. In some examples, the power delivery system may be a first electrode coupled to the illuminator and operable to capacitively couple to a second electrode to wirelessly receive power from the second electrode. In various examples, the power delivery system may be an ultrasonic receiver coupled to the illuminator and operable to convert an ultrasonic signal received from an ultrasonic transmitter into power for the illuminator. In some examples, the power delivery system may be a photodiode coupled to the illuminator and configured to convert light received from a laser diode into power for the illuminator.

In some examples, the key stack may further include a storage capacitor coupled to the illuminator that is operable to store power received from the power delivery system and provide stored power to the illuminator.

In various examples, the illuminator may be at least one of coupled to a surface of the key cap or embedded at least partially within the key cap. In some examples, the illuminator may be at least one of a light emitting diode or an organic light emitting diode.

In one or more embodiments, a key stack may include a key cap, a support mechanism coupled to the key cap that allows movement of the key cap, an illuminator coupled to the key cap, and an interconnect coupled to the illuminator and a power source that provides power from the power source to the illuminator.

In various examples, the interconnect may be a flexible material (such as a polymer) including a trace, the flexible material configured with a shape (such as at least one of a zigzag shape, a serpentine shape, and a spiral) that bends and twists when the key cap moves between a depressed position and an un-depressed position.

In some examples, the support mechanism may be a fabric web. In such examples, the interconnect may be a trace formed on the fabric web. In various examples, the support mechanism may be multiple moveable struts and the interconnect may be a conductive strut of the multiple moveable struts.

In various examples, the key cap may include a transparent region and an opaque region. In such examples, the illuminator may be coupled to the transparent region.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure will be readily understood by the following detailed description in conjunction with the accompanying drawings, wherein like reference numerals designate like structural elements.

FIG. 1 shows a computing device including a keyboard.

FIG. 2 shows a cross-sectional view of an example key stack of the keyboard of FIG. 1 that uses wireless power delivery system for illumination, taken along A-A of FIG. 1.

FIGS. 3-5A show cross-sectional views of additional examples of key stacks that use wireless power delivery systems for illumination in accordance with further embodiments of the present disclosure.

FIG. 5B shows a bottom view of the key cap of FIG. 5A with other components removed for clarity.

FIG. 6 shows a cross-sectional view of an additional example of a key stack that uses a wired power delivery system for illumination in accordance with further embodiments of the present disclosure.

FIGS. 7-8 are side views of example interconnects that may be used in the example key stack of FIG. 6.

FIGS. 9-10 show cross-sectional views of additional examples of key stacks that use wired power delivery systems for illumination in accordance with further embodiments of the present disclosure.

FIG. 11 is a flow chart illustrating a method for assembling an illuminated key for a keyboard. This method may assemble any of the keys of FIGS. 1-5B.

FIG. 12 is a flow chart illustrating a method for wirelessly illuminating keys. This method may be performed using any of the keys of FIGS. 1-5B.

DETAILED DESCRIPTION

Reference will now be made in detail to representative embodiments illustrated in the accompanying drawings. It should be understood that the following descriptions are not intended to limit the embodiments to one preferred embodiment. To the contrary, it is intended to cover alternatives, modifications, and equivalents as can be included within the spirit and scope of the described embodiments as defined by the appended claims.

The description that follows includes sample systems, methods, and apparatuses that embody various elements of the present disclosure. However, it should be understood that the described disclosure may be practiced in a variety of forms in addition to those described herein.

The following disclosure relates to surface illumination, such as illuminating the keys or other actuators of a keyboard. One or more LEDs and/or other illuminators may be coupled to the key cap of a key. This may enable distribution of illumination without light guides and/or other structures, though such may still be used in some implementations, and may prevent other key stack structures (such as movement mechanisms) from interfering with light distribution. Additionally, a key cap may include a portion that is operable to be illuminated and one or more LEDs may be coupled to that portion, further enabling distribution of illumination without light guides and/or other structures.

In particular embodiments, key stacks of keys may include power delivery systems that are operable to wirelessly transmit power from a power source (such as a power

conduit located on a printed circuit board to which the key is movably mounted) to LEDs coupled to the key caps. Such power delivery systems can include inductive transmitters and/or receivers, ultrasonic transmitters and/or receivers, laser diodes and photodiodes, electrodes that capacitively couple to wirelessly transfer power, and so on. In some implementations, the LED may be coupled to a capacitor and/or other power storage such that the LED may be operable to illuminate even when power is not currently being wirelessly transmitted.

In various embodiments, key stacks of keys may include interconnects that connect LEDs coupled to the key caps with power sources. In some implementations, the interconnect may be a flexible material (such as a polymer, elastomer, and so on) that includes one or more traces and is configured with a shape (such as a zigzag shape, a serpentine shape, a spiral, and so on) that bends and twists to allow movement of the key cap without stretching. In various implementations, the interconnect may be part of a movement or support mechanism of a key, such as where a support mechanism includes a conductive moveable strut that connects the LED and power source or where the support mechanism is a fabric web in which the key cap is mounted and the interconnect is one or more traces disposed thereon.

These and other embodiments are discussed below with reference to FIGS. 1-12. However, those skilled in the art will readily appreciate that the detailed description given herein with respect to these Figures is for explanatory purposes only and should not be construed as limiting.

FIG. 1 shows an isometric view of a computing device **100** including a keyboard **101** having a number of keys **102** that may have one or more LEDs and/or other illuminators coupled to key caps or other actuators of the keys **102**. As described with respect to FIGS. 2-12 below, the LEDs may be powered via one or more wired or wireless power delivery systems.

The keys **102** may include one or more legends, such as one or more characters, symbols, and so on. Such legends may indicate one or more functionalities associated with the keys **102**. For simplicity, only the "T" legend is shown.

FIG. 2 shows a cross-sectional view of an example key stack of the keyboard **101** of FIG. 1 that uses wireless power delivery system for illumination, taken along A-A of FIG. 1. A key **102** may include a key cap **201** (or other actuator) with one or more illuminators **206** coupled thereto (such as an LED, which may be an organic LED or OLED, and/or any other illuminator such as an incandescent bulb, an electroluminescent material or device, a quantum dot, a laser, and so on). This may enable distribution of illumination without light guides and/or other structures. As shown, the illuminator may be coupled to an underside surface **205** of the key cap **201**.

The key **102** may include a power delivery system that wirelessly delivers power from a power conduit **218** of a printed circuit board **202** or other substrate to the illuminator **206**. The power delivery system may include a power transmitter **209** that is operable to wirelessly transmit power from the power conduit **218** to a power receiver **208**, which may be coupled to the illuminator **206**. In this example, the power delivery system includes an inductive transmitter **209** that is operable to induce a current in an inductive receiver **208** by creating a magnetic field **210**. This may inductively transmit power from the power conduit **218** to the illuminator **206**.

In some implementations, the key **102** may further include a controller **250**, which may be coupled between the

inductive receiver **208** and the illuminator **206**. The controller **250** may be operable to control the illuminator **206** to perform one or more various different illumination effects.

In some examples, the controller **250** may be a simple controller capable of receiving instructions to drive the illuminator **206** to perform a limited set of illumination effects in order to minimize power utilized by the controller **250**. However, in other examples the controller **250** may be a more complex (possibly still a low power complex controller) that is operable to receive instructions to drive the illuminator **206** to perform a less limited set of illumination effects.

For example, in some implementations, the illuminator **206** may be an OLED assembly and the controller **250** may be an OLED controller. The OLED controller may be operable to receive instructions to drive individual OLED elements of the OLED assembly, perform a dithering effect using the OLED assembly, control brightness levels of the OLED assembly, and/or various other illumination effects.

In some implementations, the data specifying how the controller **250** is to control the illuminator **206** may be received by the controller **250** in a variety of ways. For example, the data may be embedded in the power transmission received by the power receiver **208**. In some cases of such an example, the data may be embedded in the power transmission at a different carrier frequency than the power.

By way of another example, the data specifying how the controller **250** is to control the illuminator **206** may be received by the controller **250** via a separate path than the power transmission received by the power receiver **208**. Such a separate path may be a wired communication path such as a flex circuit, a wireless communication path such as an infrared transmission system, and/or various other communication paths.

In various implementations, the data specifying how the controller **250** is to control the illuminator **206** may be transmitted to the controller **250** by one or more processing units, such as a processing unit of the computing device **100** or a processing unit of another computing device. Such data may be transmitted at the instruction of one or more operating systems, applications, in response to user input, and so on.

The power delivery system in this example may also include a storage capacitor **207** or other power storage component coupled between the inductive receiver **208** and the illuminator **206** (such as via the controller **250**). The storage capacitor **207** may receive and store power from the inductive receiver **208**. The storage capacitor **207** may also provide stored power to the illuminator **206**. In this way, the illuminator **206** may be operable to illuminate even when power is not currently being wirelessly transmitted.

The key cap **201** may include a first region **212** that is operable to be illuminated by the illuminator **206** and a second region **211** that is not operable to be illuminated. The illuminator **206** may be coupled to the first region **212**, further enabling distribution of illumination without light guides and/or other structures.

The first region **212** may be a transparent or translucent region and the second region **211** may be an opaque region. In this example, the key cap **201** may itself be transparent and portions thereof may be coated with an opaque coating. Thus, the first region **212** may be the portions of the key cap **201** not coated with the opaque coating and the second region **211** may be the portions of the key cap **201** coated with the opaque coating.

As shown, a cover **214** may be positioned over the illuminator **206**. The cover **214** may block direct passage of

illumination from the illuminator **206** through the first region **212**, preventing a hot spot at the location of the illuminator **206**. Instead, illumination from illuminator **206** may shine out from under the cover **214** and then illuminate the first region **212**. However, in other implementations the cover **214** may not be used. In still other implementations, a light guide and/or other structure may be utilized with the illuminator **206** instead of and/or in addition to a cover **214**.

The key cap **201** may be positioned within an aperture in a top plate **103** and mounted to the printed circuit board **202** via a movement mechanism **203** or other support mechanism. The movement mechanism **203** may allow movement of the key cap **201** to move between an un-depressed position (shown) and a depressed position where the key cap **201** may compress or otherwise activate a dome switch **204** or other switch. As shown, the movement mechanism **203** may be a “scissor” mechanism formed by moveable struts **215** and **216** connected via a spring hinge **217**. This may bias the key cap **201** is towards the un-depressed position but allow movement toward the dome switch **204** to transition the key **102** to a depressed position and activate the key **102**.

Although the key **102** is shown with a scissor type movement mechanism **203**, it should be understood that this is an example and that other movement mechanisms **203** are possible without departing from the scope of the present disclosure. For example, a “butterfly” mechanism may include two flaps joined by a hinge. Such a butterfly mechanism may allow transition of the key cap **201** from an un-depressed position to a depressed position by the flaps moving on the hinge to widen an angle formed by the flaps. Similarly, the flaps moving on the hinge to narrow the angle formed by the flaps may transition the key cap **201** from the depressed position to the un-depressed position.

Although FIG. **2** is illustrated and described as utilizing an inductive transmitter **209** that wirelessly transmits power by to an inductive receiver **208** via induction, it should be understood that this is an example. In various implementations, other wireless power delivery systems may be utilized. For example, FIGS. **3-5A** show cross-sectional views of additional examples of key stacks that use wireless power delivery systems for illumination in accordance with further embodiments of the present disclosure.

By way of contrast with FIG. **2**, FIG. **3** includes an ultrasonic transmitter **321** coupled to the power conduit **218** of the printed circuit board **202**. The ultrasonic transmitter **321** may emit an ultrasonic signal **322** using power from the power conduit **218**. The ultrasonic signal **322** may be received by an ultrasonic receiver **320**, which may convert the received ultrasonic signal **322** to power. The ultrasonic receiver **320** may provide the power from the ultrasonic signal **322** to the storage capacitor **207** and/or the illuminator **206**.

Similarly, FIG. **4** includes a first electrode **427** and a second electrode **426**. The first electrode **427** is coupled to the illuminator **206** via the storage capacitor **207**. The second electrode **426** is disposed on the dome switch **204** and connected to the power conduit **218** of the printed circuit board **202** via a trace **425**. The first electrode **427** may be operative to capacitively couple to the second electrode **426**. Particularly as the first electrode **427** moves closer to the second electrode **426**, this capacitive coupling may allow the first electrode **427** to receive power from the second electrode **426** that the second electrode **426** receives from the power conduit **218**. The first electrode **427** may provide the power from the capacitive coupling to the storage capacitor **207** and/or the illuminator **206**.

Further, the illuminator **206** may be partially or fully embedded in the key cap **201** instead of being coupled to a surface. FIG. **4** illustrates the illuminator **206** as partially embedded in the key cap **201**.

Likewise, FIG. **5A** includes a photodiode **528** coupled to the illuminator **206** and a laser diode **529** coupled to the power conduit **218** of the printed circuit board **202**. The laser diode **529** may emit a laser beam **530** to the photodiode **528** using power from the power conduit **218**. The photodiode **528** may convert the received laser beam **530** to power, which the photodiode **528** may provide to the illuminator **206**.

Although FIGS. **2-5A** illustrate a single illuminator **206**, it should be understood that these are examples. In various implementations, multiple illuminators **206** may be used. For example, FIG. **5B** shows a bottom view of the key cap **201** of FIG. **5A** with other components removed for clarity. As shown, multiple illuminators **206** are coupled to an area the underside surface **205** of the key cap **201** corresponding to the "T" legend of the key. The multiple illuminators **206** may be coupled to each other in order to receive power from one of the illuminators **206** that is coupled to the photodiode **528**. However, in some implementations such multiple illuminators **206** may be directly coupled to the photodiode **528**, such as via one or more traces on the underside surface **205** of the key cap **201**.

Further, although FIGS. **2-5A** illustrate particular configurations of components, it should be understood that these are examples and that components may be otherwise arranged without departing from the scope of the present disclosure. For example, in some implementations an inductive transmitter **209** may be coupled to the top plate **103** and connected to a power conduit **218** included therein or thereon. By way of another example, in various implementations an ultrasonic transmitter **321** may be located on the movement mechanism **203**. By way of still another example, in some implementations a second electrode **426** may be located on a side of the top plate **103** in a gap defined between the top plate **103** and the key cap **201**. In yet another example, in various implementations a laser diode **529** may be located on the printed circuit board **202** and/or beneath the dome switch **204**.

FIG. **6** shows a cross-sectional view of an additional example of a key stack that uses a wired power delivery system for illumination in accordance with further embodiments of the present disclosure. As contrasted with FIG. **2**, an interconnect **630** may be coupled to the illuminator **206** and a power source, such as the power conduit **218** of the printed circuit board **202**, that provides power from the power source to the illuminator **206**.

The interconnect **630** of the example shown in FIG. **6** may have a flexible material **631** including a trace **632**. The flexible material **631** may be flexible, but may not be elastic. In some examples, the flexible material may be formed of a polymer, an elastomer, and/or other such material. The flexible material **631** may be configured with a shape that bends and/or twists when the key cap **201** moves (such as between a depressed and an un-depressed position). For example, the flexible material **631** is illustrated as having a zigzag shape with multiple three-dimensional direction changes along the length of the flexible material **631** extending from the printed circuit board **202** to the illuminator **206**. These direction changes may allow the flexible material **631** to bend and/or twist to accommodate movement of the key cap **201** without stretching the flexible material **631**. This may prevent or reduce separation of the trace **632** from the flexible material **631** and/or tearing of the trace **632** and/or

the flexible material **631**. FIG. **7** illustrates a side view of the interconnect **630** alone with other components removed for clarity.

However, although the interconnect **630** is illustrated as being configured with a particular shape, it should be understood that this is an example and that other shapes may be utilized without departing from the scope of the present disclosure. Such shapes may include a zigzag shape, a serpentine shape (which may be similar to a zigzag shape but with curved instead of sharp direction changes), a spiral, and so on. For example, FIG. **8** shows another example interconnect **630** having a flexible material **631** configured with a spiral shape having a trace **632** formed thereon. The spiral shape may allow the flexible material **631** to bend and twist when the flexible material **631** moves.

Additionally, although a particular interconnect **630** is illustrated and described with respect to FIG. **6**, it should be understood that this is an example. In various implementations, other interconnects may be utilized without departing from the scope of the present disclosure.

For example, FIG. **9** illustrates an embodiment that utilizes the movement mechanism **203** as part of the interconnect. The moveable strut **216** of the multiple moveable struts **215** and **216** may be conductive. As such, the conductive moveable strut **216** may be connected to the power conduit **218** of the printed circuit board **202** and to the illuminator **206** via a trace **933**.

In further embodiments, the moveable strut **216** may itself be non-conductive but may still function to connect the power conduit **218** and the trace **933**. For example, in such embodiments a trace may be formed on the moveable strut **216** that connects the power conduit **218** and the trace **933**.

By way of another example, FIG. **10** illustrates an embodiment where a support mechanism for a key cap **201** is a fabric web **1040** instead of the movement mechanism **203** illustrated in FIG. **9**. In this example, the key cap **201** may be bonded to an embossed area **1042** of the fabric web **1040** adjacent unbonded bends **1041**. The fabric web **1040** may be configured to stretch and/or flex such that the bends **1041** are operable to flex and/or move allow the key cap **201** to transition between an un-depressed (shown) and a depressed position (where a plunger **1043** compressed the dome switch **204** on the printed circuit board **202** or other substrate).

Further in this example, the illuminator **206** may be coupled to a power source that is connected to a trace **1044** formed on the fabric web **1040** via a trace **1045** formed on the key cap **201**. However, it should be understood that this is an example and that other mechanisms of connecting the illuminator **206** to a power source may be utilized, such as implementations where the interconnect **630** of FIG. **7** or **8** is disposed on the fabric web **1040** to connect the illuminator **206** to a power source.

Although FIGS. **1-10** are illustrated and described above in the context of keyboard keys, it is understood that these are examples. In various implementations, one or more of the techniques described herein may be utilized with other actuators or components without departing from the scope of the present disclosure. Any illumination element may be used in and/or with any kind of input device. For example, the techniques illustrated and described herein may be utilized in one or more buttons, such as a button included in the cuff or other portion of an electronic item of apparel.

FIGS. **1-10** are illustrated and described above in the context of illuminating keyboard keys. In some implementations, the illumination may be controlled by a processing unit or the like. In various examples of such implementa-

tions, the keys may be illuminated under certain conditions. For example, one or more keys may be illuminated under the control of a processing unit or the like when ambient light sensed by an ambient light sensor falls below a threshold. In other words, if the environment becomes dark the keys may be illuminated. By way of another example, the processing unit or the like may illuminate one or more keys in response to a user input (such as illuminating a key when pressed by a user) or system operating condition (such as illuminating a key when instructed by an application or the operating system; based on change of a system variable such as a power status, storage space, available memory, and so on; and/or other system operating condition).

FIG. 1 illustrates a laptop computing device 100. Such a laptop computing device 100 may include various components, such as processing units, non-transitory storage media, communication components, input/output components, and so on. The processing unit may execute instructions stored in the non-transitory storage media to receive input via the keyboard 101, illuminate keys 102, and/or perform various other actions.

However, it should be understood that this is an example. The techniques described herein may be utilized with any device without departing from the scope of the present disclosure. Such devices may include an external keyboard, a mobile computing device, a digital media player, a smart phone, a cellular phone, a tablet computing device, a desktop computing device, a wearable device, an item of apparel, and so on.

FIG. 11 is a flow chart illustrating a method 1100 for assembling an illuminated key for a keyboard. This method may assemble any of the keys of FIGS. 1-5B.

At 1101, an illuminator may be coupled to a key cap. The illuminator may be an LED (which may be an organic LED) and/or any other device capable of providing illumination. Examples of such devices include lasers, incandescent bulbs, and so on.

At 1102, a power delivery system may be configured to wirelessly transmit power to the illuminator. The power delivery system may be an inductive power transmission system, an ultrasonic power transmission system, a capacitive coupling power transmission system, a laser power transmission system, and/or any other power transmission system capable of wirelessly providing power.

Although the example method 1100 is illustrated and described as including particular operations performed in a particular order, it is understood that this is an example. In various implementations, various orders of the same, similar, and/or different operations may be performed without departing from the scope of the present disclosure.

For example, in some implementations the example method 1100 may include the additional operation of moveably mounting the key cap on a substrate. Such mounting may moveably mount the key cap above a switch on a movement or support mechanism, such as a scissor or butterfly mechanism, a fabric web, and so on.

FIG. 12 is a flow chart illustrating a method 1200 for wirelessly illuminating keys. This method may be performed using any of the keys of FIGS. 1-5B.

At 1201, power may be wirelessly received at a receiver that is connected to an illuminator coupled to a key cap. The power may be received using induction, ultrasonic signals, light, capacitive coupling, and so on.

At 1202, the received power may be provided to the illuminator. The received power may be provided directly and/or via a storage or other component such as a capacitor.

At 1203, the key cap may be illuminated using the provided power. The key cap may be continually illuminated during operation or may be illuminated in response to particular events. For example, in some implementations the key cap may be illuminated when activated to indicate activation.

Although the example method 1200 is illustrated and described as including particular operations performed in a particular order, it is understood that this is an example. In various implementations, various orders of the same, similar, and/or different operations may be performed without departing from the scope of the present disclosure.

For example, in various implementations the example method 1200 may include the additional operation of wirelessly transmitting the power from a transmitter to the receiver. By way of another example, in some implementations the example method 1200 may include the additional operation of storing the received power. In such implementations, the power provided in 1202 may be the stored power.

As described above and illustrated in the accompanying figures, the present disclosure relates to surface illumination. One or more illuminators may be coupled to the key cap of a key. Additionally, a key cap may include a portion that is operable to be illuminated and one or more illuminators may be coupled to that portion. These techniques may enable distribution of illumination without light guides and/or other structures and may prevent other key stack structures from interfering with light distribution. In particular embodiments, key stacks may include power delivery systems that are operable to wirelessly transmit power from a power source to illuminators coupled to the key caps. Such power delivery systems can include inductive transmitters and/or receivers, ultrasonic transmitters and/or receivers, laser diodes and photodiodes, electrodes that capacitively couple to wirelessly transfer power, and so on. In various embodiments, key stacks of keys may include interconnects that connect illuminator coupled to the key caps with power sources. In some implementations, the interconnect may be a flexible material that includes one or more traces and is configured with a shape that bends and twists to allow movement of the key cap without stretching. In various implementations, the interconnect may be part of a movement or support mechanism of a key, such as where a support mechanism includes a conductive moveable strut that connects the illuminator and power source or where the support mechanism is a fabric web in which the key cap is mounted and the interconnect is one or more traces disposed thereon.

In the present disclosure, the methods disclosed may be implemented as sets of instructions or software readable by a device. Further, it is understood that the specific order or hierarchy of steps in the methods disclosed are examples of sample approaches. In other embodiments, the specific order or hierarchy of steps in the method can be rearranged while remaining within the disclosed subject matter. The accompanying method claims present elements of the various steps in a sample order, and are not necessarily meant to be limited to the specific order or hierarchy presented.

The described disclosure may utilize a computer program product, or software, that may include a non-transitory machine-readable medium having stored thereon instructions, which may be used to program a computer system (or other electronic devices) to perform a process according to the present disclosure. A non-transitory machine-readable medium includes any mechanism for storing information in a form (e.g., software, processing application) readable by a machine (e.g., a computer). The non-transitory machine-

11

readable medium may take the form of, but is not limited to, a magnetic storage medium (e.g., floppy diskette, video cassette, and so on); optical storage medium (e.g., CD-ROM); magneto-optical storage medium; read only memory (ROM); random access memory (RAM); erasable program-
5 mable memory (e.g., EPROM and EEPROM); flash memory; and so on.

The foregoing description, for purposes of explanation, used specific nomenclature to provide a thorough understanding of the described embodiments. However, it will be
10 apparent to one skilled in the art that the specific details are not required in order to practice the described embodiments. Thus, the foregoing descriptions of the specific embodiments described herein are presented for purposes of illustration and description. They are not targeted to be exhaust-
15 tive or to limit the embodiments to the precise forms disclosed. It will be apparent to one of ordinary skill in the art that many modifications and variations are possible in view of the above teachings.

What is claimed is:

1. A keyboard, comprising:
a printed circuit board;
a number of keys coupled to the printed circuit board,
each key comprising:
an actuator;
a movement mechanism coupled to the actuator that
biases the actuator towards an un-depressed position
and allows movement of the actuator towards a
depressed position to activate the respective key;
a light emitting diode coupled to the actuator; and
a power receiver coupled to the light emitting diode
that is operable to provide power wirelessly received
from the printed circuit board to the light emitting
diode.
2. The keyboard of claim 1, wherein the power receiver
35 comprises at least one of an inductive receiver, an ultrasonic receiver, a photodiode, or a first electrode that wirelessly receives power by capacitively coupling to a second electrode.
3. The keyboard of claim 1, wherein:
the actuator includes a first region that is operable to be
illuminated and a second region that is not operable to
be illuminated; and
the light emitting diode is coupled to the first region.
4. The keyboard of claim 3, wherein the light emitting
45 diode comprises multiple light emitting diodes coupled to the first region.
5. A key stack, comprising:
a substrate having a switch and a power conduit;
a key cap disposed above the switch;
a support mechanism moveably coupling the key cap to
the substrate and configured to move the key cap into
a depressed position to actuate the switch;
an illuminator coupled to the key cap; and

12

a power delivery system operable to wirelessly transmit
power from the power conduit to the illuminator.

6. The key stack of claim 5, wherein the power delivery
system comprises an inductive receiver coupled to the
5 illuminator and operable to inductively receive power from an inductive transmitter.

7. The key stack of claim 5, wherein the power delivery
system comprises a first electrode coupled to the illuminator
and operable to capacitively couple to a second electrode to
10 wirelessly receive power from the second electrode.

8. The key stack of claim 5, wherein the power delivery
system comprises an ultrasonic receiver coupled to the
illuminator and operable to convert an ultrasonic signal
received from an ultrasonic transmitter into power for the
15 illuminator.

9. The key stack of claim 5, wherein the power delivery
system comprises a photodiode coupled to the illuminator
and configured to convert light received from a laser diode
into power for the illuminator.

10. The key stack of claim 5, further comprising a storage
capacitor coupled to the illuminator that is operable to store
power received from the power delivery system and provide
stored power to the illuminator.

11. The key stack of claim 5, wherein the illuminator is at
25 least one of:

coupled to a surface of the key cap; or
embedded at least partially within the key cap.

12. The key stack of claim 5, wherein the illuminator is at
30 least one of a light emitting diode or an organic light emitting diode.

13. A key stack, comprising:

a key cap;
a support mechanism coupled to the key cap that allows
movement of the key cap and comprises a fabric web
having an underside to which the key cap is bonded;
an illuminator coupled to the key cap; and
a conductive interconnect in or on the fabric web;
wherein:

the conductive interconnect is coupled to the illuminator
and a power source that provides power from the power
source to the illuminator.

14. The key stack of claim 13, wherein the conductive
interconnect comprises a conductive trace.

15. The key stack of claim 13, wherein the conductive
interconnect comprises a trace formed on the fabric web.

16. The key stack of claim 13, wherein:
the key cap includes a transparent region and an opaque
region; and

the illuminator is coupled to the transparent region.

17. The key stack of claim 13, wherein the fabric web
50 comprises an embossed area bounded by a set of bends, and the key cap is bonded to the embossed area.

* * * * *