

(12)

United States Patent

Rus et al.

(10) Patent No.:

US 10,071,487 B2

(45) Date of Patent:

Sep. 11, 2018

(54)

SYSTEMS AND METHODS FOR COMPILING ROBOTIC ASSEMBLIES

USPC 703/6

See application file for complete search history.

(71)

Applicant: Massachusetts Institute of Technology, Cambridge, MA (US)

(56)

References Cited

U.S. PATENT DOCUMENTS

(72)

Inventors: Daniela L. Rus, Weston, MA (US); Joseph J. DelPreto, Croton-on-Hudson, NY (US); Ankur M. Mehta, Cambridge, MA (US)

2005/0036783 A1 2/2005 Morita et al.

2005/0146551 A1 7/2005 Yamazaki et al.

2009/0043543 A1 2/2009 Durney et al.

2010/0002402 A1 1/2010 Rogers et al.

2011/0287228 A1 11/2011 Durney et al.

2013/0269336 A1 10/2013 O'Connell et al.

(73)

Assignee: Massachusetts Institute of Technology, Cambridge, MA (US)

FOREIGN PATENT DOCUMENTS

(*)

Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 617 days.

EP 1 176 548 A2 1/2002

WO WO 2004/028937 A2 4/2004

WO WO 2012/024696 A2 2/2012

WO QO 2012/109559 A1 8/2012

(21)

Appl. No.: 14/705,493

OTHER PUBLICATIONS

(22)

Filed: May 6, 2015

An, Rus (inventor): Programming and Controlling Self-Folding Robots; 2012 IEEE International Conference on Robotics and Automation; RiverCentre, Saint Paul, Minnesota, USA; May 14-18, 2012.*

(65)

Prior Publication Data

US 2016/0016321 A1 Jan. 21, 2016

Related U.S. Application Data

(Continued)

(60)

Provisional application No. 61/989,310, filed on May 6, 2014.

Primary Examiner — Hugh Jones

(74)

Attorney, Agent, or Firm — Daly Crowley Mofford & Durkee LLP

(51)

Int. Cl.

G06G 7/48 (2006.01)

B25J 19/00 (2006.01)

B25J 13/00 (2006.01)

(52)

U.S. Cl.

CPC B25J 19/007 (2013.01); B25J 13/00 (2013.01); Y10S 901/50 (2013.01)

(57)

ABSTRACT


Systems and methods to systematize the development of machines using inexpensive, fast, and convenient fabrication processes are disclosed. In an embodiment, a robot compiler generates a fabrication system, including mechanical, electrical, and software assemblies, that can be used for assembling a robot according to a user design.

(58)

Field of Classification Search

CPC B25J 19/007

24 Claims, 10 Drawing Sheets



(56)

References Cited

OTHER PUBLICATIONS

Response filed on Dec. 24, 2016 to Non-Final Office Action dated Sep. 24, 2015; for U.S. Appl. No. 13/723,364; 12 pages.
 Final Office Action dated May 4, 2016; for U.S. Appl. No. 13/723,364; 16 pages.
 Non-Final Office Action dated Aug. 12, 2016; for U.S. Appl. No. 13/723,364, 13 pages.
 Response filed on Sep. 26, 2016 to Non-Final Office Action dated Aug. 12, 2016; for U.S. Appl. No. 13/723,364; 11 pages.
 Final Office Action dated Jan. 6, 2017; for U.S. Appl. No. 13/723,364; 10 pages.
 Response to Office Action dated Jan. 6, 2017 corresponding to U.S. Appl. No. 13/723,364; Response filed Jan. 20, 2017; 11 Pages.
 Notice of Allowance dated Mar. 27, 2017 for U.S. Appl. No. 13/723,364; 11 Pages.
 Non-Final Office Action dated Sep. 24, 2015; for U.S. Appl. No. 13/723,364; 15 pages.
 Hawkes et al.; "Programmable Matter by Folding;" Proceedings of the National Academy of Sciences, vol. 107, No. 28; Jul. 13, 2010;

www.pnas.org/cgi/doi/10.1073/pnas.0914069107; pp. 12441-12445.

Onal et al.; "Towards Printable Robotics: Origami-Inspired Planar Fabrication of Three-Dimensional Mechanisms;" 2011 IEEE International Conference on Robotics and Automation (ICRA); May 9-13, 2011; pp. 2-7.

Paik et al.; "Stretchable Circuits and Sensors for Robotic Origami;" 2011 IEEE/RJS International Conference on Intelligent Robots and Systems; Sep. 25-30, 2011; pp. 414-420.

PCT Search Report and Written Opinion of the ISA dated Feb. 4, 2014; for PCT Pat. App. No. PCT/US2013/059110; 9 pages.


PCT International Preliminary Report on Patentability and Written Opinion of the ISA dated Mar. 26, 2015; for PCT Pat. App. No. PCT/US2013/059110; 9 pages.


Amendment filed on Jun. 23, 2016 to the Final Office Action dated May 4, 2016; for U.S. Appl. No. 13/723,364; 13 pages.


Advisory Action dated Jun. 29, 2016; for U.S. Appl. No. 13/723,364; 3 pages.


Request for Continued Examination filed on Jul. 8, 2016; for U.S. Appl. No. 13/723,364; 3 pages.

* cited by examiner



**FIG. 2A**

**FIG. 2B**

***FIG. 2C***




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

SYSTEMS AND METHODS FOR COMPILING ROBOTIC ASSEMBLIES

RELATED APPLICATIONS

This application claims priority to and benefit of U.S. Provisional Application No. 61/989,310 (filed May 6, 2014), which is incorporated here by reference.

FEDERALLY SPONSORED RESEARCH

This invention was made with Government support under Grant No. CCF-1138967 awarded by the National Science Foundation. The government has certain rights in the invention.

BACKGROUND

The creation of new machines requires significant development time, financial resources, and technical expertise. While a wealth of tools exist for many robot development steps, there is not a single end-to-end process which begins with a novice user specifying a desired task and resulting in a fully functional robot able to perform that task.

An alternative to traditional machine design and fabrication may be referred to as “printable” and/or “foldable” machines. Such designs may utilize tools which are readily available, inexpensive to operate, and require minimal technical knowledge by a user.

As an illustrative example of the concepts, systems, circuits, devices and techniques sought to be protected herein, assume a home owner needs a machine to explore areas of his basement in order to detect carbon monoxide and radon. The machine may be required to traverse a cluttered environment, carry a sensor, and report back to the user. Using traditional design and fabrication techniques to create such a machine may be time consuming and inconvenient for the user. However, if the user uses a foldable machine described below, the user may feed specifications to a foldable machine compiler, which chooses notional designs from a pre-populated library or database, refines geometries based upon the task to be performed, and produces detailed design and program files. The machine may then be fabricated from the design and program files, and the user may collect the machine and place it into operation.

In another example, a custom gripper may be desired for an electronics assembly line. The gripper could, for example, be utilized by a pick and place machine. The assembly line manager can specify traits of the part such as the mass and approximate geometry. These specifications may be provided to the foldable machine compiler and fabrication process to produce a custom gripper to meet the task needs.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a system for compiling robot designs.

FIG. 2A is a flow-chart of a method for compiling a mechanical portion of a robot design.

FIG. 2B is a flow-chart of a method for compiling an electrical portion of a robot design.

FIG. 2C is a flow-chart of a method for compiling a software portion of a robot design.

FIG. 3 is a block diagram of an electrical controller layout of a modular robot.

FIG. 4 is a block diagram of a controller module and components.

FIG. 5 is a block diagram of a library for storing pre-defined elements of a robot.

FIG. 6 is a hierarchical diagram of a robot arm design.

FIG. 7 is a perspective view of a robot arm.

FIG. 8 is a hierarchical diagram of a manipulator arm design illustrating variable elements.

Like numbers in the drawings denote like elements.

Connectors within circuit or block diagrams may represent single wires, buses, or other types of connections between blocks. A single connector line should not be construed to limit the type of connection to a single wire.

The figures, including the flowcharts and block diagrams, are provided for exemplary purposes and are not intended to limit the scope of this disclosure. Although the figures depict diagrams and flowcharts with particular numbers of blocks connected in particular arrangements or sequences, these are examples only. Other arrangements and sequences are within the scope of this disclosure.

DETAILED DESCRIPTION

In an embodiment, to create a foldable machine, a user may provide specifications to a foldable machine compilation system, which may choose appropriate designs for completion of the specified task from a pre-populated library or database, refine geometries based upon the task to be performed, and produce detailed design and program files. The detailed design and program files may include electronics designs, software for operating and/or controlling the robot, and/or mechanical designs and instructions. The designs may include a cutting pattern for cutting a template out of a sheet of substrate material, a circuit pattern for creating and populating a circuit on the template, and/or a folding pattern that can be applied to the template in order to form the template into the final machine.

Laser cutters, lamination, and PCB-like component assembly followed by a final assembly that folds the substrate into its final form may be utilized. This so-called printable approach may allow for rapid development of low-cost machines using a general process that links specifications to prototypes, without requiring in-depth technical knowledge from the end user. The manufacturing process may include at least some or all of the following: (1) modeling of the machine; (2) parameter instantiation according to user specifications, i.e. modification of the model in order to tailor the machine to a particular task; (3) printed body fabrication; (4) printed electronics on the 2D body; (5) population of electronic components on the body; and (6) assembly of the 3D machine using folding. The resulting machines may be relatively light-weight (e.g. about 3 g in some instances) and may function as autonomous, programmable machines or robots. In an embodiment, a foldable machine may be fabricated in less than one day, less than 8 hours, less than four hours, less than two hours, less than one hour, or in any appropriate amount of time.

In an embodiment, the foldable machine compiler may generate a fabrication system for assembling the functioning robot. The fabrication system can include one or more of a mechanical design component, an electrical design component, and a software design component.

Compilation System

Referring to FIG. 1, a system **100** for generating applications for controlling a robot comprises an interface **102** to receive design specifications which may include input parameters **104** for a robot. The design specifications may

refer to or may include the subcomponents **110**, which will be described below in greater detail. In embodiments, interface **102** is a user interface that allows a user to specify a robot design, including input parameters **104** for customizing or defining the robot. The interface **102** may be a graphical user interface, a textual user interface, or any type of user interface that allows a user to enter specifications for the robot design.

The input parameters **104** are data elements generated as a result of the user's input to interface **102**. A user may, for example, use the interface **102** to choose modular components that will become part of the final robot. The user may then customize or supply parameters of the modular components. Data identifying and customizing the chosen modular components is then provided by interface **102** as input parameters **104**. These input parameters may define the user's input into the robot design. For example, if the user is designing a robotic arm, the user can use interface **102** to choose an arm portion, a finger portion, and a mount portion for mounting the arm to a fixed object, as well as other modular components of the robotic arm.

Depending on the modular component, interface **102** allows the user to specify parameters that customize the modular component for the specific robot being designed. For example, in the case of the arm portion, the user may specify the number of segments and elbows in the arm, and the size and length of each segment. In the case of the finger portion, the user may specify the number of segments and knuckles in the finger. In the case of the mount portion, the user may specify the type and size of the mount. As another example, if the robot design contains a wheel, the user may specify the size of the wheel and the number of wheels included in the robot. The type of modular component, the number of each modular component, and parameters that customize the components may be included as input parameters **104**. Optionally, the user may also specify software components that can be used to control the robot.

User interface **102** also allows the user to arrange and connect the modular components as desired to form a robot design.

System **100** also includes a component library **106**. Library **106** is a library or database of predefined modular components each describing a modular element of the robot. Continuing the example above, library **106** may contain predefined modular components that define the arm, fingers, and mount of the robotic arm. Library **106** also contains other types of modular elements including, but not limited to arms, hinges, beams, motors, fingers, mounts, tendons, electrical- or software-based controllers, sensors, wheels, robot bodies, or any other type of element to be included in a robot. Library **106** may also include software elements for controlling the robot. These software elements may include drivers and other software modules for interfacing with the robot's hardware, and may also include graphical user interface (GUI) elements that can be compiled into an application for controlling the robot. For example, Library **106** may include code, libraries, and/or compiled software modules for GUI elements such as buttons, sliders, toggle switches, levers, wheels, etc. These GUI elements can be compiled into an app that may be executed by a user on a PC, mobile device, or other computing device for controlling the robot's actions.

At least some of the modular elements may be composite elements that include or call-out other modular elements from library **106**. For example, library **106** may include a robotic hand element, which in turn includes two or more finger elements and a base element to which the fingers

attach. As another example, a wheeled platform element in library **106** may include a base element and at least two wheel elements, each of which may also be a component element in library **106**. The composite elements may also include GUI elements for controlling the composite element and/or for controlling individual elements that comprise the composite element.

In embodiments, each modular element in the library includes the predefined components including electrical, mechanical, software, and composite elements. The electrical components include lists of electrical or electromechanical components required by the electrical component, as well as definitions of electrical connections for connecting the electrical components to other elements of the robot. For example, a robotic arm may include electrical components such as servo-motors, LEDs, sensors, or other electrical components that may be included in a final assembly of the arm. The robotic arm, as defined in database **106**, may also include definitions of how the electrical components should be connected. The robotic arm may also include a modular controller as part of the electrical elements. The modular controller is an electrical element that includes a processor, that couples to and controls other electrical elements, and that facilitates communication between other modular controllers and a central controller. The modular controller will be described in greater detail below.

System **100** also includes a parameter inheritance module **108** coupled to receive the input parameters **104** from interface **102**. Parameter inheritance module **108** modifies the input parameters **104** and applies them to the modular components chosen by the user and received from library **106**. The modular components may also include fixed and/or predefined parameters such as a required voltage, a data type of a UI element, an angle of a fold, a non-adjustable width, etc. In embodiments, the modular components can also include parameters that may be calculated using functions that take other parameters (user modified parameters, fixed parameters, etc.), or other data, as inputs. The parameter inheritance module **108** may handle any of these types of parameters for producing a robot design.

The modular components may be modified or customized by the input parameters received from the user form sub-components **110** of the robot. As depicted in FIG. **1**, the sub-components **110** contain parameters **112**, which provide customization of the modular components for the specific robot being designed. As discussed above, parameters **112** may include data to specify size, number of elements, connection details, etc. In the case of the robotic arm, parameters **112** may specify the number of segments and elbows of the arm, the size of the segments, information about how the elements of the arm are to be connected, etc.

System **100** also includes a compiler **114** that receives sub-components **110** and generates a robot design, as defined by a fabrication system **116**. Compiler **114** includes a composition algorithms module **118** and an implementation engine **120**.

Composition algorithms module **118** contains algorithms and processes that receive the sub-components **110** and produce a fabrication file. As noted above, the sub-components are modular components from library **106** that have been modified by applying user parameters **112** to the components. The composition algorithms module **118** may compile each of these sub-components **110** to enable them to be connected to and operable with the final robot design. For example, assume that a particular sub-component is a robotic arm having two segments and an elbow controlled by a servo-motor. The sub-component may be defined by the

5

mechanical structure or assembly of the arm, the electrical components and connections that operate the arm, and software that can be used to control the arm. The composition algorithm module may compile each of these, within the context of parameters **112**, to generate a fabrication file that defines these elements for the specific robot.

To generate the electrical components, the composition algorithm module **118** may identify electrical connections to be made between the sub-components in order to effectuate the final robot design. To do so, the composition algorithm module **118** may form or define specific electrical connections that will allow the robot to operate. For example, in a robotic arm, the composition algorithm module **118** may specify that a servo-motor in the arm should be connected to, say, a power pin, a ground pin, and a pulse-width modulated output pin of a modular controller in the arm.

The composition algorithm module **118** may also generate electrical components and/or electrical connections based on the parameters **112**, which may include parameters set by the user, fixed parameters, parameters calculated by a function, etc. In embodiments, the composition algorithm module **118** can also choose/insert the controller modules into a robot design. For example, if the user specifies that a robotic arm has three segments and two joints, the composition algorithm module **118** may specify the number of electrical components needed and the type of components (e.g. two servo-motors in this example), and connections for two servo-motors, one at each joint.

The composition algorithm module **118** may also define inter-module connections. For example, the composition algorithm module **118** may specify that the modular controller in the arm will be connected to, say, communication pins 1 and 2 of a central controller of the robot, which may be a separate sub-component of the robot. The electrical interconnections can be subsequently used by the implementation engine **20** to create wiring diagrams, wiring instructions, etc.

To generate the mechanical components, the composition algorithm module **118** may identify mechanical interconnections and couplings between the sub-components. For example, if the user specifies that the robotic arm has two segments, the composition algorithm module **118** will define a joint between the two segments. If the user specifies that the robotic arm has three segments, the composition algorithm **118** will define two joints.

To generate the software components, the composition algorithm module **118** may identify software components associated with the sub-components **110**. The software components may comprise control elements, such as graphical user interface elements, that can be incorporated into a software application for controlling the robot. The software application may be executed by a personal computer, mobile phone, tablet computing device, etc. The software components may also include software that is programmed into the robot controller to operate the robot and its parts.

The robotic arm may include sliders, knobs, or other graphical software elements that can move individual segments of the arm. In another embodiment, the software is an API and/or software library for controlling the sub-component that can be accessed by other software applications.

The composition algorithm **118** may tailor the software elements in accordance with the parameters **112**. For example, if the robotic arm contains two servo motors, composition algorithm **118** may produce software with graphical control elements or API functions for controlling the two servo motors.

6

Composition algorithm **118** collects the electrical, mechanical, and software elements of the robot design as a so-called fabrication file, which is sent to implementation engine **120**.

In an embodiment, the composition algorithm module **118** takes, as an input, the individual design elements from each sub-component and compiles them into a single set of design elements. The single set of design elements is then sent to the implementation engine **120**. Mechanical design elements can be virtually arranged and connected according to the specified connections and combined into a mechanical design that incorporates the individual sub-components by unifying shared geometries and adding support material as necessary. The electrical elements are combined by combining all of the device requirements for assignment into available processor ports. For example, a component controller may be assigned to ports (or e.g. pins) 5 and 6, for example, of the central controller. These assigned ports are then codified into a software library and mapped to the software elements associated with each sub-component (e.g. software elements associated with the components in library **106**) to form a single software project that can be compiled into an application for controlling the robot by sending signals to the appropriate ports. The software project may include software that can run on the processor(s) of the robot, an application that can run on a computer or mobile device, or a combination thereof.

Implementation engine **120** receives the fabrication file and produces a fabrication system **116** that can be used to assemble the final robot. Implementation engine **120** comprises software drivers or algorithms that translate the fabrication file into output types that can be used by specific fabrication tools.

In one example, the mechanical elements of the robot are implemented as a foldable or printable robot that can be printed as a two-dimensional cutout and subsequently folded to form a three-dimensional structure. Such robots are described in U.S. patent application Ser. No. 13/723,364, which is incorporated here by reference in its entirety. In this example, implementation engine **120** may generate files that a printer, such as a vinyl or plastic sheet printer, can use to print the robotic structure. Compilation engine may also create a fold pattern or other printable file containing instructions for how to fold or assemble the mechanical elements of the robot. In another example, implementation engine **120** creates a 3D print file that can be sent to a 3D printer to print or grow the part.

The implementation engine **120** also generates electronic design components such as wiring diagrams and wiring instructions as part of fabrication system **116**. The wiring diagrams and instructions correspond to the electrical connections generated by the implementation engine. The wiring diagrams and instructions can be used by an assembler to connect the electrical components of the robot.

The implementation engine **116** also generates software design components. The software design components may be software code, a library, an API, and/or other software elements that can be used to control the robot such as GUI elements that can be incorporated into a software application to control the robot, a fully or partially compiled computer or mobile application for controlling the robot, or a combination thereof. The software components generated by the implementation engine **116** can also include software documentation for connecting to the API or for using the GUI elements or application.

Referring to FIG. 2A, a method **200** for generating the mechanical design for a robot begins in block **202**. In block

204 the system 100 receives user generated design parameters such as input parameters 104 from interface 102. In block 206, the system 100 receives modular components to be included in the robot design from library 106.

In block 208, compiler 114 generates an overall mechanical layout of the robot including mechanical portions of the components from library 106, parameters 104 received from interface 102.

In block 210, the composition algorithm module 118 adds mechanical support structures. For example, if two components are to be mechanically coupled, then mounts, joints, fasteners, flanges, or other mechanical support structures are added to the robot design. Additionally or alternatively, composition algorithm module 118 adds mechanical support structures by, for example, adding mechanical supports such as straps or additional beams to strengthen the mechanical structure of the robot if needed.

In block 212, composition algorithms module creates a fabrication file that defines the complete structure of the robot. In block 214, implementation engine 120 translates the fabrication file into fabrication system 116 which can be used to print, build, and/or assemble the robot.

Referring to FIG. 2B, a method 216 for generating the electrical design for a robot begins in block 218. In block 220 the system 100 receives user generated design parameters such as input parameters 104 from interface 102. In block 222, the system 100 receives modular components to be included in the robot design from library 106.

In block 224, compiler 114 generates and defines electrical connections based upon electrical portions of the selected components from library 106 and the parameters 104 received from interface 102.

In block 226, the composition algorithm module 118 generates wiring diagrams for some or all of the selected modular components. In block 228 a wiring diagram for the entire structure and/or for a portion of the structure is provided to the implementation engine 120, which generates the electrical wiring diagram and instructions as part of fabrication system 116.

Referring to FIG. 2C, a method 230 for generating software applications and/or software components for a robot begins in block 232. In block 234 the system 100 receives user generated design parameters such as input parameters 104 from interface 102. In block 236, the system 100 receives modular components to be included in the robot design from library 106.

In block 238, compiler 114 generates software libraries, GUI elements, or other software elements for controlling the robot and/or the components of the robot as retrieved from library 106. In block 240, the software code is provided to implementation engine 240.

Referring now to FIG. 3 a robot 300 includes a central controller 302 and multiple component modules 304, 306, 308, and 310. The central controller may include a processor and hardware storage, such as a memory for example. The memory may contain software which, when executed by the processor, can directly control the robot, can provide an interface for external software to control the robot, or both. In an embodiment, the central controller may include a processor, microprocessor, custom processor or any type of processor that can be used to control the robot. In one embodiment, the central processor may be implemented by an Arduino™ system, a Raspberry Pi™ system, a custom microprocessor-based system, or the like.

The component modules can be modular elements added to the robot by the user and/or components automatically added to the robot by the composition module. For example,

if the robot is a robotic arm, component modules 304-310 may be individual arms, fingers, displays, or other elements added to the robot by the user.

The component modules contain a component controller 312 for controlling the component modules. Coupled to the component controllers are one or more controllable elements 320. The controllable elements are electrical or electromechanical elements that can be controlled and operated by the component controller. Controllable elements 320 may include, but are not limited to, motors, LEDs, displays, power supplies, digital or analog input or output ports, serial or parallel communication ports, sensors, speakers, microphones, and the like. Controllable elements 320 may be any type of electrical or electromechanical device that can be included in a robot. Each component controller 314-318 can be coupled to and control one or more controllable elements 320. In other embodiments, the central controller 302 may directly control controllable elements 320 without the need for computer controllers 314-318. In this case, the controllable elements 320 may be coupled directly to the central controller 302. In other embodiments, the central controller 302 may optionally be omitted from robot 300. In this case, one or more component controllers 314-318 (individually or in concert with each other) may act to control the robot functionality.

The component controllers can be in direct communication with central controller 302, as shown by communication line 322 between central controller 302 and component controller 304. Additionally or alternatively, component controllers can be in indirect communication with central controller 302. For example, component controller 318 is coupled directly to component controller 316 via communication line 324 and communicates with central controller 302 indirectly by sending and receiving communication through component controller 316.

In an embodiment, the communication lines such as 322 and 324 are serial communication lines, parallel communication lines, wireless communication lines, or any type of communication media between component controllers and/or central controller 302.

As an example, if component module 306 is an articulable finger of a robotic arm, component controller 314 may communicate with central controller 302, which may instruct component controller 314 as to how and when to articulate the finger. Controllable element 320 may be a servo-motor to move the finger and controllable element 320a may be an LED, for example. Communications from the central controller instruct component controller 314 as to how and when to activate the servo-motor 320 to move the finger, and how and when to light the LED 320a.

Referring now to FIG. 4, a component controller 400 may be the same as or similar to one or more of component controllers 312-318. Component controller 402 includes a processor 402 and memory such as a ROM or Flash (not shown). Software, e.g. firmware, instructions may be stored on the memory and executed by the processor to effectuate functionality of the component controller 400. In an embodiment, each component controller has the same software or firmware running on its processor.

The processor 402 may have one or more input and/or output ("I/O") ports 404, 406, and 408 that can be coupled to controllable elements such as motor 410, LED 412, and sensor 414. In an embodiment, ports 404, 406, and 408 can be programmed to be input ports, output ports, digital ports, analog ports, etc. in response to configuration commands received from central controller 302. The compiler 114 may determine, during compilation of the robot design, how the

ports **404-408** will be configured based on what type of controllable element is coupled to the port.

Component controller **400** also includes one or more communication ports such as communication ports **420** and **422**. Communication ports **420** and **422** may be configurable as so-called upstream ports for communicating with an upstream component controller (e.g. component controller **316**) or for communicating with central controller **302**. Communication ports **420** and **422** may also be configurable as so-called downstream ports for communicating with a downstream component controller (e.g. component controller **318**). Communication ports may be serial ports, parallel communication ports, wireless ports, networking or LAN ports, or any other type of communication port.

The software or firmware executed by processor **402** may provide an interface to initialize the IO ports **404-408**. For example, the software compiled by compiler **114** and executed by central controller **302** may initialize the IO ports **404-408** by sending initialization command to the component controller **314** based on the type of controllable element connected to the IO port. In this example, central controller **302** may send command to initialize port **404** as an analog output port to control motor **410**, to initialize port **406** as an analog output port to control LED **412**, and initialize port **408** as a digital input port to receive digital data from sensor **418**. Of course, if sensor **418** provides analog data, port **408** can be configured as an analog input port.

Once the ports are initialized, central controller **302** can send commands to processor **402** to control the elements attached to the ports. For example, central controller **302** may issue a command that instructs processor **402** to provide, say, a 2.5 V or other output voltage on port **406** to illuminate LED **412**.

Referring now to FIG. 5, component library **500** may be the same as or similar to library **106** in FIG. 1. Library **500** can store base or atomic level elements **502**. Base level elements are elements that do not call upon other elements. They include, but are not limited to, mechanical elements such as hinges, beams, extensions, tabs, etc. that can be incorporated into the robot design; electrical elements such as an Arduino board definition, an LED, a photo-sensor, a switch, etc.; and software elements such as software that can be executed by the central controller or other software elements that can be included in the robot design such as drivers, and/or software components, such as GUI elements like sliders, toggle switches, etc., that can comprise or be included in a software application used to control the robot.

Library **500** also includes composite elements **504**, which include elements that incorporate other elements from library **500** such as the base or atomic level elements **502**. As an example, a leg element may include one or more beams, firmware, motors, software, and/or GUI elements as part of the definition of the leg. Composite elements can include base elements and/or other composite elements as part of their definition. These base and composite elements can be accessed and used by the user to design the robot. In embodiments, the user can create the component elements and store them in library **500**.

Referring to FIG. 6, a hierarchical diagram **600** of library elements shows a particular design for the robotic arm or plotter **700** of FIG. 7.

Diagram **600** includes a top level element called plotter **601**. Plotter **602** is the definition of the robot being designed. Referring also to FIG. 3, plotter **602** includes a brain **604**, which may comprise software to be downloaded into central

controller **302** to effectuate the robot design and initialize the component controllers **312-318** in accordance with the design.

Plotter **601** also includes an arm **604** having one or more actuated hinges **606** and beams **608**. The actuated hinges **606** may correspond to elbows **702** and **704** in FIG. 7. The beams **604** may correspond to the arm beams **706** and **708**. Each actuated hinge **606** includes a servo motor **610**, which in turn includes a motor **612**, an EModule or motor driver **614**, and a mount **616**. Each mount may include a cutout element **618**. The servo motor elements can be seen as servo motors **710** and **712** in FIG. 7. The actuated hinges **606** also include a hinge element **611** that defines the mechanical structure of the hinge and a tendon element **612** that can be connected between the servomotor and the arm segments so that the motor can move the arm. The arm **604** also includes one or more beams **608**.

Plotter **601** also includes an actuated gripper element **620**, which in turns includes another servo **622** and a gripper element **624**. The actuated gripper element can be seen as the grip portion **714** of arm **700**. The actuated gripper element **620** also includes a gripper **624**, which includes a block **626** and one or more fingers **628**, each having one or more beams **630**. Servo **622** corresponds to servo motor **716** in FIG. 7, and fingers **628** correspond to fingers **718** and **720** of the gripping portion **714**.

The hierarchical definition of the plotter **601** informs the compiler **114** of the robot design. The compiler **114** may then compile the mechanical, electrical, and software components of fabrication system **116** that allow the robot to be assembled, as described above. As shown in FIGS. 6 and 7, the hierarchical definition of plotter **601** may produce a fabrication system which, when assembled, results in the assembled plotter arm as shown in FIG. 7.

Referring now to FIG. 8, another robot design **800** includes a definition for a plotter **802**, which may be the same as or similar to plotter **601**. FIG. 8 illustrates that elements in the hierarchical design may include multiple instances. For example, the arm **804** includes k number of actuated hinge elements **806** and beam elements **808**, depending on the parameters input by the user. Similarly, the actuated gripper element **810** includes n number of fingers **812**, which each contain m number of beams **814**, depending on the parameters input by the user. The number k and n can be set by the user, or can be set by the system. In embodiments, the numbers k and n may have default values that are stored in library **500** or computed by the system during compilation.

In an embodiment, a computer (or a series of computers connected by a network) includes a processor or series of processors and a volatile or non-volatile memory or series of memories. Computer readable instructions stored in the memory may be executed by the processor.

The computer may also include a database or series of databases that can be stored on a hard drive or other storage device. The database may be any database, relational or otherwise, known in the art that can store data such as model data for foldable machines.

Having described various embodiments, which serve to illustrate various concepts, structures and techniques, which are the subject of this patent, it will now become apparent to those of ordinary skill in the art that other embodiments incorporating these concepts, structures and techniques may be used. Accordingly, the scope of the patent should not be limited to the described embodiments but rather should be limited only by the spirit and scope of the following claims.

11

What is claimed is:

1. A system for generating applications for controlling a robot comprising:

an interface, executed by a computing device, to receive design parameters for a robot;

a library, stored in a memory, of predefined components each describing a modular element of the robot, the predefined components including electrical, mechanical, software, and composite elements; and

computer readable instructions, stored in a memory, to implement a compiler to generate a robot design by modifying the predefined components by applying the design parameters to the predefined components, compiling software to be executed by the robot, and providing data and instructions for fabricating a mechanical and electrical system of the robot;

means for assembling the robot from the compiled robot design.

2. The system of claim 1 wherein said compiler comprises:

a composition engine configured to receive one or more predefined components and component design parameters and in response thereto provides a fabrication file, a wiring diagram, and a single set of component control code;

an implementation engine configured to receive the fabrication file, wiring diagram, and a single set of component control code and in response thereto to provide instructions to one or more fabrication systems.

3. A system for generating a robot design comprising:

an interface, executed by a computing device, receive design specification for a robot;

a library, stored in a memory, of predefined components each describing a modular element of the robot; and computer readable instructions, stored in a memory, to implement a compiler to generate a robot design in accordance with the design specification and including one or more of the predefined components;

means for assembling the robot from the compiled robot design.

4. The system of claim 3 wherein the interface is a user interface and the design specifications are entered by a user of the system.

5. The system of claim 3 wherein the predefined components comprise one or more of electrical components, mechanical components, and software components.

6. The system of claim 5 wherein the electrical components include definitions of electrical connections.

7. The system of claim 6 wherein the electrical connections include pin assignments for a controller module associated with the electrical component.

8. The system of claim 7 wherein the controller module is configured to communicate with a main controller of the robot and to control electrical and/or electromechanical elements of the predefined components.

9. The system of claim 5 wherein the mechanical components include reference designs that define a mechanical structure of a modular element of the robot.

10. The system of claim 5 wherein the software components include microcontroller code executed by the robot, user interface elements to allow a user to control the robot, or both.

11. The system of claim 5 wherein the predefined components further comprise composite components, which

12

include one or more of the electrical components, the mechanical components, the software components, and/or other composite components.

12. The system of claim 5 wherein the robot design includes mechanical fabrication files.

13. The system of claim 12 wherein the mechanical fabrication files include a file to print a two-dimensional element, a file to print a three-dimensional element, or both.

14. The system of claim 13 wherein the mechanical fabrication files further include instructions for folding a printed two-dimensional element to form a three-dimensional element.

15. The system of claim 5 wherein the robot design includes a wiring diagram, instructions for electrically connecting the predefined components, or both.

16. The system of claim 5 wherein the robot design includes a compiled software application that provides a user interface for a user to directly operate the robot.

17. The system of claim 16 wherein the software application is configured to run on a mobile device.

18. The system of claim 5 wherein the robot design includes one or more software applications configured to be run by one or more controllers of the robot.

19. The system of claim 18 wherein the software application is run by a main controller and causes the main controller to communicate with one or more controller modules associated with the predefined components to control the predefined components.

20. The system of claim 3 wherein the compiler is configured to modify one or more of the predefined elements by applying the design parameters to one or more modifiable characteristics of the predefined elements.

21. The system of claim 20 wherein the compiler is further configured to add one or more predefined elements to the robot design.

22. A method comprising:
receiving design specifications for a design of a robot;
retrieving, from a robot component database, one or more predefined components each describing a modular element of the robot, the predefined components including electrical, mechanical, software, and composite elements;

modifying the predefined components by applying the design specifications to the predefined components;

generating software to be executed by one or more of the robot, the software including one or more communication modules for communicating with auxiliary controller modules associated with the predefined components; and

generating mechanical fabrication files for manufacturing mechanical aspects of the modified predefined components of the robot; and

generating electrical fabrication files for assembling electrical aspects of the modified predefined components of the robot;

step means for assembling the robot from the compiled robot design generated software, mechanical fabrication files, and electrical fabrication files.

23. The method of claim 22 wherein generating the software includes generating software to be executed by a processing device for controlling the robot.

24. The method of claim 23 wherein the generating the software to be executed by a processing device for controlling the robot includes generating GUI elements.