

US010082467B2

(12) United States Patent

Cadieux, Jr.

(10) Patent No.: US 10,082,467 B2

(45) Date of Patent:

Sep. 25, 2018

(54) MENTHOL DETECTION ON TOBACCO

(71) Applicant: ALTRIA CLIENT SERVICES LLC,

Richmond, VA (US)

(72) Inventor: Edmond J. Cadieux, Jr.,

Mechanicsville, VA (US)

(73) Assignee: Altria Client Services LLC,

Richmond, VA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 15/346,492

(22) Filed: Nov. 8, 2016

(65) Prior Publication Data

US 2017/0052120 A1 Feb. 23, 2017

Related U.S. Application Data

- (60) Continuation of application No. 14/802,699, filed on Jul. 17, 2015, now Pat. No. 9,488,580, which is a (Continued)
- (51) Int. Cl.

 B03B 1/00 (2006.01)

 G01N 21/64 (2006.01)

 (Continued)
- (52) U.S. Cl.

21/85 (2013.01); G01N 21/94 (2013.01); G01N 21/95 (2013.01); B07C 2501/0018 (2013.01); C10N 2240/56 (2013.01);

(Continued)

(58) Field of Classification Search

CPC G01N 21/6428; A24B 1/04; A24B 13/00; A24B 15/10; B07C 5/3427; B07C 5/366

(56) References Cited

U.S. PATENT DOCUMENTS

3,417,241 A 12/1968 Davis (Continued)

FOREIGN PATENT DOCUMENTS

CA 2837315 A1 11/2012 DE 20320957 U1 7/2005 (Continued)

OTHER PUBLICATIONS

International Search Report of International Application No. PCT/US2014/026556 dated Jul. 28, 2014.


(Continued)

Primary Examiner — Terrell Howard Matthews (74) Attorney, Agent, or Firm — Harness, Dickey & Pierce, P.L.C.

(57) ABSTRACT

A method for detecting mentholated tobacco, comprising irradiating tobacco containing menthol and a fluorescent taggant with radiation and observing the tobacco for fluorescence from the taggant. A system and method for detecting and separating mentholated tobacco from non-mentholated tobacco within a product stream is also provided.

22 Claims, 1 Drawing Sheet




6,025,200 A 2/2000 Kaish et al. Related U.S. Application Data 6,058,940 A * 5/2000 Lane A24B 15/18division of application No. 14/495,756, filed on Sep. 131/297 6,060,677 A 5/2000 Ulrichsen et al. 24, 2014, now Pat. No. 9,097,688, which is a contin-6,064,032 A 5/2000 Voss et al. uation-in-part of application No. 13/842,512, filed on 6,135,386 A 10/2000 Garthaffner Mar. 15, 2013, now Pat. No. 9,073,091. 6,149,719 A 11/2000 Houle 6,166,366 A 12/2000 Lewis et al. (51)Int. Cl. 11/2001 Meyer et al. 6,312,958 B1 6,380,547 B1 4/2002 Gonzalez et al. A24B 15/10 (2006.01)6,384,359 B1 5/2002 Belcastro et al. A24B 13/00 (2006.01)6,444,143 B2 9/2002 Bawendi et al. G01N 21/84 (2006.01)6,477,227 B1 11/2002 Kaiser et al. A24B 1/04 (2006.01)6,511,756 B1 1/2003 Obuchi et al. B07C 5/342 (2006.01)6,529,273 B1 3/2003 Norris et al. 10/2003 Hegazi et al. 6,633,043 B2 B07C 5/36 (2006.01)6,734,383 B1 5/2004 Calcoen et al. C10L 1/00 (2006.01)6,771,365 B1 8/2004 Pirani et al. G01N 21/359 (2014.01)6,795,179 B2 9/2004 Kumar G01N 21/55 (2014.01)6,809,819 B1 10/2004 Vinjamoori et al. 6,830,310 B2 12/2004 Iu et al. G01N 21/85 (2006.01)6,905,538 B2 6/2005 Auslander G01N 21/94 (2006.01)6,914,678 B1 7/2005 Ulrichsen et al. B65G 27/00 (2006.01)8/2005 Bleikolm et al. 6,926,764 B2 G01N 21/95 (2006.01)10/2006 Selinfreund et al. 7,124,944 B2 G01N 21/952 (2006.01)7,142,296 B2 * 11/2006 Cunningham B01L 3/5085 356/326 U.S. Cl. (52)7,153,557 B2 12/2006 Rancien CPC G01N 21/952 (2013.01); G01N 2021/646 7,157,611 B2 1/2007 Banavali et al. (2013.01); G01N 2021/6417 (2013.01); G01N 7,227,148 B2 6/2007 Sato et al. 2021/6439 (2013.01); G01N 2021/845 8/2007 Ross et al. 7,256,398 B2 (2013.01); G01N 2021/8411 (2013.01); G01N 1/2008 Sullivan 7,319,039 B2 7,378,675 B2 5/2008 Ross et al. 2021/8466 (2013.01); G01N 2021/8592 7,391,035 B2 6/2008 Kong et al. (2013.01)7,441,704 B2 10/2008 Ross 7,488,945 B2 2/2009 Li et al. **References Cited** (56)7,538,324 B2 * 250/339.11 U.S. PATENT DOCUMENTS 7,705,144 B2 4/2010 Holmes 7/2010 Zeinali et al. 7,749,438 B2 3,806,727 A 4/1974 Leonard et al. 7,767,457 B2 8/2010 Mun et al. 3,812,349 A 5/1974 Gugliotta et al. 7,768,643 B1 8/2010 Janssens et al. 4/1975 Gray 3,880,289 A 7,800,088 B2 9/2010 Ross et al. 204/273 356/419 3,985,582 A 10/1976 Onera 7,816,616 B2 10/2010 Kenny et al. 131/300 400/241 11/1977 deVial et al. 4,057,721 A 7,842,896 B1 11/2010 Calcoen et al. 4,175,996 A 11/1979 Battard et al. 7,919,325 B2 4/2011 Eastwood et al. 4,445,520 A 5/1984 Knight et al. 5/2011 Izumiya et al. 7,938,124 B2 11/1984 Kelly, Jr. 4,480,702 A 7,985,590 B2 * 7/2011 McNeil B82Y 15/00 4,657,144 A * 4/1987 Martin A24B 1/04 436/58 131/108 8,415,165 B2 4/2013 Liang et al. 4,845,374 A 7/1989 White et al. 2/2014 Purdy et al. 8,641,933 B2 8/1989 Molina 4,858,465 A 4/2014 Sommer, Jr. et al. 8,692,148 B1 9,006,599 B2 4/2015 Adams et al. 131/108 9,073,091 B2 7/2015 Cadieux et al. 7/2015 Faenza B07C 5/342 5,048,543 A 9/1991 Smith 9,080,987 B2 * 5,092,349 A 3/1992 Smith et al. 9,097,668 B2 8/2015 Cadieux et al. 5,134,291 A 7/1992 Ruhl, Jr. et al. 9,244,017 B2 * 1/2016 Cadieux, Jr. G01N 21/88 11/1993 Long 5,265,732 A 6/2016 Bown et al. 9,361,561 B2 8/1995 Cooper 5,440,919 A 9,546,966 B2 1/2017 Cadieux, Jr. et al. 10/1995 Hereford et al. 5,462,176 A 8/2017 Cadieux, Jr. et al. 9,733,197 B2 5,476,108 A * 12/1995 Dominguez A24C 5/3412 10/2017 Urey G01N 27/447 9,791,407 B2* 131/108 2001/0045378 A1 11/2001 Charles et al. 5,525,516 A 6/1996 Krutak et al. 2002/0074269 A1 6/2002 Hensley et al. 9/1996 Cain et al. 5,554,408 A 7/2002 Kaiser et al. 2002/0094058 A1 9/1996 Patel et al. 5,554,480 A 7/2002 Kaiser et al. 2002/0097833 A1 9/1997 Slater et al. 5,665,538 A 9/2002 Kems et al. 2002/0122878 A1 2/1998 Hapke et al. 5,715,843 A 2002/0158212 A1 10/2002 French et al. 6/1998 White 5,764,874 A 2/2003 Safai 2003/0034282 A1 9/1998 Albert et al. 5,804,447 A 2003/0036201 A1 2/2003 Nelson et al. 9/1998 Tingey et al. 5,807,605 A 2003/0058990 A1 3/2003 Kaiser et al. 5,846,830 A 12/1998 Demello et al. 2003/0097833 A1 5/2003 Ingram et al. 5,887,073 A 3/1999 Fazzari et al. 7/2003 Martinez Carballido 2003/0129283 A1 11/1999 Kuroda et al. 5,974,860 A 2003/0141459 A1 7/2003 Hegazi et al. 5,990,197 A 11/1999 Escano et al. 5,998,211 A 12/1999 Albert et al. 2003/0183326 A1 10/2003 O'Connor

(56) Referen			nces Cited			0108293 A1 0131596 A1		Cadieux,	
	U.S.	PATENT	DOCUMENTS			0131390 A1 0131629 A1		Cadieux, Cadieux,	
2003/0194052	A1*	10/2003	Price G01N 23/223			FOREIGN	N PATE	NT DOC	UMENTS
2004/0134504	A1*	7/2004	Lane A24B 15/18	8	DE EP	1020110076 01462	666 A1 299 A1	10/2012 6/1985	
2005/0031838	A 1	2/2005	Lagunowich et al.	_	EP		446 A2	5/1987	
2005/0083720			Fukui et al.		EP	6570	028 B1	7/1997	
2005/0092336			Zielke et al.		EP	0897	762 A2	2/1999	
2005/0092408	$\mathbf{A}1$	5/2005	Lauf et al.		EP	27153	320 A2	4/2014	
2005/0236015	$\mathbf{A}1$	10/2005	Goel et al.		GB	20914	416 A	7/1982	
2005/0241989	$\mathbf{A}1$	11/2005	Sant et al.		JP	S612900	057 A	12/1986	
2005/0276906			Metzger		JP		095 A	3/1989	
2006/0016735			Ito et al.		JP	H06667		3/1994	
2006/0081503			Wegner		JР	20025054		2/2002	
2006/0118741			Ross et al.		JР	2002513		5/2002	
2006/0131517			Ross et al.		JP JP	20145121 20145154		5/2014 6/2014	
2006/0131518 2006/0186348			Ross et al. Nguyen et al.		WO	19910172		11/1991	
2006/0180348			Cole et al.		WO		243 A1	1/1998	
2006/0240020			Sullivan		WO	99574		11/1999	
2006/0291872			Mei et al.		WO	19990574		11/1999	
2007/0023715			Ross et al.		WO	2001025	747 A2	4/2001	
2007/0048761	A1	3/2007	Reep et al.		WO	20010257	748 A2	4/2001	
2007/0084269	A1	4/2007	Quest et al.		WO	2001025	764 A1	4/2001	
2007/0187617	A 1	8/2007	Kong et al.		WO	20010257		4/2001	
2007/0239367		10/2007	Odegard et al.		WO	2001025		4/2001	
2008/0030712			Tokhtuev et al.		WO	20010258		4/2001	
2008/0116272			Giering et al.		WO	20020689		9/2002	
2008/0121815			Agrawal et al.		WO	20080493		5/2008	
2009/0047531			Bartley et al.		WO	20100073		1/2010	
2009/0097833			Imada		WO WO	20120309 20120508		3/2012 4/2012	
2009/0104711 2009/0185182		4/2009 7/2000	Kim et al.		WO	20120303		11/2012	
2009/0183182			Maruichi et al.		WO	2012102		12/2013	
2009/0321623			Ross et al.		WO	2014168		10/2014	
2010/0080456			Paul et al.						
2010/0219377	A1	9/2010	Ebert			OTU	IDD DIT	DI ICATI	ONIC
2010/0224795	A 1	9/2010	Cole et al.			OIL	IEK PU.	BLICATI	ONS
2010/0226861			Cole et al.		Internat	tional Search Re	nort of I	nternations	al Application No. PCT/
2010/0233447			Campbell			2/039870 dated 3	-		ar rippiication 110. 1 C 17
2010/0290040			Berghmans				,		al Application No. PCT/
2010/0320371			Agrawal et al.			3/043172 dated 3	-		ar rippiication 100. 1 C 17
2011/0141272 2011/0151576			Uta et al. Yajima et al.				<i>'</i>		ion and stabilization of
2011/0151570			Yajima et al.			_	•	-	maleic anhydride) block-
2011/0216190			Shimazu B07C 5/342		-	•	- • ·	•	naging" Journal of Bio-
	_ _	· —	348/135		.				ty for Optical Engineer-
2012/0104278	A 1	5/2012	Downing et al.			-			40025-10; XP002664215.
2012/0267287	A1	10/2012			_		_		pplication No. 2,837,315
2012/0302474	A 1	11/2012	Faenza		_	May 23, 2017.			pp:://diamon.com
2013/0082173	A1*	4/2013	Cadieux, Jr G01N 21/88	8		•	rv Repor	t on Pater	ntability of International
			250/301				•		ed Nov. 26, 2013.
2013/0179090	A1*	7/2013	Conroy G01N 21/643						tability of International
0040/0400			702/25	5			•		ed Dec. 2, 2014.
2013/0188170			Wilkins						•
2013/0320216			Aiko et al.		International Preliminary Report on Patentability of International Application No. PCT/US2014/026556 dated Sep. 15, 2015.				
2013/0320237			Cadieux et al.		International Preliminary Report on Patentability and Written Opin-				
2014/0262966 2015/0008162			Cadieux, Jr. Cadieux, Jr. A24B 15/10	n			-		Γ/US2015/060179 dated
2013/0008102	Al	1/2013	209/3.3	•		5, 2017.	Pilvation	11,0,10,	L. C. DECTO, COOT / J. Gated
2015/0048250	A 1	2/2015		J	-		port of I	nternations	al Application No. PCT/
2015/0048230			Cadieux, Jr. et al.			5/060179 dated 3	-		ar reprivation 100. I C1/
2015/0290684		10/2015			00201.	orocorro dated .	Jun. 41, 1	2010.	
2013/0313311					* oitad	l by evaminer			

^{*} cited by examiner

2015/0323459 A1 11/2015 Cadieux, Jr.



MENTHOL DETECTION ON TOBACCO

RELATED APPLICATION

This patent application is a continuation of co-pending Ser. No. 14/802,699, filed on Jul. 17, 2015, which is a divisional of application Ser. No. 14/495,756, filed on Sep. 24, 2014 (now U.S. Pat. No. 9,097,668), which is a continuation-in-part of application Ser. No. 13/842,512, filed on Mar. 15, 2013 (now U.S. Pat. No. 9,073,091), directed to an ON-LINE OIL AND FOREIGN MATTER DETECTION SYSTEM AND METHOD, the contents of each are hereby incorporated by reference for all that it discloses.

FIELD

This disclosure relates to methods and systems for detecting the presence of a flavorant on an agricultural product used in producing a consumer product. More particularly, this disclosure relates to a method for detecting the presence of menthol on tobacco used to produce smoking articles, and in particular cigarettes and any other smokeable or non-smokeable tobacco products.

Environment

Menthol is used as a flavorant in many products including, 25 but not limited to, mentholated cigarettes. Routinely, finished product is "reworked" and reintroduced into raw materials for use in new product. For example, in cigarette manufacturing, cigarettes are routinely diverted from normal production when issues arise in the manufacturing process (e.g. filters not attached correctly, tears in the cigarette paper, etc.). Those cigarettes are sent back to a "ripper room" to recover the tobacco from the cigarette so that it can be reused again. It is very important that mentholated cigarette tobacco not be reintroduced back into non-mentholated 35 product.

It would be advantageous if detection of menthol in tobacco and tobacco products could be conducted on-line, that is in real time during the production process. Heretofore, there has been an absence of an on-line method of 40 detecting menthol on tobacco or in a finished cigarette.

SUMMARY

In one aspect, disclosed herein is a method for detecting 45 mentholated tobacco, comprising irradiating tobacco, especially scrap tobacco, containing menthol and a fluorescent taggant with radiation and observing the scrap tobacco for fluorescence from the taggant, such as wherein the fluorescent taggant is a Stokes shifting taggant, or an anti-Stokes 50 shifting taggant, as previously described.

The process can further comprise separating the mentholated tobacco from non-mentholated tobacco in the scrap.

Alternatively, the process can be conducted when the tobacco is disposed in a tobacco rod which is irradiated with 55 near infrared radiation from a high intensity IR LED light, and reflected IR light is observed using a high speed NIR spectrometer sensor tuned to detect fluorescence emitted from the taggant.

In another aspect, disclosed herein is a composition 60 comprising tobacco, menthol and a fluorescent taggant, such as wherein the fluorescent taggant is a Stokes shifting taggant or an anti-Stokes shifting taggant.

Advantageously, the fluorescent taggant is one which upon pyrolysis decomposes primarily into carbon dioxide 65 and water. Accordingly, the taggant can be an organic taggant, selected from among pyrazolines, oxinates, benzo-

2

xazinones, benzimidazoles, benzthiazoles, thioxanthenes, anthranilic acids, terephthalic acids, aldazines, coumarins, barbituric acids, lumiphores, oxazoles, thiazoles, cumene, stilbenes, and derivatives thereof.

In one form, the organic, fluorescent taggant is one selected from the group consisting of quinine, fluorescein, carmine and indocyanine green and derivatives thereof.

In another form, the fluorescent taggant can be one that absorbs invisible radiation and emits visible radiation, such as one that absorbs ultra violet radiation and emits visible radiation, or one that absorbs infrared radiation and emits visible radiation.

In yet another aspect, disclosed herein is a system for detecting and separating mentholated tobacco from nonmentholated tobacco within a product stream. The system includes: (a) a first conveying means for delivering a product stream; (b) a first detection apparatus for detecting mentholated tobacco, the first detection apparatus positioned proximate the product stream, the first detection apparatus including a high intensity infrared light source directed at the product stream; and a high speed NIR spectrometer sensor tuned to detect a reflected signal from a taggant disposed in the menthol of the mentholated tobacco; and (c) a controller for determining whether the product stream contains mentholated tobacco by monitoring signals obtained from the first detection apparatus.

In one form, the system further includes a second detection apparatus for detecting non-tobacco related material, the second detection apparatus positioned proximate the product stream, the second detection apparatus including a light source for illuminating the product stream and a detector for detecting light reflected from the product stream, wherein the controller also determines whether the product stream contains non-tobacco related material by monitoring signals obtained from the second detection apparatus.

In one form, the system further includes at least one deflecting system responsive to the signals obtained from the first detection apparatus and/or the second detection apparatus, the at least one deflecting system directing fluid under pressure at a portion of the product stream when the controller determines that non-tobacco related material or mentholated tobacco is present in the product stream.

In still yet another aspect, disclosed herein is a method for detecting and separating mentholated tobacco from non-mentholated tobacco within a product stream, the method comprising the steps of: (a) adding a fluorescent taggant to menthol contained in at least one processing machine; (b) conveying a product stream that has been processed by the at least one processing machine; (c) irradiating the conveyed product stream with infrared radiation; (d) detecting infrared radiation emitted from the irradiated product stream due to the presence of the fluorescent taggant and generating a first signal in response thereto; and (e) removing a portion of the conveyed product stream in response to the first signal.

In one form, the method further includes the step of: (f) illuminating the conveyed product stream; (g) detecting light reflected from the illuminated product stream; (h) comparing the light reflected from the illuminated product stream with light that would be expected to be reflected from an illuminated product stream free of non-tobacco related material, and generating a second signal when the reflected light indicates the presence of non-tobacco related material; and (i) removing a portion of the conveyed product stream in response to the second signal.

In one form, the method further includes the step of causing the product stream to fall under the influence of gravity in a cascade.

BRIEF DESCRIPTION OF THE DRAWINGS

The forms disclosed herein are illustrated by way of example, and not by way of limitation, in the FIGURE and in which like reference numerals refer to similar elements and in which:

FIG. 1 presents a schematic representation of a detection and separation system, in accordance herewith.

DETAILED DESCRIPTION

Various aspects will now be described with reference to specific forms selected for purposes of illustration. It will be appreciated that the spirit and scope of the apparatus, system and methods disclosed herein are not limited to the selected forms. Moreover, it is to be noted that the FIGURES provided herein are not drawn to any particular proportion or scale, and that many variations can be made to the illustrated forms.

Each of the following terms written in singular grammatical form: "a," "an," and "the," as used herein, may also refer to, and encompass, a plurality of the stated entity or object, unless otherwise specifically defined or stated herein, or, unless the context clearly dictates otherwise. For example, the phrases "a device," "an assembly," "a mechanism," "a 30 component," and "an element," as used herein, may also refer to, and encompass, a plurality of devices, a plurality of assemblies, a plurality of mechanisms, a plurality of components, and a plurality of elements, respectively.

Each of the following terms: "includes," "including," 35 "has," "having," "comprises," and "comprising," and, their linguistic or grammatical variants, derivatives, and/or conjugates, as used herein, means "including, but not limited to."

Throughout the illustrative description, the examples, and tion. the appended claims, a numerical value of a parameter, feature, object, or dimension, may be stated or described in terms of a numerical range format. It is to be fully understood that the stated numerical range format is provided for illustrating implementation of the forms disclosed herein, 45 upon and is not to be understood or construed as inflexibly limiting the scope of the forms disclosed herein.

Moreover, for stating or describing a numerical range, the phrase "in a range of between about a first numerical value and about a second numerical value," is considered equivalent to, and means the same as, the phrase "in a range of from about a first numerical value to about a second numerical value," and, thus, the two equivalently meaning phrases may be used interchangeably.

It is to be understood that the various forms disclosed herein are not limited in their application to the details of the order or sequence, and number, of steps or procedures, and sub-steps or sub-procedures, of operation or implementation of forms of the method or to the details of type, composition, construction, arrangement, order and number of the system, system sub-units, devices, assemblies, mechanisms, structures, components, elements, and configurations, and, peripheral equipment, utilities, accessories, and materials of forms of the system, set forth in the following illustrative description, accompanying drawings, and examples, unless otherwise specifically stated herein. The apparatus, systems and methods disclosed herein can be

4

practiced or implemented according to various other alternative forms and in various other alternative ways.

It is also to be understood that all technical and scientific words, terms, and/or phrases, used herein throughout the present disclosure have either the identical or similar meaning as commonly understood by one of ordinary skill in the art, unless otherwise specifically defined or stated herein. Phraseology, terminology, and, notation, employed herein throughout the present disclosure are for the purpose of description and should not be regarded as limiting.

Disclosed herein is a method for detecting menthol on tobacco or in finished smoking articles, particularly cigarettes. This method utilizes a taggant that is added to the menthol. An online inspection station can be used to detect the presence of the taggant. The taggant can be detected very reliably in smaller quantities and at higher speeds than detection of menthol without a taggant. Alternatively, mentholated tobacco can be detected visually.

The taggant is comprised of a material that fluoresces at a particular wavelength of light when excited by light, such as for example by ultraviolet light, infrared light or laser light. The wavelengths of light for excitation and emission are dependent on the type of taggant used.

In one form, the fluorescent taggant is a Stokes shifting taggant or an anti-Stokes shifting taggant.

A Stokes shifting taggant is one which absorbs radiation, such as light, at one wavelength and fluoresces/emits radiation at a different wavelength. Conventionally, a Stokes shifting taggant will absorb radiation at a given wavelength and fluoresce or reemit the radiation at lower energy/longer wavelengths. An anti-Stokes shifting taggant absorbs radiation at a given wavelength and remits radiation of higher energy/shorter wavelengths.

In one form of the present invention, the fluorescent taggant absorbs invisible radiation and emits visible radiation. For example, the fluorescent taggant can be one that absorbs ultra-violet radiation and emits visible radiation, or one that absorbs infrared radiation and emits visible radiation.

Alternatively, the fluorescent taggant can be one which absorbs invisible radiation at a first wavelength and emits invisible radiation at a second, different wavelength.

Importantly, the fluorescent taggant should be one which upon pyrolysis decomposes primarily into carbon dioxide and water. Accordingly, the fluorescent taggant is an organic taggant, such as one selected from the group consisting of pyrazolines, oxinates, benzoxazinones, benzimidazoles, benzthiazoles, thioxanthenes, anthranilic acids, terephthalic acids, aldazines, coumarins, barbituric acids, lumiphores, oxazoles, thiazoles, cumene, stilbenes, and derivatives thereof. Advantageously, the organic, fluorescent taggant can be selected from the group consisting of quinine, fluorescein, carmine and indocyanine green and derivatives thereof.

The on-line detection method utilizes a high-speed sensor that is tuned to detect the fluorescent taggant which is added to the menthol. The taggant can be added to the menthol prior to being added to the tobacco product. Accordingly, when combined the product is a composition comprising tobacco, menthol and a fluorescent taggant.

The high-speed sensor consists of a laser diode that is used to excite the taggant at its "excitation" frequency. The detector has a sensor that is tuned to receive light at the taggants "emission" frequency. If the sensor detects the presence of the taggant it will change the state of its output contacts. These output contacts can be used to stop the

manufacturing equipment, set an alarm, and divert the suspect product from the normal production flow.

In one form, the detection system utilizes near-infrared (NIR) reflectance, wherein a high intensity IR LED light is directed at tobacco products and reflected IR light is gathered and analyzed using a high speed NIR spectrometer sensor tuned to detect the reflected signal from the taggant added to the tobacco. NIR light can penetrate into various materials, such as tobacco rods, to a depth of several centimeters, even enabling inspection of finished cigarettes. The high speed NIR sensor can detect the taggant, and therefore menthol in finished cigarettes at a rate of 15,000 per minute, or even at a rate of 20,000 per minute.

The fluorescent taggant can be added to menthol solutions so as to provide taggant concentrations on tobacco of between about 10 and 100 ppm, typically at a concentration of about 50 ppm, based on the weight of the tobacco.

The NIR reflectance detectors can be placed virtually anywhere along the process, such that a signal received by 20 a detector at a known location will indicate the presence of the taggant in the processed material almost immediately, readily indicating the presence of menthol in the product.

In another form, the present invention is directed to a method for detecting mentholated tobacco, comprising irradiating scrap tobacco containing menthol and a fluorescent taggant with radiation and observing the scrap tobacco for fluorescence from the taggant.

According to this form, rather than utilizing a high speed detection system incorporating sensors, the fluorescence of the taggant is detected visually by an observer/inspector by irradiating the scrap tobacco with a light which emits wavelengths incorporating those of the absorbance wavelength of the taggant. Accordingly, in this form it is advantageous to select a fluorescent taggant which emits light at visible wavelengths.

Thus, a fluorescent taggant is selected from those described above which absorbs invisible radiation and emits visible radiation. For example, the fluorescent taggant can be 40 one that absorbs ultra-violet radiation and emits visible radiation, or one that absorbs infrared radiation and emits visible radiation. Of course, under certain circumstances it can be suitable to select a taggant which absorbs visible light at a first visible wavelength and emits visible light at a 45 second visible wavelength.

Upon detection of mentholated tobacco product, the process further comprises separating the mentholated tobacco from non-mentholated tobacco in the scrap.

In another aspect, an online system for detecting and 50 separating mentholated tobacco and non-tobacco related material (NTRM) from non-mentholated tobacco is provided. Referring now to FIG. 1, one form of a detection and separation system 100, as disclosed herein, is shown schematically. In operation, a product stream, such as a tobacco 55 stream, 112 containing non-tobacco related material, such as foil, cellophane, and paper, and/or mentholated tobacco, is delivered from a processing line by conveyor 114. Conveyor 114 is preferably a vibrating inclined conveyor which vibrates as shown by arrows V. In one form, conveyor 114 60 ends above another conveyor 116, which can be an ordinary conveyor belt, and is spaced vertically above conveyor 114 a sufficient distance to accommodate the remainder of the system described below. As product stream 112 reaches the end of conveyor 114, it drops under the influence of gravity 65 in a cascade C to conveyor 116. In one form, because conveyor 114 is inclined, the product stream does not have

6

as great a horizontal velocity when it falls, so that cascade C does not have any significant front-to-back horizontal spread.

Light or electromagnetic radiation having a first wavelength is provided by an optical scanner 118 and is directed toward the cascade C material in the product stream 112 by the mirror 120. Light or electromagnetic radiation that is reflected, refracted or converted by fluorescent or other emission is returned to the mirror 120, and to the optical scanner 118. Some of the light that is not returned interacts with the background element 122, where a portion is returned to the mirror 120, and to the optical scanner 118. These portions returned to the mirror 120 form first, second and third signals.

Light or electromagnetic radiation that is returned from material in the product stream 112 having a wavelength that is longer than the first wavelength is converted into a first signal by the optical scanner 118. Light or electromagnetic radiation having the first wavelength that is reflected by material in the product stream 112 and from the background element 122 is converted into a second signal by the optical scanner 118. Light or electromagnetic radiation having the first wavelength that is scattered by material in the product stream 112 and from the background element 122 is converted into a third signal by the optical scanner 118.

Then, the first, second, and third signals are transformed into a first, second, and third data streams representing the time varying magnitude of each of the signals, and represent the fluorescence channel, reflectance channel, and scatter channel respectively. The data streams are presented to processor 124 and processed.

To detect the presence of mentholated tobacco in the product stream 112, cascade C is irradiated with IR radiation from IR source 126, which may, as shown, be directed toward the cascade C material in product stream 112 by mirror 130. Radiation emitted by mentholated tobacco in cascade C of the product stream 112 is returned to the mirror 130, and then to IR detection device 128. As shown in FIG. 1, the source of radiation 126 and the IR detection device 128 may be housed in one unit, although separate units are within the scope of this disclosure. Likewise, other configurations and orientations for irradiating and detecting radiation, with and without mirrors are also contemplated.

In one form, cascade C of the product stream 112 is irradiated with IR radiation at a wavelength of about 805 nm, and instantaneously emits IR radiation at wavelengths at or about 840 nm from any tagged mentholated tobacco which might be contained in product stream. The emitted IR radiation is in turn detected by IR detection device 128, which sends a signal to processor 124 and is processed.

In one form optical detector 118 has a matrix of electrooptical detectors (not shown), which may be a line-scan camera having a lens and a suitable filter, a photomultiplier tube receiver, or other suitable device.

When optical detector 118 detects non-tobacco related material, or when IR detection device 128 detects mentholated tobacco in product stream 112, processor 124 sends a signal to ejector manifold 132, which is positioned in downstream relation to the region illuminated or radiated by optical detector 118 and irradiated by IR detection device 128. Ejector manifold 132 is in fluid transmission relation to the trajectory of the product stream 112. The ejector manifold 132 includes a plurality of ejector nozzles 134, which are individually directed and controlled to selectively remove undesirable product material 136 from the product stream 112. The ejector nozzles 134 act as conduits for directing fluid pulses to dislodge or otherwise re-direct

product material traveling in the trajectory. Individual ejector nozzles 134 contained in the ejector manifold 132 are driven by a plurality of removal signals, which may be provided by processor 124.

Ejector nozzles 134 are connected to a source of high pressure fluid which is preferably air at approximately 80 psi, although other gases, such as steam, or liquids, such as water, can be used. When one of ejector nozzles 134 opens in response to a signal, a blast of air A is directed against that portion of cascade C in which the non-tobacco related material or mentholated tobacco was detected to force that portion 136 of the product stream and/or non-tobacco related material to fall into receptacle 138 for manual sorting, if necessary. In the case of non-mentholated tobacco, it may be returned to the product processing line upstream or downstream of system 100, depending on whether or not rescanning is desired. Alternatively, portion 136 could be deflected to a conveyor that removes it to another area for processing.

As may be appreciated, system 100 allows tobacco to be 20 processed at greater rates than a system in which the tobacco is scanned on a belt conveyer. This is because when product is optically scanned on a belt, it has to be in a "monolayer," or single layer of particles, for all of the particles on the belt to be visible to the optical detector 118. However, as the 25 tobacco or other material falls in cascade C, relative vertical motion between the various particles of tobacco and nontobacco related material is induced by the turbulence of the falling stream, so there is a greater probability that a particular piece of non-tobacco related material will be 30 visible to optical detector 118 at some point in its fall. Relative vertical motion also results if the non-tobacco related material is significantly lighter or heavier than tobacco so that it has greater or less air resistance as it falls. Relative vertical motion is enhanced by the vibration of 35 conveyor 114 which brings lighter material to the surface of the tobacco before it falls in cascade C, making the lighter material, which is usually non-tobacco related material, easier to detect, as in a monolayer.

The inclination of conveyor 114, in reducing the horizon-tal spread of cascade C as discussed above, also enhances relative vertical motion because the particles in cascade C have little or no horizontal velocity component. Any horizontal velocity component that a particle has when it falls off conveyor 114 is small because conveyor 114 is inclined, and air resistance quickly reduces the horizontal motion to near zero. The relative vertical motion allows a relatively thicker layer of tobacco or other material to be scanned, so that a greater volume can be scanned per unit of scanning area. Given a constant rate of area scanned per unit time, the 50 increased volume scanned per unit area translates into a higher volume of tobacco or other material scanned per unit time.

In one form, system 100, is provided with a user interface 140 that enables an operator (not shown) to observe and 55 control various operational aspects of the system 100. The user interface 140 may include a CRT or LCD panel for output display. For input, the user interface 140 may include a keyboard, touch-screen or other input means known in the art. The operator can view representations of the articles in 60 the product stream 112 as they are processed in system 100 on the user interface 140. Yet further, the user interface 140 provides a means for the operator to configure the operation of system 100 to make a determination between acceptable product and undesirable product. Data gathered by the user 65 interface 140 and provided to the user interface are transported as user interface data 142.

8

Suitable optics and control circuitry for use with optical detector 118 are disclosed in U.S. Pat. No. 4,657,144, the contents of which are incorporated herein by reference. Other optics and control circuitry are contemplated for use herein and are within the scope of the instant disclosure.

In operation, non-tobacco related material is detected by comparing its reflectivity, which depends on a combination of color and surface properties, at a given wavelength to a reference level set above the known reflectivity of tobacco at that wavelength, so that even a particle of non-tobacco related material of the same color as tobacco will be detected if its reflectivity is higher than that of tobacco. The optical detector 118 is sensitive to light with a wavelength in the range of from about 200 nm to about 1300 nm. The sensitivity of optical detector **118** to a particular non-tobacco related material or group of non-tobacco related materials can be enhanced by using filters and windows which transmit those wavelengths that are preferentially reflected by the non-tobacco related materials as compared to the tobacco and which absorb all other wavelengths. The effect of this is to greatly reduce the noise in the electronic signal from the detector.

As may be appreciated, when there is no concern that NTRM may comprise a part of the tobacco stream being processed, the system of FIG. 1 may be modified to exclude the components required to detect NTRM. In this form, components including optical detector 118, mirror 120 and background element 122 may be eliminated from system 100.

All or a portion of the methods, systems and subsystems of the exemplary forms can be conveniently implemented using one or more general purpose computer systems, microprocessors, digital signal processors, microcontrollers, and the like, programmed according to the teachings of the exemplary forms disclosed herein, as will be appreciated by those skilled in the computer and software arts.

Appropriate software can be readily prepared by programmers of ordinary skill based on the teachings of the exemplary forms, as will be appreciated by those skilled in the software art. Further, the devices and subsystems of the exemplary forms can be implemented on the World Wide Web. In addition, the devices and subsystems of the exemplary forms can be implemented by the preparation of application-specific integrated circuits or by interconnecting an appropriate network of conventional component circuits, as will be appreciated by those skilled in the electrical art(s). Thus, the exemplary forms are not limited to any specific combination of hardware circuitry and/or software.

Stored on any one or on a combination of computer readable media, the exemplary forms disclosed herein can include software for controlling the devices and subsystems of the exemplary forms, for driving the devices and subsystems of the exemplary forms, for enabling the devices and subsystems of the exemplary forms to interact with a human user, and the like. Such software can include, but is not limited to, device drivers, firmware, operating systems, development tools, applications software, and the like. Such computer readable media further can include the computer program product of a form disclosed herein for performing all or a portion (if processing is distributed) of the processing performed in implementing the methods disclosed herein. Computer code devices of the exemplary forms disclosed herein can include any suitable interpretable or executable code mechanism, including but not limited to scripts, interpretable programs, dynamic link libraries (DLLs), Java classes and applets, complete executable programs, Common Object Request Broker Architecture (CORBA) objects,

and the like. Moreover, parts of the processing of the exemplary forms disclosed herein can be distributed for better performance, reliability, cost, and the like.

As stated above, the methods, systems, and subsystems of the exemplary forms can include computer readable medium or memories for holding instructions programmed according to the forms disclosed herein and for holding data structures, tables, records, and/or other data described herein. Computer readable medium can include any suitable medium that participates in providing instructions to a processor for 10 execution. Such a medium can take many forms, including but not limited to, non-volatile media, volatile media, transmission media, and the like. Non-volatile media can include, for example, optical or magnetic disks, magneto-optical disks, and the like. Volatile media can include dynamic 15 memories, and the like. Transmission media can include coaxial cables, copper wire, fiber optics, and the like. Transmission media also can take the form of acoustic, optical, electromagnetic waves, and the like, such as those generated during radio frequency (RF) communications, 20 infrared (IR) data communications, and the like. Common forms of computer-readable media can include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, any other suitable magnetic medium, a CD-ROM, CDRW, DVD, any other suitable optical medium, punch cards, paper tape, 25 optical mark sheets, any other suitable physical medium with patterns of holes or other optically recognizable indicia, a RAM, a PROM, an EPROM, a FLASH-EPROM, any other suitable memory chip or cartridge, a carrier wave or any other suitable medium from which a computer can read. 30

The forms disclosed herein, as illustratively described and exemplified hereinabove, have several beneficial and advantageous aspects, characteristics, and features. The forms disclosed herein successfully address and overcome short-comings and limitations, and widen the scope, of currently 35 known teachings with respect to detecting mentholated tobacco.

In the event that any patents, patent applications, or other references are incorporated by reference herein and define a term in a manner or are otherwise inconsistent with either 40 the non-incorporated portion of the present disclosure or with any of the other incorporated references, the non-incorporated portion of the present disclosure shall control, and the term or incorporated disclosure therein shall only control with respect to the reference in which the term is 45 defined and/or the incorporated disclosure was originally present.

As used herein the terms "adapted" and "configured" mean that the element, component, or other subject matter is designed and/or intended to perform a given function. Thus, 50 the use of the terms "adapted" and "configured" should not be construed to mean that a given element, component, or other subject matter is simply "capable of" performing a given function but that the element, component, and/or other subject matter is specifically selected, created, implemented, 55 utilized, programmed, and/or designed for the purpose of performing the function. It is also within the scope of the present disclosure that elements, components, and/or other recited subject matter that is recited as being adapted to perform a particular function may additionally or alternatively be described as being configured to perform that function, and vice versa.

Illustrative, non-exclusive examples of apparatus and methods according to the present disclosure are presented in the following enumerated paragraphs. It is within the scope 65 of the present disclosure that an individual step of a method recited herein, including in the following enumerated para-

10

graphs, may additionally or alternatively be referred to as a "step for" performing the recited action.

PCT1. A method for detecting mentholated tobacco, comprising irradiating tobacco containing menthol and a fluorescent taggant with radiation and observing the tobacco for fluorescence from the taggant.

PCT2. The method of paragraph PCT1, wherein the fluorescent taggant is a Stokes shifting taggant.

PCT3. The method of paragraph PCT1, wherein the fluorescent taggant is an anti-Stokes shifting taggant.

PCT4. The method of any of paragraphs PCT1-PCT3, wherein the fluorescent taggant is one which upon pyrolysis decomposes primarily into carbon dioxide and water.

PCT5. The method of any of paragraphs PCT1-PCT4, wherein the fluorescent taggant is an organic taggant.

PCT6. The method of paragraph PCT5, wherein the organic taggant is one selected from the group consisting of pyrazolines, oxinates, benzoxazinones, benzimidazoles, benzthiazoles, thioxanthenes, anthranilic acids, terephthalic acids, aldazines, coumarins, barbituric acids, lumiphores, oxazoles, thiazoles, cumene, stilbenes, and derivatives thereof.

PCT7. The method of paragraph PCT5, wherein the organic, fluorescent taggant is selected from the group consisting of quinine, fluorescein, carmine and indocyanine green and derivatives thereof.

PCT8. The method of any of paragraphs PCT1-PCT7, wherein the tobacco is scrap tobacco and further comprising separating the mentholated tobacco from non-mentholated tobacco in the scrap.

PCT9. The method of any of paragraphs PCT1-PCT8, wherein the tobacco is disposed in a tobacco rod which is irradiated with near infrared radiation from a high intensity IR LED light, and reflected IR light is observed using a high speed NIR spectrometer sensor tuned to detect fluorescence emitted from the taggant.

PCT10. A composition comprising tobacco, menthol and a fluorescent taggant.

PCT11. The composition of paragraph PCT10, wherein the fluorescent taggant is a Stokes shifting taggant or an anti-Stokes shifting taggant.

PCT12. The composition of paragraph PCT11 or PCT 12, wherein the fluorescent taggant is one which upon pyrolysis decomposes primarily into carbon dioxide and water.

PCT 13. A system for detecting and separating mentholated tobacco from non-mentholated tobacco within a product stream, comprising: (a) a first conveying means for delivering a product stream; (b) a first detection apparatus for detecting mentholated tobacco, the first detection apparatus positioned proximate the product stream, the first detection apparatus including a high intensity infrared light source directed at the product stream; and a high speed NIR spectrometer sensor tuned to detect a reflected signal from a taggant disposed in the menthol of the mentholated tobacco; and (c) a controller for determining whether the product stream contains mentholated tobacco by monitoring signals obtained from the first detection apparatus.

PCT14. The system of paragraph PCT13, further comprising a second detection apparatus for detecting nontobacco related material, the second detection apparatus positioned proximate the product stream, the second detection apparatus including a light source for illuminating the product stream and a detector for detecting light reflected from the product stream, wherein the controller also determines whether the product stream contains non-tobacco related material by monitoring signals obtained from the second detection apparatus.

PCT15. The system of paragraph PCT14, further comprising at least one deflecting system responsive to the signals obtained from the first detection apparatus and/or the second detection apparatus, the at least one deflecting system directing fluid under pressure at a portion of the product 5 stream when the controller determines that non-tobacco related material or mentholated tobacco is present in the product stream.

PCT16. The system of paragraph PCT14 or PCT 15, wherein the fluid so directed is effective to remove the 10 non-tobacco related material or mentholated tobacco.

PCT17. The system of any of paragraphs PCT13-PCT16, wherein the taggant is a fluorescent Stokes-shifting taggant, which absorbs radiation at a first wavelength and emits radiation at a second wavelength, different from the first 15 wavelength.

PCT18. A method for detecting and separating mentholated tobacco from non-mentholated tobacco within a product stream, the method comprising the steps of: (a) adding a fluorescent taggant to menthol contained in at least one 20 processing machine; (b) conveying a product stream that has been processed by the at least one processing machine; (c) irradiating the conveyed product stream with infrared radiation; (d) detecting infrared radiation emitted from the irradiated product stream due to the presence of the fluorescent 25 taggant and generating a first signal in response thereto; and (e) removing a portion of the conveyed product stream in response to the first signal.

PCT19. The method of paragraph PCT18, further including the steps of (e) illuminating the conveyed product 30 stream; (f) detecting light reflected from the illuminated product stream; (g) comparing the light reflected from the illuminated product stream with light that would be expected to be reflected from an illuminated product stream free of non-tobacco related material, and generating a second signal when the reflected light indicates the presence of nontobacco related material; and (h) removing a portion of the conveyed product stream in response to the second signal.

PCT20. The method of paragraph PCT19, further including the step of causing the product stream to fall under the 40 influence of gravity in a cascade.

INDUSTRIAL APPLICABILITY

The containers and processes disclosed herein are appli- 45 cable to the consumer products industry.

It is believed that the disclosure set forth above encompasses multiple distinct inventions with independent utility. While each of these inventions has been disclosed in its preferred form, the specific forms thereof as disclosed and 50 influence of gravity in a cascade. illustrated herein are not to be considered in a limiting sense as numerous variations are possible. The subject matter of the inventions includes all novel and non-obvious combinations and subcombinations of the various elements, features, functions and/or properties disclosed herein. Simi- 55 larly, where the claims recite "a" or "a first" element or the equivalent thereof, such claims should be understood to include incorporation of one or more such elements, neither requiring nor excluding two or more such elements.

It is believed that the following claims particularly point 60 out certain combinations and subcombinations that are directed to one of the disclosed inventions and are novel and non-obvious. Inventions embodied in other combinations and subcombinations of features, functions, elements and/or properties may be claimed through amendment of the pres- 65 ent claims or presentation of new claims in this or a related application. Such amended or new claims, whether they are

directed to a different invention or directed to the same invention, whether different, broader, narrower, or equal in scope to the original claims, are also regarded as included within the subject matter of the inventions of the present disclosure.

What is claimed is:

- 1. A system for detecting and separating mentholated tobacco from non-mentholated tobacco within a product stream, comprising:
 - (a) a first conveying means for delivering a product stream;
 - (b) a first detection apparatus for detecting mentholated tobacco, the first detection apparatus positioned proximate the product stream, the first detection apparatus including a high intensity infrared light source directed at the product stream, and a high speed NIR spectrometer sensor tuned to receive light at a taggants emission frequency and detect an emitted signal from a taggant disposed in the menthol of the mentholated tobacco; and
 - (c) a controller for determining whether the product stream contains mentholated tobacco by monitoring signals obtained from the first detection apparatus.
- 2. The system of claim 1, further comprising a second detection apparatus for detecting non-tobacco related material, the second detection apparatus positioned proximate the product stream, the second detection apparatus including a light source for illuminating the product stream and a detector for detecting light emitted from the product stream, wherein the controller also determines whether the product stream contains non-tobacco related material by monitoring signals obtained from the second detection apparatus.
- 3. The system of claim 2, further comprising at least one deflecting system responsive to the signals obtained from the first detection apparatus and/or the second detection apparatus, the at least one deflecting system directing fluid under pressure at a portion of the product stream when the controller determines that non-tobacco related material or mentholated tobacco is present in the product stream.
- 4. The system of claim 3, wherein the fluid so directed is effective to remove the non-tobacco related material or mentholated tobacco.
- 5. The system of claim 4, further comprising a second conveying means located below and spaced vertically from the first conveying means for further conveying the product stream from the first conveying means, wherein the product stream is transferred from the first conveying means to the second conveying means by falling therebetween under the
- 6. The system of claim 5, wherein the cascade is a turbulent cascade.
- 7. The system of claim 2, wherein the first conveying means is an inclined vibrating conveyor.
 - 8. The system of claim 2, wherein the fluid is a gas.
 - **9**. The system of claim **8**, wherein the gas is air.
- 10. The system of claim 1, wherein the taggant is a fluorescent Stokes-shifting taggant, which absorbs radiation at a first wavelength and emits radiation at a second wavelength, different from the first wavelength.
- 11. The system of claim 1, wherein the fluorescent taggant is an anti-Stokes shifting taggant.
- 12. The system of claim 1, wherein the fluorescent taggant is one which upon pyrolysis decomposes primarily into carbon dioxide and water.
- 13. The system of claim 12, wherein the fluorescent taggant is an organic taggant.

- 14. The system of claim 13, wherein the organic taggant is one selected from the group consisting of pyrazolines, oxinates, benzoxazinones, benzimidazoles, benzthiazoles, thioxanthenes, anthranilic acids, terephthalic acids, aldazines, coumarins, barbituric acids, lumiphores, 5 oxazoles, thiazoles, cumene, stilbenes, and derivatives thereof.
- 15. The system of claim 13, wherein the organic, fluorescent taggant is selected from the group consisting of quinine, fluorescein, carmine and indocyanine green and derivatives thereof.
- 16. A system for detecting mentholated tobacco, comprising a detection apparatus having an infrared light source and a high speed NIR spectrometer sensor positioned proximate a mentholated tobacco stream, wherein the NIR spectrometer sensor is tuned to detect a signal emitted from a taggant disposed in the menthol of the mentholated tobacco.

 15

 16. A system for detecting mentholated tobacco, comprisithioxant aldazine oxazoles thereof.
- 17. The system of claim 16, wherein the taggant is a fluorescent Stokes-shifting taggant, which absorbs radiation at a first wavelength and emits radiation at a second wavelength, different from the first wavelength.

14

- 18. The system of claim 16, wherein the fluorescent taggant is an anti-Stokes shifting taggant.
- 19. The system of claim 16, wherein the fluorescent taggant is one which upon pyrolysis decomposes primarily into carbon dioxide and water.
- 20. The system of claim 19, wherein the fluorescent taggant is an organic taggant.
- 21. The system of claim 20, wherein the organic taggant is one selected from the group consisting of pyrazolines, oxinates, benzoxazinones, benzimidazoles, benzthiazoles, thioxanthenes, anthranilic acids, terephthalic acids, aldazines, coumarins, barbituric acids, lumiphores, oxazoles, thiazoles, cumene, stilbenes, and derivatives thereof.
- 22. The system of claim 20, wherein the organic, fluorescent taggant is selected from the group consisting of quinine, fluorescein, carmine and indocyanine green and derivatives thereof.

* * * * *