



US010088026B2

(12) **United States Patent**
Versteyhe et al.

(10) **Patent No.:** **US 10,088,026 B2**
(45) **Date of Patent:** **Oct. 2, 2018**

(54) **BALL TYPE CVT WITH OUTPUT COUPLED POWERPATHS**

(71) Applicant: **Dana Limited**, Maumee, OH (US)
(72) Inventors: **Mark R. J. Versteyhe**, Oostkamp (BE);
Matthias W. J. Byltiauw, Roeselare (BE)

(73) Assignee: **Dana Limited**, Maumee, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/423,131**

(22) Filed: **Feb. 2, 2017**

(65) **Prior Publication Data**

US 2017/0184188 A1 Jun. 29, 2017

Related U.S. Application Data

(62) Division of application No. 14/425,600, filed as application No. PCT/US2013/057868 on Sep. 3, 2013, now Pat. No. 9,599,204.

(60) Provisional application No. 61/779,687, filed on Mar. 13, 2013, provisional application No. 61/697,917, filed on Sep. 7, 2012.

(51) **Int. Cl.**
F16H 37/08 (2006.01)
F16H 15/28 (2006.01)

(52) **U.S. Cl.**
CPC **F16H 37/086** (2013.01); **F16H 15/28** (2013.01); **F16H 2037/0873** (2013.01)

(58) **Field of Classification Search**
CPC F16H 37/086; F16H 15/28; F16H 2037/0873; F16H 37/0853
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,063,244 A 6/1913 Dieterich
1,215,969 A 2/1917 Murray
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2011224083 A1 10/2011
CN 101392825 A 3/2009
(Continued)

OTHER PUBLICATIONS

Fallbrook Technologies Inc. NuVinci® Technology, Feb. 26, 2013; [Retrieved from internet on Jun. 5, 2014].: URL:https://web.archive.org/web/20130226233109/http://www.fallbrooktech.com/nuvinci-technology.

(Continued)

Primary Examiner — Jacob S. Scott


Assistant Examiner — Tinh Dang

(74) *Attorney, Agent, or Firm* — Marshall & Melhorn, LLC

(57) **ABSTRACT**

Systems, devices, and methods are provided for the transmission of power in motor vehicles. Power can be transmitted in a smoother and more efficient manner, with smaller and even less mechanical components, by splitting torque into two or more torque paths. A power transmission apparatus comprises a power input shaft, a planetary gear set coupled to the power input shaft, and a variator, such as a continuously variable transmission (CVT), coupled to the gear set. The various components of the planetary gear set and the variator are arranged such that torque is split between two or more torque paths and then recombined before power is output to a gear box and a differential of the motor vehicle.

11 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

1,526,140	A	2/1925	Gruver	6,273,838	B1	8/2001	Park
2,019,006	A	10/1935	Ferrari	6,342,026	B1	1/2002	Takagi et al.
2,060,884	A	11/1936	Madle	6,358,178	B1	3/2002	Wittkopp
2,148,759	A	2/1939	Grand	6,371,880	B1	4/2002	Kam
2,405,201	A	8/1946	Franck	6,405,117	B1	6/2002	Walenty et al.
2,660,897	A	12/1953	Neidhart et al.	6,481,258	B1	11/2002	Belinky
2,729,118	A	1/1956	Emslie	6,554,735	B2	4/2003	Kanazawa
2,931,235	A	4/1960	Hayward	6,558,285	B1	5/2003	Sieber
3,203,278	A	8/1965	General	6,585,619	B2	7/2003	Henzler
3,376,633	A	4/1968	Wesley	6,609,994	B2	8/2003	Muramoto
3,407,687	A	10/1968	Hayashi	6,632,157	B1	10/2003	Gierling et al.
3,470,720	A	10/1969	Eklund et al.	6,641,497	B2	11/2003	Deschamps et al.
3,505,718	A	4/1970	Carlstrom	6,645,106	B2	11/2003	Goo
3,583,060	A	6/1971	Sigmans	6,689,012	B2	2/2004	Miller et al.
3,688,600	A	9/1972	Leonard	6,705,964	B2	3/2004	Nagai et al.
3,765,270	A	10/1973	Lemieux	6,719,659	B2	4/2004	Geiberger et al.
3,774,280	A	11/1973	Eklund et al.	6,723,016	B2	4/2004	Sumi
3,831,245	A	8/1974	Amos	6,726,590	B2	4/2004	Henzler et al.
3,894,559	A	7/1975	DePuy	6,733,412	B2	5/2004	Kumagai et al.
4,046,988	A	9/1977	Okuda et al.	6,752,696	B2	6/2004	Murai et al.
4,056,988	A	11/1977	Kubo et al.	6,793,603	B2	9/2004	Teraoka et al.
4,187,709	A	2/1980	Legate et al.	6,849,020	B2	2/2005	Sumi
4,226,140	A	10/1980	Gaasenbeek	6,866,606	B2	3/2005	Ooyama
4,333,358	A	6/1982	Grattapaglia	6,949,045	B2	9/2005	Wafzig et al.
4,344,336	A	8/1982	Carriere	6,979,275	B2	12/2005	Hiraku et al.
4,360,090	A	11/1982	Wonn	6,986,725	B2	1/2006	Morscheck
4,368,572	A	1/1983	Kanazawa et al.	7,033,298	B2	4/2006	Usoro et al.
4,464,952	A	8/1984	Stubbs	7,074,154	B2	7/2006	Miller
4,693,134	A	9/1987	Kraus	7,086,981	B2	8/2006	Ali et al.
4,731,044	A	3/1988	Mott	7,104,917	B2	9/2006	Klemen et al.
4,756,211	A	7/1988	Fellows	7,128,681	B2	10/2006	Sugino et al.
4,784,017	A	11/1988	Johnshoy	7,160,220	B2	1/2007	Shinojima et al.
4,856,371	A	8/1989	Kemper	7,186,199	B1	3/2007	Baxter et al.
4,856,374	A	8/1989	Kreuzer	7,217,214	B2	5/2007	Morscheck
4,950,208	A	8/1990	Tomlinson	7,234,543	B2	6/2007	Schaaf
4,963,122	A	10/1990	Ryan	7,288,044	B2	10/2007	Gumpoltsberger
4,963,124	A	10/1990	Takahashi et al.	7,311,634	B2	12/2007	Shim
5,109,962	A	5/1992	Sato	7,335,126	B2	2/2008	Tsuchiya et al.
5,168,778	A	12/1992	Todd et al.	7,347,801	B2	3/2008	Guenter et al.
5,217,412	A	6/1993	Indlekofer et al.	7,396,309	B2	7/2008	Heitz et al.
5,230,670	A	7/1993	Hibi	7,431,677	B2	10/2008	Miller et al.
5,238,460	A	8/1993	Esaki et al.	7,470,210	B2	12/2008	Miller et al.
5,318,486	A	6/1994	Lutz	7,473,202	B2	1/2009	Morscheck et al.
5,390,759	A	2/1995	Gollner	7,485,069	B2	2/2009	Jang et al.
5,401,221	A	3/1995	Fellows et al.	7,497,798	B2	3/2009	Kim
5,520,588	A	5/1996	Hall, III	7,588,514	B2	9/2009	McKenzie et al.
5,527,231	A	6/1996	Seidel et al.	7,637,838	B2	12/2009	Gumpoltsberger
5,577,423	A	11/1996	Mimura	7,672,770	B2	3/2010	Inoue et al.
5,599,251	A	2/1997	Beim et al.	7,686,729	B2	3/2010	Miller et al.
5,659,956	A	8/1997	Braginsky et al.	7,717,815	B2	5/2010	Tenberge
5,683,322	A	11/1997	Meyerle	7,727,107	B2	6/2010	Miller
5,726,353	A	3/1998	Matsuda et al.	7,780,566	B2	8/2010	Seo
5,730,678	A	3/1998	Larkin	7,874,153	B2	1/2011	Bhem
5,766,105	A	6/1998	Fellows et al.	7,878,935	B2	2/2011	Lahr
5,776,028	A	7/1998	Matsuda et al.	7,951,035	B2	5/2011	Platt
5,800,303	A	9/1998	Benford	7,980,972	B1	6/2011	Starkey et al.
5,860,888	A	1/1999	Lee	8,029,401	B2	10/2011	Johnson
5,915,801	A	6/1999	Taga et al.	8,052,569	B2	11/2011	Tabata et al.
5,961,415	A	10/1999	Justice et al.	8,062,175	B2	11/2011	Krueger et al.
5,971,883	A	10/1999	Klemen	8,066,614	B2	11/2011	Miller et al.
5,996,226	A	12/1999	Gibbs	8,142,323	B2	3/2012	Tsuchiya et al.
6,009,365	A	12/1999	Takahara et al.	8,226,518	B2	7/2012	Parraga Gimeno
6,036,616	A	3/2000	McCarrick et al.	8,257,216	B2	9/2012	Hoffman
6,045,477	A	4/2000	Schmidt	8,257,217	B2	9/2012	Hoffman
6,053,839	A	4/2000	Baldwin et al.	8,287,414	B2	10/2012	Weber et al.
6,059,685	A	5/2000	Hoge et al.	8,313,404	B2	11/2012	Carter et al.
6,071,208	A	6/2000	Koivunen	8,376,903	B2	2/2013	Pohl et al.
6,080,080	A	6/2000	Bolz et al.	8,382,636	B2	2/2013	Shiina et al.
6,083,135	A	7/2000	Baldwin et al.	8,447,480	B2	5/2013	Usukura
6,086,504	A	7/2000	Illerhaus	8,469,856	B2	6/2013	Thomassy
6,089,287	A	7/2000	Welsh et al.	8,545,368	B1	10/2013	Davis et al.
6,095,942	A	8/2000	Yamaguchi et al.	8,594,867	B2	11/2013	Heap et al.
6,155,951	A	12/2000	Kuhn et al.	8,622,871	B2	1/2014	Hoff
6,217,474	B1	4/2001	Ross et al.	8,639,419	B2	1/2014	Roli et al.
6,251,038	B1	6/2001	Ishikawa et al.	8,668,614	B2	3/2014	Sherrill et al.
				8,678,975	B2	3/2014	Koike
				8,870,711	B2	10/2014	Pohl et al.
				8,888,643	B2	11/2014	Lohr et al.
				8,926,468	B2	1/2015	Versteyhe et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,986,150 B2 3/2015 Versteyhe et al.
 9,052,000 B2 6/2015 Cooper
 9,114,799 B2 8/2015 Tsukamoto et al.
 9,156,463 B2 10/2015 Legner
 9,228,650 B2 1/2016 Schoolcraft
 9,551,404 B2 1/2017 Ziech et al.
 2002/0004438 A1 1/2002 Toukura et al.
 2002/0094911 A1 7/2002 Haka
 2002/0169048 A1 11/2002 Henzler et al.
 2003/0060318 A1 3/2003 Sumi
 2003/0181280 A1 9/2003 Elser et al.
 2003/0200783 A1 10/2003 Shai
 2003/0213125 A1 11/2003 Chiuchang
 2003/0216121 A1 11/2003 Yarkosky
 2003/0228952 A1 12/2003 Joe et al.
 2004/0058769 A1 3/2004 Larkin
 2004/0061639 A1 4/2004 Voigtlaender et al.
 2004/0166984 A1 8/2004 Inoue
 2004/0167391 A1 8/2004 Solar et al.
 2004/0171452 A1 9/2004 Miller et al.
 2005/0102082 A1 5/2005 Joe et al.
 2005/0137046 A1 6/2005 Miller et al.
 2005/0153810 A1 7/2005 Miller et al.
 2006/0094515 A1 5/2006 Szuba et al.
 2006/0234822 A1 10/2006 Morscheck et al.
 2006/0276294 A1 12/2006 Coffey et al.
 2007/0021259 A1 1/2007 Tenberge
 2007/0032327 A1 2/2007 Raghavan et al.
 2007/0042856 A1 2/2007 Greenwood
 2007/0072732 A1 3/2007 Klemen
 2007/0096556 A1 5/2007 Kokubo et al.
 2007/0270270 A1 11/2007 Miller et al.
 2007/0275808 A1 11/2007 Iwanaka et al.
 2008/0039273 A1 2/2008 Smithson et al.
 2008/0103002 A1 5/2008 Holmes
 2008/0121487 A1 5/2008 Miller et al.
 2008/0185201 A1 8/2008 Bishop
 2009/0017959 A1 1/2009 Triller
 2009/0048054 A1 2/2009 Tsuchiya et al.
 2009/0062064 A1 3/2009 Kamada et al.
 2009/0112424 A1 4/2009 Dahl et al.
 2009/0132135 A1 5/2009 Quinn, Jr. et al.
 2009/0221391 A1 9/2009 Bazyn et al.
 2009/0221393 A1 9/2009 Kassler
 2009/0286651 A1 11/2009 Tanaka et al.
 2009/0312137 A1 12/2009 Rohs et al.
 2010/0056322 A1 3/2010 Thomassy
 2010/0093476 A1 4/2010 Carter et al.
 2010/0093479 A1 4/2010 Carter et al.
 2010/0106386 A1 4/2010 Krasznai et al.
 2010/0113211 A1 5/2010 Schneider et al.
 2010/0137094 A1 6/2010 Pohl
 2010/0141193 A1 6/2010 Rotondo et al.
 2010/0244755 A1 9/2010 Kinugasa et al.
 2010/0267510 A1 10/2010 Nichols et al.
 2010/0282020 A1 11/2010 Greenwood et al.
 2010/0304915 A1 12/2010 Lahr
 2010/0310815 A1 12/2010 Mendonca Alves et al.
 2011/0015021 A1 1/2011 Maguire et al.
 2011/0034284 A1 2/2011 Pohl et al.
 2011/0152031 A1 6/2011 Schoolcraft
 2011/0165982 A1 7/2011 Hoffman et al.
 2011/0165985 A1 7/2011 Hoffman et al.
 2011/0165986 A1 7/2011 Hoffman et al.
 2011/0165987 A1 7/2011 Hoffman et al.
 2011/0230297 A1 9/2011 Shiina et al.
 2011/0300954 A1 12/2011 Szuba et al.
 2011/0319222 A1 12/2011 Ogawa et al.
 2012/0024991 A1 2/2012 Pilch et al.
 2012/0035016 A1 2/2012 Miller et al.
 2012/0040794 A1 2/2012 Schoolcraft
 2012/0122624 A1 5/2012 Hawkins, Jr. et al.
 2012/0142477 A1 6/2012 Winter
 2012/0165154 A1 6/2012 Wittkopp et al.
 2012/0231925 A1 9/2012 Shiina et al.

2012/0244990 A1 9/2012 Ogawa et al.
 2012/0309579 A1 12/2012 Miller et al.
 2013/0096797 A1 4/2013 Whitney et al.
 2013/0130859 A1 5/2013 Lundberg et al.
 2013/0133965 A1 5/2013 Books
 2013/0184115 A1 7/2013 Urabe et al.
 2013/0190131 A1 7/2013 Versteyhe et al.
 2013/0226416 A1 8/2013 Seipold et al.
 2013/0281244 A1* 10/2013 Vaughn F16H 47/04
 475/72
 2013/0303325 A1 11/2013 Carey et al.
 2013/0304344 A1 11/2013 Abe
 2013/0338888 A1 12/2013 Long et al.
 2014/0194242 A1 7/2014 Cooper
 2014/0194243 A1 7/2014 Versteyhe et al.
 2014/0223901 A1 8/2014 Versteyhe et al.
 2014/0274536 A1 9/2014 Versteyhe et al.
 2014/0274540 A1 9/2014 Schoolcraft
 2014/0274552 A1 9/2014 Frink et al.
 2014/0329637 A1 11/2014 Thomassy et al.
 2015/0024899 A1 1/2015 Phillips
 2015/0051801 A1 2/2015 Quinn, Jr. et al.
 2015/0111683 A1 4/2015 Versteyhe et al.
 2015/0111693 A1 4/2015 Wang et al.
 2015/0142281 A1 5/2015 Versteyhe et al.
 2015/0159741 A1 6/2015 Versteyhe et al.
 2015/0198246 A1 7/2015 Callaway et al.
 2015/0204429 A1 7/2015 Versteyhe et al.
 2015/0204430 A1 7/2015 Versteyhe et al.
 2015/0226294 A1 8/2015 Ziech et al.
 2015/0226298 A1 8/2015 Versteyhe et al.
 2015/0226299 A1 8/2015 Cooper et al.
 2015/0252881 A1 9/2015 Versteyhe
 2015/0354676 A1 12/2015 Versteyhe et al.
 2016/0033021 A1 2/2016 Cooper et al.
 2016/0047448 A1 2/2016 Versteyhe et al.
 2016/0069442 A1 3/2016 Versteyhe et al.
 2016/0109001 A1 4/2016 Schoolcraft
 2016/0116036 A1 4/2016 Schoolcraft
 2016/0131235 A1 5/2016 Phillips
 2016/0195173 A1 7/2016 Versteyhe et al.
 2016/0195177 A1 7/2016 Versteyhe et al.
 2016/0319731 A1 11/2016 Versteyhe et al.
 2016/0356366 A1 12/2016 Versteyhe et al.
 2017/0082049 A1 3/2017 David et al.
 2017/0082193 A1 3/2017 David et al.
 2017/0089433 A1 3/2017 Stevenson et al.
 2017/0089434 A1 3/2017 Waltz et al.

FOREIGN PATENT DOCUMENTS

CN 101479503 A 7/2009
 CN 101617146 A 12/2009
 CN 102297255 A 12/2011
 CN 102338208 A 2/2012
 CN 202165536 U 3/2012
 CN 202392067 U 8/2012
 DE 1237380 B 3/1967
 DE 3245045 A1 6/1984
 DE 102005010751 A1 9/2006
 EP 0156936 A1 10/1985
 EP 0210053 A2 1/1987
 EP 1061288 A2 12/2000
 EP 1174645 A2 1/2002
 EP 2113056 B1 7/2012
 FR 796188 A 3/1936
 FR 1030702 A 6/1953
 FR 1472282 A 3/1967
 FR 2185076 A5 12/1973
 FR 2280451 A1 2/1976
 FR 2918433 A1 1/2009
 GB 1127825 A 9/1968
 GB 2196892 A 5/1988
 GB 2248895 A 4/1992
 JP H09119506 A 5/1997
 JP 2008180214 A 8/2008
 JP 2009058085 A 3/2009
 JP 2011153583 A 8/2011
 WO 2006002457 A1 1/2006

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO 2006041718 A2 4/2006
 WO 2006109158 A1 10/2006
 WO 2007046722 A1 4/2007
 WO 2007051827 A1 5/2007
 WO 2008101070 A2 8/2008
 WO 2008103543 A1 8/2008
 WO 2011011991 A1 2/2011
 WO 2012008884 A1 1/2012
 WO 2012177187 A1 12/2012
 WO 2013109723 A1 7/2013
 WO 2013123117 A1 8/2013
 WO 2014039438 A2 3/2014
 WO 2014039439 A1 3/2014
 WO 2014039440 A1 3/2014
 WO 2014039447 A1 3/2014
 WO 2014039448 A2 3/2014
 WO 2014039708 A1 3/2014
 WO 2014039713 A1 3/2014
 WO 2014039846 A2 3/2014
 WO 2014039900 A1 3/2014
 WO 2014039901 A1 3/2014
 WO 2014078583 A1 5/2014
 WO 2014124291 A1 8/2014
 WO 2014151889 A2 9/2014
 WO 2014159755 A2 10/2014

WO 2014159756 A2 10/2014
 WO 2014165259 A1 10/2014
 WO 2014179717 A1 11/2014
 WO 2014179719 A1 11/2014
 WO 2014186732 A1 11/2014
 WO 2014197711 A1 12/2014
 WO 2015059601 A1 4/2015
 WO 2015073883 A1 5/2015
 WO 2015073887 A1 5/2015
 WO 2015073948 A2 5/2015
 WO 2015195759 A2 12/2015
 WO 2015200769 A1 12/2015
 WO 2016094254 A1 6/2016
 WO 2016168439 A1 10/2016
 WO 2016178913 A1 11/2016
 WO 2016182838 A1 11/2016
 WO 2016205639 A1 12/2016
 WO 2017027404 A1 2/2017

OTHER PUBLICATIONS

Moore, C. A. et al. A Three Revolute Cobot Using CVTs in Parallel, Proceedings of IMECE, 1999, 6 pgs.

Wong. The Temple of VTEC Asia Special Focus on the Multimatic Transmission. Temple of VTEC Asia. Oct. 2000.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

BALL TYPE CVT WITH OUTPUT COUPLED POWERPATHS

RELATED APPLICATIONS

This application is a divisional application of U.S. Non-Provisional application Ser. No. 14/425,600 filed on Mar. 3, 2015 which is a United States National Phase Application of International Application No. PCT/US/2013/057868, filed on Sep. 3, 2013, which claims the benefit of U.S. Provisional Application No. 61/697,917, filed Sep. 7, 2012 and U.S. Provisional Application No. 61/779,687, filed Mar. 13, 2013, which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

Automatic and manual transmissions are commonly used on automobile vehicles. Those transmissions become more and more complicated since the engine speed has to be adjusted to limit the consumption and the emissions of cars. This finer control of the engine speed in usual transmissions is typically done by adding gears and increasing the overall complexity and cost. 6-speed manual transmissions then become frequent as are 8 or 9 speed automatic transmissions.

SUMMARY OF THE INVENTION

Systems, devices, and methods are provided for the transmission of power, particularly in motor vehicles. According to various embodiments of the disclosure, power can be transmitted in a smoother and more efficient manner, typically with smaller and even less mechanical components, by splitting torque into two or more torque paths. The apparatus described herein, or obvious to one of skill in the art upon reading this disclosure, may be used in a transaxle or any other type of transmission.

An aspect of the disclosure provides an apparatus for transmitting power. This apparatus comprises a power input shaft, a planetary gear set, and a variator, such as a continuously variable transmission (CVT). Aspects of the CVTs are described in US2006084549 or AU2011224083A1, incorporated herein by reference in their entirety. The planetary gear set is engaged with the power input shaft, typically from an internal combustion engine. The variator is engaged with the gear set. The apparatus, and in particular the configuration of the planetary gear set and the variator, is configured to split torque between a first torque path and a second torque path.

The variator may comprise an input ring and an output ring. The planetary gear set may comprise a set of planet gears, a sun gear engaged with the set of planet gears and with the input ring of the variator, a carrier engaged with the power input shaft and with the set of planet gears, and a ring gear engaged with the set of planet gears and with the output ring of the variator. The first torque path may pass from the power input shaft to the carrier, to the planet gears, to the sun gear, to the input ring, to the output ring of the variator, and then to the ring gear of the planetary gear set. The second torque path may pass from the power input shaft to the carrier, to the planet gears, and then to the ring gear of the planetary gear set. In some embodiments, a gear box for outputting power from the apparatus may be coupled to the planetary gear set. The gear box may be coupled to the ring of the planetary gear set and to a differential of a motor vehicle. The gear box may be, for example, a three speed gear box.

Another aspect of the disclosure provides a method of transmitting power. An input shaft, typically from an internal combustion engine, is driven. Torque from the input shaft is split between a first torque path and a second torque path.

5 The first and second torque paths are combined to form a single output (i.e., power-split configuration). The first and second torque paths pass through various components of a planetary gear set and a variator coupled to the planetary gear set as described herein. The variator may comprise a continuously variable transmission (CVT). The first torque path may, for example, pass from the power input shaft to a carrier of the planetary gear set, to planet gears of the planetary gear set, to a sun gear of the planetary gear set, to an input ring of the variator, to an output ring of the variator, and then to a ring gear of the planetary gear set. The second torque path may, for example, pass from the power input shaft to the carrier of the planetary gear set, to the planet gears of the planetary gear set, and then to the ring gear of the planetary gear set.

Yet another aspect of the disclosure provides an apparatus for power transmission. The apparatus comprises a power input shaft, an input planetary gear set engaged with the power input shaft, a variator engaged with the input gear set, an output planetary gear set engaged with the variator, and one or more clutches and brake for switching between a plurality of operational modes of the power transmission apparatus. The apparatus is configured to split torque between a plurality of torque paths.

30 The variator may comprise an input ring and an output ring, and may be a continuously variable transmission (CVT). The input planetary gear set may comprise a set of input planet gears, an input sun gear engaged with the input planet gears and with the input ring of the variator, an input carrier engaged with the input planet gears and with the power input shaft, and an input ring engaged with the input planet gears. The output planetary gear set may comprise a set of output planetary gears, an output sun gear engaged with the power input shaft and with the output planet gears, an output carrier engaged with the output planet gears and with a gear box for outputting power from the apparatus, and an output ring engaged with the output planet and with the output ring of the variator. The power transmission apparatus may further comprise a counter shaft engaging the input ring and the output ring gears of the two planetary gear sets. The one or more clutches may comprise a first clutch and a second clutch. The first clutch may be configured to be engaged to engage the output sun gear with the output ring of the variator. The second clutch may be configured to be engaged to engage the power input shaft with the output sun gear. The power transmission apparatus may further comprise a brake for holding the output sun to achieve an additional operation mode of the power transmission apparatus. The power transmission apparatus may further comprise a gear box, such as a three speed gear box, coupled to the output carrier of the output planetary gear set as well as to a differential of a motor vehicle.

The plurality of operational modes of the power transmission apparatus may comprise a first mode, a second mode, and a third mode. The first, second, and third modes may comprise various continuously variable transmission (CVT) modes. The first mode may be selected by engaging the brake while releasing the first and second clutch. The second mode may be selected by engaging the second clutch while releasing the brake and the first clutch. The third mode may be selected by engaging the first clutch while releasing the brake and the second clutch.

In this embodiment, torque may be split into two paths—a first path through the variator and a second path through the countershaft in the first and third modes. Torque may also instead be split into three paths—a first path through the variator, a second path through the countershaft, and a third path between the power input shaft and the output sun gear of the output planetary gear set in the second mode.

Provided herein is a vehicle comprising the power transmission apparatus of any of embodiment described herein, or obvious to one of skill in the art upon reading the disclosures herein. Embodiments of the power transmission apparatus (variable transmission) described herein or that would be obvious to one of skill in the art upon reading the disclosure herein are contemplated for use in a variety of vehicle drivelines. For non-limiting example, the variable transmissions disclosed herein may be used in bicycles, mopeds, scooters, motorcycles, automobiles, electric automobiles, trucks, sport utility vehicles (SUV's), lawn mowers, tractors, harvesters, agricultural machinery, all terrain vehicles (ATV's), jet ski's, personal watercraft vehicles, airplanes, trains, helicopters, buses, forklifts, golf carts, motorships, steam powered ships, submarines, space craft, or other vehicles that employ a transmission.

While the figures and description herein are directed to ball-type variators (CVTs), alternate embodiments are contemplated another version of a variator (CVT), such as a Variable-diameter pulley (VDP) or Reeves drive, a toroidal or roller-based CVT (Extroid CVT), a Magnetic CVT or mCVT, Ratcheting CVT, Hydrostatic CVTs, Naudic Incremental CVT (iCVT), Cone CVTs, Radial roller CVT, Planetary CVT, or any other version CVT.

In some embodiments, the power transmission apparatus further comprises a traction fluid.

INCORPORATION BY REFERENCE

All publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the invention are set forth with particularity in the appended claims. A better understanding of the features and advantages of the present invention will be obtained by reference to the following detailed description that sets forth illustrative embodiments, in which the principles of the invention are utilized, and the accompanying drawings of which:

FIG. 1 is a side sectional view of a continuously variable planetary (CVP) variator;

FIG. 2 is a magnified, side sectional view of a ball and ring of the CVP variator of FIG. 1;

FIG. 3 is a block diagram of a continuously variable transmission (CVT) used in an automobile;

FIG. 4 is a block diagram of a continuously variable transmission (CVT) according to an embodiment of the present disclosure used in an automobile;

FIG. 5 is a graph of a speed diagram of the CVT of FIG. 4;

FIG. 6 is a block diagram of a continuously variable transmission (CVT) according to another embodiment of the present disclosure used in an automobile;

FIG. 7 is a graph of a speed diagram of an input planetary gear of the CVT of FIG. 6; and

FIG. 8 is a graph of a speed diagram of an output planetary gear of the CVT of FIG. 6 in its different modes.

DETAILED DESCRIPTION OF THE INVENTION

Besides automatic and manual transmissions commonly used on automobile vehicles are developed Continuously Variable Transmissions or CVTs. Those CVTs are of many types: belts with variable pulleys, toroidal, conical, etc. The principle of a CVT is that it enables the engine to run at its most efficient rotation speed by changing steplessly the transmission ratio in function of the speed of the car. If needed for example when accelerating, the CVT can also shift to a ratio providing more power. A CVT can change the ratio from the minimum to the maximum ratio without any interruption of the power transmission, at the opposite of usual transmissions which require an interruption of the power transmission by disengaging to shift of ratio. A specific use of CVTs is the Infinite Variable Transmission or IVT. Where the CVT is limited at positive speed ratios, the IVT configuration can perform a neutral gear and even reverse steplessly. A CVT can be used as an IVT in some driveline configurations.

In many currently used motor vehicle transmissions, including manual transmissions, automatic transmissions, and CVTs, power and torque are not transmitted in a smooth or efficient manner. This can reduce fuel efficiency and can result in an unsmooth ride. Therefore, improved motor vehicle transmissions for smooth and efficient power and torque transmission are desired.

Within this disclosure, we introduce new driveline configurations based on a ball type CVT, also known as CVP, for constant variable planetary, for which Fallbrook Technologies, Inc. has applied for patents under the references US20060845449P and AU2011224083A1. This CVT comprises of a certain number of balls 997 (for example, 3-15 balls), depending on the application, two discs 995, 996 with a conical surface contact with the balls 997, as input 995 and output 996, and an idler 999 as shown on FIG. 1. The balls are mounted on axles 998, themselves hold in a cage or carrier allowing changing the ratio by tilting the ball's axes. An idler 999 sits below the balls in the cage. Other types of ball CVTs also exist, such as the one produced by Milner but are slightly different.

The working principle is shown on FIG. 2. The CVP itself works with a traction fluid. The lubricant between the ball and the conical rings acts as solid at high pressure, transferring the power from the input ring, through the balls, to the output ring. By tilting the ball's axes, the ratio can be changed between input and output. When the axis is horizontal the ratio is one (1:1), when the axis is tilted the distance between the axis and the contact point change, modifying the overall ratio (input radius > output radius = underdrive; input radius < output radius = overdrive). All the ball's axes are tilted at the same time with a mechanism included in the cage.

In a car, the CVT 103 includes a CVP (continuously variable planetary) and is used to replace traditional transmission and is located between the engine 100 and the differential 102 as shown on FIG. 3. A torsional damper 101 has to be introduced between the engine and the CVT 103 to avoid transferring torque peaks and vibrations that could seriously damage the CVT 103. In some configurations, this damper 101 can be coupled with a clutch for the starting function.

5

One configuration depicted in FIG. 4 uses a planetary gearset **8** to split the torque between two different paths. A part of the power will pass through the CVP **5** while the other part of it will pass directly from the planetary gearset **8** to the output through a mechanical path with higher efficiency. This power splitting allows a relatively small CVP and increases the native efficiency of the transmission. The central part of that configuration is the variator **5** described previously in the document. A ball ramp on each side of the variator provides the clamping force necessary to transfer the torque.

This configuration uses only one mode performing CVP function. To extend the speed range in the low speed and reverse area, a three speed gearbox **22** can be added after the CVP. Since this configuration does not have an IVP mode, a slipping clutch or a torque converter is optionally used to allow the start from standstill.

The internal combustion engine (ICE) is linked to the carrier **3** which in turn is linked to the planets **1** of the planetary gearset **8**. The sun **2** of the planetary gearset **8** is connected to the variator input ring **6**. The ring **4** of the planetary gearset **8** is linked to the variator output ring **7**. This common ring **7** is connected to a three speed gearbox increasing the spread and allowing higher reverse speeds.

FIG. 5 shows the speed diagram of the planetary gearset **8**. The three horizontal axes represent respectively, from the bottom to the top, the sun rotation speed, the carrier rotation speed and the ring rotation speed. The carrier is the input and typically always turns at ICE speed. The ring is the output and is linked to a three speed gearbox. The output speed achievable is noted on the top horizontal axis in diagonal shading between the two dotted diagonal lines. The dashed area noted on the top horizontal axis can be covered by the additional gearbox. The dotted area noted on the top horizontal axis has to be covered by a slipping clutch or a torque converter.

This device is able to change continuously its ratio to provide the best ratio achievable for the engine in function of the objectives of consumption or power. In a manual or automatic transmission, only some predetermined and discrete ratios are available and an interruption of the power transmission is needed to shift of ratio. Generally, the power interruptions in this device only occur during gear shifting of the additional gearbox. Other advantages of this configuration are that a very small variator can be chosen; spread is similar to a traditional gearbox if an additional (smaller) gearbox is added and the native efficiency of the transmission is increased by using the CVP in a powersplit device, therefore letting a part of the power passing through a more efficient mechanical path. Native efficiency will be high, because the variator input ring is connected to the sun, where the torque is lower, so more power is transmitted through the mechanical path (the ring).

Another embodiment configuration (depicted in FIG. 6) uses two planetary gearsets (input planetary gearset **10**, output planetary gearset **12**) to split the torque between different paths. The input planetary gearset **10** includes a planet **1a**, a sun **2a**, a carrier **3a**, and a ring **4a**. Similarly, the output planetary gearset **12** includes a planet **1b**, a sun **2b**, a carrier **3b**, and a ring **4b**. A part of the power will pass through the CVP **5** while the other part of it will pass to the output through a mechanical path with higher efficiency. Two clutches (first clutch **16**, second clutch **18**) and one brake **14** may be needed to have three different CVP modes. This power splitting allows to have a smaller CVP and to increase the native efficiency of the transmission. The central part of that configuration is the variator described

6

previously in the document. A ball ramp on each side of the variator provides the clamping force necessary to transfer the torque.

There exist three modes performing a CVP function. To allow forward low speeds and reverse speeds, a three speed gearbox is added after the CVP. Since this configuration does not have an IVP mode, a slipping clutch or a torque converter can be used to allow starting from standstill and low speeds.

The ICE is linked to the carrier **3a** of the input planetary gearset **10** and can be linked to the sun **2** of the output planetary gearset **12** through a second clutch **18**. The sun **2a** of the input planetary gearset **10** is linked to the variator input ring while the variator output ring is connected to the ring **4b** of the output planetary gearset **12**. Both rings **4a**, **4b** of the two planetaries gearsets **10**, **12** respectively are linked by means of a countershaft **20**. The variator output ring can also be connected to the output planetary sun **2b** by engaging a first clutch **16**. A brake **14** allows holding the output planetary sun **2b** to perform an additional mode. The output is made by the carrier **3b** of the output planetary and is directly linked to an additional three speed gearbox **22**.

The three modes are selected by engaging one of the two clutches **16**, **18** or brake **14** and releasing the two others. The first mode (CVP1) is obtained by engaging the brake **14**, thus holding the sun **2b** of the output planetary gearset **12** fixed. The second mode (CVP2) is selected by engaging the second clutch **18** and releasing the others, while the third mode (CVP3) is selected by engaging the first clutch **16**. In the first and third mode, a part of the power is passing through the CVP **5** and a part of it is passing through the countershaft **20**. In the second mode (CVP2), an additional power path is created between the ICE and the sun **2b** of the output planetary gearset **12**, thus splitting the power twice. The output planetary gearset **12** combines those different paths to a single output on its carrier **3b**.

FIG. 7 shows the speed diagram of the input planetary gearset **10**. The three horizontal axes represent respectively, from the bottom to the top, the sun **2a** rotation speed, the carrier **3a** rotation speed and the ring **4a** rotation speed. The carrier **3a** of the input planetary gearset **10** is directly connected to the ICE. The ring **4a** speed is determined in function of the CVP ratio and is then directly applied to the output planetary ring **4b** through the countershaft **20**.

FIG. 8 shows the speed diagram of the output planetary gearset **12** for the three modes. This figure shows for mode CVP1, the sun **2b** is held by the brake **14** and the output speed achievable can be observed on the carrier **3b** axis. Mode CVP2 is selected by connecting the sun **2b** of the output planetary gearset **12** to the ICE. The output speed achievable by doing this is shown on the carrier **3b** axis with the text CVP2. Finally, mode CVP3 is engaged by linking the sun **2b** and the ring **4b** of the output planetary gearset **12**. The output planetary gearset **12** is then turning as a whole and the output speed equals the ring **4b** speed.

An additional gearbox **22** is added to increase the spread, allowing lower forward speeds and reverse. Since this concept has not an IVP function, a slipping clutch or a torque converter may be needed to start from standstill and to have very low driving speeds.

The transition between the three modes can simply be done by closing one of the clutches **16**, **18** or brake **14** and releasing the others. This device is able to change continuously its ratio to provide the best ratio achievable for the engine in function of the objectives of consumption or power. In a manual or automatic transmission, only some predetermined and discrete ratios are available and an inter-

ruption of the power transmission is needed to shift of ratio. Generally, the power interruptions in this device only occur during gear shifting of the additional gearbox **22**. Other advantages of this configuration are that a very small variator can be chosen; spread is similar to a traditional gearbox if an additional (smaller) gearbox is added and the native efficiency of the transmission is increased by using the CVP in a powersplit device, therefore letting a part of the power passing through a more efficient mechanical path. Native efficiency will be high, because the variator input ring is connected to the sun **2a**, where the torque is lower, so more power is transmitted through the mechanical paths. An additional feature of this configuration is that in CVP **2** mode, powersplitting occurs two times.

Provided herein is a vehicle comprising the power transmission apparatus of any of embodiment described herein, or obvious to one of skill in the art upon reading the disclosures herein. Embodiments of the power transmission apparatus (variable transmission) described herein or that would be obvious to one of skill in the art upon reading the disclosure herein are contemplated for use in a variety of vehicle drivelines. For non-limiting example, the variable transmissions disclosed herein may be used in bicycles, mopeds, scooters, motorcycles, automobiles, electric automobiles, trucks, sport utility vehicles (SUV's), lawn mowers, tractors, harvesters, agricultural machinery, all terrain vehicles (ATV's), jet ski's, personal watercraft vehicles, airplanes, trains, helicopters, buses, forklifts, golf carts, motorships, steam powered ships, submarines, space craft, or other vehicles that employ a transmission.

While the figures and description herein are directed to ball-type variators (CVTs), alternate embodiments are contemplated another version of a variator (CVT), such as a Variable-diameter pulley (VDP) or Reeves drive, a toroidal or roller-based CVT (Extroid CVT), a Magnetic CVT or mCVT, Ratcheting CVT, Hydrostatic CVTs, Naudic Incremental CVT (iCVT), Cone CVTs, Radial roller CVT, Planetary CVT, or any other version CVT.

In some embodiments, the power transmission apparatus further comprises a traction fluid.

While preferred embodiments of the present invention have been shown and described herein, it will be obvious to those skilled in the art that such embodiments are provided by way of example only. Numerous variations, changes, and substitutions will now occur to those skilled in the art without departing from the invention. It should be understood that various alternatives to the embodiments of the invention described herein may be employed in practicing the invention. It is intended that the following claims define the scope of the invention and that methods and structures within the scope of these claims and their equivalents be covered thereby.

What is claimed:

1. An apparatus for power transmission comprising:

a power input shaft;

a planetary gear set engaged with the power input shaft; and

a ball type variator including an input ring and an output ring engaged with the gear set,

wherein the apparatus is configured to split torque between a first torque path and a second torque path, wherein the ball-type variator comprises a plurality of balls in contact with the input ring and the output ring, each ball provided with a tiltable axis of rotation,

wherein a speed of the output ring is continuously variable corresponding to movement of the tiltable axis of rotation, wherein the planetary gear set comprises

a set of planet gears, a sun engaged with the set of planet gears and to the input ring of the variator, a carrier engaged with the power input shaft and with the set of planet gears, and a ring gear engaged with the set of planet gears and with the output ring of the variator, and wherein the first torque path transmits rotational power passes from the power input shaft to the carrier of the planetary gear set, to the planet gears of the planetary gear set, to the sun gear of the planetary gear set, to the input ring of the variator, to the output ring of the variator, and then to the ring gear of the planetary gear set.

2. The power transmission apparatus of claim **1**, wherein the second torque path passes from the power input shaft to the carrier of the planetary gear set, to the planet gears of the planetary gear set, and then to the ring gear of the planetary gear set.

3. The power transmission apparatus of claim **1**, further comprising a gear box for transmitting an output power from the apparatus, the gear box being coupled to the planetary gear set.

4. The power transmission apparatus of claim **3**, wherein the gear box is coupled to the ring gear of the planetary gear set.

5. The power transmission apparatus of claim **3**, wherein the gear box is coupled to a differential.

6. The power transmission apparatus of claim **5**, wherein the gear box comprises a three speed gear box.

7. The power transmission apparatus of claim **1** further comprising a traction fluid lubricant.

8. A vehicle comprising the power transmission apparatus of claim **1**.

9. A method of transmitting power comprising:
driving an input shaft;

splitting torque from the input shaft between a first torque path and a second torque path; and
combining the first and second torque paths to form a single output,

wherein the first and second torque paths pass through a planetary gear set and the first torque path passes through a ball type variator coupled to the planetary gear set,

wherein the ball-type variator comprises a plurality of balls in contact with an input ring and an output ring, each ball provided with a tiltable axis of rotation, wherein a speed of the output ring is continuously variable corresponding to movement of the tiltable axis of rotation, and

wherein splitting torque further comprises transmitting rotational power through the first torque path, wherein the first torque path corresponds to power transmission from the power input shaft to a carrier of the planetary gear set, to a set of planet gears of the planetary gear set, to a sun gear of the planetary gear set, to an input ring of the variator, to the output ring of the variator, and then to a ring gear of the planetary gear set.

10. The power transmission method of claim **9**, wherein splitting torque further comprises transmitting rotational power through the second torque path, wherein the second torque path corresponds to power transmission from the power input shaft to a carrier of the planetary gear set, to a set of planet gears of the planetary gear set, and then to a ring gear of the planetary gear set.

11. An apparatus for power transmission comprising:

a power input shaft;

a planetary gear set engaged with the power input shaft; and

a ball type variator including an input ring and an output ring engaged with the gear set, wherein the apparatus is configured to split torque between a first torque path and a second torque path,
wherein the ball-type variator comprises a plurality of 5 balls in contact with the input ring and the output ring, each ball provided with a tiltable axis of rotation, wherein a speed of the output ring is continuously variable corresponding to movement of the tiltable axis of rotation, 10
wherein the planetary gear set comprises a set of planet gears, a sun engaged with the set of planet gears and to the input ring of the variator, a carrier engaged with the power input shaft and with the set of planet gears, and 15 a ring gear engaged with the set of planet gears and with the output ring of the variator, and
wherein the second torque path passes from the power input shaft to the carrier of the planetary gear set, to the planet gears of the planetary gear set, and then to the ring gear of the planetary gear set. 20

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 10,088,026 B2
APPLICATION NO. : 15/423131
DATED : October 2, 2018
INVENTOR(S) : Mark R. J. Versteyhe and Matthias W. J. Byltiauw


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

In Claim 1, Column 8, Line 9, please amend “to the sun gear of the planetary pear set” to “to the sun gear of the planetary gear set”.

Signed and Sealed this
Twenty-seventh Day of November, 2018



Andrei Iancu
Director of the United States Patent and Trademark Office