



US010101751B2

(12) **United States Patent**
Sonnenburg

(10) **Patent No.:** **US 10,101,751 B2**
(45) **Date of Patent:** **Oct. 16, 2018**

(54) **SYSTEM AND METHOD OF AIR POLLUTION CONTROL FOR LIQUID VACUUM TRUCKS**

(71) Applicant: **Ray Sonnenburg**, Deer Park, TX (US)

(72) Inventor: **Ray Sonnenburg**, Deer Park, TX (US)

(73) Assignee: **Ray Sonnenburg**, Abilene, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 190 days.

(21) Appl. No.: **15/185,261**

(22) Filed: **Jun. 17, 2016**

(65) **Prior Publication Data**

US 2016/0375815 A1 Dec. 29, 2016

Related U.S. Application Data

(60) Provisional application No. 62/184,992, filed on Jun. 26, 2015.

(51) **Int. Cl.**
B60P 3/24 (2006.01)
G05D 7/06 (2006.01)
B60P 3/22 (2006.01)

(52) **U.S. Cl.**
CPC **G05D 7/0676** (2013.01); **B60P 3/2255** (2013.01); **B60P 3/243** (2013.01)

(58) **Field of Classification Search**
CPC **G05D 7/0676**; **B60P 3/22**; **B60P 3/2255**; **B60P 3/243**; **B60P 3/246**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,664,911 A	1/1954	Thompson	
3,159,301 A *	12/1964	Anderson F15B 1/08 220/222
3,315,611 A	4/1967	Thompson	
3,438,215 A *	4/1969	Frijlink F17C 3/022 137/578
3,621,893 A	11/1971	Nishimura	
3,971,400 A	7/1976	Thompson	
4,038,940 A	8/1977	Gierse	
4,082,124 A	4/1978	Jenkins	
4,113,410 A	9/1978	Ando	
4,408,960 A	10/1983	Allen	
4,925,532 A	5/1990	Meuser et al.	
5,030,259 A	7/1991	Bryant et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

CN	102888892	1/2013
DE	3027284	2/1981


Primary Examiner — Nicolas A Arnett

(74) Attorney, Agent, or Firm — Conley Rose PC

(57) **ABSTRACT**

A system. The system includes a container comprising a cylindrical shell, wherein the cylindrical shell defines an internal volume of the container, and a barrier. The barrier includes a disk slideably disposed within the interior volume of the container, the disk subdividing the interior volume of the container into a first portion and a second portion, and a seal disposed about a circumference of the disk and in sealing contact with an interior surface of the cylindrical shell. The first portion is configured to sustain an internal pressure in a predetermined range; and the second portion is configured to receive a waste material. When the internal pressure is at a maximum value of the predetermined range, the disk has a deflection less than a predetermined deflection at which the sealing contact is compromised.

11 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,419,400 A 5/1995 Wigington, Sr.
5,492,144 A * 2/1996 Kriewaldt B60P 3/2255
137/205
5,960,810 A 10/1999 Douglas
7,108,016 B2 * 9/2006 Moskalik B60K 6/12
138/26
7,661,442 B2 * 2/2010 O'Brien, II B60K 6/12
138/30
8,695,643 B2 * 4/2014 Rajabi F15B 1/24
138/109
8,919,391 B1 * 12/2014 Harvey B67D 7/0277
141/231
2005/0194054 A1 * 9/2005 Moskalik B60K 6/12
138/31
2008/0308168 A1 * 12/2008 O'Brien, II B60K 6/12
138/31
2009/0114296 A1 5/2009 Tsuda
2014/0341754 A1 11/2014 McClister et al.
2015/0143821 A1 5/2015 Johnson et al.
2015/0316007 A1 11/2015 Williams et al.

* cited by examiner




FIG. 1




FIG. 1A




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5




FIG. 5A




FIG. 6




FIG. 6A




FIG. 7




FIG. 8

1

**SYSTEM AND METHOD OF AIR
POLLUTION CONTROL FOR LIQUID
VACUUM TRUCKS**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application claims the benefit of U.S. Provisional Application Ser. No. 62/184,992 filed Jun. 26, 2015 and titled "System and Method of Air Pollution Control for Liquid Vacuum Trucks". The provisional application is incorporated by reference herein as if reproduced in full below.

BACKGROUND

Liquid vacuum trucks are used to collect and transport hazardous and non-hazardous liquid and semi-liquid waste. Non-hazardous waste includes sewage and septic materials. Hazardous waste, waste that poses a substantial threat to public health or the environment, includes volatile organic compounds, nitrogen oxide, sulfur dioxide, and other particulate waste matter. Liquid vacuum trucks are also frequently used to assist in cleaning up waste spills and for transporting liquids and semi-solids at industrial facilities.

BRIEF DESCRIPTION OF THE DRAWINGS

For a detailed description of exemplary embodiments of the invention, reference will now be made to the accompanying drawings in which:

FIG. 1 shows 1 illustrates a partial cutaway view of a system according to an embodiment of the disclosure;

FIG. 1A shows a portion of the system of FIG. 1 in further detail in accordance with at least some embodiments;

FIGS. 2A and 2B shows a portion of the system of FIG. 1 in further detail in accordance with at least some embodiments;

FIGS. 3A and 3B show, in two views, a portion of the system of FIG. 1 in further detail in accordance with at least some embodiments;

FIGS. 4A and 4B show, in two views, a portion of the system FIG. 1 in further detail in accordance with at least some embodiments;

FIGS. 5 and 5A show, in two views, a portion of the system of FIG. 1 in accordance with at least some embodiments;

FIG. 6 shows a partial cutaway view of a system according to an embodiment of the disclosure;

FIG. 6A shows a portion of the system of FIG. 6 in further detail;

FIG. 7 shows a portion of a system according to an embodiment of the disclosure; and

FIG. 8 shows a flowchart of a method in accordance with at least some embodiments of the disclosure.

NOTATION AND NOMENCLATURE

Certain terms are used throughout the following description and claims to refer to particular system components. As one skilled in the art will appreciate, a component may be referred to by different names. This document does not intend to distinguish between components that differ in name but not function. In the following discussion and in the claims, the terms "including" and "comprising" are used in an open-ended fashion, and thus should be interpreted to mean "including, but not limited to" Also, the term

2

"couple" or "couples" is intended to mean either an indirect or direct, connection. Thus, if a first device couples to a second device, that connection may be through a direct connection or through an indirect connection via other devices and connections.

"About" as used herein in conjunction with a numerical value shall mean the recited numerical value as may be determined accounting for generally accepted variation in measurement, manufacture and the like in the relevant industry.

"Exemplary", as used herein, means "serving as an example, instance, or illustration," An embodiment described herein as "exemplary" is not necessarily to be construed as preferred or advantageous over other embodiments.

DETAILED DESCRIPTION

The following discussion is directed to various embodiments of the invention. Although one or more of these embodiments may be preferred, the embodiments disclosed should not be interpreted, or otherwise used, as limiting the scope of the disclosure, including the claims. In addition, one skilled in the art will understand that the following description has broad application, and the discussion of any embodiment is meant only to be exemplary of that embodiment, and not intended to intimate that the scope of the disclosure, including the claims, is limited to that embodiment.

In related art, a liquid vacuum truck system contains a metal tank with a vacuum pump and nozzle attached to import liquid or semi-liquid waste into the tank for transportation and disposal. The related art liquid vacuum trucks permit vapors produced by the liquid or semi-liquid waste to enter and exhaust into the atmosphere from the vacuum pump. The vapor produced by this waste can be toxic, flammable, and/or negatively impact the environment.

A number of states have exempted the air pollution limits of facilities during special periods of activity, specifically during startup, shutdown, and malfunction operations ("SSM"). During the period of a facility's startup and shutdown procedures, or during a malfunction, high levels of hazardous pollutants can be released causing air pollution in nearby communities. These exemptions have been incorporated into State Implementation Plans ("SIP") that were approved by the United States Environmental Protection Agency ("EPA"). Recently, a number of legal challenges have resulted in the EPA re-evaluating SIPs with respect to SSM operations. On May 22, 2015, the EPA issued a Final Action determining that these emission exemptions during SSM operations are inconsistent with the Clean Air Act of 1970 and must be modified. Compliance with the EPA Final Action is required by Nov. 22, 2016.

These rules for air emissions can be applicable to the operation of liquid vacuum trucks, which often operate and emit impermissible levels of pollutants into the air during SSM. A number of methods may be used to control the emissions from liquid vacuum trucks. These methods include the use of activated carbon container scrubbers, liquid solution container scrubbers, combination carbon and liquid solution scrubbers, and internal combustion engine units. These methods, however, are expensive, time consuming, pose potential fire hazards, require additional space on or around a truck, and may require additional disposal of the spent scrubbing media.

The present disclosure provides systems and apparatus to address the control of air pollution and emissions from

liquid vacuum trucks. The systems and apparatus according to the disclosure may be adapted to existing liquid vacuum trucks, without the need for scrubbers and the like.

Turning now to FIG. 1, a liquid vacuum truck system **100** in accordance with an embodiment of the present disclosure is shown. The liquid vacuum truck system **100** includes a vacuum pump, described further below (not shown in FIG. **1**), and a waste container **102** which can be comprised of any structurally sound material, including stainless steel and other metals. For example, a stainless steel such as type 316 stainless steel. Other materials which may be used include brass, HASTELLOY®, and Carpenter 20 and similar corrosion-resistant metal alloys. Waste container **102** may comprise a shell **104**. The shell **104** and waste container **102** may be one and the same and made of the same material. A cross-section of shell **104** may be cylindrical. Alternatively, waste container **102** may include a shell **104** having end members **107** and **109** integrated therewith. In at least some embodiments, at least one of end members **107** and **109** comprises a hatch. Shell **104** comprises smooth interior surface **105**. Alternatively, the shell **104** may be a liner disposed within an outer hull (not separately shown) made of a material that exhibits a smooth interior surface **105**. In at least some embodiments, shell **104** defines an interior volume of the container, interior volume **106**. Interior volume **106** may have a diameter from about 72 inches to about 78 inches. However, other dimensions may also be used. In embodiments in which shell **104** and waste container **102** are different materials, inasmuch as waste container **102** may then be protected from contact with contents therein, waste container **102** may comprise materials that might otherwise corrode or have other chemical interactions with the contents, for example carbon steel or aluminum.

Continuing with FIG. 1, the internal volume **106** of waste container **102** is divided into two portions by a barrier **108**, thereby creating two chambers, a clean side **114** and a dirty side **112**. Barrier **108** may be comprised of a disk **110** (shown in FIG. 1A) and a seal fixture **111** which may be made of the same material as shell **104**, and one or more seals **116** disposed about an outer circumference of seal fixture **111**. Seal fixture **111** can, in alternative embodiments, be comprised of material compatible with the material of shell **104**. As described below in conjunction with FIG. 1A, the seal(s) **116** form a gasket between the disk **110** (FIG. 1A) and the interior surface **105** of the shell **104**. Seals **116** may comprise an elastomeric material that is chemically resistant to materials that might be collected in waste container **102**. Exemplary elastomers which may be used in at least some embodiments include VITON fluoroelastomer, TEFLON polytetrafluoroethylene (PTFE), Buna, neoprene, polyurethane, ethylene propylene diene monomer (EPDM) rubber, XL thermoplastic elastomer (TPE), GEOLAST thermoplastic rubber, HYTREL thermoplastic elastomer, polyvinylidene fluoride (PDVF), and polypropylene. The foregoing are by way of example, and any suitable elastomer may be used that provides a seal between disk **110** (FIG. 1A) and the interior surface **105** of the shell **104** to mitigate against the transport of materials, including volatile compounds, from the dirty side **112** to the clean side **114**.

Turning to FIG. 1A, FIG. 1A shows barrier **108** in further detail in a side perspective view. Barrier **108** further comprises a disk **110** disposed within and fixedly engaged with an interior circumference **121** of seal fixture **111**, the disk **110** separating the two portions of the interior volume **106** which define the dirty and clean sides **112** and **114**, respectively. Disk **110** may be comprised of the same material as seal fixture **111**, Disk **110** may have one or more stiffeners

123 attached thereto, as will be more fully described hereinbelow. Thus, seals **116** are disposed about disk **110** via the support of seal fixture **111** to form a gasket with the interior surface **105** (FIG. 1) of shell **104**. Seal fixture **111** may be used in at least some embodiments to mitigate against the cocking of disk **110** within the interior volume **106** of shell **104**.

The disposition of seals **116** may be further appreciated by referring to FIGS. 2A and 2B, which shows a portion of barrier **108**, and two exemplary embodiments of seals **116**, FIGS. 2A and 2B, respectively. In one embodiment three seals **116A-C** are disposed about the periphery of seal fixture **111**. Although three seals are used in this example, other numbers of seals **116** may be used. For example, in another embodiment, a single seal **116D** may be disposed about the periphery. Seal **116D** may have a width W , that about the same as a distance D across the thickness of disk **110** spanned by the seals **116A-C**. However, in alternative embodiments, the width W , may be narrower or wider than D . Further, in at least some embodiments, seal fixture **111** may be in the range of about 6 inches to 10 inches in width, and have a thickness in the range of from about 0.75 inches to about 1.5 inches. The thickness of disk **110** may be in the range of about 0.25 inches to about 0.375 inches, as described further below.

Liquid vacuum truck system **100** operates in the following manner. A vacuum pump, described further below (not shown in FIG. 1), of liquid vacuum truck system **100** creates a vacuum on the clean side **114** of the internal volume **106** of waste container **102** to move the barrier **108**. Stated differently, by drawing a vacuum on the clean side **114**, barrier **108** may slide so as to reduce the volume of the clean side **114** and, concomitantly, increase the volume of the dirty side **112**. The movement of barrier **108** thus causes a vacuum in dirty side **112** of waste container **102** that permits a liquid or semi-liquid waste material to be aspirated or vacuumed into the dirty side **112** of waste container **102**. Barrier **108** prevents leakage of waste material from dirty side **112** to clean side **114**, as described further below. As more waste is aspirated into dirty side **112** and as barrier **108** moves across the internal volume **106**, the volume of dirty side **112** continues to increase and the volume of clean side **114** continues to decrease. Once the dirty side **112** reaches its maximum volume, or otherwise reaches its maximum waste capacity, the liquid or semi-liquid waste can be transported and disposed of. The movement of barrier **108** can be reversed by operating the vacuum pump in pressure mode to offload the liquid or semi-liquid waste as necessary. Pressurizing the clean side **114** motivates the barrier **108** towards the dirty side **112**, decreasing the volume thereof and expelling the waste contained therein. As the barrier **108** is displaced, seals **116** also operate to wipe interior surface **105** of any waste residue that might be deposited thereon.

As set forth above, shell **104** included a smooth interior surface **105**. Stated differently, a smoothness of interior surface **105** and porosity of shell **104** in conjunction with the disk seals **116**, should be such that any volatile compounds in the dirty side **112** are constrained from “bleeding” into clean side **114** through interstices between the seals **116** and interior surface **105**, or through pores in the interior surface **105** and/or shell **104**. For example, the smoothness and porosity may be such that, to the extent there is any bleed through to the clean side **114** the concentration of volatile compounds therein, particularly volatile organic compounds (VOCs) is less than a predetermined amount, say about 100 parts per million (ppm). In other words, the smoothness of interior surface and porosity of the interior surface **105** and

the shell **104** should be such that these structures are impermeable to liquids and vapors, including VOCs, wherein the concentration of VOCs in the clean side **114** does not exceed a predetermined value, for example, 100 ppm. Further, the smoothness and porosity of the interior surface **105** and shell **104** may be such that the clean side **114** does not retain an amount of residue from the dirty side **112** wherein the concentration of VOCs exceeds the predetermined value after the seals have been caused to be moved toward the dirty side **112**, and have wiped the interior surface **105**.

The dirty side **112** of the interior volume **106** may be at about atmospheric pressure. Because of the pressure differential between the “clean” and “dirty” sides of barrier **108**, disk **110** may be subject to stresses tending to deform the disk. If, the deflection of the disk **110** from such stresses exceeds a predetermined value, which may be based on the particular disposition of seals **116**, the sealing contact between barrier **108** and the interior surface **105** of the shell **104** may be compromised such as to allow the passage of material, e.g. volatile compounds, between dirty side **112** and clean side **114**. These compounds may then be exhausted from clean side **114**, potentially to the atmosphere, as described further below. Thus, the structure of disk **110** may be based on the deflection of disk **110** being below the predetermined maximum deflection value when the pressure differential across the clean and dirty sides has a maximum value. Stated otherwise, as the pressure on the clean side **114** varies within a predetermined range, which may include both positive and negative pressure values, the clean side **114** of the internal volume **106** sustains an internal pressure in a predetermined range. As the pressure varies within the predetermined range, the deflection of the disk **110** may also vary, and a maximum predetermined deflection may be based on the aforesaid compromise of the sealing contact.

As previously described, a partial vacuum imposed on clean side **114** produces a displacement of the barrier **108** such that waste is aspirated into the dirty side **112**. Thus the partial vacuum may comprise a negative gauge pressure up to about -15 pounds per square inch, gauge (-15 psig). Conversely, a positive pressure imposed on clean side **114**, expels the waste from the dirty side **112**. In at least some embodiments, a positive pressure of up to about 35 psig may be imposed on clean side **114**. The aforesaid pressure values are by way of example, and other pressures, both positive and negative, may be used in various embodiments. The largest deflection of disk **110** may be expected at the largest in magnitude pressure imposed on the clean side **114**. Thus, in the foregoing example, the largest deflection of the disk **110** may be expected at the positive 35 psig pressure imposed when expelling the waste. In this example, the deflection would be expected to take the form of a convex bowing of the disk **110** toward the dirty side **112**. Conversely, with the application of negative pressure a convex bowing of the disk **110** toward the clean side **114** would be expected. In at least some embodiments, a thickness of disk **110** in a preselected range, for example, from about 0.250 inches to 0.375 inches may be used to maintain the deflection below the predetermined value based on the compromise of the sealing contact.

In some alternative embodiments, stiffeners may be attached to one or both sides of the disk **110**. This may be further appreciated by turning to FIGS. **3A** and **3B**, which illustrate, respectively, views of first and second sides **302** and **304** of an exemplary disk **110** having stiffeners **306A-C** and **308A-C** on the opposite sides of disk **110**. Stiffeners

306A-C and **308A-C** may extend from the center to the periphery of disk **110**. The three stiffeners **306A-C** are, in the exemplary embodiment in FIGS. **3A**, **3B**, circumferentially disposed at 120° intervals about the side **302**. Likewise, the three stiffeners **308A-C** may be similarly disposed about the circumference of side **304**. In at least some embodiments, the stiffeners **306A-C** and **308A-C** may be offset relative to each other by a preselected angle, 60° in the exemplary embodiment of disk **110** in FIGS. **3A**, **3B**. Alternatively, other offset angles may be used. Stated differently, stiffeners **306A-C** are rotationally offset about an axis **310** central to the disk **110**. Stiffeners **306A-C** and **308A-C** may comprise angle or channel-shaped material and may be composed of the same or different material as disk **110**. Stiffeners **306A-C** and **308A-C** may be attached to disk **110** by any suitable mechanism, such as by welding, riveting, or bolting. While three stiffeners are used in the embodiment in FIGS. **3A**, **3B**, other numbers of stiffeners may be used. Thus, in the embodiment in FIGS. **4A**, **4B**, four stiffeners **406A-D** and **408A-D** are attached to sides **402** and **404** of disk **110**, respectively. In this example, stiffeners **406A-D** and **408A-D** are symmetrically circumferentially disposed at 90° intervals. Further, in this example, the stiffeners **408A-D** and **406A-D** are offset by 45° relative to each other. The stiffeners **406A-D** and **408A-D** may be composed of materials similar to stiffeners **306A-C** and **308A-C** and attached to disk **110** in likewise fashion.

Referring to FIGS. **5** and **5A**, in an alternative embodiment, the barrier **108** may also comprise an edge **502** disposed about the periphery of seal fixture **111** and configured to scrape and remove any semi-solid or solid waste residue that has accumulated on the dirty side **112** of the interior volume **106** when the barrier **108** is pushed to offload waste. In this way, edge **502** may aid the seals **116** in wiping the interior surface **105** of shell **104**. Edge **502** may be formed from a semi-rigid plastic such as acrylonitrile butadiene styrene (ABS), or alternatively a metal such as stainless steel or brass. In at least some embodiments, edge **502** may be formed from the same material as seal fixture **111**. In FIG. **5A**. In FIGS. **5** and **5a**, any stiffeners which may be used in at least some embodiments have been omitted from disk **110** for ease of illustration.

Turning now to FIG. **6**, a liquid vacuum truck system **600** in accordance with an alternative embodiment of the present disclosure is shown. Liquid vacuum truck system **600** is similar to the system shown in FIG. **1**. Liquid vacuum truck system **600** includes a hydraulic cylinder **602** and a waste container **102** which can be comprised of any material that is structurally sound, including stainless steel and other metals. The shell **104** and waste container **102** may be one and the same and made of the same material. Alternatively, the shell **104** may be a liner made of a material that exhibits a smooth surface. The internal volume **106** of waste container **102** is bisected by a barrier **108**, thereby creating two chambers, a clean side **114** and a dirty side **112**. Hydraulic cylinder **602** is attached to barrier **108** and operates the barrier **108** back and forth across the internal volume **106**. Barrier **108** can be comprised of a disk **110** made of the same material as shell **104**. Alternatively, disk **110** can be comprised of material compatible with the material of shell **104**. As described above, disk **110** may include one more stiffeners attached thereto (not shown in FIG. **6**) to mitigate against deflection of the disk **110** when motivated by hydraulic cylinder **602**. Barrier **108** further comprises one or more seals **116** which encircle the outer rim of disk **110**, as previously described, and provide a sealing contact with interior surface **105** of shell **104**.

Liquid vacuum truck system **600** operates in the following manner. The hydraulic cylinder **602** of liquid vacuum truck system **600** motivates the barrier **108** such that the volume of dirty side **112** increases and the volume of clean side **114** decreases. The movement of hydraulic cylinder **602** creates a vacuum in dirty side **112** that permits liquid or semi-liquid waste to be aspirated or vacuumed into the dirty side **112** of waste container **102**. Barrier **108** prevents leakage of waste material from dirty side **112** to clean side **114**. As more waste is aspirated into dirty side **112** and as barrier **108** moves across the internal volume **106**, the volume of dirty side **112** increases and the volume of clean side **114** decreases. Once the dirty side **112** reaches its maximum volume, the liquid or semi-liquid waste can be transported and disposed of. The movement of the barrier **108** can be reversed by extending the hydraulic cylinder to offload the liquid or semi-liquid waste as necessary.

In another alternative embodiment, the liquid vacuum truck system **100** and the liquid vacuum truck system **600** may additionally comprise an air operated valve **604** (not shown in FIG. 1) which may be located at zero degrees, or in other words 12 o'clock in orientation to waste container **102** when viewed from the rear. The air operated valve **604** located near the top and rear of the waste container **102** permits air to be released from the dirty side **112** in order to maximize the volume of liquid waste collected during the operation of the liquid vacuum truck system if unwanted air is collected on the dirty side **112** during vacuuming operations. For example, the liquid vacuum truck system may be operating to vacuum liquid but may also take in a large quantity of air into dirty side **112** depending on the efficiency of the vacuuming operation. When the barrier **108** reaches one end of the internal volume **106** and reaches its maximum capacity whereby it cannot intake any further waste, the volume of dirty side **112** may be comprised partly of air and partly of liquid or semi-liquid waste. The air operated valve **604** can then be opened to expel air from dirty side **112** by way of movement of barrier **108** in condensing the volume of dirty side **112** until all of the air is removed. In the exemplary embodiment of liquid vacuum truck **600**, air operated valve **604** is disposed at the top of hatch **607**. The example disposition of air operated valve **604** is shown in further detail in FIG. 6A. The expelled air should be routed with hoses, e.g. hose **606** back to the original source of the waste (not shown in FIGS. 6, 6A) or vented through a means of pollution control, such as a scrubber (not shown in FIGS. 6, 6A) if required by any applicable regulations. The liquid vacuum truck system can then resume operation and vacuum additional liquid or semi-liquid waste. In at least some embodiments, air operated valve **604** may be a commercially available device, such as a NAF-Torex butterfly valve from Flowserve Corp., Irving, Tex.

Turning now to FIG. 7, further aspects of an embodiment of a system **100** are shown. FIG. 7 illustrates a waste container **102** as previously described in conjunction with FIG. 1. As described in conjunction with FIG. 1, a vacuum drawn on clean side **114** motivates barrier **108** to increase the volume of the dirty side, aspirating waste into the dirty side **112**. The vacuum may be provided by a vacuum pump **702** fluidly coupled to a port **704** disposed within shell **104** and fluidly coupled to clean side **114**. Also as described above, barrier **108** comprises a disk **110**, seal fixture **111** and seals **116** which form a gasket against the transport of volatile compounds from the dirty side **112** to clean side **114**. The detection of any leakage of volatile compounds into the clean side **114** may be facilitated by coupling a monitor **706** to an exhaust port **708** of vacuum pump **702**. An example of

a commercially available monitor that may be used in at least some embodiments is an AreaRAE Steel multi-gas monitor from Rae Systems, Inc., San Jose, Calif. However, any monitor suitable for the environmental monitoring of volatile compounds, and particularly VOCs, may be used. Further, as would be appreciated by those skilled in the art having the benefit of the disclosure, a gas monitor may be attached to the vent **611** or a port providing access to the clean side **114** in a liquid vacuum truck system **600**, FIG. 6 to monitor for leakage past the seals **116**.

FIG. 8 shows a flow chart of a method **800** in accordance with at least some embodiments. Method **800** starts at block **802**. In block **804**, a dirty side of an interior volume of a waste container is fluidly coupled to a source of waste. In block **806**, a vacuum is drawn on a clean side of the interior volume of the waste container, the clean side of the interior volume of the waste container separated from the dirty side of the interior volume of the waste container by a slideable, barrier sealably disposed within a circumference of the interior volume of the waste container. For example, a vacuum having a negative gauge pressure of up to about -15 psig may be used. In block **808**, responsive to the drawing of the vacuum on the clean side of the interior volume, waste is aspirated into the dirty side of the interior volume. Further, as described above, the barrier may be stiffened to mitigate against deflections of the barrier. As would be appreciated by persons skilled in the art having the benefit of the disclosure, the barrier sealably disposed within the circumference of the interior volume could leak due to wear or damage, for example. An exhaust stream from a vacuum pump coupled to a port in the clean side of the waste container for drawing the vacuum on the clean side may be monitored for volatile compounds, block **810**. The drawing of the vacuum may be terminated if a concentration of volatile organic compounds in the exhaust stream exceeds a predetermined value, at block **812**. For example, the predetermined value may be 100 parts per million (ppm) in at least some embodiments. As described above, the vacuum induces the displacement of the barrier such that waste is aspirated into the dirty side of the waste container. In block **814**, the drawing of a vacuum on the clean side is terminated when a capacity of the dirty side of the waste container is reached. The waste in the dirty side of the waste container is offloaded, block **816**. The waste may be offloaded by displacing the barrier towards the dirty side of the interior volume of the waste container. The barrier may be displaced toward the dirty side of the interior volume by applying a positive pressure to the clean side of the waste container. The positive pressure may be applied by reversing the vacuum pump used to draw the vacuum. A positive pressure up to about 35 psig may be used, for example. Method **800** ends at block **818**.

The above discussion is meant to be illustrative of the principles and various embodiments of the present invention. Numerous variations and modifications will become apparent to those skilled in the art once the above disclosure is fully appreciated. For example, a non-contact liquid level gauge system can be attached to the waste container shell to measure the level of liquid in the dirty side during operation. And various diameters of the interior of the shell can be used, subject to the constraints on the deflection of the barrier as described herein. It is intended that the following claims be interpreted to embrace all such variations and modifications.

What is claimed is:

1. A system comprising:
 - a container comprising:
 - a cylindrical shell;

9

- wherein the cylindrical shell defines an internal volume of the container;
- a barrier comprising:
- a disk slideably disposed within the interior volume of the container, the disk dividing the interior volume of the container into a first portion and a second portion;
- a seal disposed about the disk and in sealing contact with an interior surface of the cylindrical shell; and wherein:
- the first portion is configured to sustain an internal pressure in a predetermined range; and
- the second portion is configured to receive a waste material; and
- wherein, when the internal pressure is at a maximum value of the predetermined range, the disk has a deflection less than a predetermined deflection at which the sealing contact is compromised.
2. The system of claim 1 wherein the internal pressure predetermined range is in the range from about -15 pounds per square inch gauge (psig) to about 35 psig.
3. The system of claim 1 wherein the disk comprises a metal selected from the group consisting of: stainless steel; brass; nickel-chromium-molybdenum-iron alloy; and nickel-chromium-iron alloy.
4. The system of claim 1 wherein the disk has a thickness such that the deflection of the disk at the maximum value of the predetermined range is less than the predetermined deflection.
5. The system of claim 4 wherein the thickness is in the range from about 0.250 inches to 0.375 inches.
6. The system of claim 1 wherein the barrier further comprises:

10

- a seal fixture fixedly disposed about the disk, wherein the seal is disposed about a circumference of the seal fixture; and
- an edge disposed about the periphery of the seal fixture, the edge configured to scrape residue from the interior surface of the shell.
7. The system of claim 6 wherein the disk comprises one or more stiffeners attached to a first side of the disk.
8. The system of claim 7 wherein the disk further comprises one or more stiffeners attached to a second side of the disk opposite the first side.
9. The system of claim 8 wherein the plurality of stiffeners attached to the second side is rotationally offset about a central axis of the disk from the plurality of stiffeners attached to the first side.
10. A system comprising:
- a container comprising:
- a cylindrical shell, wherein the cylindrical shell defines an internal volume of the container;
- a barrier comprising:
- a disk slideably disposed within the interior volume of the container, the disk subdividing the interior volume of the container into a first portion and a second portion;
- a plurality of stiffeners attached to the disk; and
- a seal disposed about the disk and in sealing contact with an interior surface of the cylindrical shell;
- a hydraulic cylinder coupled to the disk, the hydraulic cylinder configured to motivate the barrier within the interior volume; and
- wherein the second portion is configured to receive a waste material.
11. The system of claim 10 further comprising a gas monitor coupled to the first portion of the interior volume.

* * * * *