



US010105729B1

(12) **United States Patent**
Fugere

(10) **Patent No.:** **US 10,105,729 B1**
(45) **Date of Patent:** ***Oct. 23, 2018**

(54) **MATERIAL DISPENSE TIPS AND METHODS FOR FORMING THE SAME**

B29K 2063/00 (2013.01); *B29K 2881/00* (2013.01); *B29L 2031/7544* (2013.01)

(71) Applicant: **DL Technology, LLC**, Haverhill, MA (US)

(58) **Field of Classification Search**

CPC *B05C 11/1034*; *B05C 17/00516*; *B05C 17/00503*; *B05B 1/02*; *B05B 15/065*; *B05B 7/0466*; *B29C 65/485*
USPC 239/390, 391, 419, 432, 589, 600, 602, 239/DIG. 12, DIG. 19; 222/372, 420, 222/427, 567

(72) Inventor: **Jeffrey P. Fugere**, Hampton Falls, NH (US)

See application file for complete search history.

(73) Assignee: **DL Technology, LLC.**, Haverhill, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 187 days.

This patent is subject to a terminal disclaimer.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,453,161 A 4/1923 Murphy et al.
1,593,016 A 7/1926 Campbell
(Continued)

(21) Appl. No.: **15/042,388**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Feb. 12, 2016**

EP 0110591 B1 10/1986

Related U.S. Application Data

(63) Continuation of application No. 14/287,714, filed on May 27, 2014, now Pat. No. 9,272,303, which is a continuation of application No. 12/647,911, filed on Dec. 28, 2009, now Pat. No. 8,864,055.

(60) Provisional application No. 61/251,497, filed on Oct. 14, 2009, provisional application No. 61/174,742, filed on May 1, 2009.

OTHER PUBLICATIONS

Micro-Mechanics Design Specifications, May 1999.
(Continued)

Primary Examiner — Steven J Ganey

(74) *Attorney, Agent, or Firm* — Onello & Mello, LLP.

(51) **Int. Cl.**

B05B 17/00 (2006.01)
B05C 11/10 (2006.01)
B05B 15/06 (2006.01)
B05B 1/02 (2006.01)
B29C 65/48 (2006.01)
B05B 15/65 (2018.01)

(Continued)


(57) **ABSTRACT**

A dispense tip constructed and arranged to communicate with a material dispensing pump comprises an elongated neck and a molded base having a first portion and a second portion opposite the first portion. The neck extends from the first portion of the base. The second portion is constructed and arranged to abut an outlet surface of the pump. An outermost region of the second portion of the base includes a compressible fluid-tight surface that compliantly conforms to the outlet surface when the dispense tip is mounted to the pump.

(52) **U.S. Cl.**

CPC *B05C 11/1034* (2013.01); *B05B 1/02* (2013.01); *B05B 15/065* (2013.01); *B05B 15/65* (2018.02); *B29C 65/485* (2013.01);

19 Claims, 10 Drawing Sheets



(51)	Int. Cl.								
	B29K 63/00	(2006.01)							
	B29L 31/00	(2006.01)							
(56)	References Cited								
	U.S. PATENT DOCUMENTS								
	2,269,823	A	1/1942	Kreiselman	5,795,390	A	8/1998	Cavallaro	
	2,506,657	A	5/1950	Webster	5,803,661	A	9/1998	Lemelson	
	2,656,070	A	10/1953	Linder	5,814,022	A	9/1998	Antanavich et al.	
	2,933,259	A	4/1960	Raskin	5,819,983	A	10/1998	White et al.	
	3,344,647	A	10/1967	Berger	5,823,747	A	10/1998	Ciavarini et al.	
	3,355,766	A	12/1967	Causemann	5,833,851	A	11/1998	Adams et al.	
	3,379,196	A	4/1968	Mitchell	5,837,892	A	11/1998	Cavallaro et al.	
	3,394,659	A	7/1968	Van Alen	5,886,494	A	3/1999	Prentice et al.	
	3,507,584	A	4/1970	Robbins, Jr.	5,903,125	A	5/1999	Prentice et al.	
	3,693,884	A	9/1972	Snodgrass et al.	5,904,377	A	5/1999	Throup	
	3,732,734	A	5/1973	Avakian	5,918,648	A	7/1999	Carr et al.	
	3,734,635	A	5/1973	Blach et al.	5,925,187	A	7/1999	Freeman et al.	
	3,771,476	A	11/1973	Heinle	5,927,560	A	7/1999	Lewis et al.	
	3,811,601	A	5/1974	Reighard et al.	5,931,355	A	8/1999	Jefferson	
	3,938,492	A	2/1976	Mercer, Jr.	5,947,022	A	9/1999	Freeman et al.	
	3,963,151	A	6/1976	North, Jr.	5,947,509	A	9/1999	Ricks et al.	
	4,004,715	A	1/1977	Williams et al.	5,957,343	A	9/1999	Cavallaro	
	4,077,180	A	3/1978	Agent et al.	5,971,227	A	10/1999	White et al.	
	4,116,766	A	9/1978	Poindexter et al.	5,984,147	A	11/1999	Van Ngo	
	4,168,942	A	9/1979	Firth	5,985,029	A	11/1999	Purcell	
	4,239,462	A	12/1980	Dach et al.	5,985,206	A	11/1999	Zabala et al.	
	4,258,862	A	3/1981	Thorsheim	5,985,216	A	11/1999	Rens et al.	
	4,312,630	A	1/1982	Travaglini	5,988,530	A	11/1999	Rockefeller	
	4,339,840	A	7/1982	Monson	5,992,688	A	11/1999	Lewis et al.	
	4,346,849	A	8/1982	Rood	5,993,183	A	11/1999	Laskaris et al.	
	4,377,894	A	3/1983	Yoshida	5,995,788	A	11/1999	Beek	
	4,386,483	A	6/1983	Schlaefi	6,007,631	A	12/1999	Prentice et al.	
	4,408,699	A	10/1983	Stock	6,017,392	A	1/2000	Cavallaro	
	4,471,890	A	* 9/1984	Dougherty	6,025,689	A	2/2000	Prentice et al.	
				A61F 9/0026	6,068,202	A	5/2000	Hynes et al.	
				222/420	6,082,289	A	7/2000	Cavallaro	
	4,513,190	A	4/1985	Ellett et al.	6,085,943	A	7/2000	Cavallaro et al.	
	4,572,103	A	2/1986	Engel	6,093,251	A	7/2000	Carr et al.	
	4,579,286	A	4/1986	Stoudt	6,112,588	A	9/2000	Cavallaro et al.	
	4,584,964	A	4/1986	Engel	6,119,895	A	9/2000	Fugere et al.	
	4,610,377	A	9/1986	Rasmussen	6,126,039	A	10/2000	Cline et al.	
	4,673,109	A	6/1987	Cassia	6,132,396	A	10/2000	Antanavich et al.	
	4,705,218	A	11/1987	Daniels	6,157,157	A	12/2000	Prentice et al.	
	4,705,611	A	11/1987	Grimes et al.	6,196,521	B1	3/2001	Hynes et al.	
	4,743,243	A	5/1988	Vaillancourt	6,199,566	B1	3/2001	Gazewood	
	4,785,996	A	11/1988	Ziecker et al.	6,206,964	B1	3/2001	Purcell et al.	
	4,803,124	A	2/1989	Kunz	6,207,220	B1	3/2001	Doyle et al.	
	4,836,422	A	6/1989	Rosenberg	6,214,117	B1	4/2001	Prentice et al.	
	4,859,073	A	8/1989	Howseman, Jr. et al.	6,216,917	B1	4/2001	Crouch	
	4,917,274	A	4/1990	Asa et al.	6,224,671	B1	5/2001	Cavallaro	
	4,919,204	A	4/1990	Baker et al.	6,224,675	B1	5/2001	Prentice et al.	
	4,935,015	A	6/1990	Hall	6,234,358	B1	5/2001	Romine et al.	
	4,941,428	A	7/1990	Engel	6,250,515	B1	6/2001	Newbold et al.	
	4,969,602	A	11/1990	Scholl	6,253,957	B1	7/2001	Messerly et al.	
	5,002,228	A	3/1991	Su	6,253,972	B1	7/2001	DeVito et al.	
	5,106,291	A	4/1992	Gellert	6,257,444	B1	7/2001	Everett	
	5,130,710	A	7/1992	Salazar	6,258,165	B1	7/2001	Cavallaro	
	5,161,427	A	11/1992	Fukuda et al.	6,299,078	B1	10/2001	Fugere	
	5,176,803	A	1/1993	Barbuto et al.	6,322,854	B1	11/2001	Purcell et al.	
	5,177,901	A	1/1993	Smith	6,324,973	B2	12/2001	Rossmeisl et al.	
	5,186,886	A	2/1993	Zerinvary et al.	6,354,471	B2	3/2002	Fujii	
	RE34,197	E	3/1993	Engel	6,371,339	B1	4/2002	White et al.	
	5,217,154	A	6/1993	Elwood et al.	6,378,737	B1	4/2002	Cavallaro et al.	
	5,265,773	A	11/1993	Harada	6,383,292	B1	5/2002	Brand et al.	
	5,348,453	A	9/1994	Baran et al.	6,386,396	B1	5/2002	Strecker	
	5,407,101	A	4/1995	Hubbard	6,391,378	B1	5/2002	Carr et al.	
	5,452,824	A	9/1995	Danek et al.	6,395,334	B1	5/2002	Prentice et al.	
	5,535,919	A	7/1996	Ganzer et al.	6,412,328	B1	7/2002	Cavallaro et al.	
	5,553,742	A	9/1996	Maruyama	6,453,810	B1	9/2002	Rossmeisl et al.	
	5,564,606	A	10/1996	Engel	6,511,301	B1	1/2003	Fugere	
	5,567,300	A	10/1996	Datta et al.	6,514,569	B1	2/2003	Crouch	
	5,637,815	A	6/1997	Takahata et al.	6,540,832	B2	4/2003	Cavallaro	
	5,685,853	A	11/1997	Bonnet	6,541,063	B1	4/2003	Prentice et al.	
	5,699,934	A	12/1997	Kolcun et al.	6,547,167	B1	4/2003	Fugere	
	5,765,730	A	6/1998	Richter	6,562,406	B1	5/2003	Chikahisa et al.	
	5,785,068	A	7/1998	Sasaki et al.	6,609,902	B1	8/2003	Blais et al.	
					6,619,198	B2	9/2003	Rossmeisl et al.	
					6,626,097	B2	9/2003	Rossmeisl et al.	
					6,851,923	B1	2/2005	Fugere	
					6,892,959	B1	5/2005	Fugere	
					6,896,202	B1	5/2005	Fugere	
					6,957,783	B1	10/2005	Fugere	
					6,981,664	B1	1/2006	Fugere	
					6,983,867	B1	1/2006	Fugere	

(56)

References Cited

U.S. PATENT DOCUMENTS

7,000,853 B2 2/2006 Fugere
 7,178,745 B1 2/2007 Fugere
 7,207,498 B1 4/2007 Fugere
 7,331,482 B1 2/2008 Fugere
 RE40,539 E 10/2008 Fugere
 7,448,857 B1 11/2008 Fugere
 7,694,857 B1 4/2010 Fugere
 7,744,022 B1 6/2010 Fugere
 7,762,480 B1 7/2010 Fugere
 7,905,945 B1 3/2011 Fugere
 8,056,833 B1 11/2011 Fugere
 8,690,084 B1 4/2014 Fugere
 8,707,559 B1 4/2014 Fugere
 8,864,055 B2 10/2014 Fugere
 2002/0007227 A1 1/2002 Prentice et al.
 2002/0020350 A1 2/2002 Prentice et al.
 2003/0000462 A1 1/2003 Prentice et al.
 2003/0038190 A1 2/2003 Newbold et al.
 2003/0066546 A1 4/2003 Bibeault et al.
 2003/0071149 A1 4/2003 Verrilli
 2003/0084845 A1 5/2003 Prentice et al.
 2003/0091727 A1 5/2003 Prentice et al.
 2003/0132243 A1 7/2003 Engel
 2004/0089228 A1 5/2004 Prentice et al.

2005/0103886 A1 5/2005 Verrilli
 2005/0158042 A1 7/2005 Verrilli
 2006/0157517 A1* 7/2006 Fiske B05C 5/001
 222/504

OTHER PUBLICATIONS

Ulrich, Rene, "Epoxy Die Attach: the Challenge of Big Chips", Semiconductor International, Oct. 1994.
 Sela, Uri, et al., "Dispensing Technology: The Key to High-Quality, High-Speed, Die-Bonding", Microelectronics Manufacturing Technology, Feb. 1991.
 Karassik, et al., "Pump Hand Book" Second Ed., McGraw Hill Inc., 1986, p. 9.30.
 Application and Prosecution history of U.S. Appl. No. 12/647,911, filed Dec. 28, 2009, by Jeffrey P. Fugere, entitled "Material Dispense Tips and Methods for Forming the Same", which is stored in the United States Patent and Trademark Office (USPTO) Image File Wrapper (IFW) System.
 "Material Dispense Tips and Methods for Forming the Same" Specification, Drawings, Claims and Prosecution History of U.S. Appl. No. 14/287,714, filed May 27, 2014, by Jeffrey P. Fugere.
 "Material Dispense Tips and Methods for Forming the Same" Specification, Drawings, Claims and Prosecution History of U.S. Appl. No. 12/647,911, filed Dec. 28, 2009, by Jeffrey P. Fugere.

* cited by examiner




FIG. 1A




FIG. 1B





FIG. 2






FIG. 3B




FIG. 3D




FIG. 3C






FIG. 4A






FIG. 5A




FIG. 5B






FIG. 5C



MATERIAL DISPENSE TIPS AND METHODS FOR FORMING THE SAME

RELATED APPLICATIONS

This application is a continuation application of U.S. patent application Ser. No. 14/287,714, filed May 27, 2014, which is a continuation application of U.S. patent application Ser. No. 12/647,911, filed Dec. 28, 2009 and issued as U.S. Pat. No. 8,864,055, which claims the benefit of U.S. Provisional Patent Application No. 61/174,742 filed on May 1, 2009 and U.S. Provisional Patent Application No. 61/251,497 filed on Oct. 14, 2009, the entire contents of each of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

A material dispense tip, also referred to as a “pin” or “needle,” is utilized in a variety of applications. For example, a material dispense tip, when attached to a material dispensing pump system, is used to deposit a precise amount of fluid material, such as glue, resin, or paste, at precise positions on a semiconductor substrate. Examples of such material dispensing pumps are described in U.S. Pat. No. 6,511,301, U.S. Pat. No. RE 40,539, U.S. Pat. No. 6,892,959, U.S. Pat. No. 6,983,867, and U.S. Pat. No. 7,331,482, the contents of each of which are incorporated herein by reference in their entirety.

A material dispense tip can be formed according to one of several different approaches. In one approach, a dispense tip can be formed by machining a first stock to form a cylindrical neck, machining a second stock to form a cylindrical base, boring a first hole in the base, inserting the neck into the hole in the base, and forming a second hole through the base and neck.

In another approach, the neck and the base can be unitary and machined from a common stock, for example, stainless steel, or the neck and the base can be molded from ceramics.

In another approach, the neck and the base can each be formed by different methods, and of different materials. For example, the dispense tip can include a molded ceramic neck that is attached to a machined steel base.

The dispense tip can be attached to a material dispensing pump by inserting the base into a cavity in the pump. The base is held in place in the cavity, for example, by a female Luer™-style fitting, which can interface with a corresponding male Luer™-style fitting on the pump. The dispense tip can alternatively be “surface mounted” to a pump, wherein the base of the dispense tip is held in place against an outlet surface of the pump by a nut or other retaining device.

However, when conventional dispense tips are attached to a material dispensing pump, fluid material can leak from an interface between the base of the dispense tip and the pump due to the presence of imperfections such as nicks, cracks, burrs, protrusions, blemishes, dents, or other imperfections on the interfacing surface of the base or on the pump surface against which the base abuts.

Also, a high solvent content may be included in the fluid material to be dispensed in order to prevent the fluid material from coagulating, congealing, drying up and the like in the material path of the dispense tip and the pump. However, these solvents can leach from the material and escape from cracks or crevices in the interfacing surface of the dispense tip, causing the material to dry up and clog the material path. Such solvents may also permeate the feed tube of the material dispense pump or the wall of the dispense tip, depending on the material used to form the dispense tip. For

example, in a case where polypropylene or silicone materials are employed to form the dispense tip, certain solvents can permeate these materials.

The base of a conventional dispense tip can be formed by machining plastics. These plastics can be highly stable, possess favorable hardness properties, be resilient to solvents, and adhere to molded necks, such as ceramic necks, using adhesives such as two-part epoxy. In addition, the base comprising such plastics can be machined to close tolerances. However, when machining these plastics from a stock, it is difficult to deburr the finished base from the stock, which can impede the flow of material in the material path formed by holes in the base and neck, or can clog the dispense tip. Further, these plastics have high viscosity properties, which are undesirable for precision micromolding, since such plastics can be prone to imperfections when filling a mold during the molding process for forming the dispense tips.

SUMMARY OF THE INVENTION

Embodiments of the present invention are directed to material dispense tips and methods of forming the same, which overcome the limitations associated with the aforementioned approaches. Embodiments are further directed to dispense pump cartridges and dispense pump systems employing such material dispense tips and methods of forming the same.

In accordance with one aspect, a dispense tip constructed and arranged to communicate with a material dispensing pump comprises an elongated neck and a molded base having a first portion and a second portion opposite the first portion, the second portion having a same width as the first portion, the neck extending from the first portion of the base, the second portion constructed and arranged to abut an outlet surface of the pump, an outermost region of the second portion of the base including a compressible fluid-tight surface that compliantly conforms to the outlet surface when the dispense tip is mounted to the pump.

In an embodiment, the neck comprises molded materials. In an embodiment, the neck comprises ceramics. In an embodiment, the neck comprises stainless steel.

In an embodiment, the second portion of the base comprises polyarylene sulfide. In an embodiment, the polyarylene sulfide is polyphenylene sulfide. In an embodiment, the polyphenylene sulfide is linear and partially crystalline.

In an embodiment, the first and second portions of the base comprise polyarylene sulfide.

In an embodiment, the base is coupled to the neck by bonding the base to the neck with a bonding material.

In an embodiment, the bonding material includes a two-part epoxy.

In an embodiment, the dispense tip is constructed and arranged to communicate with a fixed-z material dispensing pump. In an embodiment, the dispense tip is constructed and arranged to communicate with a fixed-z material dispensing pump.

In an embodiment, the neck comprises an elongated hole that extends from an input end of the neck to an output end of the neck and an inner taper between the input end of the neck and the output end of the neck that transitions the input end to the output end. In an embodiment, a portion of the elongated hole has an inner surface of a first inner diameter and the output end includes an outlet having an inner surface of a second inner diameter, the first inner diameter being greater than the second inner diameter.

In an embodiment, the base includes a funnel that delivers fluid to the neck, the funnel having a funnel inlet at an input end of the funnel and a funnel outlet at an output end of the funnel, wherein the neck communicates with the funnel outlet such that the dispense tip includes a single material path between the funnel outlet and an output end of the neck.

In an embodiment, dispense tip further comprises an alignment foot coupled to the base, the foot having a primary axis substantially parallel to a longitudinal axis of the neck, and being of a length longer than the neck.

In an embodiment, the dispense tip further comprises a plurality of elongated necks, each neck coupled to the first portion of the base, the base including a single funnel, each neck including a hole having a single input end and a single output end, the input end communicating with the funnel such that each neck includes a single fluid path between the funnel and the output end of the neck.

In accordance with another aspect, a dispense tip constructed and arranged to communicate with a material dispensing pump comprises an elongated neck and a base coupled to the neck, the base including a compressible surface such that a fluid-tight interface can be formed between the compressible surface of the base and the pump by compliantly conforming the base to the pump when the dispense tip is mounted to the pump, wherein the compressible surface of the base comprises polyarylene sulfide.

In an embodiment, the polyarylene sulfide is polyphenylene sulfide. In an embodiment, the polyphenylene sulfide is linear and partially crystalline.

In an embodiment, the base has a first portion and a second portion opposite the first portion, the neck extending from the first portion of the base, the second portion comprising the compressible surface. In an embodiment, the first and second portions have a same width.

In an embodiment, the first and second portions of the base comprise polyarylene sulfide.

In an embodiment, the dispense tip is constructed and arranged to communicate with a fixed-z material dispensing pump. In an embodiment, the dispense tip is constructed and arranged to communicate with a floating-z material dispensing pump.

In an embodiment, the neck comprises an elongated hole that extends from an input end of the neck to an output end of the neck and an inner taper between the input end of the neck and the output end of the neck that transitions the input end to the output end. In an embodiment, a portion of the elongated hole has an inner surface of a first inner diameter and the output end includes an outlet having an inner surface of a second inner diameter, the first inner diameter being greater than the second inner diameter.

In an embodiment, the base includes a funnel that delivers fluid to the neck, the funnel having a funnel inlet at an input end of the funnel and a funnel outlet at an output end of the funnel, wherein the neck communicates with the funnel outlet such that the dispense tip includes a single material path between the funnel outlet and an output end of the neck.

In an embodiment, the dispense tip comprises an alignment foot coupled to the base, the foot having a primary axis substantially parallel to a longitudinal axis of the neck, and being of a length longer than the neck.

In an embodiment, the dispense tip comprises a plurality of elongated necks, each neck coupled to the first portion of the base, the base including a single funnel, each neck including a hole having a single input end and a single output end, the input end communicating with the funnel such that each neck includes a single fluid path between the funnel and the output end of the neck.

In accordance with another aspect, a material dispensing system comprises a material dispensing pump comprising an inlet that receives a source of material and an outlet, wherein the material dispensing pump outputs the material from the inlet to the outlet; and a dispense tip compliantly conforming to a surface of the outlet of the material dispensing pump. The dispense tip comprises an elongated neck and a molded base having a first portion and a second portion opposite the first portion, the second portion having a same width as the first portion, the neck extending from the first portion of the base, the second portion constructed and arranged to abut an outlet surface of the pump, an outermost region of the second portion of the base including a compressible fluid-tight surface that compliantly conforms to the outlet surface.

In an embodiment, the neck comprises molded materials. In an embodiment, the neck comprises ceramics. In an embodiment, the neck comprises stainless steel.

In an embodiment, the second portion of the base comprises polyarylene sulfide. In an embodiment, the polyarylene sulfide is polyphenylene sulfide. In an embodiment, the polyphenylene sulfide is linear and partially crystalline.

In an embodiment, the first and second portions of the base comprise polyarylene sulfide.

In an embodiment, the material dispensing system is a fixed-z pump system. In an embodiment, the material dispensing system is a floating-z pump system.

In an embodiment, the dispense tip further comprises an alignment foot coupled to the base, the foot having a primary axis substantially parallel to a longitudinal axis of the neck, and being of a length longer than the neck.

In an embodiment, the dispense tip further comprises a plurality of elongated necks, each neck coupled to the first portion of the base, the base including a single funnel, each neck including a hole having a single input end and a single output end, the input end communicating with the funnel such that each neck includes a single fluid path between the funnel and the output end of the neck.

In an embodiment, the pump includes a cartridge, the outlet at a distal end of the cartridge, and the cartridge further comprises a feed screw that delivers the material from the pump from the inlet to the outlet.

In an embodiment, the material dispensing system comprises a retainer nut that holds the dispense tip in place against the outlet surface.

In an embodiment, the material dispensing system comprises an alignment tab that extends from the pump, and wherein a portion of the base includes a flat surface that abuts the alignment tab.

In accordance with another aspect, a material dispensing system comprises a material dispensing pump comprising an inlet that receives a source of material and an outlet, wherein the material dispensing pump outputs the material from the inlet to the outlet; and a dispense tip compliantly conforming to a surface of the outlet of the material dispensing pump, the dispense tip comprising: an elongated neck; and a base coupled to the neck, the base including a compressible surface such that a fluid-tight interface can be formed between the compressible surface of the base and the pump by compliantly conforming the base to the pump when the dispense tip is mounted to the pump, wherein the compressible surface of the base comprises polyarylene sulfide.

In an embodiment, the polyarylene sulfide is polyphenylene sulfide. In an embodiment, the polyphenylene sulfide is linear and partially crystalline.

In an embodiment, the base has a first portion and a second portion opposite the first portion, the neck extending from the first portion of the base, the second portion com-

5

prising the compressible surface. In an embodiment, the first and second portions have a same width.

In an embodiment, the first and second portions of the base comprise polyarylene sulfide.

In an embodiment, the material dispensing system is a fixed-z pump system. In an embodiment, the material dispensing system is a floating-z pump system.

In an embodiment, the pump includes a cartridge; the outlet at a distal end of the cartridge, and wherein the cartridge further comprises a feed screw that delivers the material from the pump from the inlet to the outlet.

In an embodiment, the material dispensing system further comprises a retainer nut that holds the dispense tip in place against the outlet surface.

In accordance with another aspect, a method of forming a dispense tip that communicates with a material dispensing pump comprises forming an elongated neck; molding a material to form a base having an outermost compressible surface; and coupling the base to the neck, wherein the base comprises an outermost region that includes a compressible fluid-tight surface that compliantly conforms to an outlet surface of the pump when the dispense tip is mounted to the pump.

In an embodiment, the material comprises polyarylene sulfide. In an embodiment, the polyarylene sulfide is polyphenylene sulfide. In an embodiment, the polyphenylene sulfide is linear and partially crystalline.

In an embodiment, the material has a low viscosity, such that the material conforms to the shape of the mold.

In an embodiment, the neck is formed of molded materials. In an embodiment, the neck is formed of ceramics. In an embodiment, the neck is machined from stainless steel.

In an embodiment, the base is coupled to the neck by bonding the base to the neck with a bonding material. In an embodiment, the bonding material includes a two-part epoxy.

In an embodiment, the method further comprises forming an elongated hole in the neck that extends from an input end of the neck to an output end of the neck; and forming an inner taper between the input end of the neck and the output end of the neck that transitions the input end to the output end. In an embodiment, a portion of the elongated hole has an inner surface of a first inner diameter and the output end includes an outlet having an inner surface of a second inner diameter, the first inner diameter being greater than the second inner diameter.

In an embodiment, forming the base includes forming a funnel that delivers fluid to the neck, the funnel having a funnel inlet at an input end of the funnel and a funnel outlet at an output end of the funnel, wherein the neck communicates with the funnel outlet such that the dispense tip includes a single material path between the funnel outlet and an output end of the neck.

In accordance with another aspect, a dispense tip that communicates with a material dispensing pump comprises an elongated neck, a base, and a material path between an outermost region of the base and an outlet of the neck; the dispense tip formed according to the process of molding a material having low viscosity to form a base; and coupling the base to the neck, wherein the outermost region of the base includes a compressible fluid-tight surface that compliantly conforms to an outlet surface of the pump when the dispense tip is mounted to the pump.

In accordance with another aspect, a dispense tip is constructed and arranged to communicate with a material dispensing pump, and comprises an elongated neck comprising stainless steel; and a base having a first portion and

6

a second portion opposite the first portion. The first portion comprises stainless steel, the second portion comprises a compressible fluid-tight interface that compliantly conforms to an outlet surface of the material dispensing pump when the dispense tip is mounted to the pump.

In an embodiment, the second portion of the base comprises polyarylene sulfide.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects and advantages of the invention will be apparent from the more particular description of preferred embodiments of the invention, as illustrated in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention. In the drawings:

FIG. 1A is a perspective side view of an embodiment of a dispense tip in accordance with aspects of the present invention;

FIG. 1B is a front view of the dispense tip of FIG. 1A;

FIG. 2 is a cutaway side view of an embodiment of a material dispensing system comprising a dispense tip coupled to a material dispensing pump in accordance with aspects of the present invention;

FIG. 3A is an exploded perspective view of an embodiment of a material dispensing system comprising a dispense tip and a material dispensing pump, in accordance with aspects of the present invention;

FIG. 3B is a cutaway, assembled perspective view of the material dispensing system of FIG. 3A, in accordance with aspects of the present invention;

FIG. 3C is a close-up illustrative side view of an embodiment where interfacing surfaces of the dispense tip and the material dispensing pump of FIG. 3A in a position where they are separated from each other;

FIG. 3D is a close-up illustrative side view of an embodiment of an interface between the dispense tip and the material dispensing pump of FIG. 3B in a position where they are coupled together;

FIG. 4A is a perspective view of an embodiment of a dispense tip including an alignment foot, in accordance with aspects of the present invention;

FIG. 4B is a cutaway side view of the dispense tip of FIG. 4A;

FIG. 4C is a front view of the dispense tip of FIG. 4A;

FIG. 5A is perspective view of an embodiment of a dispense tip including multiple necks coupled to a single base in accordance with aspects of the present invention;

FIG. 5B is a cutaway side view of the dispense tip of FIG. 5A;

FIG. 5C is a front view of the dispense tip of FIG. 5A;

FIG. 6A is a perspective view of an embodiment of a dispense tip having a first portion of a base that is separate from a second portion of the base, in accordance with aspects of the present invention; and

FIG. 6B is a perspective view of the dispense tip of FIG. 6A, wherein the first portion of the base is coupled to the second portion of the base, in accordance with aspects of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS

The accompanying drawings are described below, in which example embodiments in accordance with the present invention are shown. Specific structural and functional

details disclosed herein are merely representative. This invention may be embodied in many alternate forms and should not be construed as limited to example embodiments set forth herein.

Accordingly, specific embodiments are shown by way of example in the drawings. It should be understood, however, that there is no intent to limit the invention to the particular forms disclosed, but on the contrary, the invention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the claims.

It will be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are used to distinguish one element from another. For example, a first element could be termed a second element, and, similarly, a second element could be termed a first element, without departing from the scope of the present disclosure. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

It will be understood that when an element is referred to as being “on,” “connected to” “abutting,” “coupled to,” or “extending from” another element, it can be directly on, connected to or coupled to the other element or intervening elements may be present. In contrast, when an element is referred to as being “directly on,” “directly connected to,” “directly abutting,” or “directly coupled to” another element, there are no intervening elements present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.).

The terminology used herein is for the purpose of describing particular embodiments and is not intended to be limiting of the invention. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

In accordance with embodiments, dispense tips are provided that dispense precise amounts of material at precise positions on a substrate. In addition, the dispense tips prevent the material, which can include solids, liquids, and/or gases, from escaping or leaching from a material path in the dispense tip during a dispensing operation, or prevent the material from leaking from an interface formed between a surface of the dispense tip and a surface of a material dispensing pump against which the dispense tip abuts.

To achieve this, the dispense tips in accordance with embodiments comprise a compliant, deformable base that includes an interfacing surface at an outermost surface of the base that compliantly conforms to the surface of the material dispensing pump, and provides a fluid-tight interface between the dispense tip and the material dispensing pump. The term “fluid-tight interface” as used herein is also intended to refer to an airtight interface. Accordingly, the dispense tips prevent leaching of solvents through a surface thereof, and also prevent leaking of material to be dispensed from the fluid-tight interface.

In accordance with other embodiments, the dispense tips can comprise molded dispense tips, for example, formed by injection molding. In particular, a material is heated to a molding temperature, and injected into a mold. The material used to form the molded dispense tip is preferably a high-flow material, and has low viscosity properties. In certain embodiments, the dispense tips formed according to the molding process have favorable hardness properties, permitting the dispense tips to replace conventional steel dispense tips, which provides significant cost advantages over steel tips. In other embodiments, the surface of a molded

dispense tip is compliantly compressible when coupled to a material dispensing pump, which prevents leaking from occurring at an interface between the dispense tip and the material dispensing pump. In other embodiments, the molded dispense tip includes chemical resistance properties, which, inter alia, permits the dispense tip to be resistant to the leaching of solvents. In addition, the dispense tips formed by molding are precision molded, i.e., molded to close tolerances, but do not require machining, and therefore, there is no risk of burrs or particles resulting from machining, which can become trapped in the material path of the dispense tip.

FIG. 1A is a perspective side view of an embodiment of a dispense tip **200** in accordance with aspects of the present invention. FIG. 1B is a front view of the dispense tip **200** of FIG. 1A.

As shown in FIGS. 1A and 1B, the dispense tip **200** comprises a neck **210** and a base **220** (also referred to herein as a body). In an embodiment, the neck **210** is formed separately from the base **220**, and later joined to the base **220**, in which case the base **220** and neck **210** can be coupled together via press-fitting, bonding, or welding, or other applicable techniques. In an embodiment, the neck **210** can be coupled to the base **220** by a bonding material. In an embodiment, the bonding material is a two-part epoxy, or other suitable adhesive known to those of ordinary skill in the art. In other embodiments, the dispense tip **200** is a unitary dispense tip, wherein the neck **210** and the base **220** are formed from a single stock of material that is molded or machined.

In an embodiment, the neck **210** can comprise materials such as stainless steel, ceramics, composites such as plastics, glass, composites of these materials, or other materials known to those of ordinary skill in the art as being suitable to form a neck that can dispense materials, which dispensed materials can include solids, liquids, gases, or a combination thereof.

The neck **210** can be formed by molding, in particular, micromolding, or formed by die casting or machining. The term “micromolding” is a term of art that is known to those of ordinary skill in the art, and, as used herein, can mean molding small, intricate precision plastic elements or structures for a variety of applications spanning numerous industries. In an embodiment, the neck **210** is formed by machining a stock such as stainless steel stock or polymer stock, for example, plastic. In another embodiment, the neck **210** is formed by molded materials such as ceramics or polymers such as plastics. In embodiments, the neck **210** is formed according to approaches similar to those used to form necks of dispense tips disclosed in U.S. Pat. No. 6,547,167, U.S. Pat. No. 6,981,664, U.S. Pat. No. 6,957,783, and U.S. patent application Ser. No. 12/034,313, filed Feb. 20, 2008, entitled “Material Dispense Tips and Methods for Manufacturing the Same,” the contents of each of which is incorporated herein by reference in its entirety.

In an embodiment, the neck **210** comprises an outlet bevel **211** about an opening at an output end of the neck, to reduce the amount of surface tension, or “land,” at the opening, for example, as described in U.S. Pat. No. 6,547,167, U.S. Pat. No. 6,981,664, U.S. Pat. No. 6,957,783, and U.S. patent application Ser. No. 12/034,313, filed Feb. 20, 2008, entitled “Material Dispense Tips and Methods for Manufacturing the Same,” the contents of each of which is incorporated by reference herein in its entirety.

In an embodiment, the base **220**, for example, at least a second portion **222** of the base **220**, comprises a material that is compliant or deformable relative to a surface hardness

of a material dispensing pump to which the base **220** is coupled. As a result of the compliant base, when the dispense tip **200** is coupled to an outlet region of the material dispensing pump, for example, as illustrated in FIG. 2, or to a conventional dispensing pump, a fluid-tight interface is formed between the base **220** and the material dispensing pump when the dispense tip **200** is mounted to the dispensing pump. In an embodiment, the entire base **220**, at least including a first portion or main body portion **221** and the second outermost portion **222**, comprises the compliant material. In another embodiment, at least the second portion **222** of the base **220** comprises the compliant material, such that the second portion **222** of the base **220** is more deformable or compliant relative to a surface hardness of a material dispensing pump than the first portion **221** of the base **220**. In another embodiment, the first portion **221**, the second portion **222**, and a third neck-retaining portion **228** all comprise the compliant material.

As shown in FIGS. 1A and 1B, in an embodiment, the base **220** is a molded base **220** comprising a polymer material having a low viscosity, wherein cavities or voids that may otherwise be formed in the mold during formation of the molded base **220** are filled during the molding process. Therefore, the base **220** includes hardness properties similar to those of conventional machined bases, but is also resistant to solvents, and also includes a compliantly conforming fluid-tight interface **288**, as shown in FIG. 2. Other preferred properties of a molded-type base include a viscosity low enough for the composition to readily conform to the shape of the mold, high-temperature resistance (e.g., up to about 240° C.), chemical and oxidation resistance, sufficient hardness and rigidity, low creep, and low permeability after molding.

In an embodiment, the base **220** includes a first portion **221** and a second portion **222** extending from a first side surface of the first portion **221**. In an embodiment, the first and second portions **221**, **222** extend along the thickness (*t*) of the base **220** and have a same outer width, for example, a same outer width (*w1*), and/or a same outer width (*w2*). In another embodiment, the first portion **221** and the second portion **222** have different outer dimensions, such as different outer widths.

In an embodiment, the base **220** includes a third portion **228** that extends from a second side surface **227** of the first portion **221**, wherein the first portion **221** is positioned between the second portion **222** and the third portion **228**. In another embodiment, the third portion **228** extends from a surface of the second portion **222**. In an embodiment, the first and second portions **221**, **222** have greater widths than the width of the third portion **228**. The third portion **228** can provide added rigidity to the dispense tip **200** by extending from the first portion **221** and receiving the neck **210**.

Further, the third portion **228** can provide an improved geometry of the dispense tip **200** with regard to the relationship between the diameter or width of the neck **210** and the length of the base **220**. Specifically, the addition of the third portion **228** of the base **220** increases the overall length of the base **220** from base length (*t*), also referred to as base thickness, to base length (*l*). Accordingly, the ratio of base length (*l*) to neck width (*w3*) is increased as compared to the ratio of base length (*t*) to neck width (*w3*).


This increased ratio is beneficial in embodiments where the base **220** is formed separately from the neck **210**, and the neck **210** is coupled to the base **220** by inserting the neck **210** into a hole (not shown) in the base **220**. In these embodiments, the base **220** extends along a longitudinal axis A, and when the neck **210** is inserted into the base **220**, the neck **210**

likewise extends along the longitudinal axis A. It is preferable that there is no angular deviation between the neck **210** and the longitudinal axis A. To achieve this, the hole extends through the third portion **228**, as well as the first and second portions **221** and **222** of the base **220**, and the neck **210** is inserted into the hole at the third portion **228** of the base **220** and extends through the third portion **228** into at least a portion of the second portion **222** of the neck **210**. Accordingly, the increased length (*l*) of the base **220** relative to the neck width (*w3*) can minimize or prevent any angular deviation between the neck **210** and the axis A.

The neck **210** can extend from the second side **227** of the base **220**, or alternatively, when the base **220** comprises a third portion **228**, the neck **210** can extend from the third portion **228** of the neck. In embodiments where the neck **210** is formed separately from the base **220**, the neck **210** can be inserted into the third portion **228** of the neck **210**. In other embodiments, the neck **210** and the base **220** including the third portion **228** are molded from a common material.

In an embodiment, at least the second portion **222**, and optionally the first portion **221** of the base **220** comprises a compliant material, such as a molded polyarylene sulfide. In other embodiments, the first portion **221**, second portion **222**, and third portion **228** comprise a compliant material, such as a molded polyarylene sulfide. In other embodiment, the base **220** and the neck **210** comprises a compliant material, such as a molded polyarylene sulfide. In an embodiment, the molded polyarylene sulfide is a linear, partially crystalline polyphenylene sulfide, for example, available FORTRON™ 6165A6 PPS, or various forms of FORTRON™ 6165A6 PPS, such as FORTRON™ 6165A6NAT, a color designation of the material. In an embodiment, at least the second portion **222**, and optionally at least the first portion **221**, third portion **228**, and neck **210** comprise linear polymers.

The abovementioned molded polyarylene sulfide structure can also include glass fibers and one or more minerals (e.g., chalk, calcium carbonate, wollastonite, silicon dioxide, talc, mica, montmorillonite, and/or phyllosilicates) at a combined weight percent, e.g., 65%. The polyarylene sulfide includes repeating units aryl groups bonded by sulfur (thioether) linkages. The repeating unit of polyphenylene sulfide (C₆H₄S) can be expressed as follows:



Approximate mechanical properties of FORTRON™ 6165A6 polyphenylene sulfide are as follows:

Tensile Strength:	130 MPa
Strain at Break:	1.2%
Tensile Modulus:	19,000 MPa
Flexural Strength:	210 MPa
Flexural Modulus:	18,800 MPa
Compressive Strength:	230 MPa
Compressive Modulus:	18,500 MPa
Impact Strength (Charpy):	20 kJ/m ²
Notched Impact Strength (Charpy):	7 kJ/m ²
Notched Impact Strength (Izod):	6 kJ/m ²
Ball Indentation Hardness (30 sec.):	428 N/mm ²
Rockwell Hardness (scale M)	100

Other suitable compositions may possess similar approximate mechanical properties in combination with a substantial impermeability to solvents from the pumped composition.

In an embodiment, the second portion **222** has the same cross-sectional dimensions, such as width or diameter, cross-sectional surface area, etc., as the first portion **221** along its thickness relative to the longitudinal axis A, i.e., from an outermost surface **225** (also referred to as a rear face) at a first side of the base **220** to a second side **227** of the base **220**. Although the cross-sectional dimensions can be referred to herein as including “diameters,” such cross-sections are not necessarily a perfect circle; thus, the term “diameter” can include other, non-circular, cross-sectional shapes, for example, the cross-sectional shape of the base **220** shown in FIG. 1B, in which case, the term “diameter” can also refer to “widths” of those cross-sectional shapes. In another embodiment, the second portion **222** can have different dimensions than the first portion **221**. For example, the second portion **222** can have a larger diameter than the first portion **221**, or the second portion **222** can have a different shape than the first portion **221**.

In an embodiment, the base **220** is substantially cylindrical. In other embodiments, as shown in FIGS. 1A and 1B, a portion of the base **220** has a flat surface **226**, also referred to as an alignment surface or locator, that extends along a plane that is parallel to the axis A. The flat surface **226** permits the base **220** to be coupled to a material dispensing pump comprising a locator or tab that protrudes from the pump, for example, see tab **387** shown in FIG. 3A, which permits the dispense tip **200** to be properly aligned with the material dispensing pump **280**. In an embodiment, the base **220** includes a chamfer **229**, preferably about an edge of the second portion **222**, for proper seating of the base **220** against a material dispensing pump, for example, as shown in FIG. 2.

In an embodiment, the dispense tip **200** is compatible with a fixed-z dispensing pump system. In an embodiment, the dispense tip **200** is compatible with a floating-z (also referred to as compliant-z) dispensing pump system. In a fixed-z dispensing pump system, the longitudinal positions of the dispense tip and pump are fixed relative to each other. In a floating-z dispensing pump system, the longitudinal positions of the dispense tip and pump can translate in a longitudinal direction relative to each other.

In an embodiment, the dispense tip **200** is operable in a dispensing pump and gantry system configured to dispense fluid material in the form of a dot. In another embodiment, the dispense tip **200** can dispense fluid material in the form of a line. In another embodiment, the dispense tip **200** can dispense fluid material in the form of an “X” or a star-shaped pattern by an outlet similar to outlets described with regard to U.S. Pat. No. 6,957,783, incorporated by referenced above. In other embodiments, the dispense tip **200** can dispense fluid material in the form of other dispensing patterns known to those of ordinary skill in the art.

FIG. 2 is a cutaway side view of an embodiment of a material dispensing system **10** comprising a dispense tip **400** coupled to a material dispensing pump **280** in accordance with aspects of the present invention. In an embodiment, the dispensing pump **280** comprises a detachable pump cartridge **270**. The cartridge **270** includes a feed screw or auger screw **290** positioned in a feed screw cavity **291**. The feed screw **290** delivers material to an outlet region **295** of the feed screw **290**.

In an embodiment, an outermost surface or rear face **425** of a second portion **422** of the base **420** can be compressed

against, and can be made to compliantly conform to, an outlet surface **283** of the outlet region **295** to form a fluid-tight interface **288** between the base **420** and the pump cartridge **270**. In one embodiment, the interface **288** is a “surface-mount” interface, wherein the pump **280** and dispense tip **400** each has an interfacing surface, wherein the interfacing surfaces are made to come in contact with each other and retained against each other under pressure or force, for example, by a nut, clamp, or other retaining device that holds the dispense tip **400** in place against the outlet surface **283**. In another embodiment, the interface is a “threaded” interface, for example, a Luer™ or other threaded interface, wherein the dispense tip **400** is attached to or removed from the pump by turning the dispense tip **400** in a clockwise or counterclockwise direction about the axis A.

In an embodiment, as shown in FIG. 2, the material dispensing pump **280** has a dispense tip interface, referred to for purposes of the present disclosure as a “surface-mount” interface, described above, wherein the pump **280** has the abovementioned outlet surface **283** against which the dispense tip **400** abuts, and a retainer nut **284** holds the dispense tip **400** in place against the outlet surface **283**, and applies a force against the base **420** that is sufficient to compress the base **420** against the outlet surface **283** such that at least the second portion **422** of the base **420** is deformable relative to the outlet surface **283** to form a fluid-tight seal or interface **288** between the base **420** and the outlet surface **283**. In an embodiment, the rotational torque of nut **284** on threads **292** of the pump outlet translates to a force, which deforms the base **220** to form the interface **288**. In an embodiment, the retainer nut **284** is used when the base **420** is a non-threaded base. In other embodiments, a retaining nut is not required to hold the dispense tip **400** in place against the outlet surface **283**. Rather, the outlet region **295** of the dispensing pump **280** includes a threaded interface, wherein the base **420** can be attached to or removed from the threaded interface of the base **420** by turning the base in a clockwise or counterclockwise direction about the axis A. In other embodiments, the dispense tip **400** can interface with other dispensing pumps, for example, pumps having a Luer™-compliant interface, wherein the pump body has a female Luer™ fitting at its outlet, which interfaces with a corresponding male Luer™ fitting at the inlet of the dispense tip.

In an embodiment, the neck **410** comprises an elongated hole **419** that extends from an input end **412** of the neck **410** to an output end **414** of the neck **410**. The neck **410** includes an inner taper **413** between the input end **412** of the neck **410** and the output end **414** of the neck **410** that transitions the input end **412** to the output end **414**. A portion of the elongated hole **419** has an inner surface of a first inner diameter and the output end **414** includes an outlet having an inner surface of a second inner diameter that is less than the first inner diameter. In the embodiment shown in FIG. 2, the inner taper **413** is proximal to the output end region **414** of the neck. In other embodiments, the inner taper **413** can extend from an interface region proximal to the input end **412** of the neck **410** to the output end **414** of the neck **410**.

In an embodiment, the elongated hole **419** has a first inner diameter that is substantially constant along the length of the hole **419**. In another embodiment, the neck hole **419** comprises a taper or draft from the input end **412** of the neck hole **419** to an outlet hole at the outlet end **414**, such that a diameter at an input end **412** of the neck hole **419** is greater than a diameter at an output end **414** of the outlet hole. In another embodiment, the neck hole **419** comprises a taper or draft from the input end **412** of the neck hole **419** to the inner taper **413**, such that a diameter at the input end **412** of the

neck hole 419 is greater than a diameter at the opposite side of the neck hole 419 near the inner taper 413.

The base 420 includes a funnel 431 that delivers fluid to the neck 410. The funnel 431 includes a funnel inlet 435 at an input end of the funnel 431 and a funnel outlet 436 at an output end of the funnel 431 that is proximal to the input end region 412 of the neck 410. The neck 410 extends from the base 420 and communicates with the funnel outlet 436 such that the dispense tip 400 includes a single material path between the funnel outlet 436 and the output end 414 of the outlet hole. In an embodiment, the funnel inlet 435 at the input end of the funnel 431 is aligned with, and has the same or similar dimensions such as width, diameter, circumference, cross sectional surface area, etc., as an outlet hole 286 in the outlet region 295 of the material dispensing pump 280.

In an embodiment, the funnel 431 is formed in the first and second portions 421, 422 of the base 420. In an embodiment, the funnel 431 is formed in the first portion 421 of the base 420. This embodiment applies particularly to configurations where the second portion 422 of the base has different cross-sectional dimensions than the first portion 421 of the base, for example, when the second portion 422 is ring-shaped, doughnut-shaped, and the like, and has a smaller diameter than the first portion 421. Here, the second portion 422 has a hole that abuts the funnel inlet, such that an uninterrupted fluid path is provided from one end of the base 420 to the other end of the base 420.

In an embodiment, the funnel 431 in the base 420 has a funnel angle, for example, on the order of 45 degrees relative to the longitudinal axis of the neck hole 419. Other funnel angles are equally applicable to embodiments of the present invention, depending on the application.

In an embodiment, the outlet region 295 has the same cross-sectional dimensions as those dimensions of the second portion 422 of the base 420 of the dispense tip 400, for example, a same cross-sectional width or thickness.

FIG. 3A is a perspective view of an embodiment of a material dispensing system 20 comprising a dispense tip 300 and a material dispensing pump 380, wherein the dispense tip 300 is separated from the material dispensing pump 380, in accordance with aspects of the present invention. FIG. 3B is a perspective view of the material dispensing system 20 of FIG. 3A, wherein the dispense tip 300 is coupled to the material dispensing pump 380, in accordance with aspects of the present invention. FIG. 3C is a close-up illustrative side view of an embodiment where interfacing surfaces 325, 383 of the dispense tip 300 and the material dispensing pump 380 of FIG. 3A, respectively, are in a position where they are separated from each other. FIG. 3D is a close-up illustrative side view of an embodiment of an interface 388 between the dispense tip 300 and the material dispensing pump 380 of FIG. 3B in a position where they are coupled together.

In the embodiments illustrated and described with regard to FIGS. 3A-3D, the dispense tip 300 includes a molded base 320 having a second portion 322 comprising a compliant material similar to that used to form the base 220 described with regard to FIGS. 1A, 1B, and 2, for example, a molded polyarylene sulfide such as molded polyphenylene sulfide.

In FIG. 3A, the dispense tip 300 is separated from the pump 380, wherein the molded base 320 of the dispense tip 300 has similar dimensions, such as base thickness (t1), first width, and second width as those of the base 220 shown in FIGS. 1A and 1B, or FIG. 2. In an embodiment, when the base 320 is attached to the material dispensing pump 380, the thickness of the base 320 can be reduced in thickness from its first thickness (t1) to a second smaller thickness, for example, thickness (t2), and/or the cross-sectional dimen-

sions, such as a width of the base 320 perpendicular to its thickness, can be increased to a greater width. In an embodiment, the deformation of the base 320, i.e., the reduction in thickness of the base 320, and/or increase in width or other dimensions of the base 320, can occur due to a force that is applied to the base 320 as a result of a retainer nut 384 in a direction of the axis A along which the dispense tip 300 and the pump 380 are positioned. In an embodiment, the base 320 retains its deformed shape even after a subsequent separation from the pump 380, referred to as “permanent deformation” or “plastic deformation.” In another embodiment, the deformation of the base 320 undergoes a temporary shape change when the force is applied that is self-reversing after the force is removed, and after the base 320 is subsequently separated from the pump 380, referred to as “elastic deformation.” In an embodiment, little or no deformation is made to the base 320 when the base 320 is attached to the pump 380 to form the fluid-tight interface 388. Specifically, a fluid-tight interface 388 is formed between an outermost surface 325 of the base 320 of the dispense tip 300 and the outlet surface 383 of the outlet region 390 of the pump 380 with little or no change in change in thickness, width, length, surface area, or other dimensions.

As described above, a force can be applied to the dispense tip 300 by attaching a retainer nut 384 to the pump 380. Here, the dispense tip 300 is positioned between the retainer nut 384 and the pump 380 such that a fluid-tight interface 388 is formed between an outermost surface 325 of the base 320 of the dispense tip 300 and an outlet surface 383 of an outlet region 390 of the pump 380. In an embodiment, the pump 380 has a surface-mount interface, wherein the nut 384 includes threads that interface with the threads 392 on the pump 380. Here, torque is created when the nut 384 is tightened, which in turn results in a force being applied to the base 320, and the abovementioned deformation to occur. In an embodiment, the dispense tip 300 is attached to the pump 380 by threading the base 320 to the pump 380, for example, in a Luer™ configuration, or by other approaches known to those of ordinary skill in the art such that a fluid-tight interface 388 is formed between the base 320 of the dispense tip 300 and the surface 383 of the outlet region 390 of the pump 380.

In an embodiment, the base 320 comprises a flat surface 326 that is aligned with a locator or tab 387 that protrudes from the outlet region 390 cartridge 370 in a direction along the axis A. In this manner, as shown in FIG. 3A, a hole 386 in the outlet region 390 of the dispensing pump 380 is aligned with a hole (not shown) in the dispense tip 300, for example, a funnel inlet similar to that shown in FIG. 2, such that a single uninterrupted material path is formed between the outlet region 390 and an outlet 340 at the end of the dispense tip 300.

As shown in FIGS. 3A-3D, an outermost surface 325 of the second portion 322 of the base 320 can be compressed against, and tightly abut, an outlet surface of a dispensing pump 380 to form a fluid-tight seal or interface 388 between the base 320 and the outlet surface 383 of the pump 380. Thus, in the event that either the outlet surface 383 or the base surface 325 has any imperfections such as cracks, crevices, and the like, for example, illustrated in FIG. 3C, the second portion 322 of the base 320 can compliantly conform to the outlet surface 383 to reduce or eliminate leaking of dispensing material from the interface region 388 between the base 320 and the pump 380, or leaching of solvents from the material during a dispensing operation that would otherwise occur, for example, illustrated in FIG. 3D. This can include materials and/or solvents that comprise

solids, liquids, and/or gases, or other commonly dispensed materials and can include solder paste, conductive epoxy, surface mount epoxy, solder mask, epoxies, such as two-part epoxy, underfillers, oils, flux, silicone, gasket materials, glues, resins, pastes, medical reagents, certain materials, and the like, or other materials known to those of ordinary skill in the art.

The molded base 320 preferably has a substantially flat outermost surface 325. However, even if imperfections are present on the outermost surface 325 of the molded base 320, such as protrusion 336 or voids 337 shown in FIG. 3C, the fluid-tight interface 388 eliminates or reduces any leaking that may otherwise occur due to the presence of the protrusion 336 and/or voids 337, in particular, when the protrusion 336 extends from the surface less than 0.003 inches.

FIG. 4A is a perspective view of an embodiment of a dispense tip 500 including an alignment foot 530 in accordance with aspects of the present invention. FIG. 4B is a cutaway side view of the dispense tip 500 of FIG. 4A. FIG. 4C is a front view of the dispense tip 500 of FIG. 4A. In this manner, when the foot 530 comes in contact with the substrate, the tip opening 514 is a known vertical distance from the substrate during a dispensing operation.

The dispense tip 500 illustrated in FIGS. 4A-4C comprises a neck 510, a base 520, and a vertical alignment foot 530, also referred to as a vertical alignment foot. The foot 530 is adapted and configured for reliable and accurate vertical positioning of the tip opening 514 over a substrate during dispensing of material.

The foot 530 may be formed of a number of materials, including heat-treated steel, carbide, plastic, ceramic, investment casting, injection molded materials, stainless steel, titanium, gems such as ruby, sapphire, and the like, or other materials known to those of ordinary skill in the art as having hardness properties, and may be press-fit or bonded into the base 520. The foot 530 may be formed to include a radiused end 533, to allow for contact with the substrate without damaging the substrate, for example, when applying a line of material to the substrate.

In an embodiment, the base 520 comprises a first portion 521 and a second portion 522, which can be formed in a manner that is similar to the molded dispense tip bases described herein with regard to FIGS. 1A, 1B, 2, 3A, 3B, 3C, and 3D. In an embodiment, the elements of the base 520 comprise materials similar to those used to form the dispense tip bases described above with regard to FIGS. 1A, 1B, 2, and 3A-3D, for example, a molded polyarylene sulfide, such as molded polyphenylene sulfide.

In an embodiment, the base 520 comprises two holes: a first hole 531 into which the neck 510 is inserted, and a second hole 532 into which the alignment foot 530 is inserted. The neck 510 is positioned in the first hole 525 and joined to the base 520 by press-fitting, bonding, or welding, or other applicable techniques.

The neck 510 is inserted into the first hole 531 of the base 520 to interface with a third hole 519 in the base 520 that extends from a funnel 541 at an outermost surface 525 of the base 520 to the neck 510 such that an unobstructed material path is formed from the funnel 541 through the hole 519 in the base 520, through a hole 529 in the neck, to the tip opening 514 at an opposite end of the neck 510.

In an embodiment, the base 520 comprises a third portion 528 that extends from a surface 527 of the base 520 opposite the outermost surface 525 of the base 520, wherein the second hole 532 are each formed in the third portion 528 of the base 520, and wherein the first hole 531 is formed

through the third portion of the base 528 to the first portion 521, or the second portion 522.

FIG. 5A is perspective view of an embodiment of a dispense tip 600 including multiple necks 610A-D coupled to a single base 620 in accordance with aspects of the present invention. FIG. 5B is a cutaway side view of the dispense tip 600 of FIG. 5A. FIG. 5C is a cutaway front view of the dispense tip 600 of FIG. 5A.

In the embodiment shown in FIGS. 5A-5C, a dispense tip 600 comprises four necks 610A-610D coupled to a base 620. However, alternative embodiments can include dispense tips having different numbers of necks, for example, two necks or six necks coupled to a same base.

In an embodiment, the base 620 comprises four holes or apertures 632 in a portion 628 of the base 620. Each of the holes 632 communicates with a larger hole 619 that extends through the base 620, which in turn communicates with a funnel 641 proximal to an outermost surface 625 at an end of the base 620 that interfaces with a dispensing pump. The first through fourth necks 610A-610D are joined to a base 620 by press-fitting, bonding, or welding, or other applicable techniques. Each neck 610A-610D includes a hole 629A-629D, respectively, having a single input end and a single output end. In this manner, a single material path is provided between the funnel 641 through the hole 619 and an elongated hole 629A-D to a corresponding outlet 614A-D at the output end of each neck 610A-D, respectively.

In an embodiment, the dispense tip 600 includes an alignment foot 630 that is parallel to the necks 610A-D to ensure rigidity and alignment of the dispense tip.

FIG. 6A is a perspective side view of an embodiment of a dispense tip 700 having a first portion 721 of a base 720 that is separate from a second portion 722 of the base 720, in accordance with aspects of the present invention. FIG. 6B is a perspective side view of the dispense tip 700 of FIG. 6A, wherein the first portion 721 and second portion 722 of the base 700 are coupled together, in accordance with aspects of the present invention.

In one approach, the neck 710 and first portion 721 of the base 720 can be unitary and machined from a common stock, for example, stainless steel, or molded from a common material, for example, ceramics. In another approach, the neck 710 and first portion 721 of the base 720 can be formed by different methods, and of different materials, for example, plastics. In some embodiments, the dispense tip 700 including the neck 710 and first portion 721 of the base 720 can be formed in accordance with other approaches described herein.

In other embodiments, the dispense tip having the neck 710 and the first portion 721 of the base shown in FIG. 6A can be similar to those dispense tips described with regard to U.S. Pat. Nos. 6,547,167, 6,981,664, 6,957,783, and U.S. patent application Ser. No. 12/034,313, filed Feb. 20, 2008, entitled "Material Dispense Tips and Methods for Manufacturing the Same," by Jeffrey P. Fugere, the contents of each of which are incorporated herein by reference in their entirety.

In an embodiment, the first portion 721 can have the same outer width, or can be of different dimensions, for example, different outer widths.

The second portion 722 of the base 720 comprises a material that is compliant relative to a surface hardness of a material dispensing pump to which the base 720 is coupled. The second portion 722 can comprise materials similar to those described above, for example, materials similar to or the same as those of base 220 of FIG. 1 described above, for example, molded polyarylene sulfide. Accordingly, the sec-

17

ond portion 722 can include properties, geometries, and features similar to those described above, and can comprise materials similar to or the same as those of base 220 of FIG. 1 described above.

The second portion 722 and first portion 721 can be coupled together by bonding or other applicable techniques. In an embodiment, the second portion 722 can be coupled to the first portion 721 by a bonding material, such as a suitable adhesive known to those of ordinary skill in the art.

As described above, embodiments of the present invention are directed to dispense tips that include a compliant molded base that provides a fluid-tight interface when abutting the surface of a material dispensing pump during a dispensing operation. In particular, portions of the compliant base fill the imperfections to form a fluid-tight interface between the base and the pump. Thus, regardless of viscosity or other characteristics of the material that is dispensed, the fluid-tight interface prevents the material, or elements of the material, such as solvents, from leaching that would otherwise occur due to imperfections in either the dispense tip or the pump surface.

While embodiments of the invention have been particularly shown and described above, it will be understood by those skilled in the art that various changes in form and detail may be made herein without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. A method of forming a dispense tip that communicates with a material dispensing pump comprising:
 - forming an elongated neck;
 - micromolding a material to form a base having an outermost compressible surface; and
 - coupling the base to the neck, wherein the base comprises an outermost region that includes a compressible fluid-tight surface that compliantly conforms to an outlet surface of the pump when the dispense tip is mounted to the pump.
2. The method of claim 1, wherein the material comprises polyarylene sulfide.
3. The method of claim 2, wherein the polyarylene sulfide is polyphenylene sulfide.
4. The method of claim 3, wherein the polyphenylene sulfide is linear and partially crystalline.
5. The method of claim 1, wherein the material has a low viscosity, such that the material conforms to the shape of a mold.
6. The method of claim 1, wherein the neck is formed of molded materials.
7. The method of claim 1, wherein the neck is formed of ceramics.
8. The method of claim 1, wherein the neck is machined from stainless steel.
9. The method of claim 1, wherein the base is coupled to the neck by bonding the base to the neck with a bonding material.
10. The method of claim 9, wherein the bonding material includes a two-part epoxy.

18

11. The method of claim 1 further comprising:
forming an elongated hole in the neck that extends from an input end of the neck to an output end of the neck;
and

forming an inner taper between the input end of the neck and the output end of the neck that transitions the input end to the output end.

12. The method of claim 11, wherein a portion of the elongated hole has an inner surface of a first inner diameter and the output end includes an outlet having an inner surface of a second inner diameter, the first inner diameter being greater than the second inner diameter.

13. The method of claim 1, wherein forming the base includes forming a funnel that delivers fluid to the neck, the funnel having a funnel inlet at an input end of the funnel and a funnel outlet at an output end of the funnel, wherein the neck communicates with the funnel outlet such that the dispense tip includes a single material path between the funnel outlet and an output end of the neck.

14. A dispense tip that communicates with a material dispensing pump, the dispense tip comprising an elongated neck, a base, and a material path between an outermost region of the base and an outlet of the neck; the dispense tip formed according to the process of:

molding a material having low viscosity to form a base;
and

coupling the base to the neck, wherein the outermost region of the base includes a compressible fluid-tight surface that compliantly conforms to an outlet surface of the pump when the dispense tip is mounted to the pump.

15. A dispense tip constructed and arranged to communicate with a material dispensing pump, the dispense tip comprising:

an elongated neck comprising stainless steel; and
a base having a first portion and a second portion opposite the first portion, the first portion comprising stainless steel, the second portion comprising a compressible fluid-tight interface that compliantly conforms to an outlet surface of the material dispensing pump when the dispense tip is mounted to the pump.

16. The dispense tip of claim 15, wherein the second portion of the base comprises polyarylene sulfide.

17. A dispense tip constructed and arranged to communicate with a material dispensing pump, the dispense tip comprising:

an elongated neck comprising ceramics;
a base having a compressible fluid-tight interface that compliantly conforms to an outlet surface of the material dispensing pump when the dispense tip is mounted to the pump; and

a bonding material that bonds the neck to the base.

18. The dispense tip of claim 17, wherein the base comprises polyarylene sulfide.

19. The dispense tip of claim 17, wherein the neck comprises an elongated hole that extends from an input end of the neck to an output end of the neck and an inner taper between the input end of the neck and the output end of the neck that transitions the input end to the output end.

* * * * *