

US010109687B2

(12) **United States Patent**
Miyamoto et al.

(10) **Patent No.:** **US 10,109,687 B2**
(45) **Date of Patent:** ***Oct. 23, 2018**

(54) **DISPLAY DEVICE WITH TOUCH SENSOR**

(71) Applicant: **Japan Display Inc.**, Minato-ku (JP)

(72) Inventors: **Mitsuhide Miyamoto**, Minato-ku (JP);
Hajime Akimoto, Minato-ku (JP)

(73) Assignee: **Japan Display Inc.**, Minato-ku (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/833,557**

(22) Filed: **Dec. 6, 2017**

(65) **Prior Publication Data**

US 2018/0097042 A1 Apr. 5, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/336,026, filed on Oct. 27, 2016, now Pat. No. 9,871,083.

(30) **Foreign Application Priority Data**

Jan. 15, 2016 (JP) 2016-006329

(51) **Int. Cl.**

H01L 51/50 (2006.01)

H01L 27/32 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **H01L 27/323** (2013.01); **G06F 3/044** (2013.01); **G06F 3/0412** (2013.01); **G06F 3/0416** (2013.01); **H01L 27/3211** (2013.01);

H01L 27/3246 (2013.01); **H01L 51/0097** (2013.01); **H01L 51/5012** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC **H01L 51/0545**; **H01L 51/0036**; **H01L 51/0541**; **H01L 51/5012**; **H01L 27/32**; **H01L 51/50**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,385,169 B2 7/2016 Chaji
9,425,434 B2 * 8/2016 Lee **H01L 51/5262**
(Continued)

FOREIGN PATENT DOCUMENTS

JP 2009-116090 5/2009
JP 2014-154450 8/2014


Primary Examiner — Quoc Hoang

(74) *Attorney, Agent, or Firm* — Oblon, McClelland, Maier & Neustadt, L.L.P.

(57) **ABSTRACT**

A sealing member containing conductive particles and disposed in a seal region is formed between a display panel and a touch panel. A laminated structure formed on the display panel includes a first detection lines. The first detection lines extend from the seal region to a connection region and are connected through the conductive particles to terminals of second detection lines formed on the touch panel. A peripheral edge of the organic barrier is located inward from the conductive particles of the sealing member. The above described structure can facilitate a work for connecting external lines such as FPC to the display panel and the touch panel. Further, the structure can secure stability of electrical connection between the external lines and the touch panel.

5 Claims, 9 Drawing Sheets



- (51) **Int. Cl.**
G06F 3/041 (2006.01)
G06F 3/044 (2006.01)
H01L 51/00 (2006.01)
H01L 51/52 (2006.01)
- (52) **U.S. Cl.**
CPC *H01L 51/5088* (2013.01); *H01L 51/5092*
(2013.01); *H01L 51/5246* (2013.01); *H01L*
51/5253 (2013.01); *G06F 2203/04102*
(2013.01); *Y02E 10/549* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,871,083	B2 *	1/2018	Miyamoto	H01L 27/323
2009/0115743	A1	5/2009	Oowaki		
2014/0225089	A1	8/2014	Kato et al.		
2016/0293685	A1	10/2016	Kato et al.		
2016/0293890	A1	10/2016	Kato et al.		

* cited by examiner

FIG. 1




FIG. 2.





FIG. 3



৩৫৬




FIG.5




FIG. 6





FIG. 7







FIG. 9



DISPLAY DEVICE WITH TOUCH SENSOR**CROSS-REFERENCE TO RELATED APPLICATION**

The present application is a continuation of U.S. application Ser. No. 15/336,026, filed Oct. 27, 2016 and claims priority from Japanese application JP2016-006329 filed on Jan. 15, 2016, the content of which is hereby incorporated by reference into this application.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates to a display device.

2. Description of the Related Art

Some liquid crystal display devices and some organic EL display devices include a touch panel to detect positions of user's fingers on the panel. A touch panel described in JP2009-116090A (hereinafter referred to as "Patent document 1") has a plurality of first detection electrodes and a plurality of second detection electrodes formed on one surface of the touch panel. The first detection electrodes are aligned in a longitudinal direction, and the second detection electrodes are aligned in a lateral direction. An edge of the touch panel (referred to as "front pad portion" in Patent Document 1) has terminals formed thereon that are respectively provided in detection lines extending from detection electrodes. An external flexible printed circuit (FPC) is attached to the terminals.

Display panels of organic EL display devices include an organic layer including a light emitting layer made of organic materials. The organic layer tends to be deteriorated under the influence of moisture. In order to prevent moisture from penetrating the organic layer, some organic EL display devices include a barrier layer covering the organic layer. JP2014-154450A discloses a barrier layer including two inorganic barrier layers between which an organic barrier is disposed.

SUMMARY OF THE INVENTION

Similarly to in the organic EL display device disclosed in patent document 1, in organic EL display device including a touch panel, external electric lines such as FPCs are connected to the display panel and the touch panel of the display device. However, the conventional structure has a problem that laborious works are necessary for connecting the external electric lines to the display panel and the touch panel, respectively.

The present invention is to provide a technology that facilitates works for connecting external electric lines such as FPCs to the display panel and the touch panel and that secures stability of electrical connection between the external electric line and the touch panel provided in a display device including a multilayer barrier covering the organic layer.

A display device comprising: a display panel including a display region; a touch panel facing the display panel; a seal region located outside the display region and surrounding the display region; and a connection region located outside a portion of a peripheral edge of the seal region. The display panel includes a first substrate and a first laminated structure formed on a surface of the first substrate facing the touch

panel. The touch panel includes a second substrate and a second laminated structure formed on a surface of the second substrate facing the display panel. The first laminated structure includes: an organic layer including a light emitting layer and formed on the display region; a multilayer barrier covering the whole of the organic layer and including a first inorganic barrier layer that includes an inorganic material, an organic barrier layer that includes an organic material and is formed on the first inorganic barrier layer, and a second inorganic barrier layer that includes an inorganic material and covers the whole of the organic barrier layer. The second laminated structure includes a circuit layer including a detection electrode and a second detection line that extends from the detection electrode and includes a terminal in the seal region. A sealing member is located in the seal region and disposed between the display panel and the touch panel, the sealing member containing a conductive particle. The first laminated structure includes a first detection line extending from the seal region to the connection region and electrically connected to the terminal of the second detection line through the conductive particle. The organic barrier layer includes a peripheral edge located inward from the conductive particle.

In the display device described above, the first detection line is formed on the display panel and thus the works for connecting external lines such as FPC to the display panel and the touch panel can be facilitated. Further, because the peripheral edge of the organic barrier layer is located inward from the conductive particle, stability of electrical connection between the external electric line and the touch panel can be secured.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an exemplary display device of embodiments according to the present invention.

FIG. 2 is a cross section taken along line II-II in FIG. 1.

FIG. 3 illustrates an exemplary circuit formed in a circuit layer of the display device.

FIG. 4 illustrates an exemplary conductor pattern formed in a circuit layer of a touch panel.

FIG. 5 is a cross section taken along line V-V indicated in FIG. 1.

FIG. 6 is a cross section illustrating a state where a connection region in the display panel is folded. The cross section plane of the FIG. 6 is the same as that of FIG. 5.

FIG. 7 is a plan view illustrating another exemplary display device of the embodiments according to the present invention.

FIG. 8 is a cross section taken along line VIII-VIII indicated in FIG. 7.

FIG. 9 is a cross section taken along line IX-IX indicated in FIG. 7.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, embodiments according to the present invention will be described. FIG. 1 illustrates a display device 1 that is an example of the embodiments according to the present invention. FIG. 2 is a cross section taken along line II-II in FIG. 1. FIG. 3 illustrates an exemplary circuit formed in a circuit layer 31 of the display panel 3. FIG. 4 illustrates an exemplary conductor pattern formed in a circuit layer 21 of a touch panel 2. FIG. 5 is a cross section taken along line V-V indicated in FIG. 1. FIG. 6 is a cross section illustrating a state where a connection region A3 in the display panel 3

3

is folded. The following explanation refers to a direction toward the touch panel 2 from the display panel 3 as “upward direction”, and refers to a direction toward the display panel 3 from the touch panel 2 as “downward direction”. Further, the following explanation refers to a direction toward the center of a display region described later as “inward direction”.

The present specification merely discloses an example. Thus, embodiments which maintain the spirit of the present invention and are easily modified by those skilled in the art are surely contained in the scope of the invention. In addition, a width, a thickness, and a shape of each portion shown in the drawings are merely an example. The width, the thickness, and the shape shown in the drawings do not limit the interpretation of the invention.

The organic electroluminescent (EL) display device 1 includes a display panel 3 and a touch panel 2 facing the display panel 3. As shown in FIG. 1, the display panel 3 and the touch panel 2 include a display region A1 constituted by a plurality of pixels, and include a seal region A2 located outside display region A1. The seal region A2 has a sealing member 52 (see FIG. 5) disposed therein. The sealing member 52 is formed between the display panel 3 and the touch panel 2 to adhere those panels to each other. The display panel 3 includes a connection region 3 located outside a portion of a peripheral edge (e.g., one side of the rectangularly shaped seal region A2) of the seal region A2. The touch panel 2 has a size correspond to the display region A1 and the seal region A2 each formed on the display panel 3. Accordingly, the touch panel 2 does not cover the connection region 3. The display panel 3 is rectangular, and the connection region A3 is located along one of the four sides of the rectangular display panel 3. The connection region 3 has an external electric line attached thereon. In the example described in the present specification, a flexible printed circuit (FPC) 65 is employed as the external electric line and attached on the connection region 3 (see FIG. 6). In this regard, a non-light emitting region in which pixels are not formed and the sealing member 52 is not provided may be secured between the display region A1 and the seal region A2 shown in FIG. 1. The non-light emitting region has, for example, a driver circuit formed thereon.

As shown in FIG. 2, the display panel 3 includes a first substrate 30. The first substrate 30 is made of resin, such as polyimide resin, and has flexibility. As described later, the flexibility allows the connection region A3 of the display panel 3 to be folded opposite the touch panel 2 (see FIG. 6).

The first substrate 30 includes a surface facing the touch panel 2. The display panel 3 includes a laminated structure on the surface of the first substrate 30. The laminated structure of the display pane 13 is formed between the first substrate 30 and a filler 51 shown in FIG. 2. The following explanation refers to the laminated structure as “first laminated structure”.

As shown in FIG. 2, the first laminated structure includes an organic layer 33 including a light emitting layer. The organic layer 33 may further include a hole injection layer, a hole transmission layer, an electron injection layer, and an electron transmission layer. In the example of organic EL display device 1, the organic layer 33 has a common laminated structure throughout the region of pixels so that the entire organic layer 33 emits light of the same color (e.g., white light). In another example, the organic layer 33 may have a laminated structure of the pixels that correspond to the respective colors so as to emit light of colors of the respective pixels. For example, the organic layer 33 in the red pixel Pr may be formed so as to emit red light, the

4

organic layer 33 in the green pixel Pg may be formed so as to emit green light, and the organic layer 33 in the blue pixel Pb may be formed so as to emit blue light.

As shown in FIG. 2, the first laminated structure includes a plurality of lower electrodes 32 respectively formed on the plurality of pixels. Further, the first laminated structure includes a bank layer 35. The bank layer 35 has banks 35a formed therein. Each bank 35 is located between two adjacent pixels and disposed on the peripheral portion of the lower electrode 32. The organic layer 33 is formed on the lower electrodes 32 and the bank layer 35. The organic layer 33 has a portion that is located inside the banks 35 and is in contact with the lower electrode 32. An upper electrode 34 is formed on the organic layer 33. In an example, the upper electrode 34 is continuously formed throughout the display region A1. The lower electrode 32 and the upper electrode 34 supply electric charges (that is, electric current) to the organic layer 33. For example, the lower electrode 32 is an anode to supply holes to the organic layer 33. The upper electrode 34 is a cathode to supply electrons to the organic layer 33.

As shown in FIG. 2, the first laminated structure includes a circuit layer 31 formed on the first substrate 30. The lower electrodes 32 are formed above the circuit layer 31. The circuit layer 31 has circuits formed therein that control electric current to be supplied to the lower electrodes 32.

As shown in FIG. 3, the circuit layer 31 includes a pixel circuit 31A formed in each pixel. The pixel circuit 31A includes a plurality of TFTs (Thin Film Transistor) 31a, 31b, capacitor 31c, and the like. Further, the circuit layer 31 has scan signal lines 31B extending in an X direction, image data signal lines 31C extending in a Y direction, and drive power source lines 31D extending in the Y direction. The scan signal lines 31B are respectively formed for pixel rows that are arranged in the Y direction. The image data signal lines 31C are respectively formed for pixel lines that are arranged in the X direction. The scan signal lines 31B are selected in order by a scan signal line drive circuit (not shown). The selected scan signal line 31B receives a voltage for turning on a switching TFT 31a formed in each pixel. The image data signal line 31c receives a voltage corresponding to a data signal for a pixel that is connected to the selected scan signal line 31B. The voltage is applied to the capacitor 31c through the switching TFT 31a. A drive TFT 31b supplies OLED 3a with an electric current corresponding to the voltage applied to the capacitor 31c. As a result, the OLED 3a in the pixel connected to the selected scan signal line 31B emits a light. The lower electrodes 32, the organic layer 33, and the upper electrode 34 constitute the OLEDs 3a. The electric current is supplied to the OLED 3a through the drive power source line 31D and the drive TFT 31b. The anode of the OLED 3a (lower electrode 32) is connected to the drive TFT 31b. The cathode of the OLED 3a is connected to the ground potential. The cathodes of all OLEDs 3a employ a common electrode (that is, the upper electrode 34). In this regard, the pixel circuit 31A is not limited to the example shown in FIG. 3 and may be changed in various ways.

As shown in FIG. 1, the connection region A3 of the display panel 3 has a plurality of first terminals 31e formed thereon and a plurality of second terminals 31f formed thereon. The first terminals 31e are provided for the circuits formed in the circuit layer 31. In an example, a driver IC 62 is mounted on the connection region A3. The circuit layer 31 has a plurality of lines (not shown) formed therein that connect the driver IC 62 to the first terminals 31e. Further, the circuit layer 31 has a plurality of lines (not shown)

5

formed therein that connect the driver IC 62 to the scan signal lines 31B, the image data signal lines 31C, and the drive power resource lines 31D. On the other hand, the second terminals 31f are provided at the ends of the detection lines electrically connected to the touch panel 2 (hereinafter, the detection line 61 is referred to as “first detection line”). As shown in FIG. 5, the peripheral edges of the terminals 31e and 31f may be covered with the bank layer 35, which prevents the terminals 31e and 31f from being peeling off. Alternatively, the peripheral edges of the terminals 31e and 31f are covered with inorganic barrier layers 41 and 43 described later.

The first terminals 31e are connected with external lines that supply the display panel 3 with signals to drive the display panel 3. The second terminals 31f are connected with external lines that transmit signals from the touch panel 2 to an external controller. In the example of organic EL display device 1, FPC 65 (shown in FIG. 6) is employed as both of the external lines connected to the first terminals 31e and the external lines connected to the second terminals 31f.

For example, as shown in FIG. 1, all of the second terminals 31f are arranged on one side of the plurality of first terminals 31e. The arrangement of the second terminals 31f is not limited to the example shown in FIG. 1. In another example, the second terminals 31f may be distributed on two sides of the plurality of first terminals 31e.

As shown in FIG. 2, the first laminated structure includes a multilayer barrier 40 that prevents moisture from penetrating and spreading in the organic layer 33. The multilayer barrier 40 is formed on the upper electrode 34 to cover the entire organic layer 33. In other words, the multilayer barrier 40 includes a peripheral edge located outside the peripheral edge of the organic layer 33. The multilayer barrier 40 includes a first inorganic barrier layer 41, an organic barrier 42 formed on the first inorganic barrier layer 41, and a second inorganic barrier layer 43 formed on the organic barrier 42. That is, the organic barrier 42 is sandwiched between the first inorganic barrier layer 41 and the second inorganic barrier layer 43. The first inorganic barrier layer 41 and the second inorganic barrier layer 43 are made of an inorganic material. Examples of the inorganic material are silicone nitride (Sin), silicone oxide (Sio), and the like. The first inorganic barrier layer 41 and the second inorganic barrier layer 43 may be made of the same material, or may be made of different materials from one another. Each of the first inorganic barrier layer 41 and the second inorganic barrier layer 43 may include a plurality of layers. The organic barrier 42 is made of an organic material. The material of the organic barrier 42 is, for example, an acrylic resin, a polyimide resin, an epoxy resin. When a foreign particle invades the upper electrode 34 or the first inorganic barrier layer 41, for example, the organic barrier 42 covers and encloses the foreign particle so that the barrier efficiency can be prevented from being deteriorated due to the foreign particle. The second inorganic barrier layer 43 covers the entire organic barrier 42. In a plan view of the display panel 3 (see FIG. 5), the peripheral portion 41a of the first inorganic barrier layer 41 and the peripheral portion 43a of the second inorganic barrier layer 43 are located outside the peripheral edge 42a of the organic barrier 42. The peripheral portion 41a of the first inorganic barrier layer 41 and the peripheral portion 43a of the second inorganic barrier layer 43 are in contact with each other and have the organic barrier formed inside the peripheral portions 41a and 43a. The structure described here can prevent moisture from penetrating and spreading in the organic barrier 42. The organic

6

barrier in an example has thickness larger than that of the inorganic barrier layers 41 and 43.

As shown in FIG. 2, the touch panel 2 includes a second substrate 20. The second substrate 20 may employ a glass substrate or a resin substrate, such as an acrylic substrate. The second substrate 20 includes a surface facing the display panel 3. The touch panel 2 includes a laminated structure formed on the surface of the second substrate 20. The laminated structure of the touch panel 2 is layers formed between the second substrate 20 and the filler 51 shown in FIG. 2. Hereinafter, the laminated structure is referred to as “second laminated structure”. The second laminated structure includes a circuit layer 21.

As shown in FIG. 4, the circuit layer 21 includes a conductor pattern that includes a plurality of first detection electrodes 21A each extending in the X direction and a plurality of second detection electrodes 21B each extending in the Y direction. The first detection electrodes 21A are arranged in the Y direction. The second detection electrodes 21B are arranged in the X direction. In an example of the circuit layer 21, each of the first detection electrodes 21A includes a plurality of square portions 21c arranged in the X direction and connecting portions 21d each coupling two adjacent square portions 21c together. Similarly to the first detection electrodes 21A, each of the second detection electrodes 21B includes a plurality of square portions 21c arranged in the Y direction and connecting portions 21d each coupling two adjacent square portions 21c together. The connecting portion 21d of the first detection electrode 21A and the connecting portion 21d of the second detection electrode 21B cross and have an insulating layer formed therebetween. The touch panel 2 works as a capacitive touch sensor by using the detection electrodes 21A and 21B described above.

The conductor pattern of the circuit layer 21 includes a plurality of detection lines 21C respectively extending from ends of detection electrodes 21A and 21B (hereinafter, the detection line 21C is referred to as “second detection line”). The second detection lines 21C are formed along edges of the touch panel 2. Each of the sensor detection lines 21C includes terminal 21Ca at the end thereof. The detection electrodes 21A and 21B of the circuit layer 21 are made of a transparent conductive material such as Indium Tin Oxide (ITO), Indium Zinc Oxide (IZO), and the like. The second detection lines 21C may be made of a transparent conductive material or a metal.

As shown in FIG. 2, the second laminated structure may include a protection insulating layer 22 covering the circuit layer 21. Further, the second laminated structure may include a color filter layer 23 formed on the lower side of the protection insulating layer 22. The color filter layer 23 has color filters 23r, 23g, and 23b formed therein that each have the color of the pixel.

As described above, the second detection lines 21C are formed along the edges of the touch panel 2. As shown in FIGS. 4 and 5, each second detection line 21C includes a terminal 21Ca in the end thereof. The terminal 21Ca is located in the seal region A2. The seal region A2 in a plan view is shaped in a frame surrounding the display region A1. The seal region A2 includes a portion A2s (see FIG. 4) located close to the connection region A3 of the display panel 3 (hereinafter, the portion A2s is referred to as “connection side seal region”). The terminals 21Ca of the plurality of second detection lines 21C are formed in the connection side seal region A2s. In an example of organic EL display device 1, all terminals 21Ca are located in one side of the connection side seal region A2s (in FIG. 4, all

terminals **21Ca** are arranged close to an edge **20b** of the second substrate **20**). The positions of the terminals **21Ca** are not limited to those described here. For example, the plurality of terminals **21Ca** may be located on both sides of the connection side seal region **A2s**.

As shown in FIG. 5, the seal region **A2** has a sealing member **52** disposed therein. The sealing member **52** is disposed between the display panel **3** and the touch panel **2** to bond the display panel **3** and the touch panel **2** together. The display panel **3** and the touch panel **2** have a filler **51** disposed therein. The filler **51** is located inside the seal region **A2** and the sealing member **52** seals a space filled with the filler **51**.

As shown in FIG. 5, the first laminated structure of the display panel **3** includes a plurality of first detection lines **61**. The first detection lines **61** extend to the connection region **A3** from the connection side seal region **A2s**. Each first detection line **61** includes a portion **61a** formed in the connection side seal region **A2s** (hereinafter, the portion **61a** is referred to as “contact portion”). The first detection line **61** extends to the second terminal **31f** in the connection region **A3** from the contact portion **61a**. In the example in FIG. 1, each first detection line **61** extends straight in the y direction. The first detection lines **61** are made of a metal that includes, for example, **A1**, **Ag**, and the like. The arrangement and the material of the first detection line **61** are not limited to the example described here and may be changed in various ways.

As shown in FIG. 5, the contact portions **61a** of the first detection lines **61** respectively face the terminals **21Ca** of the second detection lines **21C** formed in the touch panel **2** in a thickness direction of the panels **2** and **3** across the sealing member **52**. The contact portions **61a** of the first detection lines **61** are formed in the first laminated structure and exposed toward the sealing member **52**. The terminals **21Ca** of the second detection lines **21C** are formed in the second laminated structure and exposed toward the sealing member **52**. The sealing member **52** includes conductive particles **53** made of conductive material. The contact portions **61a** of the first detection lines **61** are electrically connected with the terminals **21Ca** of the second detection lines **21C**, respectively, through the conductive particles **53**. In other words, each contact portion **61a** of the first detection line **61** is in contact with the conductive particle **53**, and each terminal **21Ca** of the second detection line **21C** is in contact with the conductive particle **53**. The first detection lines **61** enable a FPC for the touch panel **2** to be attached on the connection region **A3** of the display panel **3**, not on the touch panel **2**. Accordingly, workability for attaching the FPC to the display device **1** can be facilitated.

The conductive particle **53** has a diameter that corresponds to the distance between the touch panel **2** and the display panel **3**, for example. In more detail, the conductive particle **53** has a diameter that corresponds to the distance between the contact portion **61a** of the first detection line **61** and the terminal **21Ca** of the second detection line **21C**. The diameter enables the contact portion **61a** of the first detection line **61** and the terminal **21Ca** of the second detection line **21C** to be in contact with a common conductive particle **53**. Further, the conductive particle **53** can function as a spacer. The diameter of the conductive particle **53** is preferably larger than the thickness of the multilayer barrier **40**. Such a larger diameter enables the contact pressure between the conductive particle **53** and the second detection line **21C** and the contact pressure between the conductive particle **53** and the first detection line **61** to be adequately secured. The diameter of the conductive particle **53** is not limited to the

example described here. For example, the diameter of the conductive particle **53** may be smaller than the distance between the contact portion **61a** of the first detection line **61** and the terminal **21Ca** of the second detection line **21C**. In that case, the contact portion **61a** and the terminal **21Ca** may be connected with each other through a plurality of conductive particles **53**.

As shown in FIG. 5, the peripheral edge **42a** of the organic barrier **42** is located inward from the conductive particles **53** contained in the sealing member **52**. In other words, the peripheral edge **42a** of the organic barrier **42** is located closer to the display region **A1** than the conductive particles **53**. In an example where a non-light emitting region is formed between the display region **A1** and the seal region **A2**, the peripheral edge **42a** of the organic barrier **42** may be located in the non-light emitting region. The organic barrier **42** is relatively soft, because it is made of an organic material. Accordingly, in comparison with a structure where the conductive particles **53** are located above the organic barrier **42**, the structure shown in FIG. 5 where the peripheral edge **42a** of the organic barrier **42** is located inward from the conductive particles **53** easily secures adequate contact pressures between the conductive particle **53** and the contact portion **61a** of the first detection line **61** and between the conductive particle **53** and the terminal **21Ca** of the second detection line **21C**. As a result, the electrical connection between them can be improved in the stability. In an example, a plurality of conductive particles **53** may be arranged in the width direction (E direction shown in FIG. 5) of the connection side seal region **A2s**. In this example, the plurality of conductive particles **53** make an electrical connection between the contact portion **61a** of the first detection line **61** and the terminal **21Ca** of the second detection line **21C**. In this example, the peripheral edge **42a** of the organic barrier **42** is preferably located inward from the conductive particle **53** disposed innermost among the plurality of conductive particles (that is, the peripheral edge **42a** is preferably located inward from the conductive particle **53** disposed closest to the display region **A1** among the plurality of conductive particles **53**).

In the example of organic EL display device **1**, the peripheral edge **42a** of the organic barrier **42** is located inward from a portion of the seal region **A2** in which the conductive particle **53** is disposed. That is, the peripheral edge **42a** of the organic barrier **42** is located inward from the inner edge of the connection side seal region **A2s**. That is, the peripheral edge **42a** of the organic barrier **42** is located closer to the display region **A1** than the inner edge of the connection side seal region **A2s**. The arrangement of the organic barrier **42** described here can secure a further adequate contact pressure between the conductive particle **53** and the contact portion **61a** of the first detection line **61** and a further adequate contact pressure between the conductive particle **53** and the terminal **21Ca** of the second detection line **21C**. The entire peripheral edge **42a** of the organic barrier **42** may be located inward from the seal region **A2**. That is, the peripheral edge **42a** of the organic barrier **42** may be located inward from, not only the inner edge of the connection side seal region **A2s**, but also inner edges of other portions of the seal region **A2**.

As shown in FIG. 5, each of the first inorganic barrier layer **41** and the second inorganic barrier layer **43** includes a portion located in the seal region **A2**. The portions of the first inorganic barrier layer **41** and of the second inorganic barrier layer **43** are in contact with each other. The portions described here enable the organic barrier **42** to be surely enclosed by the first inorganic barrier layer **41** and the

second inorganic barrier layer **43**, even when the peripheral edge **42a** is positioned closer to the seal region **A2**. Accordingly, moisture is surely prevented from penetrating into the organic barrier **42**. In the example of organic EL display device **1**, the peripheral portion **41a** of the first inorganic barrier layer **41** and the peripheral portion **43a** of the second inorganic barrier layer **43** are located in the seal region **A2** and in contact with each other. Alternatively, only one of the peripheral portion **41a** of the first inorganic barrier layer **41** and the peripheral portion **43a** of the second inorganic barrier layer **43** may be located in the seal region **A2**. For example, only the peripheral portion **43a** of the second inorganic barrier layer **43** may be located on the seal region **A2**.

As shown in FIG. 5, in the example of organic EL display device **1**, the inorganic barrier layers **41** and **43** are formed in the display region **A1** and the seal region **A2**, while not formed in the connection region **A3**. The peripheral edges of the inorganic barrier layers **41** and **43** are located inward from the peripheral edge of the seal region **A2**. As described later, the connection region **A3** of the display panel **3** is folded back (see FIG. 6). In comparison with a structure where the inorganic barrier layers **41** and **43** are formed in the connection region **A3**, the structure shown in FIG. 5 where the inorganic barrier layers **41** and **43** are not formed in the connection region **A3** reduces the rigidity of the connection region **A3** of the display panel **3** to facilitate folding the connection region **A3**. The inorganic barrier layers **41** and **43** can be formed by, for example, using a mask. For example, the inorganic barrier layers **41** and **43** can be formed by a mask to block a material of the inorganic barrier layers **41** and **43** from being put on the connection region **A3**. The inorganic barrier layers **41** and **43** can be formed, for example, by Chemical Vapor Deposition (CVD). Alternatively, the inorganic barrier layers **41** and **43** may be formed on the connection region **A3**, while not covering the second terminals **31f**. In that case, the inorganic barrier layers **41** and **43** can be formed by using a mask to block the material of the inorganic barrier layers **41** and **43** from being put on the second terminal **31f**.

As shown in FIG. 5, the circuit layer **31** includes a portion located in the connection region **A3**. The portion of the circuit layer **31** has a plurality of lines (not shown) formed therein that connects the driver IC **62** to the plurality of first terminals **31e** (see FIG. 1). Further, the portion of the circuit layer **31** has a plurality of lines (not shown) formed therein that connects the driver IC **62** to the scan signal lines **31B**, the image data signal lines **31C**, the driver circuit, and the drive power resource lines **31D**. The first laminated structure of the display panel **3** includes an insulating layer formed in the connection region **A3** and covering the circuit layer **31**. The first detection lines **61** are formed above the insulating layer. The structure described here enables the plurality of lines in the circuit layer **31** to be formed under the first detection lines **61**. Accordingly, the structure described here increases the flexibility in the layout of the plurality of lines. In the example of organic EL display device **1**, the bank layer **35** is formed as the above described insulating layer between the first detection line **61** and the circuit layer **31**. In comparison with a structure where a dedicated insulating layer insulates the detection lines **61** from the circuit layer **31**, the structure described above can reduce the number of manufacturing processes.

As shown in FIG. 5, the peripheral portions **41a** and **43a** of the inorganic barrier layers **41** and **43** are formed on the bank layer **35**. The contact portions **61a** of the first detection line **61** are formed on the peripheral portions **41a** and **43a** of

the inorganic barrier layers **41** and **43**. Alternatively, only one of the peripheral portions **41a** and **43a** of the inorganic barrier layers **41** and **43** may be formed on the bank layer **35**. The bank layer **35** includes a split portion (a groove portion) **35b** in the seal region **A2**. The slit portion **35b** is formed along the entire periphery of the seal region **A2**. The split portion **35b** can prevent moisture from spreading in the bank layer **35**. The contact portions **61a** of the first detection lines **61** are located above the slit portion **35b**.

As described above, the plurality of second terminals **31f** are formed in the connection region **A3**. The plurality of second terminals **31f** are connected with the ends of the plurality of first detection lines **61**, respectively. The second terminals **31f** are formed in the same layer as the first terminals **31e**. For example, both of the first terminals **31e** and the second terminals **31f** are formed in the conductive layer in which the circuits in circuit layer **31** are formed. The structure described here evens the height of the second terminals **31f** and the height of the first terminals **31e**, and thus enables the common FPC **65** to be stably attached on the first terminals **31e** and the second terminals **31f**. Specifically, a pressure applied on the second terminals **31f** from the FPC **65** and a pressure applied on the first terminals **31e** from the FPC **65** can be equalized in a manufacturing process where the FPC **65** is pressed on the connection region **A3** of the display panel **3**. The FPC **65** is bonded to the display panel **3** by, for example, aerotropic conductive adhesive. The ends of the second terminals **31f** toward the seal region **A2** are in contact with the ends of the first detection lines **61**.

As shown in FIG. 1, in the example of organic EL display device **1**, the plurality of first terminals **31e** and the plurality of second terminals **31f** on the ends of the first detection lines **61** are arrayed in one direction. The arrangement of the terminals **31f** and **31e** described here can facilitate work for pressing the FPC **65** to the first terminals **31e** and the second terminals **31f**.

The organic EL display device **1** can be manufactured by the processes exemplified as follows. The circuit layer **31** and the lower electrodes **32** are formed on the first substrate **30**. Then, the bank layer **35** is formed so as to cover the peripheral portions of the lower electrodes **32**. In the process, the bank layer **35** is formed not to cover the first terminals **31e** and the second terminals **31f**. After that, the organic layer **33** and the upper electrode **34** are formed. Then, the inorganic barrier layer **41**, the organic barrier **42**, and the second inorganic barrier layer **43** are formed on the upper electrode **34** in the order of the layer **41**, the barrier **42**, and the layer **43**. As described above, the inorganic barrier layers **41** and **43** are formed by using a mask so that the material thereof does not cover the connection region **A3** (or terminals **31e, 31f**). As described above, the peripheral edge **42a** of the organic barrier **42** is located inward from the seal region **A2**. Such an organic barrier **42** can be made by using a mask having an opening inside the seal region **A2**. For example, the organic barrier **42** can be formed by vapor deposition. Alternatively, the organic barrier **42** may be formed by printing. After forming the second inorganic barrier layer **43**, the first detection lines **61** are formed on the inorganic barrier layers **41** and **43**. The first detection lines **61** can be formed by, for example, ink-jet printing, offset printing, and photolithography process. After the first detection lines **61** are formed, the touch panel **2** is attached on the display panel **3**. At that time, the sealing member **52** is disposed on the seal region **A2**, and the space between the display panel **3** and the touch panel **2** is filled with the filler **51**.

11

As described above, the first substrate **30** is made of resin and has flexibility. Accordingly, the peripheral portion of the display panel **3** can be bent, or the portion in the connection region **A3** can be folded. As a result, leeway in designing the organic EL display device **1** can be increased.

In the present embodiment, as shown in FIG. 6, the connection region **A3** of the display panel **3** is folded opposite to the touch panel **2** (hereinafter, the folded portion is referred as to “folded portion D”). The folded portion D enables to reduce the width of the peripheral portion of the organic EL display device **1**. As described above, the second detection lines **21C** of the touch panel **2** are connected to the first detection lines **61** through the conductive particles **53** contained in the sealing member **52**. Accordingly, the touch panel **2** does not need to include a region to be attached to external lines such as FPC. Therefore, the size of the touch panel **2** can be reduced by the unnecessary region, and the peripheral portion of the organic EL display device **1** can be reduced in the width.

As shown in FIG. 6, a spacer **71** is disposed between the folded portion D and the rest portion of the display panel **3** (that is, the spacer **71** is disposed between the folded portion D and a portion facing the folded portion D). The spacer **71** includes a peripheral surface **71a** that curves like an arc. The folded portion D is folded along the peripheral surface **71a**.

The spacer **71** is disposed below the connection side seal region **A2s**. A portion of the spacer **71** is located opposite to the conductive particles **53** contained in the sealing member **52** across the display panel **3**. Such an arrangement of the spacer can reduce a stress caused in the connection side seal region **A2s** when the connection region **A3** of the display panel **3** is folded back. For example, when the spacer **71** is pressed on the back surface of the first substrate **30** and then the connection region **A3** of the display panel **3** is folded back, a stress caused in the connection side seal region **A2s** can be reduced. As a result, it is prevented that the contacts between the second detection lines **21C** and the conductive particles **53** and the contacts between the first detection lines **61C** and the conductive particles **53** are unstable.

As shown in FIG. 6, a portion of the spacer **71** is preferably also located between a portion including the terminals **31e** and **31f** to be connected with the FPC **65** and the back surface of the display panel **3**. The arrangement of the spacer **71** described here enables the positions of the terminals **31e** and **31f** to be fixed and thus improves the connection stability between the terminals **31e** and **31f** and the FPC **65**.

The spacer **71** may not be located on the entire display panel **3**. For example, as shown in FIG. 6, the spacer **71** may be located only on the folded portion D of the display panel **3**. This arrangement can secure a space under the display panel **3** and thus enables the space to be used for parts of an electric device equipping with the organic EL display device **1**.

In the example of organic EL display device **1**, the spacer **71** has a thickness larger than that of the first substrate **30**. The spacer **71** is made of a resin, such as an acrylic resin. The thickness and the material of the spacer **71** are not limited to the examples described here.

FIGS. 7 to 9 show an organic EL display device **100** that is another example of embodiments according to the present invention. FIG. 7 is a plan view of the organic EL display device **100**. FIG. 8 is a cross section taken along line VIII-VIII indicated in FIG. 7. FIG. 9 is a cross section taken along line IX-IX indicated in FIG. 7. In the following description, portions and matters different from those of the organic EL display device **1** will be mainly explained. The

12

elements of the organic EL display device **100** that are not explained below are the same as those of the organic EL display device **1**.

In the organic EL display device **100**, second terminals **161b** are provided instead of the second terminals **31f** described above on the ends of the first detection lines **161**. The first detection lines **161** are formed on the first inorganic barrier layer **41** and the second inorganic barrier layer **43**. As shown in FIGS. 8 and 9, the second terminals **161b** are formed in the same layer as the first detection lines **161** unlike the second terminals **31f**. That is, the second terminals **161b** are formed on the first inorganic barrier layer **41** and the second inorganic barrier layer **43**, and made of the same material as that of the first detection lines **61**. The structure described here enables the second terminals **161b** to be made in the same process as that of the first detection lines **161**.

As shown in FIG. 7, the plurality of first terminals **31e** and the plurality of second terminals **161b** are arrayed in one line. The distance between the first terminals **31e** and the second terminals **161b**, that is, the distance **L1** between the first terminal **31e** closest to the second terminals **161b** and the second terminal **161b** closest to the first terminals **31e** is larger than the distance between two adjacent first terminals **31e**. The larger distance can stabilize the connections between the first terminals **31e** and FPC **65** and the connections between the second terminals **161b** and FPC **65**. In more detail, the second terminals **161b** are formed on the inorganic barrier layers **41** and **43** and thus are positioned higher than the first terminals **31e**. Accordingly, in a process in which the FPC **65** is pressed on the connection region **A3**, the FPC **65** may not be equally pressed on the terminals **31e** and **161b**. As shown in FIG. 7, the structure where the distance **L1** between the first terminals **31e** and the second terminals **161b** is larger than the distance between two adjacent first terminals **31e** can reduce the unevenness of the pressures applied to the terminals **31e** and **161b** from the FPC **65**.

The organic EL display device **100** can be manufactured by the processes exemplified as follows. The circuit layer **31** and the lower electrodes **32** are formed on the first substrate **30**. Then, the bank layer **35** is formed so as to cover the peripheral portions of the lower electrodes **32**. At the time, the bank layer **35** is formed not to cover the first terminals **31e**. After that, the organic layer **33** and the upper electrode are formed. Then, the inorganic barrier layer **41**, the organic barrier **42**, and the second inorganic barrier layer **43** are formed on the upper electrode **34** in the order of the layer **41**, the barrier **42**, and the layer **43**. For the organic EL display device **100**, unlike for the organic EL display device **1**, the inorganic barrier layers **41** and **43** are formed throughout the entire the display panel **3** without a mask. Then, the first detection lines **61** are formed on the inorganic barrier layers **41** and **43** by ink-jet printing, offset printing, photolithography process, and the like. After that, the touch panel **2** is attached on the display panel **3**. At that time, the sealing member **52** is disposed on the seal region **A2**, and the space between the display panel **3** and the touch panel **2** fills with the filler **51**. Finally, the inorganic barrier layers **41** and **43** are removed from the connection region **A3**. For example, the inorganic barrier layers **41** and **43** are removed by ashing process. In the ashing process, the touch panel **2**, the first detection lines **161** and the second terminals **161b** works as a mask, and thus a mask dedicated for the ashing is not necessary.

The present invention is not limited to the embodiments described above and may be changed in various ways. For example, the following variation can be made.

13

The peripheral edge **42a** of the organic barrier **42** may be located inward from the seal region **A2s** only on one side toward the connection region **A3** among the four sides of the seal region **A2**. That is, the peripheral edge **42a** of the organic barrier **42** may be located outward from the inner edge of the seal region **A2** on the rest three sides of the seal region **A2**.

When a plurality of conductive particles **53** are arranged in the width direction (E direction shown in FIG. 5) of the connection side seal region **A2s**, the peripheral edge **42a** of the organic barrier **42** may be located inward from the conductive particle **53** disposed outermost among the plurality of conductive particles **53** (that is, the peripheral edge **42a** may be located inward from the conductive particle **53** disposed closest to the connection region **A3**), and the other conductive particles **53** may be disposed above the organic barrier **42**.

While there have been described what are at present considered to be certain embodiments of the invention, it will be understood that various modifications may be made thereto, and it is intended that the appended claims cover all such modifications as fall within the true spirit and scope of the invention.

What is claimed is:

1. A display device comprising:

a flexible substrate, the flexible substrate having a display region including a plurality of pixels;

a multilayer barrier covering the plurality of pixels;

a plurality of detection electrodes arranged so as to overlap the display region;

a terminal on the flexible substrate, the terminal located along an edge of the flexible substrate;

a first detection line on the flexible substrate, the first detection line connected to the terminal; and

a second detection line connected to one of the plurality of detection electrodes,

the multilayer barrier comprises:

14

a first region covering the plurality of pixels, the first region having a first inorganic barrier layer, a second inorganic barrier layer, and an organic barrier layer between the first and the second inorganic barrier layer; and

a second region surrounding the first region, the second region having the first inorganic barrier layer and the second inorganic barrier layer being in contact with the first inorganic barrier layer, wherein

the first detection line and the second detection line are connected each other at a region where overlaps the second region,

the second detection line intersects a peripheral edge of the organic barrier layer,

the flexible substrate has a bent portion between the display region and the terminal, and

the first detection line intersects the bent portion.

2. The display device according to claim 1, wherein

the peripheral edge of the organic barrier layer is between the display region and the region where the first detection line and the second detection line are connected, and

the bent portion is between the edge of the flexible substrate and the region where the first detection line and the second detection line are connected.

3. The display device according to claim 1, wherein

the first detection line and the second detection line are connected via conductive particles.

4. The display device according to claim 1, wherein

the flexible substrate is folded back via the bent portion, and

the terminal is at an opposite side of the display region.

5. The display device according to claim 1 further comprising a seal region surrounding the display region, wherein the region where the first detection line and the second detection line are connected overlaps with the seal region.

* * * * *