



US010117651B2

(12) **United States Patent**
Whitman et al.

(10) **Patent No.:** **US 10,117,651 B2**
(45) **Date of Patent:** ***Nov. 6, 2018**

(54) **SURGICAL DEVICE HAVING A ROTATABLE JAW PORTION**

(71) Applicant: **Covidien LP**, Mansfield, MA (US)

(72) Inventors: **Michael P. Whitman**, New Hope, PA (US); **Peter Daticuk**, Quakerstown, PA (US); **Donald Malinouskas**, Monroe, CT (US); **David Nicholas**, Trumbull, CT (US)

(73) Assignee: **Covidien LP**, Mansfield, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 201 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/947,267**

(22) Filed: **Nov. 20, 2015**

(65) **Prior Publication Data**
US 2016/0074035 A1 Mar. 17, 2016

Related U.S. Application Data

(63) Continuation of application No. 13/731,451, filed on Dec. 31, 2012, now Pat. No. 9,204,877, which is a (Continued)

(51) **Int. Cl.**
A61B 17/04 (2006.01)
A61B 17/10 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 17/068** (2013.01); **A61B 17/07207** (2013.01); **A61B 2017/00398** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 17/068; A61B 17/07207; A61B 2017/07271; A61B 2017/00539

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,881,706 A 2/1931 Larsen
1,798,902 A 3/1931 Raney
(Continued)

FOREIGN PATENT DOCUMENTS

DE 2330182 A1 1/1975
DE 2903159 A1 7/1980
(Continued)

OTHER PUBLICATIONS

Extended European Search Report corresponding to counterpart Int'l Appl. No. EP 16178984.7 dated Oct. 7, 2016.



(Continued)

Primary Examiner — Robert Long

(57) **ABSTRACT**

A surgical device is provided that includes a jaw portion, having a first jaw in opposed correspondence with a second jaw, the second jaw including a surgical member. The surgical device may include a shaft portion coupled to a proximal end of the jaw portion and at least one motor configured to rotate the jaw portion relative to the shaft portion, to move the jaw portion relative to the shaft portion, move the first jaw relative to the second jaw and move the surgical member within the second jaw. The surgical member may be prevented from moving within the second jaw unless the first jaw is in a closed position relative to the second jaw. Advantageously, the surgical member may include one or both a cutting element or a stapling element, disposed within one of the jaws.

18 Claims, 39 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/162,811, filed on Jun. 17, 2011, now Pat. No. 8,353,440, which is a continuation of application No. 13/027,292, filed on Feb. 15, 2011, now Pat. No. 7,992,758, which is a continuation of application No. 12/235,386, filed on Sep. 22, 2008, now Pat. No. 7,918,230.

(60) Provisional application No. 60/974,291, filed on Sep. 21, 2007.

(51) **Int. Cl.**

- A61B 17/072* (2006.01)
- A61B 17/068* (2006.01)
- A61B 17/00* (2006.01)
- A61B 17/29* (2006.01)
- A61B 17/32* (2006.01)

(52) **U.S. Cl.**

CPC *A61B 2017/00734* (2013.01); *A61B 2017/07278* (2013.01); *A61B 2017/07285* (2013.01); *A61B 2017/2927* (2013.01); *A61B 2017/2929* (2013.01); *A61B 2017/2943* (2013.01); *A61B 2017/320052* (2013.01)

(58) **Field of Classification Search**

USPC 227/175.1–182.1
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,881,250 A	10/1932	Tomlinson
2,031,682 A	2/1936	Wappler et al.
2,226,789 A	11/1938	Tupy
2,229,800 A	3/1939	Dean
2,174,219 A	9/1939	Balma
2,246,647 A	6/1941	Vancura
2,355,086 A	10/1943	Lang
2,419,045 A	4/1947	Whittaker
2,725,628 A	12/1955	O’Neilly et al.
3,017,637 A	1/1962	Sampson
3,079,606 A	3/1963	Bobrov et al.
3,120,845 A	2/1964	Horner
3,193,165 A	7/1965	Akhalaya et al.
3,252,643 A	5/1966	Strekopov et al.
3,252,880 A	5/1966	Magat
3,253,643 A	5/1966	Gudheim
3,256,875 A	6/1966	Tsepelev et al.
3,269,631 A	8/1966	Takaro
3,275,211 A	9/1966	Hirsch et al.
3,315,863 A	4/1967	O’Dea
3,317,105 A	5/1967	Astafjev et al.
3,388,847 A	6/1968	Kasulin et al.
3,490,576 A	1/1970	Alessi et al.
3,490,675 A	1/1970	Green et al.
3,494,533 A	2/1970	Green et al.
3,499,591 A	3/1970	Green
3,552,626 A	1/1971	Astafiev et al.
3,568,659 A	3/1971	Karnegis
3,589,589 A	6/1971	Akopov
3,593,903 A	7/1971	Astafiev et al.
3,618,842 A	11/1971	Bryan
3,638,652 A	2/1972	Kelley
3,643,851 A	2/1972	Green et al.
3,662,939 A	5/1972	Bryan
3,675,688 A	7/1972	Bryan et al.
3,692,224 A	9/1972	Astafiev et al.
3,717,294 A	2/1973	Green
3,735,762 A	5/1973	Bryan et al.
3,777,538 A	12/1973	Weatherly et al.
3,788,303 A	1/1974	Hall
3,795,034 A	3/1974	Strekopytov et al.
3,815,476 A	6/1974	Green et al.

3,819,100 A	6/1974	Noiles et al.
3,837,555 A	9/1974	Green
3,844,289 A	10/1974	Noiles
3,858,577 A	1/1975	Bass et al.
3,859,986 A	1/1975	Okada et al.
3,879,104 A	4/1975	Shugarman et al.
3,882,854 A	5/1975	Hulka et al.
3,892,228 A	7/1975	Mitsui
3,902,614 A	9/1975	Roberts et al.
3,935,981 A	2/1976	Akopov et al.
3,949,924 A	4/1976	Green
3,952,748 A	4/1976	Kaliher et al.
RE28,932 E	8/1976	Noiles et al.
3,985,050 A	10/1976	Lurie
4,014,492 A	3/1977	Rothfuss
4,027,510 A	6/1977	Hiltebrandt
4,060,089 A	11/1977	Noiles
4,064,881 A	12/1977	Meredith
4,071,029 A	1/1978	Richmond et al.
4,085,756 A	4/1978	Weaver
4,086,926 A	5/1978	Green et al.
4,092,986 A	6/1978	Schneiderman
4,111,206 A	9/1978	Vishnevsky et al.
4,169,476 A	10/1979	Hiltebrandt
4,198,960 A	4/1980	Utsugi
4,198,982 A	4/1980	Fortner et al.
4,202,479 A	5/1980	Razgulov et al.
4,202,480 A	5/1980	Annett
4,207,873 A	6/1980	Kruey
4,207,898 A	6/1980	Becht
4,244,372 A	1/1981	Kapitanov et al.
4,261,244 A	4/1981	Becht et al.
4,273,111 A	6/1981	Tsukaya
4,273,129 A	6/1981	Boebel
4,286,585 A	9/1981	Ogawa
4,289,131 A	9/1981	Mueller
4,289,133 A	9/1981	Rothfuss
4,296,881 A	10/1981	Lee
4,304,236 A	12/1981	Conta et al.
4,310,115 A	1/1982	Inoue
4,319,576 A	3/1982	Rothfuss
4,325,377 A	4/1982	Boebel
4,334,539 A	6/1982	Childs et al.
4,349,028 A	9/1982	Green
4,351,466 A	9/1982	Noiles
4,354,628 A	10/1982	Green
4,360,110 A	11/1982	Sigman et al.
4,367,729 A	1/1983	Ogiu
4,379,457 A	4/1983	Gravener et al.
4,383,634 A	5/1983	Green
4,391,401 A	7/1983	Moshofsky
4,402,311 A	9/1983	Hattori
4,402,445 A	9/1983	Green
4,429,695 A	2/1984	Green
4,442,964 A	4/1984	Becht
4,445,509 A	5/1984	Auth
4,445,892 A	5/1984	Hussein et al.
4,448,188 A	5/1984	Loeb
4,461,305 A	7/1984	Cibley
4,473,077 A	9/1984	Noiles et al.
4,476,863 A	10/1984	Kanshin et al.
4,484,775 A	11/1984	Norkus
4,485,817 A	12/1984	Swiggett
4,487,270 A	12/1984	Huber
4,488,523 A	12/1984	Shichman
4,489,724 A	12/1984	Arnegger
4,489,875 A	12/1984	Crawford et al.
4,494,057 A	1/1985	Hotta
4,494,549 A	1/1985	Namba et al.
4,499,895 A	2/1985	Takayama
4,505,272 A	3/1985	Utyamyshev et al.
4,505,414 A	3/1985	Filipi
4,506,670 A	3/1985	Crossley
4,506,671 A	3/1985	Green
4,513,746 A	4/1985	Aranyi et al.
4,519,532 A	5/1985	Foslien
4,520,817 A	6/1985	Green
4,527,724 A	7/1985	Chow et al.
4,534,352 A	8/1985	Korthoff

(56)

References Cited

U.S. PATENT DOCUMENTS

4,534,420 A	8/1985	Goldelius	4,887,599 A	12/1989	Muller
4,535,773 A	8/1985	Yoon	4,887,612 A	12/1989	Esser et al.
4,559,928 A	12/1985	Takayama	4,890,602 A	1/1990	Hake
4,566,620 A	1/1986	Green et al.	4,892,244 A	1/1990	Fox et al.
4,573,468 A	3/1986	Conta et al.	4,893,613 A	1/1990	Hake
4,573,622 A	3/1986	Green et al.	4,893,622 A	1/1990	Green et al.
4,573,727 A	3/1986	Iikura	4,903,697 A	2/1990	Resnick et al.
4,574,806 A	3/1986	McCarthy	4,907,591 A	3/1990	Vasconcellos et al.
4,576,167 A	3/1986	Noiles	4,907,973 A	3/1990	Hon
4,589,412 A	5/1986	Kensey	4,917,114 A	4/1990	Green et al.
4,589,416 A	5/1986	Green	4,919,152 A	4/1990	Ger
4,589,582 A	5/1986	Bilotti	4,928,699 A	5/1990	Sasai
4,591,085 A	5/1986	Di Giovanni	4,930,494 A	6/1990	Takehana et al.
4,592,354 A	6/1986	Rothfuss	4,932,960 A	6/1990	Green et al.
4,593,679 A	6/1986	Collins	4,936,845 A	6/1990	Stevens
4,600,357 A	7/1986	Coules	4,941,454 A	7/1990	Wood et al.
4,603,693 A	8/1986	Conta et al.	4,941,623 A	7/1990	Pruitt
4,605,001 A	8/1986	Rothfuss et al.	4,944,093 A	7/1990	Falk
4,606,343 A	8/1986	Conta et al.	4,944,443 A	7/1990	Odds et al.
4,607,638 A	8/1986	Crainich	4,955,882 A	9/1990	Hakky
4,610,383 A	9/1986	Rothfuss et al.	4,955,959 A	9/1990	Tompkins et al.
D286,567 S	11/1986	Lichtman et al.	4,957,499 A	9/1990	Lipatov et al.
4,623,183 A	11/1986	Aomori	4,962,877 A	10/1990	Hervas
4,631,052 A	12/1986	Kensey	4,976,688 A	12/1990	Rosenblum
4,633,861 A	1/1987	Chow et al.	4,976,710 A	12/1990	Mackin
4,633,874 A	1/1987	Chow et al.	4,977,900 A	12/1990	Fehling et al.
4,643,190 A	2/1987	Heimberger	4,978,049 A	12/1990	Green
4,644,952 A	2/1987	Patipa et al.	4,982,726 A	1/1991	Taira
4,646,745 A	3/1987	Noiles	4,991,764 A	2/1991	Mericle
4,655,673 A	4/1987	Hawkes	4,994,060 A	2/1991	Rink et al.
4,657,017 A	4/1987	Sorochenko	4,995,877 A	2/1991	Ams et al.
4,664,305 A	5/1987	Blake, III et al.	5,005,749 A	4/1991	Aranyi
4,667,673 A	5/1987	Li	5,018,657 A	5/1991	Pedlick et al.
4,669,471 A	6/1987	Hayashi	5,031,814 A	7/1991	Tompkins et al.
4,671,445 A	6/1987	Barker et al.	5,040,715 A	8/1991	Green et al.
4,672,961 A	6/1987	Davies	5,059,203 A	10/1991	Husted
4,674,515 A	6/1987	Andou et al.	5,065,929 A	11/1991	Schulze et al.
4,676,542 A	6/1987	Besold	D322,143 S	12/1991	Spreckelmeier
4,688,555 A	8/1987	Wardle	5,071,430 A	12/1991	de Salis et al.
4,696,667 A	9/1987	Masch	5,077,506 A	12/1991	Krause
4,700,703 A	10/1987	Resnick et al.	5,100,041 A	3/1992	Storace
4,703,887 A	11/1987	Clanton et al.	5,104,025 A	4/1992	Main et al.
4,705,038 A	11/1987	Sjostrom et al.	5,108,391 A	4/1992	Flachenecker et al.
4,708,141 A	11/1987	Inoue et al.	5,114,065 A	5/1992	Storace
4,714,187 A	12/1987	Green	5,119,983 A	6/1992	Green et al.
4,715,502 A	12/1987	Salmon	5,129,570 A	7/1992	Schulze et al.
4,728,020 A	3/1988	Green et al.	5,133,359 A	7/1992	Kedem
4,732,156 A	3/1988	Nakamura	5,133,713 A	7/1992	Huang et al.
4,733,118 A	3/1988	Mihalko	5,133,729 A	7/1992	Sjostrom
4,742,815 A	5/1988	Ninan et al.	5,139,513 A	8/1992	Segato
4,752,024 A	6/1988	Green et al.	5,156,315 A	10/1992	Green et al.
4,754,909 A	7/1988	Barker et al.	5,157,837 A	10/1992	Rose
4,756,309 A	7/1988	Sachse et al.	5,158,222 A	10/1992	Green et al.
4,760,840 A	8/1988	Fournier, Jr. et al.	5,170,925 A	12/1992	Madden et al.
4,763,669 A	8/1988	Jaeger	5,171,247 A	12/1992	Hughett et al.
4,767,044 A	8/1988	Green	5,171,251 A	12/1992	Bregen et al.
4,771,774 A	9/1988	Simpson et al.	5,173,133 A	12/1992	Morin et al.
4,776,506 A	10/1988	Green	5,192,292 A	3/1993	Cezana et al.
4,781,186 A	11/1988	Simpson et al.	5,197,649 A	3/1993	Bessler et al.
4,784,137 A	11/1988	Kulik et al.	5,201,325 A	4/1993	McEwen et al.
4,784,422 A	11/1988	Jones et al.	5,201,501 A	4/1993	Fassler
4,789,090 A	12/1988	Blake, III	5,201,750 A	4/1993	Hocheil et al.
4,796,793 A	1/1989	Smith et al.	5,205,459 A	4/1993	Brinkerhoff et al.
4,805,823 A	2/1989	Rothfuss	5,207,691 A	5/1993	Nardella
4,815,469 A	3/1989	Cohen et al.	5,207,697 A	5/1993	Carusillo et al.
4,817,847 A	4/1989	Redtenbacher et al.	5,217,003 A	6/1993	Wilk
4,819,632 A	4/1989	Davies	5,217,460 A	6/1993	Knoepfler
4,819,853 A	4/1989	Green	5,221,279 A	6/1993	Cook et al.
4,841,888 A	6/1989	Mills et al.	5,224,951 A	7/1993	Freitas
4,848,637 A	7/1989	Pruitt	5,226,426 A	7/1993	Yoon
4,858,608 A	8/1989	McQuilkin	5,237,884 A	8/1993	Seto
4,863,088 A	9/1989	Redmond et al.	5,243,967 A	9/1993	Hibino
4,867,158 A	9/1989	Sugg	5,249,583 A	10/1993	Mallaby
4,869,415 A	9/1989	Fox	5,253,793 A	10/1993	Green et al.
4,873,977 A	10/1989	Avant et al.	5,254,117 A	10/1993	Rigby et al.
			5,258,004 A	11/1993	Bales et al.
			5,258,007 A	11/1993	Spetzler et al.
			5,258,008 A	11/1993	Wilk
			5,261,877 A	11/1993	Fine et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,267,997 A	12/1993	Farin et al.	5,443,198 A	8/1995	Viola et al.
5,268,622 A	12/1993	Philipp	5,447,265 A	9/1995	Vidal et al.
5,271,543 A	12/1993	Grant et al.	5,454,825 A	10/1995	Van Leeuwen et al.
5,271,544 A	12/1993	Fox et al.	5,456,684 A	10/1995	Schmidt et al.
5,275,322 A	1/1994	Brinkerhoff et al.	5,460,182 A	10/1995	Goodman et al.
5,275,323 A	1/1994	Schulze et al.	5,464,404 A	11/1995	Abela et al.
5,275,609 A	1/1994	Pingleton et al.	5,465,894 A	11/1995	Clark et al.
5,279,565 A	1/1994	Klein et al.	5,465,895 A	11/1995	Knodel et al.
5,285,945 A	2/1994	Brinkerhoff et al.	5,467,911 A	11/1995	Tsuruta et al.
5,289,963 A	3/1994	McGarry et al.	5,472,132 A	12/1995	Savage et al.
5,290,299 A	3/1994	Fain et al.	5,474,223 A	12/1995	Viola et al.
5,290,303 A	3/1994	Pingleton et al.	5,476,206 A	12/1995	Green et al.
5,292,053 A	3/1994	Bilotti et al.	5,478,003 A	12/1995	Green et al.
5,295,990 A	3/1994	Levin	5,482,054 A	1/1996	Slater et al.
5,300,087 A	4/1994	Knoepfler	5,482,197 A	1/1996	Green et al.
5,307,976 A	5/1994	Olson et al.	5,484,095 A	1/1996	Green et al.
5,312,023 A	5/1994	Green et al.	5,485,947 A	1/1996	Olson et al.
5,312,434 A	5/1994	Crainich	5,487,499 A	1/1996	Sorrentino et al.
5,318,221 A	6/1994	Green et al.	5,487,500 A	1/1996	Knodel et al.
5,320,627 A	6/1994	Sorensen et al.	5,490,813 A	2/1996	Danielsen et al.
5,322,055 A	6/1994	Davison et al.	5,496,269 A	3/1996	Snoke
5,324,288 A	6/1994	Billings et al.	5,496,317 A	3/1996	Goble et al.
5,324,300 A	6/1994	Elias et al.	5,514,134 A	5/1996	Rydell et al.
5,326,013 A	7/1994	Green et al.	5,518,163 A	5/1996	Hooven
5,330,471 A	7/1994	Eggers	5,518,164 A	5/1996	Hooven
5,330,486 A	7/1994	Wilk	5,520,634 A	5/1996	Fox et al.
5,333,772 A	8/1994	Rothfuss et al.	5,524,180 A	6/1996	Wang et al.
5,333,773 A	8/1994	Main et al.	5,527,313 A	6/1996	Scott et al.
5,336,229 A	8/1994	Noda	5,529,235 A	6/1996	Boiarski et al.
5,342,299 A	8/1994	Snoke et al.	5,531,687 A	7/1996	Snoke et al.
5,342,381 A	8/1994	Tidemand	5,533,661 A	7/1996	Main et al.
5,342,382 A	8/1994	Brinkerhoff et al.	5,535,935 A	7/1996	Vidal et al.
5,344,420 A	9/1994	Hilal et al.	5,535,937 A	7/1996	Boiarski et al.
5,350,104 A	9/1994	Main et al.	5,549,565 A	8/1996	Ryan et al.
5,352,222 A	10/1994	Rydell	5,553,765 A	9/1996	Knodel et al.
5,352,223 A	10/1994	McBrayer et al.	5,554,169 A	9/1996	Green et al.
5,352,235 A	10/1994	Koros et al.	5,562,677 A	10/1996	Hildwein et al.
5,354,266 A	10/1994	Snoke	5,562,702 A	10/1996	Huitema et al.
5,356,408 A	10/1994	Rydell	5,569,274 A	10/1996	Rapacki et al.
5,358,506 A	10/1994	Green et al.	5,571,116 A	11/1996	Bolanos et al.
5,364,001 A	11/1994	Bryan	5,573,543 A	11/1996	Akopov et al.
5,364,409 A	11/1994	Kuwabara et al.	5,575,799 A	11/1996	Bolanos et al.
5,366,133 A	11/1994	Geiste	5,578,052 A	11/1996	Koros et al.
5,366,476 A	11/1994	Noda	5,580,067 A	12/1996	Hamblin et al.
5,368,015 A	11/1994	Wilk	5,582,611 A	12/1996	Tsuruta et al.
5,368,607 A	11/1994	Freitas	5,584,425 A	12/1996	Savage et al.
5,370,294 A	12/1994	Bauer	5,588,579 A	12/1996	Schnut et al.
5,380,321 A	1/1995	Yoon	5,591,186 A	1/1997	Wurster et al.
5,381,943 A	1/1995	Allen et al.	5,597,107 A	1/1997	Knodel et al.
5,383,880 A	1/1995	Hooven	5,599,347 A	2/1997	Hart et al.
5,389,098 A	2/1995	Tsuruta et al.	5,603,443 A	2/1997	Clark et al.
5,391,156 A	2/1995	Hildwein et al.	5,607,094 A	3/1997	Clark et al.
5,392,789 A	2/1995	Slater et al.	5,609,285 A	3/1997	Grant et al.
5,395,030 A	3/1995	Kuramoto et al.	5,609,381 A	3/1997	Thom et al.
5,395,033 A	3/1995	Byrne et al.	5,609,560 A	3/1997	Ichikawa et al.
5,395,369 A	3/1995	McBrayer et al.	5,618,303 A	4/1997	Marlow et al.
5,396,900 A	3/1995	Slater et al.	5,618,307 A	4/1997	Donlon et al.
5,397,046 A	3/1995	Savage et al.	5,626,607 A	5/1997	Malecki et al.
5,400,267 A	3/1995	Denen et al.	5,639,008 A	6/1997	Gallagher et al.
D357,535 S	4/1995	Grant et al.	5,651,780 A	7/1997	Jackson et al.
5,403,312 A	4/1995	Yates et al.	5,653,374 A	8/1997	Young et al.
5,403,326 A	4/1995	Harrison et al.	5,665,100 A	9/1997	Yoon
5,403,327 A	4/1995	Thornton et al.	5,667,473 A	9/1997	Finn et al.
5,411,508 A	5/1995	Bessler et al.	5,667,478 A	9/1997	McFarlin et al.
5,413,267 A	5/1995	Solyntjes et al.	5,667,517 A	9/1997	Hooven
5,413,268 A	5/1995	Green et al.	5,667,526 A	9/1997	Levin
5,415,334 A	5/1995	Williamson et al.	5,676,674 A	10/1997	Bolanos et al.
5,425,705 A	6/1995	Evard et al.	5,688,269 A	11/1997	Newton et al.
5,425,738 A	6/1995	Gustafson et al.	5,692,668 A	12/1997	Schulze et al.
5,425,745 A	6/1995	Green et al.	5,693,031 A	12/1997	Ryan et al.
5,431,322 A	7/1995	Green et al.	5,697,542 A	12/1997	Knodel et al.
5,431,645 A	7/1995	Smith et al.	5,709,335 A	1/1998	Heck
5,433,721 A	7/1995	Hooven et al.	5,732,871 A	3/1998	Clark et al.
5,437,636 A	8/1995	Snoke et al.	5,732,872 A	3/1998	Bolduc et al.
5,441,507 A	8/1995	Wilk	5,735,848 A	4/1998	Yates et al.
			5,735,849 A	4/1998	Baden et al.
			5,735,861 A	4/1998	Peifer et al.
			5,741,285 A	4/1998	McBrayer et al.
			5,749,893 A	5/1998	Vidal et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,752,644 A	5/1998	Bolanos et al.	6,126,058 A	10/2000	Adams et al.
5,758,814 A	6/1998	Gallagher et al.	6,126,591 A	10/2000	McGarry et al.
5,762,458 A	6/1998	Wang et al.	6,132,368 A	10/2000	Cooper
5,776,147 A	7/1998	Dolendo	6,162,220 A	12/2000	Nezhat
5,779,130 A	7/1998	Alesi et al.	6,165,191 A	12/2000	Shibata et al.
5,779,132 A	7/1998	Knodel et al.	6,174,324 B1	1/2001	Egan et al.
5,782,396 A	7/1998	Mastri et al.	6,179,837 B1	1/2001	Hooven
5,782,397 A	7/1998	Koukline	6,193,129 B1	2/2001	Bittner et al.
5,792,135 A	8/1998	Madhani et al.	D438,617 S	3/2001	Cooper et al.
5,797,835 A	8/1998	Green	6,201,984 B1	3/2001	Funda et al.
5,797,900 A	8/1998	Madhani et al.	6,206,903 B1	3/2001	Ramans
5,797,944 A	8/1998	Nobles et al.	D441,076 S	4/2001	Cooper et al.
5,807,377 A	9/1998	Madhani et al.	6,209,773 B1	4/2001	Bolduc et al.
5,807,402 A	9/1998	Yoon	6,217,591 B1	4/2001	Egan et al.
5,814,044 A	9/1998	Hooven	D441,862 S	5/2001	Cooper et al.
5,815,640 A	9/1998	Wang et al.	6,231,587 B1	5/2001	Makower
5,817,113 A	10/1998	Gifford, III et al.	6,241,139 B1	6/2001	Milliman et al.
5,820,009 A	10/1998	Melling et al.	6,244,809 B1	6/2001	Wang et al.
5,823,956 A	10/1998	Roth et al.	6,246,200 B1	6/2001	Blumenkranz et al.
5,826,776 A	10/1998	Schulze et al.	D444,555 S	7/2001	Cooper et al.
5,829,662 A	11/1998	Allen et al.	6,264,087 B1	7/2001	Whitman
5,836,503 A	11/1998	Ehrenfels et al.	6,309,397 B1	10/2001	Julian et al.
5,846,221 A	12/1998	Snoke et al.	6,312,435 B1	11/2001	Wallace et al.
5,855,583 A	1/1999	Wang et al.	6,315,184 B1	11/2001	Whitman
5,855,590 A	1/1999	Malecki et al.	6,331,181 B1	12/2001	Tierney et al.
5,857,996 A	1/1999	Snoke	6,346,072 B1	2/2002	Cooper
5,860,953 A	1/1999	Snoke et al.	6,348,061 B1	2/2002	Whitman
5,868,760 A	2/1999	McGuckin, Jr.	6,364,888 B1	4/2002	Niemeyer et al.
5,871,471 A	2/1999	Ryan et al.	6,368,340 B2	4/2002	Malecki et al.
5,876,203 A	3/1999	Bailey	6,371,952 B1	4/2002	Madhani et al.
5,878,193 A	3/1999	Wang et al.	6,394,998 B1	5/2002	Wallace et al.
5,881,943 A	3/1999	Heck et al.	6,398,726 B1	6/2002	Ramans et al.
5,893,553 A	4/1999	Pinkous	6,443,973 B1	9/2002	Whitman
5,893,875 A	4/1999	O'Connor et al.	6,488,197 B1	12/2002	Whitman
5,895,084 A	4/1999	Mauro	6,491,201 B1	12/2002	Whitman
5,897,562 A	4/1999	Bolanos et al.	6,491,701 B2	12/2002	Tierney et al.
5,907,664 A	5/1999	Wang et al.	6,505,768 B2	1/2003	Whitman
5,913,842 A	6/1999	Boyd et al.	6,517,565 B1	2/2003	Whitman et al.
5,915,616 A	6/1999	Viola et al.	6,533,157 B1	3/2003	Whitman
5,925,055 A	7/1999	Adrian et al.	6,716,233 B1	4/2004	Whitman
5,931,848 A	8/1999	Saadat	6,764,445 B2	7/2004	Ramans et al.
5,947,363 A	9/1999	Bolduc et al.	6,766,204 B2	7/2004	Niemeyer et al.
5,951,549 A	9/1999	Richardson et al.	6,786,382 B1	9/2004	Hoffman
5,954,259 A	9/1999	Viola et al.	6,790,217 B2	9/2004	Schulze et al.
5,954,731 A	9/1999	Yoon	6,793,652 B1	9/2004	Whitman et al.
5,957,363 A	9/1999	Heck	6,866,671 B2	3/2005	Tierney et al.
5,957,882 A	9/1999	Nita et al.	6,964,363 B2	11/2005	Wales et al.
5,957,884 A	9/1999	Hooven	6,978,921 B2	12/2005	Shelton, IV et al.
5,976,159 A	11/1999	Bolduc et al.	6,981,941 B2	1/2006	Whitman et al.
5,984,919 A	11/1999	Hilal et al.	7,032,798 B2	4/2006	Whitman et al.
5,989,215 A	11/1999	Delmotte et al.	7,048,745 B2	5/2006	Tierney et al.
5,989,274 A	11/1999	Davison et al.	7,241,288 B2	7/2007	Braun
5,993,378 A	11/1999	Lemelson	7,404,509 B2	7/2008	Ortiz et al.
5,993,454 A	11/1999	Longo	7,644,848 B2	1/2010	Swayze et al.
5,993,466 A	11/1999	Yoon	7,695,485 B2	4/2010	Whitman et al.
5,997,510 A	12/1999	Schwemberger	7,743,960 B2	6/2010	Whitman et al.
6,001,108 A	12/1999	Wang et al.	7,751,870 B2	7/2010	Whitman
6,004,335 A	12/1999	Vaitekunas et al.	7,770,773 B2	8/2010	Whitman et al.
6,007,512 A	12/1999	Hooven	7,905,897 B2	3/2011	Whitman et al.
6,007,531 A	12/1999	Snoke et al.	7,951,071 B2	5/2011	Whitman et al.
6,010,054 A	1/2000	Johnson et al.	7,963,433 B2	6/2011	Whitman et al.
6,010,493 A	1/2000	Snoke	8,016,855 B2	9/2011	Whitman et al.
6,017,322 A	1/2000	Snoke et al.	8,021,373 B2	9/2011	Whitman et al.
6,017,354 A	1/2000	Culp et al.	8,241,322 B2	8/2012	Whitman et al.
6,024,741 A	2/2000	Williamson, IV et al.	8,262,560 B2	9/2012	Whitman
6,063,095 A	5/2000	Wang et al.	8,910,846 B2	12/2014	Viola
6,068,627 A	5/2000	Orszulak et al.	9,017,371 B2	4/2015	Whitman et al.
6,074,402 A	6/2000	Peifer et al.	9,204,877 B2	12/2015	Whitman et al.
6,083,163 A	7/2000	Wegner et al.	2002/0042620 A1	4/2002	Julian et al.
6,086,600 A	7/2000	Kortenbach	2003/0105478 A1	6/2003	Whitman et al.
6,090,120 A	7/2000	Wright et al.	2004/0094597 A1	5/2004	Whitman et al.
6,099,466 A	8/2000	Sano et al.	2005/0006434 A1	1/2005	Wales et al.
6,106,512 A	8/2000	Cochran et al.	2005/0222665 A1	10/2005	Aranyi
6,110,188 A	8/2000	Narciso, Jr.	2006/0049229 A1	3/2006	Milliman et al.
6,119,913 A	9/2000	Adams et al.	2006/0097026 A1	5/2006	Shelton
			2007/0023477 A1	2/2007	Whitman et al.
			2007/0175953 A1	8/2007	Shelton et al.
			2007/0175961 A1	8/2007	Shelton et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0110958 A1* 5/2008 McKenna A61B 17/00491
227/176.1
2008/0281336 A1 11/2008 Zergiebel
2009/0090764 A1* 4/2009 Viola A61B 17/07207
227/176.1
2009/0095790 A1 4/2009 Whitman et al.
2010/0042143 A1 2/2010 Cunningham
2010/0170931 A1* 7/2010 Viola A61B 17/128
227/175.1
2010/0320252 A1 12/2010 Viola et al.
2014/0025046 A1* 1/2014 Williams A61B 17/07207
606/1
2014/0299647 A1 10/2014 Scirica et al.

FOREIGN PATENT DOCUMENTS

DE 3114135 A1 10/1982
DE 3300768 A1 7/1984
DE 4213426 A1 10/1992
DE 4312147 A1 10/1993
EP 0041022 A1 12/1981
EP 0116220 A1 8/1984
EP 0121474 A2 10/1984
EP 0142225 A1 5/1985
EP 0156774 A2 10/1985
EP 0203375 A2 12/1986
EP 0216532 A1 4/1987
EP 0293123 A2 11/1988
EP 0 324 166 A2 7/1989
EP 0324637 A1 7/1989
EP 0365153 A1 4/1990
EP 0369324 A1 5/1990
EP 0373762 A1 6/1990
EP 0399701 A1 11/1990
EP 0484677 A1 5/1992
EP 0514139 A2 11/1992
EP 0536903 A2 4/1993
EP 0539762 A1 5/1993
EP 0552050 A2 7/1993
EP 0552423 A2 7/1993
EP 0581400 A1 2/1994
EP 0593920 A1 4/1994
EP 0598579 A1 5/1994
EP 0621006 A1 10/1994
EP 0630612 A1 12/1994
EP 0634144 A1 1/1995
EP 0639349 A2 2/1995
EP 0653922 A1 5/1995
EP 0679367 A2 11/1995
EP 0705571 A1 4/1996
EP 0878169 A1 11/1998
EP 0947167 A1 10/1999
EP 1813211 A2 8/2007
EP 1992296 A1 11/2008
FR 2660851 A1 10/1991
GB 1082821 A 9/1967
GB 1352554 A 5/1974
GB 1452185 A 10/1976
GB 2044108 A 10/1980
GB 2048685 A 12/1980

GB 2165559 A 4/1986
GB 2180455 A 4/1987
NL 7711347 A 4/1979
RU 659146 4/1979
WO 8203545 A1 10/1982
WO 8300992 A1 3/1983
WO 90/05489 A1 5/1990
WO 9005491 A2 5/1990
WO 9006085 A1 6/1990
WO 9107136 A1 5/1991
WO 9216141 A1 10/1992
WO 9308754 A1 5/1993
WO 9314706 A1 8/1993
WO 95/18572 A1 7/1995
WO 9535065 A1 12/1995
WO 9712555 A2 4/1997
WO 9814129 A1 4/1998
WO 9920328 A2 4/1999
WO 9958076 A1 11/1999
WO 0072765 A1 12/2000
WO 0103587 A1 1/2001
WO 0108572 A1 2/2001
WO 01/17448 3/2001
WO 0135813 A1 5/2001
WO 0162163 A1 8/2001
WO 02058539 A2 8/2002
WO 03077769 A1 9/2003
WO 2004078026 A2 9/2004

OTHER PUBLICATIONS

Canadian Office Action dated Oct. 7, 2014 for CA 2,698,329.
Australian Patent Examination Report No. 2 for AU 2013-213682 dated Feb. 24, 2015.
Supplementary European Search Report for EP 08 83 2190 dated Sep. 3, 2014.
International Search Report corresponding to PCT/US2006/029287, dated Aug. 27, 2007 (1 page).
International Search Report corresponding to PCT/US2008/077255, dated Nov. 28, 2008 (1 page).
Canadian Office Action for CA 2,698,571 dated May 4, 2015.
EP Examination Report for European Application Serial No. 08 832 190.6, dated Jul. 16, 2015.
Canadian Office Action dated Apr. 10, 2015 for Canadian patent appln. No. CA 2,698,329.
Japanese Office Action dated Jun. 19, 2015 for Japanese Appln. No. JP 2014-132135.
European Office Action corresponding to counterpart European Patent Application No. EP 16 17 8984.7 dated Oct. 31, 2017.
Chinese First Office Action corresponding to counterpart Patent Appln. CN 200880108277.9 dated Jun. 29, 2011.
Australian Examination Report No. 1 corresponding to counterpart Patent Appln. AU 2008302043 dated Jul. 23, 2012.
Japanese Office Action corresponding to counterpart Patent Appln. JP 2010-526049 dated Feb. 6, 2013.
Australian Examination Report No. 1 corresponding to counterpart Patent Appln. AU 2013213682 dated May 14, 2014.
Extended European Search Report corresponding to counterpart Patent Appln. EP 08 83 2190.6 dated Sep. 3, 2014.

* cited by examiner




FIG. 1
PRIOR ART




FIG. 2a





FIG. 2b






FIG. 3b




FIG. 3C




FIG. 3d




FIG. 3e




FIG. 3f




FIG. 3g




FIG. 3h




FIG. 3i




FIG. 3j




FIG. 3k




FIG. 31




FIG. 4a




FIG. 4b




FIG. 5a




FIG. 5b




FIG. 5c




FIG. 5d




FIG. 6a




FIG. 6b




FIG. 6c




FIG. 6d




FIG. 6e




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19

SURGICAL DEVICE HAVING A ROTATABLE JAW PORTION

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 13/731,451, filed Dec. 31, 2012, which is a continuation of U.S. patent application Ser. No. 13/162,811, filed Jun. 17, 2011, now U.S. Pat. No. 8,353,440, which is a continuation of U.S. patent application Ser. No. 13/027,292, filed Feb. 15, 2011, now U.S. Pat. No. 7,992,758, which is a continuation of U.S. patent application Ser. No. 12/235,386, filed Sep. 22, 2008, now U.S. Pat. No. 7,918,230, which claims benefit of and priority to U.S. Provisional Patent Application Ser. No. 60/974,291, filed on Sep. 21, 2007, each of which is expressly incorporated herein in its entirety by reference thereto.

INCORPORATION BY REFERENCE

The present application expressly incorporates herein by reference each of the following in its entirety: U.S. patent application Ser. No. 11/191,851, filed on Jul. 27, 2005, and issued as U.S. Pat. No. 8,241,322 on Aug. 14, 2012; U.S. Patent Application Ser. No. 60/388,644, filed on Jun. 14, 2002; U.S. patent application Ser. No. 10/460,291, filed on Jun. 11, 2003, and issued as U.S. Pat. No. 7,743,960 on Jun. 29, 2010; U.S. patent application Ser. No. 09/999,546, filed on Nov. 30, 2001, and issued as U.S. Pat. No. 7,695,485 on Apr. 13, 2010; U.S. patent application Ser. No. 09/887,789, filed on Jun. 22, 2001, and issued as U.S. Pat. No. 7,032,798 on Apr. 25, 2006; U.S. patent application Ser. No. 09/836,781, filed on Apr. 17, 2001, and issued as U.S. Pat. No. 6,981,941 on Jan. 3, 2006; U.S. patent application Ser. No. 09/723,715, filed on Nov. 28, 2000, and issued as U.S. Pat. No. 6,793,652 on Sep. 21, 2004; U.S. patent application Ser. No. 09/324,451, filed on Jun. 2, 1999, and issued as U.S. Pat. No. 6,315,184 on Nov. 13, 2001; U.S. patent application Ser. No. 09/324,452, filed on Jun. 2, 1999, and issued as U.S. Pat. No. 6,443,973 on Sep. 3, 2002; U.S. patent application Ser. No. 09/351,534, filed on Jul. 12, 1999 and issued as U.S. Pat. No. 6,264,087 on Jul. 24, 2001; U.S. patent application Ser. No. 09/510,923, filed on Feb. 22, 2000 and issued as U.S. Pat. No. 6,517,565 on Feb. 11, 2003; and U.S. patent application Ser. No. 09/510,927, filed on Feb. 22, 2000 and issued as U.S. Pat. No. 6,716,233 on Apr. 6, 2004.

FIELD OF THE INVENTION

The present invention relates to a surgical device. More specifically, the present invention relates to a powered, articulating device for clamping, cutting and stapling tissue.

BACKGROUND INFORMATION

One type of surgical device is a linear clamping, cutting and stapling device. Such a device may be employed in a surgical procedure to resect a cancerous or anomalous tissue from a gastrointestinal tract. One conventional linear clamping, cutting and stapling instrument is shown in FIG. 1. The device includes a pistol grip-styled structure having an elongated shaft and distal portion. The distal portion includes a pair of scissors-styled gripping elements, which clamp the open ends of the colon closed. In this device, one of the two scissors-styled gripping elements, such as the anvil portion, moves or pivots relative to the overall struc-

ture, whereas the other gripping element remains fixed relative to the overall structure. The actuation of this scissoring device (the pivoting of the anvil portion) is controlled by a grip trigger maintained in the handle.

In addition to the scissoring device, the distal portion also includes a stapling mechanism. The fixed gripping element of the scissoring mechanism includes a staple cartridge receiving region and a mechanism for driving the staples up through the clamped end of the tissue against the anvil portion, thereby sealing the previously opened end. The scissoring elements may be integrally formed with the shaft or may be detachable such that various scissoring and stapling elements may be interchangeable.

One problem with the foregoing surgical devices, and in particular with the foregoing linear clamping, cutting and stapling devices such as that illustrated in FIG. 1, is that the opposing jaws may be difficult to maneuver within a patient. It may be necessary for a surgeon to move the opposing jaws between various angles in order to position the desired tissue between the opposing jaws. However, it is also generally desirable to make an incision in a patient that is as small as possible, and the small size of an incision limits the degree to which the opposing jaws may be maneuvered.

Another problem with the foregoing surgical devices, and in particular with the foregoing linear clamping, cutting and stapling devices such as that illustrated in FIG. 1, is that the opposing jaws may not be sufficiently hemostatic. Specifically, the opposing jaws of the foregoing surgical devices are not clamped together with sufficient force, thereby reducing the effectiveness of the surgical device.

Thus, there is believed to be a need for an improvement in the maneuverability of clamping, cutting and stapling devices. In addition, there is believed to be a need for a clamping, cutting and stapling device that provides additional clamping force.

SUMMARY

In accordance with an example embodiment of the present invention, a surgical device is provided that includes a jaw portion pivotably connected to a shaft portion about a hinge. The hinge defines an axis of rotation of these components that is perpendicular to one or both of the jaw portion and the shaft portion. The jaw portion, or a part thereof, may also be rotatable relative to the shaft portion about the longitudinal axis of the jaw portion.

The jaw portion includes a first jaw and a second jaw. The second jaw is disposed in opposed correspondence with the first jaw. The first jaw may be pivotably coupled to the second jaw. The device may also include at least one of a cutting element and a stapling element disposed within the second jaw, preferably a blade rotatably mounted on a staple-driving wedge. The cutting element and/or the stapling element may be configured to move between a distal end and a proximal end of the second jaw to at least one of cut and staple a section of tissue disposed between the first and second jaws.

In accordance with an example embodiment of the present invention, a surgical device is provided that includes a jaw portion. The jaw portion includes a first jaw and a second jaw moveable relative to the first jaw. The surgical device also includes a shaft portion coupled to a proximal end of the jaw portion. The surgical device further includes a driver configured to cause relative movement of the jaw portion and the shaft portion. The jaw portion defines a first longitudinal axis and the shaft portion defines a second longitudinal axis. The driver may be configured to cause the jaw

portion to pivot relative to the shaft portion about a pivot axis that is perpendicular to the first and second longitudinal axes. The first and second jaws may be moveable relative to each other in a plane, the pivot axis being arranged parallel to the plane. Also, in accordance with an example embodiment of the present invention, the driver is also configured to cause at least a portion of the jaw portion to pivot relative to the shaft portion about the first longitudinal axis.

The driver may be adapted to be driven by a first rotatable drive shaft and a second rotatable drive shaft. For instance, the driver may be configured such that rotation of the first and second rotatable drive shafts in opposite directions relative to each other causes the jaw portion to pivot relative to the shaft portion about the pivot axis. Also, the driver may be configured such that rotation of the first and second rotatable drive shafts in a same direction relative to each other causes the at least a portion of the jaw portion to rotate relative to the shaft portion about the first longitudinal axis. Furthermore, the driver may be configured such that rotation of the first rotatable drive shaft without rotating the second rotatable drive shaft causes relative movement of the first jaw and the second jaw.

The surgical device may include a surgical member disposed within the first jaw. The surgical member may include a cutting element and/or a stapling element. The driver may be configured such that rotation of the second rotatable drive shaft without rotating the first rotatable drive shaft causes relative movement of the surgical member within the first jaw.

In accordance with an example embodiment of the present invention, there is provided a surgical device that includes a jaw portion including a first jaw and a second jaw moveable relative to the first jaw, a shaft portion coupled to a proximal end of the jaw portion, and a driver adapted to be driven by first and second rotatable drive shafts such that selective rotation of the first and second rotatable drive shafts causes the surgical device to perform at least four different functions, e.g., movement of a first one of the jaw portion, the first jaw, the second jaw and the shaft portion relative to at least a second one of the jaw portion, the first jaw, the second jaw and the shaft portion.

The jaw portion may define a first longitudinal axis, the first of the at least four different functions including the rotation of at least a portion of the jaw portion relative to the shaft portion about the first longitudinal axis. The driver is configured to be driven by rotation of the first and second rotatable drive shafts in a same direction relative to each other so as to cause the at least a portion of the jaw portion to rotate relative to the shaft portion about the first longitudinal axis. The shaft portion may define a second longitudinal axis, a second of the at least four different functions including pivoting the jaw portion relative to the shaft portion about a pivot axis that is perpendicular to the second longitudinal axis. The driver is configured to be driven by rotation of the first and second rotatable drive shafts in opposite directions relative to each other so as to cause the jaw portion to pivot relative to the shaft portion about the pivot axis. A third of the at least four different functions may include moving the first jaw relative to the second jaw. The driver is configured to be driven by the first rotatable drive shaft without rotation of the second rotatable drive shaft to cause relative movement of the first jaw and the second jaw. In addition, the surgical device may also include a surgical member, e.g., a cutting and/or stapling element, disposed within the first jaw, a fourth of the at least four different functions including relative movement of the surgical member within the first jaw. The driver is configured to be driven

by rotation of the second rotatable drive shaft without rotation of the first rotatable drive shaft so as to cause relative movement of the surgical member within the first jaw.

In accordance with an example embodiment of the present invention, there is provided a surgical device that includes a jaw portion, having a first jaw in opposed correspondence with a second jaw, the second jaw including a surgical member; a shaft portion coupled to a proximal end of the jaw portion; at least one motor configured to rotate the jaw portion relative to the shaft portion, to move the jaw portion relative to the shaft portion, move the first jaw relative to the second jaw and move the surgical member within the second jaw. The surgical member may be prevented from moving within the second jaw unless the first jaw is in a closed position relative to the second jaw.

When the first jaw is in an open position relative to the second jaw, the jaw portion may be rotatable relative to the shaft portion. The surgical device may also include a gear element, and the gear element may be selectively engaged based upon a position of the first jaw relative to the second jaw. The gear element may be an idler gear that is moveable between a proximal position and a distal position. The surgical device may also include a cam block that is moveable between a proximal position and a distal position. The cam block may include a surface, and the cam block may be moved between its proximal and distal positions by engagement of the surface with a surface of one of the first and second jaws when the first and second jaws are moved relative to each other. The idler gear may be moved between its proximal and distal positions by engagement of the cam block with the idler gear.

When the idler gear is in a distal position, the idler gear may engage recesses of a housing, and rotation of the idler gear by a drive element may cause the jaw portion to rotate relative to the shaft portion. When the idler gear is in a proximal position, the idler gear may be out of engagement with the recesses of the housing, such that the idler gear is rotatable relative to the housing, and rotation of the idler gear by the drive element may cause the surgical member to move within the second jaw. Advantageously, the surgical member may include a cutting element and/or a stapling element.

In accordance with an example embodiment of the present invention, there is provided a method of using a surgical device, the surgical device including a jaw portion that has a first jaw in opposed correspondence with a second jaw, the second jaw including a surgical member, and a shaft portion coupled to a proximal end of the jaw portion. The method may include the steps of: operating at least one motor so as to selectively rotate the jaw portion relative to the shaft portion, move the jaw portion relative to the shaft portion, move the first jaw relative to the second jaw, and move the surgical member within the second jaw; and locking the surgical member from moving within the second jaw unless the first jaw is in a closed position relative to the second jaw.

The method may also include the step of rotating the jaw portion relative to the shaft portion when the first jaw is in an open position relative to the second jaw. In addition, a gear element may be provided. The method may include the step of selectively engaging the gear element based upon a position of the first jaw relative to the second jaw. Providing the gear element may include providing an idler gear that is moveable between a proximal position and a distal position. A cam block may be provided that is moveable between a proximal position and a distal position.

5

The cam block may include a surface, and the method may include the step of moving the cam block between its proximal and distal positions by engagement of the surface with a surface of one of the first and second jaws when the first and second jaws are moved relative to each other. The idler gear may be moved between its proximal and distal positions by engagement of the cam block with the idler gear. The idler gear may engage recesses of a housing when the idler gear is in a distal position. When the idler gear engages the recesses of the housing, rotation of the idler gear by a drive element may cause the jaw portion to rotate relative to the shaft portion.

The method may also include the steps of moving the idler gear to a proximal position such that the idler gear is out of engagement with the recesses of the housing and rotating the idler gear relative to the housing. Upon rotating the idler gear by the drive element, the surgical member may be moved within the second jaw. Advantageously, the surgical member includes at least one of a cutting element and a stapling element, and the step of moving the surgical member includes at least one of cutting and stapling a section of tissue.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a conventional linear clamping, cutting and stapling device;

FIG. 2(a) is a perspective view of an example embodiment of an electro-mechanical driver component, according to the present invention;

FIG. 2(b) is a schematic diagram that illustrates some of the components of a surgical device, according to an example embodiment of the present invention;

FIG. 3(a) is a perspective view of a surgical device, according to an example embodiment of the present invention;

FIG. 3(b) is a rear perspective view that illustrates some of the internal components of the surgical device, according to one embodiment of the present invention;

FIG. 3(c) is a side perspective view that illustrates some of the internal components of the surgical device, according to one embodiment of the present invention;

FIG. 3(d) is a perspective view that illustrates a jaw portion being fully pivoted, e.g., articulated, relative to a shaft portion, according to one embodiment of the present invention;

FIG. 3(e) is a bottom perspective view that illustrates the jaw portion being fully pivoted relative to the shaft portion, according to one embodiment of the present invention;

FIG. 3(f) is an exploded view of a replaceable staple cartridge, according to one embodiment of the present invention;

FIG. 3(g) is a cross-sectional view of the surgical device, according to one embodiment of the present invention, in a fully closed position;

FIG. 3(h) is a bottom view of a first jaw, according to another example embodiment of the present invention;

FIGS. 3(i) to 3(l) are side cross-sectional views that illustrate the opening and closing of first and second jaws, according to another example embodiment of the present invention;

FIG. 4(a) is a perspective view of an articulating clamping, cutting and stapling attachment, according to another example embodiment of the present invention;

FIG. 4(b) is a perspective view that illustrates additional features of the second jaw of the jaw portion, according to an example embodiment of the present invention;

6

FIG. 5(a) is a perspective view that illustrates the proximal end of the second jaw, according to an example embodiment of the present invention;

FIG. 5(b) illustrates the surgical device of FIG. 4(a) when moved into a first partially closed position;

FIG. 5(c) illustrates the surgical device of FIG. 4(a) when moved into a second partially closed position;

FIG. 5(d) illustrates the surgical device of FIG. 4(a) when moved into a fully closed position;

FIG. 6(a) illustrates a flexible shaft and a first coupling, according to an example embodiment of the present invention;

FIG. 6(b) illustrates a rear perspective view of the first coupling, according to an example embodiment of the present invention;

FIG. 6(c) illustrates a front perspective view of the first coupling, according to the example embodiment shown in FIG. 6(b);

FIG. 6(d) is a side perspective view of some of the internal components of the first coupling, according to an example embodiment of the present invention;

FIG. 6(e) is a rear perspective view of the second coupling at the distal end of the flexible shaft, according to an example embodiment of the present invention;

FIG. 7 illustrates a side view, partially in section, of the flexible shaft, according to another example embodiment of the present invention;

FIG. 8 is a cross-sectional view of the flexible shaft taken along the line 8-8 illustrated in FIG. 7;

FIG. 9 illustrates a rear end view of first coupling, according to an example embodiment of the present invention;

FIG. 10, there is seen a front end view of the second coupling of the flexible shaft, according to an example embodiment of the present invention;

FIG. 11 illustrates schematically an arrangement of motors, according to an example embodiment of the present invention;

FIG. 12 illustrates a schematic view of the electro-mechanical driver component, according to an example embodiment of the present invention;

FIG. 13 is a schematic view of an encoder, according to an example embodiment of the present invention;

FIG. 14 schematically illustrates the memory module, according to an example embodiment of the present invention;

FIG. 15, there is seen a schematic view of a wireless RCU, according to an example embodiment of the present invention;

FIG. 16, there is seen a schematic view of a wired RCU, according to an example embodiment of the present invention;

FIG. 17 is a side cross-sectional view of a surgical device, according to an example embodiment of the present invention;

FIG. 18 is a perspective view of some of the internal components of the surgical device of FIG. 17; and

FIG. 19 is rear perspective view of some of the internal components of the surgical device of FIG. 17.

DETAILED DESCRIPTION

FIG. 2(b) is a schematic diagram that illustrates some of the components of a surgical device 11, according to an example embodiment of the present invention. The surgical device 11 is configured so as to be particularly well-suited for insertion into the body of a patient, e.g., via a cannula

(not shown). In the embodiment shown, the surgical device **11** is a clamping, cutting and stapling device. The surgical device **11** includes a jaw portion **11a** that is pivotably coupled to a shaft portion **11b** by a hinge portion **11c**. The jaw portion **11a** includes a first jaw **50** having a distal end **50a** and a proximal end **50b**, and a second jaw **80** having a distal end **80a** and a proximal end **80b**. The first jaw **50** and the second jaw **80** are pivotably coupled relative to each other at or near their respective proximal ends **50b**, **80b**. In the example embodiment shown, the first jaw **50** and the second jaw **80** pivot relative to each other about pivot axis A, which is oriented perpendicular to the page.

As mentioned above, the jaw portion **11a** is pivotably coupled to the shaft portion **11b** by the hinge portion **11c**. Specifically, the jaw portion **11a** is pivotable relative to the shaft portion **11b** about a pivot axis B, which may be positioned at any location on or between the jaw portion **11a** and the shaft portion **11b**, and at any circumferential location relative to the jaw portion **11a** and the shaft portion **11b**. In the example embodiment shown, the pivot axis B is oriented vertically in the view shown, such that, upon articulation, the jaw portion **11a** pivots within a plane that is perpendicular to the page. It should be recognized that, in other example embodiments, the pivot axis B may have a different orientation, so as to enable the jaw portion **11a** to pivot within a different plane. The jaw portion **11a** may be pivotable to and between any angles relative to the shaft portion **11b**, such that the jaw portion **11a** can be selectively positioned as desired during use. Multiple pivot axes relative to the longitudinal axis of the shaft portion **11b** (the longitudinal axis of the shaft portion **11b** is designated as axis D in FIG. 2(b)) may be provided. For instance, in various embodiments, the jaw portion **11a** may be rotatable relative to the shaft portion **11b** about its longitudinal axis D, or may be rotatable relative to the shaft portion **11b** about multiple pivot axes that are perpendicular to the longitudinal axis D.

The shaft portion **11b** may include a distal portion **1101**, to which the jaw portion **11a** is connected, and a proximal portion **1102**. The proximal portion **1102** of the shaft portion **11b** may include a handle **1103**, with which a user may grasp the surgical device **11**. At a proximal-most end of the proximal portion **1102**, the shaft portion **11b** may include a connection element **1104**, e.g., a quick-connect coupling, for connecting to a flexible shaft (described in further detail below).

The second jaw **80** includes a clamping surface **106**. The second jaw **80** also includes a cutting and stapling element **104**, which may form at least part of the clamping surface **106** of the second jaw **80**. The first jaw **50** includes an anvil member **700** in opposed correspondence with the second jaw **80**. The anvil member **700** includes the clamping surface **108**, which, along with the clamping surface **106** of the second jaw **80**, clamps a section of tissue to be cut and stapled. As explained in greater detail below, the cutting and stapling element **104** is configured to cut and staple a section of tissue when the first jaw **50** and the second jaw **80** are in a closed, e.g., fully closed, position. Additional features of the cutting and stapling element **104**, according to an embodiment, are illustrated and described, for instance, in connection with FIGS. 3(f) and 3(g) below, and further in U.S. patent application Ser. No. 09/999,546, filed Nov. 30, 2001 (now U.S. Pat. No. 7,695,485), and Ser. No. 10/460,291, filed Jun. 11, 2003 (now U.S. Pat. No. 7,743,960), each of which, as set forth above, are hereby expressly incorporated herein by reference in its entirety.

Various drivers may be employed to drive the movements of the surgical device **11**, e.g., pivoting the jaw portion **11a**

relative to the shaft portion **11b**, rotating the jaw portion **11a** or some part thereof around its longitudinal axis relative to the shaft portion **11b**, pivoting the first jaw **50** relative to the second jaw **80**, firing of a staple cartridge, etc. According to one embodiment of the present invention, these functions are performed by connection of the surgical device **11** to a flexible shaft having two rotatable drive shafts, although it should be recognized that in other embodiments, different types and/or a different number of drive components **35** may be employed.

FIG. 2(b) illustrates schematically an embodiment wherein the surgical device **11** employs first and second drivers **88** and **98**, each of which is connected to a respective one of two rotatable drive shafts of a, e.g., flexible, drive shaft. For instance, a first driver **88** may, e.g., operate to move the first jaw **50** and the second jaw **80** relative to each other. The first driver **88** may include any type of drive mechanism capable of moving the first jaw **50** and the second jaw **80** relative to each other. The first driver **88** may be situated at least partially in the proximal end **80b** of the second jaw **80** and may be connected to the proximal end **50b** of the first jaw **50**. The first driver **88** may engage the proximal end **50b** of the first jaw **50** so as to open and close the first jaw **50** relative to the second jaw **80**. In addition, the first driver **88** may extend through the shaft portion **11b** of the surgical device **11** to a first drive socket **654**. The first drive socket **654** of the first driver **88** is coupled to a first motor **96** by a first drive shaft **94**. As will be explained in more detail below, the first driver **88**, when engaged by the first motor **96** via the first drive shaft **94**, may operate to open and close first jaw **50** relative to second jaw **80**, in addition to performing other operations of the surgical device **11**.

The second jaw **80** also includes a second driver **98**. The second driver **98** may also extend through the shaft portion **11b** of the surgical device **11** to a second drive socket **694**. The second drive socket **694** is coupled to a second motor **100** by a second drive shaft **102**. The second driver **98**, when engaged by the second motor **100** via the second drive shaft **102**, may operate to drive the cutting and stapling element **104** to cut and staple a section of tissue **52**, in addition to performing other operations of the surgical device **11**.

While two drive sockets, e.g., the first drive socket **654** and the second drive socket **694**, and two corresponding drive shafts, e.g., the first drive shaft **94** and the second drive shaft **102**, are illustrated as being part of the surgical device **11** and as being for the purposes of clamping, cutting and stapling a section of tissue, it is possible to provide any suitable number of drive sockets and drive shafts. For example, a single drive shaft may be provided to perform the above-described functions of the surgical device **11**.

In one embodiment, the two drive shafts, e.g., the first drive shaft **94** and the second drive shaft **102**, are also configured to be employed to move the jaw portion **11a** relative to the shaft portion **11b**. An example of this type of embodiment is illustrated in, e.g., FIGS. 3(a) through 3(e), and is described further below. Alternatively, and as shown in FIG. 2(b), the surgical device **11** may also include a third driver **201** and a fourth driver **202** that are employed to move the jaw portion **11a** relative to the shaft portion **11b**. For instance, the third driver **201** may be configured to pivot the jaw portion **11a** about axis B relative to the shaft portion **11b**, while the fourth driver **202** may be configured to rotate the jaw portion **11a** about its longitudinal axis D relative to the shaft portion **11b**. In one embodiment, the third and fourth drivers **201**, **202** are rotatable drive shafts that extend through the shaft portion **11b** of the surgical device **11** to third and fourth drive sockets **2011**, **2021**, respectively. The

third drive socket **2011** is coupled to a third motor **2013** by a third drive shaft **2012**. The third driver **201**, when engaged by the third motor **2013** via the third drive shaft **2012**, operates to pivot the jaw portion **11a** about axis B relative to the shaft portion **11b**. The fourth drive socket **2021** is coupled to a fourth motor **2023** by a fourth drive shaft **2022**. The fourth driver **202**, when engaged by the fourth motor **2023** via the fourth drive shaft **2022**, operates to rotate the jaw portion **11a** about its longitudinal axis D relative to the shaft portion **11b**.

The drive shafts, e.g., first and second rotatable drive shafts **94** and **102** and any other drive shafts, may be housed within a flexible drive shaft, such as the flexible drive shaft **1620** illustrated in FIG. **2(a)**. Other types of flexible drive shafts may also be employed. For instance, the drive shafts may be housed within a flexible drive shaft of the type described and illustrated in Applicant's co-pending Provisional Patent Application No. 60/703,227, which is expressly incorporated by reference herein in its entirety.

Referring to FIG. **2(b)**, the surgical device **11** may also include a memory module **6041**. In one embodiment, the memory module **6041** is connected to or integral with the cutting and stapling element **104**. The memory module **6041** is connected to a data connector **1272** by a data transfer cable **1278**. Additional features of these components are set forth in connection with FIGS. **3(f)** and **7**.

Furthermore, FIG. **2(b)** also illustrates a connection element **1104**. The connection element **1104** may include a quick connect sleeve **713** that has quick connect slots **713a** that engage complementary quick connect elements **1664** of a flexible drive shaft **1620**, which is described in further detail below. In order to retain the quick connect elements **1664** of the flexible drive shaft **1620** in the quick connect slots **713a** of the quick connect sleeve **713**, the connection element **1104** may also include a spring.

According to an example embodiment of the present invention, the surgical device **11** may be configured as an attachment to, or may be integral with, an electro-mechanical surgical system, such as the electro-mechanical driver component **1610** having a motor system illustrated in FIG. **2(a)**. It should be appreciated that, in this example embodiment, any appropriate number of motors may be provided, and the motors may operate via battery power, line current, a DC power supply, an electronically controlled DC power supply, etc. It should also be appreciated that the motors may be connected to a DC power supply, which is in turn connected to line current and which supplies the operating current to the motors. In another example embodiment, the surgical device may be an attachment to, or may be integral with, a mechanical driver system.

FIG. **3(a)** is a perspective view of a surgical device **11**, according to one embodiment of the present invention. As set forth above, FIGS. **3(a)** to **3(e)** illustrate one embodiment of the present invention in which two drive shafts are configured to be employed to move the jaw portion **11a** relative to the shaft portion **11b**, to rotate the jaw portion **11a** about its longitudinal axis, to move the first jaw **50** relative to the second jaw **80**, and to fire a stapling and cutting cartridge. In the position shown in FIG. **3(a)**, the jaw portion **11a** is positioned at an angle of approximately 60 degrees relative to the shaft portion **11b**. The jaw portion **11a** may be appropriately positioned according to the incision made in the patient and to the position of the tissue desired to be clamped, cut and stapled.

FIG. **3(b)** is a rear perspective view that illustrates some of the internal components of the surgical device **11**, according to an example embodiment of the present invention. The

outer body of the surgical device **11** is shown in ghost lines. As shown, the jaw portion **11a** is in an initial position in which it is axially aligned with the shaft portion **11b**.

FIG. **3(b)** shows a first rotatable drive shaft **500**, which may be axially rotatable within the shaft portion **11b**. Coupled to the first rotatable drive shaft **500** is a gear element **502**. The gear element **502** rotates about a longitudinal axis and is meshingly engaged with a gear element **504**. The gear element **504** is held in position by pin **505**, the central axis of which is coaxial with the pivot axis B around which the jaw portion **11a** pivots relative to the shaft portion **11b**.

The gear element **504** is also meshingly engaged with a gear element **506** within the jaw portion **11a**. The gear element **506** is connected to a gear element **510** by a shaft **508**. The gear element **506**, the gear element **510**, and the shaft **508** rotate within the jaw portion **11a** about a longitudinal axis defined by the central axis of the shaft **508**. The gear element **510** is meshingly engaged with a gear element **512** that rotates about a pin **513** that is longitudinally arranged within the jaw portion **11a**. The gear element **512** is meshingly engaged with a gear element **514**. The gear element **514** has a shaft portion that extends distally to a set of teeth **516**. The teeth **516** are selectively engageable with a correspondingly-shaped opening in a plate **518**, the plate **518** being keyed to an internal surface of the surgical device **11** so as to prevent relative rotation of the plate **518**. The plate **518** is moveable in an axial direction between a first position, in which the correspondingly-shaped opening in the plate **518** is locked in engagement with the teeth **516**, and a second position, in which the plate **518** is moved distally relative to the first position and the correspondingly-shaped opening in the plate **518** is not in engagement with the teeth **516**.

Extending distally from the gear **514** and the shaft portion carrying the teeth **516** is a threaded screw **520**. The threaded screw **520** is arranged longitudinally and is configured to rotate about a longitudinal axis when the gear **514** is rotated. Mounted on the threaded screw **520** is a push block **522**. The push block **522** is keyed to an internal surface of the surgical device **11**, so as to prevent relative rotation of the push block **522**. Rotatably coupled to the lower distal end of the push block **522** is a pair of rollers **524**. The pair of rollers **524** are seated within respective slots **5011** on each side of the upper jaw **50**. The upper jaw **50** and the slots **5011** are shown in dotted line in FIG. **3(b)**.

FIG. **3(b)** also shows a second rotatable drive shaft **550**, which may be axially rotatable within the shaft portion **11b**. Coupled to the second rotatable drive shaft **550** is a gear element **552**. The gear element **552** rotates about a longitudinal axis and is meshingly engaged with a gear element **554**. The gear element **554** is held in position by pin **505**, the central axis of which is coaxial with the pivot axis B around which the jaw portion **11a** pivots relative to the shaft portion **11b**.

The gear element **554** is also meshingly engaged with a gear element **556** within the jaw portion **11a**. The gear element **556** is connected to a gear element **560** by a shaft **558**. The gear element **556**, the gear element **560**, and the shaft **558** rotate within the jaw portion **11a** about a longitudinal axis defined by the central axis of the shaft **558**. The gear element **560** is meshingly engaged with a gear element **562a** that is mounted on a proximal end of the pin **513**. The gear element **562a** is configured to be non-rotatably mounted on, and thus to rotate with, the pin **513**, the pin **513** extending longitudinally within the jaw portion **11a**. In addition, a gear element **562b** is adapted to be

non-rotatably mounted on a distal end of the pin **513**. Thus, the gear element **562b** is also configured to rotate with the pin **513**.

The gear element **562b** has a shaft portion that extends distally and includes a set of teeth **5661** (hidden from view in FIG. **3(b)** but shown in FIG. **3(d)**). The teeth **5661** are selectively engageable with a correspondingly-shaped opening in the plate **518**. As set forth above, the plate **518** is keyed to an internal surface of the surgical device **11** so as to prevent relative rotation of the plate **518**, and is moveable in an axial direction between the first position, in which the correspondingly-shaped opening in the plate **518** is locked in engagement with the teeth **5661**, and the second position, in which the plate **518** is moved distally relative to the first position and the correspondingly-shaped opening in the plate **518** is not in engagement with the teeth **5661**.

The gear element **562b** is meshingly engaged with a gear element **564**. Extending distally from the gear **564** is a first longitudinal rod **566**. The first longitudinal rod **566** is attached to a second longitudinal rod **568**. The second longitudinal rod **568** has a shoulder **572**. Between the first longitudinal rod **566** and the shoulder **572** of the second longitudinal rod **568** is a spring. The distal end **574** of the second longitudinal rod **568** is configured to engage a respective opening in a wedge driver **605**. The wedge driver **605** rotates so as to drive a stapling/cutting wedge (described in further detail below) along a staple cartridge.

These components are also shown in various other views. For instance, FIG. **3(c)** is a side perspective view that illustrates some of the internal components of the surgical device **11**. As shown, the jaw portion **11a** is pivoted, e.g., articulated, relative to the shaft portion **11b**. In addition, FIG. **3(d)** is a perspective view that illustrates the jaw portion **11a** being further pivoted, e.g., articulated, relative to the shaft portion **11b**. Also, FIG. **3(e)** is a bottom perspective view that illustrates the jaw portion **11a** being pivoted, e.g., articulated, relative to the shaft portion **11b**.

As set forth above, the surgical device **11** may also include a cutting and stapling element **104**. In one embodiment, the staple and cutting element **104** is a staple cartridge. FIG. **3(f)** is an exploded view of a replaceable staple cartridge **600**. The replaceable staple cartridge **600** is one type of stapling/cutting arrangement that may be employed as the cutting and stapling element **104** in the example embodiment of the present invention illustrated in FIGS. **3(a)** to **3(e)**. The replaceable staple cartridge **600** includes a staple tray **604**. The staple tray **604** has a slot **6041** at its proximal end **604d** in which the memory module **6041** is retained by a memory module retainer **6042**. The memory module **6041** may store information as described, for example, in U.S. patent application Ser. No. 09/723,715, filed on Nov. 28, 2000, now issued as U.S. Pat. No. 6,793,652 on Sep. 21, 2004; U.S. patent application Ser. No. 09/836,781, filed on Apr. 17, 2001, now issued as U.S. Pat. No. 6,981,941 on Jan. 3, 2006; U.S. patent application Ser. No. 09/887,789, filed on Jun. 22, 2001, now issued as U.S. Pat. No. 7,032,798 on Apr. 25, 2006; and U.S. patent application Ser. No. 10/099,634, filed on Mar. 15, 2002, now issued as U.S. Pat. No. 7,951,071 on May 31, 2011, each of which is expressly incorporated herein by reference in its entirety. A wedge driver **605** is configured to be rotatably disposed through a central channel **604e** of the staple tray **604**. Specifically, the wedge driver **605** has a distal end **605a** that is configured to be rotatably mounted within a distal orifice **604a** of the staple tray **604**. The wedge driver **605** also includes an externally threaded region **605b**, a non-threaded portion **605c** that rotatably extends through a proximal orifice **604b** in the proximal end

604b of the staple tray **604**, and a proximally-facing opening **605d** at its proximal-most end for receiving the distal end **574** of the second longitudinal rod **568**. The proximally-facing opening **605d** and the distal end **574** of the second longitudinal rod **568** are adapted for non-rotatable coupling relative to each other when the distal end **574** of the second longitudinal rod **568** is received, e.g., inserted, within the proximally-facing opening **605d**.

The replaceable staple cartridge **600** also includes a wedge **603** having an internally threaded bore **603a**. The externally threaded region **605b** of the wedge driver **605** is configured to extend through the internally threaded bore **603a** of the wedge **603**. The threads of the internally threaded bore **603a** of the wedge **603** match the threads of the externally threaded region **605b** of the wedge driver **605**. As is discussed further below, upon rotation of the wedge driver **605**, the wedge **603** is moved between the distal end **604c** of the staple tray **604** and the proximal end **604d** of the staple tray **604** through a central channel **604e**.

The staple tray **604** also includes a plurality of vertically-disposed slots **604f** in opposing walls **604g** of the central channel **604e**. On each side of the central channel **604e**, a staple pusher **607** is configured to be slideably disposed within the slots **604f**. More specifically, each of the staple pushers **607** has a top surface **607a** running longitudinally between two rows **607b** of staple pushing fingers **607c**. The staple pushing fingers **607c** are configured such that each staple pushing finger **607c** in the row **607b** that abuts the wall **604g** of the staple tray **604** is retained within a corresponding slot **604f** of the wall **604g** so as to be vertically slideable therein. The staple pushing fingers **607c** are positioned over slots **604h** in the staple tray **604**. The slots **604h** in the staple tray **604** house a plurality of fasteners, e.g., staples **606**. Each of the staples **606** includes a butt **606a** and a pair of prongs **606b**.

The wedge **603** also includes a pair of sloped edges **603b** that slideably engage respective top surfaces **607a** of the staple pushers **607**. When the wedge **603** is moved from the distal end **604c** to the proximal end **604d** of the staple tray **604** through the central channel **604e**, the pair of sloped edges **603b** of the wedge **603** is configured to slideably engage the respective top surfaces **607a** of the staple pushers **607** in order to successively push the staple pushing fingers **607c** of the staple pushers **607** into, and thus the staples **606** out of, the slots **604h** in the staple tray **604**. A cartridge top **611** is configured to fit over the central channel **604a** of the staple tray **604**, while a staple retainer **610** is configured to cover the clamping surface **106** of the staple tray **604**. Additional features, e.g., a blade **51**, of the staple cartridge **600** are described below in connection with FIG. **3(g)**, these features being described during operation of the surgical device **11**.

FIG. **3(h)** is a bottom view of the first jaw **50**. The first jaw **50** includes an anvil member **700** having a longitudinally-disposed slot **701** that extends from a distal end to a proximal end of the anvil member **700**. The slot **701** is aligned with the blade **51** of the second jaw **80** so that the blade **51** extends into and travels along the slot **701** when the blade is moved from the distal end **80a** to the proximal end **80b** of the second jaw **80**. The anvil member **700** also includes a plurality of rows **702** of staple guides **703**. The staple guides **703** are configured to receive the prongs **606b** of the staples **606** and to bend the prongs **606b** so as to close the staples **606**. When the surgical device **11** is in the closed position, the rows **702** of the staple guides **703** align with the slots **604h** of the staple tray **604** in the second jaw **80**.

In operation, the jaw portion **11a** is maintained in an initial position in which it is axially aligned with the shaft portion **11b**, such as the position shown in FIG. **3(b)**. In this position, the surgical device **11** may be inserted, e.g., through a trocar, into a surgical site. Depending on the position of the incision and the tissue to be clamped, stapled and cut, the user may then articulate the jaw portion **11a** relative to the shaft portion **11b**.

In a first articulation process, the jaw portion **11a** is pivoted relative to the shaft portion **11b**. The plate **518** is arranged in its first position, e.g., such that the two openings in the plate **518** are locked in respective engagement with the teeth **516** of gear element **514** and with the teeth **5661** of the gear element **562b**. The first rotatable drive shaft **500** and the second rotatable drive shaft **550** are then rotated in opposite directions. For instance, referring to FIG. **3(b)**, in order to articulate the jaw portion **11a** in a clockwise direction relative to the shaft portion **11b** (when viewed from above), the first rotatable drive shaft **500** may be rotated in a counter-clockwise direction (for the sake of simplicity, all references herein to a rotational direction, e.g., clockwise or counterclockwise, refer to a view from the proximal end of the surgical device towards the distal end of the surgical device **11**, unless otherwise noted). The gear element **502** attached to the first rotatable drive shaft **500** is thus also caused to rotate in a counter-clockwise direction. By virtue of its engagement with the gear element **504**, the counter-clockwise rotation of the gear element **502** causes the gear element **504** to rotate in a counter-clockwise direction (when viewed from above) about the pin **505**. By virtue of its engagement with the gear element **506**, the counter-clockwise rotation of the gear element **504** causes the gear element **506** to rotate in a clockwise direction.

Simultaneously, the second rotatable drive shaft **550** may be rotated in a clockwise direction. The gear element **552** attached to the second rotatable drive shaft **550** is thus also caused to rotate in a clockwise direction. By virtue of its engagement with the gear element **554**, the clockwise rotation of the gear element **552** causes the gear element **554** to rotate in a counter-clockwise direction (when viewed from above) about the pin **505**. By virtue of its engagement with the gear element **556**, the clockwise rotation of the gear element **554** causes the gear element **556** to rotate in a counter-clockwise direction. The engagement of the plate **518** with the teeth **516** and **5661** prevents the rotation of the gear elements **506** and **566** relative to the surgical device **11**. Thus, the jaw portion **11a** is caused to rotate in a clockwise direction relative to the shaft portion **11b** (when viewed from above). To rotate the jaw portion **11a** in the opposite direction, e.g., counter-clockwise relative to the shaft portion **11b** when viewed from above, the direction of rotation of the first and second rotatable drive shafts **500**, **550** are reversed.

Once the jaw portion **11a** is rotated about the pin **505** to a desired position, the jaw portion **11a** may also be rotated, in a second articulation process, relative to the shaft portion **11b** about the longitudinal axis of the jaw portion **11a**, e.g., illustrated as axis **D**. The plate **518** is maintained in its first position, such that the two openings in the plate **518** are locked in respective engagement with the teeth **516** of gear element **514** and with the teeth **5661** of the gear element **562b**. The first rotatable drive shaft **500** and the second rotatable drive shaft **550** are then rotated in the same direction. For instance, referring to FIG. **3(b)**, in order to rotate the jaw portion **11a** about its longitudinal axis in a counter-clockwise direction relative to the shaft portion **11b**, the first rotatable drive shaft **500** may be rotated in a

counter-clockwise direction. The gear element **502** attached to the first rotatable drive shaft **500** is thus also caused to rotate in a counter-clockwise direction. By virtue of its engagement with the gear element **504**, the counter-clockwise rotation of the gear element **502** causes the gear element **504** to rotate in a counter-clockwise direction (when viewed from above) about the pin **505**. By virtue of its engagement with the gear element **506**, the counter-clockwise rotation of the gear element **504** causes the gear element **506** to rotate in a clockwise direction. Since the gear element **506** is attached to the gear element **510** by the shaft **508**, rotation of the gear element **506** in the clockwise direction causes the gear element **510** to also rotate in a clockwise direction. By virtue of its engagement with the gear element **512**, the clockwise rotation of the gear element **510** causes the gear element **512** to rotate in a counter-clockwise direction.

The second rotatable drive shaft **550** may also be rotated in a counter-clockwise direction. The gear element **552** attached to the second rotatable drive shaft **550** is thus also caused to rotate in a counter-clockwise direction. By virtue of its engagement with the gear element **554**, the counter-clockwise rotation of the gear element **552** causes the gear element **554** to rotate in a clockwise direction (when viewed from above) about the pin **505**. By virtue of its engagement with the gear element **556**, the clockwise rotation of the gear element **554** causes the gear element **556** to rotate in a clockwise direction. Since the gear element **556** is attached to the gear element **560** by the shaft **558**, rotation of the gear element **556** in the clockwise direction causes the gear element **560** to also rotate in a clockwise direction. By virtue of its engagement with the gear element **562a**, the clockwise rotation of the gear element **560** causes the gear element **562a** to rotate in a counter-clockwise direction. Also, since both the gear element **562a** and the gear element **562b** are adapted to be non-rotatably mounted to, e.g., keyed to, the pin **513**, the rotation of the gear element **562a** in a counter-clockwise direction also causes the gear element **562b** to rotate in a counter-clockwise direction.

Thus, the gear element **562b** and the gear element **512** rotate together in a counter-clockwise direction about their shared longitudinal axes, e.g., the central axis of the pin **513**. Since the plate **518** is maintained in its first position, the two openings in the plate **518** are locked in respective engagement with the teeth **516** of gear element **514** and with the teeth **5661** of the gear element **562b**. Thus, the rotation of the gear element **562b**, and of the gear element **512** in the counter-clockwise direction about the pin **513**, causes the gear element **514** and the gear element **564** to also rotate in a counter-clockwise direction about the pin **513**, the central axis of which is coaxial with the longitudinal axis **D** of the jaw portion **11a**. The gear element is connected to the screw **520**, on which is mounted the push block **522**. Since the push block **522** is keyed to the internal surface of the jaw portion **11a**, the rotation of the gear element **514** about the longitudinal axis **D** causes the jaw portion **11a** to rotate relative to the shaft portion **11b** about its longitudinal axis **D**.

Once the jaw portion **11a** is rotated relative to the shaft portion **11b** about its longitudinal axis **D** to a desired position, the jaws **50**, **80** may be opened so as to enable a section of tissue to be disposed therebetween. To perform this operation, the plate **518** is moved distally to its second position, such that the two openings in the plate **518** are not locked in respective engagement with either the teeth **516** of gear element **514** nor with the teeth **5661** of the gear element **562b**. The first rotatable drive shaft **500** is then rotated in a first direction while the second rotatable drive shaft **550** is

not rotated. For instance, referring to FIG. 3(b), in order to open the first jaw 50 relative to the second jaw 80, the first rotatable drive shaft 500 may be rotated in a counter-clockwise direction. The gear element 502 attached to the first rotatable drive shaft 500 is thus also caused to rotate in a counter-clockwise direction. By virtue of its engagement with the gear element 504, the counter-clockwise rotation of the gear element 502 causes the gear element 504 to rotate in a counter-clockwise direction (when viewed from above) about the pin 505. By virtue of its engagement with the gear element 506, the counter-clockwise rotation of the gear element 504 causes the gear element 506 to rotate in a clockwise direction. Since the gear element 506 is attached to the gear element 510 by the shaft 508, rotation of the gear element 506 in the clockwise direction causes the gear element 510 to also rotate in a clockwise direction. By virtue of its engagement with the gear element 512, the clockwise rotation of the gear element 510 causes the gear element 512 to rotate in a counter-clockwise direction. By virtue of its engagement with the gear element 514, the counter-clockwise rotation of the gear element 512 causes the gear element 514 to rotate in a clockwise direction. Since the plate 518 is moved to its second position, the gear element 512 rotates about the pin 513 without the pin 513 rotating.

The clockwise rotation of the gear element 514 causes rotation of the threaded screw 520 in a clockwise direction. In an initial stage of operation, e.g., when the surgical device 11 has first been inserted into a patient's body, the push block 522 is located in a distal-most position along the threaded screw 520. Rotation of the threaded screw 520 causes the push block 522, which is adapted to be non-rotatably mounted within, e.g., keyed to, an internal surface of the surgical device 11, to travel in a proximal direction. The proximal movement of the push block 522 causes the pair of rollers 524 to move proximally within their respective slots 5011 on each side of the upper jaw 50. When the push block 522 has moved to the proximal end of the threaded screw 520, the rollers 524 are positioned at a proximal end of the slots 5011, at which position the first jaw 50 is maximally opened relative to the second jaw 80.

Once the first and second jaws 50, 80 have been opened to a desired position relative to each other, the jaws 50, 80 are closed so as to clamp a section of tissue therebetween. Again, with the plate 518 in its second position, e.g., such that the two openings in the plate 518 are not locked in respective engagement with either the teeth 516 of gear element 514 nor with the teeth 5661 of the gear element 562b, the first rotatable drive shaft 500 is rotated in a second direction while the second rotatable drive shaft 550 is not rotated. For instance, referring to FIG. 3(b), in order to close the first jaw 50 relative to the second jaw 80, the first rotatable drive shaft 500 may be rotated in a clockwise direction. The gear element 502 attached to the first rotatable drive shaft 500 is thus also caused to rotate in a clockwise direction. By virtue of its engagement with the gear element 504, the clockwise rotation of the gear element 502 causes the gear element 504 to rotate in a clockwise direction (when viewed from above) about the pin 505. By virtue of its engagement with the gear element 506, the clockwise rotation of the gear element 504 causes the gear element 506 to rotate in a counter-clockwise direction. Since the gear element 506 is attached to the gear element 510 by the shaft 508, rotation of the gear element 506 in the counter-clockwise direction causes the gear element 510 to also rotate in a counter-clockwise direction. By virtue of its engagement with the gear element 512, the counter-clockwise rotation of the gear element 510 causes the gear element 512 to rotate

in a clockwise direction. By virtue of its engagement with the gear element 514, the clockwise rotation of the gear element 512 causes the gear element 514 to rotate in a counter-clockwise direction. Since the plate 518 is moved to its second position, the gear element 512 rotates about the pin 513 without the pin 513 rotating.

The counter-clockwise rotation of the gear element 514 causes rotation of the threaded screw 520 in a counter-clockwise direction. As set forth above, the push block 522 may be located in a proximal-most position along the threaded screw 520. Rotation of the threaded screw 520 causes the push block 522, which is keyed to an internal surface of the surgical device 11, to travel in a distal direction. The distal movement of the push block 522 causes the pair of rollers 524 to move distally within their respective slots 5011 on each side of the upper jaw 50. When the push block 522 has moved to the distal end of the threaded screw 520, the rollers 524 are positioned at a distal end of the slots 5011, at which position the first jaw 50 is maximally clamped against the second jaw 80. It should be noted that, while the opening and closing of the first and second jaws 50, 80 may occur in a simple scissor type fashion, in other embodiments, the first and second jaws 50, 80 may open and close in a different manner. An example of one such type of movement is described in additional detail below in connection with FIGS. 3(f) through 3(i).

Once a section of tissue has been clamped between the first and second jaws 50, 80, the section of tissue may be cut and stapled. It should be recognized that, while the present invention is illustrated as using both cutting and stapling elements, the surgical device 11 may employ only one such element, or else may employ a different type of surgical instrument. Before the surgical device 11 is inserted into a patient's body, a staple cartridge 578 is provided within the second jaw 80. In one embodiment, the surgical device 11 is a single use device, in which the staple cartridge is integral to the second jaw 80. Alternatively, the surgical device 11 may have a replaceable staple cartridge, e.g., replaceable staple cartridge 600 as illustrated in FIG. 3(f), thereby permitting the surgical device 11 to be used numerous times with different staple cartridges. In this embodiment, if the surgical device 11 is being used for the first time, the staple cartridge 600 may be pre-installed during manufacture and assembly of the surgical device 11, or else may be installed by the user just prior to using the surgical device 11. If the surgical device 11 is being used for the second or more time, the staple cartridge 600 may be installed by the user just prior to using the surgical device 11. When the staple cartridge 600 is inserted into the second jaw 80, the distal end 574 of the longitudinal rod 568 is received within the proximally facing opening 605d of the wedge driver 605.

To illustrate the cutting/stapling operation of the surgical device 11, reference is first made to FIG. 3(b). With the staple cartridge 600 installed within the second jaw 80 of the surgical device 11, the plate 518 is maintained in its second position, such that the two openings in the plate 518 are not locked in respective engagement with either the teeth 516 of gear element 514 nor with the teeth 5661 of the gear element 562b. The second rotatable drive shaft 550 is then rotated in a first direction while the first rotatable drive shaft 500 is not rotated. For instance, in order to cut and staple a section of tissue disposed between the first and second jaw 50, 80, the second rotatable drive shaft 550 may be rotated in a counter-clockwise direction. The gear element 552 attached to the second rotatable drive shaft 550 is thus also caused to rotate in a counter-clockwise direction. By virtue of its engagement with the gear element 554, the counter-clockwise

rotation of the gear element **552** causes the gear element **554** to rotate in a clockwise direction (when viewed from above) about the pin **505**. By virtue of its engagement with the gear element **556**, the clockwise rotation of the gear element **554** causes the gear element **556** to rotate in a clockwise direction. Since the gear element **556** is attached to the gear element **560** by the shaft **558**, rotation of the gear element **556** in the clockwise direction causes the gear element **560** to also rotate in a clockwise direction. By virtue of its engagement with the gear element **562a**, the clockwise rotation of the gear element **560** causes the gear elements **562a** and **562b** to rotate in a counter-clockwise direction. By virtue of its engagement with the gear element **564**, the counter-clockwise rotation of the gear element **562b** causes the gear element **564** to rotate in a clockwise direction. Since the plate **518** is moved to its second position, the gear element **562b** rotates with the pin **513** without the gear element **514** rotating.

The clockwise rotation of the gear element **564** causes rotation of the first longitudinal rod **566** along with the second longitudinal rod **568** in the clockwise direction. The spring **570** that resides between a distal end of the first longitudinal rod **566** and a shoulder **572** of the second longitudinal rod **568** functions to bias the second longitudinal rod **568** in a distal direction, thereby insuring that the distal end **574** of the second longitudinal rod **568** seats within its respective opening **605d** of the wedge driver **605**.

To further illustrate the cutting/stapling operation of the surgical device **11**, reference is next made to FIG. **3(g)**. FIG. **3(g)** is a cross-sectional view of the surgical device **11**, according to one embodiment of the present invention, in a fully closed position. In FIG. **3(g)**, the surgical device **11** is illustrated absent a section of tissue between the clamping surfaces **106**, **108** of the first and the second jaws **50**, **80**.

As illustrated in FIG. **3(g)**, the surgical device **11** is disposed within the second jaw **80**, and the cutting and stapling element **104** includes the replaceable staple cartridge **600** of FIG. **3(g)** that is replaceably mountable within the second jaw **80**. The replaceable staple cartridge **600**, which was shown in an exploded view in FIG. **3(f)**, is shown assembled and mounted within the second jaw **80** in FIG. **3(g)**.

As illustrated in FIG. **3(g)**, the wedge **603** has disposed thereon a blade **51** having a cutting edge **51a**. Alternatively, the cutting and stapling elements may be separately disposed. In the example embodiment illustrated in FIG. **3(g)**, the blade **51** has a tail region **654** with a contact face **653**. The blade **51** is rotatably coupled to the wedge **603** around pivot **51b** to allow the blade **51** to rotate between a first and a second position. FIG. **3(g)** illustrates the wedge **603** and the blade **51** in several positions, labeled as positions A to E, as the wedge **603** and the blade **51** travel from the distal end **604c** to the proximal end **604d** of the staple tray **604**.

In the position labeled A, the wedge **603** and the blade **51** are positioned at the distal end **604c** of the staple tray **604**. In the position labeled A, the wedge **603** and the blade **51** are housed within a housing **615** and the blade **51** is rotated relative to the wedge **603** so as to be in a retracted position, e.g., the cutting edge **51a** facing upwards and is not exposed. The contact face **653** initially faces the proximal end **604d** of the staple tray **604**.

In operation, rotation of the wedge driver **605** via the distal end **574** of the second longitudinal rod **568** causes the wedge **603** and the blade **51** to advance to the position labeled B, via. In the position labeled B, the wedge **603** and the blade **51** are positioned proximally relative to the distal end **604c** of the staple tray **604**. Specifically, in the position

labeled B, the wedge **603** and the blade **51** are positioned such that the contact face **653** of the blade **51** begins to contact an actuating lip **615a** of the housing **615**. As the contact face **653** of the blade **51** begins to contact the actuating lip **615a** of the housing **615**, the blade **51** begins to rotate relative to the wedge **603**.

Further rotation of the wedge driver **605** via the distal end **574** of the second longitudinal rod **568** causes the wedge **603** and the blade **51** to advance to the position labeled C. In the position labeled C, the wedge **603** and the blade **51** are positioned still further proximally relative to the distal end **604c** of the staple tray **604**.

Specifically, in the position labeled C, the wedge **603** and the blade **51** are positioned such that the contact face **653** of the blade **51** has fully contacted the actuating lip **615a** of the housing **615**. When the contact face **653** of the blade **51** has fully contacted the actuating lip **615a** of the housing **615**, the blade **51** is fully rotated relative to the wedge **603** such that the cutting edge **51a** of the blade **51** is in an extended position, e.g., the cutting edge **51a** faces the proximal end **604d** of the staple tray **604**.

Further rotation of the wedge driver **605** via the distal end **574** of the second longitudinal rod **568** causes the wedge **603** and the blade **51** to advance to the position labeled D. In the position labeled D, the wedge **603** and the blade **51** are positioned approximately at the midpoint between the distal end **604c** and the proximal end **604d** of the staple tray **604**. In the position labeled D, the blade **51** is maintained in the extended position having the cutting edge **51a** facing the proximal end **604d** of the staple tray **604** so as to cut a section of tissue (not shown) that is clamped between the first jaw **50** and the second jaw **80**.

Further rotation of the wedge driver **605** via the distal end **574** of the second longitudinal rod **568** causes the wedge **603** and the blade **51** to advance to the position labeled E. In the position labeled E, the wedge **603** and the blade **51** are positioned at the proximal end **604d** of the staple tray **604**. In the position labeled E, the blade **51** is still maintained in the extended position with the cutting edge **51a** facing the proximal end **604d** of the staple tray **604**. Here, however, the blade **51** is enclosed within a housing **616** so that the cutting edge **51a** is not exposed.

The staples **606** housed within the staple tray **604** may simultaneously be fired with the movement of the blade **51** from the proximal end **80b** to the distal end **80a** of the second jaw **80**. For instance, rotation of the wedge driver **605** via the distal end **574** of the second longitudinal rod **568** causes the wedge **603** to be moved through the central channel **604e** of the staple tray **604**. As the wedge **603** is moved from the distal end **604c** to the proximal end **604d** of the staple tray **604** through the central channel **604e**, the pair of sloped edges **603b** of the wedge **603** slideably engage the respective top surfaces **607a** of the staple pushers **607** and successively push the staple pushing fingers **607c** of the staple pushers **607** into, and thus the staples **606** out of, the slots **604h** in the staple tray **604**. When the surgical device **11** is in the closed position, the rows **702** of the staple guides **703** align with the slots **604h** of the staple tray **604** in the second jaw **80** so that the staples **606** maintained in the slots **604h** of the staple tray **604** are pushed by the staple pushing fingers **607c** of the staple pushers **607** into, and closed by, corresponding staple guides **703** of the anvil member **700**. The staple guides **703** receive the prongs **606b** of the staples **606** when the surgical device **11** is fired and bend the prongs **606b** so as to close the staples **606**, thereby stapling the section of tissue.

It should be recognized that, according to various embodiments of the present invention, the blade **51** and the wedge **603** may be moved in either a proximal or a distal direction in order to cut a section of tissue disposed between the first jaw **50** and the second jaw **80**. Furthermore, it should be recognized that, according to various embodiments of the present invention, any mechanical arrangement that is configured to move the blade **51** and the wedge **603** in order to cut and/or staple a section of tissue disposed between the first jaw **50** and the second jaw **80** may be employed.

As set forth above, while the opening and closing of the first and second jaws **50**, **80** may occur in a simple scissor type fashion, in other embodiments, the first and second jaws **50**, **80** may open and close in a different manner. An example of one such type of movement is described generally below in connection with FIGS. **3(i)** through **3(l)**. Further details and benefits of this type of movement are described in patent application Ser. No. 10/460,291, filed Jun. 11, 2003, which is expressly incorporated herein in its entirety by reference thereto. For the purposes of clarity, those components of the surgical device **11** that are located proximal to the gear element **514** and the gear element **564** are not shown. It should be understood that these gear elements **514**, **564** may be driven by the combination of drive components illustrated in FIGS. **3(a)** through **3(e)**, or by any other combination of driving components.

FIG. **3(i)** illustrates the first jaw **50** in an open position relative to the second jaw **80**. In this position, the push block **522** is at or near a proximal end of the threaded screw **520**, and the rollers **524** attached to the push block **522** are positioned at or near the proximal end of slots **5011** of the first jaw **50**. The first jaw **50** includes a pivot pin **5012**, which is engaged within a vertical slot **5013** of the second jaw **80**. The proximal ends **50b**, **80b** of the first and second jaws **50**, **80**, respectively, are biased apart from each other, such that, in the initial position shown in FIG. **3(i)**, the pin **5012** is positioned at the lower end of the slot **5013**.

Referring to FIG. **3(j)**, as the gear element **514** is rotated, the push block **522** moves distally to a first intermediate position of the threaded screw **520**, and the rollers **524** attached to the push block **522** are likewise moved distally to a first intermediate position within the slots **5011** of the first jaw **50**. In the position shown in FIG. **3(j)**, the pin **5012** has moved within the slot **5013** until it eventually is positioned at the upper end of the slot **5013**. In this manner, the distal ends **50a**, **80a** of the first and second jaws **50**, **80** are brought together prior to the first and second jaws **50**, **80** being fully clamped together.

Referring to FIG. **3(k)**, as the gear element **514** is further rotated, the push block **522** continues to move distally to a second intermediate position of the threaded screw **520**, and the rollers **524** attached to the push block **522** are likewise continued to move distally to a second intermediate position within the slots **5011** of the first jaw **50**. In the position shown in FIG. **3(k)**, the further clamping of the first and second jaws **50**, **80** cause the pin **5012** to again move within the slot **5013** until it is eventually positioned at the lower end of the slot **5013**. In this manner, the distal ends **50a**, **80a** of the first and second jaws **50**, **80** remain together while the proximal portions of the first and second jaws **50**, **80** are gradually clamped together. Continued distal movement of the push block **522** along the threaded screw **520** eventually places the surgical device **11** in the position illustrated in FIG. **3(l)**, in which the first and second jaws **50**, **80** are clamped together at both their distal ends **50a**, **80a** and their proximal ends **50b**, **80b**.

As set forth above, there are various different mechanisms that may be employed to move the first jaw **50** relative to the second jaw **80**. Irrespective of the mechanism employed for this purpose, it is generally desirable to use a mechanism that exerts a strong clamping force on a section of tissue that is disposed between the first jaw **50** and the second jaw **80**. FIG. **4(a)** is a perspective view of the surgical device **11**, according to another embodiment of the present invention, which employs a different mechanism for moving the first jaw **50** relative to the second jaw **80**.

FIG. **4(b)** is a perspective view that illustrates additional features of the second jaw **80** of the jaw portion **11a**. For the purpose of clarity, the first jaw **50** is shown in ghost lines. Specifically, FIG. **4(b)** illustrates portions of the first driver **88**, e.g., a horizontal driver element **301** that is connected to a first rotatable clamping element **302**. These and other features of the first driver **88**, according to this embodiment, are further illustrated in FIGS. **5(a)** to **5(d)**.

FIG. **5(a)** is a perspective view that illustrates the proximal end **80b** of the second jaw **80**. The proximal end **50b** of the first jaw **50** is shown in ghost lines. FIG. **5(a)** illustrates the surgical device **11** in a fully open position. In this embodiment, the first driver **88** includes a rotating shaft **303**. The first driver **88** also includes the horizontal driver element **301**. A proximal end of the horizontal driver element **301** is engaged by the rotating shaft **303**. A distal end of the horizontal driver element **301** includes an opening **3011**. The first driver **88** also includes a first rotatable clamping element **302**. The first rotatable clamping element **302** has a proximal end **3021**, a middle portion **3022** and a distal end **3023**.

The first driver **88** also includes a second rotatable clamping element **303**. The second rotatable clamping element **303** has a proximal end **3032** and a distal end **3031**. The proximal end of the first rotatable clamping element **302** is pivotably connected to the opening **3011** at the distal end of the horizontal driver element **301**. The middle portion **3022** of the first rotatable clamping element **302** is pivotably connected to the proximal end **3032** of the second rotatable clamping element **303**. The distal end **3021** of the first rotatable clamping element **302** is pivotably connected to the first jaw **50**. The distal end **3031** of the second rotatable clamping element **303** is pivotably connected to the second jaw **80**. Also, the proximal end **50b** of the first jaw **50** is pivotably connected to the proximal end **80b** of the second jaw **80** around pivot point A.

Upon engagement of the first driver **88**, the surgical device **11** is moved into a first partially closed position, as illustrated in FIG. **5(b)**. Specifically, upon engagement of the first motor **96**, the first drive shaft **94** causes rotation of the first drive socket **654** in a first direction. Rotation of the first drive socket **654** causes rotation of the rotating shaft **303** of the first driver **88**, which in turn causes the horizontal driver element **301** to move in a distal direction. It should be recognized that the components of the first driver **88**, while described in connection with this embodiment as including a rotating shaft **303**, may include some or all of the components described in connection with the embodiment illustrated in FIG. **3(a)** through **3(e)** as set forth above, or else may include any other arrangement of components suitable for moving the horizontal driver element **301** in a distal direction driving.

Still referring to FIG. **5(b)**, distal movement of the horizontal driver element **301** causes rotation of the first rotatable clamping element **302**, such that the distal end **3023** of the second rotatable clamping element **302** begins to move in a downward direction. The downward movement of the

distal end **3023** of the second rotatable clamping element **302**, by virtue of its pivotable attachment to the first jaw **50**, causes the first jaw **50** to rotate relative to the second jaw **80** around pivot point A into the partially closed position.

Upon further engagement of the first driver **88**, the surgical device **11** is moved into a second partially closed position, as illustrated in FIG. **5(c)**. Specifically, upon further engagement of the first motor **96**, the horizontal driver element **301** is caused to move in a still further distal direction via the rotation of the first drive shaft **94**, the first drive socket **654** and the rotating shaft **303** of the first driver **88**. Continued distal movement of the horizontal driver element **301** causes further rotation of the first rotatable clamping element **302**, such that the distal end **3023** of the second rotatable clamping element **302** continues to move in a downward direction. The continued downward movement of the distal end **3023** of the second rotatable clamping element **302**, by virtue of its pivotable attachment to the first jaw **50**, causes the first jaw **50** to rotate relative to the second jaw **80** around pivot point A into a nearly fully closed position.

Upon further engagement of the first driver **88**, the surgical device **11** is moved into a fully closed position, as illustrated in FIG. **5(d)**. Specifically, upon still further engagement of the first motor **96**, the horizontal driver element **301** is caused to move to a fully distal position via the rotation of the first drive shaft **94**, the first drive socket **654** and the rotating shaft **303** of the first driver **88**. In the fully distal position, the first rotatable clamping element **302** is fully rotated, such that the distal end **3023** of the first rotatable clamping element **302** is in a fully lowered position. In the fully lowered position, the distal end **3023** of the first rotatable clamping element **302** has moved the first jaw **50** around pivot point A to a fully closed position, such that a section of tissue **52** disposed between the first and second jaws **50**, **80** is fully clamped between the first and second jaws **50**, **80**.

According to an example embodiment of the present invention, the surgical device **11** may be configured as an attachment to, or may be integral with, a purely mechanical device driver system, such as that illustrated in FIG. **1**. In another embodiment, the surgical device **11** may be configured as an attachment to, or may be integral with, an electro-mechanical surgical system, such as an electro-mechanical driver system **1610** illustrated in FIG. **2(a)**.

Specifically, FIG. **2(a)** is a perspective view of an example embodiment of an electro-mechanical driver component **1610** according to the present invention. Such an electro-mechanical surgical system is described in, e.g., U.S. patent application Ser. No. 09/723,715, filed on Nov. 28, 2000, now issued as U.S. Pat. No. 6,793,652 on Sep. 21, 2004, U.S. patent application Ser. No. 09/836,781, filed on Apr. 17, 2001, now issued as U.S. Pat. No. 6,981,941 on Jan. 3, 2006; U.S. patent application Ser. No. 09/887,789, filed on Jun. 22, 2001, now issued as U.S. Pat. No. 7,032,798 on Apr. 25, 2006; and U.S. patent application Ser. No. 10/099,634, filed on Mar. 15, 2002, now issued as U.S. Pat. No. 7,951,071 on May 31, 2011, each of which is expressly incorporated herein in their entirety by reference thereto. The electro-mechanical driver component **1610** may include, for example, a remote power console **1612**, which includes a housing **1614** having a front panel **1615**. Mounted on the front panel **1615** are a display device **1616** and indicators **1618a**, **1618b**. A flexible shaft **1620** may extend from the housing **1614** and may be detachably attached thereto via a first coupling **1622**. The distal end **1624** of flexible shaft **1620** may include a second coupling **1626** adapted to

detachably couple, e.g., the surgical device **11** described above, to the distal end **1624** of the flexible shaft **1620**. The second coupling **1626** may also be adapted to detachably attach a different surgical instrument or attachment. In another example embodiment, the distal end **1624** of the flexible shaft **1620** may permanently attach to or be integral with a surgical instrument.

FIGS. **6(a)** through **6(e)** illustrate, according to one embodiment of the present invention, an arrangement of couplings and flexible shaft that may be employed in order to connect the surgical device **11** to the electro-mechanical drive component **1610**. For instance, FIG. **6(a)** illustrates a flexible shaft **2620** that extends from the housing **1614** that is detachably attached thereto via a first coupling **2622**. The distal end **2624** of flexible shaft **2620** may include a second coupling **2626** adapted to detachably couple, e.g., the surgical device **11** described above, to the distal end **2624** of the flexible shaft **2620**. FIG. **6(b)** illustrates a rear perspective view of the first coupling **2622**, according to one embodiment of the present invention. FIG. **6(c)** illustrates a front perspective view of the first coupling **2622**, according to the embodiment shown in FIG. **6(b)**. FIG. **6(d)** is a side perspective view of some of the internal components of the first coupling **2622**. FIG. **6(e)** is a rear perspective view of the second coupling **2626** at the distal end **2624** of the flexible shaft **2620**, according to one embodiment of the present invention. For the purposes of clarity, the flexible shaft **2620** is shown in FIG. **6(e)** as ghost lines. Additional features of these components are further described in Applicant's co-pending patent application Ser. No. 60/703,227.

While the combination of the flexible shaft **2620** and couplings **2622**, **2626** provide one arrangement by which the surgical device **11** may be attached to the electro-mechanical power console **1610**, any suitable arrangement may be employed. For instance, FIGS. **7** through **10** illustrate another arrangement by which the surgical device **11** may be attached to the electro-mechanical power console **1610**. Referring to FIG. **7**, there is seen a side view, partially in section, of the flexible shaft **1620**. According to an example embodiment, the flexible shaft **1620** includes a tubular sheath **1628**, which may include a coating or other sealing arrangement configured to provide a fluid-tight seal between the interior channel **1640** thereof and the environment. The sheath **1628** may be formed of a tissue-compatible, sterilizable elastomeric material. The sheath **1628** may also be formed of a material that is autoclavable. Disposed within the interior channel **1640** of the flexible shaft **1620**, and extending along the entire length thereof, may be a first rotatable drive shaft **94**, a second rotatable drive shaft **102**, a first steering cable **1634**, a second steering cable **1635**, a third steering cable **1636**, a fourth steering cable **1637** and a data transfer cable **1638**. FIG. **8** is a cross-sectional view of the flexible shaft **1620** taken along the line **8-8** illustrated in FIG. **7** and further illustrates the several cables **94**, **102**, **1634**, **1635**, **1636**, **1637** and **1638**. Each distal end of the steering cables **1634**, **1635**, **1636**, **1637** is affixed to the distal end **1624** of the flexible shaft **1620**. Each of the several cables **94**, **102**, **1634**, **1635**, **1636**, **1637**, **1638** may be contained within a respective sheath.

The first rotatable drive shaft **94** and the second rotatable drive shaft **102** may be configured, for example, as highly flexible drive shafts, such as, for example, braided or helical drive cables. It should be understood that such highly flexible drive cables may have limited torque transmission characteristics and capabilities. It should also be understood that the surgical device **11**, or other attachments connected to the flexible shaft **1620**, may require a higher torque input

than the torque transmittable by the drive shafts **94, 102**. The drive shafts **94, 102** may thus be configured to transmit low torque but high speed, the high-speed/low-torque being converted to low-speed/high-torque by gearing arrangements disposed, for example, at the distal end and/or the proximal end of the drive flexible shaft **1620**, in the surgical instrument or attachment and/or in the remote power console **1612**. It should be appreciated that such gearing arrangement(s) may be provided at any suitable location along the power train between the motors disposed in the housing **1614** and the attached surgical instrument or other attachment connected to the flexible shaft **1620**. Such gearing arrangement(s) may include, for example, a spur gear arrangement, a planetary gear arrangement, a harmonic gear arrangement, cycloidal drive arrangement, an epicyclic gear arrangement, etc.

Referring now to FIG. **9**, there is seen a rear end view of first coupling **1622**. The first coupling **1622** includes a first connector **1644**, a second connector **1648**, a third connector **1652** and a fourth connector **1656**, each rotatably secured to the first coupling **1622**. Each of the connectors **1644, 1648, 1652, 1656** includes a respective recess **1646, 1650, 1654, 1658**. As illustrated in FIG. **9**, each recess **1646, 1650, 1654, 1658** may be hexagonally shaped. It should be appreciated, however, that the recesses **1646, 1650, 1654, 1658** may have any shape and configuration adapted to non-rotatably couple and rigidly attach the connectors **1644, 1648, 1652, 1656** to respective drive shafts of the motor arrangement contained within the housing **1614**. It should be appreciated that complementary projections may be provided on respective drive shafts of the motor arrangement to thereby drive the drive elements of the flexible shaft **1620**. It should also be appreciated that the recesses may be provided on the drive shafts and complementary projections may be provided on the connectors **1644, 1648, 1652, 1656**. Any other coupling arrangement configured to non-rotatably and releasably couple the connectors **1644, 1648, 1652, 1656** and the drive shafts of the motor arrangement may be provided.

One of the connectors **1644, 1648, 1652, 1656** is non-rotatably secured to the first drive shaft **94**, and another one of the connectors **1644, 1648, 1652, 1656** is non-rotatably secured to the second drive shaft **102**. The remaining two of the connectors **1644, 1648, 1652, 1656** engage with transmission elements configured to apply tensile forces on the steering cables **1634, 1635, 1636, 1637** to thereby steer the distal end **1624** of the flexible shaft **1620**. The data transfer cable **1638** is electrically and logically connected with data connector **1660**. The data connector **1660** includes, for example, electrical contacts **1662**, corresponding to and equal in number to the number of individual wires contained in the data cable **1638**. The first coupling **1622** includes a key structure **1642** configured to properly orient the first coupling **1622** to a mating and complementary coupling arrangement disposed on the housing **1612**. The key structure **1642** may be provided on either one, or both, of the first coupling **1622** and the mating and complementary coupling arrangement disposed on the housing **1612**. The first coupling **1622** may include a quick-connect type connector, which may engage the first coupling **1622** to the housing **1612** by a simple pushing motion. Seals may be provided in conjunction with any of the several connectors **1644, 1648, 1652, 1656, 1660** to provide a fluid-tight seal between the interior of first coupling **1622** and the environment.

Referring now to FIG. **10**, there is seen a front end view of the second coupling **1626** of the flexible shaft **1620**. In the example embodiment, the second coupling **1626** includes a first connector **1666** and a second connector **1668**, each

rotatably secured to the second coupling **1626** and each non-rotatably secured to a distal end of a respective one of the first and second drive shafts **94, 102**. A quick-connect type fitting **1664** is provided on the second coupling **1626** to detachably secure the device **11** thereto. The quick-connect type fitting **1664** may be, for example, a rotary quick-connect type fitting, a bayonet type fitting, etc. and may be a fitting complementary to the quick connect sleeve **713** illustrated in FIG. **2(b)**. A key structure **1674** may be provided on the second coupling **1626** and may be configured to properly align the surgical device **11** to the second coupling **1626**. The key structure or other arrangement configured to properly align the surgical device **11** to the flexible shaft **1620** may be provided on either one, or both, of the second coupling **1626** and the surgical device **11**. In addition, the key structure may be provided on the device **11**, as illustrated in FIG. **2(b)** as the slots **713a** of the quick connect sleeve **713**. A data connector **1670** having electrical contacts **1672** is also provided in the second coupling **1626**. Like the data connector **1660** of first coupling **1622**, the data connector **1670** of the second coupling **1626** includes contacts **1672** electrically and logically connected to the respective wires of the data transfer cable **1638** and the contacts **1662** of the data connector **1660**. Seals may be provided in conjunction with the connectors **1666, 1668, 1670** to provide a fluid-tight seal between the interior of the second coupling **1626** and the environment.

Disposed within the housing **1614** of the remote power console **1612** are electro-mechanical driver elements configured to drive the drive shafts **94, 102** and the steering cables **1634, 1635, 1636, 1637** to thereby operate the electro-mechanical driver component **1610** and the surgical device **11** attached to the second coupling **1626**. In the example embodiment illustrated schematically in FIG. **19**, five electric motors **96, 100, 1684, 1690, 1696**, each operated via a power source, may be disposed in the remote power console **1612**. It should be appreciated, however, that any appropriate number of motors may be provided, and the motors may operate via battery power, line current, a DC power supply, an electronically controlled DC power supply, etc. It should also be appreciated that the motors may be connected to a DC power supply, which is in turn connected to line current and which supplies the operating current to the motors.

FIG. **11** illustrates schematically one possible arrangement of motors. An output shaft **1678** of a first motor **96** engages with the first connector **1644** of the first coupling **1622** when the first coupling **1622**, and, therefore, the flexible shaft **1620**, is engaged with the housing **1614** to thereby drive the first drive shaft **94** and the first connector **1666** of the second coupling **1626**. Similarly, an output shaft **1682** of a second motor **100** engages the second connector **1648** of the first coupling **1622** when the first coupling **1622**, and, therefore, flexible shaft **1620** is engaged with the housing **1614** to thereby drive the second drive shaft **102** and the second connector **1668** of the second coupling **1626**. An output shaft **1686** of a third motor **1684** engages the third connector **1652** of the first coupling **1622** when the first coupling **1622**, and, therefore, the flexible shaft **1620**, is engaged with the housing **1614** to thereby drive the first and second steering cables **1634, 1635** via a first pulley arrangement **1688**. An output shaft **1692** of a fourth motor **1690** engages the fourth connector **1656** of the first coupling **1622** when the first coupling **1622**, and, therefore, the flexible shaft **1620**, is engaged with the housing **1614** to thereby drive the third and fourth steering cables **1636, 1637** via a second pulley arrangement **1694**. The third and fourth

motors **1684**, **1690** may be secured on a carriage **1100**, which is selectively movable via an output shaft **1698** of a fifth motor **1696** between a first position and a second position to selectively engage and disengage the third and fourth motors **1684**, **1690** with the respective pulley arrangement **1688**, **1694** to thereby permit the flexible shaft **1620** to become taut and steerable or limp as necessary. It should be appreciated that other mechanical, electrical and/or electro-mechanical mechanisms, etc., may be used to selectively engage and disengage the steering mechanism. The motors may be arranged and configured as described, for example, in U.S. patent application Ser. No. 09/510,923, entitled "A Carriage Assembly for Controlling a Steering Wire Mechanism Within a Flexible Shaft," now issued as U.S. Pat. No. 6,517,565 on Feb. 11, 2003, which is expressly incorporated herein in its entirety by reference thereto. It should also be appreciated that, in accordance with other embodiments of the present invention, the steering mechanism may not be present at all, the surgical device **11** providing articulation between the jaw portion **11a** and the shaft portion **11b** so as to maneuver the surgical device **11** within a surgical site.

It should be appreciated that any one or more of the motors **96**, **100**, **1684**, **1690**, **1696** may be, for example, a high-speed/low-torque motor, a low-speed/high-torque motor, etc. As indicated above, the first rotatable drive shaft **94** and the second rotatable drive shaft **102** may be configured to transmit high speed and low torque. Thus, the first motor **96** and the second motor **100** may be configured as high-speed/low-torque motors. Alternatively, the first motor **96** and the second motor **100** may be configured as low-speed/high-torque motors with a torque-reducing/speed-increasing gear arrangement disposed between the first motor **96** and the second motor **100** and a respective one of the first rotatable drive shaft **94** and the second rotatable drive shaft **102**. Such torque-reducing/speed-increasing gear arrangements may include, for example, a spur gear arrangement, a planetary gear arrangement, a harmonic gear arrangement, cycloidal drive arrangement, an epicyclic gear arrangement, etc. It should be appreciated that any such gear arrangement may be disposed within the remote power console **1612** or in the proximal end of the flexible shaft **1620**, such as, for example, in the first coupling **1622**. It should be appreciated that the gear arrangement(s) may be provided at the distal and/or proximal ends of the first rotatable drive shaft **94** and/or the second rotatable drive shaft **102** to prevent windup and breakage thereof.

Referring now to FIG. **12**, there is seen a schematic view of the electro-mechanical driver component **1610**. A controller **1122** is provided in the housing **1614** of remote power console **1612** and is configured to control all functions and operations of the electro-mechanical driver component **1610** and the linear clamping, cutting and stapling device **11** or other surgical instrument or attachment attached to the flexible shaft **1620**. A memory unit **1130** is provided and may include memory devices, such as, a ROM component **1132**, a RAM component **1134**, etc. The ROM component **1132** is in electrical and logical communication with the controller **1122** via a line **1136**, and the RAM component **1134** is in electrical and logical communication with controller **1122** via line **1138**. The RAM component **1134** may include any type of random-access memory, such as, for example, a magnetic memory device, an optical memory device, a magneto-optical memory device, an electronic memory device, etc. Similarly, the ROM component **1132** may include any type of read-only memory, such as, for example, a removable memory device, such as a PC-Card or PCMCIA-type device. It should be appreciated that the

ROM component **1132** and the RAM component **1134** may be configured as a single unit or may be separate units and that the ROM component **1132** and/or the RAM component **1134** may be provided in the form of a PC-Card or PCMCIA-type device.

The controller **1122** is further connected to the front panel **1615** of the housing **1614** and, more particularly, to the display device **1616** via a line **1154** and the indicators **1618a**, **1618b** via respective lines **1156**, **1158**. The lines **1116**, **1118**, **1124**, **1126**, **1128** electrically and logically connect controller **1122** to first, second, third, fourth and fifth motors **96**, **100**, **1684**, **1690**, **1696**, respectively. A wired remote control unit ("RCU") **1150** is electrically and logically connected to the controller **1122** via a line **1152**. A wireless RCU **1148** is also provided and communicates via a wireless link **1160** with a receiving/sending unit **1146** connected via a line **1144** to a transceiver **1140**. The transceiver **1140** is electrically and logically connected to the controller **1122** via a line **1142**. The wireless link **1160** may be, for example, an optical link, such as an infrared link, a radio link or any other form of wireless communication link.

A switch device **1186**, which may include, for example, an array of DIP switches, may be connected to the controller **1122** via a line **1188**. The switch device **1186** may be configured, for example, to select one of a plurality of languages used in displaying messages and prompts on the display device **1616**. The messages and prompts may relate to, for example, the operation and/or the status of the electro-mechanical driver component **1610** and/or to the surgical device **11** attached thereto.

According to the example embodiment of the present invention, a first encoder **1106** is provided within the second coupling **1626** and is configured to output a signal in response to and in accordance with the rotation of the first drive shaft **94**. A second encoder **1108** is also provided within the second coupling **626** and is configured to output a signal in response to and in accordance with the rotation of the second drive shaft **102**. The signal output by each of the encoders **1106**, **1108** may represent the rotational position of the respective drive shaft **94**, **102** as well as the rotational direction thereof. These encodes may be an arrangement of light sources, e.g., LEDs, and optical fibers as illustrated for instance in FIG. **6(e)**. Alternatively, such encoders **1106**, **1108** may include, for example, Hall-effect devices, optical devices, etc. Although the encoders **1106**, **1108** are described as being disposed within the second coupling **1626**, it should be appreciated that the encoders **1106**, **1108** may be provided at any location between the motor system and the surgical device **11**. It should be appreciated that providing the encoders **1106**, **1108** within the second coupling **1626** or at the distal end of the flexible shaft **1620** may provide an accurate determination of the drive shaft rotation. If the encoders **1106**, **1108** are disposed at the proximal end of the flexible shaft **1620**, windup of the first and second rotatable drive shafts **94**, **102** may result in measurement error.

FIG. **13** is a schematic view of an encoder **1106**, **1108**, which includes a Hall-effect device. Mounted non-rotatably on the drive shaft **94**, **102** is a magnet **1240** having a north pole **1242** and a south pole **1244**. The encoder **1106**, **1108** further includes a first sensor **1246** and second sensor **1248**, which are disposed approximately 90.degree. apart relative to the longitudinal, or rotational, axis of the drive shaft **94**, **102**. The output of the sensors **1246**, **1248** is persistent and changes its state as a function of a change of polarity of the magnetic field in the detection range of the sensor. Thus, based on the output signal from the encoders **1106**, **1108**, the

angular position of the drive shaft **94, 102** may be determined within one-quarter revolution and the direction of rotation of the drive shaft **94, 102** may be determined. The output of each encoder **1106, 1108** is transmitted via a respective line **1110, 1112** of data transfer cable **1638** to controller **1122**. The controller **1122**, by tracking the angular position and rotational direction of the drive shafts **94, 102** based on the output signal from the encoders **1106, 1108**, may thereby determine the position and/or state of the components of the surgical device connected to the electro-mechanical driver component **1610**. That is, by counting the revolutions of the drive shaft **94, 102**, the controller **1122** may determine the position and/or state of the components of the surgical device connected to the electro-mechanical driver component **1610**.

For example, the advancement distance of the first jaw **50** relative to the second jaw **80** and of the wedge **603** may be functions of, and ascertainable on the basis of, the rotation of the respective drive shafts **94, 102**. By ascertaining an absolute position of the first jaw **50** and the wedge **603** at a point in time, the relative displacement of the first jaw **50** and the wedge **603**, based on the output signal from the encoders **1106, 1108** and the known pitches of the threaded screw **520** and of the wedge driver **605**, may be used to ascertain the absolute position of the first jaw **50** and the wedge **603** at all times thereafter. The absolute position of the first jaw **50** and the wedge **603** may be fixed and ascertained at the time that the surgical device **11** is first coupled to the flexible shaft **1620**. Alternatively, the position of the first jaw **50** and the wedge **603** relative to, for example, the second jaw **80** may be determined based on the output signal from the encoders **1106, 1108**.

As discussed above in connection with FIGS. **2(b)** and **10**, the surgical device **11** may include a data connector **1272** adapted by size and configuration to electrically and logically connect to connector **1670** of second coupling **1626**. In the example embodiment, the data connector **1272** includes contacts **1276** equal in number to the number of contacts **1672** of connector **1670**. The memory module **6041** is electrically and logically connected with the data connector **1272**. Memory module **6041** may be in the form of, for example, an EEPROM, EPROM, etc. and may be contained, for example, within the staple tray **604** of the replaceable staple cartridge **600** in the second jaw **80** of the surgical device **11**, as illustrated in FIG. **3(f)**.

FIG. **14** schematically illustrates the memory module **6041**. As seen in FIG. **14**, data connector **1272** includes contacts **1276**, each electrically and logically connected to the memory module **6041** via a respective line, e.g., flexible data cable **1278**. The memory module **6041** may be configured to store, for example, a serial number data **1180**, an attachment type identifier (ID) data **1182** and a usage data **1184**. The memory module **6041** may additionally store other data. Both the serial number data **1180** and the ID data **1182** may be configured as read-only data. The serial number data **1180** and/or the ID data **1182** may be stored in a read-only section of the memory module **6041**. In the example embodiment, serial number data **1180** may be data uniquely identifying the particular surgical device, whereas the ID data **1182** may be data identifying the type of the attachment, such as, e.g., for an electro-mechanical driver component **1610** to which other types of surgical instruments or attachments are attachable. The usage data **1184** represents usage of the particular attachment, such as, for example, the number of times the first jaw **50** of the surgical device **11** has been opened and closed, or the number of times that the wedge **603** of the surgical device **11** has been

advanced. The usage data **1184** may be stored in a read/write section of the memory module **6041**.

It should be appreciated that the attachment attachable to the distal end **1624** of the flexible shaft **1620**, e.g., surgical device **11**, may be designed and configured to be used a single time or multiple times. The attachment may also be designed and configured to be used a predetermined number of times. Accordingly, the usage data **1184** may be used to determine whether the surgical device **11** has been used and whether the number of uses has exceeded the maximum number of permitted uses. As more fully described below, an attempt to use the attachment after the maximum number of permitted uses has been reached will generate an ERROR condition.

Referring again to FIG. **12**, the controller **1122** is configured to read the ID data **1182** from the memory module **6041** of the surgical device **11** when the surgical device **11** is initially connected to the flexible shaft **1620**. The memory module **6041** is electrically and logically connected to the controller **1122** via the line **1120** of the data transfer cable **1638**. Based on the read ID data **1182**, the controller **1122** is configured to read or select from the memory unit **1130**, an operating program or algorithm corresponding to the type of surgical instrument or attachment connected to the flexible shaft **1620**. The memory unit **1130** is configured to store the operating programs or algorithms for each available type of surgical instrument or attachment, the controller **1122** selecting and/or reading the operating program or algorithm from the memory unit **1130** in accordance with the ID data **1182** read from the memory module **6041** of an attached surgical instrument or attachment. As indicated above, the memory unit **1130** may include a removable ROM component **1132** and/or RAM component **1134**. Thus, the operating programs or algorithms stored in the memory unit **1130** may be updated, added, deleted, improved or otherwise revised as necessary. The operating programs or algorithms stored in the memory unit **1130** may be customizable based on, for example, specialized needs of the user. A data entry device, such as, for example, a keyboard, a mouse, a pointing device, a touch screen, etc., may be connected to the memory unit **1130** via, for example, a data connector port, to facilitate the customization of the operating programs or algorithms. Alternatively or additionally, the operating programs or algorithms may be customized and preprogrammed into the memory unit **1130** remotely from the electro-mechanical driver component **1610**. It should be appreciated that the serial number data **1180** and/or usage data **1184** may also be used to determine which of a plurality of operating programs or algorithms is read or selected from the memory unit **1130**. It should be appreciated that the operating program or algorithm may alternatively be stored in the memory module **6041** of the surgical device **11** and transferred to the controller **1122** via the data transfer cable **1638**. Once the appropriate operating program or algorithm is read by or selected by or transmitted to, the controller **1122**, the controller **1122** causes the operating program or algorithm to be executed in accordance with operations performed by the user via the wired RCU **1150** and/or the wireless RCU **1148**. As indicated hereinabove, the controller **1122** is electrically and logically connected with the first, second, third, fourth and fifth motors **96, 100, 1684, 1690, 1696** via respective lines **1116, 1118, 1124, 1126, 1128** and is configured to control such motors **96, 100, 1684, 1690, 1696** in accordance with the read, selected or transmitted operating program or algorithm via the respective lines **1116, 1118, 1124, 1126, 1128**.

Referring now to FIG. 15, there is seen a schematic view of wireless RCU 1148. Wireless RCU 1148 includes a steering controller 1300 having a plurality of switches 1302, 1304, 1306, 1308 arranged under a four-way rocker 1310. The operation of switches 1302, 1304, via rocker 1310, controls the operation of first and second steering cables 1634, 1635 via third motor 1684. Similarly, the operation of switches 1306, 1308, via rocker 1310, controls the operation of third and fourth steering cables 1636, 1637 via fourth motor 1692. It should be appreciated that rocker 1310 and switches 1302, 1304, 1306, 1308 are arranged so that the operation of switches 1302, 1304 steers the flexible shaft 1620 in the north-south direction and that the operation of switches 1306, 1308 steers the flexible shaft 1620 in the east-west direction. Reference herein to north, south, east and west is made to a relative coordinate system. Alternatively, a digital joystick, an analog joystick, etc. may be provided in place of rocker 1310 and switches 1302, 1304, 1306, 1308. Potentiometers or any other type of actuator may also be used in place of switches 1302, 1304, 1306, 1308.

The wireless RCU 1148 further includes a steering engage/disengage switch 1312, the operation of which controls the operation of fifth motor 696 to selectively engage and disengage the steering mechanism. The wireless RCU 1148 also includes a two-way rocker 1314 having first and second switches 1316, 1318 operable thereby. The operation of these switches 1316, 1318 controls certain functions of the electro-mechanical driver component 1610 and any surgical instrument or attachment, such as the surgical device 11, attached to the flexible shaft 1620 in accordance with the operating program or algorithm corresponding to the attached device. For example, operation of the two-way rocker 1314 may control the opening and closing of the first jaw 50 and the second jaw 80 of the surgical device 11. The wireless RCU 1148 is provided with yet another switch 1320, the operation of which may further control the operation of the electro-mechanical driver component 1610 and the device attached to the flexible shaft 1620 in accordance with the operating program or algorithm corresponding to the attached device. For example, operation of the switch 1320 may initiate the advancement of the wedge 603 of the surgical device 11.

The wireless RCU 1148 includes a controller 1322, which is electrically and logically connected with the switches 1302, 1304, 1306, 1308 via line 1324, with the switches 1316, 1318 via line 1326, with switch 1312 via line 1328 and with switch 1320 via line 1330. The wireless RCU 1148 may include indicators 1618a', 1618b', corresponding to the indicators 1618a, 1618b of front panel 1615, and a display device 1616', corresponding to the display device 1616 of the front panel 1615. If provided, the indicators 1618a', 1618b' are electrically and logically connected to controller 1322 via respective lines 1332, 1334, and the display device 1616' is electrically and logically connected to controller 1322 via line 1336. The controller 1322 is electrically and logically connected to a transceiver 1338 via line 1340, and the transceiver 1338 is electrically and logically connected to a receiver/transmitter 1342 via line 1344. A power supply, for example, a battery, may be provided in wireless RCU 1148 to power the same. Thus, the wireless RCU 1148 may be used to control the operation of the electro-mechanical driver component 1610 and the device 11 attached to the flexible shaft 1620 via wireless link 1160.

The wireless RCU 1148 may include a switch 1346 connected to a controller 1322 via line 1348. Operation of the switch 1346 transmits a data signal to the transmitter/

receiver 1146 via wireless link 1160. The data signal includes identification data uniquely identifying the wireless RCU 1148. This identification data is used by the controller 1122 to prevent unauthorized operation of the electro-mechanical driver component 1610 and to prevent interference with the operation of the electro-mechanical driver component 610 by another wireless RCU. Each subsequent communication between the wireless RCU 1148 and the electro-mechanical device surgical 610 may include the identification data. Thus, the controller 1122 may discriminate between wireless RCUs and thereby allow only a single, identifiable wireless RCU 1148 to control the operation of the electro-mechanical driver component 1610 and the surgical device 11 attached to the flexible shaft 1620.

Based on the positions of the components of the surgical device attached to the flexible shaft 1620, as determined in accordance with the output signals from the encoders 1106, 1108, the controller 1122 may selectively enable or disable the functions of the electro-mechanical driver component 1610 as defined by the operating program or algorithm corresponding to the attached device. For example, for the surgical device 11, the firing function controlled by the operation of the switch 1320 may be disabled unless the space or gap between the first jaw 50 and the second jaw 80 is determined to be within an acceptable range.

Referring now to FIG. 16, there is seen a schematic view of a wired RCU 1150. In the example embodiment, wired RCU 1150 includes substantially the same control elements as the wireless RCU 1148 and further description of such elements is omitted. Like elements are indicated in FIG. 16 with an accompanying prime. It should be appreciated that the functions of the electro-mechanical driver component 1610 and the device attached to the flexible shaft 1620, e.g., the surgical device 11, may be controlled by the wired RCU 1150 and/or by the wireless RCU 1148. In the event of a battery failure, for example, in the wireless RCU 1148, the wired RCU 1150 may be used to control the functions of the electro-mechanical driver component 1610 and the device attached to the flexible shaft 1620.

As described hereinabove, the front panel 1615 of the housing 1614 includes the display device 1616 and the indicators 1618a, 1618b. The display device 1616 may include an alpha-numeric display device, such as an LCD display device. The display device 1616 may also include an audio output device, such as a speaker, a buzzer, etc. The display device 1616 is operated and controlled by controller 1122 in accordance with the operating program or algorithm corresponding to the device attached to the flexible shaft 1620, e.g., the surgical device 11. If no surgical instrument or attachment is so attached, a default operating program or algorithm may be read by or selected by or transmitted to controller 1122 to thereby control the operation of the display device 1616 as well as the other aspects and functions of the electro-mechanical driver component 1610. If the surgical device 11 is attached to the flexible shaft 1620, the display device 1616 may display, for example, data indicative of the gap between the first jaw 50 and the second jaw 80 as determined in accordance with the output signal of encoders 1106, 1108, as more fully described hereinabove.

Similarly, the indicators 1618a, 1618b are operated and controlled by the controller 1122 in accordance with the operating program or algorithm corresponding to the device attached to the flexible shaft 1620, e.g., the surgical device 11. The indicator 1618a and/or the indicator 1618b may include an audio output device, such as a speaker, a buzzer, etc., and/or a visual indicator device, such as an LED, a lamp, a light, etc. If the surgical device 11 is attached to the

flexible shaft **1620**, the indicator **1618a** may indicate, for example, that the electro-mechanical driver component **1610** is in a power ON state, and the indicator **618b** may, for example, indicate whether the gap between the first jaw **50** and the second jaw **80** is determined to be within the acceptable range. It should be appreciated that although two indicators **1618a**, **1618b** are described, any number of additional indicators may be provided as necessary. Additionally, it should be appreciated that although a single display device **1616** is described, any number of additional display devices may be provided as necessary.

The display device **1616'** and the indicators **1618a'**, **1618b'** of wired RCU **1150** and the display device **1616''** and indicators **1618a''**, **1618b''** of the wireless RCU **1148** are similarly operated and controlled by respective controller **1322**, **1322'** in accordance with the operating program or algorithm of the device attached to the flexible shaft **1620**.

As set forth above, one problem with conventional surgical devices, and in particular with the conventional linear clamping, cutting and stapling devices such as that illustrated in FIG. **1**, is that the opposing jaws may be difficult to maneuver within a patient. It may be necessary for a surgeon to move the opposing jaws between various angles in order to position the desired tissue between the opposing jaws. However, it may also be desirable to make an incision in a patient that is as small as possible, and the small size of an incision limits the degree to which the opposing jaws may be maneuvered. Example embodiments of the present invention may provide improved maneuverability of a surgical device, e.g., the surgical device **11**, within a patient.

Another problem with the conventional surgical devices, and in particular with the foregoing linear clamping, cutting and stapling devices such as that illustrated in FIG. **1**, is that the opposing jaws may not be sufficiently hemostatic. Specifically, the opposing jaws of the foregoing surgical devices may not be clamped together with sufficient force, thereby reducing the effectiveness of the surgical device. Example embodiments of the present invention may provide improved clamping of a section of tissue disposed between the jaws of a surgical device, e.g., the surgical device **11**, thereby providing a sufficiently hemostatic condition with respect to the clamped section of tissue.

Furthermore, and as previously mentioned, one problem of conventional cutting and stapling devices is that the opposing jaws of the mechanism may not adequately clamp a section of tissue clamped therebetween, and they may not prevent a section of tissue clamped therebetween from escaping out from between the distal ends of the jaws during the operation of the device. This follows because the scissor-type gripping elements of conventional clamping, cutting and stapling devices, such as the device illustrated in FIG. **1**, pivot relative to each other around a fixed pivot point at a proximal end of the gripping elements. Thus, since the distance between the gripping elements is always less at a proximal end of the gripping elements than at the distal ends of the gripping elements, the clamping force on a section of tissue disposed between the gripping elements is greatest near the proximal ends of the gripping elements and gradually decreases in the distal direction. The relatively high clamping force at the proximal ends of the gripping elements coupled with the relatively low clamping force at the distal ends of the gripping elements causes the section of tissue to be pushed towards, and eventually out from between, the distal ends of the gripping elements. Thus, the section of tissue may not be adequately cut and stapled, and the inadequately cut and stapled end of the tissue may permit its

contents to spill into the open abdomen of the patient, increasing the likelihood of infection and other complications.

In contrast, and as previously described in detail in connection with FIGS. **3(i)** to **3(l)**, the surgical device **11** may provide an arrangement in which the distal ends **50a**, **80a** of the first and second jaws **50**, **80** are urged towards each other during the operation of the surgical device **11**, such that the clamping force between the distal ends **50a**, **80a** of the first and second jaws **50**, **80** is greater in the surgical device **11** than the clamping force between the distal ends of the jaws of a conventional clamping, cutting and stapling device. The increased clamping force at the distal ends **50a**, **80a** of the first and second jaws **50**, **80** may prevent a section of tissue which is disposed between the first and second jaws **50**, **80** from escaping out from between the distal ends **50a**, **80a** of the first and second jaws **50**, **80**.

As set forth above, FIGS. **17** to **19** illustrate another embodiment of the present invention. Like the previously described embodiment, the embodiment illustrated in FIGS. **17** to **19** illustrate an arrangement in which two rotatable drive shafts may be employed to selectively move a jaw portion relative to a shaft portion, to rotate the jaw portion about its longitudinal axis, to move a first, e.g., upper, jaw relative to a second, e.g., lower, jaw, and to fire a stapling and cutting cartridge. This particular embodiment provides an arrangement in which a position of the first and second jaws relative to each other engages and disengages a gear element so as to selectively rotate the jaw portion, or a portion thereof, about its longitudinal axis and to fire a stapling and cutting cartridge.

FIG. **17** is a side cross-sectional view that illustrates various features of this embodiment. In this embodiment, an arrangement is provided that is configured to move, e.g., articulate, a jaw portion **3111a** relative to a shaft portion **3111c**. In addition, the arrangement is configured to rotate at least a portion of the jaw portion **3111a** about its longitudinal axis, and more specifically, in the embodiment shown, to rotate a distal portion **3111d** of the jaw portion **3111a** relative to a joint portion **3111b** of the jaw portion **3111a**. Still further, the arrangement is configured to move, e.g., open and close, an upper jaw **3050** relative to the lower jaw **3080**, and to fire a stapling and cutting cartridge located in the lower jaw **3080**.

Referring to FIG. **17**, there is illustrated an upper bevel gear element **3504** that is rotatably mounted about a pin **3505**, the central axis of which is coaxial with the pivot axis B around which the jaw portion **3111a** pivots relative to the shaft portion **3111c**. The gear element **3504** is meshingly engaged with a bevel gear element **3506b** of a clamping gear shaft **3506** arranged longitudinally within the jaw portion **3111a**. The clamping gear shaft **3506** also includes a spur gear element **3506a**. The clamping gear shaft **3506**, including the bevel and spur gear elements **3506a** and **3506b**, rotates within the joint portion **3111b** about a longitudinal axis of the clamping gear shaft **3506**. The spur gear element **3506a** is meshingly engaged with a spur gear element **3512a** of a gear shaft **3512**. A proximal end of the gear shaft **3512** is rotatably mounted within a distal recess **36771** of an articulation gear **3677**, while a distal end of the gear shaft **3512** engages a threaded clamping screw **3520** (additional details of which are set forth below). In this manner, the gear shaft **3512** is rotatably mounted within the joint portion **3111b** and the distal portion **3111d** of the jaw portion **3111a**. The threaded clamping screw **3520** is arranged longitudinally and is rotatable about its longitudinal axis via engagement with the distal end of the gear shaft **3512**.

Mounted on the threaded screw **3520** is an inner shaft **3524**. Opposite lateral ends of the inner shaft **3524** are seated within respective slots **5111** on each side of the upper jaw **3050**. The upper jaw **3050** is rotatably mounted to the jaw body housing **30091** about a pin **3051**, which is distally located with respect to the slots **5111**.

A keying tube **3518** is coaxially mounted about, and is longitudinally slideable relative to, the gear shaft **3512**. The keying tube **3518** includes at its proximal end an endplate **3518a** that engages the joint portion **3111b** in a manner that prevents rotation of the keying tube **3518** relative to the joint portion **3111b**. Spring washers **3001** engage a proximally-facing surface of the endplate **3518a** so as to bias the keying tube **3518** distally. The keying tube **3518** includes a set of teeth **3518b** at a distal end thereof. The teeth **3518b** are selectively engageable with correspondingly-shaped recesses **3002a** of a proximal member **30029** of a cam block **3002**.

The cam block **3002** is non-rotatably mounted and axially movable within the distal portion **3111d** of the jaw portion **3111a**. A portion of the proximal member **30029** of the cam block **3002** extends proximally through a longitudinally-arranged bore of the jaw body housing **3009**. Specifically, the cam block **3002** is moveable in an axial direction between a first position (the position illustrated in FIG. 17), in which the correspondingly-shaped recesses **3002a** are not in engagement with the teeth **3518b**, and a second position, in which the cam block **3002** is moved proximally relative to the first position and the correspondingly-shaped recesses **3002a** are rotatably-locked in engagement with the teeth **3518b**.

An idler gear **3562** is coaxially mounted about the keying tube **3518**. A distal end of idler gear **3562** is selectively engageable with correspondingly-shaped recesses **3009b** on a proximally-facing surface of the jaw body housing **3009**, the correspondingly-shaped recesses **3009b** being circumferentially arranged about a longitudinal bore through the jaw body housing **3009**. Longitudinally moveable within the central bore of the jaw body housing **3009** is the proximal member **30029** of the cam block **3002**. A proximal face **30028** of the cam block **3002** is thereby moveable longitudinally through the bore of the jaw body housing **3009** such that the distal face of idler gear **3562** is selectively engageable with, e.g., contacted by, the proximal face **30028** of the cam block **3002**. A proximal face of the idler gear **3562** abuts a distal face of the endplate **3518a** of the keying tube **3518**, and is therefore biased distally by virtue of the distal biasing experienced by the keying tube **3518** by the spring washers **3001**.

The idler gear **3562** is moveable in an axial direction between a first position and a second position. In the first position (the position illustrated in FIG. 17), the distal end of the idler gear **3562** is seated within the correspondingly-shaped recesses **3009b** on the proximally-facing surface of the jaw body housing **3009** so as to be locked in non-rotatable engagement relative to the jaw body housing **3009**. In addition, in this first position, the proximal face **30028** of the cam block **3002** is axially spaced apart from the distal face of the idler gear **3562**.

In the second position, the cam block **3002** is moved proximally relative to the position shown in FIG. 17 such that the proximal face **30028** of the cam block **3002** engages, e.g., contacts and gradually pushes, the distal face of the idler gear **3562**. In this manner, the biasing force of the spring washers **3001** is overcome and the idler gear **3562** is caused to move proximally. Proximal movement of the idler gear **3562** eventually causes the distal face of the idler gear

3562 to be moved out of engagement with the recesses **3009b** of the jaw body housing **3009**. Once the idler gear **3562** is fully out of engagement with the recesses **3009b** of the jaw body housing **3009**, the idler gear **3562** is rotatable about the keying tube **3518**.

In addition, a lower bevel gear element **3554** is rotatable about the pin **3505**. The lower bevel gear element **3554** is meshingly engaged with a bevel gear element **3556b** of a gear shaft **3556** longitudinally arranged within the jaw portion **3111a**. The gear shaft **3556** also includes a spur gear element **3556a**. The gear shaft **3556**, including the bevel and spur gear elements **3556a** and **3556b**, rotates within the joint portion **3111b** about a longitudinal axis of the gear shaft **3556**. The gear element **3556a** is meshingly engaged with a proximal section of idler gear **3562**.

Meshingly engaged to a distal section of idler gear **3562** is a gear element **3564a** of a gear shaft **3564**. The gear shaft **3564** is mounted within jaw portion **3111a** and is rotatable about its longitudinal axis. A distal end of the gear shaft **3564** has a recess **35641** that has a cross-section that engages a correspondingly-shaped proximal end **35681** of a longitudinal rod **3568**. The longitudinal rod **3568** has a shoulder **3568a**. Between the gear shaft **3564** and the shoulder **3568a** of the longitudinal rod **3568** is a spring **3567**. The distal end **35682** of the longitudinal rod **3568** is configured to engage a respective opening in a wedge driver. The wedge driver rotates so as to drive a stapling/cutting wedge along a staple cartridge, such as described hereinabove.

The jaw body housing **3009** has, along a proximal portion of its outer circumference, a recess. A distal end of a seal sleeve **3710** fits over the recess, the seal sleeve **3710** having an outer circumferential surface at its distal end that is contiguous with the outer circumferential surface of the jaw body housing **3009**. In addition, the seal sleeve **3710** has, along a proximal portion of its outer circumference, a recess. Arranged circumferentially around this recess is a groove into which an O-ring seal **3711** is positioned. A joint portion housing **3715** fits over the recess, the joint portion housing **3715** having an outer circumferential surface that is generally contiguous with the outer circumferential surface of the distal portion of the seal sleeve **3710**. A distal portion of the joint portion housing **3715** maintains the O-ring seal **3711** within the groove of the seal sleeve **3710**. The O-ring seal **3711** enables a seal to be maintained between the seal sleeve **3710**, and the components arranged distally thereto, and the joint portion housing **3715** when these components are rotated relative to each other. In this manner, a jaw portion **3111a** (or at least a portion thereof, e.g., a distal portion **3111d**) is rotatable about its longitudinal axis.

Additional details of the cam block **3002** are shown in FIG. 18. Referring to FIG. 18, the cam block **3002** is, as set forth above, mounted so as to be axially movable within the distal portion **3111d** of the jaw portion **3111a**. As shown, the cam block **3002** includes a pair of arms **30021** that are disposed on laterally opposite sides relative to each other. Each one of the pair of arms **30021** includes a surface **3002c**. The surfaces **3002c** of the cam block **3002** engage respective cam surfaces **3050a** of the upper jaw **3050** as the upper jaw **3050** is moved relative to the lower jaw **3080**. As set forth above, the proximal member **30029** of the cam block **3002** extends proximally, e.g., through a central bore of the jaw body housing **3009** (hidden in this view). Each one of a pair of springs **3003** is located between a proximally-facing surface of the cam block **3002** and a distally-facing surface of the jaw body housing **3009** (hidden in this view) to bias the cam block **3002** distally. As set forth above, the cam block **3002** is longitudinally moveable between a first position (the

position shown in FIG. 18), in which the correspondingly-shaped recesses **3002a** are not in engagement with the teeth **3518b**, and a second position, in which the cam block **3002** is caused to move proximally relative to the first position. In this second position, the correspondingly-shaped recesses **3002a** are locked in engagement with the teeth **3518b** of the keying tube **3518**. Movement of the cam block **3002** between the first and second positions is caused by the surfaces **3002c** of the cam block **3002** engaging the respective cam surfaces **3050a** of the upper jaw **3050** as the upper jaw **3050** is moved relative to the lower jaw **3080**, as will be described in additional detail below.

FIG. 18 also illustrates a distal reload contact **3820** and a proximal reload contact **3830**. The distal reload contact **3830** contacts and communicates with the proximal reload contact in order to provide signals that the distal portion **3111d** has been rotated relative to the joint portion **3111b** back to its initial position upon a new staple cartridge being loaded in the surgical device.

Additional details of the various surfaces and recesses that engage the keying tube **3518** and the idler gear **3562** are illustrated in FIG. 19. Specifically, FIG. 19 shows, in the central-most region of the surgical device **3000**, a longitudinally-disposed central bore **3521** of the threaded clamping screw **3520**. As set forth above, the longitudinally-disposed central bore **3521** of the threaded clamping screw **3520** has a cross-section that is configured to receive and rotatably engage a correspondingly-shaped end of the gear shaft **3512**, such that rotation of the gear shaft **3512** causes rotation of the threaded clamping screw **3520**.

Located radially outside of the longitudinally-disposed central bore **3521** of the threaded clamping screw **3520** is shown the proximal face **30028** of the proximal member **30029** of the cam block **3002**. The proximal face **30028** includes the recesses **3002a**. As set forth above, the recesses **3002a** are configured to selectively engage with teeth **3518b** of the keying tube **3518**. Since the keying tube **3518** is non-rotatably arranged within the jaw portion **3111a**, engagement of the recesses **3002a** of the proximal member **30029** of the cam block **3002** with the teeth **3518b** of the keying tube **3518** prevent relative rotation between the cam block **3002** and the keying tube **3518**.

Located radially outside of the proximal face **30028** of the proximal member **30029** of the cam block **3002** is shown the proximally-facing surface **3009a** of the jaw body housing **3009**. The proximally-facing surface **3009a** of the jaw body housing **3009** includes the recesses **3009b**. As set forth above, the recesses **3009b** are configured to selectively engage a distal end of the idler gear **3562**. When the recesses **3009b** of the jaw body housing **3009** are engaged with the distal end of the idler gear **3562**, the idler gear **3562** is prevented from rotating relative to the jaw body housing **3009**. As set forth above, the idler gear **3562** is biased distally by the spring washers **3001** so as to seat within the recesses **3009b**. When the cam block **3002** is moved proximally to a position at which the proximal face **30028** of the cam block **3002** is proximal relative to the proximally-facing surface **3009a** of the jaw body housing **3009**, the idler gear **3562** is moved by the cam block **3002** out of the recesses **3009b** and is free to rotate relative thereto.

In operation, the jaw portion **3111a** is maintained in an initial position in which it is axially aligned with the shaft portion **3111c**. In this position, the surgical device **3111** may be inserted, e.g., through a trocar or cannula, into a surgical site. Depending on the position of the incision and the tissue to be clamped, stapled and cut, the user may then articulate

the jaw portion **3111a** relative to the shaft portion **3111c**, either in the manner set forth above or in any other manner.

Once the jaw portion **3111a** is articulated about the pin **3505** to a desired position, the first jaw **3050** may be moved, e.g., opened, relative to the second jaw **3080** so as to enable a section of tissue to be disposed therebetween. In order to open the first jaw **3050** relative to the second jaw **3080**, the gear element **3504** may be caused to rotate in a counter-clockwise direction (when viewed from above) about the pin **3505**. By virtue of its engagement with the gear element **3506b**, the counter-clockwise rotation of the gear element **3504** causes the gear element **3506b** to rotate in a clockwise direction (for the sake of simplicity, all references herein to a rotational direction, e.g., clockwise or counterclockwise, refer to a view from the proximal end of the surgical device towards the distal end of the surgical device **11**, unless otherwise noted; furthermore, it should be recognized that, while the disclosure hereinbelow includes, for each of the components of the surgical device **11**, various references to rotational directions in order to perform a specific function, these directions are merely exemplary because certain components may be differently configured, e.g., threaded portions may have a right-hand thread as opposed to a left-hand thread, etc., such that the rotational directions set forth herein may be reversed in order to perform the same below-described functions). Since the gear element **3506b** and the gear element **3506a** are fixed features of the gear shaft **3506**, rotation of the gear element **3506b** in the clockwise direction causes the gear element **3506a** to also rotate in a clockwise direction. By virtue of its engagement with the gear element **3512a** of gear shaft **3512**, the clockwise rotation of the gear element **3506a** causes the gear element **3512a** and the gear shaft **3512**, of which gear element **3512a** is a fixed feature, to rotate in a counterclockwise direction.

Due the engagement of the distal end of the gear shaft **3512** with the threaded clamping screw **3520**, rotation of the gear shaft **3512** in the counter-clockwise direction causes the threaded clamping screw **3520** to also rotate in the counterclockwise direction. Since the inner shaft **3524** is threadedly engaged with the outer threads of the threaded clamping screw **3520**, rotation of the threaded clamping screw **3520** in a counter-clockwise direction causes the inner shaft **555** to move in a distal direction within the slots **5111** of the first and second jaws **3050** and **3080**, respectively. This distal movement of the inner shaft **3524** allows the first and second jaws to move, e.g., open, relative to each other. Additional details of this clamping arrangement may be found, for example, in Applicant's co-pending U.S. patent application Ser. No. 11/191,851, entitled "Surgical Device," filed Jul. 27, 2005, now issued as U.S. Pat. No. 8,241,322 on Aug. 14, 2012, the disclosure of which is hereby incorporated by reference in its entirety.

Also, the opening of the first and second jaws **3050**, **3080** relative to each other allows the cam block **3002** and the idler gear **3562** to move distally. Specifically, as the jaws are opened relative to each other, the cam block **3002** and the idler gear **3562** are moved distally until the recesses **3002a** are spaced apart from and out of engagement with the teeth **3518b**. Also, distal movement of the cam block **3002** causes the proximal face **30028** of the cam block **3002** to withdraw from the distal face of the idler gear **3562**, such that the biasing force of the spring washers **3001** causes the idler gear **3562** to move distally. Continued distal movement of the idler gear **3562** eventually causes the distal face of the idler gear **3562** to engage the recesses **3009b** of the jaw body

housing **3009**, until the idler gear **3562** is prevented from rotating relative to the keying tube **3518**.

Once the first and second jaws **3050**, **3080** have been opened sufficiently, the jaw portion **3111a**, or at least a portion thereof, e.g., the distal portion **3111d**, may be rotated about its longitudinal axis. Specifically, in the embodiment shown, the distal portion **3111d** may be rotated relative to the joint portion **3111b** about the longitudinal axis of the joint portion **3111b**, e.g., illustrated as axis D. Referring to FIG. **17**, in order to rotate the distal portion **3111d** in a counter-clockwise direction relative to the joint portion **3111b** about the longitudinal axis of the joint portion **3111b**, the gear element **3554** may be caused to rotate in a clockwise direction (when viewed from above) about the pin **3505**. By virtue of its engagement with the gear element **3556b**, the clockwise rotation of the gear element **3554** causes the gear element **3556b** to rotate in a clockwise direction. Since the gear element **3556b** and the gear element **3556a** are fixed features of the gear shaft **3556**, rotation of the gear element **3556b** in the clockwise direction causes the gear element **3556a** to also rotate in a clockwise direction. By virtue of its engagement with the idler gear **3562**, the clockwise rotation of the gear element **3556a** causes the idler gear **3562** to rotate in a counter-clockwise direction. Since the idler gear is maintained in its first position, the distal end of the idler gear **3562** is locked in engagement with the correspondingly-shaped opening **3009b** of the jaw body housing **3009**. Thus, the rotation of the idler gear **3562** in the counter-clockwise direction about the central axis of the idler gear **3562** causes the jaw body housing **3009** (and all of the components distal thereto, to rotate in the counter-clockwise direction relative to the joint portion housing **3715** about the longitudinal axis D. It is noted that the arrangement of the cam block **3002** and the idler gear **3562** in this embodiment is such that firing of the staple cartridge may not occur with the jaws open—rather, upon closure of the jaws relative to each other, the staple cartridge may be fired, as set forth below.

Once the jaw portion **3111a**, or a portion thereof, is rotated in this manner about the longitudinal axis D to a desired position, the jaws **3050**, **3080** may be closed, e.g., so as to clamp a section of tissue that is disposed therebetween. To perform this operation, the gear element **3504** may be caused to rotate in a clockwise direction (when viewed from above) about the pin **3505**. By virtue of its engagement with the gear element **3506b**, the clockwise rotation of the gear element **3504** causes the gear element **3506b** to rotate in a counter-clockwise direction. Since the gear element **3506b** and the gear element **3506a** are fixed features of the gear shaft **3506**, rotation of the gear element **3506b** in the counter-clockwise direction causes the gear element **3506a** to also rotate in a counter-clockwise direction. By virtue of its engagement with the gear element **3512a** of gear shaft **3512**, the counter-clockwise rotation of the gear element **3506a** causes the gear element **3512a** and the gear shaft **3512**, of which gear element **3512a** is a fixed feature, to rotate in a clockwise direction.

Due the engagement of the distal end of the gear shaft **3512** with the threaded clamping screw **3520**, rotation of the gear shaft **3512** in the clockwise direction causes the threaded clamping screw **3520** to also rotate in the clockwise direction. Since the inner shaft **3524** is threadedly engaged with the outer threads of the threaded clamping screw **3520**, rotation of the threaded clamping screw **3520** in a clockwise direction causes the inner shaft **555** to move in a proximal direction within the slots **5111** of the first and second jaws **3050** and **3080**, respectively. This proximal movement of the

inner shaft **3524** causes the first and second jaws to move, e.g., close, relative to each other.

Also, the closing of the first and second jaws **3050**, **3080** relative to each other moves the cam block **3002** back to its initial position, which in turn moves the idler gear **3562** back to its initial position. Specifically, the cam block **3002** is moved proximally until the correspondingly-shaped recesses **3002a** are locked in engagement with the teeth **3518b**. Also, proximal movement of the cam block **3002** causes the proximal face **30028** of the cam block **3002** to push against the distal face of the idler gear **3562**. In this manner, the biasing force of the spring washers **3001** is overcome in order to move the idler gear **3562** proximally until the distal end of the idler gear **3562** is disengaged from the correspondingly-shaped recesses **3009b** on the proximally-facing surface of the jaw body housing **3009**. With the jaws closed, the idler gear **3562** is free to rotate about the keying tube **3518**.

Once a section of tissue has been clamped between the first and second jaws **3050**, **3080**, the section of tissue may be cut and/or stapled. It should be recognized that, while the present invention is illustrated as using both cutting and stapling elements, the surgical device **11** may employ only one such element, or else may employ a different type of surgical instrument.

Before the surgical device **11** is inserted into a patient's body, a staple cartridge is provided within the second jaw **3080**. In an embodiment, the surgical device **11** is a single-use device, in which the staple cartridge is integral to the second jaw **3080**. Alternatively, the surgical device **11** may have a replaceable staple cartridge, e.g., replaceable staple cartridge **600** as illustrated in FIG. **3(f)**, thereby permitting the surgical device **11** to be used numerous times with different staple cartridges. In this embodiment, if the surgical device **11** is being used for the first time, the staple cartridge **600** may be pre-installed during manufacture and assembly of the surgical device **11**, or else may be installed by the user just prior to using the surgical device **11**. If the surgical device **11** is being used for the second or more time, the staple cartridge **600** may be installed by the user just prior to using the surgical device **11**. When the staple cartridge **600** is inserted into the second jaw **3080**, the distal end **35682** of the longitudinal rod **3568** is received within the proximally-facing opening **605d** of the wedge driver **605**.

Referring to FIG. **17**, in order to fire the stapling cartridge, the gear element **3554** may be caused to rotate in a clockwise direction (when viewed from above) about the pin **3505**. By virtue of its engagement with the gear element **3556b**, the clockwise rotation of the gear element **3554** causes the gear element **3556b** to rotate in a clockwise direction. Since the gear element **3556b** and the gear element **3556a** are fixed features of the gear shaft **3556**, rotation of the gear element **3556b** in the clockwise direction causes the gear element **3556a** to also rotate in a clockwise direction. By virtue of its engagement with the idler gear **3562**, the clockwise rotation of the gear element **3556a** causes the idler gear **3562** to rotate in a counter-clockwise direction. Since the idler gear is free to rotate about the keying tube **3518**, the rotation of the idler gear **3562** in the counter-clockwise direction about the central axis of the idler gear **3562** causes the gear shaft **3564** to rotate in a clockwise direction. The engagement of the recess **35641** at the distal end of the gear shaft **3564** with the correspondingly-shaped proximal end **35681** of the longitudinal rod **3568** is such that rotation of the gear shaft **3564** in a clockwise direction causes the longitudinal rod **35681** to also rotate in a clockwise direction. The distal end **35682** of the longitudinal rod **3568** engages the opening

605*d* of the wedge driver 605 (shown in FIG. 3(*f*)). The wedge driver 605 rotates so as to drive a stapling/cutting wedge along a staple cartridge, such as described herein-above.

It should be recognized that, according to various embodiments of the present invention, the blade 51 and the wedge 603 may be moved in either a proximal or a distal direction in order to cut and/or staple a section of tissue disposed between the first jaw 3050 and the second jaw 3080. Furthermore, it should be recognized that, according to various embodiments of the present invention, any mechanical arrangement that is configured to move the blade 51 and the wedge 603 in order to cut and/or staple a section of tissue disposed between the first jaw 3050 and the second jaw 3080 may be employed.

Once the section of tissue may be cut and/or stapled, the surgical device 11 may be employed to return the wedge 603 and the blade 51 to their initial positions. This may be particularly desirable when the surgical device 11 employs replaceable staple cartridges, e.g., replaceable staple cartridge 600 as illustrated in FIG. 3(*f*), thereby permitting the surgical device 11 to be used numerous times with different staple cartridges. Once the wedge 603 and the blade 51 have been moved to their initial positions, the surgical device 11 may be used for a second or more time. To do so, the user may remove the spent staple cartridge 600 and insert in the surgical device 11*a* new staple cartridge 600, the distal end of the longitudinal rod 3568 being received within the proximally-facing opening 605*d* of the wedge driver 605 of the new staple cartridge 600. Of course, it should be recognized that this step of returning the wedge 603 and the blade 51 to their initial positions may be performed either prior to, or subsequent to, removal of the surgical device 11 from the patient's body.

In order to return the wedge 603 and the blade 51 to their initial positions, the gear element 3554 may be caused to rotate in a counter-clockwise direction (when viewed from above) about the pin 3505. By virtue of its engagement with the gear element 3556*b*, the counter-clockwise rotation of the gear element 3554 causes the gear element 3556*b* to rotate in a counter-clockwise direction. Since the gear element 3556*b* and the gear element 3556*a* are fixed features of the gear shaft 3556, rotation of the gear element 3556*b* in the counter-clockwise direction causes the gear element 3556*a* to also rotate in a counter-clockwise direction. By virtue of its engagement with the idler gear 3562, the counter-clockwise rotation of the gear element 3556*a* causes the idler gear 3562 to rotate in a clockwise direction. Since the idler gear is free to rotate about the keying tube 3518, the rotation of the idler gear 3562 in the clockwise direction about the central axis of the idler gear 3562 causes the gear shaft 3564 to rotate in a counter-clockwise direction. The engagement of the recess 35641 at the distal end of the gear shaft 3564 with the correspondingly-shaped proximal end 35681 of the longitudinal rod 3568 is such that rotation of the gear shaft 3564 in a counter-clockwise direction causes the longitudinal rod 3568 to also rotate in a counter-clockwise direction. The distal end 35682 of the longitudinal rod 3568 engages the opening 605*d* of the wedge driver 605 (shown in FIG. 3(*f*)), and counter-clockwise rotation of the wedge driver 605 moves the wedge 603 back to its initial position so that the surgical device may be ready to accommodate a new staple cartridge 600, if appropriate.

Once the wedge 603 has been moved back to its initial position, the first jaw 3050 may again be moved, e.g., opened, relative to the second jaw 3080 so as to release the stapled sections of the tissue from therebetween. In order to

open the first jaw 3050 relative to the second jaw 3080, the gear element 3504 may be caused to rotate in a counter-clockwise direction (when viewed from above) about the pin 3505. The counter-clockwise rotation of the gear element 3504 causes the gear element 3506*b* to rotate in a clockwise direction, which in turn causes the gear element 3506*a* to also rotate in a clockwise direction. The clockwise rotation of the gear element 3506*a* causes the gear element 3512*a* and the gear shaft 3512, of which gear element 3512*a* is a fixed feature, to rotate in a counter-clockwise direction. The rotation of the gear shaft 3512 in the counter-clockwise direction causes the threaded clamping screw 3520 to also rotate in the counter-clockwise direction, which in turn causes the inner shaft 555 to move in a distal direction within the slots 5111 of the first and second jaws 3050 and 3080, respectively. This distal movement of the inner shaft 3524 allows the first and second jaws to move, e.g., open, relative to each other.

Again, the opening of the first and second jaws 3050, 3080 relative to each other allows the cam block 3002 and the idler gear 3562 to move distally. Specifically, as the jaws are opened relative to each other, the cam block 3002 and the idler gear 3562 are moved distally until the recesses 3002*a* are spaced apart from and out of engagement with the teeth 3518*b*. Also, distal movement of the cam block 3002 causes the proximal face 30028 of the cam block 3002 to withdraw from the distal face of the idler gear 3562, such that the biasing force of the spring washers 3001 causes the idler gear 3562 to move distally. Continued distal movement of the idler gear 3562 eventually causes the distal face of the idler gear 3562 to engage the recesses 3009*b* of the jaw body housing 3009, until the idler gear 3562 is prevented from rotating relative to the keying tube 3518.

Once the first and second jaws 3050, 3080 have been opened sufficiently to release the section of tissue clamped therebetween, the jaw portion 3111*a*, or at least a portion thereof, e.g., the distal portion 3111*d*, may be rotated about its longitudinal axis back to its original, e.g., un-rotated, position. Referring to FIG. 17, in order to rotate the distal portion 3111*d* in a clockwise direction relative to the joint portion 3111*b*, the gear element 3554 may be caused to rotate in a counter-clockwise direction (when viewed from above) about the pin 3505 which in turn causes the gear element 3556*b* to rotate in a counter-clockwise direction. Rotation of the gear element 3556*b* in the counter-clockwise direction causes the gear element 3556*a* to also rotate in a counter-clockwise direction, which in turn causes the idler gear 3562 to rotate in a clockwise direction. Since the idler gear 3562 is maintained in its first position, the distal end of the idler gear 3562 is locked in engagement with the correspondingly-shaped recesses 3009*b* of the jaw body housing 3009. Thus, the rotation of the idler gear 3562 in the clockwise direction causes the jaw body housing 3009, and all of the components distal thereto, to rotate in the clockwise direction relative to the joint portion housing 3715. Of course, while this "return" rotation is described hereinabove as being in the clockwise direction, the direction of rotation in this step will be the opposite of whatever direction of rotation was selected by an operator when the jaw portion 3111*a* (or at least a portion thereof, e.g., the distal portion 3111*d*) was initially rotated.

Once the jaw portion 3111*a*, or a portion thereof, is rotated in this manner about the longitudinal axis D back to its initial position, the jaws 3050, 3080 may be closed, e.g., so as to enable the surgical device 11 to be removed from the patient's body via the opening, e.g., the cannula, through which it was originally introduced. To perform this opera-

41

tion, the gear element **3504** may be caused to rotate in a clockwise direction (when viewed from above) about the pin **3505**. The clockwise rotation of the gear element **3504** causes the gear element **3506b** to rotate in a counter-clockwise direction. Rotation of the gear element **3506b** in the counter-clockwise direction causes the gear element **3506a** to also rotate in a counter-clockwise direction. The counter-clockwise rotation of the gear element **3506a** causes the gear element **3512a** and the gear shaft **3512**, of which gear element **3512a** is a fixed feature, to rotate in a clockwise direction.

Rotation of the gear shaft **3512** in the clockwise direction causes the threaded clamping screw **3520** to also rotate in the clockwise direction. Rotation of the threaded clamping screw **3520** in a clockwise direction causes the inner shaft **555** to move in a proximal direction within the slots **5111** of the first and second jaws **3050** and **3080**, respectively. This proximal movement of the inner shaft **3524** causes the first and second jaws to move, e.g., close, relative to each other.

With the first and second jaws **3050**, **3080** closed relative to each other, the user may then articulate the jaw portion **3111a** relative to the shaft portion **3111c** back to its initial position, e.g., with the jaw portion **3111a** being axially aligned relative to the shaft portion **3111c**. With the jaw portion **3111a** being again axially aligned relative to the shaft portion **3111c**, the surgical device **11** may be withdrawn from the surgical site. Of course, it should be recognized that the surgical device **11** of the present invention may be returned to its initial positions, e.g., rotation, articulation, etc., either prior to or after being removed from a patient's body.

Those skilled in the art will appreciate that numerous modifications of the exemplary embodiment described hereinabove may be made without departing from the spirit and scope of the present invention. Although exemplary embodiments of the present invention have been described and disclosed in detail herein, it should be understood that this invention is in no sense limited thereby.

The invention claimed is:

1. A surgical device, comprising:

an elongate shaft assembly;

a drive system for applying a plurality of rotary control motions to the elongate shaft assembly;

a first gear train having a first gear element arrangement including a first pair of gear elements operably interfacing with a second gear element; and

a second gear train having a second gear element arrangement including a second pair of gear elements operably interfacing with a third gear element;

wherein at least one of the second or third gear elements defines a central axis coaxial with a pivot axis around which at least one of a first jaw or a second jaw pivots relative to the elongate shaft assembly, the first and second jaws positioned on a distal end of the elongate shaft assembly.

2. The surgical device according to claim **1**, wherein a distal end of the elongate shaft assembly includes a first jaw, and a second jaw disposed in opposed correspondence relative to the first jaw.

3. The surgical device according to claim **2**, wherein the elongate shaft assembly defines a longitudinal axis there-through that is perpendicular to a pivot axis defined by a pin extending through at least one of the first gear train or the second gear train.

4. The surgical device according to claim **3**, wherein the drive system includes:

42

a first driver coupled to a first rotatable drive shaft, the first driver configured to move the first jaw relative to the second jaw; and

a second driver coupled to a second rotatable drive shaft, the second driver configured to drive a cutting and stapling element included in the second jaw.

5. The surgical device according to claim **4**, wherein the first gear train meshingly engages with the first rotatable drive shaft and the second gear train meshingly engages with the second rotatable drive shaft.

6. The surgical device according to claim **5**, wherein actuation of at least one of the first and second gear trains actuates a rotation of the first and second jaws relative to the longitudinal axis defined by the elongate shaft assembly.

7. The surgical device according to claim **6**, further comprising a wedge member mechanically cooperating with a wedge driver, the wedge driver being actuated by one of the first gear train or the second gear train upon an actuation thereof.

8. The surgical device according to claim **7**, wherein a displacement of the first jaw relative to the second jaw, and a displacement of the wedge member is a function of a rotation of the first and second rotatable drive shafts.

9. The surgical device according to claim **1**, wherein the first gear arrangement is rotatably mounted about a pin defining a pivot axis.

10. The surgical device according to claim **1**, wherein the second gear arrangement is rotatably mounted about a pin defining a pivot axis.

11. The surgical device according to claim **1**, wherein the first gear element arrangement is actuatable by a first rotatable drive shaft and the second gear element arrangement is actuatable by a second rotatable drive shaft, to position the first jaw relative to the second jaw.

12. A surgical device, comprising:

an elongate shaft assembly;

a drive system for applying a plurality of rotary control motions to the elongate shaft assembly;

a first gear train having a first gear element arrangement including a first pair of gear elements operably interfacing with a second gear element; and

a second gear train having a second gear element arrangement including a second pair of gear elements operably interfacing with a third gear element;

wherein the second gear element is perpendicular to the first pair of gear elements and the third gear element is perpendicular to the second pair of gear elements.

13. The surgical device according to claim **12**, wherein a pin is secured through the second and third gear elements such that the second gear element is transverse to the third gear element.

14. A surgical device, comprising:

an elongate shaft assembly;

a first jaw, and a second jaw disposed in opposed correspondence relative to the first jaw, the first and second jaws attached at a distal end of the elongate shaft assembly;

a drive system for applying a plurality of rotary control motions to the elongate shaft assembly, the drive system including a first driver coupled to a first rotatable drive shaft and a second driver coupled to a second rotatable drive shaft, wherein the first driver moves the first jaw relative to the second jaw, and the second driver drives a cutting and stapling element included in the second jaw;

a first gear element arrangement including a first gear element, a second gear element, and a third gear

element, where the first and second gear elements meshingly engage with the third gear element; and a second gear element arrangement including a fourth gear element, a fifth gear element, and a sixth gear element, where the fourth and fifth gear elements meshingly engage with the sixth gear element; wherein at least one of the first gear element arrangement or the second gear element arrangement is rotatably mounted about a pin.

15. The surgical device according to claim **14**, wherein actuation of at least one of the first and second gear element arrangements actuates a rotation of the first and second jaws relative to a longitudinal axis defined by the elongate shaft assembly.

16. The surgical device according to claim **14**, wherein the first gear element is disposed in opposed correspondence relative to the second gear element, such that the first and second gear elements are transverse to each other; and wherein the fourth gear element is disposed in opposed correspondence relative to the fifth gear element, such that the fourth and fifth gear elements are transverse to each other.

17. The surgical device according to claim **16**, wherein the third gear element of the first gear element arrangement is transverse to the sixth gear element of the second gear element arrangement.

18. The surgical device according to claim **17**, wherein the pin is secured through the third gear element of the first gear element arrangement and the sixth gear element of the second gear element arrangement.

* * * * *