

US010161277B2

(12) **United States Patent**  
**Jorgensen et al.**

(10) **Patent No.:** **US 10,161,277 B2**  
(45) **Date of Patent:** **Dec. 25, 2018**

(54) **CAPACITOR-POWERED CATALYST HEATER**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **GM GLOBAL TECHNOLOGY OPERATIONS LLC**, Detroit, MI (US)

5,580,477 A 12/1996 Oota et al.  
8,875,487 B2 \* 11/2014 Katsuta ..... B60W 10/26  
60/277

(72) Inventors: **Scott W. Jorgensen**, Bloomfield Township, MI (US); **Shouxian Ren**, Rochester Hills, MI (US)

9,169,764 B2 \* 10/2015 Hashimoto ..... B60L 3/0069  
9,518,493 B2 12/2016 Hodgson et al.  
2012/0004801 A1 \* 1/2012 Watanabe ..... F01N 3/2026  
701/22

(73) Assignee: **GM Global Technology Operations LLC**, Detroit, MI (US)

2012/0260638 A1 \* 10/2012 Yoshioka ..... F01N 3/2013  
60/295  
2013/0291526 A1 \* 11/2013 Gonze ..... F01N 3/027  
60/311  
2013/0305692 A1 \* 11/2013 Hashimoto ..... F01N 3/2013  
60/274

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 32 days.

FOREIGN PATENT DOCUMENTS

JP 2864768 B2 3/1996

(21) Appl. No.: **15/495,445**

\* cited by examiner

(22) Filed: **Apr. 24, 2017**

*Primary Examiner* — Binh Q Tran

(74) *Attorney, Agent, or Firm* — Quinn IP Law

(65) **Prior Publication Data**

US 2018/0306080 A1 Oct. 25, 2018

(51) **Int. Cl.**

**F01N 3/00** (2006.01)  
**F01N 3/20** (2006.01)  
**F01N 13/16** (2010.01)

(52) **U.S. Cl.**

CPC ..... **F01N 3/2026** (2013.01); **F01N 13/16** (2013.01); **F01N 2900/0602** (2013.01)

(58) **Field of Classification Search**

USPC ..... 60/274, 275, 277, 280, 284, 286, 300, 60/303

See application file for complete search history.

(57) **ABSTRACT**

An after-treatment (AT) system used to treat an exhaust gas flow emitted by an internal combustion engine includes a catalyst monolith configured to actively remove a pollutant from the exhaust gas flow. The AT system also includes a heating element configured to heat the catalyst monolith. The AT system additionally includes an energy-discharge unit configured to power the heating element. The energy-discharge unit includes an energy-storage device configured to supply electrical energy. The energy-discharge unit also includes a capacitor configured to receive the electrical energy from the energy-storage device and discharge the received electrical energy to power the heating element and thereby heat the catalyst monolith. A vehicle having an internal combustion engine operatively connected to such an AT system is also contemplated.

**16 Claims, 2 Drawing Sheets**





FIG. 1






FIG. 2

## CAPACITOR-POWERED CATALYST HEATER

### TECHNICAL FIELD

The present disclosure relates to a capacitor-powered heater for an exhaust after treatment catalyst.

### BACKGROUND

Internal combustion (IC) engines typically include exhaust systems designed to collect, route, and discharge the engine's exhaust gases. An exhaust system commonly includes piping to guide exhaust gases away from the engine. Exhaust systems of modern IC engines also include various exhaust after-treatment (AT) devices, such as a gasoline three-way catalytic converter, a diesel oxidation catalytic converter, and other devices, to effectively convert toxic byproducts of combustion to less toxic substances by way of catalyzed chemical reactions.

A typical AT device employs a catalyst monolith selected or formulated to achieve effective performance at exhaust gas temperatures of the specific IC engine equipped therewith. Such an AT device is, however, less efficient under engine cold-start conditions and until the subject AT device achieves light-off, i.e., reaches its effective operating temperature. Accordingly, an IC engine equipped with such an AT device will generally produce elevated exhaust emissions following an engine cold-start and until the AT device light-off.

### SUMMARY

One embodiment of the disclosure is directed to an after-treatment (AT) system for treating an exhaust gas flow emitted by an internal combustion engine includes a catalyst monolith configured to actively remove a pollutant from the exhaust gas flow. The AT system also includes a heating element configured to heat the catalyst monolith. The AT system additionally includes an energy-discharge unit configured to power the heating element. The energy-discharge unit includes an energy-storage device configured to supply electrical energy. The energy-discharge unit also includes a capacitor configured to receive the electrical energy from the energy-storage device and discharge the received electrical energy to power the heating element and thereby heat the catalyst monolith.

The electric heating element may be arranged in the exhaust gas flow upstream of the catalyst monolith and configured to further heat the exhaust gas flow to thereby heat the catalyst monolith. Such further heating of the exhaust gas flow may be accomplished either by adding sufficient heat energy to combust fuel and air inside the exhaust gas flow or adding heat energy short of commencing combustion.

The catalyst monolith may include either a ceramic or a metallic catalyst substrate configured to remove a pollutant from the exhaust gas flow. The heating element may be either embedded in or attached to the corresponding catalyst substrate.

Wherein the catalyst monolith includes the metallic catalyst substrate, the metallic catalyst substrate may be configured as the heating element, i.e., operated as the heating element.

The catalyst monolith may include a precious metal element activated by elevated temperature of the exhaust gas flow, while the heating element may be mounted externally

to the catalyst monolith. The precious metal element may be at least one of platinum (Pt), palladium (Pd), and rhodium (Rh).

The AT system may also include a motor-generator configured to supply electrical energy either to the energy-discharge unit or to the heating element. The catalyst monolith may include other supportive catalyst ingredients, such as Ce, Zr, Mg, Mn, Co, Mo, Ni, Cu, Fe, Ba, La, Sr, Va, Ti, Si, Au, Ag, P and their oxides.

The AT system may additionally include an electronic controller configured to identify a cold-start of the engine and regulate operation of the motor-generator. The electronic controller may be additionally configured to regulate operation of the capacitor to discharge the received electrical energy and power the heating element in response to the identified cold-start of the engine.

The electronic controller may be additionally configured to regulate the motor-generator to supply electrical energy to the heating element after the capacitor has discharged the received electrical energy.

The engine may be cooled via an engine coolant. The controller may be in electronic communication with a first sensor configured to detect a temperature of the engine coolant and a second sensor configured to detect ambient temperature. In such a case, the controller may be configured to identify the cold-start of the engine via a comparison of the detected temperature of engine coolant and ambient temperature.

The controller may be additionally configured to regulate the capacitor to discharge the received electrical energy and thereby power the heating element to heat or regenerate the catalyst monolith.

Another embodiment of the present disclosure is directed to a vehicle having an internal combustion engine operatively connected to the AT system, as described above. The engine may be a compression-ignition or diesel type.

The vehicle may also include the electronic controller configured to identify a cold-start of the engine and regulate operation of the AT system.

The above features and advantages, and other features and advantages of the present disclosure, will be readily apparent from the following detailed description of the embodiment(s) and best mode(s) for carrying out the described disclosure when taken in connection with the accompanying drawings and appended claims.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic plan view of a motor vehicle having a powertrain, including an engine with an after-treatment (AT) system having an AT device, a heating element to heat the AT device, and an energy-discharge unit configured to power the heating element, according to the disclosure.

FIG. 2 is a schematic view of a partial cut-away of the AT device, the heating element arranged on the AT device, and the energy-discharge unit operatively connected to the heating element, according to the disclosure.

### DETAILED DESCRIPTION

Referring to the drawings, wherein like reference numbers refer to like components throughout the several views, FIG. 1 schematically depicts a vehicle 10. The vehicle 10 employs a powertrain 12. The powertrain 12 includes an internal combustion engine 14, a transmission 16, and drive wheels 18, wherein the engine is configured to power the vehicle by sending engine torque through the transmission to

the drive wheels. The engine **14** may be a diesel, i.e., a compression-ignition type, or a gasoline, i.e., a spark-ignition type, engine. Although the vehicle **10** is depicted as having a standard powertrain **12**, where the primary powerplant is the engine **14**, the vehicle may also be a hybrid type, where one or more electric motor-generators, such as the motor-generator **20**, are used in powering the vehicle. The vehicle **10** also includes a main energy-storage system **22**, such as one or more batteries and/or alternator (not shown). The main energy-storage system **22** is configured to supply electrical energy for powering various vehicle systems, such as an ignition system (not shown) configured to control combustion in the engine **14**, or the above-noted electric motor-generator(s).

The engine **14** includes combustion chambers (not shown) configured to receive a fuel-air mixture for subsequent combustion therein. The engine **14** is also configured to exhaust post-combustion gases into an exhaust system **26**, i.e., generate an exhaust gas flow **24**, as a by-product of generated engine torque. As shown in FIG. 1, the engine **14** may include an exhaust gas-driven turbocharger **28**. Specifically, the turbocharger **28** receives an airflow **30** from the ambient, pressurizes the received airflow, and discharges the pressurized airflow **30A** to the engine **14** for subsequent mixing with an appropriate amount of fuel **31** and subsequent combustion of the resultant fuel-air mixture in the respective combustion chambers. As shown, the turbocharger **28** is connected to an exhaust passage **26A** of the exhaust system **26** that receives the exhaust gas flow **24** and eventually releases the exhaust gases to the ambient, typically on a side or aft of the vehicle **10**.

With continued reference to FIG. 1, the exhaust system **26** is part of an exhaust after-treatment (AT) system **32** configured to treat the exhaust gas flow **24**. As shown, the AT system **32** also includes at least one AT device or catalytic converter, generally indicated by numeral **34**. The exhaust passage **26A** is configured to direct the exhaust gas flow **24** to the exhaust AT device **34**. Each AT device **34** has a catalyst monolith **34A** configured to actively remove a pollutant from the exhaust gas flow **24**, having a specific catalyst substrate **34B** formulated or selected to remove or neutralize a particular pollutant. The catalyst substrate **34B** may be either a precious metal, a ceramic material, or a precious metal and ceramic material matrix. In the event that the engine **14** is a gasoline engine (not shown), the AT device **34** may be a three-way catalytic converter.

Specifically, a gasoline three-way catalytic converter is an exhaust after-treatment device that simultaneously performs three tasks: i) reduction of nitrogen oxides, ii) oxidation of carbon monoxide, and iii) oxidation of unburned hydrocarbons. The three-way catalytic converter may be regenerated to unload the deposited hydrocarbon emissions in order to forestall elevated temperatures in the catalytic converter that may eventually cause damage thereto. The first two tasks listed above employ a process of selective catalytic reduction (SCR) for converting oxides of nitrogen, also referred to as  $\text{NO}_x$  with the aid of a catalyst into diatomic nitrogen,  $\text{N}_2$ , and water,  $\text{H}_2\text{O}$ . SCR is frequently employed to reduce  $\text{NO}_x$  emissions in the exhaust of internal combustion engines used to power motor vehicles. Exhaust emissions of both gasoline and diesel engines may be improved by the SCR process.

In the event the engine **14** is a compression-ignition or diesel engine (shown in FIG. 1), the exhaust system **32** may include a series of AT devices **34**. Such AT devices **34** in the diesel engine **14** may include one or more of the following: a diesel oxidation catalytic converter (DOC), an ammonia-

based selective catalytic reduction (SCR) catalytic converter or an SCR filter (SCRf), a diesel particulate filter (DPF), and a lean  $\text{NO}_x$  trap (LNT), none of which are specifically shown. Such exhaust after-treatment devices may be employed to reduce various exhaust emissions of the diesel engine. Each of the DOC, SCR catalytic converter or filter, DPF, and LNT typically contains precious metals, such as platinum and/or palladium, which function as catalysts in the subject devices to accomplish their respective objectives. Each of SCR catalytic converter and SCR filter (SCRf) generally includes zeolite material that contains at least one metal ion, such as Cu ion or Fe ion. Additionally, each of the DOC, SCR, SCRf, DPF, and LNT become activated and reach operating efficiency at elevated temperatures, typically, as the engine **14** approaches its normal operating temperature.

The primary function of the DOC is oxidation of carbon monoxides (CO) and non-methane hydrocarbons (NMHC). When present, the DOC is additionally configured to oxidize nitrogen oxide (NO) into nitrogen dioxide ( $\text{NO}_2$ ), which may be used by an LNT and an SCR catalytic converter, or an SCR filter (SCRf), that are typically arranged remotely downstream of the DOC and described in greater detail below. Generally, with respect to generation of  $\text{NO}_2$ , the DOC becomes activated and reaches operating efficiency at elevated temperatures. The DOC is typically arranged as the first diesel AT device downstream of the engine **14** and may be close-coupled to the turbocharger **28** in order to reduce loss of thermal energy from the exhaust gas flow **24** prior to the gas reaching the DOC.

The ammonia-based SCR catalytic converter or SCRf is employed to reduce the diesel emission of  $\text{NO}_x$  via the SCR process described above with respect to the gasoline engine specific three-way catalytic converter, and is generally positioned as the first AT device **34** downstream of the engine **14**. The SCRf is generally configured as a 2-way filter, which includes a catalyzed wash-coat, and carries two functions—actively removes particulate matter and reduces  $\text{NO}_x$ . The SCRf convert nitrogen oxides ( $\text{NO}_x$ ) into diatomic nitrogen ( $\text{N}_2$ ) and water ( $\text{H}_2\text{O}$ ) with the aid of the  $\text{NO}_2$  generated by the DOC, as described above. For effective removal of  $\text{NO}_x$ , the SCR conversion process additionally requires a predetermined amount of ammonia ( $\text{NH}_3$ ) to be present in the exhaust gas flow **24**.

The DPF is configured to collect and dispose of the particulate matter emitted by a diesel engine prior to the exhaust gas flow being discharged to the atmosphere. Accordingly, the DPF acts as a trap for removing the particulate matter, specifically, soot, from the exhaust flow. The LNT is generally configured to reduce oxides of nitrogen or  $\text{NO}_x$  that are emitted by a diesel engine as a byproduct of the reaction of nitrogen and oxygen gases in the air following a combustion event. The LNT removes  $\text{NO}_x$  molecules from the exhaust gas flow by trapping and storing them internally during operation of the engine, thus acting like a molecular sponge. Typically, the LNT includes a ceramic honeycomb substrate structure with a catalyzed wash-coat, i.e., mixed with active precious metal, that is applied to channels of the substrate. The LNT continues to collect  $\text{NO}_x$  molecules during operation of the engine until the trap is full. Once the LNT becomes full, and in order for it to be capable of adsorbing more  $\text{NO}_x$ , the trap is generally purged or regenerated to restore its storage capacity. Such regeneration of the LNT is typically accomplished via injection of hydrocarbons, i.e., fuel **31**, directly into the exhaust gas flow upstream of the trap.

The AT system 32 includes the energy-storage system 22, and also includes a heating element 36 configured to heat the respective AT device 34. The heating element 36 may be specifically used to pre-heat the AT device immediately after a cold-start of the engine 14. The heating element 36 may be either embedded in or attached to the corresponding catalyst substrate 34B. The AT system 32 additionally includes an energy-discharge unit 38. The energy-discharge unit 38 includes a capacitor 38-1, such as an electrolytic capacitor, and a battery 38-2, thereby configured as an integrated capacitor-battery combination. The energy-discharge unit 38 may be independent from the energy-storage system 22. Alternatively, the energy-discharge unit 38 may be in electrical communication with the energy-storage system 22, and thus configured to receive and store electrical energy therefrom. Notably, the energy-discharge unit 38 does not require a DC-DC converter to achieve appropriate functionality

In general, a capacitor is a passive two-terminal electrical device configured to store electrical energy in an electric field. The capacitor 38-1 may be configured as a supercapacitor or ultra-capacitor. In general, a supercapacitor is a high-capacity electrochemical capacitor with capacitance values exceeding typical capacitors, but having lower voltage limits, that bridge the gap between electrolytic capacitors and rechargeable batteries. Supercapacitors typically store 10 to 100 times more energy per unit volume or mass than electrolytic capacitors, can accept and deliver charge much faster than batteries, and tolerate many more charge and discharge cycles than rechargeable batteries. Supercapacitors are used in applications requiring many rapid charge/discharge cycles rather than long term compact energy storage.

The capacitor 38-1 is additionally configured to discharge the electrical energy received from the battery 38-2 to power the heating element 36 at a contact element 36A and thereby heat the AT device 34. The electric heating element 36 may be arranged in the exhaust gas flow 24, i.e., in the exhaust passage 26A, upstream of the AT device 34. In such an embodiment, the electric heating element 36 may be configured to combust fuel and air inside the exhaust gas flow 24 to thereby heat the AT device 34. Alternatively, electric heating element 36 may be configured to add a measure of heat energy to the exhaust gas flow 24 upstream of the AT device 34 that, while short of commencing combustion, would be sufficient to further increase temperature of the already hot exhaust gas.

In particular embodiments, the catalyst monolith 34A may include a ceramic catalyst substrate 34B activated by the elevated temperature of the exhaust gas flow 24. In such an embodiment, the heating element 36 may be embedded in the catalyst substrate 34B to heat the subject substrate. Alternatively, the catalyst monolith 34A may include a metallic catalyst substrate 34B, and the subject metallic catalyst substrate may be configured as the heating element 36, i.e., to directly receive the electrical energy either from the energy-storage system 22 or from the energy-discharge unit 38. Also, the catalyst substrate 34B may include at least one precious metal element activated by the elevated temperature of the exhaust gas flow 24. In such an embodiment, the heating element 36 may be mounted externally to the catalyst monolith to heat the precious metal element(s). The precious metal elements in the catalyst substrate 34B may be platinum (Pt), palladium (Pd), and rhodium (Rh). The catalyst monolith 34A may include other supportive catalyst ingredients, such as Ce, Zr, Mg, Mn, Co, Mo, Ni, Cu, Fe, Ba, La, Sr, Va, Ti, Si, Au, Ag, P and their oxides.

After a cold-start of the engine 14, i.e., when the engine is activated with its temperature at or near ambient, the engine proceeds through a "warm-up" period during which the engine's operating temperature is steadily increased. During the first couple minutes of operation of an internal combustion engine that has been started from a cold condition, an amount of exhaust emissions may be significantly higher than emissions during the engine's steady state operation. In cold engines fuel does not vaporize completely, thus requiring richer air-fuel ratios. Rich air-fuel ratios, in turn, generate higher emissions of hydrocarbons, nitrogen oxides, and carbon monoxide, which diminish as a result of the engine reaching operating temperature. A vehicle with a cold engine also generates increased exhaust emissions because a typical AT device is less efficient under cold conditions and until the subject AT device achieves light-off, i.e., reaches its effective operating temperature. According to the present disclosure, the energy-discharge unit 38 is used to apply heat energy to the AT device 34 to reduce the time it takes for the AT device to light-off. Additionally, the motor-generator 20 may be configured to supply electrical energy to the energy-storage system 22 or to the energy-discharge unit 38, or directly to the heating element 36, to accelerate the light-off of the AT device 34.

As shown in FIG. 1, the vehicle 10 also includes a controller 40. The controller 40 may be an electronic control module (ECM) or a powertrain controller, for example, configured to regulate operation of the engine 14, the transmission 16, the motor-generator 20, and the energy storage system 22. The controller 40 may be additionally configured to regulate the motor-generator 20 to supply electrical energy to the heating element 36 after the capacitor 38-1 has discharged the received electrical energy. Alternatively, as shown in FIG. 2, the controller 40 may be a dedicated electronic controller configured to regulate operation of the energy-discharge unit 38 in response to a command from an ECM after an engine key-on event had occurred. The motor-generator 20 may be used to supply electrical energy to the heating element 36 when the engine 14 is running and generating exhaust gas flow 24, such that the heating element is used to supplement the heat energy provided by the exhaust gas.

In order to appropriately perform the above tasks, the controller 40 includes a memory, at least some of which is tangible and non-transitory. The memory may be a recordable medium that participates in providing computer-readable data or process instructions. Such a medium may take many forms, including but not limited to non-volatile media and volatile media. Non-volatile media for the controller 40 may include, for example, optical or magnetic disks and other persistent memory. Volatile media may include, for example, dynamic random access memory (DRAM), which may constitute a main memory. Such instructions may be transmitted by one or more transmission medium, including coaxial cables, copper wire and fiber optics, including the wires that comprise a system bus coupled to a processor of a computer.

Memory of the controller 40 may also include a flexible disk or a hard disk, magnetic tape, other magnetic medium, a CD-ROM, DVD, other optical medium, etc. The controller 40 may be configured or equipped with other required computer hardware, such as a high-speed clock, requisite Analog-to-Digital (A/D) and/or Digital-to-Analog (D/A) circuitry, input/output circuitry and devices (I/O), as well as appropriate signal conditioning and/or buffer circuitry. Algorithms required by the controller 40 or accessible thereby

may be stored in the memory and automatically executed to provide the required functionality.

The controller **40** may be additionally configured to identify a cold-start **42** of the engine **14**, and regulate the energy-discharge unit **38** to discharge the received electrical energy via the capacitor **38-1** and power the heating element **36** in response to the identified cold-start **42** of the engine. Typically, an engine coolant **44** is used to remove heat energy from the engine **14**. The AT system **32** may additionally include a first sensor **46** configured to detect a temperature of the engine coolant **44** and a second sensor **48** configured to detect ambient temperature, e.g., temperature of the environment surrounding the vehicle **10**. As shown in FIG. **1**, the controller **40** is in electronic communication with the first and second sensors **46**, **48**, and may be further configured to identify the cold-start **42** of the engine **14** via a comparison of the detected engine coolant **44** and ambient temperatures.

Alternatively, the controller **40** may be configured to detect a key-on event for the engine **14**, or a time check of when the engine was last operated. Any of the above indicators may be used by the controller **40** to determine if heating of the AT device **34** via the heating element **36** is required. For example, in the event down time of the engine **14** exceeds a predetermined amount of time programmed into the controller **40**, the controller may determine that the cold-start **42** is in process, and commence heating the catalyst monolith **34A** of the AT device **34** via the heating element **36**. The controller **40** may be additionally configured to regulate the energy-discharge unit **38** to discharge the received electrical energy thereby. Accordingly, the controller **40** may thus be configured to power the heating element **36** and thereby regenerate the catalyst monolith **34A**. Specifically, in the present embodiment, regeneration of the subject AT device **34** may occur when, for example, the AT device collects or becomes full of sooty particulate matter, and the heating element **36** is powered by the energy-discharge unit **38** to generate sufficient heat energy to burn off the soot.

The detailed description and the drawings or figures are supportive and descriptive of the disclosure, but the scope of the disclosure is defined solely by the claims. While some of the best modes and other embodiments for carrying out the claimed disclosure have been described in detail, various alternative designs and embodiments exist for practicing the disclosure defined in the appended claims. Furthermore, the embodiments shown in the drawings or the characteristics of various embodiments mentioned in the present description are not necessarily to be understood as embodiments independent of each other. Rather, it is possible that each of the characteristics described in one of the examples of an embodiment may be combined with one or a plurality of other desired characteristics from other embodiments, resulting in other embodiments not described in words or by reference to the drawings. Accordingly, such other embodiments fall within the framework of the scope of the appended claims.

What is claimed is:

**1.** An after-treatment (AT) system for treating an exhaust gas flow emitted by an internal combustion engine, the AT system comprising:

- a catalytic converter having a catalyst monolith configured to actively remove a pollutant from the exhaust gas flow;
- a heating element configured to heat the catalyst monolith; and

an energy-discharge unit configured to power the heating element;

wherein the energy-discharge unit includes:

- an energy-storage device configured to supply electrical energy; and

- a capacitor configured to receive the electrical energy from the energy-storage device and discharge the received electrical energy to power the heating element and thereby heat the catalyst monolith;

- a motor-generator configured to supply electrical energy to one of the energy-discharge unit and the heating element; and

- an electronic controller configured to identify a cold-start of the engine, regulate operation of the motor-generator, and regulate the capacitor to discharge the received electrical energy and power the heating element in response to the identified cold-start of the engine.

**2.** The AT system of claim **1**, wherein the electric heating element is arranged in the exhaust gas flow upstream of the catalyst monolith and configured to add heat energy to the exhaust gas flow upstream of the catalyst monolith.

**3.** The AT system of claim **1**, wherein the catalyst monolith includes one of a ceramic and a metallic catalyst substrate configured to remove a pollutant from the exhaust gas flow, and wherein the heating element is one of embedded in and attached to the corresponding catalyst substrate.

**4.** The AT system of claim **3**, wherein the catalyst monolith includes the metallic catalyst substrate, and wherein the metallic catalyst substrate is configured as the heating element.

**5.** The AT system of claim **3**, wherein the catalyst monolith includes a precious metal element activated by elevated temperature of the exhaust gas flow, and wherein the heating element is mounted externally to the catalyst monolith.

**6.** The AT system of claim **1**, wherein the electronic controller is additionally configured to regulate the motor-generator to supply electrical energy to the heating element after the capacitor has discharged the received electrical energy.

**7.** The AT system of claim **1**, further comprising a first sensor configured to detect a temperature of an engine coolant and a second sensor configured to detect ambient temperature, wherein the controller is in electronic communication with the first and second sensors and additionally configured to identify the cold-start of the engine via a comparison of the detected engine coolant and ambient temperatures.

**8.** The AT system of claim **1**, wherein the controller is additionally configured to regulate the capacitor to discharge the received electrical energy and thereby power the heating element to one of heat and regenerate the catalyst monolith.

**9.** A vehicle comprising:

- an internal combustion engine; and

- an after-treatment (AT) system operatively connected to the internal combustion engine for treating an exhaust gas flow emitted thereby, the AT system including:

- a catalytic converter having a catalyst monolith configured to actively remove a pollutant from the exhaust gas flow;

- a heating element configured to heat the catalyst monolith; and

- an energy-discharge unit configured to power the heating element;

- wherein the energy-discharge unit includes:

- an energy-storage device configured to supply electrical energy; and

**9**

a capacitor configured to receive the electrical energy from the energy-storage device and discharge the received electrical energy to power the heating element and thereby heat the catalyst monolith;

a motor-generator configured to supply electrical energy to one of the energy-discharge unit and the heating element; and

an electronic controller configured to identify a cold-start of the engine, regulate operation of the motor-generator, and regulate the capacitor to discharge the received electrical energy and power the heating element in response to the identified cold-start of the engine.

**10.** The vehicle of claim **9**, wherein the electric heating element is arranged in the exhaust gas flow upstream of the catalyst monolith and configured to add heat energy to the exhaust gas flow upstream of the catalyst monolith.

**11.** The vehicle of claim **9**, wherein the catalyst monolith includes one of a ceramic and a metallic catalyst substrate configured to remove a pollutant from the exhaust gas flow, and wherein the heating element is one of embedded in and attached to the corresponding catalyst substrate.

**12.** The vehicle of claim **11**, wherein the catalyst monolith includes the metallic catalyst substrate, and wherein the metallic catalyst substrate is configured as the heating element.

**10**

**13.** The vehicle of claim **11**, wherein the catalyst monolith includes a precious metal element activated by elevated temperature of the exhaust gas flow, and wherein the heating element is mounted externally to the catalyst monolith.

**14.** The vehicle of claim **9**, wherein the electronic controller is additionally configured to regulate the motor-generator to supply electrical energy to the heating element after the capacitor has discharged the received electrical energy.

**15.** The vehicle of claim **9**, wherein:

the engine is cooled via an engine coolant;

the AT system also includes a first sensor configured to detect a temperature of the engine coolant and a second sensor configured to detect ambient temperature; and

the controller is in electronic communication with the first and second sensors, and further configured to identify the cold-start of the engine via a comparison of the detected engine coolant and ambient temperatures.

**16.** The vehicle of claim **9**, wherein the controller is additionally configured to regulate the capacitor to discharge the received electrical energy and thereby power the heating element to regenerate the catalyst monolith.

\* \* \* \* \*