



(12) **United States Patent**
Ishiizumi et al.

(10) **Patent No.:** **US 10,183,669 B2**
(45) **Date of Patent:** **Jan. 22, 2019**

(54) **CONTROL APPARATUS FOR VEHICULAR DRIVE UNIT**

(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota-shi, Aichi-ken (JP)
(72) Inventors: **Kazuya Ishiizumi**, Toyota (JP); **Tsuyoshi Fujikane**, Toyota (JP); **Koji Hattori**, Toyota (JP); **Akira Hino**, Toyota (JP); **Mitsuhiro Fukao**, Toyota (JP)

(73) Assignee: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 70 days.

(21) Appl. No.: **15/440,432**

(22) Filed: **Feb. 23, 2017**

(65) **Prior Publication Data**
US 2017/0253247 A1 Sep. 7, 2017

(30) **Foreign Application Priority Data**
Mar. 2, 2016 (JP) 2016-040502

(51) **Int. Cl.**
B60W 10/02 (2006.01)
B60W 30/18 (2012.01)
(Continued)

(52) **U.S. Cl.**
CPC **B60W 30/18172** (2013.01); **B60W 10/02** (2013.01); **B60W 10/107** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC **B60W 30/18172**; **B60W 10/107**; **B60W 10/02**; **B60W 2710/1005**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,336,888 B1 1/2002 Eguchi
6,344,014 B1* 2/2002 Eguchi B60K 6/485
477/39

2002/0028725 A1 3/2002 Totsuka et al.
2012/0053012 A1 3/2012 Yamada et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1070868 A2 1/2001
JP S61-88065 A 5/1986


(Continued)

Primary Examiner — Justin Holmes
Assistant Examiner — Lillian T Nguyen
(74) *Attorney, Agent, or Firm* — Oliff PLC

(57) **ABSTRACT**

A control apparatus for a vehicular drive unit is provided. The vehicular drive unit includes a continuously variable transmission, and a clutch. The control apparatus includes an electronic control unit that is configured to acquire an oil temperature of hydraulic oil for controlling the continuously variable transmission and the clutch, and control the clutch such that a torque capacity of the clutch becomes smaller than a torque capacity that is set in a case where an oil temperature of the hydraulic oil is higher than a predetermined oil temperature, when the oil temperature is equal to or lower than the predetermined oil temperature, or control the continuously variable transmission such that a speed ratio of the continuously variable transmission becomes equal to or larger than a lower limit set in advance when the oil temperature of the hydraulic oil is equal to or lower than the predetermined oil temperature.

4 Claims, 10 Drawing Sheets



(51) **Int. Cl.**
B60W 10/107 (2012.01)
F16H 61/662 (2006.01)
F16H 61/66 (2006.01)
F16H 59/72 (2006.01)

(52) **U.S. Cl.**
 CPC *F16H 61/66259* (2013.01); *B60W 2510/0291* (2013.01); *B60W 2510/107* (2013.01); *B60W 2520/26* (2013.01); *B60W 2710/027* (2013.01); *B60W 2710/1005* (2013.01); *F16H 59/72* (2013.01); *F16H 2061/6618* (2013.01); *Y10T 477/70* (2015.01)

(58) **Field of Classification Search**
 CPC ... *B60W 2510/0291*; *B60W 2510/107*; *B60W 2520/26*; *B60W 2710/027*; *B60W 2720/26*; *F16H 61/66259*; *F16H 59/07*; *F16H 2061/6618*; *Y10T 477/70*
 See application file for complete search history.

(56) **References Cited**
 U.S. PATENT DOCUMENTS
 2012/0209495 A1* 8/2012 Sakai B60K 6/485
 701/102
 2015/0088391 A1* 3/2015 Ishikawa B60W 10/06
 701/54
 2015/0119195 A1* 4/2015 Onodera F02D 29/00
 477/38

FOREIGN PATENT DOCUMENTS
 JP 2001-030801 A 2/2001
 JP 2001-132828 A 5/2001
 JP 2001-330134 A 11/2001
 JP 2002-081530 A 3/2002
 JP 2004-036848 A 2/2004
 JP 2004-125040 A 4/2004
 JP 2012-051468 A 3/2012
 JP 2012-137123 A 7/2012

* cited by examiner

FIG. 1




FIG. 2




FIG. 3





FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 10



CONTROL APPARATUS FOR VEHICULAR DRIVE UNIT

INCORPORATION BY REFERENCE

The disclosure of Japanese Patent Application No. 2016-040502 filed on Mar. 2, 2016 including the specification, drawings and abstract is incorporated herein by reference in its entirety.

BACKGROUND

1. Technical Field

The present disclosure relates to a control apparatus for a vehicular drive unit, and more particularly, to the control of a vehicular drive unit that is equipped with a belt-type continuously variable transmission.

2. Description of Related Art

There is known a vehicular drive unit that is equipped with a power source, a continuously variable transmission that is constituted of a pair of pulleys and a belt wound around the pair of the pulleys, and a clutch that is provided in a power transmission path between the continuously variable transmission and a driving wheel. A vehicle described in Japanese Patent Application Publication No. 2012-51468 (JP 2012-51468 A) is such an example. In the vehicle described in Japanese Patent Application Publication No. 2012-51468 (JP 2012-51468 A), with a view to restraining a belt from slipping as a result of the inputting of an excessive torque transmitted from a driving wheel side to a continuously variable transmission, the torque capacity of a clutch is reduced. When the excessive torque is input to the continuously variable transmission from the driving wheel side, the clutch is caused to slip, so the belt is restrained from slipping.

SUMMARY

By the way, when a driver suddenly brakes from a tire slip state, the rotational speed of the driving wheel rapidly falls. At this time, an excessive torque is input to the continuously variable transmission from the driving wheel. On this occasion, the belt may slip. In contrast, it is conceivable to adopt a method of restraining the belt from slipping by reducing the torque capacity of the clutch in advance when a tire slip state is detected, in preparation for subsequent sudden braking by the driver. It should be noted herein that the torque capacity of the clutch needs to be made smaller than the belt torque capacity of the continuously variable transmission in order to restrain the belt from slipping. However, when the oil temperature of hydraulic oil for controlling the continuously variable transmission and the clutch is low, the oil pressure responsiveness deteriorates. Therefore, it takes a long time before the torque capacity of the clutch is made smaller than the belt torque capacity. The torque capacity of the clutch may not be made smaller than the belt torque capacity in time for sudden braking. As a result, it may be impossible to restrain the belt from slipping.

The present disclosure provides a control apparatus that can restrain a belt from slipping even when the oil temperature of hydraulic oil is low, in a vehicular drive unit having a belt-type continuously variable transmission and a clutch that is provided in a power transmission path between the continuously variable transmission and a driving wheel.

A control apparatus for a vehicular drive unit according to one aspect of the present disclosure is provided. The vehicular drive unit includes a power source, a continuously

variable transmission, and a clutch. The continuously variable transmission is a belt-type continuously variable transmission. A power of the power source is input to the continuously variable transmission. The clutch is arranged in a power transmission path between the continuously variable transmission and a driving wheel. The control apparatus includes an electronic control unit that is configured to acquire an oil temperature of hydraulic oil for controlling the continuously variable transmission and the clutch, and control the clutch such that a torque capacity of the clutch becomes smaller than a torque capacity that is set in a case where an oil temperature of the hydraulic oil is higher than a predetermined oil temperature, when the oil temperature is equal to or lower than the predetermined oil temperature, or control the continuously variable transmission such that a speed ratio of the continuously variable transmission becomes equal to or larger than a lower limit set in advance when the oil temperature of the hydraulic oil is equal to or lower than the predetermined oil temperature.

With the control apparatus according to this aspect of the present disclosure, when the oil temperature of hydraulic oil is equal to or lower than the predetermined oil temperature, the torque capacity of the clutch is controlled to a value smaller than the torque capacity that is set in the case where the oil temperature of hydraulic oil is higher than the predetermined oil temperature. Thus, when a slip of the driving wheel is detected, the torque capacity of the clutch can be swiftly made smaller than the belt torque capacity of the continuously variable transmission. Alternatively, when the oil temperature of hydraulic oil is equal to the predetermined oil temperature, the speed ratio of the continuously variable transmission is controlled to a value equal to or larger than the lower limit set in advance, so the torque capacity of the clutch becomes small. Therefore, when a slip of the driving wheel is detected, the torque capacity of the clutch can be swiftly made smaller than the belt torque capacity of the continuously variable transmission. As a result, even when an excessive torque is input from the driving wheel side after detection of a slip, the clutch slips, so the belt of the continuously variable transmission can be restrained from slipping.

In the control apparatus according to the aforementioned aspect of the present disclosure, the electronic control unit may be configured to set a command oil pressure of the clutch lower than a command oil pressure that is set in a case where the oil temperature of the hydraulic oil is higher than the predetermined oil temperature, when the oil temperature of the hydraulic oil is equal to or lower than the predetermined oil temperature.

With the control apparatus according to this aspect of the present disclosure, the command oil pressure of the clutch is set lower than the command oil pressure that is set in the case where the oil temperature of hydraulic oil is higher than the predetermined oil temperature. Therefore, the torque capacity of the clutch becomes smaller than the torque capacity at the time when the oil temperature is higher than the predetermined oil temperature. When a slip of the driving wheel is detected, the torque capacity of the clutch can be swiftly made smaller than the belt torque capacity of the continuously variable transmission.

In the control apparatus according to the aforementioned aspect of the present disclosure, the electronic control unit may be configured to control the continuously variable transmission such that a belt torque capacity of the continuously variable transmission becomes larger than in a case where the oil temperature of the hydraulic oil is higher than

the predetermined oil temperature, when the oil temperature of the hydraulic oil is equal to or lower than the predetermined oil temperature.

With the control apparatus according to this aspect of the present disclosure, when the oil temperature of hydraulic oil is equal to or lower than the predetermined oil temperature, the belt torque capacity of the continuously variable transmission is controlled to a value larger than in the case where the oil temperature is higher than the predetermined oil temperature. Therefore, when a slip of the driving wheel is detected, the torque capacity of the clutch can be swiftly made smaller than the belt torque capacity of the continuously variable transmission.

In the control apparatus according to the aforementioned aspect of the present disclosure, the electronic control unit may be configured such that a value of the torque capacity of the clutch in a case where the oil temperature of the hydraulic oil is equal to or lower than the predetermined oil temperature is a value that can be made smaller than a belt torque capacity of the continuously variable transmission within a reference response time set in advance from detection of a slip of the driving wheel.

With the control apparatus according to this aspect of the present disclosure, the value of the torque capacity of the clutch that is set in the case where the oil temperature of hydraulic oil is equal to or lower than the predetermined oil temperature is set to a value that can be made smaller than the belt torque capacity of the continuously variable transmission within the reference response time set in advance from detection of a slip of the driving wheel. Therefore, when a slip of the driving wheel is detected, the torque capacity of the clutch can be made smaller than the belt torque capacity within the reference response time.

In the control apparatus according to the aforementioned aspect of the present disclosure, the electronic control unit may be configured to control the continuously variable transmission in such a manner as to make a belt torque capacity of the continuously variable transmission larger than the torque capacity of the clutch when a slip of the driving wheel is detected.

With the control apparatus according to this aspect of the present disclosure, when a slip of the driving wheel is detected, the belt torque capacity of the continuously variable transmission is enhanced to a value larger than the torque capacity of the clutch. Therefore, even when an excessive torque is input from the driving wheel side, the clutch slips, so the belt of the continuously variable transmission is restrained from slipping.

In the control apparatus according to the aforementioned aspect of the present disclosure, the electronic control unit may be configured to control the power source such that a torque of the power source is limited to a torque within such a range as not to cause the clutch to slip at a time of transmission of the torque of the power source to the clutch, when the torque capacity of the clutch becomes smaller than a torque capacity at a time when the oil temperature of the hydraulic oil is higher than the predetermined oil temperature.

With the control apparatus according to this aspect of the present disclosure, while the torque capacity of the clutch is controlled to a value smaller than the torque capacity at the time when the oil temperature of hydraulic oil is higher than the predetermined oil temperature, the torque of the power source is limited to such a range that the clutch does not slip when the torque is transmitted to the clutch. Therefore, the clutch is restrained from slipping when the torque of the power source is transmitted to the clutch.

BRIEF DESCRIPTION OF THE DRAWINGS

Features, advantages, and technical and industrial significance of exemplary embodiments of the present disclosure will be described below with reference to the accompanying drawings, in which like numerals denote like elements, and wherein:

FIG. 1 is a view showing the outline of a vehicular drive unit to which the present disclosure is favorably applied;

FIG. 2 is a functional block diagram illustrating an input/output system of an electronic control unit that is provided in the drive unit to control an engine, a continuously variable transmission and the like of FIG. 1, and illustrating an essential part of control functions performed by the electronic control unit;

FIG. 3 is a view showing the responsiveness of a torque capacity of a clutch and a belt torque capacity of the continuously variable transmission to an oil temperature;

FIG. 4 is a view showing a relationship between a speed ratio and a realization time that is needed to realize a state where the torque capacity of the clutch is smaller than the belt torque capacity;

FIG. 5 is a flowchart illustrating a control operation that is performed by the electronic control unit of FIG. 2 to make it possible to restrain a belt of the continuously variable transmission from slipping even when an inertia torque is input from driving wheels due to a slip of a vehicle;

FIG. 6 is a time chart showing an operation result based on the flowchart of FIG. 5;

FIG. 7 is a functional block diagram illustrating an essential part of control functions performed by an electronic control unit that controls a vehicular drive unit corresponding to the other embodiment of the present disclosure;

FIG. 8 is a view showing the response characteristics of a torque capacity of a clutch and a belt torque capacity of a continuously variable transmission at the time of a low oil temperature;

FIG. 9 is a flowchart illustrating a control operation that is performed by the electronic control unit of FIG. 7 to make it possible to restrain a belt of the continuously variable transmission from slipping even when an inertia torque is input from driving wheels due to a slip of a vehicle; and

FIG. 10 is a time chart showing an operation result based on the flowchart of FIG. 9.

DETAILED DESCRIPTION OF EMBODIMENTS

The embodiments of the present disclosure will be described hereinafter in detail with reference to the drawings. Incidentally, in the following embodiments of the present disclosure, the drawings are simplified or modified as appropriate, and the dimensional ratios, shapes and the like of respective portions are not necessarily depicted with accuracy.

FIG. 1 is a view showing the outline of a vehicular drive unit 10 (hereinafter referred to as the drive unit 10) to which the present disclosure is favorably applied. The drive unit 10 is configured to include an engine 12 as a power source, a torque converter 14, a belt-type continuously variable transmission 16, a clutch 18, a pair of reduction gears 20, a differential device 22 and a pair of right and left driving wheels 24.

The engine 12 is configured as an internal combustion engine, for example, a gasoline engine, a diesel engine or the like. The torque converter 14 is equipped with a pump impeller 14p that is coupled to a crankshaft 26 of the engine

12, and a turbine impeller 14t corresponding to an output-side member of the torque converter 14, and transmits power via fluid.

The continuously variable transmission 16 is provided in a power transmission path between an input shaft 28 that is coupled to the turbine impeller 14t of the torque converter 14 and a first output shaft 30. The continuously variable transmission 16 is equipped with a primary pulley 32 (a variable pulley 32) which is an input-side member coupled to the input shaft 28 and whose effective diameter is variable, a secondary pulley 34 (a variable pulley 34) which is an output-side member and whose effective diameter is variable, and a transmission belt 36 that is wound around the pair of the primary pulley 32 and the secondary pulley 34. Power is transmitted via a frictional force between the pair of the variable pulleys 32 and 34 and the transmission belt 36.

The primary pulley 32 is equipped with a fixed sheave 32a as an input-side fixed rotating body, a movable sheave 32b as an input-side movable rotating body that is provided relatively unrotatably around an axis of the fixed sheave 32a and movably in an axial direction thereof, and a hydraulic cylinder 32c that generates a thrust force for moving the movable sheave 32b to change the width of a V-shaped groove between the fixed sheave 32a and the movable sheave 32b.

The secondary pulley 34 is configured to be equipped with a fixed sheave 34a as an output-side fixed rotating body, a movable sheave 34b as an output-side movable rotating body that is provided relatively unrotatably around an axis of the fixed sheave 34a and movably in an axial direction thereof, and a hydraulic cylinder 34c that generates a thrust force for moving the movable sheave 34b to change the width of a V-shaped groove between the fixed sheave 34a and the movable sheave 34b.

Due to a change in a hanging diameter (the effective diameter) of the transmission belt 36 resulting from a change in the width of the V-shaped groove of the pair of the variable pulleys 32 and 34, an actual speed ratio (a gear ratio) γ (=an input shaft rotational speed/an output shaft rotational speed) is continuously changed. For example, when the V-groove width of the primary pulley 32 is narrowed, the speed ratio γ is reduced. That is, the continuously variable transmission 16 is upshifted. Besides, when the width of the V-shaped groove of the primary pulley 32 is widened, the speed ratio γ is increased. That is, the continuously variable transmission 16 is downshifted.

The clutch 18 is provided between the first output shaft 30 and a second output shaft 31 that is coupled to a drive gear 20a that constitutes the pair of the reduction gears 20. The clutch 18 corresponds to a disconnection/connection device that disconnects/connects the first output shaft 30 and the second output shaft 31 from/to each other, and is a hydraulic frictional engagement device that is frictionally engaged by a hydraulic cylinder 18a.

The pair of the reduction gears 20 are configured to be equipped with the drive gear 20a and a driven gear 20b that also functions as an input rotary member of the differential device 22. The differential device 22 transmits a power input from the driven gear 20b to the right and left driving wheels 24 via a pair of right and left wheels 38 while imparting a difference in rotational speed to the pair of the right and left wheels 38 as appropriate. Incidentally, a differential gear in the differential device 22 is configured according to a known art, so detailed description thereof will be omitted.

FIG. 2 is a functional block diagram illustrating an input/output system of an electronic control unit 50 that is provided in the drive unit 10 to control the engine 12, the

continuously variable transmission 16 and the like, and illustrating an essential part of control functions performed by the electronic control unit 50. The electronic control unit 50 is configured to include a so-called microcomputer that is equipped with, for example, a CPU, a RAM, a ROM, an input/output interface and the like, and performs various kinds of control of the drive unit 10 by performing a signal processing according to a program stored in advance in the ROM while utilizing a temporary storage function of the RAM. For example, the electronic control unit 50 performs output control of the engine 12, shift control and belt clamping force control of the continuously variable transmission 16, torque capacity control of the clutch 18 and the like, and is configured to be divided into an electronic control unit for engine control, an electronic control unit for continuously variable transmission control or the like if necessary.

Signals representing a rotational angle (a position) Acr of the crankshaft and a rotational speed of the engine 12 (an engine rotational speed) Ne as detection results of an engine rotational speed sensor 52, a signal representing an input shaft rotational speed Nin , that is, a rotational speed of the input shaft 28 of the continuously variable transmission 16 as a detection result of an input shaft rotational speed sensor 54, a signal representing a rotational speed $Nsec$ of the secondary pulley 34 of the continuously variable transmission 16 and the first output shaft 30 coupled thereto as a detection result of a first output shaft rotational speed sensor 56, a signal representing a rotational speed $Nout$ of the second output shaft 31 corresponding to a vehicle speed V as a detection result of a second output shaft rotational speed sensor 58, a signal representing a throttle opening degree θth of an electronic throttle valve as a detection result of a throttle sensor 60, a signal representing an accelerator opening degree Acc , that is, an operation amount of an accelerator pedal as an amount of acceleration requested by a driver as a detection result of an accelerator opening degree sensor 62, a signal representing a brake-on condition Bon indicating a state where a foot brake as a regular brake has been operated as a detection result of a foot brake switch 64, a signal representing a lever position (an operation position) Psh of a shift lever as a detection result of a lever position sensor 66, a signal representing an oil temperature $Toil$ of hydraulic oil for controlling the continuously variable transmission 16 and the clutch 18 as a detection result of an oil temperature sensor 68, and the like are supplied to the electronic control unit 50.

Besides, engine output control command signals Se for output control of the engine 12, oil pressure control command signals $Scvt$ for oil pressure control regarding the shifting of the continuously variable transmission 16, an oil pressure control command signal Scl for adjusting the torque capacity of the clutch 18, and the like are output from the electronic control unit 50. In concrete terms, a throttle signal for controlling the opening/closing of the electronic throttle valve by driving a throttle actuator, an injection signal for controlling the amount of fuel injected from a fuel injection device, an ignition timing signal for controlling the ignition timing of the engine 12 by an ignition device, and the like are output as the aforementioned engine output control command signals Se . Besides, a command signal for driving a linear solenoid valve (not shown) that adjusts a primary pressure Pin that is supplied to the hydraulic cylinder 32c constituting the primary pulley 32, a command signal for driving a linear solenoid valve (not shown) that adjusts a secondary pressure $Pout$ that is supplied to the hydraulic cylinder 34c constituting the secondary pulley 34, and the

like are output to an oil pressure control circuit **70** as the aforementioned oil pressure control command signals $Scvt$. Furthermore, a command signal for driving a linear solenoid valve that adjusts an oil pressure Pcl that is supplied to the hydraulic cylinder **18a** of the clutch **18** is output to the oil pressure control circuit **70** as the oil pressure control command signal Scl .

Next, the control functions of the electronic control unit **50** will be described. An engine output control unit **80** (engine output control means) shown in FIG. 2 outputs the engine output control command signals Se such as the throttle signal, the injection signal, the ignition timing signal and the like to the throttle actuator, the fuel injection device and the ignition device respectively for the sake of, for example, output control of the engine **12**. The engine output control unit **80** sets a target engine torque Te^* for obtaining a required driving force (a driving torque) that is calculated based on, for example, the accelerator opening degree Acc and the vehicle speed V , and performs opening/closing control of the electronic throttle valve by the throttle actuator such that the target engine torque Te^* is obtained. In addition, the engine output control unit **80** controls the fuel injection amount by the fuel injection device, and controls the ignition timing by the ignition device.

A continuously variable shift control unit **82** (continuously variable shift control means) controls the speed ratio γ of the continuously variable transmission **16** such that a target speed ratio γ^* that is calculated based on the accelerator opening degree Acc , the vehicle speed V , a brake-on signal Bon and the like is achieved. In concrete terms, the continuously variable shift control unit **82** decides a primary command pressure $Pintgt$ as a command value of the primary pressure Pin (a target primary pressure Pin^*) and a secondary command pressure $Poutgt$ as a command value of the secondary pressure $Pout$ (a target secondary pressure $Pout^*$) in such a manner as to achieve the target speed ratio γ^* of the continuously variable transmission **16** at which an operating point of the engine **12** is on an optimal fuel economy line while preventing the belt of the continuously variable transmission **16** from slipping, in other words, such that a target engine rotational speed Ne^* at which the operating point of the engine **12** is on the optimal fuel economy line is achieved, and outputs the primary command pressure $Pintgt$ and the secondary command pressure $Poutgt$ to the oil pressure control circuit **70**. Incidentally, the continuously variable shift control unit **82** calculates, as needed, the actual speed ratio γ ($=Nin/Nsec$) of the continuously variable transmission **16** based on the first output shaft rotational speed $Nsec$ and the input shaft rotational speed Nin .

A clutch torque control unit **84** (clutch torque control means) controls the torque capacity of the clutch **18** that is provided between the first output shaft **30** and the second output shaft **31**, in accordance with the running state of the vehicle. At the time of normal running, the clutch torque control unit performs control such that a torque transmitted from the continuously variable transmission **16** is transmitted to the driving wheels **24** without being lost, namely, that a torque capacity Tcl of the clutch **18** becomes larger than a transmissible belt torque capacity $Tcvt$ of the continuously variable transmission **16**. Incidentally, the belt torque capacity $Tcvt$ of the continuously variable transmission **16** is calculated based on a relationship determined in advance, from an oil pressure Pin of the hydraulic cylinder **32c** of the primary pulley **32** and an oil pressure of the hydraulic cylinder **34c** of the secondary pulley **34**. Besides, the torque

capacity Tcl of the clutch **18** is calculated based on the oil pressure Pcl of the hydraulic cylinder **18a** of the clutch **18**.

Besides, when the rotational speed of the driving wheels **24** rapidly falls due to sudden braking by the driver, a change in a friction coefficient μ of a road surface or the like with the driving wheels **24** (tires) slipping, an inertia torque resulting from a change in rotational speed is input to the continuously variable transmission **16** from the driving wheel sides. This inertia torque may cause a belt of the continuously variable transmission **16** to slip. Thus, upon detecting a slip of the driving wheels **24**, the clutch torque control unit **84** reduces the torque capacity Tcl of the clutch **18** that is provided in the power transmission path between the continuously variable transmission **16** and the driving wheels **24**, to a value that is set in advance smaller than the belt torque capacity $Tcvt$ of the continuously variable transmission **16**. Incidentally, when the amount of change in each of the engine rotational speed Ne , the input shaft rotational speed Nin , the rotational speed $Nsec$ of the first output shaft **30** and the rotational speed $Nout$ of the second output shaft **31** per unit time exceeds a prescribed value set in advance, it is determined that the driving wheels **24** have slipped.

In conjunction with the control by the aforementioned clutch torque control unit **84**, upon detecting a slip of the driving wheels **24**, the continuously variable shift control unit **82** increases the belt torque capacity $Tcvt$ of the continuously variable transmission **16** to a value that is set in advance larger than the torque capacity Tcl of the clutch **18**. Due to the performance of this control, the torque capacity Tcl of the clutch **18** becomes smaller than the belt torque capacity $Tcvt$ of the continuously variable transmission **16**. Therefore, even when an inertia torque is transmitted from the driving wheel sides, the clutch **18** slips to restrain the belt of the continuously variable transmission **16** from slipping and protect the transmission belt **36**.

It should be noted herein that when a slip is detected, the torque capacity Tcl of the clutch **18** is desired to be swiftly made smaller than the belt torque capacity $Tcvt$ of the continuously variable transmission **16** ($Tcl < Tcvt$). Thus, a reference response time $trep$ as a permissible time for making the torque capacity Tcl of the clutch **18** smaller than the belt torque capacity $Tcvt$ of the continuously variable transmission is set in advance with respect to a time point when a slip is detected. The torque capacity Tcl of the clutch **18** is so controlled as to become smaller than the belt torque capacity $Tcvt$ of the continuously variable transmission **16** within this reference response time $trep$. Incidentally, the reference response time $trep$ is a value that is obtained in advance experimentally, and is set to a time (e.g., about 0.2 sec) shorter than a period from the occurrence of a slip to the inputting of an inertia torque.

By the way, the responsiveness of the torque capacity Tcl of the clutch **18** changes in accordance with the oil pressure responsiveness of the hydraulic cylinder **18a** of the clutch **18**, and the responsiveness of the belt torque capacity $Tcvt$ of the continuously variable transmission **16** changes in accordance with the oil pressure responsiveness of the hydraulic cylinders **32c** and **34c** of the continuously variable transmission **16**. For example, when the oil temperature $Toil$ of the hydraulic oil in the oil pressure control circuit **70** becomes low, both the responsiveness of the torque capacity Tcl of the clutch **18** and the responsiveness of the belt torque capacity $Tcvt$ of the continuously variable transmission **16** deteriorate as the viscosity of the hydraulic oil increases.

FIG. 3 shows the responsiveness of the torque capacity Tcl of the clutch **18** and the belt torque capacity $Tcvt$ of the continuously variable transmission **16** to the oil temperature

Toil. FIG. 3 shows the responsiveness at the time when the oil temperature $Toil$ of hydraulic oil is equal to $80^{\circ}C$., and the responsiveness at the time when the oil temperature $Toil$ of hydraulic oil is equal to $-30^{\circ}C$. Other conditions including the speed ratio γ are the same. FIG. 3 shows a case where a predetermined value α is output as a command value of the torque capacity Tcl of the clutch **18** and a predetermined value β is output as a command value of the belt torque capacity $Tcvt$ of the continuously variable transmission **16** at a time point $t1$.

When the oil temperature $Toil$ of hydraulic oil is equal to $80^{\circ}C$., the torque capacity Tcl of the clutch **18** and the belt torque capacity $Tcvt$ of the continuously variable transmission **16** swiftly change from the time point $t1$ as a result of low viscosity of hydraulic oil and high responsiveness of oil pressure. Then, the torque capacity Tcl becomes smaller than the belt torque capacity $Tcvt$ within the reference response time $trep$ that is set in advance with respect to the time point $t1$. Accordingly, when a slip is detected, for example, at the time point $t1$ and the torque capacity Tcl is so controlled as to become smaller than the belt torque capacity $Tcvt$, the torque capacity Tcl becomes smaller than the belt torque capacity $Tcvt$ within the reference response time $trep$. Therefore, the belt can be restrained from slipping after the occurrence of a slip.

On the other hand, when the oil temperature $Toil$ of hydraulic oil is equal to $-30^{\circ}C$., the torque capacity Tcl of the clutch **18** and the belt torque capacity $Tcvt$ of the continuously variable transmission **16** gently change at and after the time point $t1$ as a result of high viscosity of hydraulic oil and low responsiveness of oil pressure. Thus, at a time point $t2$ after the lapse of the reference response time $trep$ from the time point $t1$ as well, the torque capacity Tcl does not become smaller than the belt torque capacity $Tcvt$. Accordingly, even when a slip is detected, for example, at the time point $t1$ and the torque capacity Tcl is so controlled as to become smaller than the belt torque capacity $Tcvt$, the torque capacity Tcl does not become smaller than the belt torque capacity $Tcvt$ within the reference response time $trep$. Thus, a slip of the belt may occur due to an inertia torque that is input at and after the time point $t2$.

As described above, the responsiveness of the torque capacity Tcl of the clutch **18** and the responsiveness of the belt torque capacity $Tcvt$ of the continuously variable transmission **16** change in accordance with the oil temperature $Toil$ of hydraulic oil. Therefore, the time required to make the torque capacity Tcl smaller than the belt torque capacity $Tcvt$ after the occurrence of a slip may exceed the reference response time $trep$. Thus, the torque capacity Tcl of the clutch **18** can be made smaller than the belt torque capacity $Tcvt$ of the continuously variable transmission **16** until the lapse of the reference response time $trep$ after the occurrence of a slip, by performing the control to be described below in accordance with the oil temperature $Toil$ of hydraulic oil. The control that makes the foregoing possible will be described hereinafter.

Returning to FIG. 2, an oil temperature determination unit **86** (oil temperature determination means) determines whether or not the oil temperature $Toil$ of hydraulic oil detected by the oil temperature sensor **68** has become equal to or lower than a predetermined oil temperature $T\alpha$ set in advance. The predetermined oil temperature $T\alpha$ is a value that is obtained in advance through an experiment or an analysis, and is set to a threshold of the oil temperature $Toil$ that can make the torque capacity Tcl smaller than the belt torque capacity $Tcvt$ within the reference response time $trep$, or to the vicinity of the threshold. When the oil temperature

$Toil$ is higher than the predetermined oil temperature $T\alpha$, the control of making the torque capacity Tcl smaller than the belt torque capacity $Tcvt$ within the reference response time $trep$ (hereinafter referred to as low oil temperature belt slip restraint control) is not performed even in a low oil temperature state that will be described later. On the other hand, when the oil temperature $Toil$ is equal to or lower than the predetermined oil temperature $T\alpha$, low oil temperature belt slip restraint control is performed. That is, the oil temperature determination unit **86** has the function of determining whether to perform low oil temperature belt slip restraint control or not.

A speed ratio lower limit setting unit **88** (speed ratio lower limit setting means) executes a setting for speed ratio lower limit when the oil temperature determination unit **86** determines that the oil temperature $Toil$ is equal to or lower than the predetermined oil temperature $T\alpha$. The speed ratio lower limit setting unit **88** sets a lower limit γ_{low} of the speed ratio γ of the continuously variable transmission **16**. When the speed ratio lower limit setting unit **88** sets the lower limit γ_{low} of the speed ratio γ of the continuously variable transmission **16**, the continuously variable shift control unit **82** performs control such that the speed ratio γ of the continuously variable transmission **16** becomes equal to or larger than the lower limit γ_{low} .

For example, when the speed ratio lower limit setting unit **88** sets the lower limit γ_{low} of the speed ratio γ , the continuously variable shift control unit **82** sets the target speed ratio γ^* , which is calculated based on the accelerator opening degree Acc , the vehicle speed V or the like, to the lower limit γ_{low} as soon as the target speed ratio γ^* becomes smaller than the lower limit γ_{low} . Incidentally, when the calculated target speed ratio γ^* is equal to or larger than the lower limit γ_{low} , the continuously variable shift control unit **82** performs control such that the speed ratio γ becomes equal to the calculated target speed ratio γ^* .

The lower limit γ_{low} is obtained in advance experimentally or analytically. In concrete terms, the lower limit γ_{low} is set to a value that can make the torque capacity Tcl of the clutch **18** smaller than the belt torque capacity $Tcvt$ of the continuously variable transmission **16** within the reference response time $trep$. FIG. 4 shows a relationship between the speed ratio γ and a realization time $tcon$ required to make the torque capacity Tcl smaller than the belt torque capacity $Tcvt$ at each of oil temperatures ($-30^{\circ}C$., $-20^{\circ}C$., $-10^{\circ}C$. and $0^{\circ}C$.). Incidentally, FIG. 4 is obtained based on an experiment.

In FIG. 4, the axis of abscissa represents the speed ratio γ of the continuously variable transmission **16** during running, and the axis of ordinate represents the realization time $tcon$ that is required to make the torque capacity Tcl of the clutch **18** smaller than the belt torque capacity $Tcvt$. Besides, in the drawing, "each black circle" indicates a case where the oil temperature of hydraulic oil is equal to $-30^{\circ}C$., "each blank triangle" indicates a case where the oil temperature $Toil$ is equal to $-20^{\circ}C$., "each black square" indicates a case where the oil temperature $Toil$ is equal to $-10^{\circ}C$., and "each blank circle" indicates a case where the oil temperature $Toil$ is equal to $0^{\circ}C$.

As shown in FIG. 4, the realization time $tcon$ shortens as the speed ratio γ increases. That is, the swiftness with which the torque capacity Tcl can be made smaller than the belt torque capacity $Tcvt$ increases as the speed ratio γ increases. This is because of the following reason. The torque capacity Tcl (a one-axis equivalent value) that is converted in the case where the clutch **18** is arranged concentrically with the engine **12** (on the input shaft **28**) decreases as the speed ratio

11

γ increases. Thus, even when the amount of change (the amount of decrease) of the hydraulic cylinder **18a** of the clutch **18** is small, the torque capacity T_{cl} can be made smaller than the belt torque capacity T_{cvt} . That is, even when the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** remains the same, the torque capacity T_{cl} (the one-axis equivalent value) that is converted in the case where the clutch **18** is arranged concentrically with the engine **12** decreases as the speed ratio γ of the continuously variable transmission **16** increases. Therefore, the torque capacity T_{cl} can be swiftly made smaller than the belt torque capacity T_{cvt} .

Besides, the realization time t_{con} lengthens as the oil temperature $Toil$ falls. For example, if a comparison is made at the same speed ratio γ , the realization time t_{con} is the longest in the case where the oil temperature $Toil$ is equal to -30° C. as shown in FIG. 4. Then, the realization time t_{con} shortens as the oil temperature shifts from -20° C. to -10° C. and then to 0° C.

The case where the oil temperature $Toil$ is equal to -30° C. will be described. In a region where the speed ratio γ is smaller than a predetermined value γ_a , the realization time t_{con} is longer than the foregoing reference response time t_{rep} . When the speed ratio γ reaches the predetermined value γ_a , the realization time t_{con} becomes equal to the reference response time t_{rep} . Accordingly, in the region where the speed ratio γ is smaller than the predetermined value γ_a , it is difficult to make the torque capacity T_{cl} smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} . However, when the speed ratio becomes equal to or larger than the predetermined value γ_a , the torque capacity T_{cl} can be made smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} .

In the case where the oil temperature $Toil$ is equal to -20° C., in a region where the speed ratio γ is smaller than a predetermined value γ_b , the realization time t_{con} is longer than the reference response time t_{rep} . When the speed ratio γ reaches the predetermined value γ_b , the realization time t_{con} becomes equal to the reference response time t_{rep} . Accordingly, in the region where the speed ratio γ is smaller than the predetermined value γ_b , it is difficult to make the torque capacity T_{cl} smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} . However, when the speed ratio becomes equal to or larger than the predetermined value γ_b , the torque capacity T_{cl} can be made smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} .

Besides, in the case where the oil temperature $Toil$ is equal to -10° C. or 0° C., regardless of the value of the speed ratio γ , the realization time t_{con} is shorter than the reference response time t_{rep} . Thus, in the case where the oil temperature $Toil$ is equal to -30° C., the lower limit γ_{low} of the speed ratio γ is set to the predetermined value γ_a , so the torque capacity T_{cl} can be made smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} . Besides, in the case where the oil temperature $Toil$ is equal to -20° C., the lower limit γ_{low} of the speed ratio γ is set to the predetermined value γ_b , so the torque capacity T_{cl} can be made smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} . Besides, in the case where the oil temperature $Toil$ is equal to -10° C. or 0° C., the torque capacity T_{cl} can be made smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} , without setting the lower limit γ_{low} of the speed ratio γ . In this regard, the predetermined oil temperature To_{α} is set as the oil temperature $Toil$ between -20° C. and -10° C.

12

As described above, the lower limit γ_{low} that can make the torque capacity T_{cl} smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} is obtained in advance at each oil temperature $Toil$ of hydraulic oil, and is stored as a relational map. The speed ratio lower limit setting unit **88** sets the lower limit γ_{low} by referring to the current oil temperature $Toil$, based on the relational map constituted of the oil temperature $Toil$ and the lower limit γ_{low} . By controlling the set lower limit γ_{low} as the lower limit of the speed ratio γ , the continuously variable shift control unit **82** can make the torque capacity T_{cl} of the clutch **18** smaller than the belt torque capacity T_{cvt} of the continuously variable transmission **16** after a slip of the driving wheels **24** is detected, even when the oil temperature $Toil$ is low.

FIG. 5 is a flowchart illustrating a control operation that is performed by the electronic control unit **50** to make it possible to restrain the belt of the continuously variable transmission **16** from slipping even when an inertia torque is input from the driving wheels **24** due to a slip of the vehicle. This flowchart is repeatedly executed during the running of the vehicle.

First of all, in step S1 (the word "step" will be omitted hereinafter) corresponding to the function of the oil temperature determination unit **86**, it is determined whether or not the oil temperature $Toil$ of hydraulic oil is equal to or lower than the predetermined oil temperature To_{α} . If the oil temperature $Toil$ is higher than the predetermined oil temperature To_{α} , the result of the determination in S1 is regarded as negative, and a transition to step 3, which will be described later, is made. If the oil temperature $Toil$ is equal to or lower than the predetermined oil temperature To_{α} , the result of the determination in S1 is regarded as positive, and a transition to S2 is made. In S2 corresponding to the speed ratio lower limit setting unit **88**, the lower limit γ_{low} of the speed ratio γ of the continuously variable transmission **16** is set based on the oil temperature $Toil$.

Subsequently in S3 corresponding to the clutch torque control unit **84**, it is determined whether or not a slip of the driving wheels **24** has been detected. If no slip has been detected, the result of the determination in S3 is regarded as negative, and the present routine is ended. If a slip has been detected, the result of the determination in S3 is regarded as positive, and a transition to S4 is made. In S4 corresponding to the continuously variable shift control unit **82** and the clutch torque control unit **84**, the torque capacity T_{cl} of the clutch **18** is controlled to a value smaller than the belt torque capacity T_{cvt} of the continuously variable transmission **16**.

It should be noted herein that when the oil temperature $Toil$ is equal to the predetermined oil temperature To_{α} , the speed ratio γ of the continuously variable transmission **16** is controlled in advance to a value larger than the lower limit γ_{low} . Therefore, when a slip is detected, the torque capacity T_{c} of the clutch **18** becomes smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} . Accordingly, even when an inertia torque is input to the continuously variable transmission **16** due to sudden braking after the occurrence of a slip, the clutch **18** slips, so the belt of the continuously variable transmission **16** is restrained from slipping.

FIG. 6 is a time chart showing an operation result through the control operation of the electronic control unit **50**. FIG. 6 shows the control operation while running with the oil temperature $Toil$ of hydraulic oil being lower than the predetermined oil temperature To_{α} . In FIG. 6, the axis of abscissa represents an elapsed time t , and the axes of ordinate represent, sequentially from above, the oil temperature $Toil$, the speed ratio γ of the continuously variable

13

transmission **16**, the accelerator opening degree Acc , the brake signal Bon , a tire slip determination signal $SLIP$, the various rotational speeds (the engine rotational speed N_e , the input shaft rotational speed N_{in} , the first output shaft rotational speed N_{sec} and the second output shaft rotational speed N_{out}) and the various torque capacities (the torque capacity T_{cl} and the belt torque capacity T_{cvt}) respectively.

As shown in FIG. 6, the oil temperature $Toil$ of hydraulic oil is lower than the predetermined oil temperature $T\alpha$. Accordingly, the lower limit γ_{low} of the speed ratio γ is set. The speed ratio γ changes toward a high gear side (in such a direction that the speed ratio decreases) at and before the time point $t1$. When the speed ratio γ decreases to the lower limit γ_{low} at the time point $t1$, the speed ratio γ is thereafter held equal to the lower limit γ_{low} .

When a slip is detected at the time point $t2$, the torque capacity T_{cl} of the clutch **18** indicated by a solid line is lowered to a predetermined value set in advance. In parallel, the belt torque capacity T_{cvt} of the continuously variable transmission **16** indicated by an alternate long and short dash line is enhanced to a predetermined value that is set in advance larger than the torque capacity T_{cl} of the clutch **18**. Incidentally, both the torque capacity T_{cl} and the belt torque capacity T_{cvt} , which are shown in FIG. 6, are command values. The actual torque capacity T_{cl} decreases with delay, and the actual belt torque capacity T_{cvt} increases with delay.

Depression of the accelerator pedal by the driver is canceled at a time point $t3$, and the driver depresses a foot brake pedal at a time point $t4$, so an inertia torque resulting from a change in the rotational speed of the driving wheels **24** is input from the driving wheel **24** sides. It should be noted herein that the actual torque capacity T_{cl} becomes smaller than the belt torque capacity T_{cvt} within the reference response time $trep$ set in advance from the time point $t2$. Therefore, the torque capacity T_{cl} is already smaller than the belt torque capacity T_{cvt} at the time point $t4$. Accordingly, even when an inertia torque is input at the time point $t4$, the clutch **18** slips, so the belt of the continuously variable transmission **16** is restrained from slipping.

Incidentally, the reference response time $Trep$ is not mentioned in FIG. 6, but is set sufficiently shorter than a period between the time point $t2$ and the time point $t4$. Besides, when the lower limit γ_{low} of the speed ratio γ is not set, the torque capacity T_c (the one-axis equivalent value) of the clutch **18** is large. Therefore, the actual torque capacity T_c becomes smaller than the actual belt torque capacity T_{cvt} at and after, for example, the time point $t4$. A slip of the belt may be caused by the inertia torque that is input at the time point $t4$.

As described above, according to the present embodiment of the present disclosure, when the oil temperature $Toil$ of hydraulic oil is equal to the predetermined oil temperature $T\alpha$, the speed ratio γ of the continuously variable transmission **16** is controlled to a value larger than the lower limit γ_{low} set in advance, so the torque capacity T_{cl} (the one-axis equivalent value) of the clutch **18** becomes small. Therefore, when a slip of the driving wheels **24** is detected, the torque capacity T_{cl} of the clutch **18** can be swiftly made smaller than the belt torque capacity T_{cvt} of the continuously variable transmission **16**. As a result, even when an excessive inertia torque is input from the driving wheel **24** sides after detection of a slip, the clutch **18** slips, so the belt of the continuously variable transmission **16** can be restrained from slipping.

Besides, according to the present embodiment of the present disclosure, when a slip of the driving wheels **24** is detected, the belt torque capacity T_{cvt} of the continuously

14

variable transmission **16** is enhanced to a value larger than the torque capacity T_{cl} of the clutch **18**. Therefore, even when an excessive inertia torque is input from the driving wheel sides, the clutch **18** slips, so the belt of the continuously variable transmission **16** is restrained from slipping.

Next, the other embodiment of the present disclosure will be described. Incidentally, components common to those of the foregoing embodiment of the present disclosure will be denoted by the same reference symbols respectively in the following description. The description of those components will be omitted.

FIG. 7 is a functional block diagram illustrating an essential part of control functions performed by an electronic control unit **102** that controls a vehicular drive unit **100** corresponding to the other embodiment of the present disclosure. When the oil temperature determination unit **86** determines that the oil temperature $Toil$ of hydraulic oil has become equal to or lower than the predetermined oil temperature $T\alpha$ set in advance, a clutch torque control unit **104** controls the oil pressure P_{cl} (the command oil pressure) of the hydraulic cylinder **18a** of the clutch **18** to a constant pressure P_{con} set in advance.

The constant pressure P_{con} is a value that is obtained in advance through an experiment or an analysis, and is set within a range that can make the torque capacity T_{cl} of the clutch **18** smaller than the belt torque capacity T_{cvt} of the continuously variable transmission **16** within the reference response time $trep$ with respect to a time point when a slip is detected. For example, a relational map constituted of the oil temperature $Toil$ and the constant pressure P_{con} is obtained in advance and stored. The constant pressure P_{con} is a value lower than a command oil pressure that is set when the oil temperature $Toil$ is higher than the predetermined oil temperature $T\alpha$, and is set to a value that falls as the oil temperature $Toil$ falls. Accordingly, when the oil temperature $Toil$ is equal to or lower than the predetermined oil temperature $T\alpha$, the torque capacity T_{cl} of the clutch **18** that is proportional to the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** is controlled to a value smaller than the torque capacity T_{cl} at the time when the oil temperature $Toil$ is higher than the predetermined oil temperature $T\alpha$.

The clutch torque control unit **104** decides the constant pressure P_{con} by referring to the current oil temperature $Toil$, based on the relational map constituted of the oil temperature $Toil$ and the constant pressure P_{con} , and outputs the decided constant pressure P_{con} as a command oil pressure of the hydraulic cylinder **18a** of the clutch **18**. Accordingly, the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** is controlled to the constant pressure P_{con} .

Besides, while the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** is controlled to the constant pressure P_{con} , an engine output control unit **106** sets an upper limit T_{elim} of the target engine torque T_e^* . The upper limit T_{elim} is set within such a range that the clutch **18** does not slip when the engine torque T_e is transmitted to the clutch **18**. In concrete terms, the upper limit T_{elim} is set smaller than the equivalent value (the one-axis equivalent value) of the torque capacity T_{cl} of the clutch **18** at the time when the clutch **18** is arranged concentrically with the engine **12**. Incidentally, the torque capacity of the clutch **18** at this time is a value that is calculated based on the constant pressure P_{con} as a command oil pressure of the hydraulic cylinder **18a** of the clutch **18**. The engine output control unit **106** sets the upper limit T_{elim} as an upper limit of the target engine torque T_e^* and controls the engine torque T_e within

15

a range below the upper limit T_{lim} , so the clutch **18** is restrained from slipping during running.

FIG. **8** shows response characteristics of the torque capacity T_{cl} of the clutch **18** and the belt torque capacity T_{cvt} of the continuously variable transmission **16** at the time when the oil temperature T_{oil} is equal to or lower than the predetermined oil temperature T_{α} (when the oil temperature is low). When the oil temperature is low, the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** is controlled in advance to the constant pressure P_{con} , and the torque capacity T_{cl} also assumes a value smaller than when the oil temperature T_{oil} is higher than the predetermined oil temperature T_{α} (when the oil temperature is high). At the time point t_1 , the belt torque capacity T_{cvt} is enhanced, and the torque capacity T_{cl} becomes smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} . This is because the torque capacity T_{cl} is held equal to a small value in advance due to the fact that the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** is controlled in advance to the constant pressure P_{con} .

Besides, in addition to the aforementioned control, when the oil temperature T_{oil} becomes equal to or lower than the predetermined oil temperature T_{α} , the belt torque capacity T_{cvt} of the continuously variable transmission **16** may be enhanced to a predetermined torque capacity set in advance. In concrete terms, when the oil temperature T_{oil} becomes equal to or lower than the predetermined oil temperature T_{α} , the belt torque capacity T_{cvt} of the continuously variable transmission **16** is controlled to a predetermined torque capacity that is larger than the belt torque capacity T_{cvt} that is set in the case where the oil temperature T_{oil} is higher than the predetermined oil temperature T_{α} . The belt torque capacity T_{cvt} is thus enhanced in advance to the predetermined torque capacity, so the torque capacity T_{cl} can be more swiftly made smaller than the belt torque capacity T_{cvt} when a slip is detected. Incidentally, the predetermined torque capacity is also changed in accordance with the oil temperature T_{oil} , and is preferably changed to a value that increases as the oil temperature T_{oil} falls.

FIG. **9** is a flowchart illustrating a control operation that is performed by the electronic control unit **102** to make it possible to restrain the belt of the continuously variable transmission **16** from slipping even when an inertia torque is input from the driving wheels **24** due to a slip of the vehicle. This flowchart is repeatedly executed during the running of the vehicle.

First of all, in step **S10** (the word "step" will be omitted hereinafter) corresponding to the function of the oil temperature determination unit **86**, it is determined whether or not the oil temperature T_{oil} of hydraulic oil is equal to or lower than the predetermined oil temperature T_{α} . If the oil temperature T_{oil} is higher than the predetermined oil temperature T_{α} , the result of the determination in **S10** is regarded as negative, and a transition to **S12**, which will be described later, is made. If the oil temperature T_{oil} is equal to or lower than the predetermined oil temperature T_{α} , the result of the determination in **S10** is regarded as positive, and a transition to **S11** is made. In **S11** corresponding to the clutch torque control unit **104** and the engine output control unit **106**, the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** is controlled to the constant pressure P_{con} . At the same time, the upper limit T_{lim} of the engine torque T_e is set such that the clutch **18** does not slip during running.

Subsequently in **S12** corresponding to the clutch torque control unit **104**, it is determined whether or not a slip of the driving wheels **24** has been detected. If no slip has been detected, the result of the determination in **S12** is regarded

16

as negative, and the present routine is ended. If a slip has been detected, the result of the determination in **S12** is regarded as positive, and a transition to **S13** is made. In **S13** corresponding to the continuously variable shift control unit **82** and the clutch torque control unit **104**, the belt torque capacity T_{cvt} of the continuously variable transmission **16** is enhanced and controlled to a value larger than the torque capacity T_{cl} of the clutch **18**.

It should be noted herein that if the oil temperature T_{oil} is equal to or lower than the predetermined oil temperature T_{α} , the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** is controlled to the constant pressure P_{con} . Therefore, the torque capacity T_{cl} of the clutch **18** becomes small. When a slip is detected, the torque capacity T_{cl} becomes smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} . Accordingly, even when an inertia torque is input to the continuously variable transmission **16** due to sudden braking after the occurrence of a slip, the clutch **18** slips, and the belt of the continuously variable transmission **16** is restrained from slipping.

FIG. **10** is a time chart showing an operation result through the control operation of the electronic control unit **102**. FIG. **10** shows the control operation while running with the oil temperature T_{oil} of hydraulic oil being lower than the predetermined oil temperature T_{α} . In FIG. **10**, the axis of abscissa represents the elapsed time t , and the axes of ordinate represent, sequentially from above, the oil temperature T_{oil} , the target engine torque T_e^* , the accelerator opening degree Acc , the brake signal Bon , the tire slip determination signal $SLIP$, the various rotational speeds (the engine rotational speed N_e , the input shaft rotational speed N_{in} , the first output shaft rotational speed N_{sec} and the second output shaft rotational speed N_{out}) and the various torque capacities (the torque capacity T_{cl} and the belt torque capacity T_{cvt}) respectively.

As shown at the top of FIG. **10**, the oil temperature T_{oil} of hydraulic oil is lower than the predetermined oil temperature T_{α} at and before the time point t_1 . In this regard, as shown at the bottom of FIG. **10**, the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** is controlled to the constant pressure P_{con} at and before the time point t_1 , so the torque capacity T_{cl} of the clutch **18** is held equal to a small value. Besides, the upper limit T_{lim} of the target engine torque T_e^* is set such that the clutch **18** does not slip during running, so the target engine torque T_e^* is so regulated as to become equal to or smaller than the upper limit T_{lim} .

When a slip is detected at the time point t_1 , the belt torque capacity T_{cvt} of the continuously variable transmission **16**, which is indicated by an alternate long and short dash line, is enhanced to a predetermined value larger than the torque capacity T_{cl} . Incidentally, the belt torque capacity T_{cvt} shown in FIG. **10** is a command value, and the actual belt torque capacity T_{cvt} increases with delay. In concrete terms, the actual belt torque capacity T_{cvt} becomes equal to the predetermined value within the reference response time t_{rep} from the time point t_1 . This reference response time t_{rep} is set to a value shorter than a time interval between the time point t_1 and the time point t_3 .

Depression of the accelerator pedal by the driver is cancelled at the time point t_2 , and the driver depresses the foot brake pedal at the time point t_3 , so an inertia torque resulting from a change in the rotational speed of the driving wheels **24** is input from the driving wheel **24** sides. At this time, the torque capacity T_{cl} is made in advance smaller than the belt torque capacity T_{cvt} . Therefore, even when an

17

inertia torque is input at the time point **t3**, the clutch **18** slips, and the belt of the continuously variable transmission **16** is restrained from slipping.

As described above, according to the present embodiment of the present disclosure, when the oil temperature T_{oil} of hydraulic oil is equal to or lower than the predetermined oil temperature T_{α} , the torque capacity T_{cl} of the clutch **18** is set to a value smaller than the torque capacity that is set in the case where the oil temperature T_{oil} is higher than the predetermined oil temperature T_{α} . Thus, when a slip of the driving wheels **24** is detected, the torque capacity T_{cl} of the clutch **18** can be swiftly made smaller than the belt torque capacity T_{cvt} of the continuously variable transmission **16**. Accordingly, even when an inertia torque is input from the driving wheel **24** sides, the clutch **18** slips, so the belt of the continuously variable transmission **16** is restrained from slipping.

Besides, according to the present embodiment of the present disclosure, the command oil pressure P_{cl} of the clutch **18** is set to the constant pressure P_{con} lower than the command oil pressure that is set in the case where the oil temperature T_{oil} of hydraulic oil is higher than the predetermined oil temperature T_{α} . Therefore, the torque capacity T_{cl} of the clutch **18** is smaller than a torque capacity at the time when the oil temperature T_{oil} is higher than the predetermined oil temperature T_{α} . When a slip of the driving wheels **24** is detected, the torque capacity T_{cl} of the clutch **18** can be swiftly made smaller than the belt torque capacity T_{cvt} of the continuously variable transmission **16**.

Besides, according to the present embodiment of the present disclosure, when the oil temperature T_{oil} of hydraulic oil is equal to or lower than the predetermined oil temperature T_{α} , the belt torque capacity T_{cvt} of the continuously variable transmission **16** is controlled in advance to a value larger than in the case where the oil temperature T_{oil} is higher than the predetermined oil temperature T_{α} . Thus, when a slip of the driving wheels **24** is detected, the torque capacity T_{cl} of the clutch **18** can be swiftly made smaller than the belt torque capacity T_{cvt} of the continuously variable transmission **16**.

Besides, according to the present embodiment of the present disclosure, the torque capacity T_{cl} of the clutch **18** that is set in the case where the oil temperature T_{oil} of hydraulic oil is equal to or lower than the predetermined oil temperature T_{α} is set to a value that can be made smaller than the belt torque capacity T_{cvt} of the continuously variable transmission **16** within the reference response time t_{rep} set in advance from detection of a slip of the driving wheels **24**. Therefore, when a slip of the driving wheels **24** is detected, the torque capacity T_{cl} of the clutch **18** can be made smaller than the belt torque capacity T_{cvt} within the reference response time t_{rep} .

Besides, according to the present embodiment of the present disclosure, when a slip of the driving wheels **24** is detected, the belt torque capacity T_{cvt} of the continuously variable transmission **16** is enhanced to a value larger than the torque capacity T_{cl} of the clutch **18**. Therefore, even when an excessive inertia torque is input from the driving wheel **24** sides, the clutch **18** slips, so the belt of the continuously variable transmission **16** is restrained from slipping.

Besides, according to the present embodiment of the present disclosure, while the torque capacity T_{cl} of the clutch **18** is controlled to a value smaller than a torque capacity at the time when the oil temperature T_{oil} of hydraulic oil is higher than the predetermined oil temperature T_{α} , the engine torque T_e is limited to such a range that

18

the clutch **18** does not slip. Therefore, when the engine torque T_e is transmitted to the clutch **18**, the clutch **18** is restrained from slipping.

Although the embodiments of the present disclosure have been described above in detail based on the drawings, the present disclosure is also applicable to other aspects thereof.

For example, in each of the foregoing embodiments of the present disclosure, when the oil temperature T_{oil} of hydraulic oil is equal to or lower than the predetermined oil temperature T_{α} , the lower limit γ_{low} of the speed ratio γ of the continuously variable transmission **16** is set, or the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** is controlled to the constant pressure P_{con} . However, it is not indispensable to perform one of these two kinds of control. Both the kinds of control may be performed.

Besides, in each of the foregoing embodiments of the present disclosure, the vehicular drive unit **10** is configured to be equipped with the engine **12**, the continuously variable transmission **16**, and the clutch **18** that is provided between the continuously variable transmission **16** and the driving wheels **24**. However, a gear mechanism may be further provided in parallel with the continuously variable transmission **16**, and the power transmission path between the engine **12** and the driving wheels **24** may be changed over to either the continuously variable transmission **16** or the gear mechanism. At this time, the clutch **18** that is provided between the continuously variable transmission **16** and the driving wheels **24** can also be caused to function as a changeover clutch for changing over the power transmission path. Besides, a forward-backward changeover device that changes over the traveling direction of the vehicle may be provided between the torque converter **14** and the continuously variable transmission **16**.

Besides, in each of the foregoing embodiments of the present disclosure, when the oil temperature T_{oil} of hydraulic oil is equal to or lower than the predetermined oil temperature T_{α} , the oil pressure P_{cl} of the hydraulic cylinder **18a** of the clutch **18** is controlled to the constant pressure P_{con} , but is not necessarily limited to the constant pressure P_{con} . The oil pressure may be further lowered when a slip is detected.

Incidentally, the foregoing is nothing more than the embodiments of the present disclosure. The present disclosure can be carried out in modes subjected to various alterations and improvements based on the knowledge of those skilled in the art.

What is claimed is:

1. A control apparatus for a vehicular drive unit, the vehicular drive unit including a power source, a continuously variable transmission, and a clutch, the continuously variable transmission being a belt-type continuously variable transmission, a power of the power source being input to the continuously variable transmission, and the clutch being arranged in a power transmission path between the continuously variable transmission and a driving wheel, the control apparatus comprising:

an electronic control unit configured to:
acquire an oil temperature of hydraulic oil; and
control the clutch such that, when the electronic control unit determines that the acquired oil temperature is equal to or lower than a predetermined threshold, a torque capacity of the clutch is set to a smaller value than a torque capacity that is set in a case where the electronic control unit determines that the acquired oil temperature of the hydraulic oil is higher than the predetermined threshold, wherein

19

when the electronic control unit determines that the acquired oil temperature is equal to or lower than the predetermined threshold, the electronic control unit is configured to set a command oil pressure of the clutch to a smaller value than a command oil pressure that is set by the electronic control unit in a case where the electronic control unit determines that the acquired oil temperature of the hydraulic oil is higher than the predetermined threshold.

2. A control apparatus for a vehicular drive unit, the vehicular drive unit including a power source, a continuously variable transmission, and a clutch, the continuously variable transmission being a belt-type continuously variable transmission, a power of the power source being input to the continuously variable transmission, and the clutch being arranged in a power transmission path between the continuously variable transmission and a driving wheel, the control apparatus comprising:

an electronic control unit configured to:

acquire an oil temperature of hydraulic oil; and

control the clutch such that, when the electronic control unit determines that the acquired oil temperature is equal to or lower than a predetermined threshold, a torque capacity of the clutch is set to a smaller value than a torque capacity that is set in a case where the electronic control unit determines that the acquired oil temperature of the hydraulic oil is higher than the predetermined threshold, wherein

the electronic control unit is configured such that a value of the torque capacity of the clutch in a case where the acquired oil temperature is equal to or lower than the predetermined threshold is a value that can be made smaller than a belt torque capacity of the continuously variable transmission within a reference response time set in advance from detection of a slip of the driving wheel.

3. A control apparatus for a vehicular drive unit, the vehicular drive unit including a power source, a continuously variable transmission, and a clutch, the continuously variable transmission being a belt-type continuously variable transmission, a power of the power source being input to the continuously variable transmission, and the clutch being arranged in a power transmission path between the continuously variable transmission and a driving wheel, the control apparatus comprising:

20

an electronic control unit configured to:

acquire an oil temperature of hydraulic oil; and

control the clutch such that, when the electronic control unit determines that the acquired oil temperature is equal to or lower than a predetermined threshold, a torque capacity of the clutch is set to a smaller value than a torque capacity that is set in a case where the electronic control unit determines that the acquired oil temperature of the hydraulic oil is higher than the predetermined threshold, wherein

the electronic control unit is configured to control the continuously variable transmission in such a manner as to make a belt torque capacity of the continuously variable transmission larger than the torque capacity of the clutch when a slip of the driving wheel is detected.

4. A control apparatus for a vehicular drive unit, the vehicular drive unit including a power source, a continuously variable transmission, and a clutch, the continuously variable transmission being a belt-type continuously variable transmission, a power of the power source being input to the continuously variable transmission, and the clutch being arranged in a power transmission path between the continuously variable transmission and a driving wheel, the control apparatus comprising:

an electronic control unit configured to:

acquire an oil temperature of hydraulic oil; and

control the clutch such that, when the electronic control unit determines that the acquired oil temperature is equal to or lower than a predetermined threshold, a torque capacity of the clutch is set to a smaller value than a torque capacity that is set in a case where the electronic control unit determines that the acquired oil temperature of the hydraulic oil is higher than the predetermined threshold, wherein

the electronic control unit is configured to control the power source such that a torque of the power source is limited to a torque within such a range as not to cause the clutch to slip at a time of transmission of the torque to the clutch, when the torque capacity of the clutch becomes smaller than a torque capacity at a time when the acquired oil temperature is higher than the predetermined threshold.

* * * * *