

US010192230B2

(12) **United States Patent**
Look et al.

(10) **Patent No.:** **US 10,192,230 B2**
(45) **Date of Patent:** ***Jan. 29, 2019**

(54) **SYSTEMS AND METHODS FOR
MANAGEMENT OF THROMBOSIS**

(71) Applicant: **INCUVATE, LLC**, Irvine, CA (US)

(72) Inventors: **David M. Look**, Newport Beach, CA (US); **Bradley S. Culbert**, Mission Viejo, CA (US)

(73) Assignee: **Incuvate, LLC**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/881,529**

(22) Filed: **Jan. 26, 2018**

(65) **Prior Publication Data**
US 2018/0174175 A1 Jun. 21, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/209,989, filed on Jul. 14, 2016, now Pat. No. 9,913,936, which is a (Continued)

(51) **Int. Cl.**
A61B 17/22 (2006.01)
G06Q 30/02 (2012.01)
(Continued)

(52) **U.S. Cl.**
CPC **G06Q 30/0207** (2013.01); **A61B 17/22** (2013.01); **A61B 17/32037** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 17/22; A61B 17/3203; A61B 17/32037; A61B 17/22012;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,114,268 A 10/1914 Kells
1,148,093 A 7/1915 Kells

(Continued)

FOREIGN PATENT DOCUMENTS

DE 3715418 A1 11/1987
EP 806213 A1 11/1997

(Continued)

OTHER PUBLICATIONS

“Comparison of Dimensions and Aspiration Rate of the Pronto V3, Pronto LP, Export XT, Export AP, Fetch, Xtract, Diver C.E. and QuickCat Catheter”, Vascular Solutions, Inc., downloaded from internet Oct. 22, 2014.

(Continued)



Primary Examiner — Victor Nguyen

(74) *Attorney, Agent, or Firm* — Blair Walker IP Services, LLC

(57) **ABSTRACT**

An aspiration system includes an elongate tubular member having a lumen; an aspiration catheter configured to be inserted through the lumen of the elongate tubular member, and including a tubular aspiration member having a proximal end, a distal end, and a lumen, and configured to at least partially extend out of the lumen of the elongate tubular member; an elongate support member coupled to the tubular aspiration member and extending between a proximal end of the aspiration catheter and the proximal end of the tubular aspiration member; and an annular sealing member coupled to the tubular aspiration member and configured to create a seal against an inner surface of the elongate tubular member, when a vacuum sufficient to cause aspiration is actively applied to the lumen of the elongate tubular member.

20 Claims, 36 Drawing Sheets



Related U.S. Application Data					
	continuation of application No. 14/680,017, filed on Apr. 6, 2015, now Pat. No. 9,433,427.			5,378,238 A	1/1995 Peters et al.
				5,380,282 A	1/1995 Burns
				5,383,890 A	1/1995 Miraki et al.
				5,385,562 A	1/1995 Adams et al.
				5,395,315 A	3/1995 Griep
				5,403,274 A	4/1995 Cannon
(60)	Provisional application No. 61/976,975, filed on Apr. 8, 2014, provisional application No. 62/069,817, filed on Oct. 28, 2014, provisional application No. 62/090,822, filed on Dec. 11, 2014.			5,413,561 A	5/1995 Fischell et al.
				5,419,772 A	5/1995 Teitz et al.
				5,421,826 A	6/1995 Crocker et al.
				5,423,742 A	6/1995 Theron
				5,454,788 A	10/1995 Walker et al.
(51)	Int. Cl.			5,468,225 A	11/1995 Teirstein
	<i>A61M 1/00</i> (2006.01)			5,484,412 A	1/1996 Pierpont
	<i>A61B 17/3203</i> (2006.01)			5,486,183 A	1/1996 Middleman et al.
	<i>G06Q 30/06</i> (2012.01)			5,490,837 A	2/1996 Blaeser et al.
	<i>A61B 17/00</i> (2006.01)			5,496,267 A	3/1996 Drasler et al.
(52)	U.S. Cl.			5,522,818 A	6/1996 Keith et al.
	CPC <i>A61M 1/0088</i> (2013.01); <i>G06Q 30/02</i> (2013.01); <i>G06Q 30/0601</i> (2013.01); <i>A61B 2017/00022</i> (2013.01); <i>A61B 2017/00119</i> (2013.01); <i>A61B 2017/22001</i> (2013.01); <i>A61B 2017/22039</i> (2013.01); <i>A61B 2017/22067</i> (2013.01); <i>A61B 2017/22079</i> (2013.01); <i>A61B 2017/22094</i> (2013.01); <i>A61B 2217/005</i> (2013.01)			5,527,274 A	6/1996 Zakko
				5,533,968 A	7/1996 Muni et al.
				5,536,242 A	7/1996 Willard et al.
				5,538,002 A	7/1996 Boussignac et al.
				5,567,203 A	10/1996 Euteneuer et al.
				5,577,674 A	11/1996 Altonji et al.
				5,581,038 A	12/1996 Lampropoulos et al.
				5,606,968 A	3/1997 Mang
				5,624,394 A	4/1997 Barnitz et al.
				5,647,847 A	7/1997 Lafontaine et al.
				5,658,251 A	8/1997 Ressemann et al.
(58)	Field of Classification Search			5,676,654 A	10/1997 Ellis et al.
	CPC <i>A61B 2017/922</i> ; <i>A61B 2017/2215</i> ; <i>A61B 2017/2212</i> ; <i>A61M 1/00</i> ; <i>A61M 1/0031</i>			5,702,413 A	12/1997 LaFontaine
	See application file for complete search history.			5,713,849 A	2/1998 Bosma et al.
				5,713,851 A	2/1998 Boudewijn et al.
				5,713,878 A	2/1998 Moutafis et al.
				5,720,724 A	2/1998 Ressemann et al.
(56)	References Cited			5,730,717 A	3/1998 Gelbfish
	U.S. PATENT DOCUMENTS			5,749,852 A	5/1998 Schwab et al.
				5,762,631 A	6/1998 Klein
				5,772,674 A	6/1998 Nakhjavan
				5,785,685 A	7/1998 Kugler et al.
				5,795,322 A	8/1998 Boudewijn
				5,827,229 A	10/1998 Auth et al.
				5,827,243 A	10/1998 Palestrant
				5,833,706 A	11/1998 St. Germain et al.
				5,843,022 A	12/1998 Willard et al.
				5,843,051 A	12/1998 Adams et al.
				5,855,567 A	1/1999 Ressemann
				5,863,284 A	1/1999 Klein
				5,868,702 A	2/1999 Stevens et al.
				5,871,462 A	2/1999 Yoder et al.
				5,885,238 A	3/1999 Stevens et al.
				5,885,244 A	3/1999 Leone et al.
				5,895,399 A	4/1999 Barbut et al.
				5,910,252 A	6/1999 Truitt et al.
				5,916,192 A	6/1999 Nita et al.
				5,921,958 A	7/1999 Ressemann et al.
				5,938,645 A	8/1999 Gordon
				5,941,871 A	8/1999 Adams et al.
				5,944,686 A	8/1999 Patterson et al.
				5,957,901 A	9/1999 Mottola et al.
				5,976,107 A	11/1999 Mertens et al.
				5,989,210 A	11/1999 Morris et al.
				6,001,112 A	12/1999 Taylor
				6,019,728 A	2/2000 Iwata et al.
				6,022,336 A	2/2000 Zadno-Azizi et al.
				6,096,001 A	8/2000 Drasler et al.
				6,096,009 A	8/2000 Windheuser et al.
				6,126,635 A	10/2000 Simpson et al.
				6,129,697 A	10/2000 Drasler et al.
				6,129,698 A	10/2000 Beck
				6,146,396 A	11/2000 Kónya et al.
				6,159,230 A	12/2000 Samuels
				6,176,844 B1	1/2001 Lee
				6,179,851 B1	1/2001 Barbut et al.
				6,190,357 B1	2/2001 Ferrari et al.
				6,196,989 B1	3/2001 Padget et al.
				6,216,573 B1	4/2001 Moutafis et al.
				6,224,570 B1	5/2001 Le et al.
				6,241,703 B1	6/2001 Levin et al.
				6,258,061 B1	7/2001 Drasler et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,613,724 B2 12/2013 Lanier, Jr. et al.
 8,617,110 B2 12/2013 Moberg et al.
 8,617,127 B2 12/2013 Woolston et al.
 8,623,039 B2 1/2014 Seto et al.
 8,641,671 B2 2/2014 Michaud et al.
 8,647,294 B2 2/2014 Bonnette et al.
 8,652,086 B2 2/2014 Gerg et al.
 8,657,777 B2 2/2014 Kozak et al.
 8,657,785 B2 2/2014 Torrance et al.
 8,657,845 B2 2/2014 Lentz
 8,668,464 B2 3/2014 Kensy et al.
 8,668,665 B2 3/2014 Gerg et al.
 8,670,836 B2 3/2014 Aeschlimann et al.
 8,672,876 B2 3/2014 Jacobson et al.
 8,681,010 B2 3/2014 Moberg et al.
 8,721,674 B2 5/2014 Kusleika
 8,734,399 B2 5/2014 Nelson
 8,740,874 B2 6/2014 Ravenscroft
 8,758,325 B2 6/2014 Webster et al.
 8,771,305 B2 7/2014 Shriver
 8,783,151 B1 7/2014 Janardhan et al.
 8,803,030 B1 8/2014 Janardhan et al.
 8,808,270 B2 8/2014 Dann et al.
 8,814,847 B2 8/2014 Hoffman et al.
 8,814,892 B2 8/2014 Galdonik et al.
 8,851,866 B2 10/2014 Moutafis et al.
 8,852,219 B2 10/2014 Wulfman et al.
 8,926,525 B2 1/2015 Hulvershorn et al.
 RE45,760 E 10/2015 Root et al.
 RE45,776 E 10/2015 Root et al.
 9,433,427 B2* 9/2016 Look A61B 17/22
 9,913,936 B2* 3/2018 Look A61M 1/0088
 2001/0051811 A1 12/2001 Bonnette et al.
 2002/0068895 A1 6/2002 Beck
 2002/0133114 A1 9/2002 Itoh et al.
 2002/0138095 A1 9/2002 Mazzocchi et al.
 2002/0165575 A1 11/2002 Saleh
 2002/0173819 A1 11/2002 Leeftang et al.
 2002/0176788 A1 11/2002 Moutafis et al.
 2003/0032918 A1 2/2003 Quinn
 2003/0069549 A1 4/2003 MacMahon et al.
 2003/0088209 A1 5/2003 Chiu et al.
 2003/0144688 A1 7/2003 Brady et al.
 2003/0216760 A1 11/2003 Welch et al.
 2003/0220556 A1 11/2003 Porat et al.
 2003/0236533 A1 12/2003 Wilson et al.
 2004/0049225 A1 3/2004 Denison
 2004/0087988 A1 5/2004 Heitzmann et al.
 2004/0147871 A1 7/2004 Burnett
 2004/0158136 A1 8/2004 Gough et al.
 2004/0167463 A1 8/2004 Zawacki
 2004/0193046 A1 9/2004 Nash et al.
 2004/0199201 A1 10/2004 Kellet et al.
 2004/0243157 A1 12/2004 Connor et al.
 2005/0065426 A1 3/2005 Porat et al.
 2005/0102165 A1 5/2005 Oshita et al.
 2005/0159716 A1 7/2005 Kobayashi et al.
 2005/0196748 A1 9/2005 Ericson
 2005/0240146 A1 10/2005 Nash et al.
 2005/0263150 A1 12/2005 Moutafis et al.
 2006/0009785 A1 1/2006 Maitland et al.
 2006/0058836 A1 3/2006 Bose et al.
 2006/0063973 A1 3/2006 Makower et al.
 2006/0064123 A1 3/2006 Bonnette et al.
 2006/0142630 A1 6/2006 Meretei
 2007/0073233 A1 3/2007 Thor et al.
 2007/0073268 A1 3/2007 Goble et al.
 2007/0078438 A1 4/2007 Okada
 2007/0197956 A1 8/2007 Le et al.
 2007/0225739 A1 9/2007 Pintor et al.
 2008/0009784 A1 1/2008 Leedle et al.
 2008/0086110 A1 4/2008 Galdonik et al.
 2008/0097339 A1 4/2008 Ranched et al.
 2008/0097563 A1 4/2008 Petrie et al.
 2008/0195139 A1 8/2008 Donald et al.

2008/0249501 A1 10/2008 Yamasaki
 2008/0255596 A1 10/2008 Jenson et al.
 2008/0294181 A1 11/2008 Wensel et al.
 2008/0306465 A1 12/2008 Bailey et al.
 2008/0319376 A1 12/2008 Wilcox et al.
 2009/0054825 A1 2/2009 Melsheimer et al.
 2009/0105690 A1 4/2009 Schaeffer et al.
 2009/0157057 A1 6/2009 Ferren et al.
 2009/0292212 A1 11/2009 Ferren et al.
 2010/0010524 A1 1/2010 Barrington et al.
 2010/0030186 A1 2/2010 Stivland
 2010/0094201 A1 4/2010 Mallaby
 2010/0204672 A1 8/2010 Lockhart et al.
 2010/0217276 A1 8/2010 Garrison et al.
 2010/0274191 A1 10/2010 Ting
 2011/0091331 A1 4/2011 Moutafis et al.
 2011/0106019 A1 5/2011 Bagwell et al.
 2011/0160683 A1 6/2011 Pinotti Barbosa et al.
 2011/0263976 A1 10/2011 Hassan et al.
 2012/0059340 A1 3/2012 Larsson
 2012/0071907 A1 3/2012 Pintor et al.
 2012/0123509 A1 5/2012 Merrill et al.
 2012/0130415 A1 5/2012 Tal et al.
 2012/0165756 A1 6/2012 Root et al.
 2012/0259265 A1 10/2012 Salehi et al.
 2012/0289910 A1 11/2012 Shtul et al.
 2012/0291811 A1 11/2012 Dabney et al.
 2013/0069783 A1 3/2013 Caso et al.
 2013/0116701 A1 5/2013 Wang et al.
 2013/0190701 A1 7/2013 Kim
 2013/0267891 A1 10/2013 Malhi et al.
 2013/0310845 A1 11/2013 Thor et al.
 2014/0005699 A1 1/2014 Bonnette et al.
 2014/0012226 A1 1/2014 Hochman
 2014/0147246 A1 5/2014 Chappel et al.
 2014/0155931 A1 6/2014 Bose et al.
 2014/0276920 A1 9/2014 Hendrick et al.
 2014/0309589 A1 10/2014 Momose et al.
 2014/0323906 A1 10/2014 Peatfield et al.
 2015/0094748 A1 4/2015 Nash et al.
 2015/0283309 A1 10/2015 Look et al.
 2017/0136212 A1 5/2017 Garrison et al.
 2017/0281204 A1 10/2017 Garrison et al.

FOREIGN PATENT DOCUMENTS

EP 726466 B1 4/2002
 EP 1488748 A1 12/2004
 WO WO199005493 A1 5/1990
 WO WO1996001079 A1 1/1996
 WO WO1996035469 A1 11/1996
 WO WO9918850 A1 4/1999
 WO WO2001027916 A1 5/2001
 WO WO2004100772 A2 11/2004
 WO WO2007143633 A2 12/2007
 WO WO2008097993 A2 8/2008
 WO WO2015100178 A1 7/2015

OTHER PUBLICATIONS

Frölich, G., Meier, P., White, S., Yellon, D., Hausenloy, D., "Myocardial reperfusion injury: looking beyond primary PCI", European Heart Journal Jun. 2013, pp. 1714-1722, vol. 34, No. 23, Elsevier, Amsterdam, The Netherlands.
 Gousios, A., Shearn, M., "Effect of Intravenous Heparin on Human Blood Viscosity", Circulation, Dec. 1959, pp. 1063-1066, vol. 20, American Heart Association, Dallas, USA.
 "Infusion Liquid Flow Sensors—Safe, Precise and Reliable", Sensirion, downloaded from internet Apr. 3, 2015.
 "Makes even the most difficult intervention A Fast and Smooth Run." GuideLiner brochure. Vascular Solutions, Inc., downloaded from internet Apr. 9, 2015.
 Parikh, A., Ali, F., "Novel Use of GuideLiner Catheter to Perform Aspiration Thrombectomy in a Saphenous Vein Graft" Cath Lab Digest, Oct. 2013, downloaded from internet Oct. 22, 2014.
 Prasad, A., Stone, G., Holmes, D., Gersh, B., Peperfusion Injury, Microvascular Dysfunction, and Carioprotection: The "Dark Side"

(56)

References Cited

OTHER PUBLICATIONS

of Reperfusion, *Circulation*, Nov. 24, 2009, pp. 2105-2112, vol. 120, American Heart Association, Dallas, USA.

Rodriguez, R., Condé-Green, A., "Quantification of Negative Pressures Generated by Syringes of Different Calibers Used for Liposuction", *Plastic & Reconstructive Surgery*, Aug. 2012, pp. 383e-384e, vol. 130, No. 2, Lippicott Williams & Wilkins, Philadelphia, USA.

Stys, A., Stys, T., Rajpurohit, N., Khan, M. "A Novel Application of GuideLiner Catheter for Thrombectomy in Acute Myocardial Infarction: A Case Series", *Journal of Invasive cardiology*, Nov. 2013, pp. 620-624, vol. 25, No. 11, King of Prussia, USA.

PCT International Search Report and Written Opinion for PCT/US2015/024569, Applicant Incuvate, LLC, Forms PCT/ISA/220, 210, and 237 dated Jun. 29, 2015 (14 pages).

PCT International Search Report and Written Opinion for PCT/US2015/024773, Applicant Incuvate, LLC, Forms PCT/ISA/220, 210, and 237 dated Jul. 8, 2015 (10 pages).

Meritrans, Merit Medical Systems, Inc., 400545002/B ID 120606, Date unknown (2 pages).

Merit Mentor Simulator/Tester Instructions for Use, Merit Medical Systems, Inc. 460101002 ID 062696, Date Unknown (12 pages).

Extended European Search Report dated Oct. 11, 2017, in EP App. No. 15777313.6 filed Apr. 7, 2015 (12 pages).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

FIG. 4




FIG. 5

FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15



FIG. 16

FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26A

FIG. 26B




FIG. 27




FIG. 28







FIG. 29






FIG. 33




FIG. 34A




FIG. 34B




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44A




FIG. 44B




FIG. 44C




FIG. 45A




FIG. 45B




FIG. 45C




FIG. 45D




FIG. 46A




FIG. 46B




FIG. 46C




FIG. 46D




FIG. 47




FIG. 48




FIG. 49




FIG. 50A




FIG. 50B




FIG. 51A




FIG. 51B




FIG. 51C




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56A




FIG. 56B




FIG. 56C




FIG. 57




FIG. 58A




FIG. 58B




FIG. 59




FIG. 60

SYSTEMS AND METHODS FOR MANAGEMENT OF THROMBOSIS

This application is a continuation of U.S. patent application Ser. No. 15/209,989, filed on Jul. 14, 2016, which is a continuation of U.S. patent application Ser. No. 14/680,017, filed on Apr. 6, 2015, now U.S. Pat. No. 9,433,427, which claims the benefit of priority to U.S. Provisional Application No. 61/976,975, filed on Apr. 8, 2014, U.S. Provisional Application No. 62/069,817, filed on Oct. 28, 2014, and U.S. Provisional Application No. 62/090,822, filed on Dec. 11, 2014, all of which are incorporated herein by reference in their entireties for all purposes. Priority is claimed pursuant to 35 U.S.C. § 120 and 35 U.S.C. § 119.

FIELD OF THE INVENTION

The field of the invention generally relates to an aspiration system for removing, by aspiration, undesired matter such as a thrombus from a fluid carrying cavity, duct, or lumen of the body, such as a blood vessel.

BACKGROUND

Thrombosis is managed by pharmacologic means and by interventional means. These include thrombectomy, and combinations of thrombectomy with pharmacologic agents. Thrombectomy methods include breaking up and in many cases removing thrombus from a patient having thrombosis. Thrombectomy may be mechanical or non-mechanical, and may use catheter-based cutting or macerating elements, saline jets or aspiration of the thrombus.

A treatment method for removing undesired matter such as thrombus from a blood vessel of a patient involves use of an aspiration catheter having elongate shaft formed with an aspiration lumen extending therein. An aspiration catheter may also include a guidewire lumen for placement of a guidewire, which is used to guide the aspiration catheter to a target site in the body. By applying a vacuum (i.e. negative pressure) to a proximal end of the aspiration lumen, for example, with a syringe having a hub that is connected to the proximal end of the aspiration catheter, the matter can be aspirated into an aspiration port at the distal end of the aspiration catheter, into the aspiration lumen, and thus be removed from the patient.

SUMMARY OF THE INVENTION

In one embodiment, an aspiration system includes an elongate tubular member for insertion into the vasculature of a patient, the elongate tubular member having a proximal end, a distal end, a lumen extending from the proximal end to the distal end, and an inner surface defined by the lumen; an aspiration catheter having a proximal end and a distal end and configured to be inserted through the lumen of the elongate tubular member, the aspiration catheter including a tubular aspiration member having a proximal end, a distal end, and a lumen, and configured to at least partially extend out of the lumen of the elongate tubular member at the distal end of the elongate tubular member and into the vasculature of the patient; an elongate support member coupled to the tubular aspiration member and extending between the proximal end of the aspiration catheter and the proximal end of the tubular aspiration member; and an annular seal comprising at least one annular sealing member coupled to the tubular aspiration member; a vacuum source configured for coupling to the proximal end of the elongate tubular mem-

ber; and wherein the at least one annular sealing member is configured to create a seal against the inner surface of the elongate tubular member, substantially preventing liquid having a viscosity of about 0.0025 Pascal-seconds from passing through an annular space between the elongate tubular member and the tubular aspiration member in a distal to proximal direction and into the lumen of the elongate tubular member proximal to the at least one annular sealing member when a vacuum sufficient to cause aspiration of the liquid through the lumen of the tubular aspiration member and the lumen of the elongate tubular member from the distal end of the tubular aspiration member to the proximal end of the elongate tubular member is actively applied to the lumen of the elongate tubular member at the proximal end of the elongate tubular member.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevation view of an aspiration system according to an embodiment of the present invention.

FIG. 2 is a cross-sectional view taken along line 2-2 of FIG. 1.

FIG. 3 is a sectional view of a standard aspiration system during aspiration.

FIG. 4 is a sectional view of the embodiment of FIGS. 1 and 2 during aspiration.

FIG. 5 is a sectional view of a standard aspiration system during aspiration, with a guidewire in place through the lumens.

FIG. 6 is a sectional view of the embodiment of FIGS. 1 and 2 during aspiration, with a guidewire in place through the lumens.

FIG. 7 is a view of the lumen cross-section in a standard aspiration catheter or in the distal tube of the embodiment of FIGS. 1 and 2.

FIG. 8 is a view of the lumen cross section in a portion of a guiding catheter of the embodiment of FIGS. 1 and 2.

FIG. 9 is a view of the lumen cross-section in a standard aspiration catheter or in the distal tube of the embodiment of FIGS. 1 and 2, with a guidewire in place through the lumen.

FIG. 10 is a view of the lumen cross section in a portion of a guiding catheter of the embodiment of FIGS. 1 and 2, with a guidewire in place through the lumen.

FIG. 11 is a view of an aspiration system according to an embodiment of the present invention during aspiration.

FIG. 12 is a perspective view of a distal section of an aspiration (thrombectomy) catheter according to an embodiment of the present invention.

FIG. 13 is a sectional view of an aspiration system according to an embodiment of the present invention prior to aspiration.

FIG. 14 is a sectional view of an aspiration system according to an embodiment of the present invention during aspiration.

FIG. 15 is a sectional view of an aspiration system according to an embodiment of the present invention.

FIG. 16 is a sectional view of an aspiration system according to an embodiment of the present invention.

FIG. 17 is a sectional view of an aspiration system according to an embodiment of the present invention.

FIG. 18 is a partially sectional view of an aspiration system according to an embodiment of the present invention.

FIG. 19 is a partially sectional view of aspiration system according to an embodiment of the present invention.

FIG. 20 is a sectional view of an aspiration system according to an embodiment of the present invention.

3

FIG. 21 is a sectional view of an aspiration system according to an embodiment of the present invention.

FIG. 22 is a partially sectional view of an aspiration system according to an embodiment of the present invention.

FIG. 23 is a partially sectional view of an aspiration system according to an embodiment of the present invention.

FIG. 24 is a partially sectional view of an aspiration system according to an embodiment of the present invention.

FIG. 25 is a perspective view of an aspiration system according to an embodiment of the present invention in use within a blood vessel.

FIG. 26A is a perspective view of an embodiment of a catheter joint.

FIG. 26B is a perspective view of a component of the catheter joint of FIG. 26A.

FIG. 27 is a perspective view of an aspiration catheter assembled with a dipping process according to an embodiment of the present invention.

FIG. 28 is a perspective view of a distal section of an aspiration (thrombectomy) catheter according to an embodiment of the present invention.

FIG. 29 is a sectional view of an embodiment of a saline injection aspiration (thrombectomy) catheter according to an embodiment of the present invention, with a guidewire in place through the lumens.

FIG. 30 is a plan view of a distal end of an alternative embodiment of the saline injection aspiration (thrombectomy) catheter of FIG. 29.

FIG. 31 is a sectional view of the saline injection aspiration (thrombectomy) catheter of FIG. 30, taken along the line 31-31.

FIG. 32 is a detail view of the saline injection aspiration (thrombectomy) catheter of FIG. 31 within circle 32.

FIG. 33 is a perspective view of a distal section of a saline aspiration (thrombectomy) catheter according to an embodiment of the present invention.

FIG. 34A is a cross-section of the saline injection aspiration (thrombectomy) catheter of FIG. 33, taken along the line 34A-34A.

FIG. 34B is a cross-section of the saline injection aspiration (thrombectomy) catheter of FIG. 33, taken along the line 34B-34B.

FIG. 35 is a perspective view of a proximal section of a saline aspiration (thrombectomy) catheter according to an embodiment of the present invention.

FIG. 36 is a perspective view of a distal section of a saline aspiration (thrombectomy) catheter according to an embodiment of the present invention.

FIG. 37 is a perspective view of a slotted mandrel according to an embodiment of the present invention.

FIG. 38 is a cross-sectional view of the slotted mandrel of FIG. 37 as used in a dipping process according to an embodiment of the present invention.

FIG. 39 is a top view of a marker band during an assembly process according to an embodiment of the present invention.

FIG. 40 is a perspective view of a marker band during an assembly process according to an embodiment of the present invention.

FIG. 41 is an end view of a marker band during an assembly process according to an embodiment of the present invention.

4

FIG. 42 is an end view of a marker band during an assembly process using the slotted mandrel of FIG. 37 according to an embodiment of the present invention.

FIG. 43 is a plan view of a system for aspiration according to an embodiment.

FIG. 44A is a detailed view of an aspiration monitoring system according to a first embodiment.

FIG. 44B is a view of an aspiration monitoring system according to a second embodiment.

FIG. 44C is a view of an aspiration monitoring system according to a third embodiment.

FIG. 45A is a sectional view of an aspiration catheter in a blood vessel prior to contact with a thrombus.

FIG. 45B is a sectional view of an aspiration catheter in a blood vessel upon contact with a thrombus.

FIG. 45C is a sectional view of an aspiration catheter during a loss of vacuum.

FIG. 45D is a sectional view of thrombi being aspirated through an aspiration catheter.

FIG. 46A is a graphic representation of pressure vs. time for the condition of FIG. 45A.

FIG. 46B is a graphic representation of pressure vs. time for the condition of FIG. 45B.

FIG. 46C is a graphic representation of pressure vs. time for the condition of FIG. 45C.

FIG. 46D is a graphic representation of pressure vs. time for the condition of FIG. 45D.

FIG. 47 is a diagrammatic view of a system for aspirating thrombus according to an embodiment of the present invention.

FIG. 48 is a diagrammatic view showing more detail of the proximal portion of the system for aspirating thrombus of FIG. 47.

FIG. 49 is a diagrammatic view of the distal end portion of the system for aspirating thrombus of FIG. 47.

FIG. 50A is a perspective view of an aspiration system according to an embodiment of the present invention in a first configuration.

FIG. 50B is a perspective view of the aspiration system of FIG. 50A in a second configuration.

FIGS. 51A-51C are perspective views of an aspiration catheter according to an embodiment of the present invention in three different configurations.

FIG. 52 is a perspective view of an aspiration catheter according to an embodiment of the present invention.

FIG. 53 is a perspective view of a thrombectomy catheter according to an embodiment of the present invention.

FIG. 54 is a perspective view of an aspiration catheter according to an embodiment of the present invention.

FIG. 55 is a perspective view of an aspiration system according to an embodiment of the present invention.

FIGS. 56A-56C are perspective views of an aspiration system according to an embodiment of the present invention in multiple configurations.

FIG. 57 is a perspective view of an aspiration system according to an embodiment of the present invention.

FIGS. 58A-58B are perspective views of an aspiration system according to an embodiment of the present invention.

FIG. 59 is a perspective view of a component of an aspiration catheter according to an embodiment of the present invention.

FIG. 60 is a perspective detail view of a portion of an aspiration catheter according to an embodiment of the present invention.

DETAILED DESCRIPTION

Referring first to FIGS. 1 and 2, the distal portion of an aspiration or thrombectomy system 100 is shown within a

blood vessel **102** of a patient with thrombosis, including at least one thrombus **104**. The blood vessel **102** may comprise a vein or an artery. For example, the blood vessel **102** may comprise one or more veins of the legs, including, but not limited to the femoral or iliac veins, or one or more veins of the upper extremities, including, but not limited to the subclavian, internal jugular or axillary veins. The blood vessel **102** may also comprise the inferior vena cava or superior vena cava. The blood vessel **102** may comprise an artery including, but not limited to a pulmonary artery, a coronary artery, a cerebral artery, an internal carotid artery, a femoral artery, an iliac artery, or a renal artery. The thrombectomy system **100** comprises a thrombectomy catheter **106** and a guiding catheter **108**. The guiding catheter **108** may, for example, have an outer diameter of 6 French, an inner lumen diameter of approximately 0.183 cm (0.072 inches), and have a total length of approximately 100 cm. The thrombectomy catheter **106** is configured to be placed through the inner lumen **110** of the guiding catheter **108**. The guiding catheter **108** may comprise a composite extruded and braided tubular structure, which has sufficient flexibility and pushability to reach a target area **112**. The guiding catheter **108** may also have a pre-shaped tip. For example the tip shape may aid in cannulating coronary arteries. The thrombectomy catheter **106** comprises a distal tube **114** which is configured to be extendable out of the inner lumen **110** of the guiding catheter **108**, such that a distal end **116** of the distal tube **114** can be advanced a desired length into the blood vessel **102** so that it can be placed adjacent the target area **112**. The proximal end **118** of the distal tube **114** is configured to remain within the inner lumen **110** of the guiding catheter **108**, for example, at a region near the distal end **120** of the guiding catheter **108**. In some embodiments, the thrombectomy catheter **106** includes a radiopaque marker **101**, which may comprise a band secured to the thrombectomy catheter, and made from radiodense material, such as platinum, gold, or other similar materials. In some embodiments, the distal tube **114** may be formed of polymeric materials containing radiopaque material, such as titanium dioxide (TiO₂).

A sealing member **124** is carried by the proximal end **118** of the distal tube **114**, and may comprise, for example, an annular seal attached to an outer cylindrical surface **122** of the distal tube **114**. The thrombectomy catheter **106** also comprises a support member **126**, for example a wire, a hypo tube, or a composite shaft, which is secured to the distal tube **114** by adhesive, mechanical attachment or other manners described herein. The support member **126** may be relatively stiff and may have a relatively small outer diameter so that it does not block the lumen **130** of the distal tube **114**. The sealing member **124** is configured to seal off an annulus **142** between the distal tube **114** and an inner surface **123** defined by the inner lumen **110** of the guiding catheter **108** so that an extended lumen **128** is created, at least when a negative pressure gradient is placed between the proximal end **144** (FIGS. 4 and 6) of the guiding catheter **108** and the distal end **116** of the distal tube **114**. The negative pressure gradient may result by coupling a vacuum source **146** to the proximal end of the guiding catheter **108**. For example, a y-connector **148** may be sealingly coupled to the proximal end **144** of the guiding catheter **108**, and the support member **126** may extend through the y-connector **148** and be sealed by the proximal seal **150** (e.g. hemostatic valve) of the y-connector **148**. The vacuum source **146** may be coupled to the side port **152** (e.g. luer) of the y-connector **148**. In some embodiments, the vacuum source **146** may comprise a 20 ml syringe, 30 ml syringe, or a larger syringe, that is lockable

in its evacuated condition. An example is the VacLok® syringe sold by Merit Medical Systems, Inc. of South Jordan, Utah. In some embodiments, the syringe may be attached to the side port **152** of the y-connector **148** via extension tubing known in the art. In use, when the distal end **116** of the distal tube **114** is extended out of the distal end **120** of the guiding catheter **108** into the vasculature and adjacent a thrombus **104**, and the sealing member **124** is sealingly located within the inner lumen **110** of the guiding catheter **108**, the negative pressure gradient caused by the application of the vacuum source **146** causes the thrombus **104**, or at least a portion thereof, to be aspirated through the extended lumen **128**. While being aspirated, the thrombus **104**, or a portion thereof, first enters the lumen **130** of the distal tube **114** and then enters the lumen cross-section **154a**, **154b** of the inner lumen **110** of the guiding catheter **108**, not already taken up by the support member **126** (FIG. 8), or by the support member **126** and a guidewire **134** (FIG. 10), if a guidewire is left in place within the lumens **110**, **130**. The seal created by the sealing member **124** assures that blood **132** (FIGS. 1 and 2) will not enter into the extended lumen **128** (the combination of lumen **130** and the lumen cross-section **154** of the inner lumen **110**) through location A.

Blood has a non-Newtonian viscosity, which is known to vary depending on the shear rate the blood experiences. The mean viscosity of blood can also be varied by factors including the amount of heparinization, or anti-coagulation, employed during an interventional procedure, which may include a thrombectomy procedure. Viscosities of around 0.0025 pascal-seconds (2.5 centipoise) have been measured in heparinized blood, and as heparinization may lower normal blood viscosity, embodiments of a sealing member **124** presented herein substantially prevent a liquid having a viscosity as low as 0.0025 pascal-seconds from passing through the annular space between the guiding catheter **108** and the distal tube **114** in a distal to proximal direction and into the inner lumen **110** of the guiding catheter **108** proximal to the sealing member **124** when a sufficient vacuum pressure is applied to the inner lumen **110** of the guiding catheter **108** to cause at least some aspiration. In some embodiments, the sufficient vacuum pressure may be about -34,474 pascal (-5 pounds per square inch) or lower. In some embodiments, the sufficient vacuum pressure may be about -46,662 pascal (-6.8 pounds per square inch) or lower. In some embodiments, the sufficient vacuum pressure may range between about -82,737 pascal (-12 pounds per square inch) and about -95,526 pascal (-14 pounds per square inch). In some embodiments, the sufficient vacuum pressure may be about -89,631 pascal (-13 pounds per square inch).

FIG. 11 illustrates the fluid flow **156** (e.g. blood, thrombus, macerated thrombus) out of the proximal end **118** of the distal tube **114** (lumen **130**) and through the inner lumen **110** of the guiding catheter **108**. In the embodiment of the thrombectomy system **100** illustrated in FIGS. 1 and 2, the distal tube **114** has a lumen **130** configured for tracking over the guidewire **134**. The guidewire **134** (e.g. 0.014" coronary guidewire) may be used to guide the thrombectomy catheter **106** through the blood vessel **102**, with the lumen **130** of the distal tube **114** acting as a single-operator exchange lumen. In some embodiments, the length of this lumen **130** may be between 5 cm and 35 cm. In some embodiments, it may be between 10 cm and 30 cm. In some embodiments, it may be between 15 cm and 25 cm. In some embodiments, it may be about 25 cm. As illustrated in FIG. 12, the distal tube **114** may have a skive **158** at its distal end **116** and/or a skive **160** at its proximal end **118**. The skives **158**, **160** may serve at

least two purposes. First they aid in the tracking of the distal tube **114** and thus the thrombectomy catheter **106** through the blood vessel **102**, including any thrombus **104** or atherosclerotic plaque (not shown), past the distal end **120** of the guiding catheter **108**, and in and out of the y-connector **148**, including the proximal seal **150**. Second, the skives **158**, **160** increase the cross-section area at the entry (or exit) points of the lumen **130** of the distal tube **114**, thus lowering resistance to flow, and allowing, for example, relatively larger pieces or portions of thrombus to enter the lumen **130**. The distal tube **114** in FIG. **12** is depicted in a slightly curved state so that the openings **162**, **164** at either end of the lumen **130** face the viewer, so that the skives **158**, **160** may be better appreciated.

Returning to FIG. **11**, the sealing member **124** is shown as an annular seal with a distally facing lip **166**. An annular concavity **167** extends circumferentially around the distal tube **114** between the distally facing lip **166** and the outer cylindrical surface **122** of the distal tube **114**. In some embodiments, the sealing member **124** may be made from a number of elastomeric materials including silicone, EPDM, polyurethane, or thermoplastic elastomers, such as PEBAX or Santoprene®. The thin-walled construction of the distal tube **114** allows a finite gap **G** between the distal tube **114** and the inner lumen **110** of the guiding catheter **108**, while still maintaining a relatively large lumen **130** in the distal tube **114**, in some embodiments as large as about 0.152 cm (0.060 inches) or larger (for a 6F guiding catheter compatible thrombectomy catheter **106**). In some embodiments, the gap **G** is 0.003" or more on each side, and the thin lip **166** may have a thickness **T** of about 0.000635 cm (0.00025 inches) to about 0.00508 cm (0.0020 inches). In other embodiments, the thickness **T** may be between about 0.0019 cm (0.00075 inches) and about 0.0038 cm (0.0015 inches). On other embodiments, the thickness **T** may be between about 0.00254 cm (0.001 inches) and about 0.00317 cm (0.00125 inches). With a gap **G** on the order of 0.0076 cm (0.003 inches) or more per side, there would be a risk of some movement of thrombus or macerated thrombus through the annulus **142** in direction **d**, due to agitation, and perhaps into the blood vessel **102**, creating a risk of embolization of a loose thrombus. However, the addition of the distally facing lip **166** allows the annulus **142** to be completely sealed whenever the vacuum source **146** (FIGS. **4** and **6**) is applied, causing suction within the inner lumen **110** of the guiding catheter, and thus a pressure **P₂** proximal to the distally facing lip **166** that is less than the pressure **P₁** distal to the distally facing lip **166**. Because the distally facing lip **166** is made from a flexible material, and/or has a relatively small thickness **T**, the positive pressure gradient from the **P₁** (distal) side to the **P₂** (proximal side) ($P_1 - P_2 > 0$) will cause the distally facing lip **166** to be forced against the inner wall **168** of the guiding catheter **108**, thus sealing it. The maximum outer diameter of the distally facing lip **166** may actually be smaller than the inner diameter of the inner lumen **110** of the guiding catheter **108**, because it will flex (e.g., by moment **M**) from a first configuration (FIG. **13**) to a second configuration (FIG. **14**) when activated by the positive pressure gradient ($\Delta P = P_1 - P_2$), in order to seal off the annulus **142**. The benefit of having a distally facing lip **166** whose maximum outer diameter is smaller than the inner diameter of the inner lumen **110** of the guiding catheter **108** (when not activated by pressure), is that during tracking of the thrombectomy catheter **106**, when the vacuum source **146** is not being applied, there is no seal between the distally facing lip **166** and the inner wall **168** of the guiding catheter **108**, and thus there is less axial friction, thus making it easier

to track and slide the thrombectomy catheter freely (longitudinal translation), providing both low axial resistance to motion (less drag), and high precision of motion (better "feel"). Thus, the distally facing lip **166** only expands when it is needed (i.e. during aspiration). In some embodiments, the distally facing lip **166** may be made using a dipping process. In some embodiments, the dipping process may be a polyurethane dipping process. In some embodiments the distally facing lip **166** may be made from non-elastomeric materials, such as polyolefins, nylon, as the pressure-activated sealing does not require elastomeric compression. In some embodiments, the distally facing lip **166** may be bonded to the distal tube **114** with adhesive, epoxy, or by thermal bonding methods. In some embodiments, the seal should be liquid tight, or water tight (saline tight), and in some embodiments need not be air tight (gas tight). In some cases liquid tight may be defined as not allowing any substantial amount of blood to pass through the annulus **142**. The sealing may be aided by blood viscosity, the length of the annulus **142** (distal to the sealing member **124**), and the dimension of the gap **G** (FIG. **11**). For example, a higher blood viscosity, longer annulus **142** length, and a smaller gap **G** dimension each serve alone or in combination to increase the sealing capacity (decrease the possibility of fluid passage through the annulus **142**).

In some embodiments, the distally facing lip **166** is configured to maintain a seal when a positive pressure gradient ($\Delta P = P_1 - P_2$) of about 46,662 pascal (350 mm Hg) or higher is maintained. In some embodiments, the aspiration pressure may be maintained using a vacuum pump as the vacuum source **146**. In some embodiments, the vacuum pump provides a relatively constant pressure gradient of about 46,662 pascal (350 mm Hg) to about 53,328 pascal (400 mm Hg). In some embodiments, a 20 ml to 60 ml syringe is evacuated in order to serve as the vacuum source **146**. In some embodiments, a 30 ml syringe is evacuated in order to serve as the vacuum source **146**. In some embodiments, the evacuated 30 ml syringe provides a plateau pressure gradient of about 75,993 pascal (570 mm Hg) to about 89,626 pascal (670 mm Hg). As described, heparinized blood tends to have a viscosity of about 0.0025 pascal-seconds (2.5 cP) or higher. In some embodiments, the distally facing lip **166** is configured to seal against the inner wall **168** of the guiding catheter **108** so that a 0.0025 pascal-seconds liquid will not significantly pass distal to proximal when a distal to proximal positive pressure gradient ($\Delta P = P_1 - P_2$) of 46,662 pascal (350 mm Hg) is applied. In some embodiments, the distally facing lip **166** is configured to not seal against the inner wall **168** of the guiding catheter and thus not stop the passage of a liquid from proximal to distal (i.e. through the annulus **142**) when a proximal to distal positive pressure gradient ($\Delta P = P_2 - P_1$) of 46,662 pascal (350 mm Hg) is applied.

FIG. **6** illustrates the aspiration flow path and FIGS. **9** and **10** illustrate the lumen cross-sections **136b**, **154b** if the guidewire **134** is left in place during aspiration. FIG. **4** illustrates the aspiration flow path and FIGS. **7** and **8** illustrate the lumen cross-sections **136a**, **154a** if the guidewire **134** is not left in place during aspiration, for example, if it is removed. Starting with this latter "no guidewire" condition, FIG. **7** illustrates a lumen cross-section **136a**, which may be represented by a lumen **138** of a standard thrombectomy catheter **140** in FIG. **3**, or by the lumen **130** of the thrombectomy catheter **106** of an embodiment of the present invention in FIG. **4**. A comparison between the flow characteristics of the standard thrombectomy catheter **140** and the embodiment of the thrombectomy system **100** of FIGS. **1** and **2** is presented below.

The standard Hagen-Poiseuille Law flow equation used to calculate the flow of fluids (e.g. blood and/or macerated thrombus) is:

$$Q = \frac{\Delta P \pi D^4}{128 \mu L}$$

where L is the length of a particular flow path,
 ΔP is the pressure gradient between one end of the flow path and the other end of the flow path,
 D is the diameter of the flow path, and
 μ is the viscosity of the fluid.

Because luminal cross-sectional areas are often non-circular, the term Hydraulic Diameter (D_H) is often substituted for diameter D. Hydraulic Diameter (D_H) represents the effective diameter of a circular cross-section that behaves the same as a non-circular cross-section. The Hydraulic Diameter (D_H) equation is:

$$H_D = \frac{4A}{p}$$

where A is the cross-sectional area of the lumen, and
 p is the summation of the perimeter of all of the luminal walls on cross-section.

Combining these two equations, the standard Hagen-Poiseuille Law flow equation for a particular Hydraulic Diameter (D_H) is:

$$Q = \frac{\Delta P \pi D_H^4}{128 \mu L}$$

Using the Ohm's Law analogy for fluid flow, produces the equation:

$$Q = \frac{\Delta P}{R}$$

where R is the Resistance (to fluid flow), given thus by the equation:

$$R = \frac{128 \mu L}{\pi D_H^4}$$

As differing lumen cross-sections **136**, **154** are arrayed serially in the systems being discussed, the serial resistance equation will be used, the equation being:

$$R_T = R_1 + R_2 + R_3 + \dots$$

where R_T is the total resistance, and
 R_1 , R_2 , R_3 , etc. are individual serial resistances.

The intention is to compare the total (flow) resistance of a first thrombectomy system (R_{T1}) with the total resistance of a second thrombectomy system (R_{T2}). Thus, the constant $128/\pi$ can be removed from the comparative term, leaving $\mu L/D_H^4$. Additionally, though blood is non-Newtonian, and thus may exhibit variance in viscosity at different shear rates, the variation of the effective viscosity of a thrombus/macerated thrombus/blood slurry is not expected to be

significant among the different lumen conditions described. Therefore, the viscosity (μ) term may also be removed from the comparative term. This leaves a comparative term of:

$$\text{Comparative Flow Resistance}(R_C) = L/D_H^4$$

Comparative Flow Resistance (R_C) can be calculated using the units ($1/\text{cm}^3$).

Returning to the standard thrombectomy catheter **140** of FIG. **3**, the entire length L_1 of the catheter in some models is about 140 cm and has a circular cross-sectional diameter D_1 of its lumen **138** of about 0.11 cm (0.042 inches). Because the lumen **138** is circular, 0.11 cm (0.042 inches) is also the Hydraulic Diameter (D_H). In comparison, the embodiment of the thrombectomy system **100** of FIG. **4**, includes a first length L_2 representing the length of the distal tube **114** of the thrombectomy catheter **106**, and in one embodiment L_2 is about 25 cm. In this particular embodiment, the lumen **130** of the distal tube **114** may have a circular cross-sectional diameter D_2 of its lumen **130** of about 0.15 cm (0.060 inches) The thrombectomy system **100** is inserted through a guiding catheter **108** having a lumen inner diameter of about 0.183 cm (0.072 inches) and a length of about 100 cm, thus having a flow length L_3 of about 100 cm. Assuming a support member **126** embodiment comprising a substantially rectangular cross-section stainless steel wire having a minor dimension of about 0.0305 cm (0.012 inches) and a major dimension of about 0.0508 cm (0.020 inches), the Comparative Flow Resistance (R_C) may be calculated for the standard thrombectomy catheter **140** and the thrombectomy system **100** in their "no guidewire" configurations of FIGS. **3** and **4**, respectively. Table 1 demonstrates that the Comparative Flow Resistance (R_{C1}) of the thrombectomy system **100** is only about 15% the Comparative Flow Resistance (R_{C2}) of the standard thrombectomy catheter **140**.

TABLE 1

Condition	R_{C1} ($1/\text{cm}^3$)	R_{C2} ($1/\text{cm}^3$)	R_{C1}/R_{C2}
No Guidewire (FIGS. 3 and 4)	160,822	1,080,926	0.15
Guidewire (FIGS. 5 and 6)	320,704	1,080,926	0.30

The standard thrombectomy catheter **140** in FIG. **5** has a guidewire **134** within the length of its lumen **138**. The thrombectomy system **100** of FIG. **6** has a 0.014" diameter guidewire **134** (0.036 cm) within the length of the lumen **130** of the distal tube **114** and the inner lumen **110** of the guiding catheter **108**. The thrombectomy system **100** of FIG. **6** also has a support member **126** having cross-sectional dimensions of 0.0305 cm x 0.0508 cm (0.012 inches x 0.020 inches) within the length of the inner lumen **110** of the guiding catheter **108**. Table 1 demonstrates that the Comparative Flow Resistance (R_{C1}) of the thrombectomy system **100** is only about 30% the Comparative Flow Resistance (R_{C2}) of the standard thrombectomy catheter **140**. This means that at a particular negative pressure gradient, the aspiration flow rate through the thrombectomy system **100** can be as much as 3.33 times more than the aspiration flow rate through the standard thrombectomy catheter **140**.

A test was performed wherein a 30 ml vacuum was locked onto an extraction syringe, and sealed with a closed stopcock. The extraction syringe and stopcock were then attached to a catheter/catheter system and the tip of the catheter placed in a beaker of water. The stopcock was then opened and the time was measured for the 30 ml syringe to fill with water. The data is listed in Table 2.

TABLE 2

System	Time to fill 30 ml syringe (seconds)
Medtronic Export AP	25
Prototype with 25 cm long, 0.147 cm (.058 inches) ID distal tube, and 0.0305 cm × 0.0508 cm (0.012 inches × 0.020 inches) support member in 0.183 cm (.072 inches) ID × 100 cm long guiding catheter - distal tube extending 25 cm from guiding catheter	7.2
Prototype with 25 cm long, 0.147 cm (.058 inches) ID distal tube, and 0.0305 cm × 0.0508 cm (0.012 inches × 0.020 inches) support member in 0.183 cm (.072 inches) ID × 100 cm long guiding catheter - distal tube extending 5 cm from guiding catheter	6.7

Published data using a similar 30 ml syringe water vacuum test shows Peak Extraction Rate (ml/sec) for several thrombus aspiration catheters. The peak extraction rate ranged from 0.94 ml/second to 1.71 ml/second (Table 3). Published in “Comparison of Dimensions and Aspiration Rate of the Pronto® V3, Pronto® LP, Export® XT, Export® AP, Fetch®, Xtract™, Diver C.E.™ and QuickCat™ Catheters” (ML1623 Rev. F December 2009 c2009 Vascular Solutions, Inc.) In comparison, the prototype thrombectomy system **100** tested in the two conditions of Table 1, demonstrated an average extraction rate of 3.6 ml/second to 4.0 ml/second, 2.1 to 2.3 times the peak extraction rate of the highest performing catheter (Pronto V3) in the published data set. And it should be mentioned that the designs of the thrombus aspiration catheters of the Table 3 test data are such that there is no guidewire within their lumen (as in FIG. 3) during aspiration, and the prototype thrombectomy system **100** tested also did not have a guidewire within its lumens during testing (as in FIG. 4). In use, for aspirating body fluids and materials such as blood and thrombus, embodiments of the thrombectomy system **100** of the present invention have significantly higher potential to remove thrombus more quickly and more completely than a standard thrombectomy catheter **140**, such as those represented in the published data. The amount of vacuum present at the lumen **130** at the distal end **116** of the distal tube **114** may be up to twice that (or more) of the amount of vacuum present at the distal tip of the lumen **138** of a standard thrombectomy catheter **140**, which attests to larger forces pulling the thrombus **104** into the lumen **130**.

TABLE 3

System	Peak Extraction Rate (ml/sec) of water evacuated by 30 ml syringe
Pronto ® V3 (Vascular Solutions, Inc.)	1.71
Pronto ® LP (Vascular Solutions, Inc.)	0.94
Export ® XT (Medtronic, Inc.)	1.27
Export ® AP (Medtronic, Inc.)	1.44
Fetch ® (Medrad/Possis)	1.55
Xtract™ (Volcano/Lumen Biomedical)	1.24
Diver C.E.™ (Invatec)	1.04
QuickCat™ (Spectranetics)	1.11

FIG. 15 illustrates an embodiment of the thrombectomy system **100**, wherein the thrombectomy catheter **106** includes a sealing member **124** that is an o-ring **174** having a custom cross-section having a wider base portion **170** having a width W and a wiper blade portion **172** having a width w , that is smaller than width W . Though the maximum outer diameter of the o-ring **174** of this embodiment should

be larger than the inner diameter of the inner lumen **110** of the guiding catheters **108** with which it is compatible (for sealable coupling), the thinner the width w of the wiper blade portion, the less drag and the greater feel is achieved. The distal tube **114** includes an annular groove **180**, having a width large enough to seat the base portion **170** of the o-ring **174**. In FIG. 15, the distal tube **114** of the thrombectomy catheter **106** is shown with a distal skive **158**, but without a proximal skive (**160** in FIG. 12). As mentioned, numerous combinations of the skives **158**, **160** are contemplated and are not limiting. FIG. 16 illustrates a closeup of an embodiment of the thrombectomy system **100**, wherein the thrombectomy catheter **106** includes a sealing member **124** that is an o-ring **174** having an x-shaped cross-section **178**. FIG. 17 illustrates a closeup of an embodiment of the thrombectomy system **100**, wherein the thrombectomy catheter **106** includes a sealing member **124** that is an o-ring **174** having a circular cross-section **176**. Numerous other o-ring cross-sections are contemplated. The annular groove **180** has enough width to seat the corresponding o-ring cross-sections **176**, **178** of the embodiments of FIGS. 16 and 17. A lip, such as the distally facing lip **166** of the embodiment of the thrombectomy system **100** of FIG. 11, or a seal, such as the o-ring **174** having a wiper blade portion **172** of FIG. 15, may have several optional embodiments in which their maximum outer diameter is constructed to different diameters in relation to the inner diameter of the guiding catheter **108**. For example, in some embodiments, the outer diameter may be in rubbing relation to the inner diameter of the guiding catheter **108**. In some embodiments, the outer diameter may be in touching relation to the inner diameter of the guiding catheter **108**. In some embodiments, the outer diameter may be in close clearance relation to the inner diameter of the guiding catheter **108**. In some embodiments, the outer diameter may be in a non-touching relation to the inner diameter of the guiding catheter **108**. In some embodiments, there may be multiple features, having a combination of these relationships (rubbing, touching, etc.). In some embodiments, the sealing member **124** may be an inflatable balloon, whose diameter and/or inflation pressure may be controlled.

FIG. 18 illustrates an embodiment of a thrombectomy system **100** having multiple sealing members **124**, denoted by **124a**, **124b**, **124c**, **124d**, **124e**, and **124f**. In some embodiments, the sealing members **124a-f** may be annular seals, such as any of the embodiments described herein. In some embodiments, the guiding catheter **108** may be from a different or unknown supplier and it may be difficult to know the true inner diameter of the inner lumen **110** along a significant length of the distal portion of the guiding catheter **108**. However, it may be possible for the user to measure the inner diameter at a distal portion **182** of the guiding catheter **108** (for example, using sterile pin or plug gauges). The multiple sealing members **124a-f** make it possible to adjust the distance DE that the inner tube **114** extends from the guiding catheter **108**, while assuring a sealing relationship between the particular sealing member **124a-f** and the inner diameter of the guiding catheter **108** at the distal portion **182**. For example, when sealing member **124a** is sealingly engaged with the inner diameter of the guiding catheter **108** at the distal portion **182**, DE is much shorter than when sealing member **124f** is sealingly engaged with the inner diameter of the guiding catheter **108** at the distal portion **182**. Thus, in use by the physician, the distal end **116** of the distal tube **114** can be brought into ideal position in relation to the thrombus **104** (FIGS. 1 and 2), for example, just proximal to the thrombus **104**. Additionally, the short axial

length of contact of each of the sealing members **124a-f** with the inner wall **168** of the guiding catheter **108** summed together is much less than if the entire outer cylindrical surface **122** of the distal tube **114** were a cylindrical seal, and this lowers the drag and increases the feel. Multiple axial spaces **184a-e**, located between the sealing members **124a-f**, represent the majority of the length of the distal tube **114**, and thus gap G can be large enough (e.g. 0.0076 cm (0.003 inches) or greater per side) so that even in tortuosities of the blood vessel **102**, where the catheters may be curved or angled, the drag is not unacceptably increased and the feel is not unacceptably decreased.

FIG. **19** illustrates an embodiment of a thrombectomy system **100** having one or more sealing members **124** comprising a hydrogel **186** annularly attached around the outer cylindrical surface **122** of the distal tube **114** of the thrombectomy catheter **106**. In some embodiments, the maximum outer diameter of the sealing member **124** comprising a hydrogel **186** may be less than the inner diameter of the inner lumen **110** of the guiding catheter when the hydrogel is in a non-hydrated or substantially non-hydrated state. The maximum outer diameter of the sealing member **124** comprising a hydrogel **186** may become greater than the inner diameter of the inner lumen **110** of the guiding catheter when the hydrogel is in a partially hydrated, substantially hydrated, or fully hydrated state. This feature allows the thrombectomy catheter **106** to be advanced with little drag down the guiding catheter **108** while the sealing member **124** comprising a hydrogel **186** is becoming hydrated. As the sealing member **124** comprising a hydrogel **186** becomes substantially hydrated, the sealing member **124** will likely be already placed at the location of choice in relation to the distal end **120** of the guiding catheter **108**. In this position, the larger maximum outer diameter of the sealing member **124** will seal against the inner wall **168** of the inner lumen **110** of the guiding catheter. In some embodiments, the hydrogel **186** has high lubricity in order to allow movement with minimal drag while the sealing member **124** is in sealing relationship against the inner wall **168** of the inner lumen **110** of the guiding catheter. In some embodiments, the high lubricity is achieved by the hydrogel having a higher water holding capacity. In some embodiments, the hydrogel **186** has relatively lower lubricity in order to minimize accidental axial movement of the sealing member **124** in relation to the guiding catheter. In some embodiments, the high lubricity is achieved by the hydrogel having a lower water holding capacity. In some embodiments, the hydrogel comprises p-HEMA.

FIG. **20** illustrates an embodiment of a thrombectomy system **100** having one or more sealing members **124** coupled to the proximal end **118** of the distal tube **114** of the thrombectomy catheter **106**. In some embodiments, the one or more sealing member **124** is secured to the outer cylindrical surface **122** of the distal tube **114**. In some embodiments, the sealing member **124** is a cone-shaped or bowl-shaped membrane **190** configured to seal against the inner wall **168** of the guiding catheter **108** at the wipe end **188**.

FIG. **21** illustrates an embodiment of a thrombectomy system **100** having a sealing member **124** which is formed from the proximal end **118** of the distal tube **114** of the thrombectomy catheter **106**. In some embodiments, the sealing member **124** is formed by flaring the proximal end **118** of the distal tube **114**, so that a seal ring **192** is created, for sealing against the inner wall **168** of the guiding catheter **108**.

FIG. **22** illustrates an embodiment of a thrombectomy system **100** having a sealing member **124** coupled to the

proximal end **118** of the distal tube **114** of the thrombectomy catheter **106**. In some embodiments, the sealing member **124** may comprise a cone-shaped or bowl-shaped structure **194**. In some embodiments, the structure **194** may be formed from a tubular braid **196**. In some embodiments, the tubular braid **196** may be braided from metallic wires. In some embodiments, the tubular braid **196** may be braided from Nickel-Titanium wires. In some embodiments, the tubular braid **196** may be heat set into a cone shape or a bowl shape. In some embodiments, the tubular braid **196** may be dip coated. In some embodiments, the tubular braid **196** may be dip coated after having been heat set. In some embodiments, the tubular braid **196** may be dip coated with polyurethane. In some embodiments, the tubular braid **196** may be dip coated with silicone. In some embodiments, the dip coating material may form a seal ring **198** for sealing against the inner wall **168** of the guiding catheter **108**. In some embodiments, the tubular braid **196** is formed so that the seal ring **198** is forced against the inner wall **168** of the guiding catheter **108**. In some embodiments, the dip-coated, formed tubular braid **196** is sufficiently compressible that it can be pushed through the inner lumen **110** of a guiding catheter **108**. FIGS. **20-22** illustrate embodiments of a thrombectomy catheter **106** in a condition when it is at least partially extended axially out of the inner lumen **110** of the guiding catheter **108**. In some embodiments, a stiffness transition member **197** (FIG. **22**) may be incorporated into the distal tube **114**. In some embodiments, the stiffness transition member **197** may comprise a hypo tube that is spiral cut (e.g. laser cut) with decreasing pitch moving distally. A number of other methods known in the art may be used to create a transition in stiffness, such as use of composite materials, a transition of polymeric materials, or transitioning braids or coils.

FIG. **23** illustrates an embodiment of a thrombectomy system **100** having a sealing member **124** which is the proximal end **118** of the distal tube **114** of the thrombectomy catheter **106**. In some embodiments, the entire distal tube **114** comprises a windsock-like-member **200** having a tapered portion **204**. The proximal end **118** has an increased diameter and is supported radially by a stent section **202**. In some embodiments, the stent section **202** is a coil. In some embodiments, the stent section **202** is a laser machined metal tube. In some embodiments, the stent section **202** is a tubular braid.

FIG. **24** illustrates an embodiment of a thrombectomy system **100** having a sealing member **124** which is coupled to the proximal end **118** of the distal tube **114** of the thrombectomy catheter **106**. A structure **206** comprising two or more fingers **208a-d** is secured to the proximal end **118** of the distal tube **114**. In some embodiments, the structure **206** is welded or secured using other methods to the support member **126**. In some embodiments, the structure **206** is flared outwardly towards the proximal end, leading to a sealing ring **212**. In some embodiments, the structure **206** includes a covering **210** over the fingers **208a-d**. In some embodiments, the covering **210** is a membrane.

FIG. **25** illustrates an embodiment of a thrombectomy system **100** of the present invention being used in conjunction with the deployment of a stent **214**. In the method for performing this procedure with the thrombectomy system **100**, the interventionalist (physician) places a guiding catheter **108** into the blood vessel **102**. For example, the interventionalist may place the distal end **120** of the guiding catheter **108** into the ostium of a coronary artery. The interventionalist may next place a guidewire **134** across an atherosclerotic lesion **218**, which may or may not have

thrombus 104. The interventionalist next tracks an embodiment of the thrombectomy catheter 106 of the present invention over the guidewire 134 and through the guiding catheter 108, until the distal end 116 of the distal tube 114 exits the guiding catheter. The interventionalist the tracks the distal end 116 of the distal tube to a target area 112, for example, just proximal to the location of the atherosclerotic lesion 218. The sealing member 124 is positioned within the guiding catheter 108, so that it will be sealingly coupled to the guiding catheter at least while aspiration is being performed. The interventionalist then tracks a dilatation catheter 216 over the guidewire 134, through the guiding catheter 108, and across the atherosclerotic lesion 218. The vacuum source 146 (FIGS. 1 and 2) is coupled to the side port 152 of the y-connector 148, and the stent 214 is expanded by the dilatation balloon of the dilatation catheter 216 while the thrombectomy system performs aspiration. This lowers the possibility that residual thrombus (clot) is carried downstream, causing potential complications. It also lowers then possibility that residual thrombus remains trapped between the stent 214 and the now dilated atherosclerotic lesion 218. When the interventionalist deems the result satisfactory, the interventionalist takes final fluoroscopic (or other) images, and then removes the devices.

FIGS. 26A-26B illustrate an attachment joint 228 and method for joining/coupling the support member 126 to the distal tube of a thrombectomy catheter 106 according to an embodiment of the present invention. A tapered half-pipe member 220 comprising a partial cylinder is secured at its large end 222 to the proximal end 118 of the distal tube 114 by adhesive, epoxy, welding, soldering, embedding or other attachment methods. The small end 224 of the tapered half-pipe member 220 is secured to the support member 126 by adhesive, epoxy, welding, soldering, embedding or other attachment methods. Though the skives 158, 160 are not pictured in FIG. 26, they are compatible with this joining embodiment and method. The tapered half-pipe member 220 allows for a gradual transition that provides an open area 226, so that flow is not compromised. In some embodiments, the outer radius 227 of the tapered half pipe member 220 is configured to substantially match the inner diameter of the distal tube 114. In some embodiment, the inner radius 229 of the tapered half pipe member 220 is configured to substantially match the outer diameter of the distal tube 114. These embodiments enable a close fit and thus a relatively low profile.

FIG. 27 illustrates a dipping process for an attachment joint including but not limited to the attachment joint 228 of FIG. 26. After the attachment joint 228 is assembled, a first dipping step 230 is performed over the majority of the length of the distal tube 114. In some embodiments, the distal tube 114 may comprise a lubricious inner tube layer, such as PTFE, and a spring coil inner layer around the PTFE inner tube layer. In some embodiments, a medium durometer dipping material, such as polyurethane or PEBAX, is applied to the distal tube. In some embodiments, the medium durometer material may have a durometer of about 63D. A second dipping step 232 is performed with a low durometer material, such as polyurethane or PEBAX, to form a "Soft" tip 234. In some embodiments, the low durometer material may have a durometer of about 55D. A third dipping step 236 is performed with a high durometer material over the attachment joint 228. In some embodiments, the third dipping step 236 is performed over most or all of the length of the support member 126. In some embodiments, the high durometer material may have a durometer of about 72D. The result is a stiff, pushable catheter 106 that has a smooth

transition at the attachment joint 228, a flexible distal tube 114 for tracking through the blood vessel 102 (FIGS. 1, 2 and 25) and a soft tip 234 for atraumatic characteristics within the blood vessel 102. A maximized lumen 130 cross-section area may be achieved in any of the embodiments resented herein by minimizing wall thickness and/or minimizing the thickness of any coating. Ultra-thin wall hypo tubes or polyimide tubes may be used in some embodiments. A dip coating of less than about 0.005 cm (0.002 inches) may be applied, and may include polyurethane. A dip coating of less than about 0.0025 cm (0.001 inches), or about 0.0018 cm (0.0007 inches) may be applied, and may include polyurethane.

FIG. 28 illustrates an embodiment of a thrombectomy catheter 106 of the thrombectomy system 100 having a sealing member 124 that is radially compressed over a compressible section 242 of the distal tube 114 during delivery through the guiding catheter 108 (FIG. 1). The compressible section 242 is held in a compressed state by a delivery sheath 238. In some embodiments, the delivery sheath 238 has a sheath push and pull rod 240 coupled to a portion thereof. In use, the thrombectomy catheter 106 is delivered through the guiding catheter 102 and into the blood vessel 102 by pushing the support member 126 and/or the sheath push and pull rod 240. When the distal end 116 of the distal tube 114 of the thrombectomy catheter 106 is located adjacent the target area 112 and the proximal end 118 of the distal tube 114 is within the inner lumen 110 of the guiding catheter 108 (FIG. 2), traction (tension) is applied on the sheath push and pull rod 240 while compression is applied on the support member 126, thus causing the delivery sheath 238 to be pulled proximally, and removed from the compressible section 242 of the distal tube 114, thus allowing the compressible section 242 to expand, and seal against the inner wall 168 (FIG. 15) of the guiding catheter 108. In some embodiments, the delivery sheath 238 may be retracted completely and removed completely from the guiding catheter 108. Though a guidewire 134 is not depicted in FIG. 28, this embodiment, like the other embodiments, may be used with a guidewire 134, as known in the art. In some embodiments, the support member 126 may be coupled to the distal tube 114 via a ring 244. In some embodiments, the ring 244 may be closer to the distal end 116 of the distal tube 114 than the proximal end 118.

45 Saline Injection Aspiration

FIG. 29 illustrates a thrombectomy system 300 which incorporates the high pressure injection of a liquid, for example sterile saline solution, in order to macerate and aspirate thrombus 104 (FIG. 1). A guiding catheter 108 and a y-connector 148 having a proximal seal 150 and a sideport 152 are coupled to a vacuum source 146, as described in relation to the prior embodiments. A thrombectomy catheter 306 comprises a distal tube 314 having a distal end 316 and a proximal end 318, the proximal end 318 incorporating one or more sealing members 324 for sealing off an annulus 342 between the guiding catheter 108 and the distal tube 114, as described in relation to the prior embodiments. The distal tube 314 has an aspiration lumen 330. A support/supply tube 368, having a lumen 370, is coupled to the distal tube 314. The support/supply tube 368 serves the same purpose as the support member 126 of the prior embodiments, but is also a conduit (via the lumen 370) for high pressure saline, which is injected from the proximal end 372 to the distal end 374. The saline is supplied from a saline source 376 (e.g. saline bag, bottle) and pressurized by a pump 378, through a supply tube 380 and through a luer connector 382 which is connected to a luer hub 384 coupled to the support/supply tube

368. In some embodiments, the support/supply tube 368 comprises a hypo tube. In some embodiments, the support/supply tube 368 comprises stainless steel or nitinol.

Turning to FIGS. 30-32, in some embodiments, the support/supply tube 368 may be coupled to the distal tube 314 by attachment materials 386, 388, including adhesive, epoxy, or melted/molded polymer materials. In some embodiments, the support/supply tube 368 has a closed distal end 394, and has one or more orifices 390 in its wall 392. In some embodiments, a rapid exchange tube 398 having a guidewire lumen 396 and a distal tip 408 may be coupled to the side of the distal tube 314, as seen in FIGS. 30 and 31, although the embodiment of FIG. 29 is shown with the guidewire 134 extending through the aspiration lumen 330 and the inner lumen 110.

After the user tracks the thrombectomy catheter 306 through the guiding catheter 108 and to the target area 112 in the blood vessel 102, the pump 378 is operated to inject high pressure saline through the support/supply tube 368. When the saline reaches the orifice (arrows 400), the saline is forced through the one or more orifices 390 and into the aspiration lumen 330. In some embodiments, the saline forms one or more jets 402 that impinge upon inner wall 404 of the aspiration lumen 330, adjacent the one or more orifices 390. A high pressure is thus created in the aspiration lumen 330 adjacent the skive 358, forcing thrombus 104 into the aspiration lumen 330 in a direction generally shown by arrow 406. The thrombus 104 is then carried by the positive pressure gradient from distal to proximal from the aspiration lumen 330 into the inner lumen 110 of the guiding catheter 108 and out the sideport 152 of the y-connector 148 towards the vacuum source 146. In some embodiments, the one or more jets 402 serve to break up and macerate the thrombus 104, aiding in its subsequent passage through the lumens 330, 110. The mixing of the saline with the broken up thrombus 104 serves to lower its bulk viscosity, and thus aid in its passage through the catheter lumens with less resistance. In some embodiments, the one or more orifices 390 are located a distance D from the most proximal portion 410 of a distal opening 412 formed in the aspiration lumen 330 by the skive 358. In some embodiments, the distance D between the axial center of an orifice 390 and the most proximal portion 410 of the distal opening 412 is about 0.0508 cm (0.020 inches), or in some embodiments is $0.0508 \text{ cm} \pm 0.0076 \text{ cm}$ (0.020 inches \pm 0.003 inches).

FIGS. 33-34B illustrate an alternative embodiment of the support/supply tube 368, wherein the support/supply tube 368 couples to the distal tube 314 at the proximal end 318 of the distal tube 314. The distal tube 314 includes a wall 416 having a lumen 414. The support/supply tube 368 is coupled to the lumen 414 so that saline supplied through the support/supply tube 368 then passes through the lumen 414 distally, and exits the one or more orifices 390. In some embodiments, the lumen 414 may be provided by a separate polyimide tube that is embedded in the wall 416. In some embodiments, a proximally facing lip 246, for example, an annular seal extending in both a radial and proximal direction, is sealingly coupled to the distal tube 314. The high pressure saline injection through the lumen 370 of the support/supply tube 368, in combination with the vacuum source 146 (FIGS. 3-6), causes aspiration in a direction generally shown by arrow 406. The high pressure saline injection also creates an internal pressure P_I within the inner lumen 110 of the guiding catheter 108 that is higher than the ambient pressure P_A outside the distal end 120 of the guiding catheter 108. Because $P_I > P_A$, the proximally facing lip 246 is forced against the inner wall 168 of the inner lumen 110

of the guiding catheter 108, sealing the annulus 142. In some embodiments, the proximally facing lip 246 is thin and made from a flexible material (as in the distally facing lip 166 of FIG. 11), thus aiding its ability to be forced against the inner wall 168. In some embodiments, other embodiments of the sealing member 124 may be used, including, but not limited to, o-rings and hydrogel seals. In some embodiments, as seen in FIG. 34B, the distal end of the support/supply tube 368 may have an oval, elliptical or rectangular shape in order to allow a connection to the lumen 414 of the distal tube 314 that does not significantly compromise the size of the aspiration lumen 330 of the distal tube 314.

FIG. 35 illustrates an embodiment of the thrombectomy catheter 306 wherein the lumen 370 of the support/supply tube 368 may be decoupled from the luer hub 384 (FIG. 29) so that a stylet 418 may be inserted down the lumen 370 in order to impart additional stiffness and pushability. In some embodiments, the stylet 418 comprises stainless steel. In some embodiments, the support/supply tube 368 is a circular cross-section hypo tube and has an outer diameter of about 0.0549 cm (0.0216 inches) and an inner diameter of about 0.0483 cm (0.019 inches). In some embodiments, the stylet 418 has a circular cross-section and has an outer diameter of between about 0.038 cm (0.015 inches) and about 0.0457 cm (0.018 inches). In some embodiments, the stylet 418 may have a hub 420 at its proximal end, in order to aid handling of the stylet 418 during insertion and removal.

FIG. 36 illustrates an embodiment of the thrombectomy catheter 306 wherein the lumen 370 of the support/supply tube 368 is coupled to a smaller tube 422 within the aspiration lumen 330 of the distal tube 314. In some embodiments, the smaller tube 422 is a polyimide tube. In some embodiments, the smaller tube 422 is a tapered polyimide tube, tapering to a smaller diameter as it extends distally to its orifice 424. The support/supply tube 368 is also secured to a ring 426, which in some embodiments is closer to the distal end 316 than the proximal end 318 of the distal tube 314. The ring 426 is also secured to the distal tube 314. When the user pushes on the support/supply tube 368 at its proximal end, the force that in turn is applied to the ring 426 serves to "pull" the proximal end 318 of the distal tube 314, thus lessening the chances of compressing or deforming it. The proximal end 318 of the distal tube 314 includes an expandable section 430 which may include a tubular mesh 428. The tubular mesh 428 may be encapsulated, for example by dipping in polyurethane or silicone, in order to create a sealed aspiration lumen 330 that extends from the distal end 316 to the proximal end 318. In some embodiments, the ring 426 may be constructed from a metal material, such as stainless steel or nitinol. In some embodiments, the ring 426 may include radiopaque material, such as platinum, for visualization on fluoroscopy or x-ray. The ring 426, and its use as the point of application of pushing or pulling, may be incorporated into one of the embodiments of the thrombectomy catheters 106 that do not have high pressure saline injection, but only aspiration. In this case, the support/supply tube 368 need not be a tube or hypo tube, but may also be a solid round wire flat wire.

Because of their use of the inner lumen 110 of the guiding catheter 108 as a portion of the extended lumen 128 (FIG. 2), any of the thrombectomy systems 100, 300 presented include the feature that one length (model) the thrombectomy catheter 106, 306 may be used on a variety of patient sizes and/or target area 112 depths. A single model of thrombectomy catheter 106, 306 may be adjusted to the desired depth in the blood vessel 102 so that it is adjacent to the target area 112, but the vacuum source 146 is still

coupled at the same location, on the side port **152** of the y-connector **148**. A large range of models (e.g. different lengths) of the thrombectomy catheter **106**, **306** is not required. In some cases, this may mean that a single model of thrombectomy catheter **106** and/or a single model of thrombectomy catheter **306** may satisfy the majority of thrombectomy procedures performed in a particular catheterization laboratory or other health care facility, thus requiring a smaller area of shelf space.

An assembly process for an embodiment of a thrombectomy catheter **306** is illustrated in FIGS. **37-42**. A slotted mandrel **440** having a longitudinally extending slot **442** is shown in FIG. **37**. FIG. **38** illustrates a cross-section of the slotted mandrel **440** and several components placed over it during a placement step, in the following radial order: liner tube **444**, saline lumen tube **448** having a saline lumen **446**, and a support layer **450**. In some embodiments, the orifice may be pre-cut into the saline lumen tube **448** and may be aligned during the placement step. In some embodiments, the liner tube **444** may comprise PTFE or other fluoropolymers. In some embodiments, the saline lumen tube **448** may comprise a polyimide tube. In some embodiments, the support layer **450** may comprise a tubular braid, one or more coils or a laser machined hypo tube. The slotted mandrel **440** with the components **444**, **448**, **450** placed over it, is dipped into a polyurethane, silicone, or other material to coat and set, during a dipping process, creating a composite structure **445** having an outer layer **447**. The slotted mandrel **440** is then removed, during a removal step, and the ends of the saline lumen tube **448** may be cut clean. As seen in FIGS. **39-42**, a radiopaque marker band **452** may be incorporated as part of the assembly by bonding the radiopaque marker band **452** to the saline lumen tube **448** with an adhesive **454** or epoxy, aligning the saline lumen tube **448** as in FIG. **42**, and then completing the assembly and the dipping process as described in relation to FIG. **38**.

Clog Detection/Clot Detection

Clogging of aspiration catheters, for example by large pieces of thrombus, is a common concern for users. Techniques to avoid clogging/choking of material within the catheter often involve rapidly, aggressively advancing the aspiration catheter or gently plucking at edges of a thrombus to insure only small pieces or portions are introduced at a time, pieces which are small enough to not clog or occlude the aspiration lumen. When a device becomes clogged during use, the potential for inadvertent dislodgment of thrombus downstream increases; this is referred to as distal embolism. As aspiration procedures of this type are often used in highly technical emergent settings, early clog detection of the aspiration catheter for the user during aspiration can contribute to the success of the procedure and clinical outcome. Some sources have reported that up to 50% of aspiration catheters used get clogged during use.

Additionally, the user may have difficulty determining whether there has been a loss of vacuum in the system, for example because of the syringe (or other vacuum source) being full of fluid or because of a leak in the system. Blood is relatively opaque and can coat the wall of the syringe, thus making it difficult to determine when the syringe becomes full. This makes it difficult to determine whether sufficient vacuum is being applied to the aspiration catheter. It is also difficult to determine whether there is an air leak in the system, which can be another cause for a loss of vacuum even before the syringe becomes full of the aspirated fluid.

During the aspiration of thrombus with an aspiration catheter, it is difficult to identify when thrombus is actively being aspirated, and when only blood is being aspirated.

Typically it is desired to not aspirate sizable quantities of normal blood from blood vessels, because of the importance of maintaining normal blood volume and blood pressure. However, when tracking the tip of an aspiration catheter in proximity to a thrombus, it is difficult to know whether the aspiration catheter has actively engaged a thrombus, whether it has aspirated at least a portion of the thrombus, or whether it is not engaged with the thrombus, and is only aspirating blood. The use of aspiration catheters can therefore be inefficient, and cause more blood removal than desired, causing a user to minimize the length of the therapy and in severe cases necessitating blood transfusion. An increased volume of normal blood being aspirated also means that the vacuum source (e.g. syringe) will fill in a shorter amount of time, thus required more frequent replacement of the vacuum source. Distal embolism may occur if the vacuum pressure is not sufficient, and yet the user is not aware.

An aspiration system **2** is illustrated in FIG. **43** and is configured to allow real time monitoring of catheter aspiration. The aspiration system **2** comprises an aspiration catheter **4**, a vacuum source **6**, a valve **8**, extension tubing **10**, and an aspiration monitoring system **48** including an in-line pressure transducer **12**. The aspiration catheter **4** has a proximal end **14** and a distal end **16** and an aspiration lumen **18** extending from the proximal end **14** to the distal end **16**. The aspiration lumen **18** may be sized for aspiration of thrombus, and in some embodiments may have an inner diameter of between about 0.038 cm (0.015 inches) and about 0.254 cm (0.100 inches). The aspiration catheter **4** includes a hub **20** at its proximal end which may include a female luer connector **22**. The aspiration lumen **18** at the distal end **16** of the aspiration catheter **4** may include an angled orifice **24**, which aids in the tracking through tortuous or occluded vasculature. In some embodiments, a guidewire lumen **26** is coupled to the distal end **16** of the aspiration catheter **4**, and is configured to track over a guidewire **28**. The vacuum source **6** may comprise a syringe, and may be sized between 5 ml and 100 ml, or between 20 ml and 60 ml. The vacuum source **6** may comprise a VacLok® syringe, made by Merit Medical, Salt Lake City, Utah. The vacuum source **6** may include a barrel **30** and plunger **32**, with a lock **34** which is configured to retain the plunger **32** in position in relation to the barrel **30**, for example, when the plunger is pulled back in direction **D** to create a negative pressure (vacuum) inside the barrel **30**. In some embodiments, the vacuum source **6** may comprise any other type of evacuable reservoir, or may comprise a vacuum pump. The vacuum source **6** is connected to the aspiration lumen **18** of the aspiration catheter **4** via the extension tubing **10** and the valve **8**. In some embodiments, the vacuum source **6** may be connected directly to the aspiration lumen **18** of the aspiration catheter **4**. Male luer connectors **36** and female luer connectors **38** are indicated in FIG. **43**. The valve **8** may be a standard two-way stopcock, as illustrated.

The pressure transducer **12** of the aspiration monitoring system **48** is configured to be fluidly coupled between the vacuum source **6** and the aspiration catheter **4**. In FIG. **44A**, the aspiration monitoring system **48** is illustrated as a self-contained device of a first embodiment. The pressure transducer **12** comprises a housing **40** having a cavity **42** extending between a first port **44** and a second port **46**. In some embodiments, the first port **44** comprises a female luer and the second port **46** comprises a male luer. In some embodiments, the first port **44** comprises a female luer lock and the second port **46** comprises a male luer lock, each of which is attachable to and detachable from a corresponding

luer lock of the opposite gender. The first port **44** is configured to be coupled to the vacuum source **6**, either directly, or with the valve **8** and/or extension tubing **10** connected in between. The second port **46** is configured to be coupled to the aspiration lumen **18** of the aspiration catheter **4**, for example, by coupling the second port **46** directly or indirectly to the hub **20** of the aspiration catheter **4**. When the aspiration system **2** is used to aspirate body fluids and/or materials, for example blood and/or thrombus, the body fluids and/or materials are aspirated through the aspiration lumen **18** of the aspiration catheter from the angled orifice **24** at the distal end **16** to the female luer connector **22** at the proximal end **14**, then pass through the second port **46** of the pressure transducer **12** first, through the cavity **42**, and then through the first port **44**. Depending on the amount of amount of vacuum (negative pressure) applied by the vacuum source **6**, and the amount of flow resistance and resulting pressure drop along the aspiration system **2**, the pressure within the cavity **42** will vary. For example, a more viscous fluid like blood, or a fluid having solid, semi-solid, or gel-like particles or portions, will cause more flow resistance through the relatively small aspiration lumen **18** of the aspiration catheter **4** than would water or normal saline solution. Thus the pressure within the cavity **42** of the pressure transducer **12** will decrease (the amount of vacuum will increase) as the flow resistance in the aspiration lumen **18** increases.

For definition purposes, when speaking of the amount of vacuum, a pressure of, for example, $-15,000$ pascal (-2.18 pounds per square inch, or psi) is a “larger vacuum” than $-10,000$ pascal (-1.45 psi). Additionally, $-15,000$ pascal is a “lower pressure” than $-10,000$ pascal. Furthermore, $-15,000$ pascal has a larger “absolute vacuum pressure” than does $-10,000$ pascal, because the absolute value of $-15,000$ is larger than the absolute value of $-10,000$. In FIG. **44A**, a vacuum sensor **50** is disposed within the cavity **42** of the housing **40** and is in fluid communication with fluid that passes through the cavity **42**. The vacuum sensor **50** may be a standard pressure sensor or transducer, including a pressure sensor designed primarily for measuring positive pressure. It may use any type of pressure sensing technology known in the art, including MEMS Technology. In some embodiments, the vacuum sensor **50** is configured for highest accuracy and/or precision within the range of pressures between about 0 pascal to about $-101,325$ pascal (-14.70 psi), or between about $-45,000$ pascal (-6.53 psi) and about $-90,000$ pascal (-13.05 psi), or between about $-83,737$ pascal (-12 psi) and about $-96,527$ pascal (-14 psi). In some embodiments, the power requirement for the vacuum sensor may range from 2.5 volts DC to 10 volts DC. In some embodiments, the vacuum sensor **50** may be an analog gauge with an output voltage. In the self-contained embodiment of the FIG. **44A**, the vacuum sensor **50** is powered by one or more battery **52**. Based on the power requirements of the vacuum sensor **50**, and the power requirements of other components of the aspiration monitoring system **48** described herein, in some embodiments the one or more battery **52** may range between 1.5 volts and nine volts. Also contained within the housing is a measurement device **54**, which in some embodiments may comprise a microprocessor. The measurement device **54** is coupled to the vacuum sensor **50** and receives signals from the vacuum sensor **50** indicative of real time measured pressure. In some embodiments, the measurement device **54** includes a memory module **56** in which information is stored that may be used by the measurement device **54**, for example, in calculations.

One or more communication devices **58a**, **58b**, **58c** are included within the aspiration monitoring system **48** and are coupled to the measurement device **54**. Each of the one or more communication devices **58a-c** are configured to generate a type of alert comprising an alert signal **60a-c**, in response at least in part to activity and output of the measurement device **54**. In some embodiments, the communication device **58a** may include one or more LEDs (light emitting diodes) configured to generate a visible alert via a visible alert signal **60a**, such as light that is continuously illuminated, or is illuminated in a blinking pattern. In some embodiments, lights other than LEDs may be used. In some embodiments, the communication device **58b** may include one or more vibration generators configured to generate a tactile alert via a tactile alert signal **60b**, which may include, but is not limited to, vibration or heat. In some embodiments, the vibration generator may comprise a piezoelectric device which is configured to vibrate when a voltage is applied. In some embodiments, the communication device **58c** may include one or more sound generating devices configured to generate an audible alert via an audible alert signal **60c**, such as a continuous noise, or a repeating noise. In some embodiments, the sound generating device may comprise a buzzer which is configured to sound one or more audible pitches when a voltage is applied. In some embodiments a piezoelectric device, such as that described in relation to the communication device **58b** may also serve as a sound generating device, included as communication device **58c**.

A user of an aspiration system **2** may desire to be notified of several conditions which may occur during use of the aspiration system **2**. These potential conditions include, but are not limited to clogging, a loss of vacuum due to filling of the vacuum source **6** and or a breach, break or puncture in the aspiration system **2**, and the engagement or aspiration of non-fluid, solid or semi-solid material such as thrombus. The aspiration monitoring system **48** of FIG. **44A** is configured to alert users of an aspiration system **2** about real time status of the aspiration system **2**, including operational conditions, which include: whether vacuum is being applied or not; flow conditions, which include whether a thrombus is engaged, whether a thrombus is being actively aspirated, whether the system is leaking air, whether the system is clogged, whether the vacuum source **6** is full and/or needs to be changed; or other potential set up issues. The real time feedback provided frees a user or operator from the need of excessive personal monitoring of the vacuum source **6**, extension tubing **10**, or other portions of the aspiration system **2**, for improper or undesired flow or operation conditions, and thus allows the user to focus more attention on the patient being treated.

The pressure transducer **12** of the aspiration monitoring system **48** is configured to continuously measure and monitor the absolute pressure amplitude within the closed system of the aspiration system **2**, and also is configured to measure and monitor the relative pressure over time to detect noteworthy flow changes within the flow circuit of the aspiration system **2**. Some changes are discernible via absolute pressure measurement, while more subtle pressure deflections may be compared to a stored library in memory. Noteworthy conditions may be signaled to the user when appropriate. In some embodiments, the unfiltered signal may be amplified by an amplifier and filtered by a filter, for example, to increase the signal-to-noise ratio. Examples of the (background) noise **57** in an unfiltered signal can be seen in FIGS. **46A-46D** (labeled in FIG. **46A**). In some embodiments, one

or more algorithms may be used, as described herein, to identify particular conditions of interest.

FIG. 44B illustrates a second embodiment of an aspiration monitoring system 62 having a pressure transducer 12 having a vacuum sensor 50 disposed within the cavity 42 of a housing 40. The vacuum sensor 50 may be powered by at least one battery 52. In some embodiments, the pressure transducer 12 may be reusable, and may be configured to allow charging of the battery 52, or of a capacitor (not shown) by direct charging methods, or by inductive power transfer methods and devices known in the art. Unlike the aspiration monitoring system 48 of FIG. 44A, the aspiration monitoring system 62 of FIG. 44B comprises a measurement device 64, memory module 66, and communication device 68 which are external to the pressure transducer 12. A power module 72, also external, may be used to power any of the measurement device 64, memory module 66, or communication device 68. The communication device 68 may be any of the communication device 58a, 58b, 58c described in relation to the aspiration monitoring system 48 of FIG. 44A, and are configured to product an alert via an alert signal 70. The communication device 68 may be portable so that it may be positioned close to the user.

In some embodiments, the communication device 68 may be wearable by the user. FIG. 44C illustrates an aspiration monitoring system 78 which includes an antenna 80 coupled to a measurement device 76. The measurement device 76 is similar to the measurement device 54 of prior embodiments, except that it wirelessly sends a communication signal 84 via the antenna 80 to a corresponding antenna 82 of a communication device 74. In some embodiments, the communication device 74 comprises a wristband which the user wears, and which may include a vibration generator or heat generator. In some embodiments, the communication device 74 comprises an audio speaker which may be attached to equipment or even to the patient or user. In some embodiments, the communication device 74 comprises an audio speaker on an earpiece or earbud that the user may wear. In some embodiments, Bluetooth® communication technology may be used.

FIG. 45A illustrates the distal end 16 of an aspiration catheter 4 within a blood vessel 86 having at least one thrombus 88. The aspiration catheter 4 is being advanced in a forward direction F, but the distal end 16 of the aspiration catheter 4 has not yet reached the proximal extremity 94 of the thrombus 88. A vacuum source 6 (FIG. 43) has been coupled to the aspiration lumen 18 of the aspiration catheter 4 and activated (i.e. the valve 8 is open) causing blood 96 to be aspirated into the aspiration lumen 18 (arrows A). Turning to FIG. 46A, a corresponding curve 98 is represented for the normal fluid (e.g. blood) vacuum over time for the condition of FIG. 45A. The curve 98 represents vacuum pressure over time sensed by the vacuum sensor 50 of any of the embodiments presented. No leaks are present and no thrombus is being evacuated, and therefore the curve 98 includes a downward slope 99 when the vacuum source 6 increases the vacuum up (lowers the pressure) within the cavity 42 of the pressure transducer 12 to a relatively steady state. The steady pressure curve 97 continues while blood 96 is being aspirated. As the vacuum is decoupled from the aspiration lumen 18, for example by closing the valve 8 or by detaching any two of the ports (e.g. luers), or if the vacuum source 6 fills completely with blood 96, then an upward slope 95 is measured.

The measurement device 54, 64 is configured to compare the curve 97 with information stored in the memory module 56, 66 to identify this condition. In some embodiments, the

measurement device 54, 64 uses an algorithm to make the comparison. In some embodiments, the measurement device 54, 64 then sends a signal to the communication device 58a-c, 74, and the communication device 58a-c, 74 generates an appropriate alert. Communication device 58a, for example a particular color LED, may be illuminated, or an LED may flash in a particular pattern or number of flashes. Communication device 58b may create a characteristic sound, or may generate an audio message in a number of languages. For example, the audio message may state, "Thrombus encountered," or "No thrombus encountered." Communication device 58c may vibrate or heat in a characteristic pattern, for example, a certain number of repetitions or a certain frequency between repetitions. The user may determine that an additional fluoroscopic image (e.g. angiography) or other imaging modalities may be necessary to better identify the location of the thrombus 88.

FIG. 45B illustrates the distal end 16 of an aspiration catheter 4 advanced to a position such that the distal end 16 of the aspiration catheter 4 contacts the proximal extremity 94 of the thrombus 88. The corresponding curve 93 in FIG. 46B represents vacuum pressure over time sensed by the vacuum sensor 50 of any of the embodiments presented. The curve 93 initially has a downward slope 99 followed by a steady pressure curve 97, as in the condition of FIG. 45A, graphed in FIG. 46A, however, when the distal end 16 of the aspiration catheter 4 contacts the proximal extremity 94 of the thrombus 88, if the aspiration causes a portion of the thrombus 88 (for example a large or relatively hard portion) to enter and become trapped in the aspiration lumen 18, then a clog condition occurs. A similar condition occurs if the distal end 16 of the aspiration catheter 4 is caught on the thrombus 88 by the vacuum, with virtually nothing flowing through the aspiration lumen 18. In either condition, the curve 93 includes a deviation (or disturbance) in fluid pressure 91. If the clog (or stuck condition) continues, then a flat, depressed pressure 89 is measured.

The measurement device 54, 64 is configured to compare the curve 93 with information stored in the memory module 56, 66 to identify this condition. In some embodiments, the measurement device 54, 64 uses an algorithm to make the comparison. In some embodiments, a pre-set pressure differential ΔP_1 may be stored in the memory module 56, 66 as a threshold, whereby the measurement of a pressure difference 81 less than this threshold does not result in the measurement device 54, 64 commanding the communication device 58a-c, 74 to send an alert signal 60a-c, 70. In some embodiments, when the pressure difference 81 is greater than (or greater than or equal to) the pre-set pressure differential ΔP_1 , the measurement device 54, 64 then sends a signal to the communication device 58a-c, 74, and the communication device 58a-c, 74 generates an appropriate alert. Communication device 58a, for example a particular color LED, may be illuminated, or an LED may flash in a particular pattern or number of flashes. Communication device 58b may create a characteristic sound, or may generate an audio message in a number of languages. For example, the audio message may state, "Clog Condition." Communication device 58c may vibrate or heat in a characteristic pattern, for example, a certain number of repetitions or a certain frequency between repetitions. When the user realizes that the clog condition is present, the user may pull on the aspiration catheter 4 and readvance it, in an attempt to contact a portion of the thrombus 88 that can be aspirated. If a portion of the thrombus is clogged in the aspiration lumen 18, and repositioning of the aspiration catheter 4 does not produce good results, the aspiration

catheter 4 can be removed and the aspiration system 2 can be repurged, for example by a positive pressurization.

FIG. 45C illustrates the distal end 16 of the aspiration catheter 4 in a general situation during which a breach in the aspiration system 2 has occurred. For example, a break, leak, 5 puncture, pinhole, loosening, or disconnection may cause air to be pulled into the aspiration lumen 18 of the aspiration catheter 4, the cavity 42 of the pressure transducer 12, of the interior of the extension tubing 10, valve 8, or vacuum source 6. As graphed in the curve 85 of FIG. 46C, a downward slope 99 and a subsequent steady pressure curve 97 are measured, but at the point in time of the breach 87 an upward slope 83 begins.

The measurement device 54, 64 is configured to compare the curve 85 with information stored in the memory module 56, 66 to identify this condition. In some embodiments, the measurement device 54, 64 uses an algorithm to make the comparison. In some embodiments, the measurement device 54, 64 then sends a signal to the communication device 58a-c, 74, and the communication device 58a-c, 74 generates an appropriate alert. Communication device 58a, for example a particular color LED, may be illuminated, or an LED may flash in a particular pattern or number of flashes. Communication device 58b may create a characteristic sound, or may generate an audio message in a number of languages. For example, the audio message may state, "System Leak." Communication device 58c may vibrate or heat in a characteristic pattern, for example, a certain number of repetitions or a certain frequency between repetitions. Upon receiving the alert, the user will check the components of the aspiration system 2 and either fix the breach or replace one or more of the components of the aspiration system 2. For example, in some cases, the communication device 58a-c, 74 may alert the user when the measurement device 54, 64 confirms a loss of vacuum, allowing the user to change or recharge the vacuum source 6, which has become depleted (e.g. by filling with blood and/or thrombus).

FIG. 45D illustrates the distal end 16 of the aspiration catheter 4 during the successful aspiration of pieces or portions 90 of the thrombus 88. In some cases, the pieces or portions 90 may follow a tortuous path 92, due to disturbances or collisions with the inner wall of the aspiration lumen 18 while being pulled through the aspiration lumen 18. In some cases, the pieces or portions 90 may catch and slip within the inner wall of the aspiration lumen 18, for example, do to variance of the inner diameter of the aspiration lumen 18 along the length. Either of these situations can cause a corresponding series of increases and decreases in the pressure being sensed by the pressure transducer 12, while the pieces or portions 90 are traveling through the aspiration lumen 18. As graphed in the curve 79 of FIG. 46D, a downward slope 99 and a subsequent steady pressure curve 97 are measured, but as the pieces or portions 90 of thrombus 88 travel down the aspiration lumen 18 of the aspiration catheter 4, a deviation 77 of fluid pressure comprising a plurality of decreases and increases in pressure (increases and decreases in vacuum pressure) is measured. As the pieces or portions 90 of thrombus 88 exit the proximal end of the aspiration lumen 18 of the aspiration catheter 4, a second steady pressure curve 75 is measured. The duration 67 of the deviation 77 is the amount of transit of the particular significant pieces or portions 90 of thrombus 88. The duration 67 can range quite a bit, but in some cases may be less than a second or up to about 30 seconds. When again additional pieces or portions 90 of thrombus 88 are aspirated into and travel down the aspiration lumen 18 of the aspiration catheter 4, another deviation 73 of fluid

pressure comprising a plurality of decreases and increases in pressure (increases and decreases in vacuum pressure) is measured. At the end of the curve 79, the vacuum source 6 is shown filling completely with blood 96 and the pieces or portions 90 of thrombus 88, and so an upward slope 95 is measured.

The measurement device 54, 64 is configured to compare the curve 79 with information stored in the memory module 56, 66 to identify when the pieces or portions 90 of thrombus 88 are actively being aspirated, as in deviation 77 and deviation 73, and when the pieces or portions of thrombus 88 are not being actively, or substantially, aspirated, as in steady pressure curve 97, the steady pressure curve 75, and the steady pressure curve 71. In some embodiments, the measurement device 54, 64 uses an algorithm to make the comparison. In some embodiments, a pre-set pressure differential ΔP_2 may be stored in the memory module 56, 66 as a threshold, whereby the measurement of a pressure difference 69 less than this threshold does not result in the measurement device 54, 64 commanding the communication device 58a-c, 74 to send a first type of alert via an alert signal 60a-c, 70. In some embodiments, when the pressure difference 69 is greater than (or greater than or equal to) the pre-set pressure differential ΔP_2 , the measurement device 54, 64 then sends a signal to the communication device 58a-c, 74, and the communication device 58a-c, 74 generates an appropriate alert. Communication device 58a, for example a particular color LED, may be illuminated, or an LED may flash in a particular pattern or number of flashes. In some embodiments, the communication device 58a may comprise a light whose intensity increases proportionally with the pressure. Communication device 58b may create a characteristic sound, or may generate an audio message in a number of languages. For example, the audio message may state, "Thrombus being aspirated." In some embodiments, communication device 58b may comprise one or more noises or beeps. In some embodiments, the communication device 58b may comprise a particular series of beeps corresponding to each different condition. For example, three short beeps may correspond to no thrombus being aspirated, while five long, loud beeps may correspond to a system leak. In some embodiments, a plurality of different tones (pitches) may be used to alert a user about different conditions. As an example, a low pitch sound may be used for a first condition (e.g. no thrombus being aspirated) and a second, higher pitch sound may be used for a second condition (e.g. a system leak). In some embodiments, a plurality of different tones may be used to alert a user about a first condition and a second plurality (e.g. in a different combination, or with additional tones) may be used to alert a user about a second condition. Communication device 58c may vibrate or heat in a characteristic pattern, for example, a certain number of repetitions or a certain frequency between repetitions. When the user realizes that the thrombus is being aspirated, the user may choose to advance (or retract) the aspiration catheter 4, for example with fluoroscopic visualization, along the length of the thrombus 88, in an attempt to continue the aspiration of the thrombus 88. In some cases, the user may choose to stop the advancement or retraction of the aspiration catheter 4 at a certain amount of time after the alert is generated, in order to allow the pieces or portions 90 of thrombus 88 to completely exit the aspiration lumen 18. When the measurement device 54, 64 identifies a subsequent steady pressure curve 75, 71 that follows a deviation 77, 73, the measurement device 54, 64 in some embodiments sends a signal that causes the communication device 58a-c, 74 to generate a second type of alert via an alert signal 60a-c, 70.

For example, in some embodiments, communication device **58b** may send an audio message that states, “Thrombus no longer being aspirated.” When the user realizes that the thrombus is no longer being aspirated, the user may advance or retract the aspiration catheter, in an attempt to contact another portion of the thrombus **88** that can be aspirated. In some embodiments, the deviation **77** may be positively identified as a true deviation indicating thrombus being actively aspirated, pressure difference **69** is between about 700 pascal and about 1700 pascal. In some embodiments, the deviation **77** may be positively identified as a true deviation indicating thrombus being actively aspirated, pressure difference **69** is between about 1000 pascal and about 1300 pascal. In some embodiments, the deviation **77** may be positively identified as a true deviation indicating thrombus being actively aspirated, pressure difference **69** is about 1138 pascal. The pressure difference **69** may be measured by determining a baseline pressure **63** and a peak pressure **61** and determining the absolute value difference. For example:

$$\text{Absolute value difference (AVD)} = |(-89,631 \text{ pascal}) - (-90,769 \text{ pascal})| = 1138 \text{ pascal}$$

Or for example:

$$\text{Absolute value difference (AVD)} = |(-43,710 \text{ pascal}) - (-45,102 \text{ pascal})| = 1281 \text{ pascal}$$

The pressure difference **81** (FIG. **46B**) may also represent a deviation that may be identified in a similar manner, after which the communication device **58a-c**, **74** generates an appropriate alert, such as, “Clog condition.”

Because vacuum pressure is a negative pressure, the peak pressure **61**, as shown in FIG. **46D**, is actually a lower number than the baseline pressure **63**. In some embodiments, the measurement device **54**, **64** may also be configured to make a comparison, for example by using an algorithm, between a stored differential time t_1 and a duration **65** of a single one of the plurality of decreases and increases in pressure in the deviation **77**. For example, in some embodiments, the deviation may be positively identified as a true deviation indicating thrombus being actively aspirated, if the duration is between about 0.001 seconds and about 0.50 seconds. In some embodiments, the deviation may be positively identified as a true deviation indicating thrombus being actively aspirated, if the duration is between about 0.005 seconds and about 0.10 seconds. In some embodiments, the deviation may be positively identified as a true deviation indicating thrombus being actively aspirated if the duration is between about 0.05 seconds and about 0.20 seconds. In some embodiments, the measurement device **54**, **64** is configured to recognize deviation **77** after two or more decreases and increases in pressure are measured. In some embodiments, the measurement device **54**, **64** is configured to recognize deviation **77** after five or more decreases and increases in pressure are measured. In some embodiments, the measurement device **54**, **64** is configured to recognize deviation **77** after ten or more decreases and increases in pressure are measured.

Insertion of the pressure transducer **12** in line in either the embodiment of FIG. **44A** or the embodiment of FIG. **44B** does not measurably change performance characteristics of the aspiration system **2**, because the cavity **42** is relatively short and has a relatively large inner diameter, and thus is not a significant source of fluid flow resistance. In some embodiments, the inner diameter may be between about 2.2 mm (0.086 inches) and about 3.2 mm (0.125 inches). In some embodiments, the measurement device **54**, **64**, **76** need not include a microprocessor, as pre-defined set points (e.g. for

certain thresholds) may be included in firmware, microcontroller, or other locations. In some embodiments, including but not limited to the embodiment of FIG. **44B**, the pressure transducer **12** may be an off-the-shelf blood pressure monitor system, which is modified or augmented with other components. In some embodiments an off-the-shelf blood pressure monitor system may be used as the output of the aspiration monitoring system **48**, **62**, **78**. In some embodiments, an aspiration catheter **4** may have a pressure transducer in the distal end **16**. This pressure transducer may be used as the pressure transducer **12** of the aspiration monitoring system **48**, **62**, **78**. In some embodiments, a pressure sensor may be located within a Tuohy-Borst valve, and introducer sheath, a guiding catheter, or another component of the system through which is in fluid communication with the aspiration lumen **18**. In some embodiments, the pressure sensor may be located anywhere within the aspiration lumen of the aspiration catheter.

In some embodiments, instead of an LED, the visual alert is provided by a communication device **58a** comprising a display which displays visual messages of text in a particular language, for example, “Thrombus encountered,” “No thrombus encountered,” “Clog condition,” “System leak,” “Loss of vacuum,” “Thrombus being aspirated,” or “Thrombus no longer being aspirated.” The visual messages may be combined with any of the other alert signals **60a-c**, **70** described herein. The aspiration monitoring system **48**, **62**, **78** described herein give real time awareness to users performing aspiration procedures, such as the removal of thrombus via an aspiration system **2**. One skilled in the art will recognize that by knowing the real time condition of the aspiration system **2**, the user is able to immediately make changes to the procedure in order to optimize results, increase safety for the patient and/or medical personnel, reduce costs (e.g. number of vacuum sources **6** required), and reduce procedure time (also a cost benefit). Because the user is typically performing multiple tasks during an aspiration procedure, the sensory aid provided by the aspiration monitoring system **48**, **62**, **78** allows the user to focus on these tasks without having to continually attempt to monitor conditions which are often difficult to visually monitor. The user may also modify and control the aspiration monitoring system **48**, **62**, **78** via an input **59** (FIG. **44B**), which may comprise a data entry module, keyboard, or a series of buttons with a display. The input **59** may in some embodiments comprise an auditory input which accepts voice commands. Alternatively, the user may input information and control the aspiration monitoring system, **48**, **62**, **78** remotely. Some of the alerts which the user may select or deselect in the aspiration monitoring system **48**, **62**, **78** include, but are not limited to: whether the aspiration system **2** is potentially blocked or clogged, or is flowing normally; whether thrombus has been contacted or not; whether a clog has occurred; whether the vacuum source **6** is adequate, or whether it has been depleted and requires replacement; whether there is a leak in the aspiration system **2**; whether setup or connection of the components of the aspiration system **2** was done correctly or incorrectly; whether to advance the catheter distally; whether to retract the catheter; whether to continue moving the catheter at the same speed; whether to increase or decrease the speed of catheter advancement; whether thrombus is actively being aspirated; and whether thrombus stops being actively aspirated.

In some embodiments, alternate power sources may be used, for example, standard AC power with or without an AC/DC convertor; direct connection to existing equipment (e.g. vacuum pumps, etc.); solar power. The aspiration

monitoring system **48**, **62**, **78** may be packaged sterile or may be resterilizable by techniques known by those skilled in the art. In some embodiments, flow or volume gauges may be used in conjunction with or instead of the pressure gauge **12**, in order to determine, for example, a clog, or a change in the amount of vacuum.

Though aspiration of thrombus has been described in detail, the aspiration monitoring system **48**, **62**, **78** has utility in any aspiration application wherein heterogeneous media is being aspirated. This may include the aspiration of emboli (including not thrombotic emboli) from ducts, vessels, or cavities of the body, or even from solid or semi-solid portions of the body, including, but not limited to, portions of fat, breasts, and cancerous tissue.

In some embodiments, the aspiration system **2** is provided to the user as a kit with all or several of the components described, while in other embodiments, only the aspiration monitoring system **48** is provided. Though discussion herein includes embodiments for aspiration of thrombus and blood, the definition of the word “fluid” should be understood throughout to comprise liquids and gases.

In some embodiments, an additional or alternate sensor may be used to monitor flow conditions for the notification of the user, including, but not limited to: a Doppler sensor, an infrared sensor, or a laser flow detection device. In some embodiments, an externally-attached Doppler sensor may be employed. In some embodiments, an infrared sensor or a laser flow detection device may be employed around the extension tubing **10**.

Assisted Aspiration

FIG. **47** is a diagrammatic figure depicting an assisted aspiration system **510**. The aspiration system **510** includes a remote hand piece **512** that contains a fluid pump **526** and an operator control interface **506**. In one contemplated embodiment, the system **510** is a single use disposable unit. The aspiration system **510** may also include extension tubing **514**, which contains a fluid irrigation lumen **502** and an aspiration lumen **504**, and which allows independent manipulation of a catheter **516** without requiring repositioning of the hand piece **512** during a procedure performed with the aspiration system **510**. Extension tubing **514** may also act as a pressure accumulator. High pressure fluid flow from the pump **526**, which may comprise a displacement pump, pulses with each stroke of the pump **526** creating a sinusoidal pressure map with distinct variations between the peaks and valleys of each sine wave. Extension tubing **514** may be matched to the pump **526** to expand and contract in unison with each pump pulse to reduce the variation in pressure caused by the pump pulses to produce a smooth or smoother fluid flow at tip of catheter **516**. Any tubing having suitable compliance characteristics may be used. The extension tubing **514** may be permanently attached to the pump **526** or it may be attached to the pump **526** by a connector **544**. The connector **544** is preferably configured to ensure that the extension tubing **514** cannot be attached to the pump **526** incorrectly.

An interface connector **518** joins the extension tubing **514** and the catheter **516** together. In one contemplated embodiment, the interface connector **518** may contain a filter assembly **508** between high pressure fluid injection lumen **502** of the extension tubing **514** and a high pressure injection lumen **536** of the catheter **516** (FIG. **49**). The catheter **516** and the extension tubing **514** may be permanently joined by the interface connector **518**. Alternatively, the interface connector **518** may contain a standardized connection so that a selected catheter **516** may be attached to the extension

tubing **514**. In some embodiments, the filter assembly **508** may be removably coupled to the extension tubing **514** by a quick disconnect connection.

Attached to the hand piece **512** are a fluid source **520** and a vacuum source **522**. A standard hospital saline bag may be used as fluid source **520**; such bags are readily available to the physician and provide the necessary volume to perform the procedure. Vacuum bottles may provide the vacuum source **522** or the vacuum source **522** may be provided by a syringe, a vacuum pump or other suitable vacuum source. The filter assembly **508** serves to filter particulate from the fluid source **520** to avoid clogging of the high pressure injection lumen **536** and an orifice **542** (FIG. **49**). As described herein, distal sections of the high pressure injection lumen **536** may be configured with small inner diameters, and to the filter assembly **508** serves to protect their continuing function. By incorporating one of a variety of catheters **516** into the assisted aspiration system **510**, for example with varying lumen configurations (inner diameter, length, etc.), a variety of aspiration qualities (aspiration rate, jet velocity, jet pressure) may be applied in one or more patients. These aspiration qualities can be further achieved by adjustment of the pump **526**, to modify pump characteristics (flow rate, pump pressure). In some embodiments, the catheter **516** may be used manually, for example, without the pump **526**, and controlled by hand injection. The manual use of the catheter **516** may be appropriate for certain patient conditions, and may serve to reduce the cost of the procedure.

In one contemplated embodiment, the catheter **516** has a variable stiffness ranging from stiffer at the proximal end to more flexible at the distal end. The variation in the stiffness of the catheter **516** may be achieved with a single tube with no radial bonds between two adjacent tubing pieces. For example, the shaft of the catheter **516** may be made from a single length of metal tube that has a spiral cut down the length of the tube to provide shaft flexibility. Variable stiffness may be created by varying the pitch of the spiral cut through different lengths of the metal tube. For example, the pitch of the spiral cut may be greater (where the turns of the spiral cut are closer together) at the distal end of the device to provide greater flexibility. Conversely, the pitch of the spiral cut at the proximal end may be lower (where the turns of the spiral cut are further apart) to provide increased stiffness. A single jacket covers the length of the metal tube to provide for a vacuum tight catheter shaft. Other features of catheter **516** are described with reference to FIG. **49**, below.

FIG. **48** is a diagrammatic view showing more detail of the hand piece **512** and the proximal portion of assisted catheter aspiration system **510**. The hand piece **512** includes a control box **524** where the power and control systems are disposed. The pump **526** may be a motor driven displacement pump that has a constant output. This pump displacement to catheter volume, along with the location of the orifice **542** (exit) of the catheter high pressure lumen **536** within the aspiration lumen **538** (FIG. **49**), ensures that no energy is transferred to the patient from the saline pump as all pressurized fluid is evacuated by the aspiration lumen. A prime button **528** is mechanically connected to a prime valve **530**. When preparing the device for use, it is advantageous to evacuate all air from the pressurized fluid system to reduce the possibility of air embolization. By depressing the prime button **528**, the user connects the fluid source **520** to the vacuum source **522** via the pump **526**. This forcefully pulls fluid (for example 0.9% NaCl solution, or “saline”, no “normal saline”, or heparinized saline) through the entire

pump system, removing all air and positively priming the system for safe operation. A pressure/vacuum valve **532** is used to turn the vacuum on and off synchronously with the fluid pressure system. One contemplated valve **532** is a ported one way valve. Such a valve is advantageous with respect to manual or electronic valve systems because it acts as a tamper proof safety feature by mechanically and automatically combining the operations of the two primary systems. By having pressure/vacuum valve **532**, the possibility of turning the vacuum on without activating the fluid system is eliminated.

The operator control interface **506** is powered by a power system **548** (such as a battery or an electrical line), and may comprise an electronic control board **550**, which may be operated by a user by use of one or more switches **552** and one or more indicator lamps **554**. The control board **550** also monitors and controls several device safety functions, which include over pressure and air bubble detection and vacuum charge. A pressure sensor **564** monitors pressure, and senses the presence of air bubbles. Alternatively, an optical device **566** may be used to sense air bubbles. In one contemplated embodiment, the pump pressure is proportional to the electric current needed to produce that pressure. Consequently, if the electric current required by pump **526** exceeds a preset limit, the control board will disable the pump by cutting power to it. Air bubble detection may also be monitored by monitoring the electrical current required to drive the pump at any particular moment. In order for a displacement pump **526** to reach high fluid pressures, there should be little or no air (which is highly compressible) present in the pump or connecting system (including the catheter **516** and the extension tubing **514**). The fluid volume is small enough that any air in the system will result in no pressure being generated at the pump head. The control board monitors the pump current for any abrupt downward change that may indicate that air has entered the system. If the rate of drop is faster than a preset limit, the control board will disable the pump by cutting power to it until the problem is corrected. Likewise, a block in the high pressure lumen **536**, which may be due to the entry of organized or fibrous thrombus, or a solid embolus, may be detected by monitoring the electrical current running the pump **526**. In normal use, the current fluxuations of the pump **526** are relatively high. For example, the pump may be configured so that there is a variation of 200 milliAmps or greater in the current during normal operation, so that when current fluxuations drop below 200 milliAmps, air is identified, and the system shuts down. Alternatively, current fluxuations in the range of, for example, 50 milliAmps to 75 milliAmps may be used to identify that air is in the system. Additionally, an increase in the current or current fluxuations may indicate the presence of clot or thrombus within the high pressure lumen **536**. For example, a current of greater than 600 milliAmps may indicate that thrombus is partially or completely blocking the high pressure lumen **536**, or even the aspiration lumen **538**.

A vacuum line **556**, connected to the vacuum source **522**, may be connected to a negative pressure sensor **558**. If the vacuum of the vacuum source **522** is low or if a leak is detected in the vacuum line **556**, the control board **550** disables the pump **526** until the problem is corrected. The negative pressure sensor **558** may also be part of a safety circuit **560** that will not allow the pump **526** to run if a vacuum is not present. Thereby a comprehensive safety system **562**, including the safety circuit **560**, the pressure sensor **564** and/or the optical device **566**, and the negative pressure sensor **558**, requires both pump pressure and vacuum pressure for the system to run. If a problem exists

(for example, if there is either a unacceptably low pump pressure or an absence of significant vacuum), the control board **550** will not allow the user to operate the aspiration system **510** until all problems are corrected. This will keep air from being injected into a patient, and will assure that the aspiration system **510** is not operated at incorrect parameters.

FIG. **49** is a diagrammatic view of the distal end portion **568** of the assisted catheter aspiration system **510**, showing more details of the catheter **516**. The catheter **516** is a single-operator exchange catheter and includes a short guidewire lumen **534** attached to the distal end of the device. The guidewire lumen **534** can be between about 1 and about 30 cm in length, or between about 5 and about 25 cm in length, or between about 5 and about 20 cm in length, or approximately 13.5 cm in length. An aspiration lumen **538** includes a distal opening **540** which allows a vacuum (for example, from vacuum source **522**) to draw thrombotic material into the aspiration lumen **538**. A high pressure lumen **536** includes a distal orifice **542** that is set proximally of distal opening **540** by a set amount. For example, distal orifice **42** can be set proximally of distal opening **540** by about 0.0508 cm (0.020 inches), or by $0.0508 \text{ cm} \pm 0.00762 \text{ cm}$ (0.020 inches \pm 0.003 inches) or by another desired amount. The orifice **542** is configured to spray across the aspiration lumen to macerate and/or dilute the thrombotic material for transport to vacuum source **522**, for example, by lowering the effective viscosity of the thrombotic material. The axial placement of the fluid orifice **542** is such that the spray pattern interaction with the opposing lumen wall preferably produces a spray mist and not a swirl pattern that could force embolic material out from the distal opening **540**. The system may be configured so that the irrigation fluid leaves the pump at a pressure of between about 3,447,378 pascal (500 psi) and about 10,342,135 pascal (1500 psi). In some embodiments, after a pressure head loss along the high pressure lumen **536**, the irrigation fluid leaves orifice **542** at between about 4,136,854 pascal (600 psi) and about 8,273,708 pascal (1200 psi), or between about 4,481,592 pascal (650 psi) and about 5,860,543 pascal (850 psi). In some cases, it may be possible (and even desired) to use the assisted catheter aspiration system **510** without operating the pump **526**, and thus use the catheter **516** while providing, for example, a hand saline injection via a syringe.

When normal blood flow is achieved after unblocking occlusions or blockages from atherosclerotic lesions and/or thrombosis, there is sometimes a risk of reperfusion injury. This may be particularly significant following thrombectomy of vessels feeding the brain for treatment of thromboembolic stroke, or following thrombectomy of coronary vessels feeding the myocardium. In the case of the revascularization of myocardium following a coronary intervention (e.g. thrombectomy). Reperfusion injury and microvascular dysfunction may be mechanisms that limit significant or full recovery of revascularized myocardium. The sudden reperfusion of a section of myocardium that had previously been underperfused may trigger a range of physiological processes that stun or damage the myocardium. Distal coronary emboli, such as small portions of thrombus, platelets and atheroma, may also play a part. Controlled preconditioning of the myocardium at risk has been proposed to limit the effect of reperfusion injury and microvascular dysfunction. The embodiments of the thrombectomy systems **100**, **300** presented herein may be combined with additional features aimed at allowing flow control, in order to limit the potential dangers due to reperfusion following thrombectomy.

FIGS. 50A and 50B illustrate a thrombectomy system 600 comprising a catheter 606 and a guiding catheter 608. The catheter 606 may be an aspiration or thrombectomy catheter as previously described, and may or may not comprise a proximal sealing member. Alternatively, the catheter 606 may be used for partial or complete occlusion of the blood vessel distal of the guiding catheter 608. One purpose for this use is for flow control, as described above, wherein the distal tube 614 or another portion of the catheter 606 may be expanded to partially or completely occlude a blood vessel for a period of time. The catheter 606 may be a combination of an aspiration catheter and a catheter for flow control or occlusion. For example, the distal end of the distal tube 614 may provide some flow control in relation to the blood vessel wall, and the proximal end of the distal tube 614 may provide engagement with the guiding catheter. The guiding catheter 608 may, for example, have an outer diameter of 6 French, an inner lumen diameter of approximately 0.183 cm (0.072 inches), and have a total length of approximately 100 cm. The catheter 606 is configured to be placed through the inner lumen of the guiding catheter 608. The guiding catheter 608 may comprise a composite extruded and braided tubular structure, which has sufficient flexibility and pushability to reach a target area. The guiding catheter 608 may also have a pre-shaped tip. For example the tip shape may aid in cannulating coronary arteries. The catheter 606 comprises a distal tube 614 which is configured to be extendable out of the inner lumen of the guiding catheter 608, such that a distal end 616 of the distal tube 614 can be advanced a desired length into the blood vessel so that it can be placed adjacent the target area. The proximal end 618 of the distal tube 614 is configured to remain within the inner lumen of the guiding catheter 608, for example, at a region near the distal end of the guiding catheter 608. In some embodiments, the catheter 606 includes a radiopaque marker, which may comprise a band secured to the thrombectomy catheter, and made from radiodense material, such as platinum, gold, or other similar materials. In some embodiments, the distal tube 614 may be formed of polymeric materials containing radiopaque material, such as titanium dioxide (TiO₂).

The distal tube 614 comprises a tubular braided member whose diameter increases as the distal tube is made shorter (the distal end 616 and proximal end 618 are brought toward one another) and whose diameter decreases as the distal tube is made longer (the distal end 616 and proximal end 618 are moved away from one another). A tubular member of this type is sometimes referred to as a "Chinese finger trap." A stretchable material (such as silicone or urethane) may be used in some embodiments to fill in the spaces between the woven filaments in order to make a water-tight wall. As in certain other embodiments presented herein, a support member 626 is attached to the proximal end 618 of the distal tube 614 and is used to track the catheter 606 through the guiding catheter 608 and through the vasculature. A push/pull member 605 is attached to the distal end 616 of the distal tube 614 and, like the support member 626, extends proximally, and out of the proximal end of the guiding catheter 608 for access by a user. The support member 626 and the push/pull member 605 each have sufficient tensile strength and sufficient column strength such that each can be pushed and/or pulled accordingly, to cause the distal tube 614 to shorten or lengthen in length, thus changing its diameter. The support member 626 and the push/pull member 605 are each also lockable in relation to each other at their proximal ends, for example, just proximal to the proximal end of the guiding catheter, such that they are no longer able to longitudinally move independent of each other. This locks the distal tube

614 in its particular condition (diameter and length). The catheter 606 may be manipulated by the user so that support member 626 is pulled while the push/pull member 605 is pushed, thus elongating the distal tube 614 while decreasing its diameter (FIG. 50B). In this configuration, the distal tube 614 can be easily inserted through the guiding catheter 608. Once in a desired location within the vasculature, the catheter 606 may be manipulated by the user so that support member 626 is pushed while the push/pull member 605 is pulled, thus shortening the distal tube 614 while increasing its diameter (FIG. 50A). If this is done while the proximal end 618 of the distal tube 614 is within the distal tip of the inner lumen of the guiding catheter 608, an extended lumen may be made, which includes the lumen of the distal tube 614 and the inner lumen of the guiding catheter 608. If the proximal end 618 of the distal tube 614 has a ring of fill or coating material around its outer surface, for example, a stretchable material such as silicone or urethane, a seal may be created between the outer diameter of the distal tube 614 and the inner diameter of the guiding catheter 608. This is appropriate for an aspiration catheter mode. If flow control is desired, the distal tube 614 may be shortened and expanded in the same manner to that it engages the wall of the blood vessel at a desired location. In some embodiments, the push/pull member 605 and/or the support member 626 are constructed from hypo tubing, including but not limited to stainless steel hypo tubing or nitinol hypo tubing.

FIGS. 51A-51C show how the size of the distal tube 614 may be manipulated to reach different specific diameters. Longitudinally-displaced markings 677a, 677b, 677c, 679 or detents on the proximal ends 649, 651 of the support member 626 and/or the push/pull member 605, respectively, may indicate particular corresponding sizes (diameters or lengths) of the distal tube 614. For example, in FIG. 51A, an approximately 5 French diameter configuration of the distal tube 614 may be used for delivering it through the guiding catheter 608. In FIG. 51B, an approximately 6 French diameter configuration of the distal tube 614 may be used when it is tracked through the vasculature, for example, near a lesion site or target site. In FIG. 51C, an approximately 7 French diameter configuration of the distal tube 614 may be used when it is expanded towards or against the wall of a blood vessel. One or more loops 675 are configured to maintain the distance between the support member 626 and the push/pull member 605 in the radial direction (in relation to the distal tube 614). In some embodiments, the one or more loops 675 may be located near the proximal end 618 of the distal tube 614. FIGS. 51A-51C also show how in some embodiments, the push/pull member 605 may be constructed of flat wire. The support member 626 may also be constructed of flat wire.

FIG. 52 shows an additional sleeve 607 which may be placed over the distal tube 614 to further constrain its diameter for delivery through the guiding catheter 608 and/or the vasculature. The sleeve 607 may extend proximally and out the proximal end of the guiding catheter 608 so that it can be pulled off in a proximal direction to allow the distal sleeve 614 to expand. The sleeve 607 may be used in addition to the push/pull member 605, or may be used in lieu of the push/pull member 605 and its utility in relation to the support member 626. In an alternative embodiment seen in FIG. 54, the sleeve 607 may comprise an elongate distal tube 617 which is coupled to a proximal wire or pusher member 619, this allowing a user to handle both the proximal wire 619 of the sleeve 607 and the support member 626 of the catheter 606 while removing the sleeve 607 from the patient. This would aid in holding the distal tube 614 at its

desired location in the vasculature (and/or in the guiding catheter **608**) while removing the sleeve **607**. A portion **621** of the distal tube **614** which may remain distal of the sleeve **607** may comprise a non-expandable section.

FIG. **53** illustrates a thrombectomy catheter which may share certain elements of the embodiments of FIGS. **29-42**. In this particular embodiment, a high pressure saline injection lumen **609** comprises two or more sections. As depicted, the injection lumen **609** includes a proximal portion **685**, a middle portion **683** and a distal portion **681**. The middle portion **683** is configured to telescope within the proximal portion **685** and the distal portion **681** is configured to telescope within the middle portion **683**. Each portion may be constructed from precision tubing or hypo tubing, such as polyimide or nitinol, such that the difference in diameter between the opposing outer diameter and inner diameter of two neighboring tubes is very small, in order to create a capillary seal between the two. For example, in some embodiments the difference in diameters may be about 0.002 cm (0.0008 inches) or less, or in some embodiments about 0.001 cm (0.0004 inches) or less, or in some embodiments about 0.0005 cm (0.0002 inches) or less. This allows a section of injection lumen **609** that has a variable length, while being dynamically sealed, thus minimizing or eliminating any leakage at telescope points **611**, **613**, and allowing all or the vast majority of the injected saline to exit at exit port **615**. In some embodiments, the capillary seal should be liquid tight, or water tight (saline tight), and in some embodiments need not be air tight (gas tight). A progressively smaller inner diameter from the proximal portion **685** to the distal portion **681** helps to maintain a high pressure jet at the exit port **615** (maximum pressure), without requiring too large of a pump head pressure. During delivery (tracking) of the catheter, a stylet may be placed within the injection lumen **609** in order to add stiffness, improve transition flexibility and protect the telescope points **611**, **613** from damage. The stylet may be removed once the catheter is tracked to its desired location, and prior to the injection of saline and the aspiration of thrombus. In some embodiments, the proximal portion **685** may have an outer diameter of between about 0.0508 cm (0.020 inches) and 0.0732 cm (0.030 inches) or about 0.066 cm (0.026 inches). In some embodiments, the middle portion **683** may have an outer diameter of between about 0.0305 cm (0.012 inches) and 0.0559 cm (0.022 inches) or about 0.0406 cm (0.016 inches). In some embodiments, the distal portion **681** may have an outer diameter of between about 0.020 cm (0.008 inches) and 0.0406 cm (0.016 inches) or about 0.0305 cm (0.012 inches). In some embodiments, the proximal portion **685** may have an inner diameter of about 0.559 cm (0.022 inches), the middle portion **683** may have an inner diameter of about 0.0483 cm (0.019 inches), and the distal portion **681** may have an inner diameter of about 0.028 cm (0.011 inches). In the distal portion **681**, an inner diameter of between about 0.0229 cm (0.009 inches) and about 0.0381 cm (0.015 inches) optimizes the delivery volume, while minimizing the outer diameter of the distal portion **681**, thus maintaining the largest possible aspiration lumen cross-sectional area. In some embodiments, the distal tube **614** is a Chinese finger trap (braided tubular member) as previously described, and thus, the telescoping of the injection lumen **609** tubes allows the length change of the distal tube **614** freely. In this embodiment or any of the embodiments herein, the distal tube **614** may comprise a bumper of softer material at the distal end to add atraumatic characteristics. In alternative embodiments which do not require the telescoping of the injection lumen **609**, the multiple layers of

different diameter tubes may still be used in order to create a transition from larger diameter to smaller diameter and from stiffer to more flexible moving from the proximal end to the distal end. The tube sections may in this case be adhesively, epoxy or heat bonded together, or may be friction fit. FIG. **59** illustrates possible dimensions and assembly of an embodiment. The proximal portion **687** may comprise 0.066 cm×0.048 cm (0.026 inches×0.019 inches) stainless steel hypo tubing, for example, 304 series stainless steel. The middle portion **689** may comprise 0.066 cm×0.048 cm (0.016 inches×0.013 inches) nitinol tubing. The distal portion **691** may comprise polymeric tubing having a proximal outer diameter of about 0.028 cm (0.011 inches) tapering down distally to an outer diameter of about 0.028 cm (0.011 inches). A radiopaque marker band **693** may be carried on the distal portion having the 0.028 cm (0.011 inches) outer diameter. In some embodiments the high pressure injection lumen **609** may be secured to the inner wall of the distal tube **614**, so that it will not severely flex or kink, and thus interfere with passage of a guidewire **28**, **134** or cause a pinch or clog in the high pressure injection lumen **609**. The high pressure injection lumen **609** may be secured with adhesive or other equivalent techniques.

FIG. **55** illustrates the proximal end **618** of an embodiment of the distal tube **614** of the catheter **606** having an expanding structure **695** which seals against the inner diameter **643** of the guiding catheter **608**. This may seal via the size of its formed diameter or it may be expandable by the user, for example, by using the combination of the support member **626** and the push/pull member **605** described herein.

FIGS. **56A-56C** illustrate the flow control mode of the catheter **606** for approaching and/or sealing against the blood vessel wall. In some embodiments, the distal tube **614** may include a portion that has a diameter that is less than the blood vessel diameter. In these embodiments, the push/pull member **605** may be pulled and the support member **626** pushed in order to deliver the distal tube **614** against the vessel wall (while the diameter is increased and the length is shortened). In other embodiments, the distal tube **614** may include a portion that has a diameter that is about the same or larger than the blood vessel diameter. In these embodiments, the push/pull member **605** may be pushed and the support member **626** pulled in order to decrease the diameter (while increasing the length) to allow delivery down the guiding catheter **608** and through the vasculature. FIG. **56B** illustrates the distal tube **614** extending from the guiding catheter **608**, and expanded to seal against the wall of the blood vessel **102**. FIG. **56C** illustrates the distal tube **614** in a reduced diameter state configured for placement through the inner lumen **699** of the guiding catheter **608**.

FIG. **57** illustrates an embodiment of the distal tube **614** with the Chinese finger trap in which pulling on the push/pull member **605** causes the distal tube **614** to invert at an inversion point **697**. In some embodiments, the inversion may be done partially and may be used to cause an increase in the diameter of the distal tube **614** (for example, to perform flow control in the blood vessel). In some embodiments, the inversion may be done to remove the distal tube **614** from the vasculature and into the guiding catheter **608** or to remove the distal tube from the guiding catheter **608**. By pushing on the push/pull member **605**, the distal tube **614** may be delivered into a location in the blood vessel.

FIGS. **58A-58B** illustrate how both flow control and the coupling to the guiding catheter **608** may be achieved using two different catheters, labeled in FIG. **58** as first catheter **661** and second catheter **663**. The second catheter **663**

(having support member 665) and the first catheter 661 (having support member 667) may each be delivered together within a larger delivery catheter 669 (having support member 671). After delivery through the guiding catheter 608 and to or near a target site (for example a clot/ thrombus and/or an atherosclerotic lesion), the delivery catheter 669 is removed by pulling it proximally, and the first catheter 661 is positioned in the blood vessel 102 for flow control, and/or adjacent a thrombus 104, and the second catheter 663 is positioned in a coupling manner to the guiding catheter 608.

FIG. 60 an embodiment for a catheter 700 which also makes use of a distal tube using the Chinese finger trap braided tubular member 714. In this embodiment, a wire 702, for example a Nitinol wire, is telescopically located within a proximal 704. In some embodiments, a length of a more flexible material 706, such as polyimide is attached distal of the wire 702 for a transition of flexibility. The proximal end 718 of the distal tube 714 has a seal section 724 for engaging with the guiding catheter 608. The proximal end of the wire 702 extends proximally of the proximal end of the proximal tube 704. By pushing on the proximal tube 704 and pulling on the wire 702 at each of their respective proximal ends, a user may expand the distal tube 714 for flow control (e.g. blocking or slowing down blood flow that is coming from the right side of FIG. 60 to the left side of FIG. 60). A thrombectomy procedure may be performed through the extended lumen comprising the lumen of the distal tube and the inner lumen of the guiding catheter. Any combination of the embodiments disclosed herein may be used to create a combination flow control and thrombectomy embodiment. The thrombectomy portion may include aspiration only, or may combine aspiration and saline injection.

In one embodiment, an aspiration system includes an elongate tubular member for insertion into the vasculature of a patient, the elongate tubular member having a proximal end, a distal end, and a lumen extending from the proximal end to the distal end, the lumen having a first diameter adjacent the distal end, an aspiration catheter having a proximal end and a distal end and configured to be inserted through the lumen of the elongate tubular member, the aspiration catheter including a tubular aspiration member having a proximal end and a distal end and configured to at least partially extend out of the lumen of the elongate tubular member at the distal end of the elongate tubular member and into the vasculature of the patient, an elongate support member coupled to the tubular aspiration member and extending between the proximal end of the aspiration catheter and the proximal end of the tubular aspiration member, a plurality of annular seals linearly arrayed on an outer surface of the tubular aspiration member, each of the plurality of annular seals having an outer diameter which is greater than the first diameter of the lumen of the elongate tubular member, wherein the plurality of annular seals includes a first seal located adjacent the proximal end of the tubular aspiration member and a second seal located a distance d distally of the first seal on the tubular aspiration member, and wherein the distal end of the tubular aspiration member extends a length L from the distal end of the elongate tubular member when the first seal is engaged with the first diameter at the distal end of the elongate tubular member and the distal end of the tubular aspiration member extends a length $L-d$ from the distal end of the elongate tubular member when the second seal is engaged with the first diameter at the distal end of the elongate tubular member, and a vacuum source configured for coupling to the

proximal end of the elongate tubular member such that liquid having a viscosity of about 0.0025 pascal-seconds (2.5 cP) adjacent the distal end of the tubular aspiration member is aspirated into the distal end of the tubular aspiration member and through the elongate tubular member when either the first seal or the second seal is engaged with the first diameter at the distal end of the elongate tubular member.

In another embodiment, an aspiration system includes an elongate tubular member for insertion into the vasculature of a patient, the elongate tubular member having a proximal end, a distal end, and a lumen extending from the proximal end to the distal end, an aspiration catheter having a proximal end and a distal end and configured to be inserted through the lumen of the elongate tubular member, the aspiration catheter having a tubular aspiration member having a proximal end and a distal end and configured to at least partially extend out of the lumen of the elongate tubular member at the distal end of the elongate tubular member and into the vasculature of the patient, an elongate support member coupled to the tubular aspiration member and extending between the proximal end of the aspiration catheter and the proximal end of the tubular aspiration member, an annular sealing member having a first end, a second end and a wall, the first end coupled to the tubular aspiration member and having a first diameter and the second end having a second diameter greater than the first diameter, the second end located distally from the first end, a vacuum source configured for coupling to the proximal end of the elongate tubular member, and wherein the distal end of the annular sealing member creates a seal against the lumen of the elongate tubular member, substantially preventing liquid having a viscosity of about 0.0025 pascal-seconds (2.5 cP) from passing through space between the elongate tubular member and the tubular aspiration member in a distal to proximal direction when the vacuum source is applied to the proximal end of the elongate tubular member.

In another embodiment, an aspiration system includes an elongate tubular member for insertion into the vasculature of a patient, the elongate tubular member having a proximal end, a distal end, and a lumen extending from the proximal end to the distal end, the lumen having a first diameter adjacent the distal end, an aspiration catheter having a proximal end and a distal end and configured to be inserted through the lumen of the elongate tubular member, the aspiration catheter including a tubular aspiration member having a proximal end and a distal end and configured to at least partially extend out of the lumen of the elongate tubular member at the distal end of the elongate tubular member and into the vasculature of the patient, an elongate support member coupled to the tubular aspiration member and extending between the proximal end of the aspiration catheter and the proximal end of the tubular aspiration member, a hydrogel seal disposed on at least a cylindrical outer surface portion of the tubular aspiration member and having a non-hydrated diameter and an unconstrained hydrated diameter, the non-hydrated diameter less than the first diameter of the elongate tubular member and the unconstrained hydrated diameter greater than the first diameter of the elongate tubular member, such that the hydrogel seal is configured to seal against the first diameter of the elongate tubular member when it is hydrated, and a vacuum source configured for coupling to the proximal end of the elongate tubular member such that liquid having a viscosity of about 0.0025 pascal-seconds (2.5 cP) adjacent the distal end of the tubular aspiration member is aspirated into the distal end of the tubular aspiration member and through the elongate

tubular member when the hydrogel seal is engaged with the first diameter at the distal end of the elongate tubular member.

In another embodiment, an aspiration system includes an elongate tubular member for insertion into the vasculature of a patient, the elongate tubular member having a proximal end, a distal end, and a lumen extending from the proximal end to the distal end, an aspiration catheter having a proximal end and a distal end and configured to be inserted through the lumen of the elongate tubular member, the aspiration catheter including a tubular aspiration member having a proximal end and a distal end and configured to at least partially extend out of the lumen of the elongate tubular member at the distal end of the elongate tubular member and into the vasculature of the patient, and a vacuum source configured for coupling to the proximal end of the elongate tubular member such that when the distal end of the tubular aspiration member is extended out of the distal end of the elongate tubular member at least 5 cm, liquid having a viscosity of about 0.0025 pascal-seconds (2.5 cP) adjacent the distal end of the tubular aspiration member is aspirated into the distal end of the tubular aspiration member and through the elongate tubular member at the same time that liquid having a viscosity of about 0.0025 pascal-seconds (2.5 cP) adjacent the distal end of the elongate tubular member is aspirated into space between the elongate tubular member and the tubular aspiration member and through the elongate tubular member. In some embodiments, the aspiration system is configured such that the proximal end of the tubular aspiration member is configured to extend proximally from the proximal end of the elongate tubular member when the distal end of the tubular aspiration member extends into the vasculature of the patient. In some embodiments, the aspiration system is configured such that the proximal end of the tubular aspiration member is configured to reside within the elongate tubular member when the distal end of the tubular aspiration member extends into the vasculature of the patient. In some embodiments, the aspiration system further includes an elongate support member coupled to the tubular aspiration member and extending between the proximal end of the aspiration catheter and the proximal end of the tubular aspiration member.

In another embodiment, an aspiration system includes an elongate tubular member for insertion into the vasculature of a patient, the elongate tubular member having a proximal end, a distal end, and a lumen extending from the proximal end to the distal end, the lumen having a first diameter adjacent the distal end, an aspiration catheter having a proximal end and a distal end and configured to be inserted through the lumen of the elongate tubular member, the aspiration catheter including a tubular aspiration member having a proximal end, a distal end, an inner diameter and an outer diameter and configured to at least partially extend out of the lumen of the elongate tubular member at the distal end of the elongate tubular member and into the vasculature of the patient, an elongate support member coupled to the tubular aspiration member and extending between the proximal end of the aspiration catheter and the proximal end of the tubular aspiration member, the elongate support member having a distal end including a partial cylinder having an outer radius and an inner radius, one of the outer radius and inner radius configured to substantially match one of the outer diameter and inner diameter of the tubular aspiration member for joining thereto, a seal disposed on the tubular aspiration member configured to seal against the first diameter of the elongate tubular member, and a vacuum source configured for coupling to the proximal end of the elongate

tubular member such that liquid having a viscosity of about 0.0025 pascal-seconds (2.5 cP) adjacent the distal end of the tubular aspiration member is aspirated into the distal end of the tubular aspiration member and through the elongate tubular member when the seal is engaged with the first diameter at the distal end of the elongate tubular member.

In another embodiment, a forced aspiration system includes an elongate tubular member for insertion into the vasculature of a patient, the elongate tubular member having a proximal end, a distal end, and a lumen extending from the proximal end to the distal end, the lumen having a first diameter adjacent the distal end, a forced aspiration catheter having a proximal end and a distal end and configured to be inserted through the lumen of the elongate tubular member, the forced aspiration catheter including, a tubular aspiration member having a proximal end, a distal end, an inner lumen, and an outer diameter and configured to at least partially extend out of the lumen of the elongate tubular member at the distal end of the elongate tubular member and into the vasculature of the patient, an elongate tubular support member coupled to the tubular aspiration member and having a lumen extending between the proximal end of the aspiration catheter and the proximal end of the tubular aspiration member, at least one orifice located adjacent the distal end of the tubular aspiration member, the at least one orifice configured to allow high pressure liquid injected through the lumen of the elongate tubular support member to be released into the inner lumen of the tubular aspiration member, and a seal disposed on the tubular aspiration member configured to seal against the first diameter of the elongate tubular member, a vacuum source configured for coupling to the proximal end of the elongate tubular member, and a pressurized liquid source configured for coupling to the proximal end of the lumen of the elongate tubular support member. In some embodiments, the forced aspiration system is configured such that the seal sealingly engages with the first diameter of the elongate tubular member when an internal pressure of the elongate tubular member immediately proximal to and adjacent the seal is increased upon coupling the elongate tubular support member to the pressurized liquid source.

In another embodiment, a method for aspirating material from a patient includes providing an elongate tubular member having a proximal end, a distal end, and a lumen extending from the proximal end to the distal end, the lumen having a first diameter adjacent the distal end, providing an aspiration catheter having a proximal end and a distal end and configured to be inserted through the lumen of the elongate tubular member, the aspiration catheter including a tubular aspiration member having a proximal end and a distal end and configured to at least partially extend out of the lumen of the elongate tubular member at the distal end of the elongate tubular member and into the vasculature of the patient, an elongate support member coupled to the tubular aspiration member and extending between the proximal end of the aspiration catheter and the proximal end of the tubular aspiration member, and an annular sealing member coupled to the tubular aspiration member and having a first diameter configured to seal against the first diameter of the elongate tubular member, placing the elongate tubular member into the vasculature of the patient, placing the aspiration catheter through the elongate tubular member so that the distal end of the tubular aspiration member extends from the distal end of the elongate tubular member and is adjacent a target area and the annular sealing member is aligned with the first diameter of the elongate tubular member, and coupling a vacuum source to the proximal end

41

of the elongate tubular member so that material adjacent the target area is aspirated through the tubular aspiration member and the elongate tubular member.

In another embodiment, a method for treating patients includes providing a first elongate tubular member having a proximal end, a distal end, and a lumen extending from the proximal end to the distal end, the lumen having a first diameter adjacent the distal end, providing a first aspiration catheter having a proximal end and a distal end and configured to be inserted through the lumen of the first elongate tubular member, the first aspiration catheter including a first tubular aspiration member having a proximal end, a distal end, and a first length, the first tubular aspiration member configured to at least partially extend out of the lumen of the first elongate tubular member at the distal end of the first elongate tubular member and into the vasculature of a first patient, a first elongate support member coupled to the first tubular aspiration member and extending between the proximal end of the first aspiration catheter and the proximal end of the first tubular aspiration member, the first elongate support member having a first support member length, and a first annular sealing member coupled to the first tubular aspiration member and having a first diameter configured to seal against the first diameter of the elongate tubular member, placing the first elongate tubular member into the vasculature of the first patient, placing the first aspiration catheter through the first elongate tubular member so that the distal end of the first tubular aspiration member extends from the distal end of the first elongate tubular member and is adjacent a first target area and the first annular sealing member is aligned with the first diameter of the first elongate tubular member, coupling a first vacuum source to the proximal end of the first elongate tubular member so that material adjacent the first target area is aspirated through the first tubular aspiration member and the first elongate tubular member, providing a second elongate tubular member having a proximal end, a distal end, and a lumen extending from the proximal end to the distal end, the lumen having a second diameter adjacent the distal end, the second diameter substantially the same as the first diameter of the first elongate tubular member, providing a second aspiration catheter having a proximal end and a distal end and configured to be inserted through the lumen of the second elongate tubular member, the second aspiration catheter including a second tubular aspiration member having a proximal end, a distal end, and a second length, substantially the same as the first length of the first tubular aspiration member, the second tubular aspiration member configured to at least partially extend out of the lumen of the second elongate tubular member at the distal end of the second elongate tubular member and into the vasculature of a second patient, a second elongate support member coupled to the second tubular aspiration member and extending between the proximal end of the second aspiration catheter and the proximal end of the second tubular aspiration member, the second elongate support member having a second support member length, substantially the same as the first support member length, a second annular sealing member coupled to the second tubular aspiration member and having a second diameter configured to seal against the second diameter of the second elongate tubular member, placing the second elongate tubular member into the vasculature of the second patient, placing the second aspiration catheter through the second elongate tubular member so that the distal end of the second tubular aspiration member extends from the distal end of the second elongate tubular member and is adjacent a second target area and the second annular sealing member

42

is aligned with the second diameter of the second elongate tubular member, and coupling a second vacuum source to the proximal end of the second elongate tubular member so that material adjacent the second target area is aspirated through the second tubular aspiration member and the second elongate tubular member.

Although several embodiments have been presented for breaking up or removing thrombus, general aspiration (with or without high pressure saline injection) of normal blood, or other liquids or deposits within the blood vessels, ducts or other tubular or non-tubular cavities of the body is contemplated as being within the scope of the embodiments of the present invention.

While embodiments have been shown and described, various modifications may be made without departing from the scope of the inventive concepts disclosed herein.

What is claimed is:

1. An aspiration catheter comprising:

a proximal end;

a distal end configured to be inserted through a lumen of a guiding catheter and into the vasculature of a patient; a tubular aspiration member having a proximal end, a distal end, and a lumen;

an elongate support member coupled to the tubular aspiration member and extending between the proximal end of the aspiration catheter and the proximal end of the tubular aspiration member, the elongate support member having a relatively small transverse dimension in relation to the tubular aspiration member; and

at least one annular sealing member coupled to the tubular aspiration member and configured to form an annular seal against an inner surface of the guiding catheter.

2. The aspiration catheter of claim 1, further comprising: a high pressure injection lumen having a proximal end and a distal end and extending from the proximal end of the aspiration catheter to a location adjacent the distal end of the tubular aspiration member; and

at least one orifice at or near the distal end of the high pressure injection lumen configured to allow high pressure liquid injected through the high pressure injection lumen to be released into the lumen of the tubular aspiration member.

3. The aspiration catheter of claim 1, wherein the at least one annular sealing member has a first end, a second end, and a wall, the first end coupled to the tubular aspiration member and having a first outer diameter and the second end having a second outer diameter, greater than the first outer diameter, the second end located distally from the first end.

4. The aspiration catheter of claim 3, further comprising an annular concavity at the second end of the at least one annular sealing member.

5. The aspiration catheter of claim 1, wherein the at least one annular sealing member comprises a plurality of annular sealing members arrayed along a proximal portion of the tubular aspiration member.

6. The aspiration catheter of claim 1, wherein the at least one annular sealing member comprises a hydrogel sealing member disposed on at least a cylindrical outer surface of a proximal portion of the tubular aspiration member, the hydrogel sealing member having a non-hydrated state having a non-hydrated diameter and a hydrated state having an unconstrained hydrated diameter, the non-hydrated diameter less than the unconstrained hydrated diameter.

43

7. The aspiration catheter of claim 1, wherein the at least one annular sealing member comprises a hydrogel disposed on a cylindrical outer surface of the tubular aspiration member.

8. The aspiration catheter of claim 1, wherein the proximal end of the aspiration catheter is configured to extend proximally from the guiding catheter when the distal end of the aspiration catheter is inserted through a lumen of the guiding catheter and into the vasculature of the patient.

9. The aspiration catheter of claim 1, wherein the tubular aspiration member has an outer diameter and an inner diameter, and wherein the elongate support member includes a distal end comprising a partial cylindrical section having an outer radius and an inner radius, at least one of the outer radius and inner radius configured to substantially match either the outer diameter of the tubular aspiration member or the inner diameter of the tubular aspiration member.

10. The aspiration catheter of claim 1, wherein the at least one annular sealing member is not an inflatable balloon.

11. The aspiration catheter of claim 1, wherein the at least one annular sealing member is not expandable by a user.

12. The aspiration catheter of claim 1, wherein the at least one annular sealing member comprises an elastomeric ring.

44

13. The aspiration catheter of claim 12, wherein the elastomeric ring has an O-shaped cross-section.

14. The aspiration catheter of claim 12, wherein the elastomeric ring has an X-shaped cross-section.

15. The aspiration catheter of claim 12, wherein the elastomeric ring has a cross-section comprising a base portion having a first width and a blade portion having a second width, wherein the second width is smaller than the first width, and wherein the second width is configured to interface with the inner surface of the guiding catheter.

16. The aspiration catheter of claim 12, wherein the elastomeric ring has a non-circular cross-section.

17. The aspiration catheter of claim 12, wherein the elastomeric ring comprises an elastomeric material selected from the group consisting of silicone, EPDM, polyurethane, and a thermoplastic elastomer.

18. The aspiration catheter of claim 1, wherein the elongate support member comprises a hypo tube.

19. The aspiration catheter of claim 1, wherein the elongate support member comprises stainless steel.

20. The aspiration catheter of claim 1, wherein the at least one annular sealing member surrounds a proximal portion of the tubular aspiration member.

* * * * *