

US010198036B2

(12) **United States Patent**
Wylie

(10) **Patent No.:** **US 10,198,036 B2**
(45) **Date of Patent:** ***Feb. 5, 2019**

(54) **DOCKING STATION FOR TABLET DEVICE**

(71) Applicant: **Mobile Tech, Inc.**, Lake Oswego, OR (US)

(72) Inventor: **Hunter Wylie**, Sherwood, OR (US)

(73) Assignee: **MOBILE TECH, INC.**, Lake Oswego, OR (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/875,990**

(22) Filed: **Jan. 19, 2018**

(65) **Prior Publication Data**

US 2018/0143665 A1 May 24, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/667,436, filed on Aug. 2, 2017, which is a continuation of application No. 14/097,171, filed on Dec. 4, 2013, now Pat. No. 9,760,116.

(60) Provisional application No. 61/733,842, filed on Dec. 5, 2012.

(51) **Int. Cl.**
G06F 1/16 (2006.01)

(52) **U.S. Cl.**
CPC **G06F 1/1632** (2013.01); **G06F 1/1654** (2013.01)

(58) **Field of Classification Search**
CPC G06F 1/1632
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

883,335 A	3/1908	O'Connor
3,444,547 A	5/1969	Surek
3,612,462 A	10/1971	Mooney et al.
3,780,909 A	12/1973	Callahan et al.
D244,857 S	6/1977	Hayes
4,075,878 A	2/1978	Best
4,117,465 A	9/1978	Timblin
4,335,931 A	6/1982	Kinnear
4,354,613 A	10/1982	Desai et al.
4,384,688 A	5/1983	Smith
4,590,337 A	5/1986	Engelmore
4,714,184 A	12/1987	Young et al.
4,772,878 A	9/1988	Kane

(Continued)

FOREIGN PATENT DOCUMENTS

AT	506665 A1	10/2009
CA	2465692 A1	11/2004

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 29/604,812: Filing Receipt, dated Nov. 27, 2017, 3 pages.

(Continued)



Primary Examiner — Adrian S Wilson

(74) *Attorney, Agent, or Firm* — Thompson Coburn LLP

(57) **ABSTRACT**

A docking station for a tablet device includes a security frame that is releasably connected to a pedestal. An upper head portion of the pedestal is rotatable through three degrees of freedom to allow for angular adjustment of the frame as it retains a tablet device. Electrical conductivity is maintained through the rotational connection.

30 Claims, 7 Drawing Sheets



(56)	References Cited		7,052,296 B2 *	5/2006	Yang	G06F 1/1626 439/165
	U.S. PATENT DOCUMENTS		7,053,774 B2	5/2006	Sedon et al.	
			7,068,496 B2	6/2006	Wong et al.	
4,898,493 A	2/1990	Blankenburg	7,081,822 B2	7/2006	Leyden et al.	
5,033,709 A	7/1991	Yuen	7,085,491 B2	8/2006	Chiang	
5,072,213 A	12/1991	Close	7,101,187 B1	9/2006	Deconinck et al.	
5,146,205 A	9/1992	Keifer et al.	7,135,972 B2	11/2006	Bonato	
5,176,465 A	1/1993	Holsted	7,154,039 B1	12/2006	Marszalek et al.	
5,187,744 A	2/1993	Richter	7,209,038 B1	4/2007	Deconinck et al.	
5,230,016 A	7/1993	Yasuda	D545,826 S	7/2007	Richter	
5,246,183 A	9/1993	Leyden	7,287,652 B2	10/2007	Scholen et al.	
5,436,792 A *	7/1995	Leman	D563,444 S	3/2008	Brickzin	
		F16M 11/041 16/326	D566,590 S *	4/2008	Stevens	D10/74
5,457,745 A	10/1995	Wang	7,352,567 B2	4/2008	Hotelling	
5,459,637 A	10/1995	Ma et al.	7,385,522 B2	6/2008	Belden, Jr. et al.	
5,517,434 A	5/1996	Hanson et al.	7,387,003 B2	6/2008	Marszalek et al.	
5,543,782 A	8/1996	Rothbaum et al.	7,446,659 B2	11/2008	Marsilio et al.	
5,570,267 A	10/1996	Ma	7,515,408 B2	4/2009	Bakker et al.	
5,583,742 A	12/1996	Noda et al.	7,522,047 B2	4/2009	Belden et al.	
5,586,002 A	12/1996	Notarianni	7,611,112 B2	11/2009	Lin	
5,615,258 A	3/1997	Ho	7,626,500 B2	12/2009	Belden, Jr. et al.	
5,685,436 A	11/1997	Davet	7,650,230 B1	1/2010	Laverick et al.	
5,751,548 A *	5/1998	Hall	7,652,873 B2	1/2010	Lee	
		F16C 11/10 248/122.1	7,654,399 B2	2/2010	Scholen et al.	
5,769,369 A *	6/1998	Meinel	7,658,363 B2	2/2010	Meyer	
		B60N 3/001 108/45	7,667,601 B2	2/2010	Rabinowitz et al.	
5,847,924 A	12/1998	Youn	7,669,816 B2	3/2010	Crain et al.	
5,861,807 A	1/1999	Leyden et al.	7,684,185 B2	3/2010	Farrugia	
D409,018 S	5/1999	Deuschle	7,688,205 B2	3/2010	Ott	
5,903,645 A	5/1999	Tsay	7,696,857 B2	4/2010	Kritt et al.	
5,923,528 A	7/1999	Lee	7,708,240 B2 *	5/2010	Homer	G06F 1/1601 248/130
5,982,855 A	11/1999	Ho	7,710,266 B2	5/2010	Belden, Jr. et al.	
6,039,496 A	3/2000	Bishop	7,712,661 B2	5/2010	Thomas	
6,062,518 A *	5/2000	Etue	7,724,135 B2	5/2010	Rapp et al.	
		B60R 11/0241 224/542	7,737,843 B2	6/2010	Belden, Jr. et al.	
D433,953 S	11/2000	Woznicki et al.	7,737,844 B2	6/2010	Scott et al.	
6,170,775 B1	1/2001	Kovacik et al.	7,737,845 B2	6/2010	Fawcett et al.	
6,236,435 B1	5/2001	Gertz	7,737,846 B2	6/2010	Belden, Jr. et al.	
D455,166 S	4/2002	Raad et al.	7,744,404 B1	6/2010	Henson et al.	
6,380,855 B1	4/2002	Ott	7,836,623 B2 *	11/2010	Wang	A47G 1/142 248/458
6,386,906 B1	5/2002	Burke	7,848,833 B2	12/2010	Li et al.	
6,400,560 B1	6/2002	Chian	7,866,623 B2	1/2011	Lampman et al.	
6,476,717 B1	11/2002	Gross et al.	7,883,279 B2	2/2011	Kendall	
6,491,276 B1	12/2002	Belliveau	7,909,641 B1	3/2011	Henson et al.	
6,502,727 B1	1/2003	Decoteau	D635,555 S	4/2011	Giles	
6,504,710 B2	1/2003	Sutton et al.	D636,778 S	4/2011	Corsini et al.	
6,549,130 B1	4/2003	Joao	D640,247 S	6/2011	Baumann et al.	
6,581,421 B2	6/2003	Chmela et al.	7,969,305 B2	6/2011	Belden, Jr. et al.	
6,585,201 B1 *	7/2003	Reed	D641,756 S	7/2011	Hsieh	
		B60R 11/0235 248/181.1	7,971,845 B2	7/2011	Galant	
6,644,611 B1 *	11/2003	Tai	D643,056 S	8/2011	Zalianskas et al.	
		F16C 11/10 248/292.13	8,007,188 B2 *	8/2011	Orf	F16M 11/041 248/177.1
6,659,382 B2	12/2003	Ryczek	8,009,348 B2	8/2011	Zehner et al.	
6,700,488 B1 *	3/2004	Leyden	D645,047 S	9/2011	Wike	
		G08B 13/1463 340/568.1	D649,076 S	11/2011	Alexander et al.	
6,702,604 B1	3/2004	Moscovitch	D650,783 S *	12/2011	Ausfeld	D13/107
6,714,983 B1	3/2004	Koenck	D650,784 S *	12/2011	Feldstein	D14/434
6,731,212 B2	5/2004	Hirose et al.	8,102,262 B2	1/2012	Irmscher et al.	
6,748,707 B1	6/2004	Buchalter et al.	D661,646 S	6/2012	Son	
6,761,579 B2	7/2004	Fort et al.	8,208,245 B2	6/2012	Staats	
6,773,172 B1	8/2004	Johnson et al.	D663,972 S	7/2012	Alexander et al.	
6,781,825 B2	8/2004	Shih et al.	8,230,992 B2 *	7/2012	Law	G06F 1/1626 206/320
6,786,766 B1	9/2004	Chopra	8,251,325 B2	8/2012	Molter	
6,799,994 B2	10/2004	Burke	D668,660 S	10/2012	Norfolk	
6,831,560 B2	12/2004	Gresset	8,282,060 B2	10/2012	Fan	
6,856,506 B2	2/2005	Doherty et al.	8,289,131 B2	10/2012	Cho et al.	
6,885,817 B2	4/2005	Artonne et al.	D670,702 S	11/2012	Zhang	
6,896,543 B2	5/2005	Fort et al.	D674,803 S	1/2013	Westrup	
D508,916 S	8/2005	Lee	D678,287 S *	3/2013	Hsu	D14/434
6,935,883 B2	8/2005	Oddsens, Jr.	D678,293 S	3/2013	Meehan	
6,944,294 B2	9/2005	Tsay	D682,281 S	5/2013	Barnard et al.	
6,946,961 B2	9/2005	Frederiksen et al.	8,467,178 B2	6/2013	Probst et al.	
6,952,343 B2	10/2005	Sato	8,488,832 B2 *	7/2013	Leung	G06F 1/1632 381/387
6,961,401 B1	11/2005	Nally et al.				
7,002,467 B2	2/2006	Deconinck et al.				
7,015,596 B2	3/2006	Pail				
7,032,872 B2	4/2006	Sullivan				

(56)

References Cited

U.S. PATENT DOCUMENTS

D687,440 S	8/2013	Shieh		2004/0201449 A1	10/2004	Denison et al.	
8,499,384 B2	8/2013	Zerhusen		2004/0230725 A1	11/2004	Chen et al.	
8,531,829 B2	9/2013	Oberpriller et al.		2004/0233631 A1	11/2004	Lord	
8,558,688 B2	10/2013	Henson et al.		2004/0257464 A1*	12/2004	Pandit	H04N 5/2251 348/373
8,573,394 B2	11/2013	Ahee et al.		2005/0014536 A1*	1/2005	Grady	G06F 1/1632 455/573
D696,259 S	12/2013	Howarth		2005/0047104 A1	3/2005	Grunow et al.	
8,611,086 B1	12/2013	Magnusson et al.		2005/0073413 A1	4/2005	Sedon et al.	
8,616,508 B1*	12/2013	Coleman	F16M 11/10 248/176.1	2005/0088572 A1	4/2005	Pandit et al.	
8,698,617 B2	4/2014	Henson et al.		2005/0165806 A1	7/2005	Roatis et al.	
8,698,618 B2	4/2014	Henson et al.		2005/0206522 A1	9/2005	Leyden et al.	
8,708,151 B2*	4/2014	Whitten	G06F 1/1656 206/701	2005/0215285 A1*	9/2005	Lin	H04B 1/207 455/557
D704,194 S	5/2014	Young		2005/0255895 A1	11/2005	Lee et al.	
8,749,194 B1	6/2014	Kelsch et al.		2006/0061958 A1	3/2006	Solomon et al.	
8,749,963 B2*	6/2014	Staats	G06F 1/1632 248/121	2006/0066438 A1*	3/2006	Altounian	G06F 21/86 340/5.53
8,780,548 B2	7/2014	Lee		2006/0067036 A1	3/2006	Lin et al.	
8,800,763 B2	8/2014	Hale		2006/0148575 A1	7/2006	Vitito	
8,800,942 B2	8/2014	Yu		2007/0075914 A1	4/2007	Bates	
8,807,849 B2*	8/2014	Apter	F16M 13/00 396/419	2007/0145210 A1	6/2007	Fawcett et al.	
8,814,128 B2	8/2014	Trinh et al.		2007/0152633 A1	7/2007	Lee	
8,847,759 B2	9/2014	Bisesti et al.		2007/0159328 A1	7/2007	Belden et al.	
8,851,565 B2	10/2014	Hontz et al.		2007/0221726 A1	9/2007	Thomas	
D717,804 S	11/2014	Budge		2007/0229529 A1	10/2007	Irmscher et al.	
D718,316 S	11/2014	Veltz		2007/0247793 A1	10/2007	Carnevali	
8,885,337 B2	11/2014	Schanz et al.		2008/0104301 A1	5/2008	Assouad	
D719,144 S	12/2014	Eulette		2008/0168806 A1	7/2008	Belden et al.	
8,913,380 B2	12/2014	Enomoto et al.		2008/0169923 A1	7/2008	Belden et al.	
8,955,807 B2	2/2015	Alexander et al.		2008/0222849 A1	9/2008	Lavoie	
8,963,498 B2	2/2015	Ferguson		2008/0288702 A1	11/2008	Diab	
D725,119 S	3/2015	Gaylord		2009/0007390 A1	1/2009	Tsang et al.	
D726,732 S	4/2015	Lay		2009/0009936 A1*	1/2009	Neu	H04B 1/3877 361/679.01
D732,037 S	6/2015	Wylie et al.		2009/0033492 A1	2/2009	Rapp et al.	
9,019,698 B2	7/2015	Thiers		2009/0034221 A1	2/2009	Kerrigan	
9,092,960 B2	7/2015	Wheeler et al.		2009/0059481 A1*	3/2009	Taylor	H04B 1/3816 361/679.01
9,097,380 B2	8/2015	Wheeler et al.		2009/0079566 A1	3/2009	Goldstein et al.	
9,158,336 B2*	10/2015	Brewer	A45C 11/00	2009/0080684 A1	3/2009	Groset	
9,220,358 B2	12/2015	Wheeler et al.		2009/0114556 A1	5/2009	Tai et al.	
9,229,494 B2	1/2016	Rayner		2009/0166483 A1	7/2009	Marsilio et al.	
D748,634 S	2/2016	Hofer		2009/0173868 A1	7/2009	Fawcett et al.	
9,269,247 B2	2/2016	Fawcett et al.		2009/0179127 A1	7/2009	Petty	
9,303,809 B2	4/2016	Reynolds et al.		2009/0183266 A1	7/2009	Tan et al.	
D757,731 S	5/2016	Nguyen		2009/0186583 A1*	7/2009	Seil	H04B 1/3877 455/66.1
9,373,236 B2	6/2016	Oehl et al.		2009/0225166 A1	9/2009	Dronge	
9,396,631 B2	7/2016	Fawcett et al.		2009/0303692 A1	12/2009	Terlizzi	
D766,247 S	9/2016	Burmester		2009/0328141 A1	12/2009	Zhang	
9,478,110 B2	10/2016	Fawcett et al.		2010/0012809 A1*	1/2010	Zeng	F16M 11/10 248/351
9,576,452 B2	2/2017	Fawcett et al.		2010/0075609 A1*	3/2010	Seil	B60R 11/02 455/66.1
9,641,539 B1	5/2017	Votaw		2010/0078343 A1*	4/2010	Hoellwarth	B29C 45/14639 206/320
9,659,472 B2	5/2017	Fawcett et al.		2010/0081337 A1	4/2010	Dorogusker et al.	
D795,263 S	8/2017	Fujioka		2010/0124040 A1*	5/2010	Diebel	G06F 1/1628 361/816
D798,302 S	9/2017	Burmester		2010/0138581 A1	6/2010	Bird et al.	
9,760,116 B2	9/2017	Wylie		2010/0172081 A1	7/2010	Tian et al.	
9,847,806 B1	12/2017	Dickie		2010/0195279 A1	8/2010	Michael	
2001/0049222 A1	12/2001	Fort et al.		2010/0215355 A1	8/2010	Olien	
2001/0055978 A1	12/2001	Herrod		2010/0326934 A1	12/2010	Goldberg	
2002/0044406 A1	4/2002	Shimoda et al.		2011/0047844 A1	3/2011	Fawcett et al.	
2002/0085343 A1	7/2002	Wu et al.		2011/0068919 A1	3/2011	Rapp et al.	
2002/0162366 A1	11/2002	Chmela et al.		2011/0187531 A1	8/2011	Oehl et al.	
2003/0007634 A1	1/2003	Wang		2011/0195786 A1	8/2011	Wells	
2003/0010859 A1	1/2003	Ryczek		2011/0254661 A1	10/2011	Fawcett et al.	
2003/0128975 A1	7/2003	Shevick		2011/0278885 A1	11/2011	Procter	
2003/0137584 A1	7/2003	Norvell et al.		2011/0283754 A1	11/2011	Ezzo et al.	
2003/0222149 A1	12/2003	Solomon		2011/0303816 A1	12/2011	Horvath et al.	
2003/0222848 A1	12/2003	Solomon et al.		2011/0309934 A1	12/2011	Henson et al.	
2003/0235029 A1*	12/2003	Doherty	G06F 1/1632 361/679.27	2012/0026119 A1	2/2012	Judy	
2004/0003150 A1	1/2004	Deguchi		2012/0033375 A1	2/2012	Madonna et al.	
2004/0017652 A1	1/2004	Billington et al.		2012/0037783 A1	2/2012	Alexander et al.	
2004/0113819 A1	6/2004	Gauthey et al.		2012/0043247 A1	2/2012	Westrup	
2004/0177658 A1*	9/2004	Mitchell	E05B 73/0082 70/58				

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0043451 A1 2/2012 Alexander et al.
 2012/0155004 A1 6/2012 Yukawa et al.
 2012/0175474 A1 7/2012 Barnard et al.
 2012/0182680 A1 7/2012 Wetzel
 2012/0188689 A1* 7/2012 Leung G06F 1/1632
 361/679.01
 2012/0189156 A1 7/2012 Leung
 2012/0193496 A1 8/2012 Li
 2012/0205326 A1 8/2012 Richter et al.
 2012/0217371 A1 8/2012 Abdollahzadeh et al.
 2012/0234055 A1 9/2012 Bland, III et al.
 2012/0280810 A1 11/2012 Wheeler
 2012/0286118 A1 11/2012 Richards
 2012/0293924 A1 11/2012 Dolci et al.
 2012/0303476 A1 11/2012 Krzyzanowski et al.
 2013/0026322 A1 1/2013 Wheeler
 2013/0026332 A1 1/2013 Wheeler et al.
 2013/0043369 A1 2/2013 Wheeler
 2013/0058023 A1 3/2013 Supran
 2013/0107126 A1 5/2013 Nonomura et al.
 2013/0107449 A1 5/2013 Su et al.
 2013/0161054 A1 6/2013 Allison et al.
 2013/0168527 A1 7/2013 Wheeler et al.
 2013/0238516 A1 9/2013 Moock et al.
 2013/0268316 A1 10/2013 Moock et al.
 2013/0346661 A1 12/2013 Hasenei
 2014/0118930 A1* 5/2014 Sedon E05B 73/0082
 361/679.56
 2014/0159898 A1 6/2014 Wheeler et al.
 2014/0168884 A1 6/2014 Wylie
 2014/0058023 A1 9/2014 Khodapanah
 2014/0321048 A1 10/2014 Kupferstein
 2014/0328020 A1 11/2014 Galant
 2014/0355200 A1 12/2014 Thiers
 2014/0380442 A1 12/2014 Addepalli
 2015/0048625 A1 6/2015 Weusten et al.
 2015/0156900 A1 6/2015 Yeh
 2015/0186685 A1 7/2015 Vroom
 2015/0201723 A1* 7/2015 Rayner G06F 1/1601
 224/191
 2015/0212590 A1* 7/2015 Feldstein G06F 1/1656
 345/173
 2016/0042620 A1 2/2016 Dandie et al.
 2016/0135560 A1 5/2016 Yeh
 2016/0239796 A1 8/2016 Grant et al.
 2017/0032636 A1 2/2017 Henson et al.
 2017/0193780 A1 7/2017 Moock et al.
 2018/0017992 A1 1/2018 Wylie
 2018/0032104 A1 2/2018 Schatz et al.
 2018/0143664 A1 5/2018 Wylie

FOREIGN PATENT DOCUMENTS

CA 2802845 A1 5/2011
 CN 103098104 A 5/2011
 DE 20 2009 013722 U1 1/2011
 EP 0745747 A1 12/1996
 EP 1575249 A2 9/2005
 EP 2619737 5/2011
 ES 1058183 U 11/2004
 FR 2595227 A1 9/1987
 FR 2768906 A1 4/1999
 FR 2868459 10/2005
 GB 2440600 A 2/2008
 JP H0573857 U 10/1993
 JP H0668913 A 3/1994
 JP 1997-259368 10/1997
 JP 3100287 B2 10/2000
 JP 2013529141 5/2011
 TW 103115313 A 4/2014
 WO 1997031347 A1 8/1997
 WO 2004/038670 A1 5/2004
 WO 2012039794 3/2012
 WO 2012151130 4/2012

WO 2013015855 4/2012
 WO 2012069816 A1 5/2012
 WO 2012151130 A1 11/2012
 WO 2013068036 A1 5/2013
 WO 2013134484 A1 9/2013
 WO 2014019072 A1 2/2014
 WO 2014107184 A1 7/2014
 WO 2014134718 A1 9/2014
 WO 2015050710 A1 4/2015
 WO 2015051840 A1 4/2015
 WO 2015/184993 A1 12/2015

OTHER PUBLICATIONS

U.S. Appl. No. 29/604,812: Requirement for Restriction/Election, dated Mar. 19, 2018, 7 pages.
 PCT/US17/44230: Initial Publication with ISR, dated Feb. 1, 2018, 46 pages.
 PCT/US17/44230: Written Opinion of the International Search Authority, dated Feb. 1, 2018, 7 pages.
 "35 mm Camera Display"—Walmart Publication 1995, 5 pages.
 Excerpt from Bruce Schneier, *Applied Cryptology: Protocols, Algorithms, and Source Code in C* (1994), 14 pages.
 International Search Report for PCT/US2011/037235 dated Oct. 21, 2011.
 Retailgeek, "Virtual Tour of MTI Retail Innovation Center in 2009," YouTube Video <https://www.youtube.com/watch?v=wUvcDAmhj0>, published on Aug. 2, 2010 (see transcript and sample screenshots, pp. 1-20).
 Propelinteractive, "Installing LP3 Old Version", YouTube Video <https://www.youtube.com/watch?v=FRUaOFWiDRw&t=1s>, published on Jun. 28, 2010 (see sample screenshots, pp. 1-9).
 Propelinteractive, "Freedom Universal 2 Animation_003.wmv", YouTube Video https://www.youtube.com/watch?v=_odGNnQv0BQ&t=1s, published on Feb. 16, 2010 (see sample screenshots, pp. 1-24).
 Propelinteractive, "MTI LP3 Product Mounting", YouTube Video <https://www.youtube.com/watch?v=KX4TEujljCl>, published on Jun. 23, 2010 (see sample screenshots, pp. 1-11).
 Unicam Europe, "Freedom Lp3 4.17.09", SlideShare Presentation <https://www.slideshare.net/Borfu/freedom-lp3-41709>, published on Jul. 28, 2009 (pp. 1-9).
 "Declaration of Mike Cook", *Vanguard Products Group, Inc. v. Merchandising Technologies, Inc.*, Case No. 3:10-cv-392-BR, U.S. District Court for the District of Oregon, Oct. 20, 2010, pp. 1-7.
 MTI 2008 PowerPoint, "Vanguard Program" (Exhibit 1005 of Declaration of Mike Cook), pp. 1-9.
 "Declaration of Thaine Allison in Support of Patent Owner's Reply to Petitioner's Opposition to Patent Owner's Motion to Amend", Inter Partes Review of U.S. Pat. No. 7,909,641, Case IPR2013-00122, Feb. 5, 2014, pp. 1-13.
 "Deposition of Thaine Allison, III", Inter Partes Review of U.S. Pat. No. 7,909,641, Case IPR2013-00122, Feb. 24, 2014, pp. 1-198.
 Reuters, "MTI Begins Shipping Freedom™ Universal 2.0 Merchandising Solution", Oct. 1, 2008, pp. 1-3.
 "MTI Freedom Universal 2.0 Product Manual", Dec. 2008, pp. 1-21.
 Protex International Corp., "Instructions for PowerPro Detangler", 2005, 1 page.
 Protex International Corp., "Instructions for PowerPro Sensor Head Cameras and Camcorders (Power and Security)", 2007, pp. 1-9.
 Protex International Corp., "PowerPro System", 2006, pp. 1-2.
 "Reasons for Substantial New Question of Patentability and Supplemental Examination Certificate", Inter Partes Review of U.S. Pat. No. 7,909,641, Case IPR2013-00122, Jan. 30, 2013, pp. 1-12.
 U.S. Appl. No. 61/607,802, filed Mar. 7, 2012.
 U.S. Appl. No. 61/620,621, filed Apr. 5, 2012.
 U.S. Appl. No. 61/884,098, filed Sep. 29, 2013.
 U.S. Appl. No. 61/774,870, filed Mar. 8, 2013.
 U.S. Appl. No. 14/845,146: prosecution history.
 U.S. Appl. No. 29/415,938: prosecution history.
 U.S. Appl. No. 29/605,793: app as filed.
 U.S. Appl. No. 29/605, 791: app as filed.

(56)

References Cited

OTHER PUBLICATIONS

U.S. Appl. No. 29/605,580: app as filed.
 U.S. Appl. No. 29/605,581: app as filed.
 U.S. Appl. No. 29/605,583: app as filed.
 U.S. Appl. No. 29/605,579: app as filed.
 U.S. Appl. No. 15/488,370: app as filed.
 U.S. Appl. No. 15/488,379: app as filed.
 U.S. Appl. No. 15/488,373: app as filed.
 U.S. Appl. No. 15/488,383: app as filed.
 16206866.2: app as filed.
 U.S. Appl. No. 12/351,837: app as filed.
 U.S. Appl. No. 62/323,466: app as filed.
 U.S. Appl. No. 62/323,511: app as filed.
 PCT/US2017/027798: app as filed.
 PCT/US2017/027801: app as filed.
 U.S. Appl. No. 29/604,812, filed May 19, 2017, 29 pages.
 U.S. Appl. No. 29/604,812: Filing Receipt, dated May 23, 2017, 3 pages.
 U.S. Appl. No. 15/367,028, filed Dec. 1, 2016, 113 pages.
 U.S. Appl. No. 15/367,028: Filing Receipt, dated Dec. 13, 2016, 3 pages.
 U.S. Appl. No. 15/367,028: Notice to File Missing Parts, dated Dec. 13, 2016, 3 pages.
 U.S. Appl. No. 15/367,028: Request for Corrected Filing Receipt, dated Dec. 22, 2016, 7 pages.
 U.S. Appl. No. 15/367,028: Filing Receipt, dated Dec. 28, 2016, 3 pages.
 U.S. Appl. No. 15/367,028: Applicant Response to Pre-Exam Formalities Notice, dated Feb. 13, 2017, 12 pages.
 U.S. Appl. No. 15/367,028: Filing Receipt, dated Feb. 28, 2017, 3 pages.
 U.S. Appl. No. 15/367,028: Notice of Publication, dated Jun. 8, 2017, 1 page.
 U.S. Appl. No. 15/367,028: Non-Final Rejection, dated Oct. 30, 2017, 12 pages.
 U.S. Appl. No. 15/367,028: Application Data Sheet to update/correct info, dated Nov. 21, 2017, 7 pages.
 U.S. Appl. No. 15/367,028: Filing Receipt, dated Nov. 22, 2017, 3 pages.
 U.S. Appl. No. 15/367,028: Amendment/Req. Reconsideration-After Non-Final Reject, dated Jan. 30, 2018, 14 pages.
 U.S. Appl. No. 15/656,520: Application as filed and Preliminary Amendment, dated Jul. 21, 2017, 120 pages.
 U.S. Appl. No. 15/656,520: Filing Receipt, dated Jul. 28, 2017, 3 pages.
 U.S. Appl. No. 15/656,520: Applicant Response to Pre-Exam Formalities, dated Sep. 25, 2017, 9 pages.
 U.S. Appl. No. 15/656,520: Filing Receipt, dated Sep. 26, 2017, 3 pages.
 U.S. Appl. No. 15/656,520: Non-Final Rejection, dated Nov. 27, 2017, 11 pages.
 U.S. Appl. No. 15/656,520: Notice of Publication, dated Jan. 4, 2018, 1 page.
 PCT/US16/64863 / WO2017/096330: Initial Publication without ISR, dated Jun. 8, 2017.
 PCT/US16/64863 / WO2017/096330: International Search Report, dated Oct. 20, 2017, 5 pages.
 U.S. Appl. No. 14/097,171, filed Dec. 4, 2013, 23 pages.
 U.S. Appl. No. 14,097,171: Filing Receipt, dated Dec. 23, 2013, 3 pages.

U.S. Appl. No. 14,097,171: Notice to File Missing Parts, dated Dec. 23, 2013, 2 pages.
 U.S. Appl. No. 14,097,171: Applicant Response to Pre-Exam Formalities Notice, dated Feb. 24, 2014, 9 pages.
 U.S. Appl. No. 14,097,171: Filing Receipt, dated Mar. 11, 2014, 3 pages.
 U.S. Appl. No. 14,097,171: Notice of Publication, dated Jun. 19, 2014, 1 page.
 U.S. Appl. No. 14,097,171: Non-Final Rejection, dated Jan. 2, 2015, 6 pages.
 U.S. Appl. No. 14,097,171: Amendment/Req. Reconsideration-After Non-Final Reject, dated Jul. 1, 2015, 7 pages.
 U.S. Appl. No. 14,097,171: Final Rejection, dated Sep. 17, 2015, 9 pages.
 U.S. Appl. No. 14,097,171: RCE and Amendments, dated Feb. 17, 2016, 11 pages.
 U.S. Appl. No. 14,097,171: Non-Final Rejection, dated Mar. 17, 2016, 10 pages.
 U.S. Appl. No. 14,097,171: Amendment/Req. Reconsideration-After Non-Final Reject, dated Aug. 17, 2016, 7 pages.
 U.S. Appl. No. 14,097,171: Final Rejection, dated Nov. 10, 2016, 14 pages.
 U.S. Appl. No. 14,097,171: RCE and Amendments, dated Apr. 10, 2017, 18 pages.
 U.S. Appl. No. 14,097,171: Notice of Allowance and Fees Due, dated May 2, 2017, 11 pages.
 U.S. Appl. No. 14,097,171: Issue Fee Payment, dated Aug. 2, 2017, 1 page.
 U.S. Appl. No. 14,097,171: Filing Receipt, dated Aug. 2, 2017, 3 pages.
 U.S. Appl. No. 14,097,171: Issue Notification, dated Aug. 23, 2017, 1 page.
 U.S. Appl. No. 15/667,436, filed Aug. 2, 2017, 25 pages.
 U.S. Appl. No. 15/667,436: Notice to File Missing Parts, dated Aug. 10, 2017, 2 pages.
 U.S. Appl. No. 15/667,436: Filing Receipt, dated Aug. 10, 2017, 3 pages.
 U.S. Appl. No. 15/667,436: Applicant Response to Pre-Exam Formalities Notice, dated Oct. 5, 2017, 11 pages.
 U.S. Appl. No. 15/667,436: Notice of Publication, dated Jan. 18, 2018, 1 page.
 U.S. Appl. No. 15/667,436: Non-Final Rejection, dated Feb. 22, 2018, 9 pages.
 U.S. Appl. No. 15/875,957: Application as filed, dated Jan. 19, 2018, 30 pages.
 U.S. Appl. No. 15/875,957: Filing Receipt, dated Feb. 15, 2018, 3 pages.
 U.S. Appl. No. 15/875,957: Office of Petitions Decision, dated Feb. 21, 2018, 2 pages.
 U.S. Appl. No. 15/659,556, filed Jul. 25, 2017, 62 pages.
 U.S. Appl. No. 15/659,556: Filing Receipt, dated Aug. 2, 2017, 3 pages.
 U.S. Appl. No. 15/659,556: Non-Final Rejection, dated Jan. 24, 2018, 22 pages.
 U.S. Appl. No. 15/659,556: Notice of Publication, dated Feb. 1, 2018, 1 page.
 U.S. Appl. No. 15/600,642: Application as filed, dated May 19, 2017, 30 pages.
 U.S. Appl. No. 15/600,642: Filing Receipt, dated May 31, 2017, 3 pages.
 Office Action for U.S. Appl. No. 15/667,436 dated Feb. 22, 2018.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13

DOCKING STATION FOR TABLET DEVICE**CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of and claims priority under 35 USC 120 to U.S. patent application Ser. No. 15/667,436, filed Aug. 2, 2017, entitled "DOCKING STATION FOR TABLET DEVICE," which is a continuation of U.S. patent application Ser. No. 14/097,171, filed Dec. 4, 2013, now U.S. Pat. No. 9,760,116, entitled "DOCKING STATION FOR TABLET DEVICE," which claims priority under 35 USC 119 to U.S. Provisional Application Ser. No. 61/733,842, filed Dec. 5, 2012, and entitled, "DOCKING STATION FOR TABLET DEVICE," the entire content of each of which is incorporated herein by reference; this application is related to U.S. patent application Ser. No. 15/875,957, filed Jan. 19, 2018, entitled "DOCKING STATION FOR TABLET DEVICE."

TECHNICAL FIELD

The design disclosed below relates to a docking station for a tablet device. More particularly, the design relates to a docking station that allows the tablet device to be used as a work station, or alternatively, the tablet device can be undocked and used remotely from the work station position.

BACKGROUND OF THE INVENTION

In general terms, electronic tablet devices (or "tablets") have evolved such that they are now performing many of the functions that were formerly performed by laptop or desktop computers. The processing capability of tablets now allow them to perform standard business functions.

Because of their size and portability, one of the problems associated with the use of tablets in a business setting relates to physical security and/or theft of the device itself. The design disclosed here addresses these problems.

SUMMARY OF THE INVENTION

The following is a summary of the various improvements disclosed in this document.

The disclosed design is a docking station that is primarily intended to be used in connection with tablet devices. Tablet devices are well-known electronic devices. They are sometimes called electronic tablets, tablet computers, or just "tablets."

The docking station disclosed here includes a security frame portion for retaining the tablet. The security frame portion surrounds the tablet and provides a framework for carrying the tablet from place-to-place while retained within the security frame.

The frame portion carries or has a first universal adapter that electrically couples the tablet to the frame portion. The universal adapter is designed so that it may electrically couple to the different kinds of connection ports that relate to different brands of tablets. As a person skilled in the art would know, these connection ports provide a means for transmitting power and data to and from the tablet.

The docking station also includes a pedestal, or pedestal portion, that normally rests on a workstation surface or the like. The pedestal has a connecting head portion that provides a means for releasably connecting the above-described frame portion to the pedestal portion. The head portion carries a second universal adapter for electrically coupling

the head portion to the first universal adapter on the frame portion, previously described, when the frame portion is connected or "docked" to the pedestal portion.

Another feature of the design involves a rotational connection between the head portion of the pedestal and a lower base portion of the pedestal. The rotational connection enables three degrees of angular orientation or adjustment of the head portion relative to the base portion. This, in turn, allows for adjustment of the view angle of the tablet when it is docked.

The base portion is connectable to or provides electrical connection ports for at least one electrical signal, although preferably, it includes ports for numerous kinds of electrical connections that normally involve power and data. A conductor pathway is provided through the base member to the universal adapter carried by the head portion by crossing the rotational connection between the head portion and the base portion. This allows electrical connectivity to be maintained regardless of the angular portion of the frame (and tablet) relative to the pedestal.

Another feature of the design involves locking the frame to the pedestal. While this may be accomplished in different ways, the design disclosed here includes an electronic lock for additional security.

The foregoing summary will become better understood upon review of the attached drawings which are to be taken in conjunction with the written description set forth below.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, like reference numerals and letters refer to like parts throughout the various views, and wherein:

FIG. 1 is a perspective view of a docking station constructed in accordance with the patent claims;

FIG. 2 is a top view of the docking station;

FIG. 3 is a side view of the docking station;

FIG. 4 is a perspective view of a security frame portion of the docking station that holds or retains a tablet;

FIG. 5 is a perspective view of a back-side part of the security frame portion illustrated in FIG. 4;

FIG. 6 is a perspective view of an adapter portion of the security frame illustrated in FIG. 4;

FIG. 7 is a perspective view of the back-side of the security frame portion illustrated in FIG. 4;

FIG. 8 is a perspective view of a pedestal portion of the docking station illustrated in FIG. 1;

FIG. 9 is an enlarged view of the head of the pedestal portion illustrated in FIG. 8;

FIG. 10 is a view like FIG. 9, but is taken from the back-side perspective of the pedestal portion;

FIG. 11 is a view of the lower portion of the pedestal portion illustrated in FIG. 8, with a cover removed to reveal an electronics board;

FIG. 12 is a perspective view of the docking station, showing angular rotation of the tablet device; and

FIG. 13 is a top view of FIG. 12 and shows different rotational positions of the tablet device.

DETAILED DESCRIPTION

Referring now to the drawings, and first to FIG. 1, indicated generally at 10 is a docking station in accordance with the present disclosure. The docking station 10 includes a security frame portion, indicated generally at 12, and a pedestal portion, indicated generally at 14.

The pedestal portion **14** surrounds and captures a tablet device **16**. The outline of the tablet's screen is indicated by dashed line **18** in FIG. **1**. The activating button on the tablet is indicated at **20**.

Although the frame **12** is illustrated here as surrounding and capturing the tablet **16**, it is to be understood that there could be other physical embodiments that perform the same function without completely surrounding the entire or full periphery of the tablet **16**.

Referring now to FIGS. **4-7**, further details of the frame portion **12** will now be described. FIG. **4** illustrates the frame portion **12** without the tablet inside (looking at the front). As can be seen from the Fig., it has a rectangular peripheral edge **22** that captures the edge of the tablet **16**. Depending on the configuration, the edge structure **22** may be provided with built-in openings for different kinds of tablet access ports (for the purpose of pushing buttons on the tablet or accessing jacks, etc.).

The frame **12** carries a first electrical adapter, indicated generally at **24** in FIGS. **4** and **6**, that provides the needed electrical connection to the tablet **16**. The adapter **24** is "universal" in that it has a universal connector fitting **26** that would be shaped to fit a variety of different kinds of tablets (tablet variations are dictated by brand). Typically, and as a person skilled in the art would understand, the universal adapter **24** provides power and data connections for the tablet—i.e., power for the device's battery, etc., and data for network or Internet connections, if hard-wired connections are desired. The conductors for the universal adapter **24** run through a stem portion **28** (see FIG. **6** of the universal adapter **24**).

FIG. **5** illustrates the back-side or back plate **30** of the frame portion **12**. It is surrounded by the edge **22** previously described. As is shown in FIG. **5**, it has an opening **30** for capturing the universal adapter **24** previously described. When all of these components are assembled together, it produces the frame portion of the docking station indicated in FIG. **4** (the front side) and FIG. **7** (the back side).

Referring now to FIG. **8**, reference numeral **14** generally indicates the pedestal portion of the docking station **10**. The pedestal portion includes an upper head portion, indicated generally at **36**, and a lower base portion, indicated generally at **38**. The head portion **36** carries a second universal adapter **40** that connects into a similar connector fitting in a recess of **42** of the first adapter **24**.

The first adapter **24** releasably rests on protrusions **44**, **46** on head portion **36**. It has a conventional catch **48** that allows adapter **24** (and therefore, frame **12**) to be releasably connected to and from the pedestal portion **14** (via the head **36**).

An advantage to the design is that the portion fitting **40** adjacent the front face **52** of head portion **36** creates a reliable interface connection point for engagement/disengagement of the first universal adapter **24** (and frame portion **12**) with the pedestal portion **14**.

The head portion **36** is designed to rotate at three physical positions. The first position is indicated by arrow **50** in FIG. **9**, which illustrates a circular rotation of the front face **52** of the head portion about an axis that would project normally out from face **52**. When the frame portion **12** is mounted to the pedestal **14**, this arrangement provides one degree of freedom of rotation that would allow the tablet **16** to be rotated between portrait and landscape orientations, if desired. Arrow **54** in FIG. **10** points to another area designed to allow the head **36** to rotate up or down to rotationally lift or lower the screen of the tablet for vertical positioning, as desired.

Finally, arrow **56** points to a last position for angularly rotating the head about a vertical or upright axis for angularly adjusting the tablet screen **16** from left-to-right, as desired.

The physical structure of the above rotational connections can take different forms, using different types of pins or moldings that allow one part to rotate relative to another. In all cases, what is important about the design is that it allows three degrees of rotation without interfering with the wiring in the pedestal portion. FIGS. **12** and **13** illustrate different possible rotational positions.

In this last respect, FIG. **11** illustrates base portion **38** with its cover plate **60** removed, thus exposing an electronics control board (ECB) **58** inside the base portion. A series of electrical connector fittings (USB, etc.) are electrically connected to the ECB **58** for providing data or power. These electrical signals are passed, via wiring, or a wiring harness, up through the body of the pedestal **14**, which is hollow. The position of the wiring is schematically indicated by dashed line **63** in FIG. **8**.

Referring to FIG. **10**, the pedestal **14** has openings **64**, **66** that enable the wiring to pass through the head space, and through the physical zone of rotational connections described above. This allows rotation without stressing the wiring. The wiring connects to a board **67** upon which the second adapter fitting **40** rests. The board **67** provides the wiring connections to the fitting **40**.

Finally, the frame portion **12** could be releasably locked to the pedestal portion via a RFID lock if desired. The ECB **58** in the base portion has surface space for a RFID sensor **70** that could detect a wireless keycard, if desired. The sensor would activate locks on the head portion, upon detection of the keycard.

It is to be appreciated that the foregoing description sets forth the best known examples and embodiments. It is not intended that any of the foregoing description be used to limit the scope of the patent protection. Instead, all patent protection is to be defined solely by the patent claim or claims that follow this description, the interpretation of which is to be made according to the legal rules of patent claim interpretation and the rules and regulations of the U.S. Patent and Trademark Office.

What is claimed is:

1. A docking station for a tablet device, the docking station comprising:
 - a frame assembly for retaining the tablet device, the frame assembly including a frame adapter and a first electrical connection, the frame adapter being electrically connectable to the tablet device via the first electrical connection;
 - a pedestal assembly including a head portion and a base portion, the head portion being connected to the base portion, the head portion including a pedestal adapter and a second electrical connection, the pedestal adapter being electrically connectable to a power source via the second electrical connection, the pedestal adapter being releasably connectable to the frame adapter;
 - the pedestal adapter and the frame adapter being configured such that the pedestal assembly and the frame assembly are electrically connected whenever the pedestal adapter is connected to the frame adapter, the pedestal adapter and the frame adapter being configured such that the pedestal assembly is electrically unconnected to the frame assembly whenever the pedestal adapter is not connected to the frame adapter;
 - the frame assembly being positionable relative to the base portion of the pedestal assembly in a landscape orien-

5

tation and in a rotated orientation, the rotated orientation being different from the landscape orientation, the pedestal assembly and the frame assembly being configured such that the pedestal adapter and the frame adapter are connected to each other when the frame assembly is in the landscape orientation, the pedestal assembly and the frame assembly being configured such that the pedestal adapter and the frame adapter are connected to each other when the frame assembly is in the rotated orientation, the frame assembly being electrically connected to the pedestal assembly when the frame assembly is in the landscape orientation, the frame assembly being electrically connected to the pedestal assembly when the frame assembly is in the rotated orientation.

2. The docking station as set forth in claim 1 wherein the docking station further comprises a lock assembly moveable between a locked condition and an unlocked condition, the lock assembly being configured to lock the frame assembly to the pedestal assembly in the locked condition, the lock assembly being configured to permit detachment of the frame assembly from the pedestal assembly when the lock assembly is in the unlocked condition.

3. The docking station as set forth in claim 1 wherein the frame adapter includes a first electrical interface and the pedestal adapter includes a second electrical interface, the first electrical interface being configured to connect with the second electrical interface in a manner such that the pedestal assembly and the frame assembly are electrically connected when the pedestal adapter is connected to the frame adapter.

4. The docking station as set forth in claim 1 wherein the head portion of the pedestal assembly is configured to pivot about a horizontal axis to adjust a vertical position of the frame assembly when the pedestal adapter is connected to the frame adapter.

5. The docking station as set forth in claim 1 wherein the head portion further comprises a face, a head portion axis being generally normal to the face, the frame assembly being generally normal to the head portion axis when in the landscape orientation, the frame assembly being generally normal to the head portion axis when in the rotated orientation.

6. A docking station for a tablet device, the docking station comprising:

a frame assembly for retaining the tablet device, the frame assembly including a frame adapter, a first electrical connection and a first electrical interface, the first electrical interface being electrically connectable to the tablet device via the first electrical connection;

a pedestal assembly including a head portion and a base portion, the head portion being connected to the base portion, the head portion including a pedestal adapter, a second electrical connection and a second electrical interface, the second electrical interface being electrically connectable to a power source via the second electrical connection, the pedestal adapter being releasably connectable to the frame adapter;

the first electrical interface being electrically connected to the second electrical interface whenever the pedestal adapter is connected to the frame adapter, the first electrical interface being electrically unconnected to the second electrical interface whenever the pedestal adapter is not connected to the frame adapter;

the frame assembly being positionable relative to the base portion of the pedestal assembly in a landscape orientation and in a rotated orientation, the rotated orientation being different from the landscape orientation, the

6

pedestal assembly and the frame assembly being configured such that the pedestal adapter and the frame adapter are connected to each other when the frame assembly is in the landscape orientation, the pedestal assembly and the frame assembly being configured such that the pedestal adapter and the frame adapter are connected to each other when the frame assembly is in the rotated orientation, the frame assembly being electrically connected to the pedestal assembly when the frame assembly is in the landscape orientation, the frame assembly being electrically connected to the pedestal assembly when the frame assembly is in the rotated orientation.

7. The docking station as set forth in claim 6 wherein the docking station further comprises a lock assembly moveable between a locked condition and an unlocked condition, the lock assembly being configured to lock the frame assembly to the pedestal assembly in the locked condition, the lock assembly being configured to permit detachment of the frame assembly from the pedestal assembly when the lock assembly is in the unlocked condition.

8. The docking station as set forth in claim 7 wherein the lock assembly comprises a sensor configured to receive a wireless signal, the lock assembly being configured to move from the locked condition to the unlocked condition upon the sensor receiving the wireless signal.

9. The docking station as set forth in claim 8 wherein the sensor is configured to receive an RFID signal.

10. The docking station as set forth in claim 6 wherein the first electrical interface is a first connector fitting and the second electrical interface is a second connector fitting.

11. The docking station as set forth in claim 10 wherein the first connector fitting is a female connector fitting and the second connector fitting is a male connector fitting.

12. The docking station as set forth in claim 6 wherein the first electrical connection includes a connector fitting, the connector fitting being connectable to the tablet device.

13. The docking station as set forth in claim 12 wherein the frame assembly further includes a stem portion, the connector fitting being electrically connected to the frame adapter via the stem portion.

14. The docking station as set forth in claim 6 wherein the first electrical interface forms a portion of the frame adapter and the second electrical interface forms a portion of the pedestal adapter.

15. The docking station as set forth in claim 6 wherein the head portion further comprises a face, a head portion axis being generally normal to the face, the frame assembly being generally normal to the head portion axis when in the landscape orientation, the frame assembly being generally normal to the head portion axis when in the rotated orientation.

16. A docking station for a tablet device, the docking station comprising:

a frame assembly for retaining the tablet device, the frame assembly including a frame adapter, a first electrical connection and a first electrical interface, the first electrical interface being electrically connectable to the tablet device via the first electrical connection;

a pedestal assembly including a head portion and a base portion, the head portion being connected to the base portion, the head portion including a pedestal adapter, a second electrical connection and a second electrical interface, the second electrical interface being electrically connectable to a power source via the second electrical connection, the pedestal adapter being releasably connectable to the frame adapter;

7

the first electrical interface being electrically connected to the second electrical interface whenever the pedestal adapter is connected to the frame adapter, the first electrical interface being electrically unconnected to the second electrical interface whenever the pedestal adapter is not connected to the frame adapter;

the head portion being configured such that the frame assembly is rotatable relative to the base portion of the pedestal assembly between a landscape orientation and a rotated orientation while the frame adapter is connected to the pedestal adapter, the rotated orientation being different from the landscape orientation, the pedestal assembly and the frame assembly being configured such that the pedestal adapter and the frame adapter are connected to each other when the frame assembly is in the landscape orientation, the pedestal assembly and the frame assembly being configured such that the pedestal adapter and the frame adapter are connected to each other when the frame assembly is in the rotated orientation, the first electrical interface being electrically connected to the second electrical interface when the frame assembly is in the landscape orientation, the first electrical interface being electrically connected to the second electrical interface when the frame assembly is in the rotated orientation.

17. The docking station as set forth in claim 16 wherein the docking station further comprises a lock assembly moveable between a locked condition and an unlocked condition, the lock assembly being configured to lock the frame assembly to the pedestal assembly in the locked condition, the lock assembly being configured to permit the detachment of the frame assembly from the pedestal assembly when the lock assembly is in the unlocked condition.

18. The docking station as set forth in claim 17 wherein the lock assembly comprises a sensor configured to receive a wireless signal, the lock assembly being configured to move from the locked condition to the unlocked condition upon the sensor receiving the wireless signal.

19. The docking station as set forth in claim 16 wherein the frame assembly further includes a front portion and a back portion, the front portion being connectable to the back portion, the frame assembly being configured to sandwich the tablet device between the front portion and the back portion when the front portion is connected to the back portion.

8

20. The docking station as set forth in claim 19 wherein the frame adapter is connected to the back portion.

21. The docking station as set forth in claim 16 wherein the head portion of the pedestal assembly further includes a protrusion, the frame adapter of the frame assembly being configured to engage the protrusion when the frame adapter is connected to the pedestal adapter.

22. The docking station as set forth in claim 16 wherein the base portion of the pedestal assembly includes a hollow portion.

23. The docking station as set forth in claim 22 wherein the second electrical connection includes a cable, the cable extending through the hollow portion.

24. The docking station as set forth in claim 16 wherein the first electrical connection includes a connector fitting, the connector fitting being connectable to the tablet device.

25. The docking station as set forth in claim 24 wherein the frame assembly further includes a stem portion, the connector fitting being electrically connected to the frame adapter via the stem portion.

26. The docking station as set forth in claim 16 wherein the first electrical interface is a first connector fitting and the second electrical interface is a second connector fitting, the second connector fitting being connectable to the first connector fitting.

27. The docking station as set forth in claim 26 wherein the first connector fitting is a female connector fitting and the second connector fitting is a male connector fitting, the male connector fitting being insertable into the female connector fitting.

28. The docking station as set forth in claim 16 wherein the rotated orientation is a portrait orientation.

29. The docking station as set forth in claim 16 wherein the head portion of the pedestal assembly is configured to pivot about a horizontal axis to adjust a vertical position of the frame assembly when the pedestal adapter is connected to the frame adapter.

30. The docking station as set forth in claim 16 wherein the frame assembly further includes a front portion connectable to a back portion, the frame assembly being configured such that the front portion and the back portion collectively surround the tablet device when the front portion is connected to the back portion, the frame adapter being connected to the back portion.

* * * * *