



US010206423B2

(12) **United States Patent**
Davila et al.

(10) **Patent No.:** **US 10,206,423 B2**
(45) **Date of Patent:** ***Feb. 19, 2019**

(54) **DECORATING SYSTEM FOR EDIBLE ITEMS**

(71) Applicant: **Decopac, Inc.**, Anoka, MN (US)

(72) Inventors: **Carlos A. Davila**, Maple Grove, MN (US); **Todd Brobst**, Anoka, MN (US); **Duane Wahlin**, Anoka, MN (US); **Elizabeth Glover**, Anoka, MN (US); **Douglas Boysen**, Anoka, MN (US); **John R. Anderson**, Lino Lakes, MN (US); **Kent D. Whitten**, Anoka, MN (US); **Andy Schnoebelen**, Anoka, MN (US)

(73) Assignee: **Decopac, Inc.**, Anoka, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/616,806**

(22) Filed: **Jun. 7, 2017**

(65) **Prior Publication Data**

US 2017/0265515 A1 Sep. 21, 2017

Related U.S. Application Data

(63) Continuation of application No. 15/164,545, filed on May 25, 2016, now Pat. No. 9,907,332, which is a (Continued)

(51) **Int. Cl.**
A23G 3/28 (2006.01)
A23G 3/34 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A23P 20/10** (2016.08); **A23G 3/0097** (2013.01); **A23G 3/28** (2013.01); **A23P 20/15** (2016.08);
(Continued)

(58) **Field of Classification Search**

CPC ... A23G 3/28; A23G 3/0097; A23P 2020/253; A23P 1/082; A23P 2001/089; H04N 1/00175; H04N 1/0019; G06F 3/1239
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,605,903 A	11/1926	Schuler
2,123,215 A	7/1938	Thomas
(Continued)		

FOREIGN PATENT DOCUMENTS

GB	196885	3/1924
GB	422430	1/1935
(Continued)		

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Jan. 5, 2012 in PCT Application No. PCT/US2011/047096. Reference previously submitted in U.S. Appl. No. 15/164,545.

(Continued)


Primary Examiner — Eric A. Rust

(74) *Attorney, Agent, or Firm* — Gardella Grace P.A.

(57) **ABSTRACT**

In one aspect, the present disclosure relates to decorating and printing of an edible design on a printable base media based on a user selected image. A central control device may provide, to a remote computing device, a graphical user interface for reviewing images, receive, from the remote computing device via the graphical user interface, selection of an image, generate print data based on the selected image, and transmit the print data to the remote computing device for printing with an edible media printer equipped with edible ink.

8 Claims, 44 Drawing Sheets



Related U.S. Application Data

continuation-in-part of application No. 14/569,290, filed on Dec. 12, 2014, now abandoned, which is a continuation of application No. 13/287,023, filed on Nov. 1, 2011, now Pat. No. 9,713,342, which is a continuation-in-part of application No. 12/852,988, filed on Aug. 9, 2010, now abandoned.

(51) Int. Cl.

G06F 3/12 (2006.01)
A23P 20/10 (2016.01)
A23P 20/15 (2016.01)
A23P 20/20 (2016.01)
A23P 20/25 (2016.01)

(52) U.S. Cl.

CPC **A23P 20/20** (2016.08); **A23P 20/253**
(2016.08)

(56) References Cited

U.S. PATENT DOCUMENTS

2,347,022 A	4/1944	Austin
2,353,594 A	7/1944	Seagren
2,394,322 A	2/1946	McKee
2,526,811 A	10/1950	Dawson
2,578,150 A	12/1951	Rathke
2,610,588 A	9/1952	Seagren et al.
2,895,832 A	7/1959	Bersey
3,057,730 A	10/1962	Moreck
3,192,086 A	6/1965	Gyurk
3,649,347 A	3/1972	Battista
3,654,894 A	4/1972	Rohrbacher et al.
3,658,977 A	4/1972	Baker
3,776,185 A	12/1973	Kawasaki
3,852,494 A	12/1974	Williamson
4,024,287 A	5/1977	Golchert
4,061,783 A	12/1977	Hoffman et al.
4,168,662 A	9/1979	Fell
4,285,978 A	8/1981	Quinlivan
4,292,917 A	10/1981	Ezaki
4,388,862 A	6/1983	Thomas, Jr.
4,409,893 A	10/1983	Newman et al.
4,455,320 A	6/1984	Symis
4,466,994 A	8/1984	Hubbard et al.
4,531,292 A	7/1985	Pasternak
4,537,647 A	8/1985	Foster
4,548,825 A	10/1985	Voss et al.
4,560,562 A	12/1985	Schroeder
4,578,273 A	3/1986	Krubert
4,592,916 A	6/1986	Akesson
4,668,521 A	5/1987	Newsteder
4,668,523 A	5/1987	Begleiter
4,670,271 A	6/1987	Pasternak
4,785,313 A	11/1988	Higuma et al.
4,832,966 A	5/1989	Newsteder
4,843,958 A	7/1989	Egosi
4,910,661 A	3/1990	Barth et al.
4,985,260 A	1/1991	Niaura et al.
5,006,362 A	4/1991	Hilborn
5,017,394 A	5/1991	Macpherson et al.
5,032,416 A	7/1991	Niaura et al.
5,035,907 A	7/1991	Phillips et al.
5,081,917 A	1/1992	Masuda
5,255,352 A	10/1993	Falk
5,334,404 A	8/1994	Garcia et al.
5,485,189 A	1/1996	Ebata
5,505,775 A	4/1996	Kitos
5,547,507 A	8/1996	Ciaramita

5,711,791 A	1/1998	Croker et al.
5,795,395 A	8/1998	Ben-Matitayhu et al.
5,834,047 A	11/1998	Ahn
5,895,682 A	4/1999	Tsukioka
6,045,220 A	4/2000	Kiyohara et al.
6,058,843 A	5/2000	Young
6,499,842 B1 *	12/2002	Kofman A01J 27/005 347/105
6,536,345 B1	3/2003	Young
7,286,258 B2	10/2007	Schnoebelen et al.
7,884,953 B1	2/2011	Willcocks et al.
8,219,494 B1	7/2012	Pride et al.
8,944,542 B2	2/2015	Nohilly et al.
9,282,750 B1 *	3/2016	Davila G06Q 30/00
9,907,332 B2 *	3/2018	Davila A23P 20/00
2001/0012529 A1	8/2001	Genevieve
2002/0047867 A1	4/2002	Mault et al.
2002/0049638 A1	4/2002	Ito
2002/0109600 A1	8/2002	Mault et al.
2002/0152927 A1	10/2002	Russell et al.
2005/0237567 A1	10/2005	Morris
2005/0254073 A1	11/2005	Braun et al.
2006/0279771 A1	12/2006	Ludwig et al.
2008/0209509 A1	8/2008	Koike et al.
2014/0176608 A1	6/2014	Boysen et al.
2015/0015919 A1	1/2015	Anderson et al.

FOREIGN PATENT DOCUMENTS

GB	543427	2/1942
GB	628886	9/1949
GB	786428	11/1957
JP	59118049	7/1941
JP	60126057	7/1985
JP	2163058	6/1990
WO	95/01735	1/1995
WO	97/27759	8/1997

OTHER PUBLICATIONS

Genometri, On-line Design Tools [retrieved on Mar. 14, 2017] <URL: <http://genometri.com/>>. Reference previously submitted in U.S. Appl. No. 15/164,545.

Ferguson Plarre Bakehouses, Birthday Cakes, Celebration Cakes, Sweets & Savouries Online [retrieved on Mar. 14, 2017] <URL: <http://www.fergusonplarre.com.au/designacake>>. Reference previously submitted in U.S. Appl. No. 15/164,545.

Cake Stock, A4 food cake printer, 2017 [retrieved on Mar. 7, 2017] <URL: <https://www.cake-stock.com/a4-size-printer>>. Reference previously submitted in U.S. Appl. No. 15/164,545.

Topperoo, Quick Start Guide, 2017 [retrieved on Mar. 7, 2017] <URL: <http://support.topperoo.com/article/36-quick-start-guide>>. Reference previously submitted in U.S. Appl. No. 15/164,545.

Icing Images, Order an Edible Picture or iDesigns Pattern Print, 2017 [retrieved Mar. 14, 2017] <URL: <http://www.icingimages.com/edible-cake-picture>>. Reference previously submitted in U.S. Appl. No. 15/164,545.

“From Phone to Foam—Steam CC Launches the Coffee Ripples App Putting Consumers in Control of Coffee Art Content” PR Newswire, Jan. 6, 2016, 4 pages <URL: <http://www.prnewswire.com/news-releases/from-phone-to-foam---steam-cc-launches-the-coffee-ripples-app-putting-consumers-in-control-of-coffee-art-content-in-a-cup-300200121.html>>. Reference previously submitted in U.S. Appl. No. 15/164,545.

Icing Images, iPrint Image PReinting Template Designed, web page accessed Aug. 24, 2016, 2 pages, <URL: <http://www.icingimages.com/iprint-template-designer>>. Reference previously submitted in U.S. Appl. No. 15/164,545.

* cited by examiner




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F




FIG. 1G




FIG. 1H




FIG. 1I




FIG. 1J





FIG. 2A

200a






FIG. 2B




FIG. 3








FIG. 4









600




FIG. 6




FIG. 7


800a 

FIG. 8A

800b →




FIG. 8B




FIG. 9A






FIG. 9B








FIG. 10




FIG. 11A

1100b




FIG. 11B



FIG. 12









FIG. 13












1876






FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24

2500




FIG. 25




FIG. 26





FIG. 27



2900




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33

DECORATING SYSTEM FOR EDIBLE ITEMS**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 15/164,545 entitled "Decorating System for Edible Items" and filed on May 25, 2016, which is a continuation-in-part of U.S. patent application Ser. No. 14/569,290 entitled "Online Decorating System for Edible Products" and filed Dec. 12, 2014, which is a continuation of U.S. patent application Ser. No. 13/287,023 entitled "Online Decorating System for Edible Products" and filed Nov. 1, 2011, which is a continuation-in-part of U.S. patent application Ser. No. 12/852,988, entitled "Decorating System for Edible Products" and filed on Aug. 9, 2010, each of which is incorporated herein by reference in their entireties. This application is also related to the following: U.S. application Ser. No. 10/925,459, entitled "Decorating System for Edible Items" and filed on Aug. 25, 2004, now U.S. Pat. No. 7,012,712; U.S. application Ser. No. 14/553,884 filed Nov. 25, 2014, now U.S. Pat. No. 9,282,750 and is a continuation of U.S. application Ser. No. 13/287,023; U.S. application Ser. No. 14/569,224 filed Dec. 12, 2014, now U.S. Pat. No. 9,314,050 and is a continuation of U.S. application Ser. No. 13/287,023; U.S. application Ser. No. 14/569,042 filed Dec. 12, 2014, which is Patented and is a continuation of U.S. application Ser. No. 13/287,023; U.S. application Ser. No. 14/194,000 filed Feb. 28, 2014, which is Pending and is a continuation-in-part of U.S. application Ser. No. 12/852,988; U.S. application Ser. No. 14/492,620 filed Sep. 22, 2014, which is Pending and is a continuation-in-part of U.S. application Ser. No. 12/852,988; and U.S. application Ser. No. 15/157,142 filed May 17, 2016, which is Pending and is a continuation-in-part of U.S. application Ser. No. 14/569,290, each of which is also incorporated herein by reference.

BACKGROUND OF ILLUSTRATIVE EMBODIMENTS

Decorative food products, such as cakes, are popular items, particularly for special occasions, such as birthdays, holidays, weddings, anniversaries and other celebratory events. These items are typically purchased from bakeries since the items generally require some skill and/or apparatus to create. Previously, these items were created from colored frostings applied manually by trained bakery decorators. For example, pre-made decorative items can be placed on a food product. These pre-made items are generally produced in bulk in a factory and inventoried until use. The use of such pre-made decorative items precludes uniquely decorated and/or personalized decorations. Also, these pre-made decorative items are generally pre-ordered, which requires a long lead time, or stored in inventory at the risk of under-ordering or over-ordering, as well as the cost of such inventory.

Another alternative has been to utilize an automated system for decorating cakes. One such system is disclosed in U.S. Pat. No. 5,505,775, issued to Kitos. This system utilizes an integrated work surface controlled with a computer system. A 2-dimensional image is scanned into the computer system. The computer system then uses a motion control system to manipulate a drop-on-demand colorant expulsion system over a cake carried on the work surface to reproduce the scanned image. This system produces the decorations and images directly onto the food product.

An automated system for printing images onto edible media, that can then be applied to a food product or consumed as is, is disclosed in U.S. Pat. No. 7,286,258, issued to Schnoebelen et al., which is incorporated by reference herein. This system discloses a local processing unit and a number of image sources, including a scanner and a database of digital images stored on a local computer memory system. The user selects an image from one of the image sources and prints the image onto an edible media.

A decorating system for edible items is disclosed in U.S. Pat. No. 7,012,712, issued to Spurgeon et al., which is incorporated herein by reference. This system discloses creating a decorative edible item from a selected image. The system includes at least one image source, such as a scanner and/or a library of stored images, a controller unit and a printer for creating a high-quality pictorial rendition of the image. The printed edible media can then be applied onto a product, shipped to a separate location or eaten as is.

Various websites exist for allowing users to customize decorations. One such online website is www.genometrix.com which allows users to decorate and purchase customized decorated cakes. Users can choose from pre-designed decorative templates or can choose to customize their cake decoration. Users can upload personal photographs to use in the cake decoration and can add text and clip art to the cake decoration. When the user is finished decorating the cake, the user purchases a cake decorated with the customized decoration. The purchase transaction is processed through the website.

SUMMARY OF THE ILLUSTRATIVE EMBODIMENTS

Disclosed herein are methods and systems for creating and decorating edible media. In certain embodiments, at least one local control device and a Graphical User Interface (GUI) can be used for selecting an image, receiving and/or transmitting the selected image via the Internet to and/or from a central control device containing a website with at least one image database, and printing licensed digital images at the local control device upon an edible medium using edible inks. In certain configurations, a principal user authorizes a secondary user to search and print specific, pre-authorized images from the central control device's image database. In certain implementations, the user purchases edible media via the Internet.

In selected implementations, the user decorates an edible media with images from multiple image sources. The image sources may include local image sources, such as a scanner or a digital camera, or remote image sources, such as an image library in an Internet website. The image sources may contain proportionate two dimensional images, as well as disproportionate two dimensional images that can be manipulated by a user.

In various embodiments, the user may print licensed digital images within a print environment provided internally by a software web browser used to navigate the website with at least one image database. In other implementations, a user may print licensed digital images in an external printing environment provided separately from the software web browser used to navigate the website with at least one image database. For example, the external printing environment could be a web-enabled standalone application on a local control device that accesses an image repository on a central control device through a secure connection originally authenticated via login procedures in a separate software web browser application. The web-enabled stand-

alone application may, in selected implementations, prevent received license-controlled image data from unauthorized re-use, editing, or distribution, and permits image processing, such as applying the International Color Consortium's color correction process, at the local control device. The web-enabled standalone application may further generate a printer-specific byte stream based on post-image processed data, providing a color-managed workflow independent of local control device operating system print drivers.

The details of one or more implementations are set forth in the accompanying drawings and description below. Other features, objects, and advantages will be apparent from the description and drawings, and from the claims.

DESCRIPTION OF DRAWINGS

FIG. 1A is an example system for decorating edible media;

FIGS. 1B-1E show examples of edible media that are 3D printed on a food product;

FIGS. 1F-H show a cross section of a 3D edible media according to an example;

FIG. 1I shows a perspective view of a printer having a printhead connected to a printer frame and a stationary platform according to an example;

FIG. 1J shows a drawing of a printer having a jointed movable printhead and a maneuverable platform according to an example;

FIG. 2A is an example computer system containing software modules in a central control device in a system for decorating edible media;

FIG. 2B is an example computer system containing software modules in a local control device in a system for decorating edible media;

FIG. 3 is an example swim lane diagram of a process for ordering edible media;

FIG. 4 is an example swim lane diagram of a process for a principle user to authorize secondary users and designate authorized images for the secondary users;

FIGS. 5A-5D depict an example swim lane diagram of a process for decorating an edible medium;

FIG. 6 is an example flow diagram of a process for displaying augmented reality content using a decorated edible medium with an augmented reality marker;

FIG. 7 is a flow diagram of a process for decorating edible media with licensed digital images;

FIGS. 8A and 8B are a flow diagram of a process for printing edible media that bypasses operating system print drivers;

FIGS. 9A-9D depict an example swim lane diagram of a process for printing edible media using a parallel browser module;

FIG. 10 depicts an example User Interface tree for a website in a system for decorating edible media;

FIGS. 11A-32 depict example webpages from a system for decorating edible media; and

FIG. 33 is a block diagram of an example computer system.

DETAILED DESCRIPTION OF ILLUSTRATIVE IMPLEMENTATIONS

FIG. 1A is an example system **100** for decorating an edible media **102**. The system **100** provides an online environment for creating and decorating edible media. The online environment includes one or more website applications with which the user can interact to print edible content

on edible substrates or edible media. The system **100** provides a mechanism to perform online or local searching of images and customization of images.

As used herein, an image can be any work protected by a copyright, registered copyright and/or a registered trademark including a regular image or photograph, a digital image, a fictional character, a celebrity, an emblem, a logo, a mascot, an illustration, a pictorial, a graphic, as well as works not in image form such as sculptural works, which include two- and three-dimensional works of fine, graphic, and applied art. An image can include an image protected by a commercial license. An image can include a series or collection of two or more images, a schematic, and a computer aided design (CAD) file for deriving or rendering a 2D or 3D form or object. In an example, the 2D or 3D form or object can be a figurine that is based on a copyrighted character or a generic body of a part of a figurine. Further, an image can also include derivatives of the copyrighted works and the trademarked works, as well as any other original work including non-copyright protected images or unpublished work such as personal photographs, digital images, videos, illustrations, clip art, and other original works. In an example, the 2D or 3D form or object can have 2D elements or 3D elements that can be customized, such as size, color, and features that can be merged with user data for a personalized birthday kid (e.g. image of face of kid on the figurine, etc.).

As used herein, edible media can be any two-dimensional or three-dimensional ingestible product. In an example, edible media may be a baked good such as a cake, cupcake, cookie, or pizza crust. In another example, edible media may be temperature-sensitive media such as an ice cream cake, ice form, or gelatin. In a further example, edible media may be a planar printable surface such as edible paper, wafer, or edible media sheet. In an additional example, edible media may be a three-dimensional edible confection such as an off-the-shelf edible decoration (e.g., SugarSoft® Decorations by DecoPac, Inc. of Anoka, Minn.), candy, or chocolate.

As used herein, printable base media can be any two-dimensional or three-dimensional nontoxic product used as a base for printing two-dimensional or three-dimensional edible decorations. In an example the printable base media can be the food product. In an example, the printable base media can include edible media, as described above. In another example, printable base media can include a planar nontoxic material such as a flat plastic base material, a flat metal base material, or a flat paper or cardboard base material (e.g., a cake board), a silicon transfer sheet, or a wax paper transfer sheet. In a further example, printable base media can include a formed nontoxic material such as a ring form (e.g., to be worn on the finger as a ring pop) or a stem form (e.g., popsicle stick with planar printing surface onto which an edible decoration can be printed). In additional examples, a printable base media may be printed prior to printing of an edible item. In a particular example, the printable base media can be a 3D printed flower stem form that can be made from an edible or inedible material unto which the secondary shape, edible or nonedible, may be printed, such as a flower.

The system **100** is operated by a user to print and/or customize images including both licensed and non-licensed digital images. The system **100** additionally provides digital rights management, print monitoring functions, user account management, and messaging functions.

The system **100** manages both licensed and non-licensed images for purposes of obeying licensing laws when printing

5

the images on an edible medium. Licensed digital images, such as copyrighted images including fictional characters, celebrities, emblems, logos, mascots, illustrations, or photographs having licensing terms and conditions for use can be purchased from one or more online sources. In an example, the image can be a grouping of multiple 3D elements such as a set of individual characters (e.g., a feature film character set).

Non-licensed digital images such as personal photographs, illustrations, clip art, or other non-copyright protected images can be uploaded locally to the system 100. Both licensed and non-licensed digital images are retrieved from an external device or the Internet, stored locally, and uploaded to the system 100. In some embodiments, a combination of licensed and non-licensed digital images are retrieved either locally or online and printed in combination on a single printable base media. In some embodiments, the uploaded digital files may be of a scanned three-dimensional shape such as a person or thing.

Users generally access the online environment in system 100 to search, select, edit, and purchase images. The purchased images can be printed onto the edible media 102 using edible inks. For example, a user of system 100 accesses the online environment to search for a particular image. The user selects the image, purchases and/or edits the image, and directs the system 100 to print the purchased image onto the edible media 102. The images available to system 100 can be retrieved from any number of sources including local, online, or remote storage repositories. For example, images can be retrieved from local image sources 104 which are communicably connectable to system 100. The local sources can include, but are not limited to a digital camera 106, a CD-ROM OR DVD 108, a video device 110, a flash drive 112, a scanner 114, a mobile device 116, a computer available on a local network 118, an external hard drive, a netbook, a laptop, a wireless device (e.g., Wi-Fi enabled, Bluetooth enabled, or other wirelessly enabled device), or a handheld device (not shown) such as a “smart” phone or tablet.

Images can also be retrieved via the network 118 from any number of websites containing digital images or libraries of digital images. Images can additionally be retrieved from other networked or remote storage repositories (not shown). Upon retrieving images, the system 100 provides access to additional features for handling retrieved images, such as photograph editing, social networking content insertion, or augmented reality content insertion.

Users can purchase edible media using one or more e-commerce sites. For example, users can purchase an edible sheet from an e-commerce site incorporated into system 100. E-commerce sites associated with system 100, for example, provide a number of selectable options for obtaining edible media. The user can choose standard “off-the-shelf” edible media items or custom edible media items.

In some configurations, the user is provided the option to purchase edible media locally using the system 100. For example, the user may be offered several sizes of edible media for decorating. The user can select a desired decoration size and choose an edible media (e.g., an edible sheet of paper) size comparable to the desired decoration size. The selected edible media (e.g., edible media 102) can be purchased through the system 100 by entering an appropriate edible media code or by simply selecting the desired edible media onscreen. The edible media code can, in effect, function as a part number for ordering a specific edible media sheet size. In some implementations, the edible media code is requested by the system 100 to prompt a user to

6

select an edible medium available locally in a bakery, for example. The selected edible medium can be loaded into the system 100 and images can be printed upon the edible medium.

In certain embodiments, the system 100 requests that the user enter a unique code. The unique code may be sent to the user with edible media prior to accessing system 100. The unique code can be entered once by the user to enable printing of images a specific number of times. For example, the user can enter a code and receive up to twenty-four print sessions for selected images. In operation, once the user enters the code, the system verifies that the code is valid and has not been used before. In practice, the user may be limited to the specified print sessions.

Once the edible media has traveled through the printer and the image printed thereon with the edible inks, the printed edible media is removed from the printer. The printed edible media is then placed on a food product at the point of printing and transported to a separate location for application. In some configurations, the edible media is relatively thin and sturdy allowing for convenient transport and thus minimization of damage to the decorations. In certain embodiments, the edible media may also include an optional release sheet having a silicon coating functioning as a backing material, for example.

In some implementations, the system 100 includes an image uploading device. The image uploading device may be a wired or wireless storage device operable to upload licensed and non-licensed digital images. The image uploading device may be coupled to any number of alternate image sources for uploading additional images. For example, the image uploading device may represent a scanner, while the alternate image source represents a network drive accessed over the Internet. In another example, the image uploading device represents a mobile phone device while the alternate image source represents a USB fob.

User Interface

In the system 100, User Interface controls 120 are connected to the local control device 128. The User Interface controls 120 include a keyboard 122, a mouse 124, and a display device 126. Other implementations may use other devices, such as a touch screen device, a joy stick, or a voice command system. In one example the touch screen device can be the mobile device 116 or PDA. The User Interface controls 120 allow the user to operate the system 100 to decorate edible media 102 or to display edible media-related content on the display device 126. In one example a virtual headset can be used to display a virtual reality or an augmented reality.

The user is displayed a variety of navigation screens and menus on the display device 126. The user selects desired options from the navigation screens and menus using the keyboard 122, the mouse 124, or other input mechanism. The User Interface controls 120 relay signals from the user to a local control device 128, thereby operating the system 100.

The display device 126 is operable to display a Graphical User Interface GUI 127 for interacting with the hardware and software components of system 100. The GUI 127 can, for example, include application screens, website content, software controls, and other Graphical User Interface content. The GUI 127 is operable to receive user input for accessing one or more licensed or non-licensed digital images. The GUI 127 can, for example, include graphical elements provided in one or more applications. Users can

interact with one or more graphical elements to control the behavior and output of system **100** components.

The GUI **127** is operable to control the local control device **128** and communicate with the central control device **132** over a network to retrieve at least one licensed digital image from the central control device. In an example where the User Interface controls **120** and the local control device **128** are combined into the tablet or touch screen device, the GUI **127** can be further configured to interpret and communicate through the network image manipulation input in order to execute a computational module **232**. For example, a network image manipulation input through the GUI **127** can rotate a 3D image such to change its respective center of mass and effect a base **170** needed (See FIG. 1D-1E), as determined by the computational module **232**.

The GUI **127** is also operable to cause to be printed at least one licensed digital image onto an edible medium. The GUI is also operable to switch between multiple software applications, including a software web browser and non-web browser software. In some configurations, the GUI **127** is operable to retrieve non-licensed images.

The GUI **127** can be presented within a software web browser. In certain implementations, a user may print licensed digital images within a print environment provided internally by a web browser used to navigate a website with at least one image database. In other embodiments, a user may print licensed digital images in an external printing environment provided separately from the software web browser.

Local Image Sources

The system **100** includes one or more devices which can be communicably coupled to system **100** as local image sources **104**. In this example, a variety of local image sources **104** are connected to the local control device **128**. One such local image source **104** is the scanner **114**. The scanner **114** can be a flatbed scanner, or any other type of scanner such as a drum scanner or a through feed scanner. The scanner **114** allows an image to be rendered from personal photographs, drawings, books, magazines, etc. In some embodiments, the local image sources **104** may include a 3D scanning device resulting in one or more digital image files containing a 3D representation of an object. In certain embodiments, system **100** can evaluate acquired images for copyright indicators. In an example the copyright indicators include copyright and trademarks for figurines of fictional characters, celebrities, emblems, logos, mascots, and the like. Based on the detection of copyright indicators, the user may be alerted to potential copyright limitations, or usage of the acquired image may be automatically denied.

Other local image sources **104** include the digital camera **106**, the CD-ROM OR DVD **108**, the video device **110**, the flash drive **112**, and the mobile device **116**; however, other sources of digital image storage or repositories can be used in the system **100**. In certain embodiments, the local image source **104** can be a personal electronic device such as a camera phone or PDA. In operation, when a particular local image source is connected to the local control device **128**, a user can retrieve images from the connected local image source to use in the system **100** for decorating (e.g., printing on) the edible media **102**.

Images retrieved from local image sources are uploaded to system **100** and stored. For example, scanned images retrieved from scanner **114** are uploaded into system **100**,

stored locally on system **100** and provided for use in the system. The stored images can be retrieved by users for editing, printing, and so on.

Local Video Device

The system **100** includes one or more local video devices **130**. Any device that is capable of capturing and communicating a digital video signal can be used. In certain embodiments, the local video device **130** is a web camera. The local video device **130** is generally connected to the local control device **128** by a wireless or wireline means. The user uses the local video device **130** to send a digital video signal to the local control device **128**. The local control device **128** transmits the digital video signal to a central control device **132** via the network **118**. In certain embodiments, a single frame can be extracted from the digital video signal for printing. In other embodiments, a single image for printing can be generated based on a montage of image frames extracted from the digital video signal.

In certain embodiments, the local video device **130** is a personal electronic device such as a camera phone or PDA. The local video device **130** is generally connected to the local control device **128** by a wireless means such as Wi-Fi, Bluetooth, near-field communication, or wireline means such as USB or similar connectors. In an example, the local video device **130** can also function as the local control device **128** and the local image source **104**.

Local Control Device

The local control device **128**, in an example, is coupled to the User Interface controls **120**, the local image sources **104**, the local video device **130**, and a printer **134**. Local image sources **104** contain at least one local digital image. In certain embodiments, local digital images are selectively uploaded from the local control device **128** to the central control device **132** for storage, permitting printing of the local digital image onto the edible medium at a later time.

In some configurations, the local control device **128** is coupled to a printer **134** and an image uploading device for purposes of retrieving and transmitting a digital image from the image uploading device to the printer. The retrieval and transmission is typically in response to the user selection. For example, the user uses a scanner to upload an image to the local control device **128**. The uploaded image is transferred to the printer **134** for printing.

The local control device **128** is operated by the user using the User Interface controls **120**. For example, the user operates the local control device **128** to search, select, and purchase an image. The local control device **128** is operable to print the purchased image onto the edible media **102**, for example. The local control device **128** includes a software web browser that allows the local control device **128** to communicate with the central control device **132** via network **118**. In some implementations, the central control device **132** is a web server capable of communicating using standard Internet protocols.

In this example, the local control device **128** is depicted as a computer system. However, any processing unit which can digitally process signals from local image sources **104** or other sources can be used.

Central Control Device

The central control device **132** is connected via the network **118** to the local control device **128**. The central

control device **132** includes a plurality of licensed digital images for decorating edible media by authorized users. The licensed digital images are protected from unauthorized usage and unauthorized user access. The central control device **132** provides a tracking mechanism to authorize or de-authorize usage of licensed digital images. For example, the central control device **132** authorizes the use of particular licensed digital images according to user credentials. The user credentials can be stored in system **100**, or externally. The user credentials typically include payment information, location information, and system usage data. The central control device **132** verifies whether specific users should be provided access to particular licensed images.

The central control device **132** may include a software web server which allows the local control device **128** to communicate with a website on the central control device **132**. The web server can be any web server capable of communicating using standard network protocols compatible with local control device **128** using a variety of Internet connection types and operating systems. The web server may run on a variety of operating platforms, for example Windows, Linux, MAC OS, or UNIX.

The website (not shown) hosted on the central control device **132** includes a number of software modules. The software modules may include, but are not limited to, image library modules, user account modules, edible media modules, photograph editing modules, user location recognition modules, training modules, print modules, licensing restriction modules, social networking modules, augmented reality content modules, security modules, and/or messaging modules. Other modules are possible. The described software modules can be selectively combined to form a multifunctional software module, or split into multiple software modules.

The user can access the website and accompanying software modules on the central control device **132** using the local control device **128**, for example. The user can search images, purchase images, edit images, print images, order edible media, view training content, and access social networking features and augmented reality content stored on the central control device **132**. Example software modules will be discussed below in reference to FIG. 2A.

Central control device **132** may include media servers, for example, a FLASH multimedia server, and the local control device **128** may include corresponding media players, for example, a FLASH player. FLASH players may be implemented either as a plug-in to the software web browser, or as a stand-alone application.

Printing Device

The system **100** includes the printer **134** operable to receive and print images upon edible media **102** using edible inks. The printer **134** may include a feed path through which the edible media **102** is inserted and conveyed past one or more printheads. The printhead technology can be any type of printhead technology which can be controlled by digital signals including, for example, inkjet, thermal inkjet, piezo inkjet, continuous inkjet, valve jet, electrostatic inkjet, airbrush technology, and computerized numerical control (CNC) machines.

In one example the printer **134** can be a 3D printer configured to print edible materials and/or edible inks. In an aspect, the 3D printer may be configured to print with an edible material supplied in various colors. In another aspect the edible material can have a base coloring (e.g. white, off-white, etc.) and the 3D printer can be configured to print

with a variety of edible ink colors upon the edible material. FIGS. 1B-1E show examples of a 3D edible media **160** on printable base media **150**.

FIG. 1I shows a perspective view of a printer **134'** having a printhead **192** connected to a printer frame **190** and a stationary platform **180'** according to an example.

In certain embodiments, the printer **134** can have one or more fixed and/or moveable printheads and/or a maneuverable platform. FIG. 1J shows a drawing of a printer **134''** having a jointed movable printhead **192** and a maneuverable platform **180''** according to an example. The jointed movable printhead **192** can function similar to a multi-jointed CNC robotic arm. Similarly, the maneuverable platform **180''** can function similar to a multi-jointed CNC robotic arm. The maneuverable platform can alternatively be a rotating and/or orbiting gimbal platen and/or platform configured to rotate the food product while the printhead is in operation. The maneuverable platform can have a set of securing mechanisms **182** configured to hold or grip the food product or the base **170**. In an aspect the printer can coordinate tilting of the edible media and an angle of the printhead, with tracking a set of deposition coordinates to match a secondary treatment.

In an example the printer **134** can print edible materials and edible inks on a large food product having one or more separated levels, sides, and contours such as a tiered cake. In an example, the maneuverable platform can rotate a tiered cake while printing on a side of the tiered cake. In another example the printer **134** can print edible materials and edible inks on a small food product such as a cake pop. The cake pop can be easily rotated in multiple configurations as compared to the larger tiered cake. In another example the printer **134** can print an entire cake pop with edible materials and edible inks, as well as non-edible materials. FIG. 1J shows an example of a cake pop being held in the set of securing mechanisms **182** while being created and/or decorated.

In an example, the printhead can be configured to extrude a first edible material to support a second edible material. For example, referring to FIGS. 1F-1H a combination of two or more edible materials can be printed in a coordinated manner. FIG. 1F shows a location of a cross section **164** of a 3D edible media **160**, as shown in FIGS. 1G-1H. FIG. 1G shows the cross section **164** of a first edible material **160a** surrounded by a second edible material **160b** according to an example. The first edible material **160a** can have a stiffness, density, and/or consistency to support the second edible material **160b**, which may not have been able to support itself. In an example, the first edible material can be a nougat material and the second edible material can be a chocolate coating on the nougat material, where the combined nougat material and chocolate coating material form a three-dimensional object such as a candy bunny.

FIG. 1H shows the cross section **164** of a first edible material **160a** and a second edible material **160b** adhering to the first edible material **160a** according to another example. Either the first edible material **160a** or the second edible material **160b** can have a surface feature or adhesive property to promote adhesion.

The printhead can have a set of one or more nozzles for extruding the two or more edible materials together according to an example. The nozzles can extrude each edible material separately or simultaneously by having one nozzle embedded in another nozzle.

The printheads can include one or more of an imaging device such as a camera, or a sensor such as a 3D scanner, a force transducer, a temperature detector, and an infrared

11

detector as well as any other sensor related to 3D printing. In an example the imaging device can be configured to index, scan or read an indicator on or the shape of the food product to determine a location of the surface of the food product for printing.

In another example, the imaging device or sensor can be configured to create a digital scan or data on a shape and appearance of a real object such as a food product or printable base media **150**, and to create a digital model based on the digital scan or sensor. The digital scan can be used to filter and to suggest different images that can be printed by the printer **134** at different locations on the food product.

In an aspect the 3D printer can include a contour tool or reductive modeling tool (e.g., carver/cutter/suction), a painting tool (e.g., watercolor effect, airbrush, etc.), a curing head, and a set of multi-color printheads. In an example, the contour tool can be configured to shape, to remove, to cut, and to carve the food product or edible materials into a different contour. In an example, the contour tool can carve a fondant or a cake to a different shape. In another example, the contour tool can shape an ice cream cone or other dessert cup. In another example, heads may be interchangeable to provide multiple functionality.

In an example, the printhead can include an in situ sensor and/or a biopsy probe configured to determine a mechanical or structural property of the food product such that the contour tool removes a portion of the food product without creating unintended instability. In an example, the situ sensor can be an acoustic or ultrasound sensor, a non-penetrating pressure sensor, or any other type of sensor. In an example, the biopsy probe can include a penetrating pressure sensor.

The curing head can be a cooler and/or a heater. In an aspect the 3D printer can use edible materials, as well as inedible materials such as plastic and/or wax (e.g. to print candles). In an example, the curing head can be configured to lead or to follow a second printhead and apply cooling and/or heat. In an example, a first printhead can be configured to extrude an edible material such as cake batter, followed by a second printhead supplying heat to the cake batter such that the cake batter rapidly broils or bakes.

In some embodiments, the printer **134** is configured to function within and/or provide a temperature controlled environment. For example, when the edible media is a form of ice cream, the temperature controlled environment can be a freezer or a platform that is chilled. In another example, the printer **134** can include a temperature treatment to apply to the printed edible media. In a particular example, a liquid nitrogen treatment may be deployed by one or more liquid nitrogen applicators of the printer **134** to set chilled decorations such as ice cream embellishments. In another example, a dry ice treatment may be deployed for other freezing as well as visual effects. In an example, the secondary treatment can be a coating for the dry ice treatment to slow, delay, or pattern a fog emanating from the dry ice treatment.

In some embodiments, the printer **134** includes a setting treatment for setting the edible media after decoration. For example, the printer **134** may supply a setting treatment via one or more applicators as a functional layer, such as a hardening or stiffness support layer to promote structural integrity of the 3D edible media. In another example, the printer **134** may supply an aesthetic treatment via one or more applicators, such as adding a sheen, a glitter, or a glossy appearance, that may or may not contribute a functional benefit to the finished product. In particular examples,

12

the printer **134** may be configured to apply one or more of a sugar, a starch, a wax, and a glazing agent to stabilize a decorated edible media.

In some printing systems, the edible inks described above are generally fed from a cartridge reservoir. Such cartridge reservoirs may be refilled as need. In some embodiments, images are printed onto a transfer layer, which in turn is applied onto the edible media **102**.

In another example, the printer **134** can be used to dimensionalize a frosting sheet by printing a three-dimensionally textured background or scene for a corresponding non-printed decoration (e.g., DecoSet® Decorations by DecoPac, Inc. of Anoka, Minn.). In a particular example, train tracks and landscaping (e.g., mountains, trees, grass, water, etc.) can be three-dimensionally printed upon edible media, and a toy train may be placed upon the textured scene.

Edible Media

The system **100** includes edible media **102** on which images are printed. The edible media **102**, in this example, includes at least one edible layer **136** and an edible coating **138**. The edible medium may be a single layer of edible material. For example, the edible medium may be a single layer of sugar paper, sugar paste, starch paper, fondant, or some other edible form. Examples of options for edible material include but are not limited to standard media with sizes of 1/2, 1/4, and 1/8 sheet, or precut media of sizes 8 inch round, 3 inch round, or 2 inch round, or edible strips.

One embodiment of the edible layer **136** of the edible media **102** includes a mixture of a sugar paste of varying thickness. The edible layer **136** is typically formulated for several key features. First, the edible layer **136** is mixed to depict high-quality pictorial images from particular edible inks disclosed herein. Second, the edible layer **136** travels through a printer (e.g., printer **134**) without damaging the edible media **102**, the edible layer **136**, or the printer. For example, the edible layer **136** is mixed to ensure sufficient strength to be bent and manipulated through the conveying path of the printer **134**, withstand the heat of the printing process, and still maintain suitable textural integrity as to not jam in the printer mechanism of printer **134**. Third, the edible layer **136** is mixed to ensure there is no detracting from the taste of the food product on which it is to be applied. Other variations of edible layers and edible media may be used as well.

In some implementations, the edible layer **136** is formulated for use in decorating pizza or deli type items. For example, the edible layer **136** may be formulated as savory rather than sweet.

Other examples of edible layers **136** are described in U.S. Pat. No. 5,017,394, assigned to the Lucks Company, and incorporated herein by reference. This type of edible layer **136** is formed from a flour and/or starch base as opposed to the sugar base of a fondant. Another example of an edible layer **136** is disclosed in U.S. Pat. No. 5,334,404, issued to Garcia et al. and incorporated herein by reference. Other types of edible layers **136** can be used including, but not limited to rice paper, wafer paper, and other edible substrates on which an image may be printed.

The edible coating **138** enables the edible media **102** to render a high quality pictorial image on the surface of the edible layer **136**. Without this coating **138**, the inks tend to run or bead or form an imperfect image. In one example, the coating **138** is a very thin layer of calcium carbonate. This

13

thin layer allows the inks to properly perform to render a high-quality pictorial image. Other coatings may be used in system **100**.

In some embodiments, the edible media **102** may also include an optional release sheet **140** having a silicon coating functioning as a backing material, for example. In some implementations, the edible media **102** is a standard size or shape. Example sizes can include 8.5 inches by 11 inches, 9-inch round, and 8-inch round. The size can be a precut size or a selectable size. In some configurations, frosting layers, edible material and/or fondant layers can be malleable and/or stretchable to various sizes and shapes.

FIGS. **1B-1E** show examples of a 3D edible media **160** on a food product **150**, where the 3D edible media **160** has a center of mass **162** and a contact area **152** with the food product **150**.

As shown in FIG. **1B**, the center of mass **162'** of the 3D edible media **160** on the food product **150** can be within the 3D edible media **160**. As shown in FIG. **1C**, the center of mass **162''** of the 3D edible media **160** on the food product **150** can be outside of the 3D edible media **160**. As shown in FIGS. **1D-1E**, the center of mass **162'''** of the 3D edible media **160** on the food product **150** can be unsupported by the contact area **152** and thereby can move or tip due to gravity. In an example, the 3D edible media **160** can be made from a combination of edible materials such that the center of mass **162** can be shifted.

As shown in FIG. **1D**, the 3D edible media **160** can include a base **170** that can be configured to support and mechanically compensate for the center of mass **162'''** in an example. As shown in FIG. **1E**, the base **170** can include one or more attachment features **172** that can be configured to support, couple, and mechanically compensate for the center of mass **162'''** according to an example. In an example the base **170** and attachment features **172** can be made from one or more edible materials. In another example the base **170** and attachment features **172** can be made from one or more non-edible materials. In another example the base **170** and attachment features **172** can be made from a combination of one or more edible materials and one or more non-edible materials.

Edible Inks

The edible inks used in the system **100** are typically formulated from food grade colors and ingredients to enable high quality, near-photographic images to be printed onto the edible media **102**. These inks are edible and have precise color-matching properties, but additionally function in a manner similar to other commercially available inks in printers. Edible inks may include natural inks manufactured from a food grade base.

The edible inks are specifically formulated for use in a particular printer. The user selects to print the image using different color models, according to the requirements of the printer. Providing selectable color models improves the precision of the printed image by enabling adherence to particular color matching systems. The edible inks may be inks designed to be used for decorating numerous different types of food products, including, for example, cookies, cakes, pizza, cupcakes, candy bars, edible tattoos, temporary tattoos, cereal boxes, waffles, and pancakes.

In an example the edible ink can be an edible printing material configured for 3D printing. The edible ink used for 3D printing can include any number of the following: icing, SugarSoft® by DecoPac, Inc. of Anoka, Minn., chocolate, frozen dessert material such as sorbet, yogurt, or ice cream,

14

candy material, Royal icing, fondant, gelatin, and edible materials capable of being deposited by an airbrush style printhead tool.

The edible inks are additionally formulated to faithfully render images in accordance with the appropriate color model. Possible color models include, but are not limited to, the Cyan, Magenta, Yellow and Black (CMYK) color model, as well as the RGB, LAB, HSB, Pantone, Hexachrome, and other color models. In some embodiments, the edible inks are formulated to render images in accordance with the CMYK color model. Other examples of edible inks that provide faithful matching to the CMYK color model, as well as other color models, and that function within the constraints of commercially available printing technologies may be used in the system **100**. In some configurations, the inks used in system **100** include a combination of edible inks, natural inks, synthetic inks, or other inks.

Central Control Device Software Modules

FIG. **2A** is an example computer system **200a** containing software modules of a website used in a system for decorating edible media. The system **200a** can, for example, be analogous to central control device **132** (FIG. **1A**). A user of the system **200a** accesses a website on the central control device **132** to gain access to one or more software modules **202-234**.

The software modules shown in FIG. **2A** may include an image library module **202**, an image editing module **204**, an edible media module **206**, a user account module **208**, a license module **210**, a print module **212**, a user location module **214**, a social networking module **216**, an augmented reality module **218**, a training module **220**, an ordering module **222**, a maintenance module **224**, a reporting module **226**, and a messaging module **228**.

The image library module **202** is a software module including a plurality of digital images that can be printed onto an edible media. The image library module **202** includes both images available for purchase and free images. The images may be licensed or unlicensed images, and may include clip art, illustrations, photographs, text, three-dimensional images or other 2D and/or 3D file content. The image library module **202** generally contains different formats of the same image each of which are configured for printers that use differing color models.

The images in the image library module **202** may contain embedded augmented reality markers, which allow the user access to augmented reality content. The augmented reality marker can be any asymmetric geographical shapes of any color with sufficient contrast. The user can use the image containing the augmented reality marker to access augmented reality content on the augmented reality module **218**, for example.

The image library module **202** allows the user to browse or search through the images using keyword criteria such as "Sports" or "Princess" or "Birthday." The image library module **202** may be updated with new images and new image formats. In certain embodiments, image library module **202** may be updated with an image acquired through a local image source, such as a USB WebCam. In another illustrative embodiment, image library module **202** may be updated by a reference to Web content, such as a photograph posted on a social media network. In another implementation, image library module **202** may be updated based on changes in agreements with image suppliers, and/or alterations in files supported by the system **100**.

15

The image library module **202** interacts with the license module **210** and the user location module **214** to allow or restrict users when finding and/or purchasing particular images. For example, the license module **210** may restrict access to a user based on a number of factors. One example factor may include barring image purchases based on a geographic location and/or an authorized list for the user. In this example, when a user selects to view images available from the image library module **202**, the user location module **214** can automatically identify the geographic location of the user. The user's geographic location can then be used by the license module **210** to identify whether any of the images in the image library module **202** are restricted from being sold in the user's location. If a restriction is found, the license module **210** sends to the image library module **202** information on which images are unavailable to the user. The image library module **202** removes the restricted or unavailable images from the image library made available to the user. In certain embodiments, restriction of images based on the user's geographic location can be in addition to or in substitute for an authorized list of images containing available images for the user.

The image library module **202** also interacts with the user account module **208** to allow a secondary user to only search and purchase images that have been authorized for the secondary user by a principal user. For example, a principal user can designate specific secondary users. The principal user then searches through the image library module **202** and identifies which images can be sold to which secondary users. The principal user can designate different images for users in different geographic locations. When a secondary user accesses the website and selects to search the images in the image library module **202**, the secondary user is only shown the images available at the user's geographic location, and/or on the user's authorized list, which is made of images previously authorized by the principal user.

The image library module **202** also interacts with the social networking module **216** to allow the user to identify the most popular images or designs and to access other social networking functions. For example, the user may be provided an option of viewing lists of the most popular designs. The user may also be provided an option of viewing consumer reviews of images in the image library. The provision of social networking options may be provided in an online fashion where the user can interact with social networking content using system **100**.

The image library module **202** interacts with the print module **212** to ensure that the version of the image that is compatible with the color model of the printer is sent to the user's printer. When the user selects to print an image, the print module **212** sends to the image library module **202** the color model of the user's printer. The image library module **202** sends to the user's printer the correct format of the image. In certain embodiments, the print module **212** prompts or allows the user to identify the printer **134** attached to local control device **128**. In other illustrative embodiments, the print module **212** auto detects the identity of printer **134**.

The image library module **202** also interacts with the edible media module **206** to enable the user to identify images suitable for the particular edible media selected for decoration. The user enters into the edible media module **206** the specific type of edible media being decorated. The edible media module **206** contains characteristics of the edible media, and sends to the image library module **202** specific criteria for compatible images, such as image size.

16

The image library module **202** removes the images which are not compatible with the edible media the user selected.

The edible media module **206** is a software module that includes a list of the edible media available to be used in the system **100** and which are available for purchase by the user. The user can search or browse through the edible media module **206** using various keyword criteria, such as "cupcakes" or "cake." The edible media module **206** may also contain information about the cost and availability of edible media. Furthermore, the edible media module **206** also may contain a database of unique codes that are associated with particular edible media. The unique codes may function as part numbers, printing data, cost data, retrieval data, or other data. The edible media module **206** interacts with the user account module **208** to allow the user to purchase edible media. Once the user selects an edible media for purchase, the user account module **208** processes the financial transaction. In some implementations, if a licensed image is selected, the user account module **208** may require the user to checkout before proceeding to print the image on the edible media.

The edible media module **206** interacts with the image library module **202** to allow the user to identify images that are compatible with particular edible media. The edible media module **206** contains information about edible media compatible with the system. The user chooses the specific type of edible media and the edible media module **206** sends information about this edible media to the image library module **202**. The image library module **202** then isolates specific images that are compatible with the particular type of edible media.

The edible media module **206** includes at least one repository (not shown) of unique codes that are associated with particular edible media. The edible media module **206** tracks whether or not a code has been used to authorize a print. The edible media module **206** interacts with the print module **212** to verify that the user is using authorized edible media using the codes. The print module **212** notifies the edible media module **206** upon receiving a purchase request, which prompts the user to enter the code from the edible media. The edible media module **206** verifies that the code is valid and that the code has not been previously used. If the code is valid, then the print module **212** proceeds with the print of the image. If the code is not valid, then the print module **212** notifies the user of the invalidity without printing the image.

The image editing module **204** is a software module that allows users to edit selected images. Example editing functions may include cropping, moving, rotating, re-touching, brightening, darkening, and adding text to images, as well as other image editing operations. The image editing module **204** interacts with the licensing module **210** to prevent users from editing images on which there are editing restrictions imposed by a license. The license module **210** informs the image editing module **204** if there are any restrictions on editing the selected image, and if so, how. The image editing module **204** then prevents the user from editing any images in violation of a license.

The user account module **208** is a software module that maintains profiles of individual users in user accounts. The user accounts include information pertaining to a number of users, such as address data, financial data, previous image usage, etc. In some embodiments, the user account module **208** maintains a list of user names and passwords that provide or limit access to particular user accounts. The user account module **208** can process financial transactions, for example, to allow users to purchase edible media.

17

The user account module **208** can store purchase and order histories including selected images, designs, text content printed, notifications configured, edible media purchased, etc. The user account module **208** can also store user profiles, address data, financial data, and image restrictions.

The user account module **208** interacts with the edible media module **206** to allow the user to purchase edible media. Once the user selects the desired edible media, the user selects to purchase the edible media. The user account module **208** will then process the purchase. The user account module **208** may prompt the user for credit card information or bank account information for direct debit. Alternatively, the user account module **208** may already have this information on file. The user account module **208** will charge the user the designated amount.

In some configurations, the user account module **208** provides an option to purchase credits. The credits can be applied to a particular user account for purposes of purchasing images using the credits. The credits can be incremented when purchased by a user and decremented when the user purchases images using system **100**. For example, if a user chooses to download and print a digital image, the user account module **208** can decrement the user's credits thereby providing payment, and print the requested images onto a requested edible medium.

Licensed digital images can be charged on a per use basis. Thus, if the user prints the same licensed digital image on six cupcakes, the user may be charged six credits for using the licensed digital image six times. In some implementations, the system **100** can allow printing of a licensed image multiple times on one sheet of edible media, for example, at the cost of one usage (e.g., one credit). The system **100** may allow a variable relationship between an image and the number of credits required to use the image.

In the event that the user is short on credits, the user may be prompted to purchase additional credits by using a credit card, for example. If however, the user wishes to print non-licensed digital images, no credit charge will be transacted. Rather, the user will simply purchase any materials utilized.

In some embodiments, a selected licensed digital image can be instantaneously purchased from the central control device **132**, for example, using the local control device **128** upon receiving (i) user-entered payment information and (ii) a user request for purchase of the selected licensed digital image. The payment information can, for example, allow access to an e-commerce system (e.g., within system **100**) for purchasing licensed digital images using decrementable credits for printing licensed digital images. The e-commerce system can be adjustable for multiple currencies such as the U.S. Dollar, the Pound, and the Euro, just to name a few examples.

In some configurations, users can pre-purchase credits that will enable a print function to be selectable within the GUI **127**, for example. The pre-purchased credits allow for users to easily access licensed content as part of a custom design and print the design in an accelerated fashion. For example, if the user pre-purchased credits, the user may have been asked to sign a licensing/usage agreement at the time of purchasing the credits. Thus, when the user performs a transaction with such credits, additional forms and/or steps are not required of the user during design and print stages.

In some implementations, the payment information includes credit card data rather than previously purchased credits. In some embodiments, the payment information includes credit card data presented for purchasing decrementable credits.

18

In general, the user account module **208** interacts with the image library module **202** to allow the user to purchase an image from the image library module **202**. Once the user selects the desired image, the user chooses to complete the purchase. The user account module **208** will then complete the purchase. For example, the user account module **208** can verify whether the user has any available credits. If the user does have available credits, then one or more credits are debited from the user's credits and the user account module **208** authorizes the use of the image. If the user does not already have available credits, the user account module **208** may prompt the user for credit card information or bank account information for direct debit. Alternatively, the user account module **208** may already have this information and use previously stored financial information. The user account module **208** will charge the user the designated amount and authorize the use of the image to complete the purchase.

The user account module **208** allows a principal user to designate one or more secondary users. The user account module **208** interacts with the image library module **202**, the license module **210**, and the user location module **214** to allow the principal user to designate an authorized image list for the particular secondary user. A principal user accesses the user account module **208** and designates specific secondary users. The principal user then selects the image library module **202** and searches through the image library. The principal user designates which images are authorized for which secondary users. The principal user can also authorize different images for different secondary users. This information is generally stored in the user account module **208**.

The license module **210** is a software module that includes information regarding the user's license to certain images. The license module **210** interacts with the image library module **202** and the user location module **214** to ensure that the user may only search and select for purchase authorized licensed images. The user location module **214** informs the license module **210** of the user's geographic location. The license module determines whether restrictions exist on the sales of particular images in the user's location. If restrictions exist, the license module **210** requests that the image library module **202** remove the unauthorized images from the images available to the user. In some configurations, authorized lists or pre-filtered searching options can be applied to the available licensed content such that a user is pre-approved for finding and/or downloading particular content.

The license module **210** interacts with the image editing module **204** to ensure that any licensing restrictions on images are followed. Once the user selects a particular image, the license module **210** informs the image editing module **204** if any licensing restrictions exist that prevent the user from editing the selected image. If restrictions exist, the license module **210** presents the restrictions to the user. The print module **212** is a software module that allows the user to print images using the system **100**. Once the user has selected an image and is ready to print the image onto an edible media, the user selects to print the image. The print module **212** allows a user to preselect default printer model information, which can be stored within the print module **212**. In some implementations, the print module **212** selects a color profile based on printer model information stored within print module **212**. Alternatively, print module **212** can perform hardware communication with the printer to determine printer model information for the purposes of selecting a color profile. In another illustrative embodiment, print

module **212** allows the user to select a color profile. The print module **212** provides data from the central control device to the local control device for printing on a printer attached to the local control device. In certain embodiments, the local control device **128** may print data provided by the print module **212** within a print environment provided internally by a software web browser used to navigate the website with at least one image database. In other configurations, a local control device **128** may print data provided by the print module **212** in an external printing environment provided separately from the software web browser used to navigate the website with at least one image database.

The print module **212** interacts with the edible media module **206** to verify that the user inputs a code, such as an edible media code, that corresponds to an authorized edible media. The edible media module **206** verifies that the code is valid and unused before the print module **212** proceeds with sending data to the local control device for printing.

The user location module **214** is a software module that identifies the user's geographic location. In certain implementations, this may be accomplished by comparing the user's IP address against publicly available databases. In other embodiments, the user location module **214** determines a user's geographic location from a stored user address list. For example, the user location module **508** accesses one or more user address lists to determine which users reside in a particular location. The user address list typically includes a number of users with corresponding physical mailing addresses. The user location module **508** accesses the user address lists to determine which geographic location is relevant for a particular user and provide a catalog of images having proper licensing for the determined geographic location. User address lists can be generated by a vendor or third-party and sent to individual systems (such as system **100**). The secondary user address lists can be uploaded by a primary user (e.g., a store manager) using storage media or uploaded automatically over the Internet. Although detecting IP addresses and user address lists are discussed above, any available method of determining an Internet user's location may be used.

The user location module **214** interacts with the license module **210** and the image library module **202** to ensure that the user can only select and purchase images that are licensed in the geographical area. For example, if an image is licensed to be sold or used in Canada, the same image may have requirements for use in the United States. As such, the user location module **214** can use license module **210** and image library module **202** to ensure image licensing agreements are obeyed.

The user location module **214** interacts with the user account module **208** to ensure that a secondary user can only search and select for purchase images that have been authorized by a principal user. When a user selects to search for an image from the image library module **202**, the user location module **214** identifies the user's location. The user location module **214** informs the user account module **208** of the user's location, so the user account module **208** can identify whether the user is a secondary user with geographic restrictions on the authorized images available to the user. In some configurations, authorized lists or pre-filtered searching options can be applied to the available licensed content such that a user is pre-approved for finding and/or downloading particular content, despite the user location falling within a geographic restriction.

The social networking module **216** is a software module that allows the user to access social networking content. For example, the social networking module **216** may inform the

user which of the available images are the most popular over all, the most popular for certain genders or age groups, or the most popular for certain events, such as birthdays. The social networking module **216** may contain user or consumer reviews of certain images. The social networking module **216** may also suggest ways that images can be altered using the image editing module **204**. The social networking module **216** interacts with the image library module **202** to allow the user to purchase images identified in the social networking module **216**.

The augmented reality module **218** is a software module that allows the user to access augmented reality content when the system **100** detects a valid augmented reality marker. The system **100** can print images onto edible media that contain embedded augmented reality markers. The user can then display the decorated edible media to a video device. In certain configurations, this video device is a web camera. The local control device **128** sends the video data to the central control device **132**. The augmented reality module **218** on the central control device **132** scans the incoming video signal, and identifies a valid augmented reality marker. The augmented reality module **218** will respond by displaying augmented reality content. For example, in certain implementations the augmented reality marker may be embedded in an image of a princess that is used to decorate a cake. The augmented reality module **218** may display a singing and dancing princess in response to recognizing the augmented reality marker. In a further example, a three-dimensional image (e.g., figurine) including an augmented reality marker may be augmented to display a portion of the three-dimensional image in animated form. In a particular illustration, the augmented reality module **218** may display an expressive, singing face upon a three-dimensional printed princess figurine in conjunction with accompanying audio.

The training module **220** is a software module that includes training content which instructs users on how to use the decorating system. The training module **220** may contain videos, lists of common questions and the answers thereto, diagrams, or any other training content that user may find useful.

The ordering module **222** is a software module that includes inventory items for a system owner (e.g., a bakery owner, store owner) to access for reordering edible media, edible ink, replacement parts, printheads, and other system supplies.

The maintenance module **224** is a software module that includes maintenance menus for updating software, hardware, or inventory. The maintenance module **224** can additionally provide troubleshooting instructions, printer maintenance features, testing functions, and cleaning functions.

The reporting module **226** is a software module that includes mechanisms for reporting on sales, inventory, customers, errors, malfunctions, and other events occurring in system **200a**. In some embodiments, reporting data can be exported to comma delimited files, Excel files, or exported to particular reporting software. The reporting module **226** can additionally provide site metric reporting via NetInsight, Google analytics, or similar site metric reporting software.

The messaging module **228** is a software module that includes mechanisms for generating and sending electronic messages to users. For example, the messaging module **228** may send an electronic message to specific user accounts or groups of user accounts based on previous purchases. The messaging module **228** may send system users receipts or other billing information in the form of a message. The messaging module **228** may also send advertising content or fliers to known users. In some configurations, the messaging

module **228** sends messages to system managers or store managers regarding system updates or image updates.

Security module **230** is a software module that handles secure socket connections from local control device **128**. For example, following authentication through login procedures through a software web browser, central control device **132** can establish additional secure connections to the same local control device **128** with software modules separate from the software web browser. Functionality not incorporated into the software web browser on local control device **128** can interact with the software modules on central control device **132** through security module **230**. Interaction with software modules on central control device **132** can proceed through multiple software applications on local control device **128**. In certain implementations, security module **230** handles secure transmission of both licensed image data and financial data for purchases of licensed images. In other illustrative implementations, security module **230** handles secure transmission of financial data for purchases of licensed images, but does not apply security policies to licensed image data. In certain embodiments, HTTP (hypertext transfer protocol) can be used for transmitting payment and/or image data, such as in the form of unsecured HTTPS or secured HTTPS. In other embodiments, FTP (file transfer protocol) can be used for transmitting payment and/or image data. Alternatively, SMTP (simple mail transfer protocol) can be used for data transfer.

A computational module **232**, in some implementations, is a software module that can perform computations for modeling and printing the 3D edible media. In an example, the computational module **232** can compute a finite element model in order to determine the center of mass **162** and stability of the 3D edible media **160** as shown in FIGS. 1B-1E. In an example, the computational module **232** can compute structural mechanics in order to determine the center of mass **162** and stability of the 3D edible media **160** as shown in FIGS. 1B-1E. In an example, the computational module **232** can compute a set of equations based on mechanical statics and dynamics in order to determine an interoperability of a 3D edible media **160** divided into multiple parts or two or more 3D edible media **160**. In an aspect, the 3D edible media **160** can be configured to divide into multiple parts, or the one or more 3D edible media **160** can be configured to interact, based on an event such as melting, cutting, or breaking, of a part of the 3D edible media **160**. In one example, a candle can be configured to melt a part of the 3D edible media **160** and create an event.

In an aspect each edible media material has a known density. In an aspect the computational module **232** can determine the center of mass **162** of the 3D edible media **160** based on the density of the edible media material. In an aspect the computational module **232** can determine a suitable base **170** and attachment features **172** for the 3D edible media **160** to prevent from dislocation or tipping. In an example, the computational module **232** can determine a base **170** with a set of attachment features **172** to compensate for the center of mass. In an aspect the computational module **232** can determine one or more edible media materials to print the 3D edible media **160** such that it can have a center of mass to prevent tipping or other unplanned movement. In an aspect the computational module **232** can determine one or more edible media materials to print the 3D edible media **160** such that it can have a center of mass to result in a planned movement.

In some implementations, the computational module **232** can use a 3D scan or digital data of the shape and appearance of the food product **150** or other two or three dimensional

element presented upon an edible media (e.g., frosting sheet, cake top, etc.) to determine a feature of the 3D edible media **160**. In some embodiments, the computational module **232** identifies the location of a three dimensional element and decorates the three-dimensional element. In a first example, the 3D printer may first print a three-dimensional element (e.g., a frosting fish) and then later add decorative elements to the three-dimensional element (e.g., airbrush edible ink onto the frosting fish). In a second example, the computational module **232** may identify placement of an off-the-shelf three dimensional element positioned on the edible substrate by a user, and alter the appearance of the off-the-shelf three dimensional element using one or more print-heads and/or other features of the 3D printer (e.g., airbrush tool, reductive modeling tool, etc.) to customize the appearance of the off-the-shelf three dimensional element. The customizations, for example, may be based upon user instructions supplied to the 3D printer. In a particular illustration, the computational module **232** may identify the position of a three-dimensional edible figurine and modify the figurine to conform to image data provided by the user matching or mimicking the supplied image data (e.g. by adding facial features, hair, etc. a figurine of the birthday girl created from an off-the-shelf avatar). In some examples, the computational module **232** may identify the off-the-shelf three dimensional element based in part upon one or more of a three-dimensional shape, a color, or a marking (e.g., barcode, QR code) on the off-the-shelf three dimensional element.

Additional modules **234** can be included in system **200a**. For example, service oriented third party applications can be merged or supplied as add-ins as appropriate. Similarly, online advertising content, Internet access, FLASH applications, database management, online shopping, and other services may be offered in system **200a**.

Local Control Device Software Modules

FIG. 2B is an example computer system **200b** containing examples of software modules used in a system for decorating edible media. The system **200b** can, for example, be analogous to local control device **128** (FIG. 1A). A user of the system **200b** accesses a website on the central control device **132** to gain access to one or more software modules **202-234** (FIG. 2A).

The software modules on local control device **128** include authentication modules, parallel connection modules, parallel browser modules, color management modules, and/or printer communication modules. Additional modules are possible. The described software modules can be selectively combined to form a multifunctional software module, or split into multiple software modules.

The authentication module **240** interacts with the parallel connection module **242**. Upon successful verification of an authenticated session between the software web browser on local control device **128** and central control device **132** via network **118**, the authentication module **240** causes parallel connection module **242** to establish a second connection to central control device **132** in parallel to the connection used by the software web browser on local control device **128**. In some implementations, the parallel connection is established automatically after authentication of a secure connection for the software web browser by authentication module **240**. In other embodiments, the second connection is established based on user request. The parallel connection module **242** connects with the security module **230** shown in FIG. 2A. In certain implementations, parallel connection module **242**

23

may utilize the connection created by the software web browser for communication with central control device 132.

In certain configurations, the second connection occurs over the network 118 used by the software web browser. In other implementations, the second connection occurs over a network different from network 118. The connection established by the parallel connection module 242 can use identical networking protocols or encryption protocols to the connection utilized by the software web browser, or can use a different networking and/or encryption protocols.

In some embodiments, the second connection persists despite the initial connection between the software web browser on local control device 128 and central control device 132 being terminated. In other configurations, the second connection terminates concurrently with termination of the first connection between the software web browser on local control device 128 and the central control device 132.

The parallel connection module 242 interacts with parallel browser module 244. Parallel browser module 244 utilizes the secure socket connection with central control device 132 over the second connection created by the parallel connection module 242. Access to software modules on central control device 132, including the image library 202, are accessible to the parallel browser module 244 concurrently with accessibility from the software web browser on local control device 128. In certain implementations, the software web browser on local control device 128 is a generic web browser. The software web browser on central control device 132 can be implemented as 3.sup.rd party software, with closed, proprietary, or undocumented application programming interfaces, and/or security profiles that deny access to system functions including local file system access or low level printer control commands. In other embodiments, the software web browser on local control device 128 provides a documented application programming interface (API) for the software web browser to interact with other software installed on local control device 128. Parallel browser module 244 can co-exist on local control device 128 with either implementation of software web browser on local control device 128.

In certain configurations, parallel browser module 244 provides a streamlined user-interface for accessing software modules residing on central control device 132. The parallel browser module 244 can be implemented in a variety of programming languages or development environments. In certain implementations, the parallel browser module can be implemented as an Adobe Integrated Runtime (AIR) application. In the AIR application, the parallel browser module 244 acts as a cross-platform, browser-based runtime application. In other embodiments, parallel browser module can be implemented in C++ using Qt libraries. In the C++/Qt framework implementation, the parallel browser module 244 acts as a web-enabled cross-platform application and UI framework with access to system functions, such as the local file system.

The parallel browser module 244 is implemented as a Rich Internet Application, providing both local file system access and remote web content access. For example, remote web content including but not limited to thumbnail representations of licensed images from image library module 202 can be downloaded by parallel browser module 244 and stored in a local cache residing on the local file system of local control device 128, providing low latency rendering of images during image manipulation events including browsing and editing. In other embodiments, the parallel browser module 244 is implemented in a software package complying with security policies that permit remote web content

24

access, but not local file system access, or vice versa. Local cache contents are in a custom format that prevents users from extracting local cache contents for unauthorized editing and/or printing of cached licensed images.

The parallel browser module 244 on local control device 128 exchanges data with central control device 132 over the same network connection established by the software web browser. In select implementations, the software web browser utilized an unsecured connection such as HTTP (Hypertext Transfer Protocol). The software web browser utilizes a secured connection such as HTTPS (HTTP with secure socket layer (SSL)/transport layer security (TLS)), performing security procedures including but not limited to server authentication, client authentication, and secure encryption key exchange.

The parallel browser module 244 on local control device 128 exchanges data with central control device 132 over a network connection different than the network connection established by the software web browser. The separate connection established by the parallel browser module 244 can either be secured or unsecured, independent of if the software web browser connection is secured or unsecured.

The parallel browser module 244 is capable of sending and receiving separate classes of data on different connections and/or different connection security profiles. For example, image data from image library module 202 may be received by the parallel browser module 244 over an unsecure HTTP connection between the parallel browser module 244 and the central control device 132, while financial data may be sent from the local control device 128 to central control device 132 over a secure connection established by the software web browser. In another example embodiment, both image data and financial data may be sent over a secure connection established by either the software web browser or the parallel browser module 244.

Parallel browser module 244 bypasses existing print drivers provided by the operating system when printing. When bypassing operating system print drivers, parallel browser module 244 interacts with a color management module 246. The color management module 246 provides color matching and correction to print data provided by print module 212 on central control device 132. Color encoding on print data propagating from print module 212 may be indexed by a color representation scheme as known in the art.

In certain configurations, the color representation scheme is as described by the International Color Consortium (ICC). The ICC specification uses the CIE color profile and is widely used and is referred to in many International and other de-facto standards, and was approved as an International Standard, ISO 15076-1, which is incorporated herein by reference. A standardized color representation scheme such as the ISO 15076-1 ensures color rendition accuracy despite variations in color detection and production across image capture devices (e.g., scanners), image display devices (e.g., monitors), and image reproduction devices (e.g., printers). Color management module 246 provides a color managed workflow from source image to printer output, applying color representation transformations that ensure accurate color representation in each color domain. The general principles of color managed workflows using the ICC Color management Model have been described variously, for example in U.S. Pat. No. 7,161,710 to MacLoed, et al, assigned to Adobe Systems Incorporated, which is incorporated herein by reference.

In some implementations, color profile information is embedded in the image provided by the print module 212. In other embodiments, color profile information is retrieved

25

separately from the image data provided by the print module **212**. In certain configurations, a separate image color profile for the display device connected to the local control device **128** is applied to the retrieved image. In other implementations, the display device connected to local control device **128** is not color corrected using any color profile.

Application of color correction to print devices is independent of application of color correction to display devices. In certain embodiments, a user can automatically retrieve the corresponding color profile for a printing device connected to local control device **128** based on hardware model information for printer **134**. In other cases, the user can provide their own color profile based on color spectrography measurements performed on printed outputs of printer **134**.

The color management module **246** interacts with a printer communication module **248**. The printer communication module **248** provides communication to a printer device connected to local control device **128** without utilizing printer drivers installed on the operating system on local control device **128**. In certain configurations, printer communication module **248** automatically detects the model number of the attached printer **134**, and downloads corresponding software through the second connection established by parallel connection module **242**. In other implementations, printer communication module **248** includes pre-installed software for several different print hardware manufacturers and/or vendors. In further embodiments, printer communication capabilities provided by the printer communication module **248** are not dependent on specific cartridge reservoirs utilized by the printer.

Parallel web browser module **244** is associated with network address identification information. In certain embodiments, network address identification information allows modules residing on the local control device **128** to interact with one another without networks external to the local control device **128**, such as a LAN, MAN, or the Internet. In other embodiments, network address identification information only allows modules residing on the local control device **128** to interact with one another through an external network connection, with or without messages passing through the central control device **132**.

Parallel web browser module **244** and the software web browser on the local control device **128** communicate with a pre-defined message format and message exchange patterns. In an illustrative embodiment, the Simple Open Access Protocol (SOAP) is utilized. Alternatives communication schemes for exchanging complex data structures include but are not limited to Extensible Markup Language-Remote Procedure Call (XML-RPC).

Additional modules **250** can be included in system **200b**. For example, media players, advertising displays, and other services may be offered in system **200b**.

Account Management

User accounts can be managed by an administrator (e.g., a bakery or store owner). The administrator typically configures an administrative profile where administrative tasks can be carried out. For example, the system owner can log in to an administrative profile for configuring the system **100**, reviewing inventory reports, and purchasing consumables. The administrative profile can also include options to create additional user accounts, update or modify users or passwords, generate contact lists, browse and order consumables, view order or purchase histories, modify language

26

parameters (e.g., Spanish, English, Mandarin, French, etc.), manage licensed image assets, edit pricing, etc.

Web Host Server

A web host server within central control device **132** is configured by the administrator to allow users to select particular edible items, select customization options, and preview designed products before printing. The administrator can add or remove User Interface controls to provide or remove functionality in the GUI. For example, the administrator can modify a User Interface within the web host server to ensure all design modification buttons are presented in one interface. This can provide the advantage of allowing the user to quickly modify designs without having to move through multiple screens.

In one example, the web host server includes updatable links with (i) helpful hints and exceptional cake design examples, (ii) how-to instructions, (iii) frequently asked questions, (iv) tips and tricks from other users, and (v) online demonstration videos, just to name a few example links. In some configurations, a full help section is integrated into the system including tool tips, videos, etc.

In some implementations, the web host server includes notification and messaging functionality. For example, the web host server may include calendar integration options complete with scheduling and reminder notifications for particular holidays, birthdays, etc. The notification functionality can also include customized templates or projects which can be attached to the notifications. For example, if a company provides customized birthday cakes for all employees, the company can create a birthday template coupled to each employee's birthday date in a reminder notification. The notifications can be configured to email a customer, for example, in advance of an event requiring configuration of an edible media item.

In some embodiments, the web host server includes advanced browsing options with predictive text and faceted search filters. As such, a customer can easily navigate images and enter text in an expedited fashion. The web host server is operable to attach metadata or categorical information to particular images, frames, characters, or reminders to facilitate users in improving design time for preparing an image for printing.

Website Content

The websites hosted in system **100** can include menus, buttons, and other controls. The websites generally include standard website content such as contact information, privacy policies, warranty information, a site map, advertising content, social media content, and licensing information. Other content may be provided in websites hosted in the system **100**.

Image Manipulation

The systems disclosed herein can provide image manipulation functions. Image manipulation functions can be performed in the GUI **127** in a mocked up on-screen version of the final product. Users can modify image media, backgrounds, frames, and text within the system **100**. Functions for modifying and editing images include, but are not limited to color skewing, cropping, zooming, rotating, conversion to black/white or grayscale, and filtering. Images can be previewed, stretched, scaled, skewed, or otherwise manipulated in a Graphical User Interface to obtain a desired result for

27

the user. Text can be added, removed, or otherwise modified. For example, text can be arced for a round design or angled for special effects. Text can be entered by a user or selected from a list of standard common phrases such as Happy Birthday, Congratulations, or Happy Anniversary, to name a few examples. In some configurations, watermarks can be added graphically and printed onto the edible media.

In an example, the image manipulation functions performed in the GUI 127 can be configured for 3D printing. In an example, the image media is a 3D media. In an example, each 3D media can have an expected center of mass 162 and a corresponding suggested base 170 or suggested attachment features 172 based on the edible materials and edible inks. In an aspect, the image manipulation functions performed in the GUI 127 can be based on the computational module 232. In one example, when the 3D media is manipulated, the computational module 232 can automatically suggest one or more combinations of edible materials that can be used to make the 3D edible media 160 based on the 3D media such that the center of mass of the 3D edible media 160 would be within a tolerance to prevent tipping. In an example, the tolerance can be provided by a computation done by the computational module 232.

In one example, when the 3D media is manipulated, the computational module 232 can automatically suggest or determine a design for the base 170, as shown in FIGS. 1D-1E, to compensate for the center of mass 162 of the 3D edible media 160 within the tolerance to prevent tipping. In one example, when the 3D media is manipulated, the computational module 232 can automatically suggest or determine a design for the attachment features 172, as shown in FIG. 1E, such that a combined center of mass of the 3D edible media 160 and the base 170 would be within the tolerance to prevent tipping.

Media Authentication

The systems disclosed herein can provide media authentication for licensed images. For example, the system 100 validates particular licensed images for printing based on user information, image information, and/or product information. The system 100 provides an inventory system with trackable records. Each trackable record contains information regarding unique lot numbers assigned to each image to ensure image disclosures can be accounted for. Each trackable record can additionally contain quantity information for a product and media type compatible with such a product. Trackable records can be linked to user logs to determine customer accounts that activated particular products or images. This can be used to track lot numbers for recall purposes, for example. In some implementations, the trackable records can be used as an advertising tool to market to one or more specific customer.

In some embodiments, the system 100 prevents unauthorized usage of licensed images by preventing the system and/or user from locally saving a licensed image. In addition, the system 100 prevents unauthorized usage of licensed images by preventing the user from accessing a particular licensed image more than once in one session, for example. Other mechanisms of preventing unauthorized usage of licensed images can be implemented. Low level image processing, such as applying ICC color management, can still occur in the presence of the above mechanisms for preventing unauthorized image usage.

Checkout

Upon determining one or more items for purchase, users can choose to checkout and purchase such items. The

28

checkout process generally leverages standard e-commerce functionality using application programming interfaces (APIs) for performing transactions. The APIs can integrate functionality such as shopping carts, shipping options, order preview, order confirmation, payment options, add/remove functions, etc. The checkout process guides the user through transactions. In some configurations, the checkout process can additionally manage reporting and accounting functions.

Process for Ordering Edible Media

FIG. 3 is an example swim lane diagram of a process 300 for ordering edible media. The process 300 can, for example, be performed in the online environment in system 100. Although the process 300 is described with reference to system 100, other systems, environments, or processors can perform the steps in process 300.

The online environment in system 100 may represent a website hosting one or more software modules. Software modules in this example include an edible media module 301 and a user account module 302. The edible media module 301 is a software module that includes information about edible media that is available for purchase, including current availability and inventory statistics. The user account module 302 is a software module that includes user accounts having profiles of information regarding particular users, such as financial information and address information. The user account module 302 can be configured to process financial transactions.

The user accesses a User Interface element in the website, such as GUI 127 to access the user account module 302. The user account module 302 presents a logon screen to the user and requests entry of a username and password. The user inputs the user name and password to login (303) and the user is logged into the system 100. In certain illustrative embodiments, in the event that the user forgets login credentials, an additional prompt permits the user to input identification information, such as the answer to a preselected security question, a PIN, or an e-mail address, to authenticate the user's request either to reset login credentials, or request secure delivery of login credentials.

The username and password may or may not be secure when sent from the software web browser to central control device 132. For example, the username/password may be encapsulated in TCP/IP packets as unencrypted plain text. Alternatively, username and password information may be secured over SSL/TLS.

The user account module 302 displays navigation menus (304). The navigation menus include a number of options representing different ways that the user may use the system 100. Options can include, but are not limited to quick launch items (e.g., quick copy, quick upload, quick print, etc.), photograph manipulation options, framing configuration options, artwork selection and manipulation options, purchasing options (e.g., enter media codes, user data, etc.), ordering options (e.g., pre-order forms), PhotoCake configuring options, settings options, and administrative options (e.g., shut down, restart, test system, etc.). The user can also choose to open a prior design to print copies on new edible media. Other options are possible.

The edible media module 301 provides an option to select to search for edible media (305). For example, the edible media module 301 offers the user the option of searching for specific edible media or browsing through a catalogue of edible media. The user navigates through the catalogue (306) and selects the edible media that the user wishes to purchase (307). In some implementations, the user is pro-

29

vided an option to select multiple types of edible media in a single purchase. When the user has selected the desired edible media, the user instructs the user account module **302** that the user is ready to complete the purchase (**308**). The user is directed to the user account module **302**, which processes the purchase of the edible media.

The user account module **302** prompts the user to enter the user's financial information (**309**). The user may enter credit card information or bank account information for direct debit. In certain embodiments, the user account module **302** may store the user's financial information. The user has the option of using previously used financial information that is remembered by the user account module **302**. In an illustrative embodiment, the user is presented with a screen to allow verification of purchase details before finalizing a purchase. The user account module **302** then completes the purchase (**310**) by charging the user according to the information that has been entered. In certain embodiments, the user has agreement terms that do not require purchase procedures to be executed for each individual image, and instead, purchase procedures are applied to a batch of images periodically, such as at monthly billing cycle.

In some configurations, the user account module **302** provides an option for shipping purchased edible media to the user. The user account module **302** may request additional information, such as an address the edible media should be sent to, or which shipping method the user prefers. Alternatively, the user account module **302** may retain previously used address information, in which case the user may choose to use previously stored information. The user completes the process **300** by logging off of the system (**312**).

Process for Establishing Secondary User Authorization

FIG. **4** is an example swim lane diagram of a process **400** for a principle user to authorize secondary users and designate authorized images for the secondary users. The process **400** can, for example, be performed in the online environment in system **100**. Although the process **400** is described with reference to system **100**, other systems, environments, or processors can perform the steps in process **400**.

The online environment includes an Internet website hosting a user account module **401** and an image library module **402**. The user account module **401** is a software module that includes user accounts containing profiles of information regarding particular users. The image library module **402** is a software module containing a searchable and browsable library of images.

The principal user accesses the user account module **401** and logs in to the principal user's account (**403**) by entering the principal user's user name and password. The principal user is shown a navigation menu containing a number of selectable options (**404**).

The principal user selects to designate secondary users (**405**). The principal user is then prompted for information regarding the secondary users and how such secondary users will be identified (**406**). For example, the principal user may be asked to enter unique user names and passwords for secondary users. Alternatively, the principal user may enter email or physical address information for the secondary users. The secondary users may be sent instructions on how to access their new secondary user accounts. The user account module **401** saves the information given on the secondary users, and associates the secondary user accounts with the principal user's account.

30

The image library module **402** allows the principal user to search for authorized images for the secondary users (**407**). The principal user searches or browses through available images, using keyword criteria such as "Princess" or "Birthday." The principal user selects images, or groups or categories of images, that will be authorized for the secondary users and the image library module **402** receives the selections (**408**).

Once the principal user has finished searching through the images and selecting images, the principal user selects to associate particular images and the user account module **401** associates the selected images with the particular secondary users.

The user account module **401** displays the designated secondary users, and the principal user associates the selected images, groups or images, or categories of images with specific users. The principal user designates different authorized images for users in different geographic locations and/or authorized lists. The principal user can subsequently log off of the system **100**.

Process for Decorating an Edible Medium

FIGS. **5A-5D** depict an example swim lane diagram of a process **500** for decorating an edible medium. The process **500** can be performed by system **100**, for example, in the online environment in system **100**. Although the process **500** is described with reference to system **100**, other systems, environments, or processors can perform the steps in process **500**. In other implementations, the process **500** for decorating an edible medium may include fewer or more events than shown in FIGS. **5A-5D**.

Referring now to FIG. **5A**, an Internet website includes a number of modules **501-509**. An edible media module **501** is a software module that includes information about which edible media are compatible with the system **100** and characteristics of the individual types of edible media. The edible media module **501** includes a database of unique codes and information on whether or not the particular codes have been used or not.

A user account module **502** is a software module that includes profiles of information regarding particular users. The user account module **502** allows or disallows users to login to user accounts using a username and a password. The user account module **502** also stores financial information and address information about the user and processes financial transactions.

A license module **503** is a software module that includes information about system licensing to certain images. System licensing information may include data identifying where particular images can be sold by geographic location and if and/or how the images may be edited.

An image library module **504** is a software module that includes a searchable and browsable library of images. The image library module **504** also allows the user to upload images from local image sources to use in the system.

An image editing module **505** is a software module that allows a user to edit images. A print module **506** is a software module that provides data to a local control device **128** for printing of selected images onto edible media using a specific color profile for a particular printer. A training module **507** is a software module that includes training content that instructs users to use the system **100**. A user location module **508** is a software module that identifies the geographic location of the user. The user location module **508** can ensure that licensing restrictions are obeyed. In addition, the user location module **508** can allow principal

users to control which images are offered for sale to secondary users in certain geographic zones. A social networking module **509** is a software module that allows a user to access social networking content and resources.

In operation, the user inserts an edible media into the printer. The user accesses the user account module **502** using the GUI **127** and logs into the user's account (**510**) by entering the user's unique username and password. The system **100** displays a menu containing a number of navigation options (**511**).

The user selects the training module **507** to learn how to use the system to decorate edible media (**512**). The training content may be any content that aids the user in using the system. In certain embodiments, the training module **507** may contain video demonstrations, written instructions, and lists of common questions and answers. The user selects the training content for viewing (**513**) and the training module **507** presents the selected training content to the user (**514**).

After viewing the training content, the user can choose an image to use to decorate an edible media (**515**). The user can additionally select an image source. The user may choose a local image source, an online image source, or the image library in the image library module **504**, for example. In this example, the user selects the image library as the image source (**516**).

The system **100** accesses the user location module **508** and determines the geographic location of the user (**517**). In certain configurations, the user location module **508** determines the geographic location by looking up the user's IP address and associating the user's IP address with a geographic location. Other methods of determining the user's geographic location may be used.

After the user's geographic location is determined (**517**), the system **100** accesses the license module **503** and determines whether any licensing restrictions exist for the selected images in the user's geographic location (**518**). For example, the system **100** may determine the user's physical address from an authorization list and verifies whether any licensing restrictions exist. If licensing restrictions exist for the user's geographic location, the system **100** narrows the number of images provided to the user.

If licensing restrictions do not exist for the user or the user's geographic location and/or the user is on an authorized list, the system **100** can provide the user with all licensed images. The system **100** can additionally provide free images, non-copyright images, or third party designed images.

Referring now to FIG. **5B**, upon determining whether licensing restrictions exist, the license module **503** informs the image library module **504** whether any of the images are restricted and/or are on an authorized list that can override restrictions, such as restrictions based on the user's location (**519**). The system **100** identifies whether there are any restrictions from the user account module **502** on the images that the particular user is authorized to purchase (**520**). For example, the particular user may be a secondary user, in which case a principal user may have previously instructed the system **100** which images the secondary user is authorized to purchase. If the particular user has restrictions on which images the user is authorized to purchase, the user account module **502** sends the list of authorized images to the image library module **504** (**521**).

The image library module **504** receives information on which images are available to the particular user from both the user account module **502** and the license module **503**. The image library module **504** restricts access to unauthorized images from the library of image options available to

the user (**522**). The image library module **504** displays to the user a searchable and browsable library of images available to the user for purchase or use (**523**). The user may search through the images, using word searching, or alternatively by browsing through image categories and viewing all images in a category.

The edible media module **501** displays a list of the edible media that may be used with the system **100** (**524**). The image library module **504** then displays the images that are authorized for the user to purchase and that are compatible with the edible media that the user is decorating (**525**). The user selects from the list of edible media the type of edible media that is being decorated (**526**). Examples of options for edible media include but are not limited to standard media with sizes of $\frac{1}{2}$, $\frac{1}{4}$, and $\frac{1}{8}$ sheet, or precut media of sizes 8 inch round, 3 inch round, or 2 inch round, or Designer Prints.

In some implementations, the user can choose to access the social networking module **509** to aid the user in choosing an image. The social networking module **509** can be used in a number of ways. For example, the social networking module **509** may inform the user which of the available images are the most popular overall, the most popular for certain genders or age groups, or the most popular for certain events, such as birthdays, holidays, or other events. The social networking module **509** may include user or consumer reviews of certain images. The social networking module **509** can suggest ways that images can be altered using the image editing module **505**.

Referring now to FIG. **5C**, the user can request to view one or more libraries of images. The image library module **504** displays at least one searchable library of authorized images for the user-selected media type (**527**). In an example of 3D images, the image library module **504** can display a GUI presentation of only the 3D elements and customization of the 3D elements, such as size, color, features that can be merged with user data for a personalized birthday kid (e.g., figurine, etc.), that are compatible with the target printing system. In an example, the image library module **504** can display a rotating or animating presentation of the 3D images (e.g. Graphics Interchange Format or GIF).

The user selects to view social networking options (**528**) and selects a social networking option to view the social networking content (**529**).

The user selects an image (**530**) and instructs the system that the user wishes to purchase the image (**531**). In an example, the user selects an image (**530**) and instructs the system that the user wishes to purchase the image (**531**) by dragging and dropping placement of the image, which can include the grouping of a set of 3D elements such as the set of individual characters (e.g., set of cartoon characters from popular feature film).

The user account module **502** checks to see whether the user has sufficient credit to purchase the image (**532**). If the user does not have sufficient credit, the user has the option of purchasing more credit (**533**). The user is prompted to enter financial information, such as a credit card to be charged or a bank account for direct debit. Alternatively, the user may choose to use previously-entered financial information stored in the user's account in the user account module **502**. In some embodiments, the user may enter address information and request an invoice of a printing/purchasing transaction. In the event that the user has sufficient credit, the user is asked to confirm the purchase. Upon confirmation by the user, the purchase is completed and the credit is deducted from the user's account (**534**).

In some configurations, the user may choose to edit the purchased image (**535**). Editing a purchased image can be

performed using the image editing module **505**. Referring now to FIG. **5D**, the image editing module **505** verifies with the license module **503** that the user is authorized to modify the image. The verification identifies restrictions on editing particular images (**536**). If a license does not prevent the image from being altered, then the user makes desired edits to the image (**537**). The user may be able to crop, rotate, resize, brighten, darken, re-touch, and perform other operations to the selected image. In certain embodiments, the user can save the edited image for later use or continued editing.

The user selects to print the image (**538**). The print module **506** prepares print data and the edible media module **501** prompts the user to enter a code (**539**). The user can find the code (e.g., edible media code) in a location on the edible media, or on the packaging and documentation sent to the user with the edible media.

The user inputs the edible media code (**540**). The edible media module **501** verifies that the inputted code is valid and that the code has not been previously used (**541**).

The user is prompted to input a printer type for use in printing on the edible media (**542**). The image library module **504** stores different versions of the same image that are compatible with different printer color profiles. The print module **506** ensures that an image compatible with the color profile of each selected printer is sent to local control device **128**.

Once the printer information is input, the print module **506** provides the user the option of viewing a preview of the image printed onto the selected edible media. If the user wishes to see a preview, then the image is displayed to the user (**543**). If the user declines, or once the preview has been shown, then the user is asked to confirm the generation of print data. Once the user confirms the print, the print information is sent to the local control device **128**, for printing onto an edible media (**544**). Upon completion of the printing process, the user selects to log off the system (**545**). Alternatively, the user can remain logged on to process additional images to print.

At any point, the user can choose to clear a design in progress or reset the design in progress to a previous state. This option provides the user an efficient mechanism to remove mistakes or simply begin a new design.

Process for Viewing Augmented Reality Content

FIG. **6** is a flowchart diagram of a process **600** for viewing augmented reality content using the system. Although the process **600** is described with reference to system **100**, other systems, environments, or processors can perform the steps in process **600**. The system of FIG. **1A** may be used to print an image containing an embedded augmented reality marker onto an edible media. The user can use the image with the embedded augmented reality marker to access augmented reality content.

The embedded augmented reality marker may be any asymmetrical geometric shape with at least two colors, of sufficiently high contrast to allow the augmented reality marker to be recognized when scanning image frames within a video signal. The augmented reality marker shape is not required to be related to the augmented reality content, but can be any geometric and asymmetrical shape.

The augmented reality content may be any content that combines reality with virtual reality. For example, the augmented reality marker may be embedded in an image of a popular cultural figure or may be the figure itself. The augmented reality content shown to the user could be a display of the cultural figure from the image singing and

dancing on the GUI **127**. In another example, the augmented reality content could be the opportunity to purchase items related to the image, which are otherwise unavailable for purchase.

In another example, the augmented reality content can be a virtual image that is projected on the food product, the edible media, and/or the edible ink. In an aspect, the projector projects different parts of the virtual image based on detection of the augmented reality marker with respect to the food product, the edible media, and the edible ink. In an example the projector projects different parts of the virtual image based on the augmented reality marker on the 3D edible media **160**. For example, the projector can project a first part of the virtual image as a background on the food product and a second part of the virtual image as a two-dimensional or three-dimensional animation on a surface of the 3D edible media. In a particular example, the projector may project a koi fish swimming and jumping in a printed edible media pond.

The system **100** prints an image with an embedded augmented reality marker onto an edible media (**601**). For example, the printing can be performed using the process **500** of FIG. **5**. After printing the image with an embedded augmented reality marker onto the edible media, the system **100** accesses the augmented reality module **218** on the website. In certain implementations, the user enters a web address into the web browser of the local control device **128** and selects the augmented reality module **218**.

The user identifies the video device (**603**). For example, the user instructs the augmented reality module **218** of the source of the incoming video signal. The augmented reality module **218** prompts the user to enter a specific video device location. The augmented reality module **218** may communicate with the local control device **128** to determine which video devices are installed for use on the local control device **128**. In some embodiments, the augmented reality module **218** can display to the user a list of possible video devices for the user to select a particular device. The user selects a video device.

The augmented reality module **218** scans incoming video signal (**604**). The augmented reality module **218** scans the incoming video signal to detect the video signal for a valid augmented reality marker.

The user displays the edible media containing the augmented reality marker to the video device (**605**). The video device thus captures video footage of the augmented reality marker and sends the video signal to the augmented reality module **218** on the system controller.

The augmented reality module **218** recognizes the augmented reality marker (**606**). The augmented reality module **218** can continually or periodically scan incoming video data to detect other valid augmented reality markers. When the user displays an edible media with an augmented reality marker printed upon the media to the video device, the augmented reality module **218** recognizes the marker in the incoming video signal. The augmented reality module **218** responds to the user by displaying augmented reality content (**607**). In an illustrative embodiment, augmented reality content transmitted over network **118** is displayed on the local control device **128**.

Process for Decorating Edible Media with Licensed Digital Image

FIG. **7** is a flow diagram of a process **700** for decorating edible media with licensed digital images. The process **700** can be performed by system **100**, for example, in the online environment in system **100**.

35

The system **100** includes a printing system connected to the Internet which receives an edible medium (**701**). The edible medium may be selected by the user and placed within the system **100**, for example.

The system **100** receives a first user input identifying a user of the system (**702**). For example, a user logs into the system using a username and password. The system **100** determines whether the user is a registered user or a new user (**703**).

The system **100** receives a second user input selecting at least one licensed image (**704**). For example, a user enters a request to select a copyrighted cartoon character for printing on a cake top. In some configurations, the system **100** can limit the available licensed images shown to the user according to the user's geographic location and/or authorization list. The system **100** retrieves the at least one licensed image from an Internet repository (**705**). Upon retrieving the licensed image of the copyrighted cartoon character, the system **100** generates an invoice for the user if the user is a registered user. If the user is an unregistered user or a new user, the system **100** requests payment information to ensure the licensed image is purchased before printing occurs (**706**). Upon verifying payment, the system **100** prints the selected licensed image onto the selected edible medium. In an example, the system **100** prints a 3D edible media **160** based on the selected licensed image. In some implementations, the system **100** enables the user to digitally edit the selected image prior to printing the selected image onto the edible medium.

Process for Printing Selected Image in Software Web Browser

FIG. **8A** is a flow diagram of a process **800a** for printing a selected image in a software web browser. The process **800a** can be performed by system **100**, for example, in the online environment in system **100**.

The system **100** receives a print selected image request (**801**). Either licensed or unlicensed images can be printed using the process **800**.

The print module **212** checks the source of the incoming print request (**802**). In this example, the source is identified as the software web browser. In certain embodiments, the print module **212** checks the source by evaluating identifier packets within a data stream. In other configurations, the print module **212** recognizes network addresses to identify source applications for a particular data packet.

Upon identifying the source of the print request, print module **212** forwards print data over the corresponding secure connection. In this example, print data is forwarded over the secure connection between the software web browser on the local control device **128** and the central control device **132** in system **100** (**803**).

After the software web browser receives print data from print module **212** over a secure connection, the software web browser invokes an internal print environment (**804**).

Based on the software web browser's internal print environment, a particular print driver installed within the operating system on local control device **128** is invoked by the software web browser (**805**). In various implementations, the print driver is implemented by a vendor or manufacturer of the printer, in some cases using proprietary or not publicly documented code.

The invoked print driver generates a byte stream compatible with the target printer **134**, and queues the print task in the operating system's printer spooler (**806**). For example, at **600** vertical dpi (dots per inch), **600** horizontal dpi, 8.5 by

36

11 inches, 4 colors, and 8 bits per color, a 134 Megabyte raw byte stream is created. In certain embodiments, the software web browser's internal print service and the print driver installed on the operating system are based on proprietary or non-documented code. In other configurations, certain elements of the software web browser's internal print service or the print driver installed on the operating system provide an open or documented interface, allowing print data propagated from print module **212** to be modified prior to being delivered to the operating system printer spooler.

The operating system's printer spooler queues print tasks for the particular printer hardware. The operating system can queue multiple print jobs in the spooler while the printer executes tasks on the queue at a throughput dependent on printing configuration and hardware technology. The printer eventually processes the print corresponding to the requested image (**807**). In certain implementations, tasks within the spooler can be rearranged such that the print request corresponding to (**801**) may be processed out of first in first out order.

Process for Printing Selected Image in Parallel Browser Module

FIG. **8B** is a flow diagram of a process **800b** for printing a selected image in parallel browser module. The process **800b** can be performed by system **100**, for example, in the online environment in system **100**.

The system **100** receives a print selected image request (**810**). Either licensed or unlicensed images can be printed using the process **800b**.

The print module **212** checks the source of the incoming print request. In this example, the source is identified as the parallel browser module **244** (**811**). In certain embodiments, the print module **212** checks the source by evaluating identifier packets within a data stream. In other configurations, the print module **212** recognizes network addresses to identify source applications for a particular data packet.

Upon identifying the source of the print request, print module **212** forwards print data over the corresponding secure connection. In this example, the print module **212** forwards print data over the secure connection between the parallel browser module **244** on the local control device **128** and the central control device **132** in system **100** (**812**).

After the parallel browser module **244** receives print data from print module **212** over a secure connection, the parallel browser module **244** bypasses the operating system's printer drivers (**813**) and forwards print data to the color management module **246** (**814**). The color management module **246** applies color correction by converting from the color profile of the image to the color profile of the particular printing device in order to maintain color consistency. In certain implementations, color management module **246** also provides color space conversion, such as between CMYK and RGB, as necessary, and converts to the bit depth required by the printer, such as 8 bits or 16 bits. In some embodiments, color management module **246** also performs linearization and half tone control to improve image reproduction. In an illustrative embodiment, color management module **246** does not entirely rely on operating system color management functions, resulting in an installation independent framework for color management. Color management functions may be implemented in an open source implementation, such as the Little Color Management System (LCMS), or in a proprietary implementation, such as EFI's Colorproof XF software.

37

Color corrected print data is propagated to printer communication module **248**. The printer communication module **248** creates a byte stream compatible with the intended printer, and queues the print task in the operating system's printer spooler (**815**).

The operating system's printer spooler queues print tasks for particular printer hardware to print. The printer eventually processes the print corresponding to the requested image (**816**).

Process for Decorating Edible Medium Using Parallel Browser Module

FIGS. **9A-9D** depict an example swim lane diagram of a process **900** for printing a decoration on an edible medium using the parallel browser module **244** shown in FIG. **2B**. In other configurations, the process **900** for printing a decoration on an edible medium using the parallel browser module **244** may include fewer or more events than shown in FIGS. **9A-9D**. The process **900** can be performed by system **100**, for example, with central control device **132** and local control device **128** connected via network **118**. Although the process **900** is described with reference to system **100**, other systems, environments, or processors can perform the steps in process **900**.

Referring now to FIG. **9A**, a central control device **132** and local control device **128** shown in system **100** includes a number of modules **901-909**. A parallel connection module **901** is a software module that establishes a secondary connection between central control device **132** and local control device **128**. This secondary connection is in parallel with a connection between a software web browser residing on local control device **128** and the central control device **132**.

A user account module **902** is a software module that includes profiles of information regarding particular users. The user account module **902** allows or disallows users to login to user accounts using a username and a password. The user account module **902** also stores financial information and address information about the user and processes financial transactions. Following successful login, central control device **132** provides local control device **128** with user identification data. In some embodiments, parallel web browser module **244** may receive user identification data directly from central control device **132**. In other embodiments, parallel web browser module **244** may receive user identification data through the software web browser.

In certain embodiments, Parallel web browser module **244** receives user identification data through the associated network address identification information, and following reception of user identification data, parallel web browser module **244** remains independently operable from the software web browser during the duration of an active socket connection between parallel web browser module **244** and the software web browser.

In an illustrative embodiment, a valid user login session for parallel web browser module **244** is determined by the inclusion of unexpired user identification data, such as a unique token provided by central control device **132**, in communications between the central control device **132** and local control device **128**.

A license module **903** is a software module that includes information about system licensing to certain images. System licensing information may include data identifying where particular images can be sold and if and/or how the images may be edited.

38

A parallel browser module **904** is a software module that provides a GUI to software modules shown in FIG. **2A**, such as the image library module **202**, which allows the user to upload images from local image sources to use in the system, and the image editing module **204**, which allows a user to edit images. An authentication module **905** is a software module that verifies successful login to the user account module **902** before permitting parallel browser module **904** to establish a connection. A print module **906** is a software module that initiates the printing of selected images onto edible media using a specific color profile for a particular printer. A color management module **907** is a software module that applies color correction algorithms to images provided by print module **906**. A printer communication module **908** is a software module that encodes color corrected output into a byte stream compatible with a particular printer.

Prior to process **900**, the user utilizes a software web browser to log into a secure site, establish an account, and download an application installer. The application installer creates modules including but not limited to the parallel browser module **904**, authentication module **905**, color management module **907**, and printer communication module **908** on the local control device **128**.

Process **900** begins with execution of the authentication module **905** (**910**). Execution can occur manually through the GUI **127**, or automatically through startup events during operating system bootup. Following execution, authentication module **905** enters an inactive state, and is activated manually via GUI **127**, or automatically using a threshold condition such as elapsed time (**911**). Upon activation, authentication module **905** verifies if a secure session with user account module **902** through a software web browser has already been established (**912**). Following detection of no existing secure session with user account module **902**, authentication module **905** initiates an instance of a software web browser residing on local control device **128**. Authentication module **905** causes the new instance of the software web browser to navigate to an Internet website providing access to the user account module **902**, the website displaying a prompt for user login credentials (**915**).

Following successful login, the parallel browser module is activated (**916**). In certain implementations, parallel browser module **904** can be activated from a navigation option shown within the software web browser used for login procedures. In other embodiments, parallel browser module **904** can be activated externally from the software web browser, such as an icon in GUI **127**.

In each method of activating parallel browser module **904**, parallel connection module **901** first establishes a second connection in parallel with the secure connection between the software web browser on local control device **128** and the website server on central control device **132** (**917**). In certain configurations, the second parallel connection is automatically terminated when the first secure connection is terminated. In other implementations, the second connection established by parallel connection module **901** persists after the first secure connection module is terminated.

Referring now to FIG. **9B**, following establishment of a second connection by parallel connection module **901**, parallel browser module **904** displays a menu containing a number of navigation options (**920**). In another embodiment, for instance, when parallel browser module **904** interacts with software modules that the software web browser is not capable of interaction with, parallel browser module **904** displays more navigation options than displayed in the

39

software web browser, such as color correction, page layout, and printer configuration options. In other configurations, independent of if parallel browser module 904 is communicable with more software modules than the software web browser, parallel browser module 904 displays fewer navigation options. In this example, parallel browser module 904 displays options relating to designing edible media, and does not display options available in the software web browser such as subscription information, account management, and customer alerts.

After parallel browser module 904 displays navigation options, the user can choose an image to use to decorate an edible media. The user may choose images from a local image source, an online image source, or the image library in the image library module 202 of FIG. 2A. In this example, the user selects the image library as the image source (921).

The system 100 can perform operations not explicitly shown in FIG. 9A-9D. As one example, the system 100 can access the user location module 214, shown in FIG. 2A, and determine the geographic location of the user. After the user's geographic location is determined, the system 100 can access the license module 903, and determine whether any licensing restrictions exist for images in the user's geographic location. The system 100 narrows the number of images provided to the user in parallel browser module 904 based on licensing restrictions (922).

Parallel browser module 904 displays to the user a searchable and browsable library of images available to the user for purchase or use (923). The user may search through the images, using word searching, or alternatively by browsing through image categories and viewing all images in a category. While not shown in this example, in some embodiments, the user can choose to access the social networking module 216, shown in FIG. 2A, to aid the user in choosing an image.

The user selects an image and instructs the system that the user wishes to purchase the image (924). In some configurations, the user account module 902 prompts the user through parallel browser module 904 to enter financial information, such as a credit card to be charged or a bank account for direct debit. Alternatively, as shown in this example, the user account module 902 operates in the background to utilize payment data associated with the unique username and password used for establishing the first secure connection between the software web browser and web server, without interrupting the process of designing the edible media.

Referring now to FIG. 9C, following image selection, the user selects an edible media type (930). Examples of options for edible media include but are not limited to standard media with sizes of $\frac{1}{2}$, $\frac{1}{4}$, and $\frac{1}{8}$ sheet, or precut media of sizes 8 inch round, 3 inch round, or 2 inch round.

In some implementations, the user may choose to edit the purchased image from within the parallel browser module 904 (931). The user may crop, rotate, resize, stretch to width, stretch to height, brighten, darken, re-touch, and perform other operations to the selected image. The parallel browser module 904 also permits the user to undo operations, navigate back to a previous options interface, or navigate to the next options interface.

In some embodiments, the user may choose to add text to the purchased image (932). In one option, the user can select from a list of phrases, such as "Congratulations," "Bon Voyage," or "Happy Birthday." In another option, the user can type a custom phrase. The user may be able to bend a phrase upwards or downwards to varying degrees of curvature, straighten a phrase, change font type, font color, and

40

select left, right, or centered justification. Furthermore, the user may be able to crop, rotate, resize, stretch to width, stretch to height, brighten, darken, re-touch, and perform other operations to the text independently or in conjunction with the selected image. The parallel browser module 904 also permits the user to undo operations, navigate back to a previous options interface, or navigate to the next options interface.

The user selects print options after the parallel browser module 904 prompts the user for print options, such as number of prints for the particular image (933). Other examples include but are not limited to print orientation, image tiling, and providing grayscale or color options for a given image or print region. Parallel browser module 904 passes on print options to print module 906. In some cases, the user is prompted to input a printer type for use in printing on the edible media.

The image library module 202, shown in FIG. 2A, stores different versions of the same image that are compatible with different printer color profiles. The print module 906 ensures that an image compatible with the color profile of each selected printer is transmitted to the local control device 128 for printing (934).

Upon receiving print data from print module 906 over the secure second connection between local control device 128 and central control device 132, parallel browser module 904 forwards print data to color management module 907 (935).

Referring now to FIG. 9D, color management module 907 applies color correction by converting from the color profile of the image to the color profile of the particular printing device in order to maintain color consistency across devices (940). Color management module 907 provides color correction capabilities to each graphical text, photo, and artwork element, flattening multiple layers into a single bitmap following color correction. Color management module 907 also provides any color space conversion, such as between CMYK and RGB, as necessary (941), and converts to the bit depth compatible with the printer, such as 8 bits or 16 bits (942). Color management module 907 also performs linearization and half tone control to further improve image reproduction (943).

Printer communication module 908 bypasses printer drivers installed in the operating system (944), and instead directly encodes a printer compatible byte stream and appends the byte stream to the printer spooler in the operating system (945). The operating system printer spooler proceeds to execute the print tasks in the queue, resulting in an edible media being printed. The printer communication module 908, together with parallel connection module 901, provides a user rights controlled low-level print management process for the edible media decorating system 100.

At any point in the process of FIG. 9A-D, the user can choose to clear a design in progress or reset the design in progress to a previous state. This option provides the user an efficient mechanism to remove mistakes or simply begin a new design.

Example User Interface Functionality

Any number of User Interface elements can be provided to a user of system 100. The User Interface elements may include multiple screens presented as web pages. As is typical, the GUI 127 in system 100 provides a home screen and various other screens available for user navigation. One example home screen may include user-selectable controls to perform a quick copy of an image, upload or print a

41

photograph, select options such as frames or artwork, generate an order, create a design, and modify system settings.

The quick copy control can be selected by a user to initiate a scanner for uploading an image and quickly copying the image to a system repository. The quick copy control can provide instructions onscreen to the user for accomplishing the quick copy. The instructions may include text, graphics, and/or video content. The instructions can be provided in a user-selectable language.

The upload or print a photograph control can be selected to upload and print a photograph. The photograph control can instruct a user to identify a media source (e.g., scanner, CD, USB, Flash card, web camera, etc.). The photograph control can request that the user verify media settings and upon verification, the control can upload the photograph. The user can choose to edit the uploaded photograph and print the uploaded photograph with applied editing.

Options such as selecting frames or artwork are selected by the user to invoke the system to configure frames and/or artwork for printing. The configuration options can, for example, include verifying original media settings, and selecting a frame or artwork item. The system 100 can retrieve the frame and/or artwork and allow the user to perform edits. The users can additionally edit a particular edible media (e.g., topping) before printing the frame and/or artwork on the edible media.

The order form control can be used to generate an order. For example, users can choose to generate and complete a number of standard order forms. Example order forms include a licensed artwork order form, a licensed frames order form, a general order form, a customer cake order form, and a customer deli order form. In some configurations, users can print an order form and manually request an edible media print or product.

Other controls can be provided to present other information about the system 100 and or inventory available to the system 100. For example, controls can be provided to present inventory management items such as quarterly purchase reports, complete purchase history reports, on-hand inventory reports, and the like.

Another example control can include options or screens for modifying system settings including default color and default fonts. Users may also wish to customize a user account associated with the websites hosted on system 100. For example, a user may wish to change a color scheme or font size when logging into one or more websites hosted on system 100.

Another example control can provide maintenance checklists and tasks for an administrative user. The maintenance controls may only be visible to the administrative user upon login. Other standard system users may not view or access the maintenance controls and/or menus.

In some implementations, the User Interface can provide links to copyright release forms, copyright statement forms or other legal documents. Users can choose to preview and/or print the legal documents on demand.

Example User Interface Tree

FIG. 10 depicts an example User Interface Tree 1000 for a website in a system for decorating edible media, with each node representing a webpage. The hierarchy of the User Interface Tree 1000 shown in FIG. 10 is merely exemplary, with nodes capable of being re-positioned at different hierarchies, divided into separate nodes, or merged into a single node. The labels for nodes are also exemplary of subject matter contained within each webpage. All user interfaces in

42

the User Interface Tree 1000 can be displayed in the software web browser on local control device 128, or certain user interfaces in the User Interface Tree 1000 can be displayed in the software web browser, and other user interfaces in the User Interface Tree 1000 can be displayed in a software environment external to the software web browser, such as the parallel browser module 244.

FIG. 11A depicts an example User Interface 1100a, corresponding to node 1001 of User Interface Tree 1000, for the main page of the system for decorating edible media. FIG. 11A contains a User Interface region 1102 to select between display languages. In certain embodiments, the languages can be selected from a drop down list. In other configurations, the central control device 132 can automatically detect the localization settings of local control device 128 accessing the website, and display a corresponding native language.

FIG. 11A contains a User Interface region 1104 that provides additional details on the various components of the system, such as the printer, scanner, display device, and local control device.

FIG. 11A depicts connectivity to the image library module 202 through User Interface region 1106. A subset of selected images, such as featured, new, or popular images are selected from the overall image library for preview on the User Interface 1100a. A scroll bar is included to enable viewing of images beyond the quantity that can concurrently be shown on User Interface 1100a.

FIG. 11A contains a User Interface region 1108 that provides information on the capabilities and services of the system for decorating edible media, such as a video tutorial of system operation. User Interface 1100a provides a region 1110 with a plurality of navigation choices to other webpages including a Why PhotoCake webpage, a webpage relating to an overview of services of the system for decorating edible media, an Image Library webpage, a webpage for browsing contents of the image library module 202, a Cake Ideas webpage, a webpage relating to examples of outputs of the system for decorating edible media, a Resource Center webpage, a webpage relating to technical support and customer service issues, and a Contact Us webpage, a webpage relating to modes of communication for reaching providers of the services of the system for decorating edible media.

FIG. 11B depicts an example User Interface 1100b, corresponding to a different state of node 1001 of User Interface Tree 1000, for the main page of the system for decorating edible media.

FIG. 11B additionally contains a User Interface region 1112 that prompts for user authentication through a username/password entry region. A region for providing information on account creation is also provided. In certain implementations, the authentication prompt can be a pop-up window overlaid above User Interface 1100b as shown in FIG. 11B. In other embodiments, the authentication prompt can be embedded within the User Interface 1100b.

FIG. 11B may contain a User Interface region 1114 that permits the user, in the event that the user forgets login credentials, to invoke a prompt to input identification information, such as the answer to a preselected security question, a PIN, or an e-mail address, to authenticate the user's request either to reset login credentials, or request secure delivery of login credentials.

FIG. 12 depicts an example User Interface 1200, corresponding to a state of node 1001 of User Interface Tree 1000 after successful login, with a region 1202 showing an updated plurality of navigation choices to other webpages.

43

FIG. 12 also depicts a User Interface region 1204 for signing out of a user account. In certain configurations, after successful login, the User Interface regions relating to login, including but not limited to regions 1112 and 1114 shown in FIG. 11B are removed, and region 1110 is updated with a new plurality of navigation options. For example, the Why PhotoCake webpage can be substituted with a MyPhotoCake webpage, a webpage relating to account management, and the Create Cake webpage can be added, a webpage relating to designing decorative edible media for printing.

FIG. 13 depicts an example User Interface 1300, corresponding to node 1011 of User Interface Tree 1000, for the MyPhotoCake webpage. FIG. 13 provides a region 1302 with a plurality of navigation choices to other webpages. FIG. 13 also depicts a User Interface region 1304 for signing out of a user account. FIG. 13 includes a summary of account information region 1306, which displays information such as account number, expiration, and contact information. FIG. 13 depicts connectivity to the image library module 202 through image library subset display region 1308, which displays a subset of selected images, such as featured, new, or popular images, from the overall image library. An image library search region 1310 is included, allowing user input of keyword or image number to retrieve images from image library module 202. A favorite image library subset display region 1312 provides a thumbnail view of a subset of photos classified as favorites by the logged in user. An alert timeline region 1314 displays a subset of alerts, including version updates, and image credit availability information. A credit and media count availability of region 1316 displays the number of licensed image credits available, and the number of print media available.

FIG. 13 includes an account management region 1318 which contains a plurality of navigation choices to other webpages relating to account management, including Image Use, a webpage displaying historical statistics on images printed on edible media, Consumable Media, a webpage displaying historical statistics on edible media usage, Annual Subscription, a webpage displaying subscription information, Customer Alerts, a webpage relating to his play of alerts, Change Password, a webpage relating to password management, and Order Form, a webpage relating to purchasing of edible media.

FIG. 14 depicts an example User Interface 1400, corresponding to node 1021 of User Interface Tree 1000, for the Image Use webpage. FIG. 14 provides a region 1402 with a plurality of navigation choices to other webpages. FIG. 14 also depicts a User Interface region 1404 for signing out of a user account. A favorite image library subset display region 1406 provides a thumbnail view of a subset of photos classified as favorites by the logged in user. An alert timeline region 1408 displays a subset of alerts, including version updates, and image credit availability information. A credit and media count availability region 1410 displays the number of licensed image credits available, and the number of print media available. FIG. 14 includes an account management region 1412, which contains a plurality of navigation choices to other webpages relating to account management, including Image Use, Consumable Media, Annual Subscription, Customer Alerts, Change Password, and Order Form webpages.

FIG. 14 includes a purchase history region 1414, which allows a user to input the date range to display purchase history information. Purchase history filter region 1416 allows a user to input the choice of filtering purchase history by date or by image number. Purchase history display region 1418 displays a tabular representation of information relat-

44

ing to date of image use, image number, text description of image, number of credits utilized, and cost of utilization.

FIG. 15 depicts an example User Interface 1500, corresponding to node 1022 of User Interface Tree 1000, for the Consumable Media webpage. FIG. 15 provides a region 1502 with a plurality of navigation choices to other webpages. FIG. 15 also depicts a User Interface region 1504 for signing out of a user account. A favorite image library subset display region 1506 provides a thumbnail view of a subset of photos classified as favorites by the logged-in user. An alert timeline region 1508 displays a subset of alerts, including version updates, and image credit availability information. A credit and media count availability of region 1510 displays the number of licensed image credits available, and the number of print media available. FIG. 15 includes an account management region 1512, which contains a plurality of navigation choices to other webpages relating to account management, including Image Use, Consumable Media, Annual Subscription, Customer Alerts, Change Password, and Order Form webpages.

FIG. 15 also includes a media access code entry region 1514, which allows a user to enter a unique code corresponding to purchased edible media in order to increase the number of available prints to a user. Redemption history region 1516 allows a user to input the date range to display redemption history information. Redemption history display region 1518 displays a tabular representation of information relating to date of edible media redemption, media code number, and a text description of edible media type.

FIG. 16 depicts an example User Interface 1600, corresponding to node 1023 of User Interface Tree 1000, for the Annual Subscription webpage. FIG. 16 provides a region 1602 with a plurality of navigation choices to other webpages. FIG. 16 also depicts a User Interface region 1604 for signing out of a user account. A favorite image library subset display region 1606 provides a thumbnail view of a subset of photos classified as favorites by the logged in user. An alert timeline region 1608 displays a subset of alerts, including version updates, and image credit availability information. A credit and media count availability of region 1610 displays the number of licensed image credits available, and the number of print media available. FIG. 16 includes an account management region 1612, which contains a plurality of navigation choices to other webpages relating to account management, including Image Use, Consumable Media, Annual Subscription, Customer Alerts, Change Password, and Order Form webpages.

FIG. 16 also includes an account expiration date region 1614, which displays when the currently active subscription is targeted to expire. Subscription history display region 1616 displays a tabular representation of information including date of subscription, cost of subscription, subscription years purchased, and account expiration date corresponding to subscription type purchase.

FIG. 17 depicts an example User Interface 1700, corresponding to node 1024 of User Interface Tree 1000, for the Customer Alerts webpage. FIG. 17 provides a region 1702 with a plurality of navigation choices to other webpages. FIG. 17 also depicts a User Interface region 1704 for signing out of a user account. A favorite image library subset display region 1706 provides a thumbnail view of a subset of photos classified as favorites by the logged in user. An alert timeline region 1708 displays a subset of alerts, including version updates, and image credit availability information. A credit and media count availability of region 1710 displays the number of licensed image credits available, and the number of print media available. FIG. 17 includes an account

45

management region **1712**, which contains a plurality of navigation choices to other webpages relating to account management, including Image Use, Consumable Media, Annual Subscription, Customer Alerts, Change Password, and Order Form webpages.

FIG. **17** also includes a customer alert history display region **1714**, which displays a tabular representation of information including date of customer alert, and a text description of the customer alert.

FIG. **18** depicts an example User Interface **1800**, corresponding to node **1025** of User Interface Tree **1000**, for the Change Password webpage. FIG. **18** provides a region **1802** with a plurality of navigation choices to other webpages. FIG. **18** also depicts a User Interface region **1804** for signing out of a user account. A favorite image library subset display region **1806** provides a thumbnail view of a subset of photos classified as favorites by the logged in user. An alert timeline region **1808** displays a subset of alerts, including version updates, and image credit availability information. A credit and media count availability of region **1810** displays the number of licensed image credits available, and the number of print media available. FIG. **18** includes an account management region **1812**, which contains a plurality of navigation choices to other webpages relating to account management, including Image Use, Consumable Media, Annual Subscription, Customer Alerts, Change Password, and Order Form webpages.

FIG. **18** also includes a password update region **1814**, which prompts a user for the current, new, and a confirmation of a new password.

FIG. **19** depicts an example User Interface **1900**, corresponding to node **1026** of User Interface Tree **1000**, for the Order Form webpage. FIG. **19** provides a region **1902** with a plurality of navigation choices to other webpages. FIG. **19** also depicts a User Interface region **1904** for signing out of a user account. A favorite image library subset display region **1906** provides a thumbnail view of a subset of photos classified as favorites by the logged in user. An alert timeline region **1908** displays a subset of alerts, including version updates, and image credit availability information. A credit and media count availability of region **1910** displays the number of licensed image credits available, and the number of print media available. FIG. **19** includes an account management region **1912**, which contains a plurality of navigation choices to other webpages relating to account management, including Image Use, Consumable Media, Annual Subscription, Customer Alerts, Change Password, and Order Form webpages.

FIG. **19** also includes an itemized order form region **1914**, which displays the items for purchase, such as licensed image credits and annual subscription renewals, along with respective unit prices and quantities. Region **1916** prompts the user for billing information to provide payment for the order described by region **1914**.

FIG. **20** depicts an example User Interface **2000**, corresponding to node **1031** of User Interface Tree **1000**. In certain implementations, User Interface **2000** can be displayed in the same web browser used to access the User Interface **1100a**. In other embodiments, User Interface **2000** can be displayed in an external software application from the software web browser, as shown in this example. The software web browser and the external application can run concurrently on the local control device **128**, and the external software application can be installed on local control device **128** prior to the user login process on User Interface **1100a**, or can be prompted for download when navigating to the Create Cake webpage for the first time. In configurations

46

that use the external software application to display the Create Cake User Interface **2000**, a separate parallel secure connection by the external software application can be established between the local control device **128** and central control device **132** to allow secure remote access of licensed images in the image library module **202**.

The User Interface **2000** contains a region **2002** to select between display languages. Region **2004** displays the subscriber's name, software version, number of licensed image credits available, and the number of print media available. Region **2006** provides a navigation option to return to the software web browser to display the User Interface **1300** for the MyPhotoCake webpage. Region **2008**, shown without a text label in this example, provides a quick link to a webpage in a software web browser providing technical support and frequently asked questions relating to the User Interface **2000**. In alternative implementations, region **2008** can include a text label.

The User Interface **2000** also contains a region **2010** for the user to choose what to print on a topping, including Photo, Image, and Frame+Photo sources.

FIG. **21** depicts an example User Interface **2100**, corresponding to node **1041** of User Interface Tree **1000**, displayed when the user chooses the option to print a topping with the Photo type. User Interface **2100** includes a region **2102** to select between display languages. Region **2104** displays the subscriber's name, software version, number of licensed image credits available, and the number of print media available. Region **2106** provides a navigation option to return to the software web browser to display the User Interface **1300** for the MyPhotoCake webpage. Region **2108** provides a quick link to a webpage in a software web browser providing technical support and frequently asked questions relating to the User Interface **2000**. Region **2110** provides the option to navigate backwards or forwards within the Create Cake User Interface sequence. User Interface **2100** also includes a local file selection region **2112** for allowing a user to select an image file stored on or accessible by local control device **128**.

FIG. **22** depicts an example User Interface **2200**, corresponding to node **1042** of User Interface Tree **1000**, displayed after the user has completed local image file selection following user selection of the option to print a topping with the Photo type. User Interface **2200** includes a region **2202** to select between display languages. Region **2204** displays the subscriber's name, software version, number of licensed image credits available, and the number of print media available. Region **2206** provides a navigation option to return to the software web browser to display the User Interface **1300** for the MyPhotoCake webpage. Region **2208** provides a quick link to a webpage in a software web browser providing technical support and frequently asked questions relating to the User Interface **2000**. Region **2210** provides the option to navigate backwards or forwards within the Create Cake User Interface sequence. User Interface **2200** also includes a photo editing region **2212**, which allows modifications to the selected local file image. Editing capabilities include, but are not limited to, maximizing width, maximizing height, cropping to various shapes, and converting to grayscale. User Interface **2200** also includes manual photo editing region **2214**, which allows a user to use a point-and-click interface to edit a photo, such as cropping.

FIG. **23**, corresponding to node **1043** of User Interface Tree **1000**, depicts an example User Interface **2300** displayed for selecting topping configuration. In the example User Interface Tree **1000** of FIG. **10**, User Interface **2300** is

a common user interface for the Photo, Image, and Frame+Photo print types, as depicted by the branches converging on node **1052** in FIG. **10**.

User Interface **2300** includes a region **2302** to select between display languages. Region **2304** displays the subscriber's name, software version, number of licensed image credits available, and the number of print media available. Region **2306** provides a navigation option to return to the software web browser to display the User Interface **1300** for the MyPhotoCake webpage. Region **2308** provides a quick link to a webpage in a software web browser providing technical support and frequently asked questions relating to the User Interface **2000**. Region **2310** provides the option to navigate backwards or forwards within the Create Cake User Interface sequence. User Interface **2300** also includes a topping selection region **2312** which provides multiple topping options including but not limited to standard media with sizes of $\frac{1}{2}$, $\frac{1}{4}$, and $\frac{1}{8}$ sheet, or precut media of sizes 8 inch round, 3 inch round, or 2 inch round. User Interface **2300** also includes topping selection preview region **2314**, which allows a user to preview changes to the image based on a selected topping configuration in real-time.

FIG. **24** depicts an example User Interface **2400**, corresponding to node **1044** of User Interface Tree **1000**, displayed for editing a topping following selection of a topping in User Interface **2300**. User Interface **2400** includes a region **2402** to select between display languages. Region **2404** displays the subscriber's name, software version, number of licensed image credits available, and the number of print media available. Region **2406** provides a navigation option to return to the software web browser to display the User Interface **1300** for the MyPhotoCake webpage. Region **2408** provides a quick link to a webpage in a software web browser providing technical support and frequently asked questions relating to the User Interface **2000**. Region **2410** provides the option to undo or redo topping edits, and to navigate backwards or forwards within the Create Cake User Interface sequence.

User Interface **2400** also includes a topping editing region **2412**, which provides multiple topping editing options. Editing options include, but are not limited to crop, rotate, resize, stretch to width and stretch to height.

Editing options also include the choice to add text. The user can select from a list of phrases, such as "Congratulations," "Bon Voyage," or "Happy Birthday," or the user can type a custom phrase. The user may be able to bend a phrase upwards or downwards to varying degrees of curvature, straighten a phrase, change font type, font color, and select left, right, or centered justification.

User Interface **2400** also includes topping editing preview region **2414**, which allows a user to preview changes to the image based on a selected edits in real-time.

FIG. **25** depicts an example User Interface **2500**, corresponding to node **1045** of User Interface Tree **1000**, displayed for print editing following topping editing User Interface **2400**. User Interface **2500** includes a region **2502** to select between display languages. Region **2504** displays the subscriber's name, software version, number of licensed image credits available, and the number of print media available. Region **2506** provides a navigation option to return to the software web browser to display the User Interface **1300** for the MyPhotoCake webpage. Region **2508** provides a quick link to a webpage in a software web browser providing technical support and frequently asked questions relating to the User Interface **2000**. Region **2510** provides the option to navigate backwards or to initiate the print process of the final design. User Interface **2500** also

includes a print configuration region **2512**, which provides the user print options, such as the number of prints for the particular image.

FIG. **26** depicts an example User Interface **2600**, corresponding to node **1051** of User Interface Tree **1000**, displayed for selecting a frame from a frame image. As shown in the exemplary User Interface Tree of FIG. **10**, the sequence of User Interface displays for creating a topping involving the Frame+Photo Type is similar with the exception of the additional User Interface **2600** for Frame image selection preceding User Interface **2100** for local image file selection.

User Interface **2600** includes a region **2602** to select between display languages. Region **2604** displays the subscriber's name, software version, number of licensed image credits available, and the number of print media available. Region **2606** provides a navigation option to return to the software web browser to display the User Interface **1300** for the MyPhotoCake webpage. Region **2608** provides to the user a searchable and browsable library of frame images available to the user. The user may search through the frame images, using word searching, or alternatively by browsing through image categories and viewing all images in a category. Region **2610** provides a scrollable region displaying thumbnails of frame images available to the user based on search results or selected categories from region **2608**. To select a particular frame image, the user clicks on a thumbnail displayed in region **2610**. Following selection of a particular frame image, the User Interface **2100** of FIG. **21** is displayed for the purposes of selecting the local image file to be displayed within the framed area. Subsequent User Interface displays for creating a print of the Frame+Photo type proceeds in the same sequence as for the Photo type, as described earlier in regards to discussion of nodes **1041-1045** of User Interface Tree **1000**.

FIG. **27** depicts an example User Interface **2700**, corresponding to node **1061** of User Interface Tree **1000**, displayed for selecting an image from Image Library Module **202** following user selection of the Image type print in User Interface **2000**. As shown in the exemplary User Interface Tree of FIG. **10**, the sequence of User Interface displays for creating a topping involving the Image type is similar to creating a Photo type print with the exception that following Image selection in User Interface **2700**, the User Interface display sequence proceeds to User Interface **2300** for topping selection, bypassing photo selection User Interface **2100** and photo editing User Interface **2200**.

User Interface **2700** includes a region **2702** to select between display languages. Region **2704** displays the subscriber's name, software version, number of licensed image credits available, and the number of print media available. Region **2706** provides a navigation option to return to the software web browser to display the User Interface **1300** for the MyPhotoCake webpage. Region **2708** provides to the user a searchable and browsable library of images available to the user. The user may search through the images, using word searching, or alternatively by browsing through image categories and viewing all images in a category. Region **2710** provides a scrollable region displaying thumbnails of images available to the user based on search results or selected categories from region **2708**. To select a particular image, the user clicks on a thumbnail displayed in region **2710**. Following selection of a particular image, the User Interface **2100** of FIG. **21** is displayed for the purposes of selecting the local image file. Subsequent User Interface displays for creating a print of the Image type proceeds in

the same sequence as described earlier in regards to discussion of nodes **1043-1045** of User Interface Tree **1000**.

FIG. **28** depicts an example User Interface **2800**, corresponding to node **1013** of User Interface Tree **1000**, for the Image Library webpage. FIG. **28** provides a region **2802** with a plurality of navigation choices to other webpages. FIG. **28** also depicts a User Interface region **2804** for signing out of a user account. A region **2806** provides the option to only display images of the frame image type.

Region **2810** provides to the user a searchable and browsable library of images available to the user. The user may search through the images, using word searching, or alternatively by browsing through image categories and viewing all images in a category. Prior to entering a search term or category selection, region **2808** provides separate scrollable row regions displaying thumbnails of images corresponding to Featured, New, and Popular Images available to the user. Following entering a search term or category selection, region **2808** is replaced with a single scrollable region displaying a matrix of thumbnails corresponding to search or category selection results. New images in the Image Library Module **202** are labeled with a NEW marker on the respective thumbnails.

For each thumbnail, when the user performs a mouse-over, the thumbnail is overlaid with details, such as an image title and/or price, as shown in region **2902** of FIG. **29**. When the user performs a click action on a thumbnail, a pop-up window appears, providing ever further information on the selected image, such as copyright information, and the option to Add to Favorites, or Create this Cake corresponding to the clicked image, as shown in region **2904** of FIG. **29**. The Create this Cake option in FIG. **29** takes the user to the User Interface **2300**, as depicted by the converging branches on node **1052** in FIG. **10**.

FIG. **30** depicts an example User Interface **3000**, corresponding to node **1014** of User Interface Tree **1000**, for the Cake Ideas webpage. FIG. **30** provides a region **3002** with a plurality of navigation choices to other webpages. FIG. **30** also depicts a User Interface region for signing out of a user account **3004**.

Region **3008** provides to the user a searchable and browsable library of exemplary cake designs available to the user. The user may search through the cake designs, using word searching, or alternatively by browsing through design categories and viewing all cake designs in a category. Prior to entering a search term or category selection, region **3006** provides separate scrollable row regions displaying thumbnails of cake designs corresponding to Featured and New designs available to the user. Following entering a search term or category selection, region **3006** is replaced with a single scrollable region displaying a matrix of thumbnails corresponding to search or category selection results. New cake designs are labeled with a NEW marker on the respective thumbnails.

Similar to the Create Cake webpage, for each thumbnail, when the user performs a mouse-over, the thumbnail is overlaid with details, such as a descriptive title. When the user performs a click action on a thumbnail, a pop-up window appears, providing ever further information on the selected image, such as the item number and the image used, and the option to Create Cake corresponding to the clicked image. The Create Cake option takes the user to the User Interface **2300**, as depicted by the converging branches on node **1052** in FIG. **10**.

FIG. **31** depicts an example User Interface **3100**, corresponding to node **1015** of User Interface Tree **1000**, for the Resource Center webpage. FIG. **31** provides a region **3102**

with a plurality of navigation choices to other webpages. FIG. **31** also depicts a User Interface region **3104** for signing out of a user account **3104**. FIG. **31** further provides a drop down menu region **3106** containing a plurality of navigation choices to other webpages, such as Frequently Asked Questions or Technical Requirements. FIG. **31** also depicts a User Interface region for signing out of a user account **3104**. Region **3108** provides a preview of common questions, such as how to create and save favorites, and upload images, in this example. A region **3110** provides alternative navigation options to either Frequently Asked Questions or Technical Requirements, with additional explanation of each link.

FIG. **32** depicts an example User Interface **3200**, corresponding to node **1016** of User Interface Tree **1000**, for the Contact Us webpage. FIG. **32** provides a region **3202** with a plurality of navigation choices to other webpages. FIG. **32** also depicts a User Interface region **3204** for signing out of a user account. FIG. **32** further provides a region **3206** with a user entry form for providing contact information at which operators of the online system for decorating edible media may contact the user. Region **3206** also provides for similar user entry form for providing contact information relating to general inquiries, and for technical support. FIG. **32** also includes a region **3208** for accessing a Why PhotoCake webpage, a webpage relating to an overview of services of the system for decorating edible media. FIG. **32** additionally may include a region **3210** for accessing a webpage for ordering inventory items for a system owner (e.g., a bakery owner, store owner), such as edible media, edible ink, replacement parts, printheads, and other system supplies.

FIG. **33** is a schematic diagram of a generic computer system **3300**. The system **3300** is optionally used for the operations described in association with any of the computer-implement methods described previously, according to one implementation. The system **3300** includes a processor **3310**, a memory **3320**, a storage device **3330**, and an input/output device **3340**. Each of the components **3310**, **3320**, **3330**, and **3340** are interconnected using a system bus **3350**. The processor **3310** is capable of processing instructions for execution within the system **3300**. In one implementation, the processor **3310** is a single-threaded processor. In another implementation, the processor **3310** is a multi-threaded processor. The processor **3310** is capable of processing instructions stored in the memory **3320** or on the storage device **3330** to display graphical information for a User Interface on the input/output device **3340**.

The memory **3320** stores information within the system **3300**. In one implementation, the memory **3320** is a computer-readable medium. In one implementation, the memory **3320** is a volatile memory unit. In another implementation, the memory **3320** is a non-volatile memory unit.

The storage device **3330** is capable of providing mass storage for the system **3300**. In one implementation, the storage device **3330** is a computer-readable medium. In various different implementations, the storage device **3330** is optionally a floppy disk device, a hard disk device, an optical disk device, or a tape device.

The input/output device **3340** provides input/output operations for the system **3300**. In one implementation, the input/output device **3340** includes a keyboard and/or pointing device. In another implementation, the input/output device **3340** includes a display unit for displaying Graphical User Interfaces.

In some examples, the features described are implemented in digital electronic circuitry, or in computer hardware, firmware, software, or in combinations of them. The apparatus is optionally implemented in a computer program

51

product tangibly embodied in an information carrier, e.g., in a machine-readable storage device or in a propagated signal, for execution by a programmable processor; and method steps are performed by a programmable processor executing a program of instructions to perform functions of the described implementations by operating on input data and generating output. The described features are optionally implemented advantageously in one or more computer programs that are executable on a programmable system including at least one programmable processor coupled to receive data and instructions from, and to transmit data and instructions to, a data storage system, at least one input device, and at least one output device. A computer program is a set of instructions that are optionally used, directly or indirectly, in a computer to perform a certain activity or bring about a certain result. A computer program is optionally written in any form of programming language, including compiled or interpreted languages, and it is deployed in any form, including as a stand-alone program or as a module, component, subroutine, or other unit suitable for use in a computing environment.

Suitable processors for the execution of a program of instructions include, by way of example, both general and special purpose microprocessors, and the sole processor or one of multiple processors of any kind of computer. Generally, a processor will receive instructions and data from a read-only memory or a random access memory or both. The essential elements of a computer are a processor for executing instructions and one or more memories for storing instructions and data. Generally, a computer will also include, or be operatively coupled to communicate with, one or more mass storage devices for storing data files; such devices include magnetic disks, such as internal hard disks and removable disks; magneto-optical disks; and optical disks. Storage devices suitable for tangibly embodying computer program instructions and data include all forms of non-volatile memory, including by way of example semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The processor and the memory are optionally supplemented by, or incorporated in, ASICs (application-specific integrated circuits).

To provide for interaction with a user, the features in some instances are implemented on a computer having a display device such as a CRT (cathode ray tube) or LCD (liquid crystal display) monitor for displaying information to the user and a keyboard and a pointing device such as a mouse or a trackball by which the user provides input to the computer.

The features are optionally implemented in a computer system that includes a back-end component, such as a data server, or that includes a middleware component, such as an application server or an Internet server, or that includes a front-end component, such as a client computer having a Graphical User Interface or an Internet browser, or any combination of them. The components of the system are connected by any form or medium of digital data communication such as a communication network. Examples of communication networks include, e.g., a LAN, a WAN, and the computers and networks forming the Internet.

The computer system optionally includes clients and servers. A client and server are generally remote from each other and typically interact through a network, such as the described one. The relationship of client and server arises by

52

virtue of computer programs running on the respective computers and having a client-server relationship to each other.

A number of implementations have been described. Nevertheless, it will be understood that various modifications are optionally made without departing from the spirit and scope of this disclosure. Accordingly, other embodiments are within the scope of the following claims.

The invention claimed is:

1. A system for printing images on edible base media, comprising:

a plurality of local control devices, wherein

each local control device is remotely located relative to a central server and each of the other local control devices, and

each local control device of the plurality of local control devices is operated by a different user of a plurality of users;

the central server including processing circuitry configured to

receive a plurality of print options and a plurality of images, wherein the print options and images are uploaded to the central server from at least one of the plurality of local control devices and at least one image source,

access a unique code to determine whether a particular edible medium is authorized edible media by determining whether the user has exceeded an allocated number of prints corresponding to that particular edible media, and

prepare, using the plurality of print options and the plurality of images, a plurality of print data sets; and

a plurality of edible media printers, each edible media printer being uniquely assigned to and in communication with a respective local control device of the plurality of local control devices, wherein

each edible media printer is equipped with edible ink and specially configured to print on edible base media;

wherein each local control device comprises processing circuitry configured to

receive a print data set from at least one of the central server and the at least one image source, and

cause printing of edible ink by an assigned edible media printer of the plurality of edible media printers upon edible base media.

2. The system of claim 1, wherein the central server provides different sets of users of a plurality of users access to different sets of images of a plurality of sets of images for printing on the edible base media,

wherein a particular user of the plurality of users is denied access to a particular set of images of the plurality of sets of images based on at least one of a geographic location of the particular user and a lack of authorization of the particular user.

3. The system of claim 2, wherein the central server maintains a profile for each user of the plurality of users.

4. The system of claim 1, wherein the processing circuitry of each local control device is further configured to:

responsive to receiving the print data set, invoke an internal print environment; and

generate, by the internal print environment, a print file based on the print data, the print file including a representation of the selected image;

wherein causing printing comprises transmitting, from the local control device to the assigned edible media printer via a communications link, the print file.

5. The system of claim 4, wherein:

the internal print environment comprises a printer communication module; and

generating the print file comprises

bypassing an operating system printer driver, and 5

generating a byte stream compatible with the edible media printer.

6. The system of claim 1, wherein the plurality of print options comprise at least one editing option for editing the selected image. 10

7. The system of claim 6, wherein the at least one editing option comprises at least one of cropping, rotating, resizing, brightening, darkening, re-touching, stretching, and adding a text message.

8. The system of claim 1, wherein the at least one image source includes at least one of a mobile device, a remote storage repository, a digital image storage, and a social network. 15

* * * * *