



US010216865B1

(12) **United States Patent**
Theobald

(10) **Patent No.:** **US 10,216,865 B1**
(45) **Date of Patent:** **Feb. 26, 2019**

- | | |
|--|--|
| (54) MONITORING ONE OR MORE ARTICLES ON A SUPPORT SURFACE | 6,370,222 B1 * 4/2002 Cornick, Jr. G01V 5/0016
378/57 |
| (71) Applicant: Vecna Technologies, Inc. , Cambridge, MA (US) | 7,233,682 B2 * 6/2007 Levine G06Q 50/32
378/57 |
| (72) Inventor: Daniel Theobald , Sommerville, MA (US) | 7,415,613 B2 * 8/2008 Impson et al. 713/176
7,422,149 B2 * 9/2008 Aptekar G06Q 10/08
235/385 |
| (73) Assignee: VECNA ROBOTICS, INC. , Cambridge, MA (US) | 7,719,222 B2 5/2010 Theobald
7,798,402 B2 * 9/2010 Bochicchio 235/385
7,896,113 B1 3/2011 Ramirez
7,927,063 B2 4/2011 Keenan et al.
8,094,781 B1 * 1/2012 Safai et al. 378/87
8,538,577 B2 * 9/2013 Bell et al. 700/215 |
| (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 148 days. | 2002/0156645 A1 10/2002 Hansen
2005/0131645 A1 6/2005 Panopoulos
2008/0077511 A1 * 3/2008 Zimmerman 705/28
2008/0089477 A1 * 4/2008 Eshed G01N 23/04
378/57 |
| (21) Appl. No.: 13/678,193 | 2011/0071677 A1 3/2011 Stilman
2013/0110281 A1 * 5/2013 Jones G06Q 50/28
700/228 |
| (22) Filed: Nov. 15, 2012 | |

Related U.S. Application Data

- (60) Provisional application No. 61/607,319, filed on Mar. 6, 2012.
- (51) **Int. Cl.**
G06F 17/50 (2006.01)
- (52) **U.S. Cl.**
CPC **G06F 17/50** (2013.01)
- (58) **Field of Classification Search**
CPC G06Q 10/08; G06Q 20/203; G01N 23/04;
G01N 23/203; G06K 2209/09; G06K
9/3233; G06K 9/6814; G06K 9/746;
G04F 17/50
USPC 703/2; 705/22, 28; 318/568.11
See application file for complete search history.

References Cited

U.S. PATENT DOCUMENTS

- 3,785,669 A 1/1974 Doheny
6,194,860 B1 * 2/2001 Seelinger et al. 318/587

OTHER PUBLICATIONS

Yaman, H., Manufacturer's mixed pallet design problem, European Journal of Operational Research 186 (2008) 826-840.*


(Continued)

Primary Examiner — Brian S Cook

(57) **ABSTRACT**

Devices, systems and methods are provided for monitoring a plurality of articles that are arranged on a support surface according to an article arrangement modeled with a first processing device. One of the methods includes receiving image data generated from the modeled article arrangement. The image data is received by a second processing device, and is indicative of an image of the arranged articles on the support surface. The received image data is used to inspect the arranged articles.

8 Claims, 7 Drawing Sheets



(56)

References Cited

OTHER PUBLICATIONS

AIDCO International: AIDCO robot palletizing for building mixed product pallets, May 12, 2009 <https://www.youtube.com/watch?v=1khQAnGDCSo>.*

James, R.J.W., Three Dimensional Container Packing for Drums and Pallets, University of Canterbury, New Zealand, 1999.*

Moura, A. "A Grasp Approach to the Container-Loading Problem." IEEE Intelligent Systems 20.4 (2005): 50-57.*

Terno, J., An Efficient Approach for the Multi-Pallet Loading Problem, Institute of Numerical Mathematics, Technical University Dresden Mommsenstr. 13, D-01062 Dresden, Germany Oct. 15, 1997.*

Schlenoff, C., Performance Evaluation of Intelligent Systems at the National Institute of Standards and Technology (NIST) ITEA Journal 2011; 32: 59-67.*

Whelan, P.F., Automated Packing Systems—A Systems Engineering Approach IEEE Transactions on Systems, Man, and Cybernetics—Part A: Systems and Humans, vol. 26, No. 5, Sep. 1996.*

Leonardo: Robotic Pallet Wrapper Operation Book, Model: Robospir Leonardo, Apr. 2005.*

Robopac, Stretch Wrapping Website, <http://web.archive.org/web/201109032059/http://www.althika.ae/robopac.html>.*

Hvilshoj, M., The Mobile Robot "Little Helper": Concepts, ideas and working principles, IEEE 2009.*

Garibotto, G., Industrial Exploitation of Computer Vision in Logistic Automation: Autonomous Control of an Intelligent Forklift Truck, Proceedings of the 1998 IEEE International Conference on Robotics & Automation Leuven, Belgium, May 1998.*

Kahn, Z., Robot Based Logistics System for Hospitals—Survey. In IDT Workshop on Interesting Results in Computer Science and Engineering, 2008.*

Baldassari, E., Vecna's QC Bot, <https://www.youtube.com/watch?v=-gZdHNmX2KY> Apr. 20, 2011.*

Wiki Archive Page dated Nov. 15, 2011: Battlefield Extraction—Assist Robot.*

Overview BEAR Robot dated 2010 <https://www.youtube.com/watch?v=8rdRxV-qn3w>.*

Episode 2 BEAR Robot dated 2009 <https://www.youtube.com/watch?v=0RuVidE73Y8>.*

Episode 1 BEAR Robot dated 2009 <https://www.youtube.com/watch?v=irvDKCszJxk>.*

Rosen, J., Surgical Robotics: Systems Applications and Visions, Springer Science & Business Media, 2011.*

Gilbert, G.R., United States Department of Defense Research in Robotic Unmanned Systems for Combat Casualty Care, 2010.*

Tanner, H.G., Advanced Agricultural Robots: Kinematics and Dynamics of Multiple Mobile Manipulators Handling Non-Rigid Materials, Computers and Electronics in Agriculture 31 (2001) 91-105.*

Hvilshoj, M., "Little Helper"—An Autonomous Industrial Mobile Manipulator Concept, International Journal of Advanced Robotics Systems, vol. 8, No. 2 (2011) p. 80-90.*

Steidle, D., et al Stable Stacking for the Distributors Pallet Packing Problem, IEEE/RSJ International Conference on Intelligent Robots and Systems, Oct. 18-22, 2010, Taipei Taiwan.*

Fiorini, P., et al An Autonomous Robot for Indoor Light Logistics, Proceedings 2004 IEEE/RSJ International Conference on Intelligent Robots and Systems Sep. 26-Oct. 2, 2004, Sendai, Japan.*

Frost, T., Automated Shipboard Build-up of Customized Pallet Loads, Navy SBIR 2010.1—Topic N101-091 Dec. 10, 2009 http://www.navysbir.com/n10_1/N101-091.htm.*

Balakirsky_2010 (Metrixis for Mixed Pallet Stacking, PERMIS' 10 Sep. 28-30, 2010 Baltimore, MD USA).*

Rantan_2011 (Securing Images Using Inversion and Shifting, Proceedings of the International Conference on Soft Computing for Problem Solving (SocProS 2011) Dec. 20-22, 2011—vol. 2).*

Amin_1995 (The Lack of Protection Afforded Software under the Current Intellectual Property Laws, Cleveland State Law Review, 1995).*

Machine Vision defined by Wikipedia archived Jan. 15, 2012 downloaded from https://en.wikipedia.org/w/index.php?title=Machine_vision&oldid=471584781.*

Tomlinson_2009 (History and Impact of the Intermodal Shipping Container, Pratt Institute, Sep. 22, 2009).*

James_1999 (H.T. Dean, J. N. Baggaley and R.J.W. James, Three Dimensional Container Packing of Drums and Pallets, University of Canterbury, New Zealand, 1999).*

Kamlang_2008 (On the Government of Electronic Bills of Lading, University of Oslo, Sep. 4, 2008).*

Bao_2012 (Object Co-detection, (S. Y.-Z. Bao, Y. Xiang, and S. Savarese, "Object co-detection," in Proc. Eur. Conf. Comput. Vision, Firenze, Italy, Oct. 7-13, 2012).*

Frost (Automated Shipboard Build-up of Customized Pallet Loads, Dec. 10, 2009.*

Fiorini (An Autonomous Robot for Indoor Light Logistics, 2004).*

Schlenoff_2011 (Performance Evaluation of Intelligent Systems at the National Institute of Standards and Technology (NIST), ITEA Journal 2011; 32: 59-67).*

DARPA_2007 (DARPA Grand Challenge: Urban Challenge Rules, Oct. 27, 2007).

Templeton 2011 (Deliverbots—self-driving delivery robots <https://www.templetons.com/brad/robocars/deliverbots.html> archived Feb. 9, 2011).

Fraizer_2011 (ARMADA: Autonomous Robotic Mail and Delivery Assistant, Dept. of CIS—Senior Design 2010-2011).

TEUN_2009 (The Best Way to Unload a Container, Lex de Prieelle, downloaded from <https://www.youtube.com/watch?v=Mc-IC1yclgU>).

Brandon_2009 (Retrofit kit allows cars to drive themselves, http://newatlas.com/kairos-autonomi-pronto4/13417/Nov._23,_2009).

McBride_2007 (DARPA Urban Challenge Intelligent Vehicle Systems Technical Paper, IVS Team, Apr. 13, 2007).

DARPA_Grand_Challenge_Wiki_2011 (DARPA Grand Challenge (2007), Wikipedia archived date: Dec. 4, 2011).

Box_Truck_2012 (Box Truck Defined, Archived Wikipedia Jan. 11, 2012 downloaded from https://en.wikipedia.org/w/index.php?title=Box_truck&oldid=470811655).

The New World Thesaurus published by Webster's New World New York, 1985.

Enon_2006 (Enon—Fujitsu's Service Robot, Robot News, Apr. 8, 2006, downloaded from (<http://Uphotosl.blogspot.com/blogger/6323/2375/1600//Fujitsu%20Enon1.3.jpg>).

The Randomhouse College Dictionary: Revised Edition dated 1982. Fiorini_2008.pdf Fiorini, P., Introducing Service Robotics to the Pharmaceutical Industry, Intel Serv Robotics (2008) 1:267-280 DOI 10.1007/s11370-008-0019-2.

By Bogh (Autonomous Industrial Mobil Manipulation (AIMM): From Research to Industry. In Proceedings of the 42nd International Symposium on Robotics. VDE Verlag GMBH, 2011).

Ramde (Driverless Truck Lurches Out of Lab, The Washington Post, Tuesday, Oct. 2, 2007, 10:49 PM).

Fetzek (Behavior-Based Power Management in Autonomous Mobile Robots, Thesis, Air Force Institute of Technology Wright-Patterson Air Force Base Ohio, Mar. 2008).

Correa, A., Multimodal Interaction with an Autonomous forklift, IEEE, 2010.

Coleman, N., Smart Crane Ammunition Transfer System: Real-Time Control, American Institute of Aeronautic and Astronautics, Inc., 1998.

Cox, W., Robots Replace Dock Workers, Dec. 19, 2005 <http://robotshop.com/blogs/en/robots-replace-dock-workers-4097>.

McIlraith, S., CSC2542 Representations for (Classical) Planning problem, Department of Computer Science University of Toronto, 2010.

Anders, R., BEAR robot loading a truck, Aug 3, 2006 https://www.youtube.com/watch?v=shSyxA_eflk.

DARPA Autonomous robot cars drive DARPA Urban challenge, Feb. 20, 2008 <http://youtube/pontv2mbihA>.

Enterprise Resource Planning (ERP) Wikipedia Archive dated Feb. 25, 2011 http://en.wikipedia.org/w/index.php?title=Enterprise_resource_planning&oldid=415865075.

(56)

References Cited

OTHER PUBLICATIONS

Manufacturing Execution System (MES) Wikipedia Archive dated
Feb. 23, 2012 [http://en.wikipedia.org/w/index.php?title=Manufacturing_Execution_System&oldid=478343](http://en.wikipedia.org/w/index.php?title=Manufacturing_execution_system&oldid=478343)

* cited by examiner




FIG. 1




FIG. 2




FIG. 4




FIG. 3




FIG. 5




FIG. 6




FIG. 10A

FIG. 10B




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D




FIG. 9E




FIG. 9F




FIG. 11




FIG. 12

1**MONITORING ONE OR MORE ARTICLES
ON A SUPPORT SURFACE**

RELATED APPLICATIONS

This application claims priority to U.S. Provisional Application Ser. No. 61/607,319 filed on Mar. 6, 2012, which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

1. Technical Field

The present invention relates generally to article handling and monitoring and, more particularly, to loading articles on one or more support surfaces with a mobile device and to monitoring the arranged articles before, during and/or after transportation of the loaded support surfaces.

2. Background Information

Transporting articles from one location to another is a common task undertaken by a majority of businesses and various other enterprises, and is sometimes generally referred to as “material handling”. The military and shipping services such as the U.S. Postal Service, FedEx® and the like, for example, utilize supply chains to pickup, transport and deliver various types of articles between different locations worldwide. The term “logistics” may be used to describe flow management of the articles and information for transporting, inventorying, warehousing, material handling and packaging of the articles within such supply chains.

Typical material handling and logistical tasks may include handling articles at their source, their destination and many points in-between. These tasks frequently involve packaging and/or repackaging a variety of articles into larger or smaller packages, pallets, containers and the like for shipping across a distance. These tasks may also involve unpacking the articles at their destination for storage, use, delivery or further transportation. Additionally, articles frequently are moved and stored at various places at various times within a particular building or group of buildings, such as in a manufacturing operation, hospital, or warehouse as well as an aircraft, ship, cargo plane or other military environment.

At their source, order picking (also referred to as “palletizing”) typically is employed in a warehouse or other location where a number of articles are taken from a number of source locations, such as pallets, for example, and placed on a destination or shipping pallet or other shipping container or the like. Once filled, the pallet or container is then taken to a loading dock or similar area where it may be packaged, such as with strapping, shrink wrap or the like, and loaded into a transport vehicle such as, for example, a truck, rail car, plane, helicopter, ship or other vehicle.

At their destination, the pallets or containers are removed from their transport vehicles. The articles may subsequently be removed from the pallets or containers and placed in another transport vehicle or another storage location for further shipment, storage or use. This process and associated tasks are routinely undertaken by businesses on a daily basis and are an integral part of providing cargo for private and military use in locations around the world and must be accomplished with a high degree of accuracy to avoid additional costs and to sustain or increase customer satisfaction.

2

In many operations, order picking and pallet or container unloading is performed using manual labor, which is not only time consuming and labor intensive, but is subject to errors and injury to workers particularly with heavier loads.

5 Additionally, workers typically use various types of equipment to make such tasks easier, such as forklifts, pallet jacks and conveyor belts, for example, which not only require a substantial amount of capital for purchasing and maintaining such equipment but are limited in the environments where they can be employed and create serious safety hazards in the work environment.

10 Although automated systems have been developed, they typically are fixed installation types of systems that require a substantial amount of infrastructure installation and facility renovation and simply cannot be flexibly deployed in different warehouses, manufacturing facilities, planes, ships or other environments as needed. This required infrastructure and renovation not only dramatically increases the cost, complexity and maintenance of such systems, but also limits their application to large warehouses and operations with significant budgets. Additionally, if such systems go down for repair or maintenance the entire material handling operation is typically shut down if not significantly disrupted since those systems take up a substantial amount of floor space thereby inhibiting any backup systems from being employed, such as using forklifts or fork trucks, for example.

20 It would be desirable therefore to provide a readily deployable and near-zero infrastructure solution to the above and other needs.

SUMMARY OF THE DISCLOSURE

35 Devices, systems and methods are provided for monitoring a plurality of articles arranged on a support surface according to an article arrangement modeled with a first processing device. One of the methods includes receiving image data generated from the modeled article arrangement. The image data is received by a second processing device, and is indicative of an image of the arranged articles on the support surface. The received image data is used to inspect the arranged articles.

BRIEF DESCRIPTION OF THE DRAWINGS

45 The following detailed description will be better understood when read in conjunction with the appended drawings, in which there is shown one or more of the multiple embodiments of the present disclosure. It should be understood, however, that the various embodiments of the present disclosure are not limited to the precise arrangements and instrumentalities shown in the drawings.

50 FIG. 1 is an illustration of an electro-mechanical mobile device loading one or more articles onto one or more support surfaces;

FIG. 2 is a system block diagram illustration of an electro-mechanical mobile device;

55 FIG. 3 is an illustration of an autonomous mobile robot embodiment of the mobile device of FIG. 2;

FIG. 4 is an illustration of another autonomous mobile robot embodiment of the mobile device of FIG. 2;

60 FIG. 5 is a flow diagram of a method for loading articles on a support surface using the mobile device of FIGS. 1 and 2;

65 FIG. 6 is an illustration of an embodiment of a stable arrangement of articles on a support surface;

3

FIG. 7 is an illustration of a plurality of autonomous mobile robots loading a plurality of support surfaces;

FIG. 8 is another illustration of the mobile robots of FIG. 7 loading the support surfaces;

FIGS. 9A-9F are illustrations of another embodiment of the mobile device of FIG. 2 arranging articles on a support surface;

FIG. 10A is an illustration of an article arrangement wrapped with packaging material;

FIG. 10B is an illustration of the article arrangement of FIG. 10A subsequent to being tampered with;

FIG. 11 is a block diagram illustration of a system for monitoring articles in an article arrangement on a loaded support surface; and

FIG. 12 is a flow diagram of a method for monitoring articles in an article arrangement on a loaded support surface using the system of FIG. 11.

DETAILED DESCRIPTION OF THE INVENTION

Autonomous devices, systems and/or methods may perform one or more tasks without continuous outside control and/or intervention. An autonomous mobile robot, for example, may receive instructions to perform a certain task at a certain location. The mobile robot may subsequently determine and perform the operation(s) necessary to move to the location and/or complete the task based on, for example, its current location, surrounding obstacles, its operating environment, the type of task to be performed, etc. Such autonomous devices, systems and/or methods may also adapt to unknown, new and/or changing operating environments without additional outside control and/or intervention.

Autonomous devices, systems and/or methods may be fully autonomous or semi-autonomous. The term “fully autonomous” is used to describe a device, system and/or method that may perform one or more tasks without, for example, any outside control and/or intervention. A fully autonomous mobile robot, for example, may perform a task without receiving instructions (e.g., vectors, commands, etc.) from a human operator during performance of the task. The term “semi-autonomous” is used to describe a device, system and/or method that may perform one or more tasks without, for example, continuous outside control. A semi-autonomous mobile robot, for example, may perform a task utilizing one or more periodic instructions from a human operator that bound and/or qualify the performance of the task. The instructions, for example, may provide an updated location of where the task is to be performed, identify an unknown obstacle, control the scope of the task, control when the task should be performed, etc.

FIG. 1 illustrates an electro-mechanical mobile device 20 (e.g., an autonomous mobile robot) autonomously performing a task of loading one or more articles 22, 24, 26 and 28 onto one or more support surfaces 30, 32 and 34, where these articles may have different (or similar) shapes, sizes, weights, etc. Examples of articles include boxes, crates, containers, packages, barrels, canisters, luggage, chests, and amorphous bags, sacks and other such objects. Other examples of articles include electronic and/or mechanical devices and equipment, etc. Examples of support surfaces include pallets, cargo bay floors, warehouse floors, truck beds, ship hold floors, etc. Other examples of support surfaces include interior surfaces of support containers, boxes and the like in which the articles may be placed and subsequently transported and/or stored. The present inven-

4

tion of course is not limited to any particular article and/or support surface type or configuration.

Briefly, the mobile device 20 may load one or more of the articles 22, 24, 26 and 28 onto a first of the support surfaces (e.g., the transport pallet 30), for example, by gathering the articles from one or more respective source pallets 36, 38, 40 and 42 and arranging the gathered articles onto the first support surface 30. Each of the source pallets 36, 38, 40 and 42 is located at a respective article pickup location, and may support (e.g., hold) similar types of articles; e.g., the source pallet 36 supports the articles 28, the source pallet 38 supports the articles 26, etc. Each of the support surfaces 30, 32 and 34 is located at a respective support surface location and may support one or more different types of articles. The articles loaded onto the first support surface 30 may be selected based on, for example, a destination of the first support surface, intended (e.g., medical, culinary, warfare/combat, humanitarian aid, etc.) use of the articles, etc. Subsequent to the loading, the mobile device 20 or another device (e.g., a fork lift, crane, conveyor, etc.) may move the loaded first support surface 30 onto a vehicle (e.g., a ship, train, truck, helicopter, airplane, submersible, spacecraft, etc.) for transport to another location (e.g., final destination), or into a building (e.g., warehouse, business, etc.) or other facility for storage or subsequent distribution.

FIG. 2 is a system block diagram illustration of the mobile device 20. The mobile device 20 includes device electronics and/or mechanisms operable to (e.g., fully and/or semi-) autonomously perform one or more tasks such as, for example, loading article(s) onto support surface(s) as illustrated in FIG. 1. The device electronics and/or mechanisms may include a sensor system 44, a device interface system 46, memory 48, a mobile platform 50 (e.g., drive system), a manipulator system 52, and a controller 54. The present invention of course is not to be limited to the aforesaid electronics and/or mechanisms, and may include alternate electronics and/or mechanisms other than those specifically described herein as well as known or future equivalents thereof.

The sensor system 44 is configured to survey the mobile device's surroundings and operating environment, and/or to receive location data. The sensor system 44 may include, for example, one or more location and/or proximity sensors that spatially locate (e.g., triangulate) the mobile device 20 relative to, for example, its surrounding environment, its geographic location, and/or one or more locators (e.g., RF tags, physical landmarks, etc.). Examples of location and/or proximity sensors include, but are not limited to, global positioning system (GPS) receivers, radar systems, sonar systems, infrared sensors, lasers, cameras, radio transceivers, etc. The sensor system 44 may additionally or alternatively include one or more cameras, one or more electro-acoustic transducers (e.g., microphones), etc.

The device interface system 46 is configured to receive instructions (e.g., vectors, commands, etc.) in the form of control data from an operator and/or from a remote control system. The device interface system 46 may also be configured to communicate data to the operator and/or to the remote control system. The device interface system 46 may include a communication device and/or an operator interface. The communication device may include a cellular, satellite and/or radio transmitter, and/or a cellular, satellite and/or radio receiver. The operator interface may include one or more input and/or output (I/O) devices such as, for example, a display screen, a speaker, a touch screen, a keypad, a voice command system with an electro-acoustic transducer (e.g., microphone), etc.

5

The memory **48** (e.g., a non-transitory computer readable medium) may be configured to store software (e.g., program instructions) for execution by the controller **54**. The memory may include a volatile memory and/or a nonvolatile memory. Examples of a volatile memory may include a random access memory (RAM) such as a dynamic random access memory (DRAM), a static random access memory (SRAM), a synchronous dynamic random access memory (SDRAM), a video random access memory (VRAM), etc. Examples of a nonvolatile memory may include a read only memory (ROM), an electrically erasable programmable read-only memory (EEPROM), a computer hard drive, etc.

The mobile platform **50** is configured to move the mobile device **20** to various locations within its operative environment. The mobile platform **50** may include one or more motorized and/or steerable propulsion devices such as, for example, motorized drive wheels, motorized track systems, etc. An embodiment of the mobile platform **50** with motorized drive wheels **56** is illustrated in FIG. **3**. An embodiment of the mobile platform **50** with motorized (e.g., robotic and multi-linkage) track systems **58** is illustrated in FIG. **4**. The present invention of course is not limited to the aforesaid mobile platform configurations and components.

Referring again to FIG. **2**, the manipulator system **52** includes one or more electronically, hydraulically, pneumatically and/or mechanically actuated manipulators **60**, **62** and **64** configured to move one or more articles within the operative environment. Examples of a manipulator include, but are not limited to, a robotic manipulator arm (e.g., a multi-axis manipulator arm), a pallet jack, a lift platform, a conveyor system, a slide carriage, a crane, etc. In the specific embodiment illustrated in FIG. **3**, the manipulator system **52** includes a plurality of robotic manipulator arms **60** and **62** and a pallet jack **64**. Each of the robotic manipulator arms **60** and **62** includes an end effector **66** connected to one or more arm members **68** (e.g., linkages). Examples of an end effector include, but are not limited to, a gripping device, a suction device, an electromagnet, a winch, a clasp, etc. Alternative examples of a manipulator system are disclosed in U.S. Pat. Nos. 7,902,784; 7,719,222 and 7,348,747, each of which is hereby incorporated by reference in its entirety.

Referring again to FIG. **2**, the controller **54** may be implemented using hardware or a combination of hardware and software. The controller **54** may include one or more processing devices, analog and/or digital circuitry, etc. The controller **54** is in signal communication (e.g., hardwired or wirelessly connected) with the sensor system **44**, the device interface system **46**, the memory **48**, the mobile platform **50** and the manipulator system **52**.

FIG. **5** is a flow diagram of a method for loading a plurality of the articles (e.g., the articles **22**, **24**, **26** and **28**) on the first support surface **30** using the mobile device **20** illustrated in FIGS. **1** and **2**. In step **500**, the controller **54** receives control data (e.g., one or more vectors, commands, etc.) through the device interface system **46**. The control data may include inventory data, location data, etc. The inventory data may, for example, identify the contents, types, states (e.g., amorphous or non-amorphous), masses and/or weights, dimensions, et cetera, of the articles to be arranged on the first support surface. The location data may, for example, identify the respective article pickup locations, and/or the respective support surface locations. Alternatively, the controller **54** may autonomously determine the article pickup locations and/or the support surface locations using the sensor system **44** where, for example, the articles and/or the support surfaces are configured with RF ID tags, locator beacons, etc. The controller **54** may alternatively

6

and/or additionally identify the articles using image and shape recognition software. The control data may also include other types of data such as, for example, scheduling data that designates on which support surface(s) and by when and/or in which order the articles should be loaded.

In step **502**, the controller **54** autonomously models at least some of the articles (e.g., the articles **22**, **24**, **26** and **28**) in a stable article arrangement on the first support surface **30**. The term "stable" is used to describe an article arrangement having, for example, (i) a relatively low center of gravity, (ii) articles that are substantially supported by the support surface and/or other articles in the arrangement, (iii) articles that are (e.g., equally) balanced on the support surface and/or other articles in the arrangement, etc.

FIG. **6** illustrates an embodiment of a stable article arrangement **70** modeled having a geometry that fits and is positioned within a perimeter **72** of the first support surface **30**. Articles (e.g., base articles **74**, free standing articles **76**, etc.) contacting the first support surface **30** are substantially (e.g., completely) supported by the first support surface **30**. Articles **78** and **80** stacked on one or more of the base articles **74** and/or intermediate articles **78** are substantially supported by the respective articles upon which they are stacked. A bottom surface of the intermediate stacked article **78**, for example, is substantially (e.g., completely) supported by a top surface of the base article **74**, and substantially parallel to the first support surface **30**. In another example, each bottom corner of the stacked article **80** is supported by top surfaces of the base articles **74** and the intermediate stacked article **78**. The stacked articles **78** and **80** may weigh less than the articles upon which they are stacked. The stacked articles **78** and **80** may also have smaller geometries (e.g., horizontal cross sectional areas, etc) than the articles upon which they are stacked. In some embodiments, the base articles **74** may be staggered relative the stacked articles **80** to interlock the articles together with frictional forces. The present invention of course is not limited to any particular placement and/or arrangement of the articles.

Referring again to FIGS. **1**, **2** and **5**, the stable article arrangement may be computationally modeled using a constrained optimization program or algorithm such as, for example, a Mix Integer Linear Program (MILP) constrained optimization program. The controller **54**, for example, may input a plurality of given, fixed and/or variable parameters into a plurality of equality and/or inequality constraint equations, and subsequently solve the equations using the constrained optimization program. The parameters may be indicative of, for example, (i) a number of articles to be arranged on the support surface, (ii) dimensions of the articles and the support surface, (iii) weights and/or masses of the articles, (iv) dimensions between each article and one or more other articles and/or the support surface, (v) maximum dimensions for the article arrangement, etc. The constraint equations may be formulated to describe, for example, (i) spatial orientations of the articles relative to other articles and/or the support surface, (ii) relative positions of the articles relative to other articles and/or the support surface, (iii) the manner in which the articles are supported, (iv) the order in which the articles will be used at their destination, etc. The present invention of course is not limited to any particular type of optimization programs, parameters and/or constraint equation formulations.

The stable article arrangement may also be modeled to efficiently load and tightly pack the articles **22**, **24**, **26** and **28** on the first support surface **30**. The controller **54**, for example, may iteratively change one or more of the parameter values within the constraint equations to model the

articles in a plurality of different arrangements. The controller **54** may subsequently identify an optimum modeled article arrangement as, for example, the modeled article arrangement that (i) fits the greatest number of articles on the first support surface **30**, (ii) has the greatest arrangement density, and/or (iii) has the greatest control volume density.

The term “arrangement density” is used to describe a ratio of a collective volume of the articles in the modeled article arrangement to an overall volume of the modeled article arrangement. The collective volume may be determined by adding together volumes of the respective articles **22**, **24**, **26** and **28** in the modeled article arrangement. The overall volume may be determined by adding the collective volume to volumes of respective spaces (e.g., gaps) between the articles **22**, **24**, **26** and **28** in the modeled article arrangement. The controller **54** may utilize the arrangement density to identify the modeled article arrangement that packs the articles closest together.

The term “control volume density” is used to describe a ratio of the collective volume to a control volume. The control volume may be given, or determined from a surface area of the support surface **30**, and a control volume height (e.g., maximum vertical article arrangement height). The control volume height may be sized based on, for example, a height of a shipment container, a trailer, a cargo hold, etc. The control volume density may be utilized by the controller **54** to identify the modeled article arrangement that most efficiently packs the articles **22**, **24**, **26** and **28** within the control volume.

In step **504**, the controller **54** autonomously schedules the order in which the articles **22**, **24**, **26** and **28** in the optimum modeled article arrangement are to be gathered and moved to the first support surface **30** location. The controller **54**, for example, may schedule the base articles to be gathered and moved before the stacked articles such that the stacked articles may be properly disposed on the base articles. In another example, the controller **54** may schedule the article proximate a back side of the first support surface to be gathered and moved before the articles proximate to a front side of the first support surface.

In step **506**, the mobile device **20** autonomously gathers one or more of the articles (e.g., the article **28**) in the optimum modeled article arrangement. The controller **54**, for example, may signal the mobile platform **50** to move the mobile device **20** to the article **28** pickup location. The controller **54** may subsequently signal the manipulator system **52** to pick up the article **28** with one or more of the robotic manipulator arms (e.g., the manipulator arm **60**). The end effector **66**, for example, may engage (e.g., grip) the article **28** utilizing one of a plurality of (e.g., predetermined) article engagement (e.g., gripping) techniques, and the arm member **68** may lift the article **28** off of the respective source pallet **36**. In another example, the controller **54** may signal the manipulator system **52** to pick up one of the articles with the first robotic manipulator arm **60**, and to pick up another one of the articles with the second robotic manipulator arm **62**.

The controller **54** may select the article engagement technique used to engage (e.g., grip, push, etc.) the article(s) based on, for example, the type and/or state of the article **28** being gathered, the orientation of the article **28** relative to the source pallet **36** and/or the mobile device **20**, how the article is to be moved (e.g., lifted, pushed, cradled, etc.), etc. Each of the article engagement techniques may define, for example, a specific gripping force or range of gripping forces, a relative end effector spatial orientation, how far to open the (e.g., gripping) end effectors **66**, etc. The controller

54, for example, may select a gripping technique that uses a relatively large gripping force to grasp a heavy article, and a relatively small gripping force to grasp a light or fragile article or an article having an amorphous state. FIGS. **7** and **8** illustrate a plurality of autonomous mobile robots utilizing various examples of the gripping techniques.

Referring again to FIGS. **1**, **2** and **5**, in step **508**, the mobile device **20** autonomously moves the gathered article(s) from the respective article pickup location(s) to the first support surface **30** location. The controller **54**, for example, may signal the mobile platform **50** to move the mobile device **20** from the first article pickup location to the first support surface location.

In step **510**, the mobile device **20** autonomously arranges the gathered article(s) on the first support surface **30** according to the optimum modeled article arrangement. The controller **54**, for example, may signal the manipulator system **52** to place the article **28** in a particular position and orientation on the first support surface **30** using, for example, the robotic manipulator arm **60** holding the article **28**.

In step **512**, the mobile device **20** may repeat the steps **506**, **508** and **510** to gather, move and arrange the remaining articles of the optimum modeled article arrangement.

In step **514**, the mobile device **20** may autonomously secure the articles **22**, **24**, **26** and **28** together and/or to the first support surface **30**. The mobile device **20**, for example, may utilize the manipulator system **52** to wrap the articles together in packaging material such as, for example, shrink wrap, transparent or non-transparent plastic wrap, etc. In another example, the mobile device **20** may utilize the manipulator system **52** to secure the article arrangement to the first support surface **30** with, for example, tie down straps.

In some embodiments, the step **508** may be omitted from the method of FIG. **5** where, for example, the articles **22**, **24**, **26** and **28** may be respectively gathered and subsequently (e.g., immediately) arranged on the first support surface **30**. Such an embodiment is illustrated in FIGS. **9A-9F** where the pallet jack **64** is engaged with a pallet **82** that defines the first support surface **30**. In other embodiments, the pallet **82** may be utilized to temporarily hold the gathered article(s) during movement of the article(s) between the article pickup location(s) and the first support surface location; i.e., where the step **508** is not omitted.

In some embodiments, where the articles identified in the step **500** cannot fit within the control volume of a single support surface, the controller **54** may model a first grouping of the articles in a first stable article arrangement on the first support surface, a second grouping of the articles in a second stable article arrangement on a second support surface, etc. The controller **54** may also utilize the constrained optimization program to reduce (e.g., minimize) the number of support surfaces necessary to hold the identified articles. In such an embodiment, the mobile device **20** may perform the steps **506**, **508** and **510** iteratively for each of the modeled article arrangements, or substantially concurrently in a manner that reduces (e.g., minimizes) loading time. The loading time may be minimized, for example, by gathering and arranging a similar type of the articles onto a plurality of the support surfaces before beginning the gathering and arranging of another type of the articles. Alternatively, the mobile device **20** may signal a second mobile device to load the second support surface while the mobile device **20** loads the first support surface, etc.

In some embodiments, the constraint equations used in the step **502** may be weighted in order to arrange certain

types of the articles at certain positions within the modeled article arrangement. Such weighting may be useful, for example, where certain types of the articles are scheduled to be unpacked at a final destination before other types of the articles, are scheduled to be removed mid-transit, etc.

In alternate embodiments, a remote control system may be provided that autonomously controls one or more mobile devices to load one or more support surfaces. The control system, for example, may perform the steps **500**, **502** and **504** and subsequently autonomously coordinate and signal a first of the mobile devices and a second of the mobile devices to gather and arrange respective articles on the first support surface. In another example, the control system may autonomously coordinate and signal the first of the mobile devices and the second of the mobile devices to gather and arrange respective articles on different support surfaces that are to be transported to and/or stored in, for example, the same location. In some embodiments, the control system may select which of the mobile devices loads which of the support surfaces based on, for example, the mobile device's proximity to the article pickup locations and/or support surface locations, the mobile device's load capacities or fuel/battery level, etc.

During transportation, warehousing and/or storage of a loaded support surface, one or more articles in an article arrangement **84** on the support surface may be damaged, stolen, replaced with other articles, or otherwise tampered with, which may alter the geometry and appearance of the article arrangement as illustrated in FIGS. **10A** and **10B**. The geometry and appearance of the article arrangement **84** may change, for example, where (i) one of the perimeter articles is missing, (ii) one of the articles is replaced with an article having a different size or physical appearance, (iii) the packaging material wrapped around the article arrangement is removed and replaced with different packaging material or wrapped in a different manner, etc.

FIG. **11** illustrates a system **86** for monitoring articles in an article arrangement on a loaded support surface. The system **86** may include the mobile device **20** and an article inspection system **88**. The article inspection system **88** includes a processing device **90** that is in signal communication with a communication device **92** as well as a camera **94**, a printer **96** and/or a display screen **98**. The mobile device **20** may be located at a first location (e.g., an article distribution/loading facility, etc.), and the article inspection system **88** may be located at a second location (e.g., an article receiving facility, another article distribution/loading facility, a final destination, etc.).

FIG. **12** is a flow diagram of a method for monitoring the articles in an article arrangement using the system **86** of FIG. **11**. In step **1200**, the mobile device **20** performs the method of FIG. **5** to arrange the articles on the support surface according to an autonomously modeled article arrangement.

In step **1202**, the controller **54** (see FIG. **2**) generates image data from the modeled article arrangement, where the image data is indicative of an image of the arranged articles on the loaded support surface. The imaged data may be generated, for example, by processing the modeled article arrangement with given or determined dimensions and geometries of the articles in the modeled article arrangement. The controller **54** may also fit a surface to the modeled article arrangement to represent the packaging material wrapped around the articles in the step **514** (see, e.g., FIGS. **10A** and **10B**). It is contemplated that image data may include a datum that establishes an image coordinate system for the image.

In step **1204**, the mobile device **20** transmits the image data to the processing device **90** through the communication device **92**. The image data may be transmitted before, after and/or during the transportation of the loaded support surface from the first location to the second location.

In step **1206**, the image data received by the processing device **90** is utilized to inspect the arranged articles on the loaded support surface at the second location. The processing device **90**, for example, may signal the printer **96** to print the image of the arranged articles. An inspector, security guard, dock worker, government employee, etc. may subsequently visually compare the arranged articles on the loaded support surface to the printed image to determine whether any of the articles are damaged, tampered with, missing, etc. In another example, the processing device **90** may signal the display screen **98** to display the image of the arranged articles such that it may be visually compared to the arranged articles on the loaded support surface.

In other embodiments, the processing device **90** may receive second image data from the camera **94**, where the second image data is indicative of a second image of the arranged articles on the loaded support surface at the second location. The processing device **90** may subsequently compare one or more image characteristics between the first image data and the second image data to determine whether any of the articles are damaged, tampered with, missing, etc. The image characteristics may be compared utilizing, for example, image and/or shape recognition software. In some embodiments, the inspection system **88** may autonomously generate the second image data with the camera **94** and compare the first and second image data where, for example, the inspection system **88** is configured as the mobile device **20** described above.

In other embodiments, the method of FIG. **12** may be utilized to inspect the articles on the loaded support surface before they have been transported to the second location, or during transit to the second location.

A person of skill in the art will recognize that the methods of FIGS. **5** and **12** and the various embodiments thereof may be performed by devices and systems other than those specifically described above. A stationary robotic device, a mobile or stationary crane system, a conveyor system as well as various stationary or mobile manipulator devices, for example, may be adapted to perform one or more of the afore-described methods.

A person of skill in the art will also recognize that the modeled article arrangement utilized in the method of FIG. **12** need not be autonomously modeled as set forth in the step **1200**. The modeled article arrangement, for example, maybe developed by a worker to provide a plan of how the articles should be arranged by loading personnel on the support surface.

It is to be understood that the terminology used herein is used for the purpose of describing specific embodiments, and is not intended to limit the scope of the present invention. It should be noted that as used herein, the singular forms of "a", "an" and "the" include plural references unless the context clearly dictates otherwise. In addition, unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs.

Although the description above contains many specific examples, these should not be construed as limiting the scope of the embodiments of the present disclosure, but as merely providing illustrations of some of the presently preferred embodiments of the present invention. It will be

11

appreciated by those skilled in the art that changes could be made to the embodiments described above without departing from the broad inventive concept thereof. It is to be understood therefore that this disclosure is not limited to the specific embodiments disclosed herein, but it is intended to cover modifications within the spirit and scope of the embodiments of the present disclosure. Accordingly, the present invention is not to be restricted except in light of the attached claims and their equivalents.

What is claimed is:

1. A method for autonomously determining potential tampering or damage of a shipment of a plurality of articles at a destination point without any human intervention, the method comprising:

providing a list of the plurality of articles to be shipped to a destination point, the list of plurality of articles comprising a first article having a rectangular shape and a second article having a non-rectangular shape and a third article having an amorphous shape, and a fourth article having a shape wherein the shape of the fourth article is rectangular, non-rectangular or amorphous;

modeling the plurality of articles provided on the list in an article arrangement for placement on a first support surface using a first processing device to yield a modeled article arrangement;

arranging the plurality of articles on the first support surface according to the modeled article arrangement using a fully autonomous mobile robot to yield a first article arrangement;

electronically generating a first set of digital image data from the modeled article arrangement, wherein the digital image data is indicative of a digital image of all of the first article arrangement on the first support surface at a first point in time at a first shipping point for the plurality of articles;

providing a second set of digital image data from a digital camera, the second set of digital image data being indicative of a second article arrangement on a second support surface at a second point in time at a second destination point for the second article arrangement, the second destination point being geographically remote from the first shipping point, wherein the first article arrangement on the first support surface are in a different configuration from the second article arrangement on the second support surface;

receiving the second set of digital image data by a second processing device; and

comparing autonomously and electronically, via the second processing device, the first set of digital image data generated from the modeled article arrangement at the first point in time at the first shipping point with the second set of digital image data of the second article arrangement at the second point in time at the destination point without any human intervention needed to

12

compare the first set of digital image data and the second set of digital image data;

identifying a set of differences between the first set of digital image data and the second set of digital image data, the set of differences comprising at least one or more of a missing article, a reoriented article or damage to one or more articles to yield an identified set of differences between the first set of digital image data and the second set of digital image data; and

determining potential tampering or damage of the first article arrangement on the first support surface by a fully autonomous mobile robot classifying the identified set of differences between the first set of digital image data and the second set of digital image data wherein the classification is selected from the group consisting of potential tampering or damage.

2. The method as defined in claim 1, wherein the second processing device utilizes image and shape recognition software to compare the first set of digital image data and the second set of digital image data.

3. The method as defined in claim 1, wherein the modeled article arrangement includes a particular predetermined control volume, the particular predetermined control volume being variable depending upon a type of support surface being utilized both with and without pallets.

4. The method as defined in claim 3, wherein at least one of the first support surface or the second support surface is a floor of a shipping container and the particular predetermined control volume is adjusted to provide maximum efficiency in modeling the first article arrangement and the second article arrangement on the floor of the shipping container both with and without pallets.

5. The method as defined in claim 3, wherein at least one of the first support surface or the second support surface is a floor of a trailer in use with a tractor trailer truck and the particular predetermined control volume is adjusted to provide maximum efficiency in modeling the first article arrangement and the second article arrangement on the floor of the trailer both with and without pallets.

6. The method as defined in claim 1, wherein similar articles are loaded onto the first support surface prior to dissimilar items while still achieving a stable modeling of articles.

7. The method as defined in claim 1, including encasing the first article arrangement and the second article arrangement in shrink-wrap and autonomously determining without any human intervention if the shrink-wrap has been tampered with.

8. The method as defined in claim 1, wherein both the first set of digital image data and the second set of digital image data further identify a particular type of each of the articles arranged on the first support surface with a particular article description or identifier.

* * * * *