

US010224135B2

(12) **United States Patent**
Rapoport et al.

(10) **Patent No.:** **US 10,224,135 B2**
(45) **Date of Patent:** **Mar. 5, 2019**

(54) **DEVICE, SYSTEM AND METHOD FOR OBTAINING A MAGNETIC MEASUREMENT WITH PERMANENT MAGNETS**

(58) **Field of Classification Search**
USPC 324/309
See application file for complete search history.

(71) Applicant: **Aspect Imaging Ltd.**, Shoham (IL)

(56) **References Cited**

(72) Inventors: **Uri Rapoport**, Moshav Ben Shemen (IL); **Yair Goldfarb**, Ness Ziona (IL); **Yoram Cohen**, Yarkona (IL)

U.S. PATENT DOCUMENTS

(73) Assignee: **ASPECT IMAGING LTD.**, Shoham (IL)

3,534,251 A 10/1970 Richards
4,612,505 A 9/1986 Zijlstra
4,698,611 A 10/1987 Vermilyea
4,758,813 A 7/1988 Holsinger et al.
4,899,109 A 2/1990 Tropp et al.

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 126 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **15/402,438**

CN 102136337 7/2011
EP 0921527 6/1999

(Continued)

(22) Filed: **Jan. 10, 2017**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2018/0040406 A1 Feb. 8, 2018

Liming Hong and Donglin Zu, Shimming Permanent Magnet of MRI Scanner, Piers Online, 2007, vol. 3, No. 6, 859-864.

(Continued)

Related U.S. Application Data

Primary Examiner — Rodney E Fuller

(60) Provisional application No. 62/372,065, filed on Aug. 8, 2016, provisional application No. 62/381,079, filed on Aug. 30, 2016.

(74) *Attorney, Agent, or Firm* — Pearl Cohen Zedek Latzer Baratz LLP

(51) **Int. Cl.**

G01V 3/00 (2006.01)
H01F 7/02 (2006.01)
G01R 33/383 (2006.01)
G01R 33/3873 (2006.01)
G01R 33/421 (2006.01)


(57) **ABSTRACT**

A magnetic field device, with a first magnet, a first ferromagnetic element positioned adjacent to the first magnet, a second magnet, a second ferromagnetic element positioned adjacent to the second magnet and relative to the first ferromagnetic element to create a gap between the first ferromagnetic element and the second ferromagnetic element, and a third magnet positioned between the first ferromagnetic element and the second ferromagnetic element and within the gap.

(52) **U.S. Cl.**

CPC **H01F 7/0278** (2013.01); **G01R 33/383** (2013.01); **G01R 33/3873** (2013.01); **G01R 33/421** (2013.01)

18 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,931,733 A 6/1990 Hanawa
 5,235,284 A 8/1993 Tahara et al.
 5,343,151 A 8/1994 Gory et al.
 5,359,310 A 10/1994 Pissanetzky
 5,539,316 A 7/1996 Sukumar
 5,565,834 A * 10/1996 Hanley G01R 33/383
 324/319
 5,635,889 A 6/1997 Stelter
 5,664,569 A 9/1997 Damadian et al.
 5,760,585 A 6/1998 Dorri
 6,081,120 A 6/2000 Shen
 6,147,578 A 11/2000 Panfil et al.
 6,157,278 A 12/2000 Katznelson et al.
 6,177,795 B1 1/2001 Zhu et al.
 6,191,584 B1 * 2/2001 Trequattrini G01R 33/383
 324/319
 6,411,187 B1 6/2002 Rotem et al.
 6,452,388 B1 9/2002 Reiderman et al.
 6,535,092 B1 3/2003 Hurley et al.
 6,600,401 B2 7/2003 Zuk et al.
 6,646,530 B2 * 11/2003 Ruhrig B82Y 25/00
 335/306
 6,687,526 B2 2/2004 Brand et al.
 6,707,363 B1 3/2004 Abele
 6,751,496 B2 6/2004 Su et al.
 6,838,964 B1 1/2005 Knight et al.
 6,897,750 B2 5/2005 Neuberth
 6,946,939 B2 9/2005 Doi
 7,034,530 B2 4/2006 Ahluwalia et al.
 7,116,198 B1 10/2006 Abele
 7,148,689 B2 12/2006 Huang et al.
 7,205,764 B1 4/2007 Anderson et al.
 7,400,147 B2 7/2008 Rapoport
 7,423,431 B2 9/2008 Amm et al.
 7,529,575 B2 5/2009 Rezzonico et al.
 7,551,954 B2 6/2009 Green et al.
 7,800,368 B2 9/2010 Vaughan et al.
 8,089,281 B2 1/2012 Zhai et al.
 8,319,496 B2 11/2012 Eryaman et al.
 8,896,310 B2 11/2014 Rapoport
 8,969,829 B2 3/2015 Wollenweber et al.
 9,100,111 B2 8/2015 Behrendt et al.
 9,157,975 B2 10/2015 Dale
 9,159,479 B2 10/2015 Rotem
 9,696,269 B2 * 7/2017 Fordham G01N 24/081
 2001/0013779 A1 8/2001 Marek
 2002/0050895 A1 5/2002 Zuk et al.
 2005/0030028 A1 2/2005 Clarke et al.
 2005/0043612 A1 2/2005 Saint-Jalmes et al.
 2007/0068862 A1 3/2007 Sisemore
 2007/0096737 A1 5/2007 Rapoport

2007/0108850 A1 * 5/2007 Chertok H02K 1/145
 310/15
 2007/0249928 A1 10/2007 Blezek et al.
 2007/0265520 A1 11/2007 Posse
 2007/0273378 A1 11/2007 Trequattrini et al.
 2008/0001601 A1 1/2008 Sellers et al.
 2008/0246476 A1 10/2008 Rapoport
 2009/0072939 A1 * 3/2009 Shen G01R 33/3806
 335/306
 2009/0085700 A1 * 4/2009 Lian G01R 33/3806
 335/302
 2009/0120615 A1 5/2009 Icoz et al.
 2009/0259560 A1 10/2009 Bachenheimer
 2012/0119742 A1 5/2012 Rapoport
 2014/0257081 A1 9/2014 Rapoport
 2015/0059157 A1 3/2015 Rapoport
 2015/0137812 A1 5/2015 Rapoport
 2015/0168519 A1 6/2015 Rapoport
 2015/0253397 A1 9/2015 Rapoport
 2015/0253400 A1 9/2015 Rapoport
 2015/0253401 A1 9/2015 Rapoport
 2016/0022123 A1 1/2016 Katznelson et al.

FOREIGN PATENT DOCUMENTS

GB 863272 3/1961
 WO WO2007/052275 5/2007
 WO WO2011/001429 1/2011
 WO WO2014/141251 9/2014

OTHER PUBLICATIONS

Yingying Yao, Yong-Kwon Choi and Chang-Seop Koh, The Optimal Design of Passive Shimming Elements for High Homogenous Permanent Magnets Utilizing Sensitivity Analysis, Journal of Electrical Engineering & Technology, 2006, vol. I, No. 4, pp. 461-465.
 Z. Ren, D. Xie, and H. Li, Study on Shimming Method for Open Permanent Magnet of MRI, Progress in Electromagnetics Research M, 2009, vol. 6, 23-34.
 Keith Wachowicz, Evaluation of Active and Passive Shimming in Magnetic Resonance Imaging, Research and Reports in Nuclear Medicine, 2014:4 1-12.
 R Prost and L F Czervionke, How does an MR scanner operate? American Journal of Neuroradiology, Aug. 1994, 15 (7) 1383-1386.
 Belov, A. et al. Passive Shimming of the Superconducting Magnet for MRI, IEEE Transactions on Applied Superconductivity, Jun. 1995, vol. 5, No. 2, 679-681.
 McGinley et al., A permanent MRI magnet for magic angle imaging having its field parallel to the poles, Journal of Magnetic Resonance, 2016, 271; 60-67.

* cited by examiner




Fig. 1A




Fig. 2A




Fig. 2B




Fig. 3




Fig. 4A

Fig. 4B




Fig. 4C




Fig. 4D







Fig. 4E






Fig. 5B

1

**DEVICE, SYSTEM AND METHOD FOR
OBTAINING A MAGNETIC MEASUREMENT
WITH PERMANENT MAGNETS**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application claims the benefit of U.S. Provisional Patent Applications 62/372,065 filed on Aug. 8, 2016 entitled "DEVICE, SYSTEM AND METHOD FOR OBTAINING A MAGNETIC MEASUREMENT WITH PERMANENT MAGNETS" and U.S. Provisional Patent Application 62/381,079 filed on Aug. 30, 2016 entitled "NMR/MRI MAGNET ASSEMBLY COMPRISING SUPERCONDUCTING COILS AND A FERROMAGNETIC POLE PIECE", incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

Generally, the present invention relates to magnetic devices. More particularly, the present invention relates to devices, systems and methods for obtaining magnetic measurements.

BACKGROUND OF THE INVENTION

Electromagnetic based instruments can be used for measuring properties of matter and/or used for identifying its composition. For example, an electromagnetic based instrument capable of performing magnetic resonance spectroscopy can be used to obtain physical, chemical and/or structural information about matter (e.g., a molecule). Typically, in order to perform magnetic resonance spectroscopy, for example to provide high quality measurements of an object/subject (e.g., high resolution image and/or image contrast), it can be desirable for the magnetic field inside of a zone of measurement (e.g., an area where an object is to be measured is positioned) to be substantially stable and/or uniform. Other applications (e.g., magnetic resonance imaging (MRI)) can also require a high, stable, and/or uniform magnetic field strength.

Some systems that use magnetic fields for measurements can include magnetic coils to create the magnetic fields, with application of current to the coil, while other systems can utilize permanent magnets to create the magnetic fields, which typically do not require application of a current.

One difficulty in creating a magnetic field in a zone of measurement with permanent magnet(s) that is sufficient for magnetic resonance spectroscopy and/or magnetic imaging (e.g., that is substantially stable and/or uniform) is that magnetic fields produced by the permanent magnets(s) can be non-homogeneous, thus typically resulting in a non-homogenous magnetic field within the zone of measurement.

Some current solutions for creating a homogenous and/or stable magnetic field within a zone of measurement using a permanent magnet can include adding additional elements to an imaging device (e.g., coils) and/or increasing the size of the permanent magnets. One difficulty with current solutions is that as the number of elements in a magnetic measurement device increases and/or the size of the permanent magnets increases, the weight, size and/or cost of the device can increase.

Another difficulty with current solutions is that a magnetic measurement device that is heavy can cause a lack of mobility. For example, for magnetic measurement devices in

2

a hospital setting (e.g., magnetic resonance imaging (MRI) devices), a heavy and/or large device can prevent hospital personnel from moving an MRI. This can cause further difficulties, when imaging patients that can be hard to move (e.g., patients that are hooked up to multiple life support and/or monitoring equipment).

In another example, for magnetic measurement devices in an industrial setting (e.g., nuclear magnetic measurement (NMR) devices that measure properties of fluids and/or drilling muds in oil production facilities), a heavy and/or large device can prevent personnel from measuring the fluids/muds at various locations in the processes.

Therefore it can be desirable to achieve a desired magnetic field strength, having sufficient homogeneity and/or stability, and/or reducing a total weight of a magnetic measurement system.

SUMMARY OF THE INVENTION

There is thus provided, in accordance with some embodiments of the invention, a magnetic field device, including a first magnet, a first ferromagnetic element positioned adjacent to the first magnet, a second magnet, a second ferromagnetic element positioned adjacent to the second magnet and relative to the first ferromagnetic element to create a gap between the first ferromagnetic element and the second ferromagnetic element, and a third magnet positioned between the first ferromagnetic element and the second ferromagnetic element and within the gap.

In some embodiments, the third magnet has a first surface that faces a first surface of the first ferromagnetic element and a second surface that faces a first surface of the second ferromagnetic element. In some embodiments, the first surface of the third magnet abuts the first surface of the first ferromagnetic element and the second surface of the third magnet abuts the first surface of the first ferromagnetic element. In some embodiments, the third magnet has a dimension that allows the third magnet to translate between a first position and a second position, the first position being the first surface of the first ferromagnetic element, the second position being the first surface of the second ferromagnetic element

In some embodiments, the magnetic field device further includes a fourth magnet positioned between the first ferromagnetic element and the second ferromagnetic element and within the gap. In some embodiments, the fourth magnet has a first surface that faces a first surface of the first ferromagnetic element and a second surface that faces a first surface of the second ferromagnetic element. In some embodiments, the fourth magnet has a dimension that allows the fourth magnet to translate between a first position and a second position, the first position being the first surface of the first ferromagnetic element, the second position being the first surface of the second ferromagnetic element.

In some embodiments, the first magnet, the second magnet and the third magnet are permanent magnets, superconducting magnets, or resistive magnets. In some embodiments, the first magnet, the second magnet and the third magnet have dimensions that are based on a desired magnetic field strength, a type of object to be imaged, or any combination thereof. In some embodiments, the first magnet, the second magnet and the third magnet has a length between 10 and 1100 millimeters, a width between 10 and 300 millimeters, and a height between 45 and 200 millimeters.

In some embodiments, the gap has dimensions that are based on a type of object to be imaged. In some embodi-

ments, the gap has a diameter of 190 millimeters. In some embodiments, the magnetic field device further includes at least one fifth magnet coupled to the first magnet.

In some embodiments, the third magnet is positioned to cause a decrease of a magnetic field that is peripheral to the magnetic field device. In some embodiments, a first axis of the magnetic field device is defined as passing from the first ferromagnetic element to the second ferromagnetic element, wherein the first magnet and the second magnet are positioned to cause a magnetic field with a magnetization direction along the first axis, and wherein the third magnet is positioned to cause a magnetic field with a magnetization direction along the first axis.

In some embodiments, the magnetization direction of the third magnet is opposite of the magnetization direction of the first magnet. In some embodiments, the magnetic field device is positioned within an outer shell, the outer shell including a metal alloy. In some embodiments, at least one of the first and second magnets emits a magnetic field with a predetermined magnetic field strength, wherein the third magnet emits a magnetic field with a predetermined magnetic field strength, and wherein the strength of the magnetic field of at least one of the first and second magnets is substantially greater than the strength of the magnetic field of the third magnet. In some embodiments the total magnetic field produced during operation of the magnetic field device is substantially homogeneous and uniform within the gap.

There is thus provided, in accordance with some embodiments of the invention, a method of directing magnetic fields into a measurement volume, the method including generating a first magnetic field in a first direction with a first magnetic field strength, distributing the first magnetic field into the measurement volume to create a substantially uniform magnetic flux, and increasing a total magnetic flux into the measurement volume by directing a second magnetic field in a second direction with a second magnetic field strength, wherein the second direction is parallel to the first direction.

In some embodiments, the method further includes directing a third magnetic field into the measurement volume in a third direction, wherein the third direction is perpendicular to the first direction. In some embodiments, the method further includes positioning an object within the measurement volume, and performing magnetic field analysis on the object.

In some embodiments, at least one of the first magnetic field strength, and the second magnetic field strength is between 0.5 and 1.5 Tesla. In some embodiments, the first magnetic field strength and the first direction, and the second magnetic field strength and the second direction are based on a size of the measurement volume, a type of object to be measured, or any combination thereof. In some embodiments, the total magnetic flux in the measurement volume is a substantially homogeneous field.

BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter regarded as the invention is particularly pointed out and distinctly claimed in the concluding portion of the specification. The invention, however, both as to organization and method of operation, together with objects, features, and advantages thereof, can be understood by reference to the following detailed description when read with the accompanying drawings in which:

FIG. 1A schematically illustrates a perspective cross-sectional view of a magnetic field device, according to illustrative embodiments of the invention;

FIG. 1B schematically illustrates a perspective cross-sectional view of a magnetic field device having additional magnets to the device of FIG. 1A, according to illustrative embodiments of the invention;

FIG. 2A schematically illustrates a frontal cross-sectional view of the magnetic field device, according to illustrative embodiments of the invention;

FIG. 2B schematically illustrates a frontal cross-sectional view of the magnetic field device, with additional magnets, according to illustrative embodiments of the invention

FIG. 3 shows a flow chart for a method of directing magnetic fields into a measurement volume, according to illustrative embodiments of the invention;

FIGS. 4A-4H schematically illustrate top cross-sectional views of various magnetic field devices, according to illustrative embodiments of the invention;

FIG. 5A schematically illustrates a frontal cross-sectional view of a magnetic field device, according to illustrative embodiments of the invention;

FIG. 5B schematically illustrates a frontal cross-sectional view of a magnetic field device, according to illustrative embodiments of the invention; and

FIG. 6 schematically illustrates a frontal cross-sectional view of a head magnetic field device, according to illustrative embodiments of the invention.

It will be appreciated that for simplicity and clarity of illustration, elements shown in the figures have not necessarily been drawn to scale. For example, the dimensions of some of the elements can be exaggerated relative to other elements for clarity. Further, where considered appropriate, reference numerals can be repeated among the figures to indicate corresponding or analogous elements.

DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the invention. However, it will be understood by those skilled in the art that the present invention can be practiced without these specific details. In other instances, well-known methods, procedures, and components have not been described in detail so as not to obscure the present invention.

FIG. 1A schematically illustrates a cross-sectional perspective view of a magnetic field device **100**, according to illustrative embodiments of the invention. The magnetic field device **100** can include an outer shell **111**, a first magnet **101** (e.g., a first permanent magnet), a first ferromagnetic element **102** (e.g., a first pole piece), and a second magnet **121** (e.g., a second permanent magnet) and a second ferromagnetic element **122** (e.g., a second pole piece). In some embodiments, first magnet **101** and first ferromagnetic element **102** and/or second magnet **121** and second ferromagnetic element **122** can be grouped together as a single unit (e.g., as an assembly).

The first ferromagnetic element **102** can be coupled to and/or positioned adjacent to the first magnet **101**. The second ferromagnetic element **122** can be coupled to and/or positioned adjacent to the second magnet **121**. In some embodiments, the magnetic field device **100** can include a third magnet **130**, positioned between the first ferromagnetic element **102** and the second ferromagnetic element **122**.

The first and second ferromagnetic elements **102**, **122** can be coupled and positioned adjacent to a corresponding first and second magnets **101**, **121** such that the first and second ferromagnetic elements **102**, **122** can be proximal to a gap

150 (e.g., zone of measurement) of the magnetic field device **100**. The first magnet **101** and the second magnet **121** can be distal to the gap **150** of the magnetic field device **100**. The magnetization direction of the first magnet **101** can be parallel to the magnetization direction of the second magnet **121**, along the second axis (indicated “X” in FIG. 1A), where the first and second ferromagnetic elements **102**, **122** can face each other with the gap **150** created therebetween.

In various embodiments, dimensions of the gap **150** (and thus positioning on of the elements **102**, **122**, **101**, **121**) can depend on a subject/object to be measured. For example, if the subject to be measured is an adult human head gap **150** can have dimensions that comfortably fit an adult human head. In another example, if the subject to measured is a mouse, gap **150** can fit the mouse. It is apparent to one of ordinary skill that other objects/subjects can be measured, and that these are examples.

FIG. 1B schematically illustrates a cross-sectional perspective view of a magnetic field device **200**, having additional magnets to the device of FIG. 1A, according to illustrative embodiments of the invention. The magnetic field device **200** can include an outer shell **211**, a first magnet **201**, a first ferromagnetic element **202** (e.g., a first pole piece), a second magnet **221**, a third magnet **230**, a fourth magnet **240**, a first ferromagnetic element **202**, and a second ferromagnetic element **222** (e.g., a second pole piece). The first ferromagnetic element **202** can be coupled to and/or positioned adjacent to the first magnet **201**. The second ferromagnetic element **222** can be coupled to and/or positioned adjacent to the second magnet **221**.

In some embodiments, the magnetic field device **200** can include additional magnets such as magnets **103**, **123** in FIG. 1A or magnets **203**, **223** in FIG. 1B. In some embodiments, magnets **103**, **123** in FIG. 1A are not present.

The first and second ferromagnetic elements **202**, **222** can be coupled to and positioned adjacent to its corresponding first and second magnets **201**, **221** such that the first and second ferromagnetic elements **202**, **222** can be proximal to a gap **250** (e.g., zone of measurement) of the magnetic field device **200**. The first magnet **201** and the second magnet **221** can be distal to the gap **250** of the magnetic field device **200**. The magnetization direction of the first magnet **201** can be parallel to the magnetization direction of the second magnet **221**, along the second axis (indicated “X” in FIG. 1B), where the first and second ferromagnetic elements **202**, **222** can face each other with the gap **250** created therebetween.

The third magnet **230** can be coupled to and can be positioned between the first ferromagnetic element **202** and the second ferromagnetic element **222**.

The third magnet **230** can have a first surface **231** that faces a first surface **204** of the first ferromagnetic element **202** and a second surface **232** that faces a first surface **224** of the second ferromagnetic element **222**. The first surface **231** of the third magnet **230** can abut the first surface **204** of the first ferromagnetic element **202** and the second surface **232** of the third magnet **230** can abut the first surface **224** of the second ferromagnetic element **222**. In some embodiments, the third magnet **230** can have a dimension that allows the third magnet **230** to translate between a first position and a second position, the first position being the first surface **204** of the first ferromagnetic element **202**, the second position being the first surface **224** of the second ferromagnetic element **222**.

The fourth magnet **240** can be positioned between the first ferromagnetic element **202** and the second ferromagnetic element **222** and within the gap **250**. The fourth magnet **240** can have a first surface **241** that faces the first surface **204**

of the first ferromagnetic element **202** and a second surface **242** that faces the first surface **224** of the second ferromagnetic element **222**. The fourth magnet **240** can have a dimension that allows the fourth magnet **240** to translate between a first position and a second position, the first position being the first surface **204** of the first ferromagnetic element **202**, the second position being the first surface **224** of the second ferromagnetic element **222**.

As is apparent to one of ordinary skill in the art, while magnetic gradient coils (creating a magnetic field with application of current) can be utilized in the gap to provide a magnetic gradient, an embodiment of the invention uses permanent magnets that have no need for magnetic gradient coils.

In some embodiments, the first magnet **201**, the second magnet **221** and the third magnet **230** are permanent magnets and/or superconducting magnets and/or resistive magnets. The first magnet **201**, the second magnet **221** and the third magnet **230** can have dimensions that are based on a desired magnetic field strength, a type of object to be imaged, or any combination thereof.

In some embodiments, at least one of the first magnet **201**, the second magnet **221** and the third magnet **230** has a length between 10 and 1100 millimeters, a width between 10 and 300 millimeters, and a height between 45 and 200 millimeters.

Each of the magnets of magnetic field device **200** has a direction of magnetization and creates a magnetic field. The dashed arrows in FIG. 1B indicate a direction of the magnetization of the particular magnet the arrow is displayed on.

The first magnet **201** and second magnet **221** can have the same magnetization direction along a first axis (indicated “Y” in FIG. 1B), for example a transverse axis of the magnetic field device **200**.

The magnetization direction of the third magnet **230** can be opposite to the magnetization direction of the first and second magnets **201**, **221** for instance along the first axis (indicated “Y” in FIG. 1B).

In some embodiments, the first ferromagnetic element **202** and the second ferromagnetic element **222** can extend and can direct the magnetic field produced by the corresponding first magnet **201** and second magnet **221**, and/or reduce noise from outside of the magnetic field device **200**.

FIG. 2A schematically illustrates a frontal cross-sectional view of the magnetic field device **200**, according to illustrative embodiments of the invention. FIG. 2B schematically illustrates a frontal cross-sectional view of the magnetic field device **200**, with additional magnets, according to illustrative embodiments of the invention.

In some embodiments, the magnetic field device **200** can include additional magnets. For example, turning to FIG. 2B, the magnetic field device **200** can include a fifth magnet **203**, and a sixth magnet **223**. In some embodiments at least one of fifth magnet **203** and sixth magnet **223** is a permanent magnet.

In some embodiments, the magnetic field device **200** can include additional magnets **203**, **223** while the third magnet **230** can be coupled to the first and second ferromagnetic elements **202**, **222**.

In various embodiments, the fifth and sixth magnets **203**, **223** are positioned around the first and second magnets **201**, **221**, respectively, for instance the sixth magnet **223** can be positioned around the second magnet **221**.

The fifth and sixth magnets **203**, **223** can have a magnetization direction perpendicular to the magnetization direction of the first magnets **201** along a second axis (indicated “X” in FIG. 2B) perpendicular to the first axis, for example

a longitudinal axis of the magnetic field device **200**. According to some embodiments, the magnetization direction of the at least one fifth magnet **203** can be away from the first magnet **201**, and the magnetization direction of the at least one sixth magnet **223** can be towards the second magnet **221**.

As is apparent to one of ordinary skill in the art, additional magnets can be included in the magnetic field device **200**. For example, in some embodiments, additional third magnets, fifth magnets and/or first magnets can be used.

In some embodiments, the outer shell **211** can include a metal alloy, and can allow confining (or substantially confining) the magnetic field created by the magnets of magnetic field device **200** within the outer shell **211**. In this manner, the existence of a magnetic field outside of the outer shell **211** can be zero and/or negligible. For example, if a device that is susceptible to the effects of a magnetic field (e.g., cell phone, pacemaker, etc.) is positioned adjacent to the outer shell **211** outside of the device **200**, the magnetic field in that location can have a negligible effect on the device. In some embodiments, outer shell **211** can also have an opening so as to provide access to the gap **250**.

In various embodiments, the third magnet **230** and/or the fourth magnet **240** can have a hollow structure and surround the gap **250** between the first and second ferromagnetic elements **202**, **222**. In various embodiments, the third magnet **230** and/or the fourth magnet **240** can be provided in a variety of shapes and sized, for instance cylindrical or triangular, with varying shape and size.

In case that magnetic field device **200** is utilized for magnetic resonant imaging, additional electromagnetic elements can be included, such as a radio frequency (RF) generator or field sensors. The third magnet **230** can be configured to surround the gap **250** between the first and second ferromagnetic elements **202**, **222** in order to, for example, prevent radiation leakage from additional electromagnetic elements, for instance RF generator in magnetic resonance devices. For example, third magnet **230** can be in a shape of a hollow cube or a hollow cylinder surrounding gap **250** in order to, for example, prevent radiation leakage from additional electromagnetic elements outside of third magnet **230**.

The third magnet **230** can contribute to causing the overall magnetic field to be a homogeneous and/or uniform magnetic field, for magnetic field device **200** in the area of measurement. The third magnet **230** can allow for a reduction of size, weight, and/or magnetic field strength of the first and/or second magnets **201**, **221** and/or the fifth and/or sixth magnets **203**, **223** due to, for example, the third magnet **230** contributing to the overall magnetic field strength within the gap. A reduction in size of the first and/or second magnets **201**, **221** and/or the fifth and/or sixth magnets **203**, **223**, can allow for a having lower weight of the magnetic field device with substantially the same field strength compared to, for example, a magnetic field device that does not include the third magnet **230**.

In some embodiments, magnetic field device **200** includes two fifth magnets **203**, and also includes two sixth magnets **223**. In these embodiments, the ability to reduce the size of the magnets due to, for example, the third magnet **230** can provide even further weight reduction of the magnetic field device.

In some embodiments, at least one of the first and second magnets **201**, **221** emits a magnetic field with a predetermined magnetic field strength, wherein the third magnet **230** can emit a magnetic field with a predetermined magnetic field strength, and wherein the strength of the magnetic field

of at least one of the first and second magnets **201**, **221** can be substantially greater than the strength of the magnetic field of the third magnet **230**.

According to some embodiments, the outer shell **211** can constitute the main bulk of the weight of the magnetic field device **200**. Since the addition of the third magnet **230** can reduce weight of other components as well as provide a homogeneous and uniform magnetic field, it can be possible to utilize an outer shell with reduced weight. In some embodiments, a reduction of at least twenty percent can be created for the total weight of the magnetic field device **200** in comparison to, for example, devices that do not have the third magnet. In some embodiments, an increase of at least thirty percent can be created for the magnetic field strength, for example in comparison to, for example, device that do not have the third magnet but have substantially the same total weight of the magnetic field device **200**. The third magnet **230** can allow obtaining stronger magnetic fields and/or lower total magnet weight.

In some embodiments, the area of the fringe field can be reduced from the center of the gap, for example for a limit of a field of about 1 Gauss (sometimes referred to as the 1G line) can be reduced at substantially 100 millimeters. Therefore, reduction of fringe field can cause the dimensions of the outer shell **211** to be reduced, for example, from substantially 860×1032 millimeters to substantially 786×894 millimeters. Reduction of the outer shell **211** can accordingly cause a reduction of the total weight of magnetic field device **200**.

Overall weight of a magnetic field device can be reduced, and for example an increase of over ten percent for the ratio of magnetic field strength to total weight of at least the combination of the first and second magnets and the at least one third magnet. In some embodiments, an increase in magnetic field caused by the third magnets can be larger than the increase that may be achieved by a corresponding enlargement of the first and second magnets (without a third magnet). This is due to the alignment of the third permanent magnets and also due to the scalability of the weight savings such that addition of magnets can cause a reduction of weight.

In some embodiments, the outer shell **211** can also have a smaller surface area compared to a commercially available magnetic resonance device, due to a reduction in fringe weight of the outer shell and/or due to reduction of the fringe field. Such reduction can occur since the addition of the third magnet **230** can increase magnetic field in the gap **250**, between the first and second ferromagnetic elements **202**, **222** and therefore reduce the fringe field of the magnetic field device **200** so that there is no longer a need for the outer shell **211** to be at same large weight and large surface area, for example compared to a commercially available magnetic resonance device.

In some embodiments, additional material, for example including Iron, can be added to magnetic field device **200** in order to further confine and manipulate the magnetic field in the gap. In some embodiments, the added material, for example including Iron and/or Titanium, can be added adjacent to at least one magnet **201** and/or adjacent to at least one ferromagnetic element **202**.

It may be appreciated that regions of high magnetic flux density causing external fringe fields can occur adjacent to connection of the magnets, e.g., indicated with a dashed line in FIG. 4A. In some embodiments, an outer shell (or envelope), usually including Iron, surrounds the magnetic resonance device to reduce the magnetic flux.

In some embodiments, the third magnet **230** can prevent at least a portion of magnetic flux from exiting a gap (e.g., an area where the magnetic field is directed). Magnetic field device **200** can be utilized in order to provide a strong magnetic field while providing reduced weight of the device, for example utilized for magnetic resonant imaging or for other devices where a strong magnetic field can be required. It may be appreciated that addition of the third magnets can counter the magnetic flux, for example in regions indicated with a dashed line in FIG. **4A**, so as to, for example, reduce the fringe fields.

According to some embodiments, an existing magnetic field system that includes two magnets, neither of which includes a third magnet can be modified with insertion of at least one third magnet between the two magnets, in order to, for example, increase the magnetic field within the gap and/or reduce the fringe field. For example, a comparison between three systems: a first system "A" without third magnets, a second system "B" provided with at least one third magnet, and a third system "C" that is modified with the addition of at least one third magnet. In this example, in weight comparison to the first system "A", the second system "B" can have weight reduced at about 5.5%, while the third system "C" can have weight increase at about 6.5%. In this example, in comparison to the first system "A" of field strength in the gap, the second system "B" can have increase of about 15%, and the third system "C" can have increase of about 13%. In this example, in comparison to the first system "A" of fringe field reduction, the second system "B" can have decrease of about 55%, and the third system "C" can have decrease of about 16%. Therefore, in correct positioning of third magnets can provide various advantages to new systems as well as to existing systems that can be modified. It is apparent to one of ordinary skill in the art that the example provided above gives exemplary weight reduction values for explanatory purposes, and that other comparison weight configurations are within the scope of the invention.

Reference is now made to FIG. **3**, which shows a flow chart for a method of directing magnetic fields into a measurement volume, according to some embodiments of the invention.

The method includes generating a first magnetic field in a first direction with a first magnetic field strength (Step **301**). For example, the first and second magnets **201** and **221** as described above in FIG. **1B** can direct a first magnetic field in a first direction and having first magnetic field strength.

The method can further include distributing the first magnetic field into the measurement volume to create a substantially uniform magnetic flux. (Step **302**). For example, the first ferromagnetic element **202** and/or the second ferromagnetic element **222**, as described above in FIG. **1B** can distribute the first magnetic field into the measurement volume.

The method can further include increasing a total magnetic flux into the measurement volume by directing a second magnetic field in a second direction with a second magnetic field strength, where the second direction is parallel to the first direction (Step **303**). For example, the third magnet **230** as described above in FIG. **1** can direct a second magnetic field in a second direction and having second magnetic field strength. In some embodiments, the method includes directing a third magnetic field in a third direction having a third magnetic field strength, wherein the third direction is perpendicular to the first direction. For example, the fifth magnets **203** and/or sixth magnets **223** as described

above in FIG. **2** can direct a third magnetic field in a third direction and having third magnetic field strength.

In some embodiments, the method includes positioning an object within the measurement volume, and performing magnetic field analysis on the object (e.g., by using the magnetic device **200** within a NMR device and/or an MRI device).

In some embodiments, first, second and third magnetic fields are directed such that a desired magnetic field strength is achieved. The desired magnetic field strength can be based on a particular device performing the measurements and/or object to be measured. For example, the desired magnetic field strength can be between 0.5-1.5 T, for magnetic resonance imaging of living human tissue. As is apparent to one of ordinary skill in the art, the desired magnetic field strength shown is for exemplary purposes only, and that the desired magnetic field strengths can vary based on subject/application of the magnetic field.

In some embodiments, the first magnetic field strength and the first direction, and the second magnetic field strength and the second direction are based on a size of the measurement volume and/or type of object to be measured, and/or any combination thereof. In some embodiments, the total magnetic flux in the measurement volume can be a substantially homogeneous field.

Reference is now made to FIGS. **4A-4H**, which schematically illustrate a top cross-sectional view of some exemplary configurations for magnetic components of a magnetic field device (for example magnetic field device **200**), according to some embodiments of the invention. FIG. **4A** schematically illustrates a first exemplary configuration, where at least one third magnet **430** (similar to the third magnet **230**, as shown in FIGS. **1-2**) can be positioned adjacent to the first magnet **401** (similar to the first magnet **201**, as shown in FIGS. **1-2**), for example perpendicularly. Such positioning can be utilized to at least partially surround and/or envelope the gap **450** (similar to gap **250**, as shown in FIGS. **1-2**). In some embodiments, a plurality of the third magnets **430** can be utilized, wherein each third magnet **430** (e.g., main magnets) can have a different size and/or shape. In some embodiments, the fifth and sixth magnets can be positioned such that they do not physically contact the third magnets.

FIG. **4B** schematically illustrates a first exemplary configuration, where at least one first intermediate magnet **432** (e.g., main magnet) can be positioned between two adjacent third magnets **430**. FIG. **4C** schematically illustrates a first exemplary configuration, where at least one second intermediate magnet **434** e.g., main magnet) can be positioned between adjacent third magnet **430** and first intermediate magnet **432**. In some embodiments, at least one of first intermediate magnet **432** and/or second intermediate magnet **434** can be a permanent magnet.

According to some embodiments, an object (or a subject) can be introduced to the gap (or measurement region), for example in order to adjust an element therein, from any one of four possible directions due to, for example, the symmetry of the system. In some embodiments, access can also be provided for introduction of cameras, air conditioning and/or other equipment to be adjacent to the gap.

FIG. **4D** schematically illustrates a first exemplary configuration, where at least one first intermediate magnet **442** can be positioned between two adjacent third magnets **440** and at least one second intermediate magnet **444** can be positioned between two adjacent third magnets **440**. Different sizes and/or shapes of at least one first intermediate magnet **442** and at least one second intermediate magnet **444** can allow differentiation of the magnets, e.g., providing

11

smaller magnets of different shapes at particular locations instead of single large magnet, in order to allow a desired magnetic flux within the gap **450**. In case that shape symmetry about an axis through the center of the third magnet is broken, e.g., for magnetic shimming and/or for creation of an opening to allow access to the gap, other elements (e.g., permanent magnets) can be modified so as to maintain the predetermined magnetic field. In some embodiments, a break in symmetry, e.g., of the shape of the magnet, can require modification of the outer shell as well.

FIG. 4E schematically illustrates a first exemplary configuration, where at least one first intermediate magnet **442** can be positioned at a predetermined distance, based on the predetermined magnetic field strength, from the center of first magnet **401**, in order to allow a desired magnetic flux within the gap **450**. FIG. 4F schematically illustrates a first exemplary configuration, where at least one first intermediate magnet **442** can be positioned between two adjacent third magnets **440** and at least one second intermediate magnet **444** can be positioned between two adjacent third magnets **440**. In some embodiments, addition of the at least one first intermediate magnet **442** can be configured to further support the structure of the system and/or to create at least a partial magnetic cage within the gap **450**.

FIG. 4G schematically illustrates a first exemplary configuration, where a circularly shaped third magnet **460** can surround the gap **450**. FIG. 4H schematically illustrates a first exemplary configuration, where a hexagon shaped third magnet **470** can surround the gap **450**. In some embodiments, an opening can be provided in a third magnet surrounding the gap **450** in order to allow insertion of an object therein.

Reference is now made to FIGS. 5A-5B, which show the magnetic field device **500** (e.g., magnetic field device **200** as described above in FIG. 2) including support elements. FIG. 5A schematically illustrates a frontal cross-sectional view of a magnetic field device **500** having first support elements **511**, according to some embodiments of the invention. It may be appreciated that the magnetic field device **500** can include all elements of the magnetic field device **200** (e.g., as shown in FIGS. 1-2) with the addition of at least one first support element **511** between the first ferromagnetic element **202** and the second ferromagnetic element **222**.

According to some embodiments, at least one third magnet **530** can be added to a first support element **511** such that at least one air gap (not shown) can be created between the third magnet **530** and the first and/or second magnets **201**, **221**. In some embodiments, instead of air gaps, a gap of diamagnetic material can be formed therein.

FIG. 5B schematically illustrates a frontal cross-sectional view of a magnetic field device **500** having second support elements **513**, according to some embodiments of the invention. It may be appreciated that the magnetic field device **500** can include all elements of the magnetic field device **200** (e.g., as shown in FIGS. 1-2) with the addition of at least one second support element **513**. In some embodiments, the outer shell **211** (or envelope) can contact at least one third magnet **230** with at least one second support element **513** in order to support the positioning of the third magnets **230**. It may be appreciated that such support of third magnets **230** can counter magnetic attraction forces acting on third magnets **230**, such that third magnet **230** can remain in the desired position. In some embodiments, the at least one second support element **513** can couple the third magnets **230** with at least one of the outer shell **211** and first and second ferromagnetic elements **202**, **222**.

12

Reference is now made to FIG. 6, which schematically illustrates a frontal cross-sectional view of a head magnetic field device **600**, according to some embodiments of the invention. The head magnetic field device **600** includes a first magnet **201** and a first ferromagnetic element **202** coupled to the first magnet **201**, and a second magnet **221** and a second ferromagnetic element **222** coupled to the second magnet **221**. The first magnet **201** and the second magnet **221** can be positioned to create a gap **250** therebetween, with the first ferromagnetic element **202** and the second ferromagnetic element **222** positioned adjacent the gap **250** and between the gap **250** and a respective first magnet **201** and second magnet **221**. The head magnetic field device **600** can also include an opening **650**, the opening configured to allow, for example, at least partial accommodation of a head **610** of a patient within the gap **250** (or measurement volume). In some embodiments, head magnetic field device **600** can also include at least one third magnet **230**. It may be appreciated that while the head **610** of the patient is described here, any other body part can be similarly introduced to the gap **250** for inspection, for example and arm or a leg.

In some embodiments, magnetic resonance imaging elements (e.g., RF coil) can be coupled to the head magnetic field device **600** in order to allow imaging the head **610** of the patient within the gap **250**. In an exemplary embodiment, the magnetic field strength for such a head magnet is above 4900 Gauss or about 4988 Gauss. In an exemplary embodiment, the field of view for MRI imaging within the gap **250** is a sphere with a diameter of about 190 millimeters. In an exemplary embodiment, the diameter of the opening **650** to the gap **250** is above 660 millimeters or about 665 millimeters. In an exemplary embodiment, the dimensions for a permanent head magnet are 1226×1226×866 millimeters.

Unless explicitly stated, the method embodiments described herein are not constrained to a particular order in time or chronological sequence. Additionally, some of the described method elements can be skipped, or they can be repeated, during a sequence of operations of a method.

Various embodiments have been presented. Each of these embodiments can of course include features from other embodiments presented, and embodiments not specifically described can include various features described herein.

The invention claimed is:

1. A magnetic field device, comprising:

- a first magnet;
- a first ferromagnetic element positioned adjacent to the first magnet;
- a second magnet;
- a second ferromagnetic element positioned adjacent to the second magnet and relative to the first ferromagnetic element to create a gap between the first ferromagnetic element and the second ferromagnetic element;
- a third magnet positioned between the first ferromagnetic element and the second ferromagnetic element and within the gap; and
- a fourth magnet positioned between the first ferromagnetic element and the second ferromagnetic element and within the gap.

2. The magnetic field device of claim 1, wherein the third magnet has a first surface that faces a first surface of the first ferromagnetic element and a second surface that faces a first surface of the second ferromagnetic element.

3. The magnetic field device of claim 2, wherein the first surface of the third magnet abuts the first surface of the first

13

ferromagnetic element and the second surface of the third magnet abuts the first surface of the second ferromagnetic element.

4. The magnetic field device of claim 2, wherein the third magnet has a dimension that allows the third magnet to translate between a first position and a second position, the first position being the first surface of the first ferromagnetic element, the second position being the first surface of the second ferromagnetic element.

5. The magnetic field device of claim 1, wherein the fourth magnet has a first surface that faces a first surface of the first ferromagnetic element and a second surface that faces a first surface of the second ferromagnetic element.

6. The magnetic field device of claim 1, wherein the fourth magnet has a dimension that allows the fourth magnet to translate between a first position and a second position, the first position being the first surface of the first ferromagnetic element, the second position being the first surface of the second ferromagnetic element.

7. The magnetic field device of claim 1, wherein the first magnet, the second magnet and the third magnet are permanent magnets, superconducting magnets, or resistive magnets.

8. The magnetic field device of claim 1, wherein the first magnet, the second magnet and the third magnet have dimensions that are based on a desired magnetic field strength, a type of object to be imaged, or any combination thereof.

9. The magnetic field device of claim 1, wherein the first magnet, the second magnet and the third magnet has a length between 10 and 1100 millimeters, a width between 10 and 300 millimeters, and a height between 45 and 200 millimeters.

10. The magnetic field device of claim 1, wherein the gap has dimensions that are based on a type of object to be imaged.

11. The magnetic field device of claim 1, wherein the gap has a diameter of 190 millimeters.

12. The magnetic field device of claim 1, further comprising at least one fifth magnet coupled to the first magnet.

14

13. The device of claim 1, wherein the third magnet is positioned to cause a decrease of a magnetic field that is peripheral to the magnetic field device.

14. The device of claim 1, wherein a first axis of the magnetic field device is defined as passing from the first ferromagnetic element to the second ferromagnetic element, wherein the first magnet and the second magnet are positioned to cause a magnetic field with a magnetization direction along the first axis, and wherein the third magnet is positioned to cause a magnetic field with a magnetization direction along the first axis.

15. The device of claim 14, wherein the magnetization direction of the third magnet is opposite of the magnetization direction of the first magnet.

16. The device of claim 1, wherein at least one of the first and second magnets emits a magnetic field with a predetermined magnetic field strength, wherein the third magnet emits a magnetic field with a predetermined magnetic field strength, and wherein the strength of the magnetic field of at least one of the first and second magnets is substantially greater than the strength of the magnetic field of the third magnet.

17. The device of claim 1, wherein the total magnetic field produced during operation of the magnetic field device is substantially homogeneous and uniform within the gap.

18. A magnetic field device, comprising:
 a first magnet;
 a first ferromagnetic element positioned adjacent to the first magnet;
 a second magnet;
 a second ferromagnetic element positioned adjacent to the second magnet and relative to the first ferromagnetic element to create a gap between the first ferromagnetic element and the second ferromagnetic element;
 a third magnet positioned between the first ferromagnetic element and the second ferromagnetic element and within the gap, wherein the magnetic field device is positioned within an outer shell, the outer shell comprising a metal alloy.

* * * * *