

US010230542B2

(12) **United States Patent**  
**Joshua et al.**

(10) **Patent No.:** **US 10,230,542 B2**  
(45) **Date of Patent:** **Mar. 12, 2019**

(54) **INTERCONNECTED RING NETWORK IN A MULTI-PROCESSOR SYSTEM**

(71) Applicant: **Marvell World Trade Ltd.**, St. Michael (BB)

(72) Inventors: **Eitan Joshua**, Ramot Menashe (IL); **Shaul Chapman**, Alonei Aba (IL); **Erez Amit**, Pardes Hana Karkur (IL); **Noam Mizrahi**, Modiin (IL); **Moshe Raz**, Rishon Lezion (IL); **Husam Khshaiboun**, KFar Kana (IL); **Amit Shmilovich**, Kiryat ATA (IL); **Sujat Jamil**, Gilbert, AZ (US); **Frank O'Bleness**, Tempe, AZ (US)

(73) Assignee: **Marvell World Trade Ltd.**, St. Michael (BB)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 15 days.

(21) Appl. No.: **15/453,262**

(22) Filed: **Mar. 8, 2017**

(65) **Prior Publication Data**

US 2017/0180156 A1 Jun. 22, 2017

**Related U.S. Application Data**

(63) Continuation of application No. 14/155,773, filed on Jan. 15, 2014.

(60) Provisional application No. 61/753,094, filed on Jan. 16, 2013, provisional application No. 61/753,091, filed on Jan. 16, 2013.

(51) **Int. Cl.**  
**H04L 12/46** (2006.01)  
**G06F 12/0813** (2016.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **H04L 12/4637** (2013.01); **G06F 12/0811** (2013.01); **G06F 12/0813** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
None

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,590,117 A 12/1996 Iida et al.  
6,081,868 A 6/2000 Brooks  
(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 1697416 A 11/2005  
CN 102521201 A 6/2012

**OTHER PUBLICATIONS**

"Examiner's Answer", U.S. Appl. No. 14/161,423, dated Jul. 15, 2016, 6 pages.

(Continued)


*Primary Examiner* — Sean D Rossiter

*Assistant Examiner* — Charles J Choi

(57) **ABSTRACT**

In various embodiments, the present disclosure provides a system comprising a first plurality of processing cores, ones of the first plurality of processing cores coupled to a respective core interface module among a first plurality of core interface modules, the first plurality of core interface modules configured to be coupled to form in a first ring network of processing cores; a second plurality of processing cores, ones of the second plurality of processing cores coupled to a respective core interface module among a second plurality of core interface modules configured to be coupled to form a second ring network of processing cores; a first global interface module to form an interface between the first ring network and a third ring network; and a second global interface module to form an interface between the second ring network and the third ring network.

**15 Claims, 15 Drawing Sheets**










Fig. 1

200




Fig. 2




Fig. 3

Distributed snoop filter (DSF) entry 314a1




Fig. 4

Remote line directory (RLD) 318a1




Fig. 5




Fig. 6A




Fig. 6B





Fig. 6C





**Fig. 6D**




Fig. 6E




Fig. 7A




Fig. 7B







Fig. 7C






Fig. 7E





Fig. 8



**Fig. 9**

## 1

**INTERCONNECTED RING NETWORK IN A  
MULTI-PROCESSOR SYSTEM****CROSS REFERENCE TO RELATED  
APPLICATIONS**

The present application is a continuation of and claims priority to U.S. patent application Ser. No. 14/155,773, filed Jan. 15, 2014, which claims priority to U.S. Provisional Patent Application No. 61/753,091, filed Jan. 16, 2013, and to U.S. Provisional Patent Application No. 61/753,094, filed Jan. 16, 2013, the entire specifications of which are hereby incorporated by reference.

**TECHNICAL FIELD**

Embodiments of the present disclosure relate to a computing system, and more specifically, to architecture of a multi-processor system.

**BACKGROUND**

Unless otherwise indicated herein, the approaches described in this section are not prior art to the claims in the present disclosure and are not admitted to be prior art by inclusion in this section.

A multi-processor system generally comprises a plurality of processors. A multi-processor system can also comprise a plurality of caches. In an example, a cache can be accessed only by a corresponding single processor of the plurality of processors. In another example, the cache can be shared, i.e., can be accessed by more than one of the plurality of processors.

**SUMMARY**

In various embodiments, the present disclosure provides a system comprising a first plurality of processing cores, ones of the first plurality of processing cores coupled to a respective core interface module among a first plurality of core interface modules, the first plurality of core interface modules configured to be coupled to form in a first ring network of processing cores; a second plurality of processing cores, ones of the second plurality of processing cores coupled to a respective core interface module among a second plurality of core interface modules, the second plurality of core interface modules configured to be coupled to form a second ring network of processing cores; a first global interface module configured to form an interface between the first ring network and a third ring network by transmitting data between the first ring network and the third ring network, the third ring network interconnecting the first ring network and the second ring network; and a second global interface module configured to form an interface between the second ring network and the third ring network by transmitting data between the second ring network and the third ring network.

In various embodiments, the present disclosure also provides a method comprising communicating, by ones of a first plurality of processing cores coupled to a respective one of a first plurality of core interface modules, with the respective core interface module of the first plurality of core interface modules, the first plurality of core interface modules being arranged in a first ring network; communicating, by ones of a second plurality of processing cores coupled to a respective ones of a second plurality of core interface modules, with the respective core interface module of the second

## 2

plurality of core interface modules, the second plurality of core interface modules arranged in a second ring network; interfacing, by a first global interface module, between the first ring network and a third ring network by transmitting data between the first ring network and the third ring network, the third ring network interconnecting the first ring network and the second ring network; and interfacing, by a second global interface module, between the second ring network and a third ring network by transmitting data between the second ring network and the third ring network.

In various embodiments, the present disclosure also provides a system comprising a plurality of processing cores; a plurality of core interface modules, wherein ones of the plurality of processing cores are coupled to a respective core interface module of the plurality of core interface modules; a plurality of caches, wherein ones of the plurality of core interface modules comprises or is coupled to a respective cache of the plurality of caches; a memory; and a memory interface module coupled to the memory, the memory interface module and the plurality of core interface modules being configured as a first ring network, ones of the plurality of core interface modules configured to interface the respective processing core to the first ring network by transmitting data between the respective processing core and the first ring network, and the memory interface module configured to interface the memory to the first ring network by transmitting data between the memory and the first ring network.

In various embodiments, the present disclosure also provides a method comprising communicating, by ones of a plurality of processing cores coupled to a respective one of a plurality of core interface modules, with the respective core interface module of the plurality of core interface modules; communicating, by ones of the plurality of core interface modules coupled to a respective one of a plurality of caches, with the respective cache of the plurality of caches; and communicating, by a memory interface module, with a memory that is coupled to the memory interface, the memory interface module and the plurality of core interface modules being configured as a first ring network, ones of the plurality of core interface modules configured to interface the respective processing core to the first ring network by transmitting data between the respective processing core and the first ring network, and the memory interface module configured to interface the memory to the first ring network by transmitting data between the memory and the first ring network.

In various embodiments, the present disclosure also provides a method comprising communicating by ones of a plurality of processing cores with a respective core interface module of a plurality of core interface modules, the plurality of core interface modules being configured as a first ring network, wherein ones of the plurality of core interface modules are coupled to a corresponding cache of a plurality of caches; receiving, by a first core interface module of the plurality of core interface modules from a corresponding first processing core of the plurality of processing cores, a transaction request to read data; checking, by the first core interface module, if the data to be read is cached in a first cache that is coupled to the first core interface module; and while checking if the data to be read is cached in the first cache, transmitting, by the first core interface module, the transaction request to a second core interface module to check if the data to be read is cached in a second cache that is coupled to the second core interface module.

In various embodiments, the present disclosure also provides a system comprising a plurality of processing cores; and a plurality of core interface modules, ones of the



plurality of processing cores coupled to a respective core interface module of the plurality of core interface modules, wherein ones of the plurality of core interface modules is associated with a respective cache of a plurality of caches, wherein a first core interface module of the plurality of core interface modules is coupled to a corresponding first processing core of the plurality of processing cores, wherein the plurality of core interface modules is configured as a first ring network, wherein the first core interface module is configured to receive, from the first processing core, a transaction request to read data, check to determine if the data to be read is cached in a first cache that is coupled to the first core interface module, and while checking to determine if the data to be read is cached in the first cache, transmit the transaction request to a second core interface module to check if the data to be read is cached in a second cache that is coupled to the second core interface module.

In various embodiments, the present disclosure also provides a method comprising communicating, by ones of a first plurality of processing cores coupled to a respective one of a first plurality of core interface modules, with the respective core interface module of the first plurality of core interface modules, the first plurality of core interface modules being arranged in a first ring network, ones of the first plurality of core interface modules configured to interface the respective processing core to the first ring network by transmitting data between the respective processing core and the first ring network; communicating, by ones of a second plurality of processing cores coupled to a respective ones of a second plurality of core interface modules, with the respective core interface module of the second plurality of core interface modules, the second plurality of core interface modules being arranged in a second ring network, ones of the second plurality of core interface modules configured to interface the respective processing core to the second ring network by transmitting data between the respective processing core and the second ring network; interfacing, by a global ring network, between the first ring network and the second ring network; receiving, by a first core interface module of the first plurality of core interface modules from a corresponding first processing core of the first plurality of processing cores, a transaction request to read data, a first cache being coupled to the first core interface module; and transmitting, by the first core interface module, the transaction request to a second core interface module of the first plurality of core interface modules to check if the data to be read is cached in a second cache that is coupled to the second core interface module.

In various embodiments, the present disclosure also provides a system comprising a first plurality of processing cores; a first plurality of core interface modules, ones of the first plurality of processing cores coupled to a respective core interface module of the first plurality of core interface modules, the first plurality of core interface modules being arranged in a first ring network, ones of the first plurality of core interface modules configured to interface the respective processing core of the first plurality of processing cores to the first ring network by transmitting data between the respective processing core and the first ring network; a second plurality of processing cores; a second plurality of core interface modules, ones of the second plurality of processing cores coupled to a respective core interface module of the second plurality of core interface modules, the second plurality of core interface modules being arranged in a second ring network, ones of the second plurality of core interface modules configured to interface the respective processing core of the second plurality of processing cores

to the second ring network by transmitting data between the respective processing core and the second ring network; and a global ring network configured to interface between the first ring network and the second ring network, wherein a first core interface module of the first plurality of core interface modules is configured to receive, from a corresponding first processing core of the first plurality of processing cores, a transaction request to read data, a first cache being coupled to the first core interface module, and transmit, by the first core interface module, the transaction request to a second core interface module of the first plurality of core interface modules to check if the data to be read is cached in a second cache that is coupled to the second core interface module.

In various embodiments, the present disclosure also provides a system comprising a memory; and a memory interface module coupled to the memory, the memory interface module configured to control access to the memory, the memory interface module comprising a request combination module configured to: receive a first memory access request to access data stored in the memory; receive a second memory access request to access data stored in the memory; based on the first and second memory access requests, generate a third memory access request; and based on the third memory access request, access the memory to read data from the memory.

In various embodiments, the present disclosure provides a method comprising receiving, by a memory interface module coupled to a memory, a first memory access request to access data stored in the memory, the memory interface module configured to control access to the memory; receiving, by the memory interface module, a second memory access request to access data stored in the memory; based on the first and second memory access requests, generating a third memory access request; and based on the third memory access request, accessing the memory to read data from the memory.

#### BRIEF DESCRIPTION OF THE DRAWINGS

In the following detailed description, reference is made to the accompanying drawings which form a part hereof wherein like numerals designate like parts throughout, and in which is shown by way of embodiments that illustrate principles of the present disclosure. It is noted that other embodiments may be utilized and structural or logical changes may be made without departing from the scope of the present disclosure. Therefore, the following detailed description is not to be taken in a limiting sense, and the scope of embodiments in accordance with the present disclosure is defined by the appended claims and their equivalents.

FIG. 1 schematically illustrates a multi-core processing system comprising a plurality of processing cores arranged in a plurality of ring networks.

FIG. 2 illustrates a system comprising a global ring interconnecting a plurality of local rings.

FIG. 3 illustrates an example core interface module.

FIG. 4 illustrates an example of contents stored in an entry of an example distributed snoop filter.

FIG. 5 illustrates an example remote line directory.

FIGS. 6A-6D illustrate example read operations while a multi-core processing system operates in a static mapped cache architecture mode.

FIG. 6E is a flow diagram illustrating an example method for a read operation while a multi-core processing system operates in the static mapped cache architecture mode.



## 5

FIGS. 7A-7D illustrate example read operations while a multi-core processing system operates in a dynamic mapped cache architecture mode.

FIG. 7E is a flow diagram illustrating an example method for a read operation while a multi-core processing system operates in the dynamic mapped cache architecture mode.

FIG. 8 illustrates a system for combining a plurality of memory access requests.

FIG. 9 is a flow diagram illustrating an example method for operating the system of FIG. 8.

## DETAILED DESCRIPTION

FIG. 1 schematically illustrates a multi-core processing system 100 (henceforth referred to as “system 100”) comprising a plurality of processing cores arranged in a plurality of ring networks (a “processing core” is also referred to herein as a “processor”). The plurality of processors includes a first plurality of processors 120a1, . . . , 120a4, and a second plurality of processors 120b1, . . . , 120b4. In an embodiment, ones of the plurality of processors are coupled to a respective core interface module. For example, each of the processors 120a1, . . . , 120a4, 120b1, . . . , 120b4 is respectively coupled to a corresponding one of core interface modules 122a1, . . . , 122a4, 122b1, . . . , 122b4. In an embodiment, each core interface module comprises (or is coupled to) a corresponding cache. For example, the core interface module 122a1 comprises a corresponding cache 124a1, the core interface module 122b1 comprises a corresponding cache 124b1, and so on.

In an embodiment, the core interface modules 122a1, . . . , 122a4 are arranged in a first ring network 160a (a “ring network” henceforth is also referred to as a “ring”), and the core interface modules 122b1, . . . , 122b4 are arranged in a second ring 160b. For example, the core interface modules 122a1, . . . , 122a4 are coupled or linked using one or more communication links (along with various other components of the system 100, as illustrated in FIG. 1) to form the ring 160a. Similarly, the core interface modules 122b1, . . . , 122b4 are coupled or linked using one or more communication links (along with various other components of the system 100, as illustrated in FIG. 1) to form the ring 160b. Each core interface module forms an interface between the corresponding processor and the corresponding ring. For example, the core interface module 122a1 forms an interface between the corresponding processor 120a1 and the corresponding ring 160a, the core interface module 120b1 forms an interface between the corresponding processor 120b1 and the corresponding ring 160b, and so on.

In an embodiment, a global ring 160g (e.g., illustrated using dotted lines in FIG. 1) interconnects the rings 160a and 160b. For example, the global ring 160g forms an interface between the rings 160a and 160b. The global ring 160g comprises a global interface module 112a configured to interface between the ring 160a and the global ring 160g. The global ring 160g further comprises a global interface module 112b configured to interface between the ring 160b and the global ring 160g. In an example, the global interface modules 112a and 112b are coupled or linked using one or more communication links (along with various other components of the system 100, as illustrated in FIG. 1) to form the global ring 160g. To differentiate the rings 160a and 160b from the global ring 160g, each of the rings 160a and 160b is also referred to herein as a local ring. Thus, in an embodiment, a local ring comprises (i) one or more core interface modules and (ii) at least one global interface module (for example, to interface the local ring to the global

## 6

ring). In an embodiment, a global ring comprises one or more global interface modules to interface with one or more corresponding local rings.

In an embodiment, the system 100 comprises caches 123a1, . . . , 123b4, as illustrated in FIG. 1. For example, ones of the processors 120a1, . . . , 120b4 comprise (or is coupled to) a respective ones of caches 123a1, . . . , 123b4. For example, the processor 120a1 comprises (or is coupled to) the cache 123a1, the processor 120b1 comprises (or is coupled to) the cache 123b1, and so on. In an embodiment, the caches 123a1, . . . , 123b4 are, for example, level 1 (L1) cache, level 2 (L2) cache, and/or the like. In an example, the cache 123a1 can be accessed by the processor 120a1 directly, for instance, without interfacing with any of the rings of the system 100 (for example, by bypassing any of the rings of the system 100). In an example, one or more of the caches 123a1, . . . , 123b4 cache data from one or more memories of the system 100 (for example, memories 128a, 128b, or the like).

In an embodiment, the caches 124a1, . . . , 124b4 are, for example, level 1 (L1) cache, level 2 (L2) cache, last level cache (LLC), and/or the like. In an example, the cache 124a1 is accessible by the processor 120a1 directly, e.g., by bypassing any of the rings 160 of the system 100. As will be discussed in detail herein, for example, the cache 124a1 is also accessible by the processor 120a3 via the ring 160a; and the cache 124a1 is also accessible by the processor 120b1 via the rings 160a and 160b, and the global ring 160g. As such, in embodiments described herein, access to any given cache in system 100 is hierarchical in the sense that the cache is accessible to any processor in system 100, whether directly or by way of communication over one or more rings 160.

In an embodiment, each of the rings 160a and 160b comprises one or more corresponding memory interface modules. For example, the ring 160a comprises a memory interface module 126a, and the ring 160b comprises a memory interface module 126b. The memory interface modules 126a and 126b are respectively coupled to memories 128a and 128b. The memory interface module 126a forms an interface between the memory 128a and the ring 160a, and the memory interface module 126b forms an interface between the memory 128b and the ring 160b. Ones of the memories 128a, 128b are, for example, a random access memory (RAM), a double data rate synchronous dynamic random-access memory (DDR SDRAM), or the like. In an embodiment, the caches 124a1, . . . , 124b3 selectively cache data from the memories 128a and 128b, as will be discussed in detail herein below. In an embodiment, data of, for example, a first memory address of the memory 128a can be cached in one or more caches of the local rings 160a and/or 160b, as will be discussed in detail herein below.

In an embodiment, the system 100 further comprises one or more input/output (I/O) interface modules. For example, the global ring 160g comprises I/O interface modules 114g1 and 114g2. Although not illustrated in FIG. 1, in an embodiment, one or both of the local rings 160a and 160b also comprise one or more corresponding I/O interface modules. In an embodiment, an I/O interface module forms an interface between the associated ring and one or more I/O devices. For example, the I/O interface module 114g1 forms an interface between the global ring 160g and one or more I/O devices 118 (e.g., one or more I/O peripheral devices). In another example, the I/O interface module 114g2 forms an interface between the global ring 160g and a memory management unit 119. The memory management unit 119 is,



for example, a virtual memory system architect (VMSA) component that translates and exhibits security protection on I/O transactions. In an example, the virtual memory system architect (VMSA) component translates addresses between a virtual address space and a physical space, and/or exhibits security protection. In an example, the memory management unit **119** is coupled to one or more I/O devices (for example, one or more I/O devices, labeled as I/O devices **119a** in FIG. **1**), and exchanges data with the I/O devices **119a**, as illustrated in FIG. **1**.

Unless otherwise mentioned and for the purposes of this disclosure, an interface module refers to one of a core interface module, a global interface module, a memory interface module, and/or an I/O interface module.

Unless otherwise indicated, a cluster refers to a corresponding local ring and various components associated with the local ring. For example, a first cluster refers to the local ring **160a**, and various components associated with the local ring **160a** (for example, the core interface modules **122a1**, . . . , **122a4**, the processors **120a1**, . . . , **120a4**, the memory interface module **126a** coupled to the local ring **160a**, the memory **128a** coupled to the memory interface module **126a**, and the like). Similarly, a second cluster refers to the local ring **160b**, and various components associated with the local ring **160b** (i.e., the core interface modules **122b1**, . . . , **122b4**, the processors **120b1**, . . . , **120b4**, the memory interface module **126b** coupled to the local ring **160b**, the memory **128b** coupled to the memory interface module **126b**, and the like).

Although FIG. **1** illustrates each of the rings **160a** and **160b** comprising four respective core interface modules (and four associated processors), in another embodiment, one or both of the rings **160a** and **160b** comprise any different number of core interface modules (and corresponding number of associated processors).

In an embodiment and as discussed, ones of the processors **120a1**, . . . , **120b4** represents a corresponding processing core. However, in another embodiment, a processor of the system **100** of FIG. **1** represents more than one processing core. As an example, the processor **120a1** represents a group or cluster of processing cores. In such an example, the cluster of processing cores (that is represented by the processor **120a1**) is coupled to the local ring **160a** via the core interface module **122a1**, and the cluster of processing cores adheres to protocols associated with the corresponding core interface module.

In an embodiment, the system **100** is located in an integrated circuit chip. For example, the system **100** is a part of a system-on-chip (SoC). In another embodiment, a first section of the system **100** (for example, various components associated with the local ring **160a**) is located in a first integrated circuit chip, and a second section of the system **100** (for example, various components associated with the local ring **160b**) is located in one or more other integrated circuit chips. In such an embodiment, for example, some sections of the global ring **160g** (e.g., the global interface module **112a**) is located in the first integrated circuit chip, while other sections of the global ring **160g** (e.g., the global interface module **112b**) is located in the one or more other integrated circuit chips.

Although FIG. **1** illustrates the global ring **160g** interfacing two local rings **160a** and **160b**, in another embodiment, the global ring **160g** interfaces more than two rings. For example, FIG. **2** illustrates a system **200** comprising a global ring **260g** interconnecting local rings **260a**, . . . , **260d**. The global ring **260g** comprises global interface modules **212a**, . . . , **212d**, that are respectively interconnected with

the local rings **260a**, . . . , **260d**. Although each of the rings **260a**, . . . , **260d** and the global ring **260g** comprises various other components (e.g., similar to the rings **160a**, **160b**, and the global ring **160g** of FIG. **1**), these components are not illustrated in FIG. **2** for purposes of illustrative clarity. For example, the system **200** comprises a plurality of processors, core interface modules, caches, memory interface modules, I/O interface modules, etc., although these components are not illustrated in FIG. **2**. In the system **200** of FIG. **2**, the global ring **260g** is connected to four local rings **260a**, . . . , **260d**, by respective global interface modules **212a**, . . . , **212d**. Thus, as illustrated in FIGS. **1** and **2**, the systems **100a** and **200** are readily scalable, e.g., more local rings can be interfaced with the global ring, for example, by adding corresponding global interface modules in the global ring.

Referring again to FIG. **1**, in an embodiment, various components of the system **100** can issue a transaction request. For example, ones of the processors **120a1**, . . . , **120b3** of the system **100** can selectively issue one or more corresponding transaction requests. Various types of transaction requests can be issued in the system **100**. For example, a read transaction request can be issued by a processor to read data from a cache or from a memory, a write transaction request can be issued by a processor to write data to a cache or to a memory, a cache transaction request can be issued by a processor to perform an operation on a cache (e.g., to evict a cache line from a cache, to update a cache line), and so on.

If a processor of the system **100** issues a transaction request, the corresponding core interface module receives the transaction request and transmits the transaction request to an appropriate destination via the corresponding ring. For example, if the processor **120a1** issues a transaction request, the corresponding core interface module **124a1** receives the transaction request and transmits the transaction request to an appropriate destination, e.g., to another core interface module or a memory interface module in the ring **160a**, or in the ring **160b**. In an embodiment, the core interface modules **124a1**, . . . , **124a3** perform a coherency check on the transaction request issued by the processor **120a1** (as well as any other processor), and/or track coherency information of the transaction request. In an embodiment, the core interface module **124a1** becomes a local interface module on the ring **160a** for a transaction request issued by the associated processor **120a1**. In an embodiment, one of the core interface modules **124a1**, . . . , **124a3** become a home interface module on the ring **160a** for a transaction request issued by the processor **120a1** (or any other processor in the ring **160a**). For example, the transaction request issued by the processor **120a1** has a source address mapped to the core interface module **124a1**, thereby making the core interface module **122a1** the local interface module in the ring **160a** for the transaction request. Thus, a core interface module, from which a transaction request is initialized or issued in a ring, is the local interface module for the transaction request.

A transaction request initialized in a core interface module can also be mapped to another interface module in the system **100**. For example, the core interface module **122a3** can be a destination of the transaction request issued by the processor **120a1**, and accordingly, the core interface module **122a3** forms a home interface module for the transaction request. For purposes of this disclosure and unless otherwise mentioned, the another interface module (e.g., the core interface module **122a3**), which forms a destination for a transaction request, forms a home interface module of the



transaction request. Thus, in an example, a transaction request is initiated in a local interface module, and is transmitted to a corresponding home interface module for handling and processing (e.g., to ensure coherency of the transaction and/or coherency of the caches of the system **100**). In an example, for a transaction request, a corresponding home interface module and a corresponding local interface module can be the same core interface module. For example, if the processor **120a1** issues a transaction request that targets the cache **124a1** of core interface module **122a1**, the core interface module **122a1** is both the home interface module and the local interface module for the transaction request.

Referring again to FIG. 1, in an embodiment, the caches **124a1**, . . . , **124b3** selectively cache data from the memories **128a** and **128b**. Data from the memories **128a** and **128b** can be cached in the caches of the system **100** using static mapping or dynamic mapping. For example, as illustrated in FIG. 1, the memory **128a** is coupled to the ring **160a**, and the memory **128b** is coupled to the ring **160b**. In static mapping, data of a specific memory address of a memory (e.g., memory **128a**) can be cached in specific caches, and the mapping is static in nature. For example, as will be discussed later, one or more tables (e.g., a distributed snoop filter and/or a remote line directory) identify the specific caches in which the data of the specific memory address of the memory can be cached. In an embodiment, in the static mapping, a first data stored in a first address of the memory **128a** may be cached in more than one of the caches **124a1**, . . . , **124b4** of the system **100**, and one or more tables identify the caches in which the first data is potentially cached. In an embodiment, there exists a static map of the first address to one of the caches **124a1**, . . . , **124a4** in the ring **160a**, and to one of the caches **124b1**, . . . , **124b4** in the ring **160b**.

In dynamic mapping, data of a specific memory address of a memory (e.g., memory **128a**) can also be cached in one or more of the caches **124a1**, . . . , **124b4** of the system **100**. However, unlike static mapping, the caches which can potentially cache the data changes (e.g., is dynamic), and the above discussed one or more tables (e.g., the distributed snoop filter and/or the remote line directory) does not necessarily identify the caches in which the data is potentially cached. Static and dynamic mapping will be discussed in more detail herein below.

#### Core Interface Module

FIG. 3 illustrates an example core interface module (for instance, the core interface module **122a1**) of the system **100** of FIG. 1. Although only the core interface module **122a1** is illustrated in FIG. 3, various other core interface modules of the system **100** may have structure that is at least in part similar to that of FIG. 3, in an embodiment.

The example core interface module **122a1** of FIG. 3 comprises the cache **124a1**, although in another embodiment, the cache **124a1** is external to the core interface module **122a1** (e.g., directly coupled to the core interface module **122a1**). The core interface module **122a1** further comprises a coherency control module **310a1**. In an embodiment, the coherency control module **310a1** ensures that the cache **124a1** is coherent (e.g., synchronized) with other caches and memories of the system **100**.

In an embodiment, a memory address in a memory of the system **100** is mapped to one or more corresponding core interface module of the system **100**. For example, each of the addresses of the memory **128a** is assigned to at least one of

the corresponding core interface modules **122a1**, . . . , **122a4**. That is, the entire span of memory addresses of the memory **128a** is assigned among the core interface modules **122a1**, . . . , **122a4** of the ring **160a**. In an example, if a first address of a memory (e.g., the memory **128a**) is mapped to a specific core interface module, the specific core interface module (e.g., the core interface module **122a1**) forms a home interface module of the first memory address. Each memory address of a memory has a corresponding home interface module. If, for example, the first memory address of the memory **128a** has the core interface module **122a1** as the home interface module, then the core interface module **122a1** stores various information associated with cache coherency of the first memory address of the memory **128a**.

Also, a specific address of the memory **128a** may be mapped to more than one core interface module. As an example, a first address of the memory **128a** is mapped to core interface modules **122a1** and **122b1** in an embodiment. Thus, each of the core interface modules **122a1** and **122b1** form home interface modules for the first memory address. Furthermore, the core interface module **122a1** forms a local home interface module for the first memory address in the local ring **160a**, and the core interface module **122b1** forms a local home interface module for the first memory address in the local ring **160b**. As the memory **128a** is coupled to the ring **160a**, the core interface module **122a1** also forms a global home interface module for the first memory address of the memory **128a**. For example, a local home interface module stores various information associated with cache coherency of the first memory address for the corresponding local ring, and a global home interface module stores various information associated with cache coherency of the first memory address for the entire system **100**. In an example, one fourth of the addresses of the memory **128a** are mapped to the core interface modules **122a1** and **122b1**, one fourth of the addresses of the memory **128a** are mapped to the core interface modules **122a2** and **122b2**, one fourth of the addresses of the memory **128a** are mapped to the core interface modules **122a3** and **122b3**, and one fourth of the addresses of the memory **128a** are mapped to the core interface modules **122a4** and **122b4**.

As discussed, in an embodiment, a first data stored in one of the memories of the system (e.g., one of memories **128a** and **128b**) can be cached in more than one of the caches of the system **100**. For example, a first data stored in a first memory address of the memory **128a** can be cached in one or more of the caches **124a1**, . . . , **124b4**. Assume that the core interface module **122a1** is the home interface module (e.g., the global home interface module) of the first memory address of the memory **128a**. In an embodiment, the core interface module **122a1** further comprises a distributed snoop filter (DSF) **314a1**. In an example, the core interface module **122a1** being the home interface module of the first memory address of the memory **128a**, the DSF **314a1** keeps track of all the caches in the local ring **160a** that can store the first data of the first memory address of the memory **128a**. For example, if the first data can be stored (or are stored) in the caches **123a1** and **123a3** of the local ring **160a**, the DSF **314a1** indicates that the first data associated with the first memory address of the memory **128a** can be stored by caches within the processors **120a1** and **120a3**. For example, FIG. 4 illustrates an example of contents stored in an entry of an example distributed snoop filter (e.g., an entry in the DSF **314a1** of FIG. 3). The entry in the DSF **314a1** in FIG. 4 indicates that the first data associated with the first memory address of the memory **128a** can be stored by caches included in the processors **120a1** and **120a3** (i.e., can



## 11

be stored in the caches **123a1** and **123a3**). This indicates that the first data of the first address of the memory **128a** are held by the processors **120a1** and **120a3**. Put differently, if a DSF is included in a first core interface module, then the DSF entry indicates, for a memory address for which the first core interface module is the home interface module, one or more processors, where one or more caches included in the one or more processors can cache the first data.

In an embodiment, for a specific memory address of a memory that is coupled to a first local ring, the corresponding DSF only indicates the processors of the first local ring that can hold the data of the specific memory address. For example, referring to FIG. 4, even if the first data of the first address of the memory **128a** can be cached by caches of the processors **120a1**, **120a3** and **120b2**, the entry of the DSF **314a1** only indicates processors **120a1** and **120a3** (as only these two processors are associated with the local ring **160a**). That is, in this example, the entry of the DSF **314a1** does not indicate that the cache associated with the processor **120b2** can store the first data of the first address of the memory **128a**.

Referring again to FIG. 3, in an embodiment, the core interface module **122a1** further comprises a remote line directory (RLD) **318a1**. In an example, the core interface module **122a1** being the home interface module (e.g., the global home interface module) of a first memory address of the memory **128a**, the RLD **318a1** keeps track of all the remote clusters in the system **100** that store the first data of the first memory address of the memory **128a**, in an embodiment. For example, assume the first data can be stored (or are stored) in the caches **120a1** and **120a3** of the local ring **160a**, and in the cache **124b2** of the local ring **160b**. Then, the RLD **318a1** indicates that the first data associated with the first memory address of the memory **128a** can be stored in a cluster associated with the local ring **160b**. That is, the RLD **318a1** identifies one or more remote clusters (i.e., one or more clusters that are remote to, or different from the cluster associated with the local ring **160a**) that can cache the first data associated with the first memory address of the memory **128a**. FIG. 5 illustrates an example remote line directory (e.g., the RLD **318a1** of FIG. 3). The RLD **318a1** in FIG. 5 indicates that the first data associated with the first memory address of the memory **128a** can be stored in a cluster 2 (e.g., which is associated with the local ring **160b**). Thus, the RLD **318a1** in FIG. 5 identifies all the remote clusters (and the associated remote local rings) in which the first data associated with the first memory address of the memory **128a** can be stored. It is noted that although the cluster associated with the local ring **160a** can cache the first data associated with the first memory address of the memory **128a**, the RLD **318a1** does not identify the cluster associated with the local ring **160a**—rather, the RLD **318a1** only identifies remote clusters (that is, clusters that are remote to, or different from the cluster associated with the local ring **160a**) that can cache the first data associated with the first memory address of the memory **128a**.

A first cluster associated with the local ring **160a** is a home cluster for the first memory address of the memory **128a** (e.g., as the memory **128a** is included in the first cluster). A second cluster associated with the local ring **160b** is a remote cluster for the first memory address of the memory **128a**. The RLD **318a1** selectively identifies one or more remote clusters for caching the first data stored in the first memory address of the memory **128a**, in an embodiment.

## Cache Architecture

As previously discussed, the cache architecture of the system **100** comprises a multi-bank cache (e.g., a plurality of

## 12

cache slices, including caches **124a1**, . . . , **124b4**), in which each cache can be accessed by more than one processor. In the system **100**, the access time to different caches differs and depends on a requesting processor (i.e., the processor that requests the cache access). For example, a time taken for the processor **120a1** to access the cache **124a1** is relatively less compared to a time taken for the processor **120a1** to access the cache **124a2**. Similarly, the time taken for the processor **120a1** to access the cache **124a2** is relatively less compared to a time taken for the processor **120a1** to access the cache **124b4**. The cache architecture of the system **100** is also referred to herein as Non Unified Cache Architecture (NUCA), for example, as the time taken takes by ones of the processors to access ones of the caches is non-uniform.

In an embodiment, the cache architecture of the system **100** can operate in one of a plurality of modes. For example, the cache architecture of the system **100** can operate in one of a static mapped cache architecture mode and a dynamic mapped cache architecture mode.

In the static mapped cache architecture mode, a specific memory address of, for example, the memory **128a** is statically mapped to one of the caches in ring **160a** and to one of the caches in ring **160b**. Furthermore, in the static mapped cache architecture mode, the mapping of the specific memory address of the memory **128a** to the cache is in accordance with the corresponding DSF and RLD residing in the home interface module (e.g., the global home interface module) of the specific memory address. For example, in the static mapped cache architecture mode, if the core interface module **122a1** is the home interface module of the specific memory address of the memory **128a**, then the DSF and RLD residing in the core interface module **122a1** identifies the specific caches in which the data of the specific memory address can be cached. If a cache (e.g., the cache **123a1**) can cache the data of the specific memory address of the memory **128a**, then the corresponding processor (e.g., the processor **120a1**) is said to hold the data of the specific memory address of the memory **128a**.

In the dynamic mapped cache architecture mode, a specific memory address of, for example, the memory **128a** is allocated dynamically to any cache of the system **100** for caching, in an embodiment. Thus, in the dynamic mapped cache architecture mode, data of the specific memory address of the memory **128a** can be dynamically allocated and cached in any cache of the system **100** (e.g., to any cache in the local ring **160a** and/or the local ring **160b**). In an embodiment, in the dynamic mapped cache architecture mode, the caching of the data of the specific memory address of the memory **128a** by one or more caches of the system **100** may not be in accordance with the DSF and RLD residing in the home interface module (e.g., the global home interface module) of the specific memory address.

The following sections discuss operations of the system **100** in the static mapped cache architecture mode and the dynamic mapped cache architecture mode in more details.

## Static Mapped Cache Architecture Mode

FIG. 6A illustrates an example read operation while a multi-core processing system (e.g., the system **100** of FIG. 1) operates in a static mapped cache architecture mode. FIG. 6A is a simplified version of FIG. 1. For example, in FIG. 6A, only one local ring **0** (e.g., which may be any one of the rings **160a** and **160b**) is illustrated. Furthermore, for purposes of simplicity, in FIG. 6A, the processors of the local ring **0** are labeled as P0, . . . , P3, and the respective core interface modules are labeled as CIM 0, . . . , CIM 3.



Furthermore, each of the core interface modules CIM 0, . . . , 3 is associated with a corresponding one of the caches 0, . . . , 3, as illustrated in FIG. 6A. In FIG. 6A, each cache is illustrated to be external to the corresponding core interface module, although in another embodiment (e.g., as illustrated in FIG. 1), the cache can be included in the corresponding core interface module. FIG. 6A also illustrates various transaction requests transmitted between various components of the local ring 0.

In FIG. 6A and various subsequent figures (e.g., FIGS. 6B-7D), issuance, processing and/or transmission of a transaction request (or data) is identified by a number and a type of the transaction request. For example, each action in these figures is labeled using a corresponding number and one or more corresponding alphabets indicating a type of the action. For example, FIG. 6A illustrates 0AR, 1AR, etc. The numbers indicate a sequence in which the associated action occurs. For example, the action associated with the number "1" occurs subsequent to the action associated with the number "0". If two actions have the same number, the two actions can at least in part occur simultaneously.

In the example of FIG. 6A, the processor P1 initiates a transaction request, which may be an address request to read data cached in a cache of the local ring 0. For example, initially, the processor P1 issues an address request (labeled as 0AR in FIG. 6A) to the corresponding CIM 1. Thus, the CIM 1 is the local interface module of the transaction request. In the example of FIG. 6A, assume that the CIM 3 is the home interface module (i.e., the CIM 3 is the destination of the address request, and is to process the address request). The address request issued by the processor P1 has an address of the home interface module (i.e., identifies the CIM 3 as the home interface module). In a static mapped cache architecture mode, this implies that the cache 3 associated with the CIM 3 can cache the data that the processor P1 wants to access. Accordingly, the CIM 1 forwards the address request to the CIM 2 (e.g., illustrated as 1AR in FIG. 6A); and subsequently, the CIM 2 forwards the address request to the CIM 3 (e.g., illustrated as 2AR in FIG. 6A). Once the CIM 3 receives the address request, the CIM 3 determines that the address request results in a cache hit (e.g., illustrated as 3 cache hit in FIG. 6A). That is, the requested data is cached in the cache 3. The CIM 3 access and reads the data from the cache 3 (e.g., illustrated as 4RD in FIG. 6A), and the cache 3 outputs the data (e.g., illustrated as 5DATA in FIG. 6A) to the CIM 3. The CIM 3 receives the data read from the cache 3, and transmits the data to the processor P1 (i.e., to the initiator of the request), via CIM 2 and CIM 1 (e.g., illustrated as 6R, 7R and 8R in FIG. 6A).

In FIG. 6A, the read request was a hit at the cache 3 of the home interface module. However, in another example, the read request may not result in a cache hit in the cache of the home interface module. FIG. 6B illustrates another example read operation while a multi-core processing system (e.g., the system 100 of FIG. 1) operates in the static mapped cache architecture mode. In FIG. 6B, the read request results in a cache miss in the cache of the home interface module. Similar to FIG. 6A, in the example of FIG. 6B, the processor P1 initiates an address request (labeled as 0AR in FIG. 6B) to, for example, read data. The data to be read is stored in a specific address of the memory 0, which has the CIM 3 as the home interface module. Accordingly, the CIM 1 is the local interface module of the address request and the CIM 3 is the home interface module (i.e., the CIM 3 is the destination of the address request, and is to process the address request). The address request issued by the processor P1 reaches the CIM 3, via CIM 1 and CIM 2 (e.g., illustrated as

1AR and 2AR in FIG. 6B). Once the CIM 3 receives the address request, the CIM 3 determines a cache miss (e.g., illustrated as 3 cache miss in FIG. 6B). That is, the cache 3 does not have a valid copy of the requested data.

In response to the cache miss in the cache 3, the CIM 3 then forwards the address request by the to the memory interface module 0 (e.g., illustrated as 4AR in FIG. 6B). The memory interface module 0 reads the data from the memory 0 (e.g., illustrated as 5RD in FIG. 6B), and transmits the data read from the memory 0 to the processor P1, via the global interface module 0, the CIM 0 and the CIM 1 (e.g., illustrated as 7R, 8R, 9R and 10R in FIG. 6B). The CIM 1 also transmits the data read from the memory 0 to the CIM 3 (e.g., illustrated as 10R and 11R in FIG. 6B). Once the CIM 3 receives the data, the CIM 3 writes the data to the cache 3 (e.g., illustrated as 12W in FIG. 6B). Thus, in FIG. 3, in response to the cache miss in the cache 3 associated with the home interface module, the requested data is directly fetched from the memory 0.

In FIGS. 6A and 6B, the local interface module and the home interface module were in the same local ring. That is, the processor P1 of the local ring 0 attempted to read data cached in the cache 3 of the local ring 0.

FIG. 6C illustrates another example read operation while a multi-core processing system (e.g., the system 100 of FIG. 1) operates in the static mapped cache architecture mode. In the example of FIG. 6C, a processor of a local ring 0 reads data from a different local ring (e.g., a local ring 1). Similar to FIG. 6A, the system in FIG. 6C has the local ring 0, associated processors P0, . . . , P3, associated CIMs 0, . . . , 3, associated caches 0, . . . , 3, and memory interface module 0. In addition, FIG. 6C illustrates a second local ring 1 comprising processors P10, . . . , P13, CIMs 10, . . . , 13, caches 10, . . . , 13, a memory interface module 1, and a memory 1 coupled to the memory interface module 1. A global ring (e.g., illustrated using dotted lines in FIG. 6C), comprising global interface modules 0 and 1, interconnects the two local rings 0 and 1.

In FIG. 6C, the processor P2 issues a transaction request to read data that is stored in a specific memory address of the memory 1. That is, the processor P2, which is in local ring 0, attempts to read data stored in the specific memory address of the memory 1 that is coupled to the local ring 1. The CIM 2 is the local interface module, as the transaction is issued in the processor P2.

Also assume that the data in the specific memory address of the memory 1 can be cached by the caches 1 and 11. Thus, the cache 1 is the local home interface module for the specific memory address of the memory 0 in the ring 0, and the cache 11 is the local home interface module for the specific memory address of the memory 1 in the ring 1. Furthermore, as the memory 1 is coupled to the local ring 1, the cache 11 is also the global home interface module for the specific memory address of the memory 1. For example, a DSF maintained by the global home interface module (i.e., the CIM 11) identifies that the cache 11 can potentially cache the data of the specific memory address of the memory 1. Furthermore, an RLD maintained by the global home interface module (i.e., the CIM 11) identifies that the data of the specific memory address of the memory 1 is potentially cached in caches of both the local rings 0 and 1.

Referring again to FIG. 6C, when the processor P2 issues the address request to the CIM 2 (e.g., illustrated as 0AR), the cache 1 associated with the CIM 1 (i.e., the local home interface module) is checked first to determine if the requested data is stored in the cache 1. As illustrated in FIG. 6C, it is determined that the requested data is a miss in the



## 15

cache 1 (e.g., illustrated as 2 cache miss in FIG. 6C). As the requested data is not stored in cache 1 of the local home interface module CIM 1 of the local ring 0, the cache 11 of the CIM 11 (i.e., the global home interface module) is then checked to determine if the requested data is cached therein. For example, the transaction request is transmitted from the CIM 1 to the CIM 11 via the CIM 0, the global interface module 0, the global interface module 1, and the CIM 10 (e.g., illustrated as 3AR, . . . , 7AR in FIG. 6C).

In the example of FIG. 6C, the transaction request also results in a cache miss in cache 11 of the global home interface module CIM 11. Accordingly, the transaction request is transmitted to the memory interface module 1, e.g., to fetch the requested data from the memory 1 (e.g., illustrated as 9AR, . . . , 12RD in FIG. 6C). Once the data is read by the memory interface module 1 from the memory 1, the requested data is transmitted to the processor P2 via the global interface modules 1 and 0, and the CIMs 0, 1 and 2 (e.g., illustrated as 14R, . . . , 19R in FIG. 6C). In an embodiment, the data read from the memory 1 may also be transmitted to one or both of the caches 1 and 11 (i.e., to the caches associated with the local and global home interface module), for caching the data (e.g., caching of the data in the cache 1 is illustrated as 18W in FIG. 6C).

It is noted that in FIG. 6C, 18W indicates transmitting the data from the CIM 1 to the cache 1, and 18R indicates transmitting the data from the CIM 1 to the CIM 2. Both these actions having the same numerical “18” indicates that these two actions can be performed at least in part simultaneously.

FIG. 6D illustrates another example read operation while a multi-core processing system (e.g., the system 100 of FIG. 1) operates in the static mapped cache architecture mode. The system architecture of FIG. 6D is similar to that of FIG. 6C. For example, both FIGS. 6C and 6D illustrate the two local rings 0 and 1, various components associated with the local ring, and the global ring connecting the two local rings.

In FIG. 6D, the processor P2 issues a transaction request to read data that is stored in a specific memory address of the memory 0. That is, the processor P2, which is in local ring 0, attempts to read data stored in the specific memory address of the memory 0 that is also coupled to the local ring 0. The CIM 2 is the local interface module, as the transaction is issued in the processor P2.

In the example of FIG. 6D, assume that the data in the specific memory address of the memory 0 can be cached by the caches 1 and 11. Thus, the CIM 1 is the local home interface module in the local ring 0 for the specific memory address of the memory 0, and the CIM 11 is the local home interface module in the local ring 1 for the specific memory address of the memory 0. Furthermore, as the memory 0 is coupled to the local ring 0, the CIM 1 is also the global home interface module for the specific memory address of the memory 0. An RLD maintained by the global home interface module (i.e., the CIM 1) identifies that the data of the specific memory address of the memory 0 is potentially cached in caches of the local ring 1.

In FIG. 6D, when the processor P2 issues the address request to the CIM 2 (e.g., illustrated as 0AR), the cache 1 associated with the CIM 1 (i.e., the global home interface module) is checked first to determine if the requested data is stored in the cache 1. As illustrated in FIG. 6D, it is determined that the requested data is a miss in the cache 1 (e.g., illustrated as 2 cache miss in FIG. 6D). As the requested data is not stored in cache 1 of the global home interface module CIM 1 of the local ring 0, the RLD included in the CIM 1 is looked up to check if the requested

## 16

data is cached in a cache of a remote local ring. In the example of FIG. 6D, the RLD of CIM1 returns a HIT (illustrated as 2RLD hit in FIG. 6D) and points to the local ring 1. Accordingly, the cache 11 of the CIM 11 (i.e., the local home interface module in the local ring 1) is then checked to determine if the requested data is cached therein. For example, the transaction request is transmitted from the CIM 1 to the CIM 11 via the CIM 0, the global interface modules 0 and 1, and the CIM 10 (e.g., illustrated as 3AR, . . . , 7AR in FIG. 6D). In the example of FIG. 6D, the transaction request results in a cache hit in cache 11 of the local home interface module CIM 11 of the local ring 1 (e.g., illustrated as 8 cache hit in FIG. 6D). The requested data is read by the CIM 11 from the cache 11 (e.g., illustrated as 9RD and 10DATA in FIG. 6D). Subsequently, the data read from the cache 11 is transmitted from the CIM 11 to the processor P2, as illustrated in FIG. 6D (e.g., illustrated as 11R, . . . , 17R in FIG. 6D). Also, when the CIM 1 receives the data read from the cache 11, in an embodiment, the CIM 1 may also store the data in the cache 1 (e.g., illustrated as 16W in FIG. 6D). It is to be noted that in FIG. 6D, 16W indicates transmitting the data from the CIM 1 to the cache 1, and 16R indicates transmitting the data from the CIM 1 to the CIM 2. Both these actions having the same numerical “16” indicates that these two actions are performed at least in part simultaneously, in an embodiment.

FIG. 6E is a flow diagram illustrating an example method 650 for a read operation while a multi-core processing system (e.g., the systems illustrated in FIGS. 6A-6D) operates in the static mapped cache architecture mode. Referring to FIGS. 6A-6E, at 654, ones of a first plurality of processing cores (e.g., processors P0, . . . , P3) coupled to a respective one of a first plurality of core interface modules (e.g., CIMs 0, . . . , 3) communicates with the respective core interface module of the first plurality of core interface modules, the first plurality of core interface modules being arranged in a first ring network (e.g., local ring 0); ones of a second plurality of processing cores (e.g., processors P10, . . . , P13) coupled to a respective ones of a second plurality of core interface modules (e.g., CIMs 10, . . . , 13) communicates with the respective core interface module of the second plurality of core interface modules, the second plurality of core interface modules being arranged in a second ring network (e.g., local ring 1); and a global ring network interfaces between the first ring network and the second ring network.

At 658, a first core interface module (e.g., CIM 2 of FIG. 6C) of the first plurality of core interface modules receives from a corresponding first processing core (e.g., processor P2) of the first plurality of processing cores receives a transaction request to read data, a first cache (e.g., cache 2) being coupled to the first core interface module.

At 662, the first core interface module transmits the transaction request to a second core interface module (e.g., CIM 1, which is the local home interface module in the first ring network) of the first plurality of core interface modules to check if the data to be read is cached in a second cache (e.g., cache 1) that is coupled to the second core interface module.

At 666, it is determined that the data to be read is not cached in the second cache (e.g., illustrated as 2 cache miss in FIG. 6C), and is potentially cached in a third cache of the second ring network (e.g., based on an RLD hit); and in response to determining that the data to be read is not cached in the second cache (and is potentially cached in a third cache of the second ring network), the second core interface module transmits the transaction request to a third core



interface module (e.g., CIM 11 of FIG. 6C, which is the local home interface module in the second ring network) of the second plurality of core interface modules to check if the data to be read is cached in the third cache (e.g., cache 11) that is coupled to the third core interface module.

At 670, it is determined that the data to be read is not cached in the third cache (e.g., illustrated as 8 cache miss in FIG. 6C); and in response to determining that the data to be read is not cached in the third cache, the transaction request is transmitted to a memory interface module (e.g., memory interface module 1) to fetch the data from a memory (e.g., memory 1) that is coupled to the memory interface module.

#### Dynamic Mapped Cache Architecture Mode

As previously discussed, in the static mapped cache architecture mode, for a specific memory address of, for example, the memory 128a of system 100, a corresponding DSF keeps track of the caches included in the corresponding processors (e.g., caches 123a1, . . . , 123a4 of FIG. 1); and a corresponding RLD keeps track of the caches included in one or more remote rings (e.g., RLDs of CIM0, . . . , CIM3 keeps track of caches in the CIMs of the local ring 1, i.e., CIM10, . . . , CIM13). Accordingly, in the static mapped cache architecture mode, as discussed with respect to FIGS. 6A-6D, caches associated with the home interference modules (e.g., one or more local and global home interference modules), or any other cache as indicated in the corresponding DSF and/or the RLD, are checked to determine if a data requested by a processor is cached. That is, in the static mapped cache architecture mode, a transaction checks a pre-determined number of caches (e.g., based on the corresponding DSF and/or the RLD) to determine if the data requested is cached in any of these caches. If the data requested by is not cached in any of these caches, the data is fetched from the memory, in an embodiment.

In contrast, in the dynamic mapped cache architecture mode, for a specific memory address of, for example, the memory 128a of system 100, the caches attached to the CIM (e.g., caches 124a1, . . . , 124b3 in FIG. 1) can hold data that is not tracked by the corresponding DSF and RLD of same node. For example, in the dynamic mapped cache architecture mode, one or more caches dynamically caches the data of the specific memory address of the memory 128a, while the RLD and DSF tracking the same data can be in a different CIM. To locate a cached data, in the dynamic mapped cache architecture mode, when a processor requests data of a specific memory address of, for example, the memory 128a, the caches associated with the local interface module and the home interface modules are checked first. If the requested data is not stored in these caches, any other number of caches in the system can also be checked to determine if any of these other caches have cached the requested data. The dynamic mapped cache architecture mode is discussed in detail herein below.

FIG. 7A illustrates an example read operation while a multi-core processing system (e.g., the system 100 of FIG. 1) operates in a dynamic mapped cache architecture mode. The architecture presented in FIG. 7A is similar to FIG. 6A. For example, FIG. 7A illustrates only one local ring 0 (e.g., any one of the rings 160a and 160b) comprising processors P0, . . . , P3, core interface modules CIM 0, . . . , CIM 3, caches 0, . . . , 3, the memory interface module 0, and the memory 0.

In the example of FIG. 7A, the processor P1 initiates an address request to, for example, read data of a specific memory address of the memory 0, which may be cached in

one of the caches of the local ring 0. For example, initially, the processor P1 issues an address request (labeled as 0AR in FIG. 7A) to the corresponding CIM 1. Thus, the CIM 1 is the local interface module of the transaction request. In the example of FIG. 7A, assume that the CIM 3 is the home interface module of the transaction request (i.e., i.e. the DSF and RLD that track the address of the transaction are in CIM3).

In dynamic mapped cache architecture mode, the data requested by the processor P1 may, with relatively high probability, be cached in the caches associated with the local interface module and/or the home interface module. For example, in an embodiment, a heuristic algorithm attempts to ensure that the data, which is to be likely requested by a processor, is cached in the cache coupled to the processor or in a cache of the associated home interface module. The heuristic algorithm, for example, is based on past data requested by the processor, a prior knowledge about which application runs on which processor (and which processor may request data), and/or the like. For example, the data requested by the processor P1 may, with relatively high probability, be cached in the cache 1; and when a data is found to be shared by multiple processors, the data may be cached with relatively high priority in the cache of the home interface module (e.g., cache 3 of the CIM 3). For example, the data requested by the processor P1 may, with relatively high probability, be cached in the caches 1 and 3. Accordingly, the cache 1 (associated with the local CIM 1) and cache 3 (associated with the home interface module CIM 3) are checked first to determine if the data requested by the processor P1 is cached in one of the caches 1 and 3.

Accordingly, once the CIM 1 receives the address request, the CIM 1 determines whether the address request is a cache hit or a cache miss in the cache 1. In the example of FIG. 7A, the address request results in a cache hit in the cache 1 (e.g., illustrated as 1 cache hit in FIG. 7A). While the CIM 1 determines whether the address request is a cache hit or a cache miss in the cache 1, the CIM 1 also at least partially simultaneously transmits the address request to the home interface module CIM 3 (e.g., illustrated as 1AR and 2AR in FIG. 7A). Thus, in FIG. 7A, the CIM 1 transmits the address request to the CIM 3 irrespective of whether the address request results in a cache hit or a cache miss in the cache 1. For example, the CIM 1 transmits the address request to the CIM 3, while the CIM 1 checks to determine if the address request results in a cache hit in the cache 1.

Also, the address request results in a cache miss, an RLD miss and a DSF miss in CIM 3 (e.g., illustrated as 3 cache miss, 3 DSF miss, 3 RLD miss in FIG. 7A). The CIM 3 transmits a response to the CIM 1 (e.g., illustrated as 4Resp and 5Resp in FIG. 7A), indicating that the address request resulted in a cache miss in the cache 3. As the address request results in a cache hit in the cache 1, the CIM 1 reads the requested data from the cache 1 (e.g., illustrated as 2RD and 3DATA in FIG. 7A). Prior to, subsequent to or while the CIM 1 receives the response from the CIM 3 indicating the cache miss in the cache 3, the CIM 1 transmits the requested data, read from the cache 1, to the processor P1. In the example of FIG. 7, subsequent to the CIM 1 receiving the response from the CIM 3 indicating the cache miss in the cache 3, the CIM 1 transmits the requested data, read from the cache 1, to the processor P1 (e.g., illustrated as 6R in FIG. 7A).

FIG. 7B illustrates another example read operation while a multi-core processing system (e.g., the system 100 of FIG. 1) operates in the dynamic mapped cache architecture mode. In FIG. 7A, the address request resulted in a cache hit in the



cache of the local interface module, while resulting in a cache miss in the home interface module. In contrast, in FIG. 7B, the address request results in a cache miss in the cache of the local interface module, while resulting in a cache hit in the home interface module.

Similar to FIG. 7A, in the example of FIG. 7B, the processor P1 initiates an address request to, for example, read data of a specific memory address of the memory 0. Also, similar to FIG. 7A, in the example of FIG. 7B, the CIM 1 is the local interface module and the CIM 3 is the home interface module.

In FIG. 7B, initially, the processor P1 issues an address request (labeled as 0AR in FIG. 7A) to the corresponding CIM 1. Once the CIM 1 receives the address request, the CIM 1 determines whether the address request is a cache hit or a cache miss in the cache 1. In the example of FIG. 7B, the address request results in a cache miss in the cache 1 (e.g., illustrated as 1 cache miss in FIG. 7B). While the CIM 1 determines whether the address request is a cache hit or a cache miss in the cache 1, the CIM 1 also transmits the address request to the home interface module CIM 3 (e.g., illustrated as 1AR and 2AR in FIG. 7B). Thus, in FIG. 7B, the CIM 1 transmits the address request to the CIM 3 irrespective of whether the address request results in a cache hit or a cache miss in the cache 1.

In the example of FIG. 7B, the address request results in a cache hit in the cache 3 (e.g., illustrated as 3 cache hit in FIG. 7B). The CIM 3 reads the requested data from the cache 3 (e.g., illustrated as 4RD and 5DATA in FIG. 7B), and transmits the data read from the cache 3 to the processor P1 via the CIM 2 and the CIM 1 (e.g., illustrated as 6R, 7R and 8R in FIG. 7B).

FIG. 7C illustrates another example read operation while a multi-core processing system (e.g., the system 100 of FIG. 1) operates in the dynamic mapped cache architecture mode. As discussed, in FIG. 7A, the address request resulted in a cache hit in the cache of the local interface module, while resulting in a cache miss in the home interface module. Also, in FIG. 7B, the address request resulted in a cache miss in the cache of the local interface module, while resulting in a cache hit in the home interface module. In contrast, in FIG. 7C, the address request results in a cache miss in the caches of both the local interface module and the home interface module, as a result of which other caches of the local ring 0 are checked.

Similar to FIGS. 7A and 7B, in the example of FIG. 7C, the processor P1 initiates an address request to, for example, read data of a specific memory address of the memory 0. Also, similar to FIGS. 7A and 7B, in the example of FIG. 7C, the CIM 1 is the local interface module and the CIM 3 is the home interface module.

In FIG. 7C, initially, the processor P1 issues an address request (labeled as 0AR in FIG. 7C) to the corresponding CIM 1. Once the CIM 1 receives the address request, the CIM 1 determines whether the address request is a cache hit or a cache miss in the cache 1. In the example of FIG. 7C, the address request results in a cache miss in the cache 1 (e.g., illustrated as 1 cache miss in FIG. 7C). While the CIM 1 determines whether the address request is a cache hit or a cache miss in the cache 1, the CIM 1 also transmits the address request to the home interface module CIM 3 (e.g., illustrated as 1AR and 2AR in FIG. 7C). Thus, in FIG. 7C, the CIM 1 transmits the address request to the CIM 3 irrespective of whether the address request results in a cache hit or a cache miss in the cache 1.

In the example of FIG. 7C, the address request also results in a cache miss in the cache 3 (e.g., illustrated as 3 cache hit

in FIG. 7C), along with a DSF miss and RLD miss. The CIM 3 transmits a response to the CIM 1 (e.g., illustrated as 4Resp and 5Resp in FIG. 7C), indicating that the address request resulted in a cache miss in the cache 3.

As the address request resulted in a cache miss in caches of both the local interface module and the home interface module, the CIM 1 then transmits the address request to (i) one or more other caches of the local ring 0 (e.g., to caches of all the interface modules of the local ring 0, except the local interface module and the home interface module), and (ii) to the memory interface module 0. For example, subsequent to receiving indication that the address request resulted in a cache miss in the cache 3, the CIM 1 transmits address requests to each of CIM 0 and CIM 2 (e.g., illustrated as 6AR and 6AR in FIG. 7C), to check if the requested data is cached in one or both of the caches 0 and 2. The address request is also transmitted to the memory interface module 0. In an embodiment, the CIM 1 initiates the transmission of the address requests to each of the CIM 0 and CIM 2 at least in part simultaneously. In an example, the address request is transmitted to the memory interface module 0 via (i) the CIM 0 and (ii) the global interface module 0 (illustrated as 7AR and 8AR in FIG. 7C).

In the example of FIG. 7C, the address requests also results in a cache miss in the cache 0 (e.g., illustrated as 7 cache miss in FIG. 7C), while resulting in a cache hit in the cache 2 (e.g., illustrated as 7 cache hit in FIG. 7C). The CIM 2 reads the requested data from the cache 2 (e.g., illustrated as 8RD and 9DATA in FIG. 7C), and transmits the data read from the cache 2 to the processor P1 via the CIM 1 (e.g., illustrated as 10R and 11R in FIG. 7C).

As discussed, the address request is also transmitted to the memory interface module 0 via (i) the CIM 0 and (ii) the global interface module 0 (illustrated as 7AR and 8AR in FIG. 7C). In response to the cache miss in the cache 0, the CIM 0 transmits a response to the memory interface module 0, indicating that the address request resulted in a cache miss (illustrated as 8Resp(miss) and 9 Resp(miss) in FIG. 7C). Also, in response to the cache hit in the cache 2, the CIM 2 transmits a response to the memory interface module 0, indicating that the address request resulted in a cache hit in the cache 2 (illustrated as 8Resp(hit) and 9 Resp(hit) in FIG. 7C). Based on receiving an indication that the address request resulted in a cache hit in the cache 2, the memory interface module 0 refrains from accessing the memory 0 to fetch data corresponding to the address request (or from transmitting data pre-fetched from the memory 0 to the requesting processor).

In an embodiment, when the address request is transmitted to the memory interface module 0 (e.g., by the CIM 0, indicated by 7AR and 8AR in FIG. 7C), the address request includes a number of responses that will follow the address request. For example, in FIG. 7C, based on the cache miss in caches 1 and 3 (i.e., caches associated with the local and home interface modules), there are two other caches (e.g., caches 0 and 2) that are to be checked. Thus, two responses indicating hit or miss (e.g., from the two caches 0 and 2) is to be received by the memory interface module 0, subsequent to receiving the address request. Thus, the address requested received by the memory interface module 0 indicate that two responses will follow the address request. Once the memory interface module 0 receives the address request, the memory interface module 0 waits to receive the two responses (e.g., and while waiting, in an embodiment, the memory interface module 0 can pre-fetch the requested data from the memory 0). If at least one of the two responses received by the memory interface module 0 indicates a hit,



the memory interface module 0 discards the address request. For example, in FIG. 7C, one of the responses (e.g., response from the CIM 2) is a hit—accordingly, the memory interface module 0 discards the address request. However, as discussed herein later with respect to FIG. 7D, if both the responses are miss, the memory interface module 0 access the memory 0 (e.g., if the memory interface module 0 has not already pre-fetched the requested data), and transmits the fetched data from the memory 0 to the requesting processor.

FIG. 7D illustrates another example read operation while a multi-core processing system (e.g., the system 100 of FIG. 1) operates in the dynamic mapped cache architecture mode. As discussed, in FIG. 7A, the address request resulted in a cache hit in the cache of the local interface module, while resulting in a cache miss in the home interface module. In FIG. 7B, the address request resulted in a cache miss in the cache of the local interface module, while resulting in a cache hit in the home interface module. In FIG. 7C, the address request resulted in a cache miss in the caches of both the local interface module and the home interface module, but resulted in a cache hit in another cache of the ring 0. In the example of FIG. 7D, the address request results in a cache miss in all the caches of local ring 0, as a result on which the data is read from the memory 0.

Similar to FIGS. 7A-7C, in the example of FIG. 7D, the processor P1 initiates an address request to, for example, read data of a specific memory address of the memory 0. Also, similar to FIGS. 7A-7C, in the example of FIG. 7D, the CIM 1 is the local interface module and the CIM 3 is the home interface module.

In FIG. 7D, initially, the processor P1 issues an address request (labeled as 0AR in FIG. 7D) to the corresponding CIM 1. Once the CIM 1 receives the address request, the CIM 1 determines whether the address request is a cache hit or a cache miss in the cache 1. In the example of FIG. 7D, the address request results in a cache miss in the cache 1 (e.g., illustrated as 1 cache miss in FIG. 7D). While the CIM 1 determines whether the address request is a cache hit or a cache miss in the cache 1, the CIM 1 also transmits the address request to the home interface module CIM 3 (e.g., illustrated as 1AR and 2AR in FIG. 7D). In the example of FIG. 7D, the address request also results in a cache miss in the cache 3 (e.g., illustrated as 3 cache hit in FIG. 7D). The CIM 3 transmits a response to the CIM 1 (e.g., illustrated as 4Resp and 5Resp in FIG. 7D), indicating that the address request resulted in a cache miss in the cache 3.

As the address request resulted in a cache miss in caches of both the local interface module and the home interface module, the CIM 1 transmits the address request to one or more other caches of the local ring 0 (e.g., to caches of all the interface modules of the local ring 0, except the local interface module and the home interface module). For example, subsequent to receiving the indication that the address request resulted in a cache miss in the cache 3, the CIM 1 transmits address requests to each of the CIM 0 and CIM 2 (e.g., illustrated as 6AR and 6AR in FIG. 7D), to check if the requested data is cached in one or both of the caches 0 and 2. In an embodiment, the CIM 1 transmits the address requests to each of the CIM 0 and CIM 2 at least in part simultaneously. The address request is also transmitted to the memory interface module 0 (e.g., illustrated as 7AR and 8AR in FIG. 7D). In the example of FIG. 7D, the address requests also results in a cache miss in both the caches 0 and 1 (e.g., illustrated as 7 cache miss in FIG. 7D).

As the address request results in a cache miss in all the caches of the local ring 0, the requested data is fetched from the memory 0. For example, while the CIM 0 checks for a

cache hit or a cache miss, the CIM 0 also transmits the address request to the memory interface module 0, e.g., to pre-fetch data, in case of a cache miss (e.g., illustrated as 7AR and 8AR in FIG. 7D). Subsequent to determining that the address request is a cache miss, the CIM 0 also transmits a response to the memory interface module 0, indicating that the address request is a cache miss in the cache 0 (e.g., illustrated as 8Resp(miss) and 9Resp(miss) in FIG. 7D). Similarly, the CIM 2 also transmits a response to the memory interface module 0, indicating that the address request is a cache miss in the cache 2 (also illustrated as 8Resp(miss) and 9Resp(miss) in FIG. 7D).

As previously discussed with respect to FIG. 7C, the address request received by the memory interface module 0 in FIG. 7D also indicates that two responses (e.g., from CIMs 0 and 2) will follow the address request. Once the memory interface module 0 receives the two cache miss indication (e.g., from the CIM 0 and the CIM 2), the memory interface module 0 fetches the requested data from the memory 0 (e.g., illustrated as 10RD and 11DATA in FIG. 7D). The memory interface module 0 then transmits the data fetched from the memory 0 to the processor P1, e.g., via the global interface module 0, the CIM 0 and the CIM 1 (e.g., illustrated as 12R, . . . , 15R in FIG. 7D).

Although FIGS. 7A-7D illustrate checking the caches of only the local ring 0 to determine if the address request is a cache hit or a cache miss, in an embodiment, caches of another local ring (e.g., a local ring 1 interconnected to the local ring 0 via a global ring) can also be checked, e.g., in case all the caches of the local ring 0 results in a cache miss. Thus, in such an embodiment, access to a cache in the local ring 1 is performed via the global ring. In an embodiment, a cache associated with a local interface module of the local ring 1 is checked first, prior to checking other caches of the local ring 1.

FIG. 7E is a flow diagram illustrating an example method 750 for a read operation while a multi-core processing system (e.g., the systems illustrated in FIGS. 7A-7D) operates in the dynamic mapped cache architecture mode.

At 754, ones of a plurality of processing cores (e.g., processors P0, . . . , P3 of FIGS. 7A-7D) communicates with a respective core interface module of a plurality of core interface modules (e.g., CIMs 0, . . . , 3), the plurality of core interface modules being configured as a first ring network, wherein ones of the plurality of core interface modules are coupled to a corresponding cache of a plurality of caches (e.g., caches 0, . . . , 3).

At 758, by a first core interface module (e.g., CIM 1 of FIG. 7D) of the plurality of core interface modules receives from a corresponding first processing core (e.g., processor P1) of the plurality of processing cores, a transaction request to read data.

At 762, the first core interface module checks to determine if the data to be read is cached in a first cache (e.g., cache 1) that is coupled to the first core interface module; and while checking if the data to be read is cached in the first cache, the first core interface module transmits the transaction request to a second core interface module (e.g., CIM 3 of FIG. 7D, which is the home interface module) to check if the data to be read is cached in a second cache (e.g., cache 3) that is coupled to the second core interface module.

At 766, it is determined that the data to be read is not cached in any of the first cache and the second cache (e.g., illustrated as 1 cache miss and 3 cache miss in FIG. 7D). Accordingly, the transaction request is transmitted to each of one or more other core interface modules (e.g., CIMs 0 and 2) of the first ring network to check if the data to be read is



cached in one or more other caches (e.g., caches **0** and **2**) respectively coupled to the one or more other core interface modules.

At **770**, it is determined that the data to be read is not cached in any of the one or more other caches e.g., illustrated as **7** cache miss in FIG. **7D**). Accordingly, the transaction request is transmitted to a memory interface module (e.g., memory interface module **0** of FIG. **7D**) to fetch the data from a memory (e.g., memory **0**) that is coupled to the memory interface module.

In an embodiment, the system operates in any one of the static mapped cache architecture mode or the dynamic mapped cache architecture mode. In an example, the static mapped cache architecture mode is relatively less complex to implement than implementing the dynamic mapped cache architecture mode. In an example, a penalty for a cache miss in the dynamic mapped cache architecture mode can be higher in terms of power consumption and latency than a miss penalty in the static mapped cache architecture mode. However, in an example, in view of the above discussed heuristic algorithm, the dynamic mapped cache architecture mode can provide relatively better latency and better bandwidth compared to the static mapped cache architecture mode. In an embodiment, whether the system **100** operates in the static mapped cache architecture mode or the dynamic mapped cache architecture mode is configurable. For example, a parameter of the system **100** is configured to selectively operate the system **100** in one of the static mapped cache architecture mode or the dynamic mapped cache architecture mode. In another example, whether the system **100** operates in the static mapped cache architecture mode or the dynamic mapped cache architecture mode is based on configuration or properties of various components of the system **100**. As an example, if the system **100** exhibits a relatively small memory foot print per processor (and thus, exhibit high hit ratio in the caches) and a relatively high affinity between memory and the processor, the system **100** operates in the dynamic mapped cache architecture mode. In another example, if the system **100** has a memory that is relatively largely shared between various processors, the system **100** operates in the dynamic mapped cache architecture mode.

#### Combining Memory Access Requests

FIG. **8** illustrates a system **800** for combining a plurality of memory access requests. The system **800** comprises a memory interface module **808** coupled to a local ring **804**. The memory interface module **808** is also coupled to a memory **812**. In an embodiment, the ring **804**, the memory interface module **808** and the memory **812** are similar to the corresponding components of the system **100** of FIG. **1** (or corresponding components of FIGS. **6A-6D** and **7A-7D**). For example, the ring **804**, the memory interface module **808** and/or the memory **812** are respectively similar to the ring **160a**, the memory interface module **126a**, and the memory **128a** of the system **100** of FIG. **1**. FIG. **8** illustrates only a part of the ring **804**, and various components coupled to the ring (e.g., as discussed with respect to FIG. **1**) are not illustrated in FIG. **8**. In an embodiment, the memory interface module **808** acts as a memory controller for the memory **812**, by controlling access to the memory **812**.

The memory interface module **808** receives a stream of memory requests. Some of these requests are memory access requests, e.g., to read data from various memory addresses of the memory **812**. For example, the memory interface module **808** receives a pre-fetch request **822** to pre-fetch

data from an address of the memory **812**. For example, the pre-fetch request **822** is issued by a processor, prior to the processor actually needing the data. For example, the processor issues the pre-fetch request **822**, speculating that the requested data may be needed some time soon. In an embodiment, the pre-fetch request **822** is a speculative read request, e.g., to read data from the memory **812** based on a speculation that the data might be needed in near future (for example, based on a processor processing a first data, the processor speculates that a second data may be needed in near future by the processor).

The memory interface module **808** also receives a read request **826** to fetch data from an address of the memory **812**. For example, the read request **826** is issued by a processor, when the processor wants to fetch data from the address of the memory **812**.

In an embodiment, the pre-fetch request **822** and the read request **826** can be received from a single component (e.g., a processor). In another embodiment, the pre-fetch request **822** and the read request **826** can be received from two different corresponding components (e.g., the pre-fetch request **822** is received from a first processor, and the read request **826** is received from a second processor).

FIG. **8** illustrates the memory interface module **808** receiving the pre-fetch request **822** over a first communication link (e.g., from a left side of the ring **804**) and receiving the read request **826** over a second communication link (e.g., from a right side of the ring **804**). However, in another embodiment and although not illustrated in FIG. **8**, the memory interface module **808** can receive the pre-fetch request **822** and the read request **826** over a same communication link (e.g., from a same side of the ring **804**).

In an embodiment, the memory interface module **808** receives the pre-fetch request **822** and the read request **826** simultaneously. Alternatively, in another embodiment, the memory interface module **808** receives the pre-fetch request **822** prior to receiving the read request **826** (e.g., the memory interface module **808** receives the read request **826** while the memory interface module **808** processes the pre-fetch request **822**, receives the read request **826** while the pre-fetch request **822** is queued in the memory interface module **808** for processing, or receives the read request **826** prior to fully executing the pre-fetch request **822** by the memory interface module **808**). Alternatively, in yet another embodiment, the memory interface module **808** receives the pre-fetch request **822** subsequent to receiving the read request **826** (e.g., the memory interface module **808** receives the pre-fetch request **822** while the memory interface module **808** processes the read request **826**, receives the pre-fetch request **822** while the read request **826** is queued in the memory interface module **808** for processing, or receives the pre-fetch request **822** prior to fully executing the read request **826** by the memory interface module **808**).

In an embodiment, each of the read request **826** and the pre-fetch request **822** are issued to read data from a same memory address of the memory **812**. As an example, each of the read request **826** and the pre-fetch request **822** aims to read data from a first memory address of the memory **812**.

In an embodiment, the memory interface module **808** comprises a request combination module **832** and a priority assignment module **838**. In an embodiment, the request combination module **832** determines that (i) both the read request **826** and the pre-fetch request **822** are currently pending in the memory interface module **808** for execution, and (ii) each of the read request **826** and the pre-fetch request **822** are issued to read data from a same memory address of the memory **812**. In an embodiment, based on



25

such determination, the request combination module **832** combines the read request **826** and the pre-fetch request **822**. For example, the request combination module **832** generates a combined request **840** to fetch data from the memory **812**, and reads data from the memory **812**. In an embodiment, once the requested data is read from the memory **812**, the memory interface module **808** transmits the data read from the memory **812** to the initiators of the read request **826** and the pre-fetch request **822**, thereby completing the processing of the read request **826** and the pre-fetch request **822**. In an embodiment, the combined request **840** comprises the read request **826**, and fetching of data in response to the pre-fetch request **822** is not executed. In an embodiment, the combined request **840** comprises a request to fetch data from the memory **812**.

Thus, if the read request **826** and the pre-fetch request **822** were to be executed separately (that is, if the read request **826** and the pre-fetch request **822** were not combined by the request combination module **832**), the memory interface module **808** would have needed to access the memory **812** twice, to read the same data twice from the same memory address of the memory **812** (in other words once for processing the read request **826**, and once for processing the pre-fetch request **822**). However, by combining the read request **826** and the pre-fetch request **822**, the memory interface module **808** needs to access the memory **812** only once while processing the read request **826** and the pre-fetch request **822**.

In an embodiment, a request to access the memory **812** has a corresponding associated priority (for example, a pre-defined priority based on a type of the request). For example, a read request (e.g., the read request **826**) received by the memory interface module **808** has a first priority, and a pre-fetch request (e.g., the pre-fetch request **822**) received by the memory interface module **808** has a second priority. In an embodiment, the first priority is higher than the second priority. That is, if a read request having the first priority is residing in the memory interface module **808** for processing along with a pre-fetch request, the read request is to be executed prior to an execution of the pre-fetch request (e.g., due to the first priority being higher than the second priority). Thus, the first priority being higher than second priority implies that the read request has a higher execution priority compared to the pre-fetch request.

As discussed, in an example, the read request **826** received by the memory interface module **808** has the first priority, and the pre-fetch request **822** received by the memory interface module **808** has the second priority. In an embodiment, the priority assignment module **838** assigns a third priority to the combined request **840**. In an embodiment, the third priority is a higher of the first priority and the second priority. In an example, the first priority is higher than the second priority, and hence, the third priority is equal to the first priority.

In an embodiment, as a higher priority (e.g., the first priority) is assigned to the combined request **840**, the combined request **840** is executed by the memory interface module **808** prior to execution of, for example, various other pre-fetch requests residing in the memory interface module **808**.

FIG. **9** is a flow diagram illustrating an example method **900** for operating the system **800** of FIG. **8**. At **904**, a memory interface module (e.g., memory interface module **808**), which is coupled to a memory (e.g., memory **812**), receives a first memory access request (e.g., the pre-fetch request **822**) to access data stored in the memory, the memory interface module configured to control access to the

26

memory; and the memory interface module receives a second memory access request (e.g., read request **826**) to access data stored in the memory.

At **908**, based on the first and second memory access requests, the memory interface module (e.g., the request combination module **832**) generates a third memory access request (e.g. the combined request **840**), by, for example, combining the first and second memory access requests. At **912**, based on the third memory access request, the memory interface module accesses the memory to read data from the memory.

The description incorporates use of the phrases “in an embodiment,” or “in various embodiments,” which may each refer to one or more of the same or different embodiments. Furthermore, the terms “comprising,” “including,” “having,” and the like, as used with respect to embodiments of the present disclosure, are synonymous.

Various operations may have been described as multiple discrete actions or operations in turn, in a manner that is most helpful in understanding the claimed subject matter. However, the order of description should not be construed as to imply that these operations are necessarily order dependent. In actuality, these operations may not be performed in the order of presentation. Operations described may be performed in a different order than the described embodiment. Various additional operations may be performed and/or described operations may be omitted in additional embodiments.

Although specific embodiments have been illustrated and described herein, it is noted that a wide variety of alternative and/or equivalent implementations may be substituted for the specific embodiment shown and described without departing from the scope of the present disclosure. The present disclosure covers all methods, apparatus, and articles of manufacture fairly falling within the scope of the appended claims either literally or under the doctrine of equivalents. This application is intended to cover any adaptations or variations of the embodiment disclosed herein. Therefore, it is manifested and intended that the present disclosure be limited only by the claims and the equivalents thereof.

What claimed is:

1. A method comprising:

communicating by ones of a plurality of processing cores with a respective core interface module of a plurality of core interface modules, the plurality of core interface modules being configured as a ring network, wherein ones of the plurality of core interface modules are coupled to a corresponding cache of a plurality of caches, and wherein the plurality of core interface modules comprises (i) a first core interface module, (ii) a second core interface module, (iii) a third core interface module, and (iv) a fourth core interface module;

receiving, by the first core interface module from a first processing core of a plurality of processing cores, a transaction request to read data, wherein the data to be read is associated with a first memory address of a memory, and wherein the second core interface module is a home interface module for the first memory address of the memory;

in response to the data not being cached in either a first cache or a second cache, receiving, by a memory interface coupled to the memory, a memory read request, wherein the memory read request comprises (i) a request to read the data from the memory and (ii) a first number;



27

subsequent to receiving the memory read request, receiving, by the memory interface, a first number of cache miss indications from the third core interface module; and

in response to receiving the first number of cache miss indications, executing, by the memory interface, the memory read request.

2. The method of claim 1, further comprising: refraining, by the memory interface, from executing the memory read request prior to receiving the first number of cache miss indications.

3. The method of claim 1, further comprising: in response to the data being cached in either the first cache or the second cache, discarding, by the memory interface, the memory read request.

4. The method of claim 1, further comprising: based upon executing the memory read request, forwarding, by the memory interface, the data to the first processing core.

5. A system comprising:

- a plurality of processing cores;
- a plurality of core interface modules, wherein ones of the plurality of processing cores communicate with a respective core interface module of the plurality of core interface modules, and wherein the plurality of core interface modules are configured as a ring network;
- a plurality of caches, wherein ones of the plurality of core interface modules are coupled to a corresponding cache of the plurality of caches;
- a memory; and
- a memory interface;

wherein the core interface modules are configured to receive transaction requests to read data from the memory, wherein the transaction requests are received from processing cores of the plurality of processing cores, and wherein data to be read is associated with a memory address of the memory,

wherein in response to the data not being cached in either a first cache or a second cache of the plurality of caches, the core interface modules are configured to send cache miss indications to the memory interface,

wherein the memory interface is configured for receiving a memory read request, wherein the memory read request comprises (i) a request to read the data from the memory and (ii) a first number, and

wherein in response to receiving, by the memory interface, the first number of cache miss indications from one of the core interface modules, the memory interface is configured to execute the memory read request to read the data from the memory.

6. The system of claim 5, wherein the memory interface is further configured to refrain from executing the memory read request prior to receiving the first number of cache miss indications.

7. The system of claim 5, wherein the memory interface is further configured to, in response to the data being cached in either the first cache or the second cache, discard the memory read request.

8. The system of claim 5, wherein the memory interface is further configured to, based upon executing the memory read request, forward the data to a requesting processing core.

28

9. The system of claim 5, wherein ones of the plurality of caches are included in a corresponding one of the plurality of core interface modules.

10. A method comprising:

communicating by ones of a plurality of processing cores with a respective core interface module of a plurality of core interface modules, the plurality of core interface modules being configured as a ring network, wherein ones of the plurality of core interface modules are coupled to a corresponding cache of a plurality of caches;

receiving, by a first core interface module of the plurality of core interface modules from a first processing core of the plurality of processing cores, a transaction request to read data, wherein the data to be read is associated with a memory address of a memory, and wherein a second core interface module is a home interface module for the memory address of the memory;

checking, by the first core interface module, if the data to be read is cached in a first cache that is coupled to the first core interface module or a second cache that is coupled to the second core interface module; and

in response to the data not being cached in either the first cache or the second cache, transmitting a memory read request to a memory interface coupled to the memory, wherein the memory read request comprises (i) a request to read the data from the memory and (ii) a first number, wherein the memory interface is configured to read the data from the memory if the memory interface receives the first number of cache miss indications subsequent to receiving the memory read request.

11. The method of claim 10, wherein the plurality of core interface modules comprises (i) the first core interface module, (ii) the second core interface module, and (iii) the first number of other core interface modules, and wherein the method further comprises:

receiving, by the memory interface, the number of cache miss indications respectively from the first number of other core interface modules; and

in response to receiving the first number of cache miss indications, executing the memory read request and reading the data from the memory.

12. The method of claim 11, wherein the first number is in a range of two to four.

13. The method of claim 11, further comprising:

refraining, by the memory interface, from executing the memory read request prior to receiving the first number of cache miss indications.

14. The method of claim 11, further comprising:

in response to the data being cached in either the first cache or the second cache, discarding, by the memory interface, the memory read request.

15. The method of claim 11, further comprising:

based upon executing the memory read request, forwarding, by the memory interface, the data to the first processing core.

\* \* \* \* \*